



FCC Test Report

Report No: FCS202607152W01

Issued for

Applicant:	Shenzhen ZhiHuiJu Technology Co., Ltd.
Address:	Room A315, Block A, Huafeng International Robot Industrial Park, Gushu Xixiang, Baoan District, Shenzhen, China
Product Name:	Smart watch
Brand Name:	N/A
Model Name:	Dora T
Series Model:	N/A
FCC ID:	2BXIH-DORAT
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 0769-27280901 Fax:0769-27280901 http://www.FCS-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name.....: Shenzhen ZhiHuiJu Technology Co., Ltd.

Address.....: Room A315, Block A, Huafeng International Robot Industrial Park,
Gushu Xixiang, Baoan District, Shenzhen, China

Manufacture's Name.....: Shenzhen ZhiHuiJu Technology Co., Ltd.

Address.....: Room A315, Block A, Huafeng International Robot Industrial Park,
Gushu Xixiang, Baoan District, Shenzhen, China

Product Description

Product Name.....: Smart watch

Brand Name.....: N/A

Model Name.....: Dora T

Series Model.....: See the first page of the report

Test Standards.....: FCC Rules and Regulations Part 15 Subpart C, Section 247

Test Procedure.....: ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to
C63.10a-2024

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document..

Date of Test.....:


Date (s) of performance of tests.: July 13, 2026~July 26, 2026

Date of Issue.....: July 26, 2026

Test Result.....: Pass

Tested by

:



(orange OuYang)

Reviewed by

:



(jayden)

Approved by

:



(Jack Wang)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.4 EQUIPMENTS LIST	12
3. 6DB BANDWIDTH	13
3.1 Limit	13
3.2 Test Procedure	13
3.3 Test setup	13
3.4 Test results	14
3.5 Original Test Data	14
4. CONDUCTED OUTPUT POWER	16
4.1 LIMIT	16
4.2 TEST PROCEDURE	16
4.3 TEST SETUP	16
4.4 TEST RESULTS	17
5. BAND EDGE AND SPURIOUS(CONDUCTED)	17
5.1 LIMIT	17
5.2 TEST PROCEDURE	17
5.3 TEST SETUP	18
5.4 TEST RESULTS	18
5.5 Original test data	19
6. POWER SPECTRAL DENSITY	23
6.1 LIMIT	23
6.2 TEST PROCEDURE	23
6.3 TEST SETUP	23
6.4 TEST RESULTS	23
6.5 original test data	24
7. RADIATED EMISSION MEASUREMENT	26

Table of Contents	Page
7.1 RADIATED EMISSION LIMITS	26
7.2 TEST PROCEDURE	27
7.3 TESTSETUP	28
7.4 TEST RESULTS	29
RADIATED EMISSION (30MHZ-1000MHZ)	30
RADIATED EMISSION ABOVE 1GHZ	32
7.5 RADIATED BAND EDGE DATA	35
8 CONDUCTED EMISSION MEASUREMENT	36
8.1 LIMIT	36
8.2 TEST PROCEDURE	36
8.3 TEST SETUP	37
8.4 TEST RESULTS	38
9.DUTY CYCLE	40
9.1 TEST REQUIREMENT	40
9.2 TEST PROCEDURE	40
9.3 TEST SETUP	40
9.4 TEST RESULTS	40
10. ANTENNA REQUIREMENT	42
10.1 STANDARD REQUIREMENT	42
10.2 RESULT	42

Revision History

Rev.	Issue Date	Effect Page	Contents
00	July 26, 2026	N/A	N/A

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209,15.247(d), 15.205	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.247(a)(2)	6dB Bandwidth 99% Bandwidth	PASS	--
15.247(d), 15.209, 15.205	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-0769-27280901
Fax:	+86-0769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number: 5545.01 ISED Number: 25801 CAB ID : CN0097	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	± 0.71 dB
2	Unwanted Emissions, conducted	± 2.988 dB
3	Conducted Emission (9KHz-150KHz)	± 4.13 dB
4	All emissions radiated (9KHz -30MHz)	± 3.1 dB
5	Conducted Emission (150KHz-30MHz)	± 4.74 dB
6	All emissions,radiated(<1G) 30MHz-1000MHz	± 5.2 dB
7	All emissions,radiated 1GHz -18GHz	± 4.66 dB
8	All emissions,radiated 18GHz -40GHz	± 4.31 dB
9	Occupied bandwidth	± 0.3 dB
10	Power Spectral Density	± 0.48 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart watch	
Trade Name	N/A	
Model Name	Dora T	
Series Model	See the first page of the report	
Model Difference	PCB board, structure and internal of these model(s) are the same, only differing in Model name and color. So no additional models were tested	
Product Description	Operation Frequency:	2402-2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	LE
	Number Of Channel:	40 CH
	Antenna Gain (dBi)	0.08
	Transmitter rate:	1Mbps
Channel List	Please refer to the Note 2.	
Power Supply	Input:100-230V Output:DC 5V	
Battery	DC 3.85V,120mAh	
Hardware version number	V1.0	
Software version number	V1.0	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Channel List

Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)	Channel	Freq.(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	Copper wire monopole antenna	N/A	0.08	Antenna

2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test

Mode 1:



Mode 2:



Test software: RFTTest_0901_boxed

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

No.	Test model descrtion
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK

Note:

1. All the test modes can be supply by AC, only the result of the worst case recorded in the report. GFSK mode is worst mode.
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The test voltage was tuned from 85% to 115% of the Nominal rate supply votage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A
1	adapter	NexTech Solutions	N/A	N/A	N/A
2	Cable	PrimeConnect Systems	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1	N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2025.08.25	2026.08.24
Signal Analyzer	R&S	FSV40-N	FCS-E012	2025.08.25	2026.08.24
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2025.08.25	2026.08.24
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2025.08.25	2026.08.24
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2025.08.25	2026.08.24
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2025.08.25	2026.08.24
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2025.08.25	2026.08.24
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2025.08.25	2026.08.24
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E005	2025.08.25	2026.08.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2025.08.25	2026.08.24
LISN	R&S	ENV216	FCS-E007	2025.08.25	2026.08.24
LISN	ETS	3810/2NM	FCS-E009	2025.08.25	2026.08.24
Temperature & Humidity	HTC-1	victor	FCS-E008	2025.08.25	2026.08.24

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
Spectrum Analyzer	Keysight	N9020A	FCS-E015	2025.08.25	2026.08.24
Spectrum Analyzer	Agilent	E4447A	MY50180039	2025.08.25	2026.08.24
Spectrum Analyzer	R&S	FSV-40	101499	2025.08.25	2026.08.24
Power meter	Agilent	UX2021XA	FCS-E021	2025.08.25	2026.08.24
Cable	Woke	RWP50-402-SM SM-1M	FCS-E025	2025.08.25	2026.08.24

3. 6DB BANDWIDTH

3.1 Limit

FCC Part 15.247, Subpart C RSS-Gen Clause 6.7				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5	PASS
RSS-Gen Clause 6.7	99% Bandwidth	For reporting purposes only.	2400-2483.5	PASS

3.2 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows

RBW: 100 kHz (6dB Bandwidth) / 30 kHz (99%Bandwidth)

VBW: 300 kHz (6dB Bandwidth) / 100 kHz (99%Bandwidth)

Detector Mode: Peak

Sweep time: auto

Trace mode Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

3.3 Test setup




3.4 Test results


TestMode	Channel (MHz)	6dB Bandwidth(MHz)	Limit [MHz]	Verdict
Lowest	2402MHz	0.678	0.5	Pass
Middle	2440MHz	0.684	0.5	Pass
Highest	2480MHz	0.682	0.5	Pass

3.5 Original Test Data


6BW,1M_PHY,Lowest



6BW,1M_PHY,Middle



6BW,1M_PHY,Highest



4. CONDUCTED OUTPUT POWER

4.1 LIMIT

FCC Part 15 Subpart C			
Section	Test Item	Limit	Frequency Range
15.247(b)(3)	Peak output power	Power <1W(30dBm)	2400-2483.5

4.2 TEST PROCEDURE

- (1) The EUT was directly connected to the power meter and antenna output port as show in The block diagram above.
- (2) The EUT was set to continuously transmitting in the max power during the test.

4.3 TEST SETUP



4.4 TEST RESULTS

TestMode	Channel (MHz)	Result (dBm)	Limit (dBm)	Verdict
Lowest	2402MHz	2.21	30	Pass
Middle	2440MHz	2.71	30	Pass
Highest	2480MHz	2.41	30	Pass

5. BAND EDGE AND SPURIOUS(CONDUCTED)

5.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

5.3 TEST SETUP




5.4 TEST RESULTS


Eut set mode	CH or Frequency	Result
GFSK	CH0	Pass
	CH19	Pass
	CH39	Pass

5.5 Original test data


CH0 2402MHz



CH19 2440MHz




CH39 2480MHz




Spurious emissions


2402



2440



2480



6. POWER SPECTRAL DENSITY

6.1 LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP




6.4 TEST RESULTS


TestMode	Channel (MHz)	Result (dBm/3KHz)	Limit (dBm/3KHz)	Verdict
GFSK	2402MHz	-7.65	8	Pass
GFSK	2440MHz	-6.07	8	Pass
GFSK	2480MHz	-7.82	8	Pass

6.5 original test data


GFSK-2402MHz



GFSK-2440MHz



GFSK-2480MHz



7. RADIATED EMISSION MEASUREMENT

7.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 below has to be followed LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

7.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

7.3 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.4 TEST RESULTS

(9KHz-30MHz)

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	DC 3.85V from battery	Test Mode:	GFSK

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

RADIATED EMISSION (30MHZ-1000MHZ)

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	DC 3.85V from battery	Phase:	Horizontal
Test Mode:	Middle CH (GFSK)		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.7455	24.74	-12.30	12.44	40.00	-27.56	QP
2	61.3463	25.39	-13.35	12.04	40.00	-27.96	QP
3	118.1862	25.01	-13.88	11.13	43.50	-32.37	QP
4	269.4284	25.80	-12.56	13.24	46.00	-32.76	QP
5	478.8456	26.10	-7.24	18.86	46.00	-27.14	QP
6	942.1305	26.19	0.30	26.49	46.00	-19.51	QP

Note: 1. Margin = Result (Result =Reading + Factor)-Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 500 kHz, Sweep time: auto.

Temperature:	26°C	Relative Humidity:	54%
Test Voltage:	DC 3.85V from battery	Phase:	Vertical
Test Mode:	Middle CH (GFSK)		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.7486	26.16	-12.30	13.86	40.00	-26.14	QP
2	60.9176	26.12	-13.33	12.79	40.00	-27.21	QP
3	119.8556	26.06	-13.70	12.36	43.50	-31.14	QP
4	269.4284	25.71	-12.56	13.15	46.00	-32.85	QP
5	510.0436	26.18	-6.76	19.42	46.00	-26.58	QP
6	958.7943	26.76	0.41	27.17	46.00	-18.83	QP

Note: 1. Margin = Result (Result = Reading + Factor) – Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 500 kHz, Sweep time: auto.

RADIATED EMISSION ABOVE 1GHZ

Temperature:	26 °C	Relative Humidity:	54%
Test Mode:	Low CH (GFSK)	Test Voltage:	DC 3.85V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	51.36	32.01	5.775	43.81	45.33	74	-28.67	Vertical
7206	48.45	35.19	6.425	42.55	47.51	74	-26.49	Vertical
9608	46.17	37.32	7.274	41.74	49.02	74	-24.98	Vertical
12010	*					74		Vertical
14412	*					74		Vertical
4804	46.63	32.01	5.775	43.81	40.60	74	-33.40	Horizontal
7206	45.92	35.19	6.425	42.55	44.98	74	-29.02	Horizontal
9608	45.61	37.32	7.274	41.74	48.46	74	-25.54	Horizontal
12010	*					74		Horizontal
14412	*					74		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss- Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. "**", means this data is the too weak instrument of signal is unable to test.
- 4.For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit

Temperature:	26 °C	Relative Humidity:	54%
Test Mode:	Middle CH (GFSK)	Test Voltage:	DC 3.85V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4882	53.72	32.16	5.823	43.69	48.01	74	-25.99	Vertical
7323	49.73	35.38	6.489	42.42	49.18	74	-24.82	Vertical
9764	47.64	37.40	7.350	41.64	50.75	74	-23.25	Vertical
12205	*					74		Vertical
14646	*					74		Vertical
4882	49.74	32.16	5.823	43.69	44.03	74	-29.97	Horizontal
7323	50.62	35.38	6.489	42.42	50.07	74	-23.93	Horizontal
9764	49.84	37.40	7.350	41.64	52.95	74	-21.05	Horizontal
12205	*					74		Horizontal
14646	*					74		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. "*", means this data is too weak instrument of signal is unable to test.
4. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit

Temperature:	26 °C	Relative Humidity:	54%
Test Mode:	High CH (GFSK)	Test Voltage:	DC 3.85V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960	54.79	32.74	5.874	43.56	49.84	74	-24.16	Vertical
7440	47.73	35.86	6.556	42.27	47.87	74	-26.13	Vertical
9920	46.52	37.46	7.430	41.55	49.86	74	-24.14	Vertical
12400	*					74		Vertical
14880	*					74		Vertical
4960	50.84	32.74	5.874	43.56	45.89	74	-28.11	Horizontal
7440	51.26	35.86	6.556	42.27	51.40	74	-22.60	Horizontal
9920	46.53	37.46	7.430	41.55	49.87	74	-24.13	Horizontal
12400	*					74		Horizontal
14880	*					74		Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- "*", means this data is too weak, instrument of signal is unable to test.
- For emissions above 1GHz, if peak level complies with average limit, then the average level is deemed to comply with average limit

7.5 RADIATED BAND EDGE DATA

Low CH (GFSK)

Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	58.59	27.62	3.70	47.84	42.07	74	-31.93	Horizontal
2390	57.47	27.14	3.79	47.72	40.68	74	-33.32	Horizontal
2400	59.18	27.10	3.80	47.70	42.38	74	-31.62	Horizontal
2310	57.25	27.62	3.70	47.84	40.73	74	-33.27	Vertical
2390	57.64	27.14	3.79	47.72	40.85	74	-33.15	Vertical
2400	58.57	27.10	3.80	47.70	41.77	74	-32.23	Vertical

High CH(GFSK)

Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	57.68	27.60	3.89	47.57	41.60	74	-32.40	Horizontal
2500	59.35	27.70	3.91	47.55	43.41	74	-30.59	Horizontal
2483.5	59.57	27.60	3.89	47.57	43.49	74	-30.51	Vertical
2500	58.52	27.70	3.91	47.55	42.58	74	-31.42	Vertical

Remark.

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
2. The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
3. All restriction band have been tested, and only the worst case is shown in report
4. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit

8 CONDUCTED EMISSION MEASUREMENT

8.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


8.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

8.3 TEST SETUP




Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


8.4 TEST RESULTS

Temperature:	23℃	Relative Humidity:	56%
Phase:	L	Test Mode:	GFSK
Test Voltage:	AC 230V		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1635	20.52	9.96	30.48	65.28	-34.80	QP
2	0.1635	7.19	9.96	17.15	55.28	-38.13	AVG
3	0.6000	25.48	9.90	35.38	56.00	-20.62	QP
4	0.6000	15.48	9.90	25.38	46.00	-20.62	AVG
5	1.2614	19.05	10.00	29.05	56.00	-26.95	QP
6	1.2614	5.72	10.00	15.72	46.00	-30.28	AVG
7	2.5665	15.84	10.05	25.89	56.00	-30.11	QP
8	2.5665	4.41	10.05	14.46	46.00	-31.54	AVG
9	5.5140	13.58	10.09	23.67	60.00	-36.33	QP
10	5.5140	3.02	10.09	13.11	50.00	-36.89	AVG
11	22.0785	15.90	10.28	26.18	60.00	-33.82	QP
12	22.0785	4.99	10.28	15.27	50.00	-34.73	AVG

Temperature:	23°C	Relative Humidity:	56%
Phase:	N	Test Mode:	GFSK
Test Voltage:	AC 230V		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.2850	20.50	9.85	30.35	60.67	-30.32	QP
2	0.2850	6.39	9.85	16.24	50.67	-34.43	AVG
3	0.6134	29.65	9.93	39.58	56.00	-16.42	QP
4	0.6134	15.96	9.93	25.89	46.00	-20.11	AVG
5	1.0004	24.27	9.96	34.23	56.00	-21.77	QP
6	1.0004	10.42	9.96	20.38	46.00	-25.62	AVG
7	1.7924	21.78	10.03	31.81	56.00	-24.19	QP
8	1.7924	7.22	10.03	17.25	46.00	-28.75	AVG
9	5.5005	17.81	10.03	27.84	60.00	-32.16	QP
10	5.5005	3.19	10.03	13.22	50.00	-36.78	AVG
11	13.5960	15.67	10.19	25.86	60.00	-34.14	QP
12	13.5960	2.38	10.19	12.57	50.00	-37.43	AVG

9.DUTY CYCLE

9.1 TEST REQUIREMENT


47 CFR Part 15C 15.247 and KDB 558074 D01 v05r02

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

9.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.


9.3 TEST SETUP




9.4 TEST RESULTS


Frequency(MHz)	On time(ms)	Period(ms)	Duty Cycle(%)
2402	100	100	100
2440	100	100	100
2480	100	100	100

Duty Cycle NVNT 2402MHz



Duty Cycle NVNT 2440MHz





10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2 RESULT

The antennas used for this product are Copper wire monopole antenna and no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 0.08dBi.

*****END OF THE REPORT*****