

# Appendix IV MPE

FCC ID: 2BXJ7-VG51105

## Prediction of MPE at a given distance

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

KDB Test Methodology: KDB 447498 D01 v06.

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure         |                               |                               |                                     |                          |
| 0.3-3.0                                                 | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30                                                  | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300                                                  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                               |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                           |                               |                               | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3-1.34                                                | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30                                                 | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                               |                               |                               | f/1500                              | 30                       |
| 1,500-100,000                                           |                               |                               | 1.0                                 | 30                       |

### 2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

### 3. Result

| Mode  | Frequency (MHz) | Prediction distance (cm) | RF output power(Max) (dBm) | Tune-up power (Max) |        | MPE (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | SAR Test Exclusion |
|-------|-----------------|--------------------------|----------------------------|---------------------|--------|---------------------------|-----------------------------|--------------------|
|       |                 |                          |                            | dBm                 | mW     |                           |                             |                    |
| BT LE | 2402-2480       | 20                       | -0.84                      | 0                   | 1.0000 | 0.0003                    | 1.0000                      | Yes                |

BT:

Internal antenna, Maximum Gain is 1.05dBi.

#### Then SAR evaluation is not required.

§ 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.

For purposes of this section, the definitions in § 1.1307(b)(2) of this chapter shall apply. A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons.