

TEST REPORT

Report No.: BCTC2608630719-1E

Applicant: HONGKONG BAOKANGDA LIMITED

Product Name: Headphones


Test Model: T2

Tested Date: 2026-08-04 to 2026-08-19

Issued Date: 2026-08-19



Shenzhen BCTC Technology Co., Ltd.



FCC ID: 2BXJW-T2

Product Name: Headphones

Trademark: JoySpark

Model/Type Reference: T2

Prepared For: HONGKONG BAKANGDA LIMITED

Address: ROOM140, 1/F TUSPARK, 118 WAI YIP ST, KWUN TONG, HONGKONG

Manufacturer: HONGKONG BAKANGDA LIMITED

Address: ROOM140, 1/F TUSPARK, 118 WAI YIP ST, KWUN TONG, HONGKONG

Prepared By: Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China

Sample Received Date: 2026-08-04

Sample Tested Date: 2026-08-04 to 2026-08-19


Report No.: BCTC2608630719-1E

Test Standards: FCC 47 CFR Part 15 Subpart C (clause 15.247)
ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

Test Results: PASS

Remark: This is Bluetooth Classic radio test report.

Prepared by :



Louis Zeng

Reviewer by :



Mike Zheng

Approved by:




Sewen Guo

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Technology Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Content

Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information and Test Setup	8
4.1 Product Information	8
4.2 Test Setup Configuration	9
4.3 Support Equipment	9
4.4 Channel List	10
4.5 Test Mode	10
4.6 Table Of Parameters Of Text Software Setting	11
5. Test Facility And Test Instrument Used	12
5.1 Test Facility	12
5.2 Test Instrument Used	12
6. Conducted Emissions	14
6.1 Block Diagram Of Test Setup	14
6.2 Limit	14
6.3 Test procedure	14
6.4 EUT operating Conditions	14
6.5 Test Result	15
7. Radiated emissions	17
7.1 Block Diagram Of Test Setup	17
7.2 Limit	18
7.3 Test procedure	19
7.4 EUT operating Conditions	20
7.5 Test Result	21
8. Radiated Band Emission Measurement and Restricted Bands of Operation	27
8.1 Block Diagram Of Test Setup	27
8.2 Limit	27
8.3 Test procedure	28
8.4 EUT operating Conditions	28
8.5 Test Result	29
9. Spurious RF Conducted Emissions	30
9.1 Block Diagram Of Test Setup	30
9.2 Limit	30
9.3 Test procedure	30
9.4 Test Result	31
10. 20 dB Bandwidth	52
10.1 Block Diagram Of Test Setup	52
10.2 Limit	52
10.3 Test procedure	52
10.4 Test Result	53
11. Maximum Peak Output Power	59
11.1 Block Diagram Of Test Setup	59
11.2 Limit	59
11.3 Test procedure	59

11.4	Test Result.....	59
12.	Hopping Channel Separation	65
12.1	Block Diagram Of Test Setup.....	65
12.2	Limit	65
12.3	Test procedure	65
12.4	Test Result.....	65
13.	Number of Hopping Frequency	71
13.1	Block Diagram Of Test Setup.....	71
13.2	Limit	71
13.3	Test procedure	71
13.4	Test Result.....	71
14.	Dwell Time.....	74
14.1	Block Diagram Of Test Setup.....	74
14.2	Limit	74
14.3	Test procedure	74
14.4	Test Result.....	74
15.	Antenna Requirement	85
15.1	Limit	85
15.2	Test Result.....	85
16.	EUT Test Setup Photographs.....	86



1. Version

Report No.	Issue Date	Description	Approved
BCTC2608630719-1E	2026-08-19	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted emission AC power port	§15.207	PASS*
2	Conducted peak output power for FHSS	§15.247(b)(1)	PASS*
3	20dB Occupied bandwidth	§15.247(a)(1)	PASS*
4	Number of hopping frequencies	§15.247(a)(1)(iii)	PASS*
5	Dwell Time	§15.247(a)(1)(iii)	PASS*
6	Spurious RF conducted emissions	§15.247(d)	PASS*
7	Band edge	§15.247(d)	PASS*
8	Spurious radiated emissions for transmitter	§15.247(d) & §15.209 & §15.205	PASS*
9	Antenna Requirement	15.203	PASS

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

Note 3: "*" indicates that the test results are determined base on FCC 47 CFR Part 15 Subpart C (clause 15.247). And the test results are took into account measurement uncertainty (see section 3 for measurement uncertainty information)

BCTC CO., LTD

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2:2011/AMD2:2018. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=5.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=5.0dB
5	Conducted Emission(150kHz-30MHz)	U=3.0dB
6	Power Spectral Density	U=3.46dB
7	Peak Power	U=0.31dB
8	Occupied Bandwidth/Frequency Range	U=3.46%
9	Conducted output power uncertainty	U=0.55dB
10	Frequency Error	U= 53.50 Hz
11	Frequency Drift	U=0.64 KHz
12	Temperature	U= 0.59 °C
13	Humidity	U= 5.3 %

4. Product Information and Test Setup


4.1 Product Information

Model/Type reference:	T2(Test color is blue)
Note:	Except for the difference in color, circuit and RF module is the same.
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	Bluetooth: 2402-2480MHz
Type of Modulation:	GFSK modulation for BR(1Mbps) $\pi/4$ -DQPSK modulation for EDR(2Mbps) 8DPSK modulation for BT EDR (3Mbps)
Number Of Channel	79 channels
Antenna installation:	PCB antenna
Antenna Gain:	1.68dBi
	Remark: ☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. The laboratory assumes no responsibility for its authenticity. ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information. The laboratory assumes no responsibility for its authenticity.
Ratings:	DC 5V from adapter or DC 3.7V from battery


4.2 Test Setup Configuration

See test photographs attached in eut test setup photographs for the actual connections between product and support equipment.

Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Headphones	JoySpark	T2	N/A	EUT
E-2	Adapter	N/A	N/A	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	N/A	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	79	/

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Mode	Test mode	Low channel	Middle channel	High channel
1	Transmitting(GFSK)	2402MHz	2441MHz	2480MHz
2	Transmitting($\pi/4$ DQPSK)	2402MHz	2441MHz	2480MHz
3	Transmitting(8DPSK)	2402MHz	2441MHz	2480MHz
4	Transmitting (Conducted emission & Radiated emission)			

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) Fully-charged battery is used during the test

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

RF Function	Mode Or Modulation type	Power Class	Software For Testing
BT	GFSK	4	FCC_assist 1.0.1.1
	$\pi/4$ -DQPSK	4	
	8DPSK	4	

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China.

The site and apparatus are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-1:2019 other equivalent standards.

FCC Test Firm Registration Number: 754702

ANAB certificate registration number is: CN3479

5.2 Test Instrument Used

Conducted emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESCI	101421	2025.08.30	2026.08.29
AMN	SCHWHRZBECK	NSLK8128	05152	2026.01.22	2027.01.21
AMN	SCHWHRZBECK	NSLK8127	8127739	2025.09.16	2026.09.15
Pulse Limiter	SCHWHRZBECK	VTSD 9561-F-N	00547	2025.08.30	2026.08.29
Temperature & Humidity	Wetest	HTC-1	/	2025.09.01	2026.08.31
Software	EZ-EMC	Ver.EMC-CON 3A1	/	/	/


Radiated disturbance 2#					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Shielded room	ChengYu	9*6*6	/	2023.09.25	2026.09.24
Loop Antenna	Schwarzbeck	FMZB1519B	00014	2026.01.05	2027.01.04
Broadband antenna	SCHWHRZBECK	VULB9168	01620	2025.08.29	2026.08.28
Horn antenna(1 GHz -18GHz)	SCHWARZBECK	BBHA 9120 D	2792	2025.08.29	2026.08.28
Horn antenna (18 GHz -40GHz)	SCHWARZBECK	BBHA9170	00822	2025.12.29	2026.12.28
Receiver	R&S	ESR	1316	2025.08.30	2026.08.29
Spectrum Analyzer	R&S	FSV40	101328	2026.01.22	2027.01.21
Amplifier	SCHWHRZBECK	BBV9744	568	2025.08.30	2026.08.29

Amplifier	EMC INSTRUMENTS CORPORATION	EMC0518A45SE E	EMT-SZ2 233	2025.08.30	2026.08.29
Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	2026.05.09	2027.05.08
RF cable 3# (9kHz-6GHz)	Yunyi	10M	/	2025.08.30	2026.08.29
RF cable 9# (9kHz-1GHz)	Yunyi	2M	/	2025.10.28	2026.10.27
RF cable 5# (1GHz-18GHz)	SKET	9M	18038626	2025.08.30	2026.08.29
RF cable 6# (1GHz-18GHz)	SKET	5M	#10	2025.09.05	2026.09.04
RF cable 10# (18GHz-40GHz)	/	2M	2M	2026.05.09	2027.05.08
RF cable 11# (18GHz-40GHz)	/	2.5M	2.5M	2026.05.09	2027.05.08
Temperature & Humidity	Wetest	HTC-1	/	2025.09.05	2026.09.04
Software	EZ-EMC	Ver.FA-03A2	/	/	/

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9020A	MY51287403	2025.08.30	2026.08.29
Signal Generator	Keysight	N5182A	MY50144088	2025.08.30	2026.08.29
Power Sensor	Keysight	U2001	MY51250006	2025.10.28	2026.10.27
Temperature & Humidity	Wetest	HTC-1	/	2025.09.01	2026.08.31
Communication test set	R&S	CMW500	157483	2025.08.30	2026.08.29
Radio frequency control box	MWRFtest	MW100-RFCB	\	\	\
Software	MWRFtest	MTS 8310	V 3.0.0.0	\	\
D.C. Power Supply	Elektro-Automatik GmbH & Co.KG	D-41747 Viersen	6230316	2025.09.30	2026.08.29
Temperature and humidity test chamber	Auchno	OJN-9606-408 L	19120183	2026.07.07	2027.07.06

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:
1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	23.5℃	Relative Humidity:	51%RH
Pressure:	101KPa	Phase:	L
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = LISN factor + Cable Loss+ Limiter (10dB).
3. Margin = (Reading+ Factor)-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5237	25.82	10.79	36.61	56.00	-19.39	QP
2	0.5237	16.14	10.79	26.93	46.00	-19.07	AVG
3	0.6011	25.71	10.83	36.54	56.00	-19.46	QP
4	0.6011	16.75	10.83	27.58	46.00	-18.42	AVG
5 *	0.8520	33.26	10.79	44.05	56.00	-11.95	QP
6	0.8520	22.58	10.79	33.37	46.00	-12.63	AVG
7	0.8925	32.30	10.83	43.13	56.00	-12.87	QP
8	0.8925	22.41	10.83	33.24	46.00	-12.76	AVG
9	3.4080	21.12	11.73	32.85	56.00	-23.15	QP
10	3.4080	8.02	11.73	19.75	46.00	-26.25	AVG
11	4.2000	18.76	11.98	30.74	56.00	-25.26	QP
12	4.2000	5.60	11.98	17.58	46.00	-28.42	AVG

* Indicates the worst data.

Temperature:	23.5°C	Relative Humidity:	51%RH
Pressure:	101KPa	Phase:	N
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = LISN factor + Cable Loss+ Limiter (10dB).
3. Margin = (Reading+ Factor)-Limit


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2085	21.54	10.71	32.25	63.26	-31.01	QP
2	0.2085	8.15	10.71	18.86	53.26	-34.40	AVG
3	0.3570	20.38	10.71	31.09	58.80	-27.71	QP
4	0.3570	8.83	10.71	19.54	48.80	-29.26	AVG
5	0.5325	22.55	10.80	33.35	56.00	-22.65	QP
6	0.5325	12.88	10.80	23.68	46.00	-22.32	AVG
7	0.8520	29.77	10.87	40.64	56.00	-15.36	QP
8	0.8520	19.99	10.87	30.86	46.00	-15.14	AVG
9 *	0.8790	33.02	10.88	43.90	56.00	-12.10	QP
10	0.8790	19.29	10.88	30.17	46.00	-15.83	AVG
11	24.5625	16.34	17.18	33.52	60.00	-26.48	QP
12	24.5625	5.51	17.18	22.69	50.00	-27.31	AVG

* Indicates the worst data.


7. Radiated emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	24000/F(kHz)	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Frequency Range Of Radiated Measurement

(a) For an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator operates at or above 95 GHz: To the third harmonic of the highest fundamental frequency or to 750 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (5) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a) (1)through (4) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
1-25GHz	RBW 1 MHz /VBW 1 MHz for Peak, RBW 1 MHz / VBW 10Hz for Average

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not

have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	26 °C	Relative Humidity:	54%RH
Pressure:	101KPa	Test Voltage :	DC 3.7V
Test Mode:	Mode 4		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuv) + distance extrapolation factor.

Between 30MHz – 1GHz

Temperature:	23.1°C	Relative Humidity:	55%RH
Pressure:	101KPa	Phase:	Horizontal
Test Mode:	Mode 4	Test Voltage :	DC 3.7V




Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Margin = (Reading + Factor)–Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	50.0566	26.58	-11.41	15.17	40.00	-24.83	QP
2	192.4186	41.70	-13.49	28.21	43.50	-15.29	QP
3	230.9068	37.21	-12.06	25.15	46.00	-20.85	QP
4	346.8092	39.73	-9.02	30.71	46.00	-15.29	QP
5 *	385.2805	43.01	-7.73	35.28	46.00	-10.72	QP
6	845.0878	30.77	1.63	32.40	46.00	-13.60	QP

* Indicates the worst data.

Temperature:	23.1°C	Relative Humidity:	55%RH
Pressure:	101KPa	Phase:	Vertical
Test Mode:	Mode 4	Test Voltage :	DC 3.7V



Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Margin = (Reading + Factor) – Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.0066	26.21	-11.62	14.59	40.00	-25.41	QP
2	147.4036	26.21	-10.08	16.13	43.50	-27.37	QP
3	307.8313	28.94	-9.75	19.19	46.00	-26.81	QP
4	385.2805	30.84	-7.73	23.11	46.00	-22.89	QP
5	462.3455	31.04	-5.75	25.29	46.00	-20.71	QP
6 *	771.4486	31.05	0.54	31.59	46.00	-14.41	QP

* Indicates the worst data.

Between 1GHz – 25GHz

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
GFSK Low channel							
V	4804.00	64.85	-9.61	55.24	74.00	-18.76	PK
V	4804.00	56.60	-9.61	46.99	54.00	-7.01	AV
V	7206.00	56.22	-4.13	52.09	74.00	-21.91	PK
V	7206.00	45.86	-4.13	41.73	54.00	-12.27	AV
H	4804.00	61.39	-9.61	51.78	74.00	-22.22	PK
H	4804.00	51.77	-9.61	42.16	54.00	-11.84	AV
H	7206.00	53.61	-4.13	49.48	74.00	-24.52	PK
H	7206.00	45.24	-4.13	41.11	54.00	-12.89	AV
GFSK Middle channel							
V	4882.00	63.31	-8.84	54.47	74.00	-19.53	PK
V	4882.00	56.78	-8.84	47.94	54.00	-6.06	AV
V	7323.00	55.19	-3.41	51.78	74.00	-22.22	PK
V	7323.00	46.82	-3.41	43.41	54.00	-10.59	AV
H	4882.00	60.43	-8.84	51.59	74.00	-22.41	PK
H	4882.00	49.95	-8.84	41.11	54.00	-12.89	AV
H	7323.00	53.80	-3.41	50.39	74.00	-23.61	PK
H	7323.00	46.70	-3.41	43.29	54.00	-10.71	AV
GFSK High channel							
V	4960.00	66.12	-8.65	57.47	74.00	-16.53	PK
V	4960.00	56.50	-8.65	47.85	54.00	-6.15	AV
V	7440.00	59.89	-3.4	56.49	74.00	-17.51	PK
V	7440.00	50.37	-3.4	46.97	54.00	-7.03	AV
H	4960.00	63.57	-8.65	54.92	74.00	-19.08	PK
H	4960.00	53.96	-8.65	45.31	54.00	-8.69	AV
H	7440.00	57.20	-3.4	53.80	74.00	-20.20	PK
H	7440.00	48.29	-3.4	44.89	54.00	-9.11	AV

Remark:

1. Measurement = Reading Level + Correct Factor, Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Measurement - Limit

2.If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
π/4-DQPSK Low channel							
V	4804.00	63.51	-9.61	53.90	74.00	-20.10	PK
V	4804.00	55.05	-9.61	45.44	54.00	-8.56	AV
V	7206.00	53.31	-4.13	49.18	74.00	-24.82	PK
V	7206.00	43.89	-4.13	39.76	54.00	-14.24	AV
H	4804.00	62.11	-9.61	52.50	74.00	-21.50	PK
H	4804.00	52.84	-9.61	43.23	54.00	-10.77	AV
H	7206.00	50.31	-4.13	46.18	74.00	-27.82	PK
H	7206.00	42.18	-4.13	38.05	54.00	-15.95	AV
π/4-DQPSK Middle channel							
V	4882.00	59.86	-8.84	51.02	74.00	-22.98	PK
V	4882.00	53.54	-8.84	44.70	54.00	-9.30	AV
V	7323.00	50.19	-3.41	46.78	74.00	-27.22	PK
V	7323.00	40.95	-3.41	37.54	54.00	-16.46	AV
H	4882.00	54.86	-8.84	46.02	74.00	-27.98	PK
H	4882.00	45.39	-8.84	36.55	54.00	-17.45	AV
H	7323.00	47.53	-3.41	44.12	74.00	-29.88	PK
H	7323.00	39.54	-3.41	36.13	54.00	-17.87	AV
π/4-DQPSK High channel							
V	4960.00	62.52	-8.65	53.87	74.00	-20.13	PK
V	4960.00	54.42	-8.65	45.77	54.00	-8.23	AV
V	7440.00	56.26	-3.4	52.86	74.00	-21.14	PK
V	7440.00	46.39	-3.4	42.99	54.00	-11.01	AV
H	4960.00	60.14	-8.65	51.49	74.00	-22.51	PK
H	4960.00	49.48	-8.65	40.83	54.00	-13.17	AV
H	7440.00	53.33	-3.4	49.93	74.00	-24.07	PK
H	7440.00	46.03	-3.4	42.63	54.00	-11.37	AV

Remark:

1. Measurement = Reading Level + Correct Factor, Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Measurement - Limit
- 2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
8DPSK Low channel							
V	4804.00	63.28	-9.61	53.67	74.00	-20.33	PK
V	4804.00	54.39	-9.61	44.78	54.00	-9.22	AV
V	7206.00	55.48	-4.13	51.35	74.00	-22.65	PK
V	7206.00	44.98	-4.13	40.85	54.00	-13.15	AV
H	4804.00	59.46	-9.61	49.85	74.00	-24.15	PK
H	4804.00	48.63	-9.61	39.02	54.00	-14.98	AV
H	7206.00	54.33	-4.13	50.20	74.00	-23.80	PK
H	7206.00	47.33	-4.13	43.20	54.00	-10.80	AV
8DPSK Middle channel							
V	4882.00	59.60	-8.84	50.76	74.00	-23.24	PK
V	4882.00	51.57	-8.84	42.73	54.00	-11.27	AV
V	7323.00	50.49	-3.41	47.08	74.00	-26.92	PK
V	7323.00	41.03	-3.41	37.62	54.00	-16.38	AV
H	4882.00	57.10	-8.84	48.26	74.00	-25.74	PK
H	4882.00	46.91	-8.84	38.07	54.00	-15.93	AV
H	7323.00	49.26	-3.41	45.85	74.00	-28.15	PK
H	7323.00	42.20	-3.41	38.79	54.00	-15.21	AV
8DPSK High channel							
V	4960.00	61.68	-8.65	53.03	74.00	-20.97	PK
V	4960.00	52.73	-8.65	44.08	54.00	-9.92	AV
V	7440.00	53.76	-3.4	50.36	74.00	-23.64	PK
V	7440.00	42.85	-3.4	39.45	54.00	-14.55	AV
H	4960.00	60.26	-8.65	51.61	74.00	-22.39	PK
H	4960.00	49.89	-8.65	41.24	54.00	-12.76	AV
H	7440.00	51.17	-3.4	47.77	74.00	-26.23	PK
H	7440.00	43.54	-3.4	40.14	54.00	-13.86	AV


Remark:

1. Measurement = Reading Level + Correct Factor, Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Measurement - Limit
- 2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8. Radiated Band Emission Measurement and Restricted Bands of Operation

8.1 Block Diagram Of Test Setup

Radiated Emission Test-Up Frequency Above 1GHz



8.2 Limit

FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3)Emission level (dBuV/m)=20log Emission level (uV/m).

8.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (Emission In Restricted Band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Above 1GHz test procedure as below:

a.The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

8.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

8.5 Test Result

Test mode	Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)		Result
					PK	PK	AV	
GFSK	Low Channel 2402MHz							
	H	2390.00	62.56	-17.27	45.29	74.00	54.00	PASS
	H	2400.00	66.36	-17.23	49.13	74.00	54.00	PASS
	V	2390.00	63.85	-17.27	46.58	74.00	54.00	PASS
	V	2400.00	65.66	-17.23	48.43	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	66.32	-16.91	49.41	74.00	54.00	PASS
	H	2500.00	62.11	-16.71	45.40	74.00	54.00	PASS
	V	2483.50	66.04	-16.91	49.13	74.00	54.00	PASS
	V	2500.00	63.32	-16.71	46.61	74.00	54.00	PASS
π/4DQPSK	Low Channel 2402MHz							
	H	2390.00	63.01	-17.27	45.74	74.00	54.00	PASS
	H	2400.00	66.64	-17.23	49.41	74.00	54.00	PASS
	V	2390.00	62.32	-17.27	45.05	74.00	54.00	PASS
	V	2400.00	66.09	-17.23	48.86	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	65.32	-16.91	48.41	74.00	54.00	PASS
	H	2500.00	63.83	-16.71	47.12	74.00	54.00	PASS
	V	2483.50	66.04	-16.91	49.13	74.00	54.00	PASS
	V	2500.00	62.94	-16.71	46.23	74.00	54.00	PASS
8DPSK	Low Channel 2402MHz							
	H	2390.00	63.44	-17.27	46.17	74.00	54.00	PASS
	H	2400.00	65.00	-17.23	47.77	74.00	54.00	PASS
	V	2390.00	62.74	-17.27	45.47	74.00	54.00	PASS
	V	2400.00	65.77	-17.23	48.54	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	66.85	-16.91	49.94	74.00	54.00	PASS
	H	2500.00	63.08	-16.71	46.37	74.00	54.00	PASS
	V	2483.50	65.24	-16.91	48.33	74.00	54.00	PASS
	V	2500.00	63.06	-16.71	46.35	74.00	54.00	PASS

Remark:

1. Measurement = Reading Level + Correct Factor, Correct Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Measurement - Limit


2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

9. Spurious RF Conducted Emissions

9.1 Block Diagram Of Test Setup




9.2 Limit



Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))



9.3 Test procedure



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 Below 30MHz:
 RBW = 100kHz, VBW = 300kHz, Sweep = auto
 Detector function = peak, Trace = max hold
 Above 30MHz:
 RBW = 100KHz, VBW = 300KHz, Sweep = auto
 Detector function = peak, Trace = max hold



9.4 Test Result






































CO., LTD

