



Shenzhen Huaxia Testing Technology Co., Ltd.

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD 102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20260801700E-03
Applicant: Changzhou Sifary Medical Technology Co.,Ltd.
Address of Applicant: No.26 Yandanghe Road, Xinbei District, Changzhou City, Jiangsu Province, China
Equipment Under Test (EUT):
EUT Name: 3D Printer
Model No.: SideLab P1
Test Model No.: SideLab P1
Brand Name: Eighteeth
FCC ID: 2BXX7-SIDELABP1
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2026-08-03
Date of Test: 2026-08-03 to 2026-08-19
Date of Issue: 2026-8-27
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Azir Wang
(Azir Wang)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260801700E-03	Rev.01	Initial report	2026-8-27

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
3.4 GENERAL DESCRIPTION OF 5G WIFI CLASSIC	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure	7

3 General Information

3.1 Client Information

Applicant:	Changzhou Sifary Medical Technology Co.,Ltd.
Address of Applicant:	No.26 Yandanghe Road, Xinbei District, Changzhou City, Jiangsu Province, China
Manufacturer:	Changzhou Sifary Medical Technology Co.,Ltd.
Address of Manufacturer:	No.26 Yandanghe Road, Xinbei District, Changzhou City, Jiangsu Province, China
Factory:	Changzhou Sifary Medical Technology Co.,Ltd.
Address of Factory:	No.26 Yandanghe Road, Xinbei District, Changzhou City, Jiangsu Province, China

3.2 General Description of EUT

Product Name:	3D Printer
Model No.:	SideLab P1
Test Model No.:	SideLab P1
Trade Mark:	Eighteeth
Software Version:	V2.0
Hardware Version:	V2.1
EUT Power Supply:	Adapter: MODEL:AK120WG-2400500W1 INPUT:100-240V~50/60Hz 2.0A OUTPUT:24.0V $\pm$ 5.0A 120W

3.3 General Description of 2.4G WIFI Classic

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	802.11b: DSSS(CCK/QPSK/BPSK) 802.11g: OFDM(BPSK/QPSK/16QAM/64QAM) 802.11n : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Transfer Rate:	802.11b: 1M/2M/5.5M/11M bps 802.11g: 6M/9M/12M/18M/24M/36M/48M/54M bps 802.11n: 7.2M/14.4M/21.7M/28.9M/43.3M/57.8M/65M/72.2Mbps
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	FPC antenna
Antenna Gain:	1.96dBi

3.4 General Description of 5G WIFI Classic

Operation Frequency:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250 MHz IEEE802.11n/ac(40M): 5150MHz ~5250 MHz IEEE802.11n/ac(80M): 5150MHz ~5250 MHz
Channel Numbers:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11n/ac(80M): 5150MHz ~5250MHz/ 1 channel
Type of Modulation:	OFDM
Sample Type:	☒ Mobile ☐ Portable
Test Software of EUT:	CMD
Antenna Type:	FPC antenna
Antenna gain:	4.09dBi
Cable loss:	1dB

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For 2.4G WIFI

Antenna Gain: 1.96dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.57 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11B mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	11.90	12.0 ± 1	13.0	19.953
Middle(2437MHz)	12.27	12.0 ± 1	13.0	19.953
Highest(2462MHz)	12.34	12.5 ± 1	13.5	22.387

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
22.387	1.96	0.0069940564	1.0	PASS

Note: 1) Refer to report No. CQASZ20260801700E-01 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (22.387 * 1.57) / (4 * 3.1416 * 20^2) = 0.0069940564$

4) For 5G WIFI Classic

Antenna Gain: 4.09dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.56 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

11N20 mode				
Test channel	AV Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(5180MHz)	8.66	8.5 ± 1	9.5	8.91
Middle(5200MHz)	8.95	9.0 ± 1	10.0	10.00
Highest(5240MHz)	8.62	8.5 ± 1	9.5	8.91

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
10.00	4.09	0.0051018670	1.0	PASS

Note: 1) Refer to report No. CQASZ20260801700E-02 for EUT test Max Conducted AV Output Power value.

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (10.00 * 2.56) / (4 * 3.1416 * 20^2) = 0.0051018670$

*** END OF REPORT ***