



FCC RF Exposure

EUT Description: Remote control

Model No.: J2,J1

FCC ID: 2BXKI-J2

Equipment type: portable device

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz. The result is rounded to one decimal place for comparison

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min test separation distance in mm})^2} \right]^{1/2} < 3.0 \text{ for 1-g SAR, and } < 7.5 \text{ for 10-g extremity SAR, where}$$

Power and distance are rounded to the nearest mW and mm before calculation

Limits for Maximum Permissible Exposure (MPE)

2.4G

Frequency(MHz)	Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Min. distance(m)	Calc. thresholds	limit
2402	97.94	2.782	1.8978	5	0.58825	3.0
2440	97.83	2.672	1.8503	5	0.57805	3.0
2480	98.18	3.022	2.0056	5	1.99796	3.0

Conclusion: No SAR is required