

RF TEST REPORT

For

Shenzhen Aikechuangpin Technology Co., Ltd.

Product Name: security camera

Test Model(s): 6606

Report Reference No. : DACE260730003RF001

FCC ID : 2BXKL-6606

Applicant's Name : Shenzhen Aikechuangpin Technology Co., Ltd.

Address : Rm 1005, Tower 3, Manjinghua Yiluan Bldg, No. 230 Avenue, Xixiang,
Bao'an, Shenzhen, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park,
Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen,
Guangdong, China

Test Specification Standard : 47 CFR Part 24E
47 CFR Part 22H
47 CFR Part 27

Date of Receipt : July 30, 2026

Date of Test : July 30, 2026 to August 5, 2026

Date of Issue : August 5, 2026

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

Apply for company information

Applicant's Name	:	Shenzhen Aikechuangpin Technology Co., Ltd.
Address	:	Rm 1005, Tower 3, Manjinghua Yiluan Bldg., No. 230 Avenue, Xixiang, Bao'an, Shenzhen, China
Product Name	:	security camera
Test Model(s)	:	6606
Series Model(s)	:	6609, 6610, 6611, 6612, 6613, 6615, 9562, 6601, 6008, 6009, 6002, 6003, 6005, 6006, 6007, 6010, 9836, 9936, 9632, 5601, 9560, 6701, 6702, 6703, 6607, 6608
Test Specification Standard(s)	:	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

August 5, 2026

Supervised by:

Ben Tang

Ben Tang / Project Engineer

August 5, 2026

Approved by:

Machael Mo

Machael Mo / Manager

August 5, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260730003RF001	August 5, 2026

CONTENTS

1	TEST SUMMARY	5
1.1	TEST STANDARDS	5
1.2	SUMMARY OF TEST RESULT	5
2	GENERAL INFORMATION	6
2.1	CLIENT INFORMATION	6
2.2	DESCRIPTION OF DEVICE (EUT)	6
2.3	DESCRIPTION OF TEST MODES	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	EQUIPMENTS USED DURING THE TEST	7
2.6	STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
2.7	AUTHORIZATIONS	9
2.8	ANNOUNCEMENT	9
3	EVALUATION RESULTS (EVALUATION)	10
3.1	ANTENNA REQUIREMENT	10
3.1.1	Conclusion:	10
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	11
4.1	EFFECTIVE (ISOTROPIC) RADIATED POWER OUTPUT	11
4.1.1	E.U.T. Operation:	11
4.1.2	Test Setup Diagram:	11
4.1.3	Test Data:	11
4.2	PEAK TO AVERAGE RATIO	12
4.2.1	E.U.T. Operation:	12
4.2.2	Test Setup Diagram:	12
4.2.3	Test Data:	12
4.3	BANDWIDTH	13
4.3.1	E.U.T. Operation:	14
4.3.2	Test Setup Diagram:	15
4.3.3	Test Data:	15
4.4	SPURIOUS UNWANTED EMISSION	16
4.4.1	E.U.T. Operation:	18
4.4.2	Test Setup Diagram:	18
4.4.3	Test Data:	19
4.5	OUT OF BAND EMISSION	38
4.5.1	E.U.T. Operation:	40
4.5.2	Test Setup Diagram:	40
4.5.3	Test Data:	40
4.6	FIELD STRENGTH OF RADIATED EMISSION	41
4.6.1	E.U.T. Operation:	43
4.6.2	Test Data:	43
4.7	FREQUENCY STABILITY	44
4.7.1	E.U.T. Operation:	46
4.7.2	Test Setup Diagram:	46
4.7.3	Test Data:	46
5	TEST SETUP PHOTOS	47
6	PHOTOS OF THE EUT	48

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 24E: Personal Communications Services - Broadband PCS
47 CFR Part 22H: Public Mobile Services - Cellular Radiotelephone Service
47 CFR Part 27: Miscellaneous Wireless Communications Services

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Effective (Isotropic) Radiated Power Output	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	ANSI C63.26-2015, Section 5.2.4.2	47 CFR Part 2.1046, Part 22.913	Pass
Peak To Average Ratio	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	ANSI C63.26-2015, Section 5.2.3.4	47 CFR Part 2.1046, Part 27.50	Pass
Bandwidth	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	ANSI C63.26-2015, Section 5.4	47 CFR Part 2.1049(h)	Pass
Spurious Unwanted Emission	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	47 CFR Part 24.238(b) ANSI C63.26-2015, Section 5.7.3	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)	Pass
Out of Band Emission	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	47 CFR Part 24.238(b) ANSI C63.26-2015, Section 5.7.3	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)	Pass
Field Strength of Radiated Emission	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	ANSI C63.26-2015, Section 5.5.3	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)	Pass
Frequency Stability	47 CFR Part 24E 47 CFR Part 22H 47 CFR Part 27	ANSI C63.26-2015, Section 5.6	47 CFR Part 2.1055, Part 27.54	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Shenzhen Aikechuangpin Technology Co., Ltd.
Address : Rm 1005, Tower 3, Manjinghua Yiluan Bldg., No. 230 Avenue, Xixiang, Bao'an, Shenzhen, China

Manufacturer : Shenzhen Aikechuangpin Technology Co., Ltd.
Address : Rm 1005, Tower 3, Manjinghua Yiluan Bldg., No. 230 Avenue, Xixiang, Bao'an, Shenzhen, China

2.2 Description of Device (EUT)

Product Name:	security camera
Model/Type reference:	6606
Series Model:	6609, 6610, 6611, 6612, 6613, 6615, 9562, 6601, 6008, 6009, 6002, 6003, 6005, 6006, 6007, 6010, 9836, 9936, 9632, 5601, 9560, 6701, 6702, 6703, 6607, 6608
Model Difference:	The product has many models, only the model name and color is different, and the other parts such as the circuit principle, pcb and electrical structure are the same.
Trade Mark:	N/A
Power Supply:	DC 5V charging from adapter DC 3.7V by battery
Operation Frequency:	LTE BAND2: 1850-1910MHz LTE BAND4: 1710-1755 MHz LTE BAND5: 824-849MHz LTE BAND7: 2500-2570MHz LTE BAND38: 2570-2620MHz LTE BAND41: 2496-2690MHz LTE BAND66: 1710-1780 MHz
Modulation Type:	QPSK, 16QAM
Antenna Type:	Internal Antenna
Antenna Gain:	Band2: 2.69dBi; Band4: 1.71; Band5: -0.96dBi; Band7: -0.84dBi; Band38: -1.65dBi; Band41: -0.84dBi; Band66: 2.46dBi
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	FDD-LTE Band 2	Low, Middle, High Channels
TM2	FDD-LTE Band 4	Low, Middle, High Channels
TM3	FDD-LTE Band 5	Low, Middle, High Channels
TM4	FDD-LTE Band 7	Low, Middle, High Channels
TM5	FDD-LTE Band 38	Low, Middle, High Channels
TM6	FDD-LTE Band 41	Low, Middle, High Channels
TM7	FDD-LTE Band 66	Low, Middle, High Channels
Test Environment		Normal Voltage(AC): 120V

2.4 Description of Support Units

The EUT was tested as an independent device.

2.5 Equipments Used During The Test

Peak To Average Ratio
Bandwidth
Spurious Unwanted Emission
Out of Band Emission
Frequency Stability
Effective (Isotropic) Radiated Power Output

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she n zhen) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Sensor Unit	Tachoy Information Technology(she n zhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Vector Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01

Field Strength of Radiated Emission					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Cable(HF)2	SCHWARZ BECK	50Ω	/	2026-04-14	2027-04-13
Cable(HF)1	SCHWARZ BECK	50Ω	/	2026-04-14	2027-04-13
Cable(LF)2	SCHWARZ BECK	50Ω	/	2026-04-14	2027-04-13
Cable(LF)1	SCHWARZ BECK	50Ω	/	2026-04-14	2027-04-13
Control	MF	MF-7802	MF780208362	2025-12-02	2026-12-01
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	1164.6607K03 -102109-MH	2026-04-14	2027-04-13
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2026-04-14	2027-04-13
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2026-04-14	2027-04-13
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2026-04-14	2027-04-13
Test Receiver	R&S	ESCI 3	1166.5950K03 -101431-Jq	2026-04-14	2027-04-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2026-04-14	2027-04-13
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
RF conducted power	$\pm 0.733\text{dB}$
Occupied Bandwidth	$\pm 3.63\%$
RF power density	$\pm 0.234\%$
Radiated Emission (Above 1GHz)	$\pm 5.46\text{dB}$
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.	

2.7 Authorizations

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
Designation Number:	CN1342
Test Firm Registration No.:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client(item 2.2). When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

3.1.1 Conclusion:



4G-ANT

4 Radio Spectrum Matter Test Results (RF)


4.1 Effective (Isotropic) Radiated Power Output

Test Method:	ANSI C63.26-2015, Section 5.2.4.2
Procedure:	If the EUT cannot be configured to transmit continuously (i.e., burst duty cycle < 98%), then the following options can be implemented to facilitate measurement of the average power with an average power meter: a) A gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only during active transmission bursts at maximum output power levels. b) A conventional average power meter with no signal gating capability can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than or equal to $\pm 2\%$) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $[10 \log (1/\text{duty cycle})]$. See 5.2.4.3.4 for guidance with respect to measuring the transmitter duty cycle.

4.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.4 °C	Humidity:	47 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.1.2 Test Setup Diagram:



4.1.3 Test Data:

Please Refer to Appendix for Details.


4.2 Peak To Average Ratio

Test Requirement:	47 CFR Part 2.1046, Part 27.50
Test Limit:	The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.
Test Method:	ANSI C63.26-2015, Section 5.2.3.4
Procedure:	a) Set resolution/measurement bandwidth $\geq$ OBW or specified reference bandwidth. b) Set the number of counts to a value that stabilizes the measured CCDF curve. c) Set the measurement interval as follows: 1) For continuous transmissions, set to the greater of $[10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$ or 1 ms. 2) For burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize. Set the measurement interval to a time that is less than or equal to the burst duration. 3) If there are several carriers in a single antenna port, the peak power shall be determined for each individual carrier (by disabling the other carriers while measuring the required carrier) and the total peak power calculated from the sum of the individual carrier peak powers. d) Record the maximum PAPR level associated with a probability of 0.1%. e) The peak power level is calculated from the sum of the PAPR value from step d) to the measured average power.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.7 °C	Humidity:	48 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.

4.3 Bandwidth

Test Requirement:	47 CFR Part 2.1049(h)
Test Limit:	OBW: No limit, only for report use. EBW: No limit, only for report use.
Test Method:	ANSI C63.26-2015, Section 5.4
Procedure:	OBW: a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient). b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$. c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3. NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances. d) Set the detection mode to peak, and the trace mode to max-hold. e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies. f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s). EBW: a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement. b) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$. c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3. NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances. d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB

OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.

e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.

f) Determine the reference value by either of the following:

- 1) Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- 2) Set the EUT to transmit an unmodulated carrier. Set the spectrum analyzer marker to the level of the carrier.

g) Determine the “-X dB amplitude” as equal to (Reference Value - X). Alternatively, this calculation can be performed on the spectrum analyzer using the delta-marker measurement function.

h) If the reference value was determined using an unmodulated carrier, turn the EUT modulation on, then either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise the trace from step f) shall be used for step i).


i) Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB amplitude” determined in step f). If a marker is below this “-X dB amplitude” value it should be as close as possible to this value. The OBW is the positive frequency difference between the two markers. The spectral envelope can cross the “-X dB amplitude” at multiple points. The lowest or highest frequency shall be selected as the frequencies that are the farthest away from the center frequency at which the spectral envelope crosses the “-X dB amplitude.”

j) The OBW shall be reported by providing plot(s) of the measuring instrument display, to include markers depicting the relevant frequency and amplitude information (e.g., marker table). The frequency and amplitude axis and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.7 °C	Humidity:	51 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.

4.4 Spurious Unwanted Emission

Test Requirement:	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)
Test Limit:	(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations; (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation. (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. (h) (1) $10 (P)$ dB. (2) paragraph (h)(1) of this section: (i) Operations in the 2180-2200 MHz band are subject to the out-of-band emission requirements set forth in § 27.1134 for the protection of federal government operations operating in the 2200-2290 MHz band. (ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB. (iii) For operations in the 1915-1920 MHz band, the power of any emission between 1930-1995 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB.

	(iv) For operations in the 1995-2000 MHz band, the power of any emission between 2005-2020 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10}(P)$ dB.
Test Method:	47 CFR Part 24.238(b) ANSI C63.26-2015, Section 5.7.3
Procedure:	Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (a) Set the spectrum analyzer center frequency to the block, band, or channel edge frequency. b) Set the span wide enough to capture the fundamental emission closest to the authorized block or band edge, and to include all modulation products that spill into the immediately adjacent frequency band. In some cases, it may be possible to set the center frequency and span so as to encompass the fundamental emission and the unwanted out-of-band (band-edge) emissions on either side of the authorized block, band, or channel. This can be accomplished with a single (slow) sweep, if adequate overload protection and sufficient dynamic range can be maintained. c) Set the number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. d) Sweep time should be auto for peak detection. For rms detection the sweep time should be set as follows: 1) If the device can be configured to transmit continuously (duty cycle $\geq 98\%$), set the (sweep time) $> (\text{number of points in sweep}) \times (\text{symbol period})$ (e.g., by a factor of $10 \times \text{symbol period} \times \text{number of points}$). Increasing the sweep time (i.e., slowing the sweep speed) will allow for averaging over multiple symbols 2) If the device cannot transmit continuously (duty cycle $< 98\%$), a gated sweep shall be used when possible (i.e., gate triggered such that the analyzer only sweeps when the device is transmitting at full power), set the sweep time $> (\text{number of points in sweep}) \times (\text{symbol period})$ but the sweep time shall always be maintained at a value that is less than or equal to the minimum transmission time. 3) If the device cannot be configured to transmit continuously (duty cycle $< 98\%$) and a freerunning sweep must be used, set the sweep time so that the averaging is performed over multiple on/off cycles by setting the sweep time $> (\text{number of points in sweep}) \times (\text{transmitter period})$ (i.e., the transmit on-time + the off-time). The spectrum analyzer readings shall subsequently be corrected by $[10 \log (1/\text{duty cycle})]$. This assumes that the transmission period and duty cycle is relatively constant (duty cycle variation $\leq \pm 2\%$). 4) If the device cannot be configured to transmit continuously and a free-running

sweep must be used, and if the transmissions exhibit a non-constant duty cycle (duty cycle variations $> \pm 2\%$), set the sweep time so that the averaging is performed over the on-period by setting the sweep time $> (\text{symbol period}) \times (\text{number of points})$, while also maintaining the sweep time $< (\text{transmitter on-time})$. The trace mode shall be set to max hold, since not every display point will be averaged only over just the on-time. Thus, multiple sweeps (e.g., 100) in maximum hold are necessary to ensure that the maximum power is measured.


e) The test report shall include the plots of the measuring instrument display and the measured data.

f) See Annex I for example emission mask plots.

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.3 °C	Humidity:	48 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

LTE Band 2-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.49	Vertical	-38.40	-6.68	-45.08	- 13.00	PASS
		2289.74	V	-49.72	-3.42	-53.14		
		3285.45	V	-49.28	-1.42	-50.70		
		285.07	Horizontal	-35.80	-6.68	-42.48	- 13.00	PASS
		2288.59	H	-43.20	-3.42	-46.62		
		3284.49	H	-47.79	-1.42	-49.21		
	Mid	300.30	Vertical	-38.82	-6.68	-45.50	- 13.00	PASS
		2288.45	V	-48.01	-3.42	-51.43		
		3293.13	V	-44.75	-1.42	-46.17		
		285.22	Horizontal	-32.96	-6.68	-39.64	- 13.00	PASS
		2287.73	H	-47.04	-3.42	-50.46		
		3293.68	H	-45.31	-1.42	-46.73		
	High	288.03	Vertical	-39.87	-6.68	-46.55	- 13.00	PASS
		2298.52	V	-44.41	-3.42	-47.83		
		3288.25	V	-45.86	-1.42	-47.28		
		299.32	Horizontal	-37.98	-6.68	-44.66	- 13.00	PASS
		2288.09	H	-47.05	-3.42	-50.47		
		3296.13	H	-51.98	-1.42	-53.40		
3MHz	Low	298.86	Vertical	-30.94	-6.68	-37.62	- 13.00	PASS
		2289.18	V	-47.94	-3.42	-51.36		
		3295.13	V	-45.70	-1.42	-47.12		
		284.92	Horizontal	-36.08	-6.68	-42.76	- 13.00	PASS
		2291.98	H	-46.93	-3.42	-50.35		
		3297.41	H	-48.11	-1.42	-49.53		
	Mid	295.96	Vertical	-31.29	-6.68	-37.97	- 13.00	PASS
		2298.41	V	-40.46	-3.42	-43.88		
		3294.03	V	-44.06	-1.42	-45.48		
		300.86	Horizontal	-31.63	-6.68	-38.31	- 13.00	PASS
		2291.72	H	-49.44	-3.42	-52.86		
		3283.62	H	-52.14	-1.42	-53.56		
	High	294.34	Vertical	-36.35	-6.68	-43.03	- 13.00	PASS
		2295.71	V	-42.31	-3.42	-45.73		
		3296.15	V	-51.63	-1.42	-53.05		

		286.34	Horizontal	-38.44	-6.68	-45.12	- 13.00	PASS
		2291.18	H	-47.91	-3.42	-51.33		
		3292.02	H	-51.92	-1.42	-53.34	- 13.00	PASS
5MHz	Low	287.50	Vertical	-33.94	-6.68	-40.62	- 13.00	PASS
		2293.73	V	-41.39	-3.42	-44.81		
		3289.93	V	-44.04	-1.42	-45.46		
		284.37	Horizontal	-32.56	-6.68	-39.24	- 13.00	PASS
		2287.75	H	-44.07	-3.42	-47.49		
		3290.39	H	-47.74	-1.42	-49.16		
	Mid	293.75	Vertical	-31.04	-6.68	-37.72	- 13.00	PASS
		2283.60	V	-43.95	-3.42	-47.37		
		3289.40	V	-46.69	-1.42	-48.11		
		288.63	Horizontal	-37.17	-6.68	-43.85	- 13.00	PASS
		2294.72	H	-42.30	-3.42	-45.72		
		3291.30	H	-51.15	-1.42	-52.57		
	High	298.31	Vertical	-33.16	-6.68	-39.84	- 13.00	PASS
		2297.84	V	-44.10	-3.42	-47.52		
		3294.74	V	-49.65	-1.42	-51.07		
		291.01	Horizontal	-38.50	-6.68	-45.18	- 13.00	PASS
		2301.22	H	-50.14	-3.42	-53.56		
		3291.71	H	-49.25	-1.42	-50.67		
10MHz	Low	294.42	Vertical	-37.07	-6.68	-43.75	- 13.00	PASS
		2300.16	V	-47.40	-3.42	-50.82		
		3291.64	V	-45.91	-1.42	-47.33		
		295.12	Horizontal	-37.24	-6.68	-43.92	- 13.00	PASS
		2300.51	H	-41.26	-3.42	-44.68		
		3293.74	H	-45.59	-1.42	-47.01		
	Mid	294.34	Vertical	-36.71	-6.68	-43.39	- 13.00	PASS
		2289.70	V	-44.03	-3.42	-47.45		
		3299.35	V	-48.82	-1.42	-50.24		
		298.32	Horizontal	-30.36	-6.68	-37.04	- 13.00	PASS
		2284.12	H	-47.33	-3.42	-50.75		
		3300.12	H	-52.37	-1.42	-53.79		
	High	284.04	Vertical	-34.19	-6.68	-40.87	- 13.00	PASS
		2285.40	V	-45.70	-3.42	-49.12		
		3294.69	V	-49.60	-1.42	-51.02		
		300.56	Horizontal	-38.31	-6.68	-44.99	- 13.00	PASS
		2286.10	H	-47.60	-3.42	-51.02		

15MHz	Low	3284.45	H	-51.77	-1.42	-53.19	- 13.00	PASS
		297.11	Vertical	-32.30	-6.68	-38.98		
		2290.58	V	-49.18	-3.42	-52.60		
		3295.95	V	-44.32	-1.42	-45.74	- 13.00	PASS
		282.49	Horizontal	-32.47	-6.68	-39.15		
		2301.25	H	-40.29	-3.42	-43.71		
	Mid	3293.10	H	-45.44	-1.42	-46.86	- 13.00	PASS
		282.52	Vertical	-35.44	-6.68	-42.12		
		2293.33	V	-42.74	-3.42	-46.16		
		3282.94	V	-43.23	-1.42	-44.65	- 13.00	PASS
		297.57	Horizontal	-37.83	-6.68	-44.51		
		2300.82	H	-44.89	-3.42	-48.31		
	High	3282.73	H	-45.92	-1.42	-47.34	- 13.00	PASS
		294.21	Vertical	-33.81	-6.68	-40.49		
		2293.27	V	-47.58	-3.42	-51.00		
		3283.69	V	-43.76	-1.42	-45.18	- 13.00	PASS
		298.46	Horizontal	-34.21	-6.68	-40.89		
		2283.44	H	-41.36	-3.42	-44.78		
20MHz	Low	3289.18	H	-51.96	-1.42	-53.38	- 13.00	PASS
		298.15	Vertical	-33.61	-6.68	-40.29		
		2296.44	V	-41.94	-3.42	-45.36		
		3285.88	V	-46.98	-1.42	-48.40	- 13.00	PASS
		290.31	Horizontal	-37.37	-6.68	-44.05		
		2282.24	H	-43.47	-3.42	-46.89		
	Mid	3296.60	H	-49.73	-1.42	-51.15	- 13.00	PASS
		291.24	Vertical	-34.22	-6.68	-40.90		
		2291.70	V	-49.13	-3.42	-52.55		
		3297.60	V	-48.22	-1.42	-49.64	- 13.00	PASS
		286.69	Horizontal	-32.50	-6.68	-39.18		
		2301.20	H	-40.68	-3.42	-44.10		
	High	3297.86	H	-47.20	-1.42	-48.62	- 13.00	PASS
		282.35	Vertical	-34.50	-6.68	-41.18		
		2286.24	V	-44.16	-3.42	-47.58		
		3287.67	V	-51.51	-1.42	-52.93	- 13.00	PASS
		299.93	Horizontal	-31.10	-6.68	-37.78		
		2285.17	H	-50.08	-3.42	-53.50		
		3283.86	H	-49.39	-1.42	-50.81		

LTE Band 4-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.20	Vertical	-38.33	-6.68	-45.01	- 13.00	PASS
		2289.85	V	-49.60	-3.42	-53.02		
		3285.70	V	-49.23	-1.42	-50.65		
		284.87	Horizontal	-35.83	-6.68	-42.51	- 13.00	PASS
		2288.86	H	-43.07	-3.42	-46.49		
		3284.68	H	-47.67	-1.42	-49.09		
	Mid	300.59	Vertical	-38.71	-6.68	-45.39	- 13.00	PASS
		2288.36	V	-48.10	-3.42	-51.52		
		3292.84	V	-44.81	-1.42	-46.23		
		284.77	Horizontal	-32.97	-6.68	-39.65	- 13.00	PASS
		2287.97	H	-47.06	-3.42	-50.48		
		3293.45	H	-45.40	-1.42	-46.82		
	High	287.98	Vertical	-39.91	-6.68	-46.59	- 13.00	PASS
		2298.13	V	-44.44	-3.42	-47.86		
		3288.46	V	-45.95	-1.42	-47.37		
		299.34	Horizontal	-38.05	-6.68	-44.73	- 13.00	PASS
		2287.80	H	-47.03	-3.42	-50.45		
		3295.85	H	-51.83	-1.42	-53.25		
3MHz	Low	298.49	Vertical	-30.87	-6.68	-37.55	- 13.00	PASS
		2289.24	V	-48.02	-3.42	-51.44		
		3295.17	V	-45.63	-1.42	-47.05		
		284.92	Horizontal	-36.18	-6.68	-42.86	- 13.00	PASS
		2291.81	H	-46.88	-3.42	-50.30		
		3297.62	H	-48.03	-1.42	-49.45		
	Mid	295.82	Vertical	-31.24	-6.68	-37.92	- 13.00	PASS
		2298.57	V	-40.36	-3.42	-43.78		
		3294.06	V	-44.05	-1.42	-45.47		
		301.06	Horizontal	-31.61	-6.68	-38.29	- 13.00	PASS
		2291.97	H	-49.36	-3.42	-52.78		
		3283.33	H	-52.15	-1.42	-53.57		
	High	294.47	Vertical	-36.30	-6.68	-42.98	- 13.00	PASS
		2295.84	V	-42.22	-3.42	-45.64		
		3296.32	V	-51.51	-1.42	-52.93		
		286.12	Horizontal	-38.59	-6.68	-45.27	- 13.00	PASS

5MHz	Low	2291.37	H	-47.78	-3.42	-51.20	- 13.00	PASS
		3291.70	H	-51.95	-1.42	-53.37		
		287.50	Vertical	-33.90	-6.68	-40.58		
		2293.59	V	-41.37	-3.42	-44.79		
		3289.56	V	-43.97	-1.42	-45.39		
		284.14	Horizontal	-32.71	-6.68	-39.39		
		2287.89	H	-43.91	-3.42	-47.33		
	Mid	3290.64	H	-47.79	-1.42	-49.21	- 13.00	PASS
		293.51	Vertical	-31.09	-6.68	-37.77		
		2283.22	V	-43.85	-3.42	-47.27		
		3289.49	V	-46.79	-1.42	-48.21		
		288.87	Horizontal	-37.23	-6.68	-43.91		
		2294.75	H	-42.28	-3.42	-45.70		
		3291.49	H	-51.30	-1.42	-52.72		
	High	298.76	Vertical	-33.01	-6.68	-39.69	- 13.00	PASS
		2297.64	V	-44.07	-3.42	-47.49		
		3294.67	V	-49.69	-1.42	-51.11		
		290.92	Horizontal	-38.54	-6.68	-45.22		
		2301.04	H	-50.18	-3.42	-53.60		
		3291.65	H	-49.16	-1.42	-50.58		
		294.00	Vertical	-37.17	-6.68	-43.85	- 13.00	PASS
10MHz	Low	2300.26	V	-47.38	-3.42	-50.80		
		3291.65	V	-45.87	-1.42	-47.29		
		295.02	Horizontal	-37.32	-6.68	-44.00		
		2300.41	H	-41.23	-3.42	-44.65		
		3293.85	H	-45.57	-1.42	-46.99		
	Mid	294.33	Vertical	-36.67	-6.68	-43.35	- 13.00	PASS
		2289.85	V	-44.07	-3.42	-47.49		
		3299.05	V	-48.75	-1.42	-50.17		
		298.73	Horizontal	-30.20	-6.68	-36.88		
		2284.43	H	-47.41	-3.42	-50.83		
		3299.93	H	-52.31	-1.42	-53.73		
	High	283.96	Vertical	-34.15	-6.68	-40.83	- 13.00	PASS
		2285.29	V	-45.63	-3.42	-49.05		
		3294.77	V	-49.74	-1.42	-51.16		
		300.67	Horizontal	-38.34	-6.68	-45.02		
		2286.19	H	-47.52	-3.42	-50.94		
		3284.36	H	-51.80	-1.42	-53.22		

15MHz	Low	297.06	Vertical	-32.32	-6.68	-39.00	- 13.00	PASS
		2290.69	V	-49.19	-3.42	-52.61		
		3295.91	V	-44.29	-1.42	-45.71		
		282.63	Horizontal	-32.35	-6.68	-39.03	- 13.00	PASS
		2301.24	H	-40.37	-3.42	-43.79		
		3293.02	H	-45.46	-1.42	-46.88		
	Mid	282.51	Vertical	-35.41	-6.68	-42.09	- 13.00	PASS
		2293.05	V	-42.78	-3.42	-46.20		
		3283.08	V	-43.25	-1.42	-44.67		
		297.59	Horizontal	-37.87	-6.68	-44.55	- 13.00	PASS
		2300.91	H	-44.75	-3.42	-48.17		
		3283.15	H	-45.86	-1.42	-47.28		
	High	294.17	Vertical	-33.77	-6.68	-40.45	- 13.00	PASS
		2293.46	V	-47.72	-3.42	-51.14		
		3283.47	V	-43.73	-1.42	-45.15		
		298.65	Horizontal	-34.25	-6.68	-40.93	- 13.00	PASS
		2283.58	H	-41.45	-3.42	-44.87		
		3289.40	H	-52.08	-1.42	-53.50		
20MHz	Low	298.15	Vertical	-33.48	-6.68	-40.16	- 13.00	PASS
		2296.25	V	-41.87	-3.42	-45.29		
		3285.81	V	-47.07	-1.42	-48.49		
		290.44	Horizontal	-37.35	-6.68	-44.03	- 13.00	PASS
		2282.28	H	-43.33	-3.42	-46.75		
		3296.63	H	-49.82	-1.42	-51.24		
	Mid	290.99	Vertical	-34.18	-6.68	-40.86	- 13.00	PASS
		2291.91	V	-49.13	-3.42	-52.55		
		3297.24	V	-48.18	-1.42	-49.60		
		286.72	Horizontal	-32.44	-6.68	-39.12	- 13.00	PASS
		2301.22	H	-40.80	-3.42	-44.22		
		3297.77	H	-47.26	-1.42	-48.68		
	High	282.37	Vertical	-34.49	-6.68	-41.17	- 13.00	PASS
		2286.31	V	-44.21	-3.42	-47.63		
		3287.26	V	-51.56	-1.42	-52.98		
		300.37	Horizontal	-31.21	-6.68	-37.89	- 13.00	PASS
		2285.29	H	-49.94	-3.42	-53.36		
		3283.82	H	-49.40	-1.42	-50.82		

LTE Band 5-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.52	Vertical	-38.31	-6.68	-44.99	- 13.00	PASS
		2289.85	V	-49.78	-3.42	-53.20		
		3285.39	V	-49.23	-1.42	-50.65		
		284.89	Horizontal	-35.85	-6.68	-42.53	- 13.00	PASS
		2288.88	H	-43.12	-3.42	-46.54		
		3284.53	H	-47.64	-1.42	-49.06		
	Mid	300.32	Vertical	-38.71	-6.68	-45.39	- 13.00	PASS
		2288.46	V	-48.07	-3.42	-51.49		
		3293.13	V	-44.82	-1.42	-46.24		
		285.22	Horizontal	-32.98	-6.68	-39.66	- 13.00	PASS
		2287.74	H	-47.10	-3.42	-50.52		
		3293.59	H	-45.30	-1.42	-46.72		
	High	287.93	Vertical	-39.90	-6.68	-46.58	- 13.00	PASS
		2298.50	V	-44.59	-3.42	-48.01		
		3288.21	V	-45.95	-1.42	-47.37		
		299.29	Horizontal	-38.05	-6.68	-44.73	- 13.00	PASS
		2288.13	H	-46.93	-3.42	-50.35		
		3296.13	H	-51.87	-1.42	-53.29		
3MHz	Low	298.74	Vertical	-30.91	-6.68	-37.59	- 13.00	PASS
		2289.45	V	-48.03	-3.42	-51.45		
		3295.17	V	-45.56	-1.42	-46.98		
		284.82	Horizontal	-36.19	-6.68	-42.87	- 13.00	PASS
		2292.06	H	-46.98	-3.42	-50.40		
		3297.77	H	-48.10	-1.42	-49.52		
	Mid	296.27	Vertical	-31.22	-6.68	-37.90	- 13.00	PASS
		2298.61	V	-40.36	-3.42	-43.78		
		3293.94	V	-44.20	-1.42	-45.62		
		300.85	Horizontal	-31.65	-6.68	-38.33	- 13.00	PASS
		2291.64	H	-49.51	-3.42	-52.93		
		3283.63	H	-52.12	-1.42	-53.54		
	High	294.51	Vertical	-36.39	-6.68	-43.07	- 13.00	PASS
		2295.92	V	-42.39	-3.42	-45.81		
		3296.46	V	-51.71	-1.42	-53.13		
		286.35	Horizontal	-38.52	-6.68	-45.20	- 13.00	PASS

5MHz	Low	2291.59	H	-47.73	-3.42	-51.15	- 13.00	PASS
		3291.91	H	-52.01	-1.42	-53.43		
		287.73	Vertical	-33.95	-6.68	-40.63		
		2293.72	V	-41.48	-3.42	-44.90		
		3289.63	V	-44.13	-1.42	-45.55		
		284.10	Horizontal	-32.58	-6.68	-39.26		
		2287.61	H	-43.96	-3.42	-47.38		
	Mid	3290.26	H	-47.81	-1.42	-49.23	- 13.00	PASS
		293.79	Vertical	-31.00	-6.68	-37.68		
		2283.50	V	-43.91	-3.42	-47.33		
		3289.45	V	-46.71	-1.42	-48.13		
		288.56	Horizontal	-37.17	-6.68	-43.85		
		2294.35	H	-42.27	-3.42	-45.69		
		3291.14	H	-51.25	-1.42	-52.67		
	High	298.40	Vertical	-33.00	-6.68	-39.68	- 13.00	PASS
		2297.60	V	-44.27	-3.42	-47.69		
		3294.65	V	-49.69	-1.42	-51.11		
		290.83	Horizontal	-38.47	-6.68	-45.15		
		2301.32	H	-50.10	-3.42	-53.52		
		3291.57	H	-49.18	-1.42	-50.60		
	10MHz	294.08	Vertical	-37.23	-6.68	-43.91	- 13.00	PASS
		2300.35	V	-47.24	-3.42	-50.66		
		3291.47	V	-45.82	-1.42	-47.24		
		294.95	Horizontal	-37.25	-6.68	-43.93	- 13.00	PASS
		2300.50	H	-41.31	-3.42	-44.73		
		3294.09	H	-45.63	-1.42	-47.05		
		294.20	Vertical	-36.81	-6.68	-43.49	- 13.00	PASS
		2289.78	V	-44.10	-3.42	-47.52		
		3299.07	V	-48.69	-1.42	-50.11		
		298.29	Horizontal	-30.19	-6.68	-36.87	- 13.00	PASS
		2284.15	H	-47.33	-3.42	-50.75		
		3300.23	H	-52.37	-1.42	-53.79		
	High	284.33	Vertical	-34.15	-6.68	-40.83	- 13.00	PASS
		2285.58	V	-45.79	-3.42	-49.21		
		3294.71	V	-49.69	-1.42	-51.11		
		300.89	Horizontal	-38.41	-6.68	-45.09	- 13.00	PASS
		2286.06	H	-47.68	-3.42	-51.10		
		3284.30	H	-51.85	-1.42	-53.27		

LTE Band 7-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.40	Vertical	-38.26	-6.68	-44.94	- 13.00	PASS
		2289.74	V	-49.78	-3.42	-53.20		
		3285.30	V	-49.36	-1.42	-50.78		
		285.12	Horizontal	-35.81	-6.68	-42.49	- 13.00	PASS
		2288.52	H	-43.11	-3.42	-46.53		
		3284.62	H	-47.79	-1.42	-49.21		
	Mid	300.56	Vertical	-38.71	-6.68	-45.39	- 13.00	PASS
		2288.30	V	-48.07	-3.42	-51.49		
		3292.77	V	-44.87	-1.42	-46.29		
		284.91	Horizontal	-33.03	-6.68	-39.71	- 13.00	PASS
		2287.61	H	-47.17	-3.42	-50.59		
		3293.53	H	-45.31	-1.42	-46.73		
	High	288.21	Vertical	-39.87	-6.68	-46.55	- 13.00	PASS
		2298.33	V	-44.59	-3.42	-48.01		
		3288.42	V	-45.98	-1.42	-47.40		
		299.32	Horizontal	-38.02	-6.68	-44.70	- 13.00	PASS
		2287.97	H	-47.00	-3.42	-50.42		
		3296.23	H	-51.83	-1.42	-53.25		
3MHz	Low	298.46	Vertical	-31.02	-6.68	-37.70	- 13.00	PASS
		2289.18	V	-47.89	-3.42	-51.31		
		3295.39	V	-45.72	-1.42	-47.14		
		284.99	Horizontal	-36.07	-6.68	-42.75	- 13.00	PASS
		2292.06	H	-46.84	-3.42	-50.26		
		3297.77	H	-48.16	-1.42	-49.58		
	Mid	296.04	Vertical	-31.38	-6.68	-38.06	- 13.00	PASS
		2298.54	V	-40.49	-3.42	-43.91		
		3294.08	V	-44.07	-1.42	-45.49		
		300.83	Horizontal	-31.65	-6.68	-38.33	- 13.00	PASS
		2291.75	H	-49.49	-3.42	-52.91		
		3283.19	H	-52.06	-1.42	-53.48		
	High	294.71	Vertical	-36.25	-6.68	-42.93	- 13.00	PASS
		2295.83	V	-42.27	-3.42	-45.69		
		3296.38	V	-51.61	-1.42	-53.03		
		286.27	Horizontal	-38.54	-6.68	-45.22	- 13.00	PASS

5MHz	Low	2291.53	H	-47.81	-3.42	-51.23	- 13.00	PASS
		3291.85	H	-51.85	-1.42	-53.27		
		287.65	Vertical	-33.98	-6.68	-40.66		
		2293.40	V	-41.49	-3.42	-44.91		
		3289.48	V	-44.13	-1.42	-45.55		
		284.41	Horizontal	-32.60	-6.68	-39.28		
		2287.42	H	-43.93	-3.42	-47.35		
	Mid	3290.63	H	-47.70	-1.42	-49.12	- 13.00	PASS
		293.39	Vertical	-31.06	-6.68	-37.74		
		2283.58	V	-43.83	-3.42	-47.25		
		3289.56	V	-46.75	-1.42	-48.17		
		288.39	Horizontal	-37.28	-6.68	-43.96		
		2294.49	H	-42.44	-3.42	-45.86		
		3291.10	H	-51.23	-1.42	-52.65		
	High	298.34	Vertical	-33.16	-6.68	-39.84	- 13.00	PASS
		2297.78	V	-44.17	-3.42	-47.59		
		3294.67	V	-49.69	-1.42	-51.11		
		291.00	Horizontal	-38.40	-6.68	-45.08		
		2301.37	H	-50.07	-3.42	-53.49		
		3291.37	H	-49.25	-1.42	-50.67		
		294.44	Vertical	-37.20	-6.68	-43.88	- 13.00	PASS
10MHz	Low	2300.01	V	-47.26	-3.42	-50.68		
		3291.76	V	-45.96	-1.42	-47.38		
		295.01	Horizontal	-37.31	-6.68	-43.99		
		2300.28	H	-41.21	-3.42	-44.63		
		3293.96	H	-45.72	-1.42	-47.14		
	Mid	294.42	Vertical	-36.74	-6.68	-43.42	- 13.00	PASS
		2289.72	V	-44.05	-3.42	-47.47		
		3299.45	V	-48.70	-1.42	-50.12		
		298.39	Horizontal	-30.32	-6.68	-37.00		
		2284.02	H	-47.39	-3.42	-50.81		
		3299.91	H	-52.36	-1.42	-53.78		
	High	284.02	Vertical	-34.17	-6.68	-40.85	- 13.00	PASS
		2285.25	V	-45.76	-3.42	-49.18		
		3294.55	V	-49.61	-1.42	-51.03		
		300.45	Horizontal	-38.40	-6.68	-45.08		
		2286.25	H	-47.61	-3.42	-51.03		
		3284.17	H	-51.68	-1.42	-53.10		

15MHz	Low	296.84	Vertical	-32.20	-6.68	-38.88	- 13.00	PASS
		2290.57	V	-49.19	-3.42	-52.61		
		3296.25	V	-44.34	-1.42	-45.76		
		282.89	Horizontal	-32.46	-6.68	-39.14	- 13.00	PASS
		2301.48	H	-40.35	-3.42	-43.77		
		3293.12	H	-45.50	-1.42	-46.92		
	Mid	282.61	Vertical	-35.38	-6.68	-42.06	- 13.00	PASS
		2292.99	V	-42.82	-3.42	-46.24		
		3283.29	V	-43.19	-1.42	-44.61		
		298.03	Horizontal	-37.92	-6.68	-44.60	- 13.00	PASS
		2300.60	H	-44.87	-3.42	-48.29		
		3282.70	H	-45.90	-1.42	-47.32		
	High	294.15	Vertical	-33.76	-6.68	-40.44	- 13.00	PASS
		2293.70	V	-47.58	-3.42	-51.00		
		3283.30	V	-43.71	-1.42	-45.13		
		298.42	Horizontal	-34.28	-6.68	-40.96	- 13.00	PASS
		2283.80	H	-41.51	-3.42	-44.93		
		3289.28	H	-52.08	-1.42	-53.50		
20MHz	Low	298.33	Vertical	-33.54	-6.68	-40.22	- 13.00	PASS
		2296.28	V	-41.96	-3.42	-45.38		
		3285.49	V	-46.92	-1.42	-48.34		
		290.64	Horizontal	-37.38	-6.68	-44.06	- 13.00	PASS
		2282.39	H	-43.46	-3.42	-46.88		
		3296.33	H	-49.75	-1.42	-51.17		
	Mid	291.04	Vertical	-34.28	-6.68	-40.96	- 13.00	PASS
		2291.82	V	-49.11	-3.42	-52.53		
		3297.55	V	-48.17	-1.42	-49.59		
		286.59	Horizontal	-32.51	-6.68	-39.19	- 13.00	PASS
		2301.37	H	-40.82	-3.42	-44.24		
		3297.59	H	-47.24	-1.42	-48.66		
	High	282.28	Vertical	-34.33	-6.68	-41.01	- 13.00	PASS
		2286.18	V	-44.21	-3.42	-47.63		
		3287.40	V	-51.61	-1.42	-53.03		
		300.26	Horizontal	-31.11	-6.68	-37.79	- 13.00	PASS
		2285.47	H	-50.06	-3.42	-53.48		
		3283.61	H	-49.37	-1.42	-50.79		

LTE Band 38-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
5MHz	Low	287.86	Vertical	-34.01	-6.68	-40.69	- 13.00	PASS
		2293.60	V	-41.36	-3.42	-44.78		
		3289.73	V	-44.11	-1.42	-45.53		
		284.04	Horizontal	-32.62	-6.68	-39.30	- 13.00	PASS
		2287.87	H	-43.96	-3.42	-47.38		
		3290.30	H	-47.81	-1.42	-49.23		
	Mid	293.57	Vertical	-31.12	-6.68	-37.80	- 13.00	PASS
		2283.12	V	-43.94	-3.42	-47.36		
		3289.61	V	-46.80	-1.42	-48.22		
		288.75	Horizontal	-37.18	-6.68	-43.86	- 13.00	PASS
		2294.60	H	-42.35	-3.42	-45.77		
		3291.11	H	-51.15	-1.42	-52.57		
	High	298.50	Vertical	-33.16	-6.68	-39.84	- 13.00	PASS
		2297.51	V	-44.23	-3.42	-47.65		
		3294.61	V	-49.77	-1.42	-51.19		
		290.84	Horizontal	-38.37	-6.68	-45.05	- 13.00	PASS
		2301.17	H	-50.18	-3.42	-53.60		
		3291.68	H	-49.10	-1.42	-50.52		
10MHz	Low	294.40	Vertical	-37.18	-6.68	-43.86	- 13.00	PASS
		2300.00	V	-47.34	-3.42	-50.76		
		3291.68	V	-45.97	-1.42	-47.39		
		294.92	Horizontal	-37.31	-6.68	-43.99	- 13.00	PASS
		2300.34	H	-41.32	-3.42	-44.74		
		3293.68	H	-45.76	-1.42	-47.18		
	Mid	294.15	Vertical	-36.66	-6.68	-43.34	- 13.00	PASS
		2289.46	V	-44.13	-3.42	-47.55		
		3299.49	V	-48.72	-1.42	-50.14		
		298.54	Horizontal	-30.27	-6.68	-36.95	- 13.00	PASS
		2284.37	H	-47.37	-3.42	-50.79		
		3300.23	H	-52.27	-1.42	-53.69		
	High	284.36	Vertical	-34.15	-6.68	-40.83	- 13.00	PASS
		2285.36	V	-45.77	-3.42	-49.19		
		3294.73	V	-49.75	-1.42	-51.17		
		300.64	Horizontal	-38.25	-6.68	-44.93	- 13.00	PASS

15MHz	Low	2286.41	H	-47.67	-3.42	-51.09	- 13.00	PASS
		3284.16	H	-51.81	-1.42	-53.23		
		297.00	Vertical	-32.28	-6.68	-38.96		
		2290.63	V	-49.26	-3.42	-52.68		
		3296.35	V	-44.20	-1.42	-45.62		
		282.81	Horizontal	-32.30	-6.68	-38.98		
		2301.15	H	-40.27	-3.42	-43.69		
	Mid	3293.25	H	-45.53	-1.42	-46.95	- 13.00	PASS
		282.49	Vertical	-35.56	-6.68	-42.24		
		2293.05	V	-42.84	-3.42	-46.26		
		3282.98	V	-43.22	-1.42	-44.64		
		297.93	Horizontal	-37.93	-6.68	-44.61		
		2300.70	H	-44.72	-3.42	-48.14		
		3282.79	H	-45.86	-1.42	-47.28		
	High	293.92	Vertical	-33.82	-6.68	-40.50	- 13.00	PASS
		2293.46	V	-47.59	-3.42	-51.01		
		3283.65	V	-43.79	-1.42	-45.21		
		298.36	Horizontal	-34.21	-6.68	-40.89		
		2283.81	H	-41.48	-3.42	-44.90		
		3289.17	H	-51.94	-1.42	-53.36		
20MHz	Low	298.22	Vertical	-33.54	-6.68	-40.22	- 13.00	PASS
		2296.12	V	-41.95	-3.42	-45.37		
		3285.77	V	-46.89	-1.42	-48.31		
		290.32	Horizontal	-37.39	-6.68	-44.07		
		2282.43	H	-43.47	-3.42	-46.89		
		3296.22	H	-49.82	-1.42	-51.24		
	Mid	291.13	Vertical	-34.29	-6.68	-40.97	- 13.00	PASS
		2291.91	V	-48.97	-3.42	-52.39		
		3297.38	V	-48.15	-1.42	-49.57		
		286.85	Horizontal	-32.34	-6.68	-39.02		
		2301.14	H	-40.80	-3.42	-44.22		
		3297.94	H	-47.23	-1.42	-48.65		
	High	282.68	Vertical	-34.36	-6.68	-41.04	- 13.00	PASS
		2286.36	V	-44.09	-3.42	-47.51		
		3287.55	V	-51.56	-1.42	-52.98		
		300.14	Horizontal	-31.07	-6.68	-37.75		
		2285.05	H	-49.96	-3.42	-53.38		
		3283.82	H	-49.32	-1.42	-50.74		

LTE Band 41-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.41	Vertical	-38.21	-6.68	-44.89	- 13.00	PASS
		2289.96	V	-49.63	-3.42	-53.05		
		3285.46	V	-49.29	-1.42	-50.71		
		284.77	Horizontal	-35.77	-6.68	-42.45	- 13.00	PASS
		2288.58	H	-43.16	-3.42	-46.58		
		3284.34	H	-47.80	-1.42	-49.22		
	Mid	300.58	Vertical	-38.79	-6.68	-45.47	- 13.00	PASS
		2288.38	V	-48.14	-3.42	-51.56		
		3292.94	V	-44.72	-1.42	-46.14		
		285.16	Horizontal	-33.09	-6.68	-39.77	- 13.00	PASS
		2287.59	H	-47.10	-3.42	-50.52		
		3293.62	H	-45.33	-1.42	-46.75		
	High	288.17	Vertical	-39.93	-6.68	-46.61	- 13.00	PASS
		2298.23	V	-44.39	-3.42	-47.81		
		3288.45	V	-45.91	-1.42	-47.33		
		299.24	Horizontal	-37.94	-6.68	-44.62	- 13.00	PASS
		2288.11	H	-47.01	-3.42	-50.43		
		3295.92	H	-51.82	-1.42	-53.24		
3MHz	Low	298.60	Vertical	-30.98	-6.68	-37.66	- 13.00	PASS
		2289.22	V	-48.04	-3.42	-51.46		
		3295.50	V	-45.72	-1.42	-47.14		
		284.67	Horizontal	-36.16	-6.68	-42.84	- 13.00	PASS
		2291.84	H	-46.99	-3.42	-50.41		
		3297.67	H	-48.17	-1.42	-49.59		
	Mid	296.27	Vertical	-31.34	-6.68	-38.02	- 13.00	PASS
		2298.34	V	-40.38	-3.42	-43.80		
		3294.02	V	-44.18	-1.42	-45.60		
		301.18	Horizontal	-31.67	-6.68	-38.35	- 13.00	PASS
		2291.75	H	-49.45	-3.42	-52.87		
		3283.23	H	-52.13	-1.42	-53.55		
	High	294.48	Vertical	-36.34	-6.68	-43.02	- 13.00	PASS
		2295.72	V	-42.24	-3.42	-45.66		
		3296.25	V	-51.55	-1.42	-52.97		
		286.02	Horizontal	-38.63	-6.68	-45.31	- 13.00	PASS

5MHz	Low	2291.59	H	-47.77	-3.42	-51.19	- 13.00	PASS
		3291.73	H	-51.91	-1.42	-53.33		
		287.97	Vertical	-34.09	-6.68	-40.77		
		2293.72	V	-41.37	-3.42	-44.79		
		3289.88	V	-43.99	-1.42	-45.41		
		284.32	Horizontal	-32.58	-6.68	-39.26		
		2287.86	H	-43.93	-3.42	-47.35		
	Mid	3290.44	H	-47.78	-1.42	-49.20	- 13.00	PASS
		293.82	Vertical	-31.10	-6.68	-37.78		
		2283.44	V	-43.79	-3.42	-47.21		
		3289.37	V	-46.84	-1.42	-48.26		
		288.67	Horizontal	-37.27	-6.68	-43.95		
		2294.33	H	-42.27	-3.42	-45.69		
		3291.25	H	-51.33	-1.42	-52.75		
	High	298.53	Vertical	-32.98	-6.68	-39.66	- 13.00	PASS
		2297.62	V	-44.08	-3.42	-47.50		
		3294.60	V	-49.77	-1.42	-51.19		
		290.90	Horizontal	-38.42	-6.68	-45.10		
		2301.06	H	-50.05	-3.42	-53.47		
		3291.70	H	-49.14	-1.42	-50.56		
10MHz	Low	294.23	Vertical	-37.24	-6.68	-43.92	- 13.00	PASS
		2300.39	V	-47.29	-3.42	-50.71		
		3291.94	V	-45.85	-1.42	-47.27		
		294.95	Horizontal	-37.26	-6.68	-43.94		
		2300.41	H	-41.22	-3.42	-44.64		
		3293.86	H	-45.59	-1.42	-47.01		
	Mid	294.40	Vertical	-36.83	-6.68	-43.51	- 13.00	PASS
		2289.61	V	-44.06	-3.42	-47.48		
		3299.07	V	-48.72	-1.42	-50.14		
		298.30	Horizontal	-30.19	-6.68	-36.87		
		2284.09	H	-47.26	-3.42	-50.68		
		3299.81	H	-52.33	-1.42	-53.75		
	High	284.35	Vertical	-34.20	-6.68	-40.88	- 13.00	PASS
		2285.58	V	-45.68	-3.42	-49.10		
		3294.83	V	-49.64	-1.42	-51.06		
		300.50	Horizontal	-38.30	-6.68	-44.98		
		2286.13	H	-47.54	-3.42	-50.96		
		3284.10	H	-51.77	-1.42	-53.19		

15MHz	Low	296.83	Vertical	-32.32	-6.68	-39.00	- 13.00	PASS
		2290.93	V	-49.24	-3.42	-52.66		
		3295.99	V	-44.18	-1.42	-45.60		
		282.57	Horizontal	-32.32	-6.68	-39.00	- 13.00	PASS
		2301.36	H	-40.21	-3.42	-43.63		
		3292.84	H	-45.53	-1.42	-46.95		
	Mid	282.91	Vertical	-35.47	-6.68	-42.15	- 13.00	PASS
		2293.09	V	-42.75	-3.42	-46.17		
		3283.07	V	-43.36	-1.42	-44.78		
		297.99	Horizontal	-37.92	-6.68	-44.60	- 13.00	PASS
		2300.75	H	-44.85	-3.42	-48.27		
		3283.14	H	-45.93	-1.42	-47.35		
	High	294.06	Vertical	-33.81	-6.68	-40.49	- 13.00	PASS
		2293.48	V	-47.66	-3.42	-51.08		
		3283.41	V	-43.81	-1.42	-45.23		
		298.72	Horizontal	-34.23	-6.68	-40.91	- 13.00	PASS
		2283.59	H	-41.42	-3.42	-44.84		
		3289.33	H	-51.99	-1.42	-53.41		
20MHz	Low	298.23	Vertical	-33.52	-6.68	-40.20	- 13.00	PASS
		2296.34	V	-41.90	-3.42	-45.32		
		3285.85	V	-47.08	-1.42	-48.50		
		290.44	Horizontal	-37.40	-6.68	-44.08	- 13.00	PASS
		2282.16	H	-43.47	-3.42	-46.89		
		3296.67	H	-49.79	-1.42	-51.21		
	Mid	291.05	Vertical	-34.18	-6.68	-40.86	- 13.00	PASS
		2291.57	V	-49.05	-3.42	-52.47		
		3297.71	V	-48.21	-1.42	-49.63		
		287.02	Horizontal	-32.47	-6.68	-39.15	- 13.00	PASS
		2301.41	H	-40.84	-3.42	-44.26		
		3297.93	H	-47.28	-1.42	-48.70		
	High	282.36	Vertical	-34.33	-6.68	-41.01	- 13.00	PASS
		2286.38	V	-44.14	-3.42	-47.56		
		3287.43	V	-51.47	-1.42	-52.89		
		300.06	Horizontal	-31.14	-6.68	-37.82	- 13.00	PASS
		2285.49	H	-49.98	-3.42	-53.40		
		3283.88	H	-49.32	-1.42	-50.74		

LTE Band 66-QPSK								
Bandwidth	Channel	Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
			Polarization	Reading (dBm)	Factor (dB)	Level (dBm)		
1.4MHz	Low	295.32	Vertical	-38.33	-6.68	-45.01	- 13.00	PASS
		2289.94	V	-49.64	-3.42	-53.06		
		3285.35	V	-49.18	-1.42	-50.60		
		284.69	Horizontal	-35.73	-6.68	-42.41	- 13.00	PASS
		2288.70	H	-43.16	-3.42	-46.58		
		3284.32	H	-47.71	-1.42	-49.13		
	Mid	300.65	Vertical	-38.74	-6.68	-45.42	- 13.00	PASS
		2288.14	V	-48.14	-3.42	-51.56		
		3292.75	V	-44.87	-1.42	-46.29		
		284.99	Horizontal	-32.96	-6.68	-39.64	- 13.00	PASS
		2287.67	H	-47.18	-3.42	-50.60		
		3293.36	H	-45.28	-1.42	-46.70		
	High	288.10	Vertical	-39.92	-6.68	-46.60	- 13.00	PASS
		2298.12	V	-44.52	-3.42	-47.94		
		3288.25	V	-45.87	-1.42	-47.29		
		299.25	Horizontal	-38.01	-6.68	-44.69	- 13.00	PASS
		2287.83	H	-46.96	-3.42	-50.38		
		3296.05	H	-51.91	-1.42	-53.33		
3MHz	Low	298.59	Vertical	-31.06	-6.68	-37.74	- 13.00	PASS
		2289.24	V	-47.95	-3.42	-51.37		
		3295.29	V	-45.72	-1.42	-47.14		
		284.81	Horizontal	-36.03	-6.68	-42.71	- 13.00	PASS
		2291.79	H	-46.95	-3.42	-50.37		
		3297.63	H	-48.06	-1.42	-49.48		
	Mid	295.91	Vertical	-31.24	-6.68	-37.92	- 13.00	PASS
		2298.60	V	-40.37	-3.42	-43.79		
		3294.18	V	-44.16	-1.42	-45.58		
		301.10	Horizontal	-31.60	-6.68	-38.28	- 13.00	PASS
		2291.88	H	-49.39	-3.42	-52.81		
		3283.14	H	-52.12	-1.42	-53.54		
	High	294.75	Vertical	-36.42	-6.68	-43.10	- 13.00	PASS
		2295.96	V	-42.39	-3.42	-45.81		
		3296.24	V	-51.69	-1.42	-53.11		
		285.95	Horizontal	-38.61	-6.68	-45.29	- 13.00	PASS

5MHz	Low	2291.53	H	-47.71	-3.42	-51.13	- 13.00	PASS
		3291.58	H	-51.94	-1.42	-53.36		
		287.94	Vertical	-34.02	-6.68	-40.70		
		2293.57	V	-41.40	-3.42	-44.82		
		3289.78	V	-44.06	-1.42	-45.48		
		284.51	Horizontal	-32.72	-6.68	-39.40		
		2287.48	H	-44.11	-3.42	-47.53		
	Mid	3290.33	H	-47.78	-1.42	-49.20	- 13.00	PASS
		293.86	Vertical	-31.11	-6.68	-37.79		
		2283.44	V	-43.95	-3.42	-47.37		
		3289.49	V	-46.73	-1.42	-48.15		
		288.79	Horizontal	-37.22	-6.68	-43.90		
		2294.53	H	-42.43	-3.42	-45.85		
		3291.43	H	-51.15	-1.42	-52.57		
	High	298.36	Vertical	-33.05	-6.68	-39.73	- 13.00	PASS
		2297.52	V	-44.15	-3.42	-47.57		
		3294.73	V	-49.68	-1.42	-51.10		
		290.91	Horizontal	-38.46	-6.68	-45.14		
		2301.12	H	-50.10	-3.42	-53.52		
		3291.33	H	-49.26	-1.42	-50.68		
		294.33	Vertical	-37.25	-6.68	-43.93	- 13.00	PASS
10MHz	Low	2300.32	V	-47.33	-3.42	-50.75		
		3291.62	V	-45.80	-1.42	-47.22		
		294.82	Horizontal	-37.26	-6.68	-43.94		
		2300.41	H	-41.31	-3.42	-44.73		
		3293.99	H	-45.60	-1.42	-47.02		
	Mid	294.33	Vertical	-36.74	-6.68	-43.42	- 13.00	PASS
		2289.65	V	-44.04	-3.42	-47.46		
		3299.11	V	-48.77	-1.42	-50.19		
		298.53	Horizontal	-30.27	-6.68	-36.95		
		2284.29	H	-47.34	-3.42	-50.76		
		3300.13	H	-52.36	-1.42	-53.78		
	High	284.09	Vertical	-34.20	-6.68	-40.88	- 13.00	PASS
		2285.59	V	-45.73	-3.42	-49.15		
		3294.74	V	-49.64	-1.42	-51.06		
		300.52	Horizontal	-38.35	-6.68	-45.03		
		2286.54	H	-47.56	-3.42	-50.98		
		3284.30	H	-51.69	-1.42	-53.11		

15MHz	Low	297.11	Vertical	-32.28	-6.68	-38.96	- 13.00	PASS
		2290.56	V	-49.20	-3.42	-52.62		
		3295.98	V	-44.33	-1.42	-45.75		
		282.61	Horizontal	-32.38	-6.68	-39.06	- 13.00	PASS
		2301.06	H	-40.22	-3.42	-43.64		
		3293.14	H	-45.57	-1.42	-46.99		
	Mid	282.77	Vertical	-35.46	-6.68	-42.14	- 13.00	PASS
		2293.29	V	-42.87	-3.42	-46.29		
		3282.87	V	-43.19	-1.42	-44.61		
		298.01	Horizontal	-37.81	-6.68	-44.49	- 13.00	PASS
		2300.57	H	-44.84	-3.42	-48.26		
		3282.89	H	-45.94	-1.42	-47.36		
	High	293.86	Vertical	-33.79	-6.68	-40.47	- 13.00	PASS
		2293.68	V	-47.69	-3.42	-51.11		
		3283.32	V	-43.84	-1.42	-45.26		
		298.39	Horizontal	-34.25	-6.68	-40.93	- 13.00	PASS
		2283.71	H	-41.36	-3.42	-44.78		
		3289.08	H	-52.06	-1.42	-53.48		
20MHz	Low	298.30	Vertical	-33.65	-6.68	-40.33	- 13.00	PASS
		2296.33	V	-41.86	-3.42	-45.28		
		3285.83	V	-46.89	-1.42	-48.31		
		290.65	Horizontal	-37.54	-6.68	-44.22	- 13.00	PASS
		2282.17	H	-43.34	-3.42	-46.76		
		3296.31	H	-49.82	-1.42	-51.24		
	Mid	291.05	Vertical	-34.12	-6.68	-40.80	- 13.00	PASS
		2291.59	V	-49.02	-3.42	-52.44		
		3297.24	V	-48.18	-1.42	-49.60		
		286.75	Horizontal	-32.52	-6.68	-39.20	- 13.00	PASS
		2301.18	H	-40.67	-3.42	-44.09		
		3297.75	H	-47.29	-1.42	-48.71		
	High	282.39	Vertical	-34.36	-6.68	-41.04	- 13.00	PASS
		2286.23	V	-44.11	-3.42	-47.53		
		3287.31	V	-51.61	-1.42	-53.03		
		300.10	Horizontal	-31.08	-6.68	-37.76	- 13.00	PASS
		2285.43	H	-50.06	-3.42	-53.48		
		3283.65	H	-49.24	-1.42	-50.66		

4.5 Out of Band Emission

Test Requirement:	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)
Test Limit:	(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations; (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation. (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. (h) (1) $10 (P)$ dB. (2) paragraph (h)(1) of this section: (i) Operations in the 2180-2200 MHz band are subject to the out-of-band emission requirements set forth in § 27.1134 for the protection of federal government operations operating in the 2200-2290 MHz band. (ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB. (iii) For operations in the 1915-1920 MHz band, the power of any emission between 1930-1995 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB.

	(iv) For operations in the 1995-2000 MHz band, the power of any emission between 2005-2020 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10}(P)$ dB.
Test Method:	47 CFR Part 24.238(b) ANSI C63.26-2015, Section 5.7.3
Procedure:	Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (a) Set the spectrum analyzer center frequency to the block, band, or channel edge frequency. b) Set the span wide enough to capture the fundamental emission closest to the authorized block or band edge, and to include all modulation products that spill into the immediately adjacent frequency band. In some cases, it may be possible to set the center frequency and span so as to encompass the fundamental emission and the unwanted out-of-band (band-edge) emissions on either side of the authorized block, band, or channel. This can be accomplished with a single (slow) sweep, if adequate overload protection and sufficient dynamic range can be maintained. c) Set the number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. d) Sweep time should be auto for peak detection. For rms detection the sweep time should be set as follows: 1) If the device can be configured to transmit continuously (duty cycle $\geq 98\%$), set the (sweep time) $> (\text{number of points in sweep}) \times (\text{symbol period})$ (e.g., by a factor of $10 \times \text{symbol period} \times \text{number of points}$). Increasing the sweep time (i.e., slowing the sweep speed) will allow for averaging over multiple symbols 2) If the device cannot transmit continuously (duty cycle $< 98\%$), a gated sweep shall be used when possible (i.e., gate triggered such that the analyzer only sweeps when the device is transmitting at full power), set the sweep time $> (\text{number of points in sweep}) \times (\text{symbol period})$ but the sweep time shall always be maintained at a value that is less than or equal to the minimum transmission time. 3) If the device cannot be configured to transmit continuously (duty cycle $< 98\%$) and a freerunning sweep must be used, set the sweep time so that the averaging is performed over multiple on/off cycles by setting the sweep time $> (\text{number of points in sweep}) \times (\text{transmitter period})$ (i.e., the transmit on-time + the off-time). The spectrum analyzer readings shall subsequently be corrected by $[10 \log (1/\text{duty cycle})]$. This assumes that the transmission period and duty cycle is relatively constant (duty cycle variation $\leq \pm 2\%$). 4) If the device cannot be configured to transmit continuously and a free-running

sweep must be used, and if the transmissions exhibit a non-constant duty cycle (duty cycle variations $> \pm 2\%$), set the sweep time so that the averaging is performed over the on-period by setting the sweep time $> (\text{symbol period}) \times (\text{number of points})$, while also maintaining the sweep time $< (\text{transmitter on-time})$. The trace mode shall be set to max hold, since not every display point will be averaged only over just the on-time. Thus, multiple sweeps (e.g., 100) in maximum hold are necessary to ensure that the maximum power is measured.


e) The test report shall include the plots of the measuring instrument display and the measured data.

f) See Annex I for example emission mask plots.

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	51 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.

4.6 Field Strength of Radiated Emission

Test Requirement:	47 CFR Part 2.1051, Part 27.53(c)(1)(2)(3)(4), Part 27.53(f) 47 CFR Part 2.1051, Part 27.53(g) 47 CFR Part 2.1051, Part 27.53(h)(1)(2)
Test Limit:	(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB; (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations; (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation. (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. (h) (1) $10 (P)$ dB. (2) paragraph (h)(1) of this section: (i) Operations in the 2180-2200 MHz band are subject to the out-of-band emission requirements set forth in § 27.1134 for the protection of federal government operations operating in the 2200-2290 MHz band. (ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB. (iii) For operations in the 1915-1920 MHz band, the power of any emission between 1930-1995 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10} (P)$ dB.

	(iv) For operations in the 1995-2000 MHz band, the power of any emission between 2005-2020 MHz shall be attenuated below the transmitter power (P) in watts by at least $70 + 10 \log_{10}(P)$ dB.
Test Method:	ANSI C63.26-2015, Section 5.5.3
Procedure:	a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency. b) Each emission under consideration shall be evaluated: 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height. 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position. 3) Return the turntable to the azimuth where the highest emission amplitude level was observed. 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude. 5) Record the measured emission amplitude level and frequency using the appropriate RBW. c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude. d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the Passial EUT measurement. e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna. f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor. g) For each emission that was detected and measured in the Passial test [i.e., in step b) and step c)]: 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude. 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c). 3) Record the output power level of the signal generator when equivalence is

achieved in step 2).
h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where

P_e	= equivalent emission power in dBm
P_s	= source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.

j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$. If necessary, the antenna gain can be calculated from calibrated antenna factor information

k) Provide the complete measurement results as a part of the test report.

4.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	49 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.6.2 Test Data:

Please Refer to Appendix for Details.

4.7 Frequency Stability

Test Requirement:	47 CFR Part 2.1055, Part 27.54
Test Limit:	The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
Test Method:	ANSI C63.26-2015, Section 5.6
Procedure:	Frequency stability over variations in temperature: a) Supply the EUT with a nominal 60 Hz ac voltage, dc voltage, or install a new or fully charged battery in the EUT. b) If possible a dummy load should be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, the EUT should be placed in the center of the chamber with the antenna adjusted to the shortest length possible. c) Turn on the EUT, and tune it to the center frequency of the operating band. d) Couple the transmitter output to the measuring instrument through a suitable attenuator and coaxial cable. If connection to the EUT output is not possible, make the measurement by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away). NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory authority is the recommended measuring instrument. e) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT). Adjust the detector bandwidth and span settings to achieve a resolution capable of accurate frequency measurements over the applicable frequency stability limits. f) Turn the EUT off, and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit. g) Set the temperature control on the chamber to the highest temperature specified in the regulatory requirements for the type of device, and allow the oscillator heater and the chamber temperature to stabilize. Unless otherwise instructed by the regulatory authority, this temperature should be 50 °C. h) While maintaining a constant temperature inside the environmental chamber, turn on the EUT and allow sufficient time for the EUT temperature to stabilize. i) Measure the frequency. j) Switch off the EUT, but do not switch off the oscillator heater. k) Lower the chamber temperature to the next level that is required by the standard and allow the temperature inside the chamber to stabilize. Unless otherwise instructed by the regulators, this temperature step should be 10 °C. l) Repeat step h) through step k) down to the lowest specified temperature. Unless otherwise instructed by the regulators, this temperature should be -30 °C. When the frequency stability limit is stated as being sufficient such that the fundamental emissions

stay within the authorized bands of operation, a reference point shall be established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as fL and fH respectively. The worst-case frequency offset determined in the above methods shall be added or subtracted from the values of fL and fH and the resulting frequencies must remain within the band.

m) The following additional information is required for equipment incorporating heater type crystal oscillators to be used in mobile stations except for battery powered, hand carried, and portable equipment having mean output power lower than the threshold specified.

1) Measurement data showing variation in transmitter output frequency from a cold start and the elapsed time necessary for the frequency to stabilize within the applicable tolerance. Tests shall be made after temperature stabilization at each of the ambient temperature levels required by the standard.

2) Beginning at each temperature level specified, the frequency shall be measured within 60 s after application of primary power to the transmitter and at intervals of no more than 60 s thereafter until 10 min have elapsed or until sufficient measurements are obtained to indicate clearly that the frequency has stabilized within the applicable tolerance, whichever time period is greater.

3) The elapsed time necessary for the frequency to stabilize within the applicable tolerance from each beginning temperature level as determined from the tests specified in this paragraph shall be specified in the instruction book for the transmitter furnished to the user.

4) When it is impracticable to subject the complete transmitter to this test because of its physical dimensions or power rating, only its frequency determining and stabilizing portions need be tested.

Frequency stability when varying supply voltage:

a) Couple the transmitter output to the measuring instrument through a suitable attenuator and coaxial cable. If connection to the EUT output is not possible make the measurement by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away)


b) Supply the EUT with nominal ac or dc voltage. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

- c) Turn on the EUT, and couple its output to a frequency counter or other frequency-measuring instrument.
- d) Tune the EUT to the center frequency of the operating band. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument, but is strong enough to allow measurement of the operating or fundamental frequency of the EUT). Adjust the detector bandwidth and span settings to achieve a resolution capable of accurate frequency measurements over the applicable frequency stability limits.
- NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory authority is the recommended measuring instrument.
- e) Measure the frequency.
- f) Unless otherwise specified, vary primary supply voltage from 85% to 115% of the nominal value for other than hand carried battery equipment.
- g) For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- h) Repeat the frequency measurement.
- NOTE—For band-edge compliance, it can be required to make these measurements at the low and high channel of the operating band.

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	49 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:	TM1, TM2, TM3, TM4, TM5, TM6				
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6				

4.7.2 Test Setup Diagram:





4.7.3 Test Data:

Please Refer to Appendix for Details.

5 TEST SETUP PHOTOS

Spurious Unwanted Emission



6 PHOTOS OF THE EUT

Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

***** End of Report *****