



FCC Test Report

Report No: FCS202607267W01

Issued for

Applicant:	Shenzhen Anyue Acousto-Optic Intelligent Technology Co., Ltd.
Address:	No. 112, Liyuan Street, Fenghuang Community, Pinghu Subdistrict, Longgang District, Shenzhen City
Product Name:	EDC Sleep Aid Speaker
Brand Name:	N/A
Model Name:	AY-05
Series Model:	N/A
FCC ID:	2BXMK-AY-05
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.FCS-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name.....: Shenzhen Anyue Acousto-Optic Intelligent Technology Co., Ltd.

Address.....: No. 112, Liyuan Street, Fenghuang Community, Pinghu Subdistrict, Longgang District, Shenzhen City

Manufacture's Name.....: Shenzhen Anyue Acousto-Optic Intelligent Technology Co., Ltd.

Address.....: No. 112, Liyuan Street, Fenghuang Community, Pinghu Subdistrict, Longgang District, Shenzhen City

Product Description

Product Name.....: EDC Sleep Aid Speaker

Brand Name.....: N/A

Model Name.....: AY-05

Series Model.....: See the first page of the report

Test Standards.....: FCC Rules and Regulations Part 15 Subpart C, Section 247

Test Procedure.....: ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document.

Date of Test.....:

Date (s) of performance of tests.: July. 20, 2026 ~Aug. 26, 2026

Date of Issue.....: Aug. 27, 2026

Test Result.....: Pass

Tested by :



(orange OuYang)

Reviewed by :



(Jayden)

Approved by :



(Jack Wang)

Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.4 EQUIPMENTS LIST	12
3. 20 DB BANDWIDTH	13
3.1 Limit	13
3.2 Test Procedure	13
3.3 Test setup	14
3.4 Test results	14
3.5 Original Test Data	15
4. CONDUCTED OUTPUT POWER	18
4.1 LIMIT	18
4.2 TEST SETUP	18
4.3 TEST RESULTS	18
5 NUMBER OF HOPPING CHANNEL	19
5.1 LIMIT	19
5.2 TEST PROCEDURE	19
5.3 TEST SETUP	19
5.4 EUT OPERATION CONDITIONS	19
5.5 TEST RESULTS	20
6. BAND EDGE AND SPURIOUS(CONDUCTED)	21
6.1 LIMIT	21
6.2 TEST PROCEDURE	21
6.3 TEST SETUP	21
6.4 TEST RESULTS	22
6.5 Original test data	22
7. RADIATED EMISSION MEASUREMENT	28
7.1 RADIATED EMISSION LIMITS	28

Table of Contents	Page
7.2 TEST PROCEDURE	29
7.3 TESTSETUP	30
7.4. TEST RESULTS	32
7.5 (30MHZ-1000MHZ)	33
7.6 ABOVE 1GHZ	35
7.7 RADIATED BAND EDGE DATA	39
8. AVERAGE TIME OF OCCUPANCY	41
8.1 LIMIT	41
8.2 TEST PROCEDURE	41
8.3 TEST SETUP	41
8.4 TEST RESULTS	42
8.5 ORIGINAL TEST DATA	42
9. HOPPING CHANNEL SEPARATION MEASUREMEN	43
9.1 LIMIT	43
9.2 TEST PROCEDURE	43
9.3 TEST SETUP	43
9.4 EUT OPERATION CONDITIONS	43
9.5 TEST RESULTS	44
10 CONDUCTED EMISSION MEASUREMENT	45
10.1 LIMIT	45
10.2 TEST PROCEDURE	45
10.3 TEST SETUP	46
10.4 TEST RESULTS	47
11. ANTENNA REQUIREMENT	49
11.1 STANDARD REQUIREMENT	49
11.2 RESULT	49

Revision History

Rev.	Issue Date	Effect Page	Contents
00	Aug. 27, 2026	N/A	N/A

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	PASS	--
15.247 (b)(1)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247(a)(1)(i)	Number of Hopping Frequency	PASS	--
15.247(a)(1)(i)	Dwell Time	PASS	--
15.247(a)(1)	20dB Bandwidth 99% Bandwidth	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) All tests are according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
Laboray Accreditations	
FCC Test Firm Registration Number: 514908 CNAS Number: L15566 Designation number: CN0127 A2LA accreditation number: 5545.01 ISED Number: 25801	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.71 \text{ dB}$
2	Unwanted Emissions, conducted	$\pm 2.988 \text{ dB}$
3	Conducted Emission (9KHz-150KHz)	$\pm 4.13 \text{ dB}$
4	All emissions radiated (9KHz -30MHz)	$\pm 3.1 \text{ dB}$
5	Conducted Emission (150KHz-30MHz)	$\pm 4.74 \text{ dB}$
6	All emissions,radiated(<1G) 30MHz-1000MHz	$\pm 5.2 \text{ dB}$
7	All emissions,radiated 1GHz -18GHz	$\pm 4.66 \text{ dB}$
8	All emissions,radiated 18GHz -40GHz	$\pm 4.31 \text{ dB}$
9	Occupied bandwidth	$\pm 0.3 \text{ dB}$
10	Dwell Time	$\pm 0.24 \text{ ms}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	EDC Sleep Aid Speaker
Trade Name	N/A
Model Name	AY-05
Series Model	See the first page of the report
Model Difference	N/A
Channel List	Please refer to the Note 2.
Operation frequency	2402MHz-2480MHz
Modulation:	GFSK
Channel number	79 CH
Transmitter rate:	1MHz
Power Supply	Input:100-230V Output:5V
Battery	DC 3.7V,300mAh
Report number	FCS202607267W01
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

3. Table for Filed Antenna


Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB antenna	N/A	-0.58	N/A

2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test

Mode 1:



Test software:

FrequencyTool_v0.3.2

Power:default

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

No.	Test model descrption
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Hopping GFSK

Note:

1. All the test modes can be supply by adapter, only the result of the worst case recorded in the report.

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Adapter	Xiaomi	HW-050450C00	N/A	N/A
C-1	USB Cable	Xiaomi	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2026.08.25	2027.08.24
Signal Analyzer	R&S	FSV40-N	FCS-E012	2026.08.25	2027.08.24
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2026.08.25	2027.08.24
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2026.08.25	2027.08.24
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2026.08.25	2027.08.24
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2026.08.25	2027.08.24
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2026.08.25	2027.08.24
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2026.08.25	2027.08.24
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2026.08.25	2027.08.24
Temperature & Humidity	HTC-1	victor	FCS-E005	2026.08.25	2027.08.24
Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2026.08.25	2027.08.24
LISN	R&S	ENV216	FCS-E007	2026.08.25	2027.08.24
LISN	ETS	3810/2NM	FCS-E009	2026.08.25	2027.08.24
Temperature & Humidity	HTC-1	victor	FCS-E008	2026.08.25	2027.08.24
Testing Software	EZ-EMC(Ver.EMC-CON 3A1.1)				

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
MXA SIGNAL Analyzer	Keysight	N9020A	FCS-E015	2026.08.25	2027.08.24
Spectrum Analyzer	Agilent	E4447A	MY50180039	2026.08.25	2027.08.24
Spectrum Analyzer	R&S	FSV-40	101499	2026.08.25	2027.08.24
Attenuator	Talent Microwave	TA10A0-S-26.5	FCS-E026	2026.08.25	2027.08.24
Cable	Woke	RWP50-402-SM SM-1M	FCS-E025	2026.08.25	2027.08.24
Power Sensor	Agilent	UX2021XA	FCS-E021	2026.08.25	2027.08.24

Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)
------------------	----------------------------

3. 20 DB BANDWIDTH

3.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247a(1)	20dB bandwidth	N/A	2400-2483.5

3.2 Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 20 dB Bandwidth :30KHz For 99% Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 20dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Bandwidth : approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto

- (1) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
- (2) Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- (3) Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

3.3 Test setup




3.4 Test results


20BW						
Condition	Mode	Frequency(MHz)	99%OBW(MHz)	20BW(MHz)	Frequency Range(MHz)	Result
NVNT	1DH1	2402	0.88675	0.934	2400-2483.5	Pass
NVNT	1DH1	2441	0.90220	1.022	2400-2483.5	Pass
NVNT	1DH1	2480	0.93447	1.034	2400-2483.5	Pass

3.5 Original Test Data


20BW,1DH1,LOWEST




20BW,1DH1,MIDDLE




20BW,1DH1,HIGHEST




99%OBW,1DH1,LOWEST



99%OBW,1DH1,MIDDLE



99%OBW,1DH1,HIGHEST




4. CONDUCTED OUTPUT POWER

4.1 LIMIT

FCC Part 15 Subpart C			
Section	Test Item	Limit	Frequency Range
15.247(b)(1)	Peak output power	Power <21dBm	2400-2483.5

- 1.Connect each EUT's antenna output to power sensor by RF cable and attenuator
- 2.Measure the PK output power of each antenna port by power sensor.

4.2 TEST SETUP



4.3 TEST RESULTS

TestMode	Channel (MHz)	Result (dBm)	Limit (dBm)	Verdict
Lowest	2402MHz	-13.07	21	Pass
Middle	2441MHz	-12.70	21	Pass
Highest	2480MHz	-13.74	21	Pass

5 NUMBER OF HOPPING CHANNEL

5.1 LIMIT

FCC Part 15.247,Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii) RSS-247	Number of Hopping Channel	>15	2400-2483.5	PASS

5.2 TEST PROCEDURE

a The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.

b Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto

5.3 TEST SETUP




5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.5 TEST RESULTS

Temperature:	24.5 °C	Relative Humidity:	60%
Test Mode:	Hopping Mode -GFSK Mode	Test Voltage:	DC 5V by Adapter

Number_Of_Hopping_Frequency					
Condition	Mode	Hopping Number	Limit	Frequency Range(MHz)	Results
NVNT	GFSK	79	>15	2400-2483.5	Pass



6. BAND EDGE AND SPURIOUS(CONDUCTED)

6.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

6.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


6.3 TEST SETUP




6.4 TEST RESULTS

Eut set mode	CH or Frequency	Result
GFSK	CH1	Pass
	CH39	Pass
	CH79	Pass


6.5 Original test data




BAND_EDGE_EMISSION,1DH1,MIDDLE




BAND_EDGE_EMISSION,1DH1,HIGHEST




HOPPING_BAND_EDGE_EMISSION,1DH1



HOPPING_BAND_EDGE_EMISSION,1DH1,LEFT




HOPPING_BAND_EDGE_EMISSION,1DH1,RIGHT




Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	GFSK Mode	Test Voltage:	DC 5V by Adapter


Spurious emissions



MIDDLE CHANNEL 30MHZ-25GHZ



HIGHEST CHANNEL 30MHZ-25GHZ



7. RADIATED EMISSION MEASUREMENT

7.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 below has to be followed LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

7.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

7.3 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.4. TEST RESULTS

(9KHz-30MHz)

Temperature:	23.7°C	Relative Humidity:	61%
Test Voltage:	DC 5V by Adapter	Test Mode:	GFSK(worst mode)

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


7.5 (30MHZ-1000MHZ)

Temperature:	24.6℃	Relative Humidity:	54%
Test Voltage:	DC 3.7V from battery	Phase:	Horizontal
Test Mode:	Mode 1		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.0783	27.44	-11.73	15.71	40.00	-24.29	QP
2	73.6170	26.98	-15.69	11.29	40.00	-28.71	QP
3	140.8351	25.63	-12.10	13.53	43.50	-29.97	QP
4	285.9778	26.55	-12.03	14.52	46.00	-31.48	QP
5	504.7062	26.75	-6.80	19.95	46.00	-26.05	QP
6	952.0937	27.98	0.37	28.35	46.00	-17.65	QP

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit




Temperature:	24.6℃	Relative Humidity:	54%
Test Voltage:	DC 3.7V from battery	Phase:	Vertical
Test Mode:	Mode 1		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9791	26.73	-12.30	14.43	40.00	-25.57	QP
2	63.5356	27.44	-13.68	13.76	40.00	-26.24	QP
3	129.9226	27.56	-13.05	14.51	43.50	-28.99	QP
4	274.1939	27.34	-12.37	14.97	46.00	-31.03	QP
5	494.1984	26.62	-7.05	19.57	46.00	-26.43	QP
6	945.4399	27.00	0.36	27.36	46.00	-18.64	QP

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit



7.6 ABOVE 1GHZ

Temperature:	24.6 °C	Relative Humidity:	60%
Test Mode:	Low CH (GFSK)	Test Voltage:	DC 3.7V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	66.06	32.01	5.77	43.81	60.03	74	-13.97	Vertical
7206	56.20	35.19	6.43	42.55	55.27	74	-18.73	Vertical
9608	46.60	37.32	7.27	41.74	49.45	74	-24.55	Vertical
12010	39.84	38.10	8.56	40.79	45.71	74	-28.29	Vertical
14412	36.42	36.77	9.02	39.36	42.85	74	-31.15	Vertical
16814	*					74		Vertical
4804	67.95	32.01	5.77	43.81	61.92	74	-12.08	Horizontal
7206	55.62	35.19	6.43	42.55	54.69	74	-19.31	Horizontal
9608	47.58	37.32	7.27	41.74	50.43	74	-23.57	Horizontal
12010	40.64	38.10	8.56	40.79	46.51	74	-27.49	Horizontal
14412	37.39	36.77	9.02	39.36	43.82	74	-30.18	Horizontal
16814	*					74		Horizontal

Avg

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	58.24	32.01	5.77	43.81	52.21	54	-1.79	Vertical
7206	48.69	35.19	6.43	42.55	47.76	54	-6.24	Vertical
9608	38.68	37.32	7.27	41.74	41.53	54	-12.47	Vertical
12010	31.32	38.10	8.56	40.79	37.19	54	-16.81	Vertical
14412	28.14	36.77	9.02	39.36	34.57	54	-19.43	Vertical
16814	*					54		Vertical
4804	57.31	32.01	5.77	43.81	51.28	54	-2.72	Horizontal
7206	48.85	35.19	6.43	42.55	47.92	54	-6.08	Horizontal
9608	40.50	37.32	7.27	41.74	43.35	54	-10.65	Horizontal
12010	33.25	38.10	8.56	40.79	39.12	54	-14.88	Horizontal
14412	29.59	36.77	9.02	39.36	36.02	54	-17.98	Horizontal
16814	*					54		Horizontal

Temperature:	24.5 °C	Relative Humidity:	60%
Test Mode:	Middle CH (GFSK)	Test Voltage:	DC 3.7V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4882	66.42	32.16	5.82	43.69	60.71	74	-13.29	Vertical
7323	55.98	35.39	6.49	42.41	55.45	74	-18.55	Vertical
9764	48.27	37.40	7.35	41.64	51.38	74	-22.62	Vertical
12205	40.70	38.72	8.55	40.68	47.29	74	-26.71	Vertical
14646	37.41	36.99	9.14	39.46	44.08	74	-29.92	Vertical
17087	*					74		Vertical
4882	67.12	32.16	5.82	43.69	61.41	74	-12.59	Horizontal
7323	57.65	35.39	6.49	42.41	57.12	74	-16.88	Horizontal
9764	48.98	37.40	7.35	41.64	52.09	74	-21.91	Horizontal
12205	41.60	38.72	8.55	40.68	48.19	74	-25.81	Horizontal
14646	39.16	36.99	9.14	39.46	45.83	74	-28.17	Horizontal
17087	*					74		Horizontal

Avg

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4882	58.03	32.16	5.82	43.69	52.32	54	-1.68	Vertical
7323	47.56	35.39	6.49	42.41	47.03	54	-6.97	Vertical
9764	40.51	37.40	7.35	41.64	43.62	54	-10.38	Vertical
12205	32.94	38.72	8.55	40.68	39.53	54	-14.47	Vertical
14646	30.19	36.99	9.14	39.46	36.86	54	-17.14	Vertical
17087	*					54		Vertical
4882	57.10	32.16	5.82	43.69	51.39	54	-2.61	Horizontal
7323	50.22	35.39	6.49	42.41	49.69	54	-4.31	Horizontal
9764	42.43	37.40	7.35	41.64	45.54	54	-8.46	Horizontal
12205	34.77	38.72	8.55	40.68	41.36	54	-12.64	Horizontal
14646	30.51	36.99	9.14	39.46	37.18	54	-16.82	Horizontal
17087	*					54		Horizontal

Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	High CH (GFSK)	Test Voltage:	DC 3.7V from battery

Peak

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960	66.37	32.74	5.87	43.56	61.42	74	-12.58	Vertical
7440	54.96	36.40	6.76	41.91	56.21	74	-17.79	Vertical
9920	50.16	37.46	7.43	41.55	53.50	74	-20.50	Vertical
12400	42.33	38.90	8.54	40.56	49.21	74	-24.79	Vertical
14880	36.60	38.38	9.30	39.55	44.73	74	-29.27	Vertical
17360	*					74		Vertical
4960	67.01	32.74	5.87	43.56	62.06	74	-11.94	Horizontal
7440	54.70	36.40	6.76	41.91	55.95	74	-18.05	Horizontal
9920	48.34	37.46	7.43	41.55	51.68	74	-22.32	Horizontal
12400	41.04	38.90	8.54	40.56	47.92	74	-26.08	Horizontal
14880	34.46	38.38	9.30	39.55	42.59	74	-31.41	Horizontal
17360	*					74		Horizontal

Avg

Frequency (MHz)	Reading (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4960	66.37	32.74	5.87	43.56	61.42	74	-12.58	Vertical
7440	54.96	36.40	6.76	41.91	56.21	74	-17.79	Vertical
9920	50.16	37.46	7.43	41.55	53.50	74	-20.50	Vertical
12400	42.33	38.90	8.54	40.56	49.21	74	-24.79	Vertical
14880	36.60	38.38	9.30	39.55	44.73	74	-29.27	Vertical
17360	*					74		Vertical
4960	67.01	32.74	5.87	43.56	62.06	74	-11.94	Horizontal
7440	54.70	36.40	6.76	41.91	55.95	74	-18.05	Horizontal
9920	48.34	37.46	7.43	41.55	51.68	74	-22.32	Horizontal
12400	41.04	38.90	8.54	40.56	47.92	74	-26.08	Horizontal
14880	34.46	38.38	9.30	39.55	42.59	74	-31.41	Horizontal
17360	*					74		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. "**", means this data is the too weak instrument of signal is unable to test.

7.7 RADIATED BAND EDGE DATA

Low CH (GFSK)

Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390	72.06	27.14	3.79	47.72	55.27	74	-18.73	Horizontal
2400	77.14	27.10	3.80	47.70	60.34	74	-13.66	Horizontal
2390	74.40	27.14	3.79	47.72	57.61	74	-16.39	Vertical
2400	76.27	27.10	3.80	47.70	59.47	74	-14.53	Vertical

Avg

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390	62.52	27.14	3.79	47.72	45.73	54	-8.27	Horizontal
2400	66.28	27.10	3.80	47.70	49.48	54	-4.52	Horizontal
2390	63.89	27.14	3.79	47.72	47.10	54	-6.90	Vertical
2400	67.51	27.10	3.80	47.70	50.71	54	-3.29	Vertical

High CH(GFSK)
Peak

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	66.91	27.60	3.89	47.57	50.83	74	-23.17	Horizontal
2500	58.37	27.70	3.91	47.55	42.43	74	-31.57	Horizontal
2483.5	67.13	27.60	3.89	47.57	51.05	74	-22.95	Vertical
2500	60.28	27.70	3.91	47.55	44.34	74	-29.66	Vertical

Avg

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	56.36	27.60	3.89	47.57	40.28	54	-13.72	Horizontal
2500	51.42	27.70	3.91	47.55	35.48	54	-18.52	Horizontal
2483.5	57.65	27.60	3.89	47.57	41.57	54	-12.43	Vertical
2500	50.85	27.70	3.91	47.55	34.91	54	-19.09	Vertical

Remark.

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor
- 2.The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.
- 3.All restriction band have been tested, and only the worst case is shown in report

8. AVERAGE TIME OF OCCUPANCY


8.1 LIMIT

FCC Part 15.247, Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Average Time of Occupancy	0.4 sec	2400-2483.5

8.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW = 1MHz/VBW = 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- The number of pulses in the observation period of 31.6 seconds is 134(DH5).
- To the number of pulses in the observation period of 31.6 seconds is 231(DH3).
- To the number of pulses in the observation period of 31.6 seconds is 320(DH1).

8.3 TEST SETUP



8.4 TEST RESULTS

AVERAGE TIME OF OCCUPANCY							
CONDITION	MODE	FREQUENCY (MHZ)	PULSE TIME (MS)	AVERAGE TIME OF OCCUPANCY (MS)	LIMIT (MS)	BURST NUMBER	RESULTS
NVNT	1DH1	2402	0.4080	130.56	400	320	PASS
NVNT	1DH3	2402	1.6667	358.3405	400	215	PASS
NVNT	1DH5	2402	2.92	391.28	400	134	PASS
NVNT	1DH1	2441	0.4080	112.608	400	276	PASS
NVNT	1DH3	2441	1.6697	385.7007	400	231	PASS
NVNT	1DH5	2441	2.92	347.48	400	119	PASS
NVNT	1DH1	2480	0.4091	119.8663	400	293	PASS
NVNT	1DH3	2480	1.6697	370.6734	400	222	PASS
NVNT	1DH5	2480	2.916	320.76	400	110	PASS

8.5 ORIGINAL TEST DATA

For the measurement records, refer to the Annex I.

9. HOPPING CHANNEL SEPARATION MEASUREMENT

9.1 LIMIT


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

9.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement

9.3 TEST SETUP




9.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

9.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	GFSK Mode	Test Voltage:	DC 3.7V from battery

Modulation	Test Mode	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
GFSK	1DH1	2402	1.002	> 0.62	Pass
	1DH1	2441	1.174	> 0.68	Pass
	1DH1	2480	1.002	> 0.69	Pass



10 CONDUCTED EMISSION MEASUREMENT

10.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (4) The tighter limit applies at the band edges.
- (5) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


10.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.


10.3 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


10.4 TEST RESULTS

Temperature:	25℃	Relative Humidity:	50%
Test Mode:	GFSK(L)	Test Voltage:	AC 120/60Hz
Result:	L	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1815	32.50	9.92	42.42	64.42	-22.00	QP
2	0.1815	24.80	9.92	34.72	54.42	-19.70	AVG
3	0.2355	31.21	9.89	41.10	62.25	-21.15	QP
4	0.2355	20.81	9.89	30.70	52.25	-21.55	AVG
5	0.3576	40.53	9.89	50.42	58.78	-8.36	QP
6	0.3576	29.52	9.89	39.41	48.78	-9.37	AVG
7	0.4155	41.95	9.90	51.85	57.54	-5.69	QP
8	0.4155	29.41	9.90	39.31	47.54	-8.23	AVG
9	0.7214	37.39	9.88	47.27	56.00	-8.73	QP
10	0.7214	21.19	9.88	31.07	46.00	-14.93	AVG
11	1.0500	35.78	9.99	45.77	56.00	-10.23	QP
12	1.0500	18.12	9.99	28.11	46.00	-17.89	AVG

Temperature:	25°C	Relative Humidity:	50%
Test Mode:	GFSK(L)	Test Voltage:	DC 5V by adapter
Result:	N	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1815	33.72	9.85	43.57	64.42	-20.85	QP
2	0.1815	28.05	9.85	37.90	54.42	-16.52	AVG
3	0.2445	32.66	9.84	42.50	61.94	-19.44	QP
4	0.2445	24.67	9.84	34.51	51.94	-17.43	AVG
5	0.3704	44.13	9.89	54.02	58.49	-4.47	QP
6	0.3704	33.26	9.89	43.15	48.49	-5.34	AVG
7	0.4155	41.72	9.90	51.62	57.54	-5.92	QP
8	0.4155	30.69	9.90	40.59	47.54	-6.95	AVG
9	0.7439	39.05	9.96	49.01	56.00	-6.99	QP
10	0.7439	24.22	9.96	34.18	46.00	-11.82	AVG
11	1.2119	36.83	9.98	46.81	56.00	-9.19	QP
12	1.2119	21.80	9.98	31.78	46.00	-14.22	AVG

Remark:

1. All readings are Quasi-Peak and Average values

11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 RESULT

The antennas used for this product are PCB antenna and no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is -0.58dBi.

※※※※※END OF THE REPORT※※※※※