

# TEST REPORT

Applicant : Albert Kerbl GmbH  
Address : Felizenzell 9, 84428 Buchbach, Germany  
Manufacturer : Albert Kerbl GmbH  
Address : Felizenzell 9, 84428 Buchbach, Germany  
Product Name : Automatic Chicken Door Duo Smart Control unit  
Model Number : 70521, 70531, 70531-ROSE, 70533  
Trademark : KERBL  
FCC ID : 2BXNK-70521  
Test Date : Feb. 25, 2026 to Mar. 06, 2026  
Date of Report : Mar. 06, 2026

Test Result : This device described above has been tested by NTT, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.


## Test Procedure Used:

Standards : FCC CFR Title 47 Part 15 Subpart C Section 15.247  
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024  
KDB 558074 D01 15.247 Meas Guidance v05r02

Prepared by(Test Engineer):  
Zhao Di



Approved(Manager):  
Ken Wu



Approved(Manager):  
Abel Yu



**TABLE OF CONTENT**

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>1. General Information .....</b>                             | <b>4</b>  |
| 1.1. Description of Device (EUT) .....                          | 4         |
| 1.2. Channel List.....                                          | 4         |
| 1.3. Summary of test result.....                                | 5         |
| 1.4. Special Accessories and Auxiliary Equipment .....          | 5         |
| 1.5. Test mode .....                                            | 5         |
| 1.6. Test configuration .....                                   | 5         |
| 1.7. Block Diagram .....                                        | 6         |
| 1.8. Test Conditions .....                                      | 6         |
| 1.9. Measurement Uncertainty (95% confidence levels, k=2) ..... | 6         |
| 1.10. Test Facility .....                                       | 7         |
| 1.11. Test Equipment.....                                       | 8         |
| <b>2. Conducted emission at the mains terminals test.....</b>   | <b>10</b> |
| 2.1. Limit.....                                                 | 10        |
| 2.2. Test Setup .....                                           | 10        |
| 2.3. Test Procedure .....                                       | 10        |
| 2.4. Test Result .....                                          | 11        |
| <b>3. Radiated Spurious Emissions.....</b>                      | <b>13</b> |
| 3.1. Limit.....                                                 | 13        |
| 3.2. Test Setup .....                                           | 14        |
| 3.3. Test Procedure .....                                       | 16        |
| 3.4. Test Result .....                                          | 17        |
| <b>4. Conducted Spurious Emissions .....</b>                    | <b>22</b> |
| 4.1. Limit.....                                                 | 22        |
| 4.2. Test Setup .....                                           | 22        |
| 4.3. Test Procedure .....                                       | 22        |
| 4.4. Test Result .....                                          | 23        |
| <b>5. Band Edge Measurement .....</b>                           | <b>24</b> |
| 5.1. Limit.....                                                 | 24        |
| 5.2. Test setup .....                                           | 24        |
| 5.3. Test Procedure .....                                       | 24        |
| 5.4. Test Result .....                                          | 25        |
| <b>6. -6 dB Bandwidth and 99% Bandwidth Measurement.....</b>    | <b>26</b> |
| 6.1. Limit.....                                                 | 26        |
| 6.2. Test Setup .....                                           | 26        |
| 6.3. Test Procedure .....                                       | 26        |
| 6.4. Test Result .....                                          | 27        |
| <b>7. Maximum Peak Output Power.....</b>                        | <b>29</b> |
| 7.1. Limit.....                                                 | 29        |
| 7.2. Test Setup .....                                           | 29        |
| 7.3. Test Procedure .....                                       | 29        |
| 7.4. Test Result .....                                          | 30        |
| <b>8. Power Spectral density.....</b>                           | <b>33</b> |
| 8.1. Limit.....                                                 | 33        |
| 8.2. Test Setup .....                                           | 33        |
| 8.3. Test Procedure .....                                       | 33        |
| 8.4. Test Result .....                                          | 34        |
| <b>9. Antenna Requirement .....</b>                             | <b>36</b> |
| <b>10. TEST SETUP &amp; EUT PHOTOGRAPH.....</b>                 | <b>37</b> |

## Revision History of This Test Report

[illegible]

## 1. General Information

### 1.1. Description of Device (EUT)

|                        |   |                                                                                                                               |
|------------------------|---|-------------------------------------------------------------------------------------------------------------------------------|
| EUT Name               | : | Automatic Chicken Door Duo Smart Control unit                                                                                 |
| Model No.              | : | 70521, 70531, 70531-ROSE, 70533                                                                                               |
| Model Difference       | : | All the model are the same circuit and RF module, only the name and appearance colors are different. Test sample model: 70521 |
| Power supply           | : | Input :AC 100-240V~50/60Hz 0.6A<br>Output:12V/1A                                                                              |
| Operation frequency    | : | 2402-2480MHz                                                                                                                  |
| Modulation             | : | GFSK                                                                                                                          |
| Antenna Type           | : | External antenna, Maximum Gain is 3.49dBi                                                                                     |
| Intend use environment | : | Residential, commercial and light industrial environment                                                                      |

## 1.2.Channel List

| Channel | Frequency<br>(MHz) | Channel   | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) |
|---------|--------------------|-----------|--------------------|---------|--------------------|
| 00      | <b>2402</b>        | 14        | 2430               | 28      | 2458               |
| 01      | 2404               | 15        | 2432               | 29      | 2460               |
| 02      | 2406               | 16        | 2434               | 30      | 2462               |
| 03      | 2408               | 17        | 2436               | 31      | 2464               |
| 04      | 2410               | 18        | 2438               | 32      | 2466               |
| 05      | 2412               | <b>19</b> | <b>2440</b>        | 33      | 2468               |
| 06      | 2414               | 20        | 2442               | 34      | 2470               |
| 07      | 2416               | 21        | 2444               | 35      | 2472               |
| 08      | 2418               | 22        | 2446               | 36      | 2474               |
| 09      | 2420               | 23        | 2448               | 37      | 2476               |
| 10      | 2422               | 24        | 2450               | 38      | 2478               |
| 11      | 2424               | 25        | 2452               | 39      | <b>2480</b>        |
| 12      | 2426               | 26        | 2454               |         |                    |
| 13      | 2428               | 27        | 2456               |         |                    |

### 1.3.Summary of test result

| RF PART                                                                                                                             |                               |        |
|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--------|
| Test Items                                                                                                                          | Test Requirement              | Result |
| Antenna requirement                                                                                                                 | FCC part 15.203/15.247 (b)(4) | PASS   |
| AC Power Line Conducted Emission                                                                                                    | FCC part 15.207               | PASS   |
| Conducted Peak Output Power                                                                                                         | FCC part 15.247 (b)(3)        | PASS   |
| Channel Bandwidth& 99% OCB                                                                                                          | FCC part 15.247 (a)(2)        | PASS   |
| Power Spectral Density                                                                                                              | FCC part 15.247 (e)           | PASS   |
| Band Edge                                                                                                                           | FCC part 15.247(d)            | PASS   |
| Spurious Emission                                                                                                                   | FCC part 15.205/15.209        | PASS   |
| Remark:<br>N/A is an abbreviation for Not Applicable.<br>Measurement Uncertainty is not taken into account for conformity statement |                               |        |

### 1.4.Special Accessories and Auxiliary Equipment

| Description | Manufacturer | Model No.   | Hardware Version | Software Version |
|-------------|--------------|-------------|------------------|------------------|
| Laptop      | DELL         | Vostro 5490 | /                | /                |
| Adapter     |              |             |                  |                  |
| cable       |              |             |                  |                  |

### 1.5.Test mode

The special RF test software was used to control EUT work in Continuous BLE TX mode, and select test channel, wireless mode.

| Test mode | Low channel | Middle channel | High channel |
|-----------|-------------|----------------|--------------|
| GFSK      | 2402MHz     | 2440MHz        | 2480MHz      |

Note: Only the worst Data Record in the report

### 1.6. Test configuration


|                                                                                                                                                                                                                                       |                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                     | Keep the EUT in continuously transmitting mode. |
| Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. |                                                 |
| Test Software                                                                                                                                                                                                                         | ESP_RF_Test_CN                                  |
| Power level setup                                                                                                                                                                                                                     | default                                         |

## 1.7. Block Diagram


### Conducted Emission



### Radiated Emission



### RF Conducted Test



## 1.8. Test Conditions

| Category          | Normal Conditions | Extreme Conditions |
|-------------------|-------------------|--------------------|
| Temperature range | 15-35°C           | N/A                |
| Humidity range    | 20-75%            | N/A                |
| Pressure range    | 86-106kPa         | N/A                |
| Power supply      | DC 12V            | N/A                |

Note: N/A is an abbreviation for Not Applicable.

## 1.9. Measurement Uncertainty (95% confidence levels, k=2)

| Parameter                                                                                       | Uncertainty              |
|-------------------------------------------------------------------------------------------------|--------------------------|
| RF output power, conducted                                                                      | ±1.0dB                   |
| Power Spectral Density, conducted                                                               | ±2.2dB                   |
| Radio Frequency                                                                                 | ± 1 x 10 <sup>-6</sup>   |
| Bandwidth                                                                                       | ± 1.5 x 10 <sup>-6</sup> |
| Time                                                                                            | ±2%                      |
| Duty Cycle                                                                                      | ±2%                      |
| Temperature                                                                                     | ±1°C                     |
| Humidity                                                                                        | ±5%                      |
| DC and low frequency voltages                                                                   | ±3%                      |
| Conducted Emissions (150kHz~30MHz)                                                              | ±3.64dB                  |
| Radiated Emission(9KHz~30MHz)                                                                   | ±4.51dB                  |
| Radiated Emission(30MHz~1GHz)                                                                   | ±5.03dB                  |
| Radiated Emission(1GHz~25GHz)                                                                   | ±4.74dB                  |
| Remark: When making a conformity declaration based on test results for regulations/standards or |                          |

specifications,the default is to use Clause 4.2.1of ILAC-G8:09/2019 and the guidelines on decision rules and conformity declaration in IEC Guide 115:2023.

## 1.10.Test Facility

|                                   |   |                                                                                                                                                                                                     |
|-----------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Site Description                  |   |                                                                                                                                                                                                     |
| Name of Firm                      | : | Shenzhen NTT Testing Technology Co.,Ltd.                                                                                                                                                            |
| Site Location                     | : | 1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, China |
| FCC Designation Number            | : | CN3446                                                                                                                                                                                              |
| FCC Test Firm Registration Number | : | 129414                                                                                                                                                                                              |

## 1.11.Test Equipment

### Conducted Test Site

| Name              | Model No. | Serial No. | Manufacturer  | Date of Cal. | Due Date   |
|-------------------|-----------|------------|---------------|--------------|------------|
| 944 Shielded Room | HSRCE944  | /          | HTEC          | 2025/04/30   | 2028/04/29 |
| EMI Test Receiver | ESCI      | 100881/003 | ROHDE&SCHWARZ | 2026/09/04   | 2027/09/03 |
| LISN              | AMN6500   | 101185     | ROHDE&SCHWARZ | 2026/09/04   | 2027/09/03 |
| LISN              | NNLK 8129 | 00603      | SCHWARZBECK   | 2026/09/04   | 2027/09/03 |
| Cable             | RG223-2M  | /          | RG            | 2026/09/04   | 2027/09/03 |

### Radiated Test Site(Below 1G and Above 1G)&RF Test Site

| Name                                                | Model No.       | Serial No. | Manufacturer  | Date of Cal. | Due Date   |
|-----------------------------------------------------|-----------------|------------|---------------|--------------|------------|
| 966 Shielded Room                                   | 966 Room        | /          | EMToni        | 2025/07/24   | 2028/07/23 |
| EMI Test Receiver                                   | ESPI            | 101018     | ROHDE&SCHWARZ | 2026/09/04   | 2027/09/03 |
| Amplifier<br>(30MHz-1GHz)                           | BBV 9745        | 00431      | SCHWARZBECK   | 2026/09/04   | 2027/09/03 |
| Bilog Antenna<br>(30MHz-1GHz)                       | VULB9168        | 1858       | SCHWARZBECK   | 2026/09/05   | 2027/09/04 |
| Horn antenna<br>(1GHz-18GHz)                        | BBHA 9120<br>D  | 02622      | SCHWARZBECK   | 2026/09/05   | 2027/09/04 |
| Preamplifier<br>(1GHz-18GHz)                        | BBV 9718D       | 0024       | SCHWARZBECK   | 2026/09/04   | 2027/09/03 |
| Spectrum Analyzer<br>(10Hz-40GHz)                   | FSV 40          | 100952     | ROHDE&SCHWARZ | 2026/09/04   | 2027/09/03 |
| Preamplifier<br>(18GHz-40GHz)                       | BBV 9721        | 0056       | SCHWARZBECK   | 2026/09/04   | 2027/09/03 |
| Double Ridge Guide<br>Horn Antenna<br>(18GHz-40GHz) | SAS-574         | 588        | A.H.System    | 2026/09/05   | 2027/09/04 |
| Loop Antenna<br>(9KHz-30MHz)                        | FMZB<br>1513-60 | 00115      | SCHWARZBECK   | 2026/09/04   | 2027/09/03 |
| MXG Signal Analyzer                                 | N9020A          | MY49100730 | Agilent       | 2026/09/04   | 2027/09/03 |
| MXG Vector Signal<br>Generator                      | N5182A          | MY50144920 | Agilent       | 2026/09/04   | 2027/09/03 |
| WIDEBAND RADIO<br>COMMUNICATION<br>TESTER           | CMW500          | /          | ROHDE&SCHWARZ | 2026/09/07   | 2027/09/06 |

|              |                        |                    |          |            |            |
|--------------|------------------------|--------------------|----------|------------|------------|
| Power Sensor | MW100-RFC<br>B-2       | MW260105N<br>TT-64 | MWRFtest | 2026/09/04 | 2027/09/03 |
| RF Swith     | MW100-RFC<br>B-1       | MW260105N<br>TT-64 | MWRFtest | 2026/09/04 | 2027/09/03 |
| Cable        | RG223-3M               | /                  | DA       | 2026/09/04 | 2027/09/03 |
| Cable        | RG223-12M              | /                  | DA       | 2026/09/04 | 2027/09/03 |
| Cable        | SFT205-NM<br>NMSW-2.5M | /                  | DA       | 2026/09/04 | 2027/09/03 |
| Cable        | SFT205-NM<br>NM-12M    | /                  | DA       | 2026/09/04 | 2027/09/03 |
| Cable        | UCA500-NJ<br>WSM-1.5M  | 017                | MWRFtest | 2026/09/04 | 2027/09/03 |

## 2. Conducted emission at the mains terminals test


### 2.1.Limit

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Test Requirement:     | FCC Part15 C Section 15.207                                          |
| Test Method:          | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 |
| Test Frequency Range: | 150KHz to 30MHz                                                      |
| Receiver setup:       | RBW=9KHz, VBW=30KHz, Sweep time=auto                                 |

| Frequency<br>MHz | Limits dB( $\mu$ V) |               |
|------------------|---------------------|---------------|
|                  | Quasi-peak Level    | Average Level |
| 0.15 ~ 0.50      | 66 ~ 56*            | 56 ~ 46*      |
| 0.50 ~ 5.00      | 56                  | 46            |
| 5.00 ~ 30.00     | 60                  | 50            |

Notes: 1. \*Decreasing linearly with logarithm of frequency.  
2. The lower limit shall apply at the transition frequencies.

### 2.2.Test Setup




### 2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.

## 2.4.Test Result

| Conducted Emission At The Mains Terminals Test Data |                                           |                    |            |
|-----------------------------------------------------|-------------------------------------------|--------------------|------------|
| Temperature:                                        | 25.1℃                                     | Relative Humidity: | 56%        |
| Pressure:                                           | 1008hPa                                   | Phase :            | Line       |
| Test Voltage :                                      | DC 12V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.2020       | 24.65                    | 10.08                   | 34.73                    | 63.53         | -28.80     | QP       |
| 2   |     | 0.2020       | 6.60                     | 10.08                   | 16.68                    | 53.53         | -36.85     | AVG      |
| 3   | *   | 0.6180       | 25.48                    | 10.10                   | 35.58                    | 56.00         | -20.42     | QP       |
| 4   |     | 0.6180       | 10.40                    | 10.10                   | 20.50                    | 46.00         | -25.50     | AVG      |
| 5   |     | 1.6060       | 12.85                    | 10.15                   | 23.00                    | 56.00         | -33.00     | QP       |
| 6   |     | 1.6060       | -1.15                    | 10.15                   | 9.00                     | 46.00         | -37.00     | AVG      |
| 7   |     | 3.9100       | 10.76                    | 10.24                   | 21.00                    | 56.00         | -35.00     | QP       |
| 8   |     | 3.9100       | -1.65                    | 10.24                   | 8.59                     | 46.00         | -37.41     | AVG      |
| 9   |     | 10.5860      | 14.39                    | 10.47                   | 24.86                    | 60.00         | -35.14     | QP       |
| 10  |     | 10.5860      | -0.84                    | 10.47                   | 9.63                     | 50.00         | -40.37     | AVG      |
| 11  |     | 29.6300      | 16.95                    | 11.24                   | 28.19                    | 60.00         | -31.81     | QP       |
| 12  |     | 29.6300      | 3.89                     | 11.24                   | 15.13                    | 50.00         | -34.87     | AVG      |

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(GFSK) in the report

Conducted Emission At The Mains Terminals Test Data

|                |                                           |                    |            |
|----------------|-------------------------------------------|--------------------|------------|
| Temperature:   | 25.1℃                                     | Relative Humidity: | 56%        |
| Pressure:      | 1008hPa                                   | Phase :            | Neutral    |
| Test Voltage : | DC 12V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.2260       | 20.06                    | 10.08                   | 30.14                    | 62.60         | -32.46     | QP       |
| 2   |     | 0.2260       | 10.89                    | 10.08                   | 20.97                    | 52.60         | -31.63     | AVG      |
| 3 * |     | 0.6060       | 23.90                    | 10.10                   | 34.00                    | 56.00         | -22.00     | QP       |
| 4   |     | 0.6060       | 7.22                     | 10.10                   | 17.32                    | 46.00         | -28.68     | AVG      |
| 5   |     | 1.9860       | 6.88                     | 10.17                   | 17.05                    | 56.00         | -38.95     | QP       |
| 6   |     | 1.9860       | -3.18                    | 10.17                   | 6.99                     | 46.00         | -39.01     | AVG      |
| 7   |     | 5.1740       | 10.43                    | 10.29                   | 20.72                    | 60.00         | -39.28     | QP       |
| 8   |     | 5.1740       | -2.31                    | 10.29                   | 7.98                     | 50.00         | -42.02     | AVG      |
| 9   |     | 11.1820      | 12.99                    | 10.51                   | 23.50                    | 60.00         | -36.50     | QP       |
| 10  |     | 11.1820      | -2.13                    | 10.51                   | 8.38                     | 50.00         | -41.62     | AVG      |
| 11  |     | 29.4980      | 23.91                    | 11.24                   | 35.15                    | 60.00         | -24.85     | QP       |
| 12  |     | 29.4980      | 3.98                     | 11.24                   | 15.22                    | 50.00         | -34.78     | AVG      |

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(GFSK) in the report

### 3. Radiated Spurious Emissions

#### 3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247  
 Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;  
 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024  
 Test Result: PASS  
 Measurement Distance: 3m

| Frequency    | Detector   | RBW    | VBW    | Value      |
|--------------|------------|--------|--------|------------|
| 9KHz-150KHz  | Quasi-peak | 200Hz  | 600Hz  | Quasi-peak |
| 150KHz-30MHz | Quasi-peak | 9KHz   | 30KHz  | Quasi-peak |
| 30MHz-1GHz   | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
| Above 1GHz   | Peak       | 1MHz   | 3MHz   | Peak       |
|              | Peak       | 1MHz   | 10Hz   | Average    |


Limit:

| Frequency (MHz) | Field Strength        |              | Field Strength Limit at 3m Measurement Dist |                                    |
|-----------------|-----------------------|--------------|---------------------------------------------|------------------------------------|
|                 | uV/m                  | Distance (m) | uV/m                                        | dBuV/m                             |
| 0.009 ~ 0.490   | $2400/F(\text{kHz})$  | 300          | $10000 * 2400/F(\text{kHz})$                | $20\log(2400/F(\text{kHz})) + 80$  |
| 0.490 ~ 1.705   | $24000/F(\text{kHz})$ | 30           | $100 * 24000/F(\text{kHz})$                 | $20\log(24000/F(\text{kHz})) + 40$ |
| 1.705 ~ 30      | 30                    | 30           | $100 * 30$                                  | $20\log(30) + 40$                  |
| 30 ~ 88         | 100                   | 3            | 100                                         | $20\log(100)$                      |
| 88 ~ 216        | 150                   | 3            | 150                                         | $20\log(150)$                      |
| 216 ~ 960       | 200                   | 3            | 200                                         | $20\log(200)$                      |
| Above 960       | 500                   | 3            | 500                                         | $20\log(500)$                      |


### 3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.



The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 3.3.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.

### 3.4.Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 1GHz

| Radiation Emission Test Data |                                           |                    |            |
|------------------------------|-------------------------------------------|--------------------|------------|
| Temperature:                 | 25.1℃                                     | Relative Humidity: | 56%        |
| Pressure:                    | 1008hPa                                   | Phase :            | Horizontal |
| Test Voltage :               | DC 12V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 46.5030      | 27.49                    | -6.24                   | 21.25                      | 40.00         | -18.75     | QP       |
| 2   |     | 85.1486      | 26.78                    | -8.41                   | 18.37                      | 40.00         | -21.63     | QP       |
| 3   |     | 134.3235     | 33.20                    | -5.76                   | 27.44                      | 43.50         | -16.06     | QP       |
| 4   |     | 343.1800     | 31.84                    | -1.82                   | 30.02                      | 46.00         | -15.98     | QP       |
| 5   |     | 633.9073     | 25.01                    | 4.80                    | 29.81                      | 46.00         | -16.19     | QP       |
| 6   | *   | 782.3453     | 31.07                    | 8.18                    | 39.25                      | 46.00         | -6.75      | QP       |

Note:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(GFSK) in the report

| Radiation Emission Test Data |                                           |                    |            |
|------------------------------|-------------------------------------------|--------------------|------------|
| Temperature:                 | 25.1°C                                    | Relative Humidity: | 56%        |
| Pressure:                    | 1008hPa                                   | Phase :            | Vertical   |
| Test Voltage :               | DC 12V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 42.6000      | 33.72                    | -6.01                   | 27.71                      | 40.00         | -12.29     | QP       |
| 2   |     | 104.1701     | 32.16                    | -7.47                   | 24.69                      | 43.50         | -18.81     | QP       |
| 3   |     | 136.6992     | 41.47                    | -5.60                   | 35.87                      | 43.50         | -7.63      | QP       |
| 4   |     | 239.5669     | 31.44                    | -5.11                   | 26.33                      | 46.00         | -19.67     | QP       |
| 5   |     | 434.8267     | 25.45                    | -0.26                   | 25.19                      | 46.00         | -20.81     | QP       |
| 6   | *   | 775.5168     | 30.99                    | 8.03                    | 39.02                      | 46.00         | -6.98      | QP       |

Note:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(GFSK) in the report

1GHz~25GHz

| Polar<br>(H/V)      | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-ampli<br>fier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Detector<br>Type |
|---------------------|--------------------|----------------------------|---------------------------|-----------------------|---------------------------|-------------------------------|--------------------|----------------|------------------|
| Low Channel:2402MHz |                    |                            |                           |                       |                           |                               |                    |                |                  |
| V                   | 4804.00            | 52.09                      | 34.12                     | 5.03                  | 32.39                     | 55.39                         | 74                 | -18.61         | Pk               |
| V                   | 4804.00            | 39.79                      | 34.12                     | 5.03                  | 32.39                     | 43.09                         | 54                 | -10.91         | AV               |
| V                   | 7206.00            | 49.60                      | 32.54                     | 6.29                  | 35.86                     | 59.21                         | 74                 | -14.79         | Pk               |
| V                   | 7206.00            | 35.62                      | 32.54                     | 6.29                  | 35.86                     | 45.23                         | 54                 | -8.77          | AV               |
| V                   | 9608.00            | 47.60                      | 32.98                     | 7.55                  | 38.4                      | 60.57                         | 74                 | -13.43         | Pk               |
| V                   | 9608.00            | 33.75                      | 32.98                     | 7.55                  | 38.4                      | 46.72                         | 54                 | -7.28          | AV               |
| V                   | 12010.00           | 44.58                      | 32.09                     | 8.93                  | 39                        | 60.42                         | 74                 | -13.58         | Pk               |
| V                   | 12010.00           | 28.57                      | 32.09                     | 8.93                  | 39                        | 44.41                         | 54                 | -9.59          | AV               |
| H                   | 4804.00            | 50.02                      | 34.12                     | 5.03                  | 32.39                     | 53.32                         | 74                 | -20.68         | Pk               |
| H                   | 4804.00            | 40.80                      | 34.12                     | 5.03                  | 32.39                     | 44.10                         | 54                 | -9.90          | AV               |
| H                   | 7206.00            | 47.35                      | 32.54                     | 6.29                  | 35.86                     | 56.96                         | 74                 | -17.04         | Pk               |
| H                   | 7206.00            | 32.30                      | 32.54                     | 6.29                  | 35.86                     | 41.91                         | 54                 | -12.09         | AV               |
| H                   | 9608.00            | 47.30                      | 32.98                     | 7.55                  | 38.4                      | 60.27                         | 74                 | -13.73         | Pk               |
| H                   | 9608.00            | 30.18                      | 32.98                     | 7.55                  | 38.4                      | 43.15                         | 54                 | -10.85         | AV               |
| H                   | 12010.00           | 39.20                      | 32.09                     | 8.93                  | 39                        | 55.04                         | 74                 | -18.96         | Pk               |
| H                   | 12010.00           | 25.76                      | 32.09                     | 8.93                  | 39                        | 41.60                         | 54                 | -12.40         | AV               |

| Polar<br>(H/V)         | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-ampli<br>fier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Detector<br>Type |
|------------------------|--------------------|----------------------------|---------------------------|-----------------------|---------------------------|-------------------------------|--------------------|----------------|------------------|
| Middle Channel:2440MHz |                    |                            |                           |                       |                           |                               |                    |                |                  |
| V                      | 4880.00            | 50.73                      | 34.07                     | 5.09                  | 32.59                     | 54.34                         | 74                 | -19.66         | Pk               |
| V                      | 4880.00            | 39.42                      | 34.07                     | 5.09                  | 32.59                     | 43.03                         | 54                 | -10.97         | AV               |
| V                      | 7320.00            | 45.17                      | 32.63                     | 6.34                  | 35.96                     | 54.84                         | 74                 | -19.16         | Pk               |
| V                      | 7320.00            | 35.93                      | 32.63                     | 6.34                  | 35.96                     | 45.60                         | 54                 | -8.40          | AV               |
| V                      | 9760.00            | 42.83                      | 32.92                     | 7.59                  | 38.4                      | 55.90                         | 74                 | -18.10         | Pk               |
| V                      | 9760.00            | 30.78                      | 32.92                     | 7.59                  | 38.4                      | 43.85                         | 54                 | -10.15         | AV               |
| V                      | 12200.00           | 41.75                      | 31.96                     | 8.88                  | 39.04                     | 57.71                         | 74                 | -16.29         | Pk               |
| V                      | 12200.00           | 29.69                      | 31.96                     | 8.88                  | 39.04                     | 45.65                         | 54                 | -8.35          | AV               |
| H                      | 4880.00            | 49.11                      | 34.07                     | 5.09                  | 32.59                     | 52.72                         | 74                 | -21.28         | Pk               |
| H                      | 4880.00            | 38.89                      | 34.07                     | 5.09                  | 32.59                     | 42.50                         | 54                 | -11.50         | AV               |
| H                      | 7320.00            | 47.44                      | 32.63                     | 6.34                  | 35.96                     | 57.11                         | 74                 | -16.89         | Pk               |
| H                      | 7320.00            | 33.73                      | 32.63                     | 6.34                  | 35.96                     | 43.40                         | 54                 | -10.60         | AV               |
| H                      | 9760.00            | 42.03                      | 32.92                     | 7.59                  | 38.4                      | 55.10                         | 74                 | -18.90         | Pk               |
| H                      | 9760.00            | 29.52                      | 32.92                     | 7.59                  | 38.4                      | 42.59                         | 54                 | -11.41         | AV               |
| H                      | 12200.00           | 39.16                      | 31.96                     | 8.88                  | 39.04                     | 55.12                         | 74                 | -18.88         | Pk               |
| H                      | 12200.00           | 29.95                      | 31.96                     | 8.88                  | 39.04                     | 45.91                         | 54                 | -8.09          | AV               |

| Polar<br>(H/V)       | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|----------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                      | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| High Channel:2480MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                    | 4960.00   | 48.96            | 34.02             | 5.15          | 32.8              | 52.89             | 74       | -21.11 | Pk               |
| V                    | 4960.00   | 35.94            | 34.02             | 5.15          | 32.8              | 39.87             | 54       | -14.13 | AV               |
| V                    | 7440.00   | 44.44            | 32.71             | 6.4           | 36.05             | 54.18             | 74       | -19.82 | Pk               |
| V                    | 7440.00   | 36.39            | 32.71             | 6.4           | 36.05             | 46.13             | 54       | -7.87  | AV               |
| V                    | 9920.00   | 40.56            | 32.86             | 7.62          | 38.4              | 53.72             | 74       | -20.28 | Pk               |
| V                    | 9920.00   | 31.01            | 32.86             | 7.62          | 38.4              | 44.17             | 54       | -9.83  | AV               |
| V                    | 12400.00  | 37.92            | 31.82             | 8.84          | 39.08             | 54.02             | 74       | -19.98 | Pk               |
| V                    | 12400.00  | 28.64            | 31.82             | 8.84          | 39.08             | 44.74             | 54       | -9.26  | AV               |
| H                    | 4960.00   | 48.69            | 34.02             | 5.15          | 32.8              | 52.62             | 74       | -21.38 | Pk               |
| H                    | 4960.00   | 37.71            | 34.02             | 5.15          | 32.8              | 41.64             | 54       | -12.36 | AV               |
| H                    | 7440.00   | 45.30            | 32.71             | 6.4           | 36.05             | 55.04             | 74       | -18.96 | Pk               |
| H                    | 7440.00   | 32.23            | 32.71             | 6.4           | 36.05             | 41.97             | 54       | -12.03 | AV               |
| H                    | 9920.00   | 40.65            | 32.86             | 7.62          | 38.4              | 53.81             | 74       | -20.19 | Pk               |
| H                    | 9920.00   | 27.30            | 32.86             | 7.62          | 38.4              | 40.46             | 54       | -13.54 | AV               |
| H                    | 12400.00  | 40.33            | 31.82             | 8.84          | 39.08             | 56.43             | 74       | -17.57 | Pk               |
| H                    | 12400.00  | 30.82            | 31.82             | 8.84          | 39.08             | 46.92             | 54       | -7.08  | AV               |

Note: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
 Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

All the modes have tested and recorded the worst mode(GFSK) in the report.

The 1-25GHz range has been tested, and the report only records the worst performance of the 1-18G range.

## Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

|                                                                                                                            | Polar<br>(H/V)        | Frequenc<br>y<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBuV<br>/m) | Margi<br>n<br>(dB) | Detec<br>tor<br>Type |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-----------------------|--------------------|----------------------|
| GFSK                                                                                                                       | Low Channel: 2402MHz  |                        |                            |                           |                       |                             |                               |                       |                    |                      |
|                                                                                                                            | H                     | 2390.00                | 60.04                      | 35.17                     | 3.48                  | 27.49                       | 55.84                         | 74                    | -18.16             | PK                   |
|                                                                                                                            | H                     | 2390.00                | 48.86                      | 35.17                     | 3.48                  | 27.49                       | 44.66                         | 54                    | -9.34              | AV                   |
|                                                                                                                            | H                     | 2400.00                | 61.45                      | 35.16                     | 3.49                  | 27.52                       | 57.30                         | 74                    | -16.70             | PK                   |
|                                                                                                                            | H                     | 2400.00                | 49.68                      | 35.16                     | 3.49                  | 27.52                       | 45.53                         | 54                    | -8.47              | AV                   |
|                                                                                                                            | V                     | 2390.00                | 57.45                      | 35.17                     | 3.48                  | 27.49                       | 53.25                         | 74                    | -20.75             | PK                   |
|                                                                                                                            | V                     | 2390.00                | 51.09                      | 35.17                     | 3.48                  | 27.49                       | 46.89                         | 54                    | -7.11              | AV                   |
|                                                                                                                            | V                     | 2400.00                | 59.57                      | 35.16                     | 3.49                  | 27.52                       | 55.42                         | 74                    | -18.58             | PK                   |
|                                                                                                                            | V                     | 2400.00                | 50.36                      | 35.16                     | 3.49                  | 27.52                       | 46.21                         | 54                    | -7.79              | AV                   |
|                                                                                                                            | High Channel: 2480MHz |                        |                            |                           |                       |                             |                               |                       |                    |                      |
|                                                                                                                            | H                     | 2483.50                | 59.10                      | 35.11                     | 3.56                  | 27.75                       | 55.30                         | 74                    | -18.70             | PK                   |
|                                                                                                                            | H                     | 2483.50                | 48.94                      | 35.11                     | 3.56                  | 27.75                       | 45.14                         | 54                    | -8.86              | AV                   |
|                                                                                                                            | H                     | 2500.00                | 61.74                      | 35.1                      | 3.57                  | 27.8                        | 58.01                         | 74                    | -15.99             | PK                   |
|                                                                                                                            | H                     | 2500.00                | 49.05                      | 35.1                      | 3.57                  | 27.8                        | 45.32                         | 54                    | -8.68              | AV                   |
|                                                                                                                            | V                     | 2483.50                | 59.47                      | 35.11                     | 3.56                  | 27.75                       | 55.67                         | 74                    | -18.33             | PK                   |
|                                                                                                                            | V                     | 2483.50                | 50.83                      | 35.11                     | 3.56                  | 27.75                       | 47.03                         | 54                    | -6.97              | AV                   |
|                                                                                                                            | V                     | 2500.00                | 58.57                      | 35.1                      | 3.57                  | 27.8                        | 54.84                         | 74                    | -19.16             | PK                   |
|                                                                                                                            | V                     | 2500.00                | 51.73                      | 35.1                      | 3.57                  | 27.8                        | 48.00                         | 54                    | -6.00              | AV                   |
| Remark:<br>1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit |                       |                        |                            |                           |                       |                             |                               |                       |                    |                      |

## 4. Conducted Spurious Emissions


### 4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247  
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2,2019;  
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024  
Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 4.2.Test Setup



### 4.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
  - a) Set instrument center frequency to DTS channel center frequency.
  - b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
  - c) Set the RBW = 100 kHz.
  - d) Set the VBW  $\geq [3 \times \text{RBW}]$ .
  - e) Detector = peak.
  - f) Sweep time = auto couple.
  - g) Trace mode = max hold.
  - h) Allow trace to fully stabilize.
  - i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.


NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b).

Report the three highest emissions relative to the limit.

#### 4.4. Test Result



## 5. Band Edge Measurement

### 5.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247


Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which

the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting


### 5.2.Test setup



### 5.3.Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

## 5.4. Test Result




## 6. -6 dB Bandwidth and 99% Bandwidth Measurement

### 6.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;  
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

### 6.2.Test Setup



### 6.3.Test Procedure

#### For 6dB Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2.The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1(i.e, RBW= 100 kHz VBW>3 x RBW,and peak detector with maximum hold) is implemented by the instrumentation function.When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.
3. The steps for the first option are as follows:
  - a.Set RBW= shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
  - b.Set the VBW[3 x RBW].
  - c.Detector = peak
  - d.Trace mode = max-hold.
  - e.Sweep = No faster than coupled (auto) time.
  - f.Allow the trace to stabilize.
  - g.Measure the maximum width of the emission by placing two markers, one at the lowest frequencyand the other at the highest frequency of the envelope of the spectral display, such that each markeris at or slightly below the "-6 dB down amplitude". If a marker is below this "-6 dB down amplitude?" value, then it shall be as close as possible to this value.

#### For 99% Bandwidth Measurement


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW  $\geq 3$ RBW

## 6.4.Test Result

| Test Mode | Frequency    | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|-----------|--------------|---------------------|-------------|--------|
| GFSK      | Low channel  | 0.65                | $\geq 500$  | PASS   |
|           | Mid channel  | 0.651               | $\geq 500$  | PASS   |
|           | High channel | 0.649               | $\geq 500$  | PASS   |

Note: All modes of operation were Pre-scan and the worst-case emissions are reported.

Test Graph:

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>GFSK<br/>Low channel</p>  |  <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.402000000 GHz</p> <p>Ref Offset 6.99 dB<br/>Ref 26.99 dBm</p> <p>Mkr3 2.402322 GHz<br/>-5.5511 dBm</p> <p>Center 2.402 GHz<br/>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 3 MHz<br/>Sweep 1 ms</p> <p>Occupied Bandwidth 1.0258 MHz</p> <p>Total Power 7.18 dBm</p> <p>Transmit Freq Error -2.791 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 649.8 kHz</p> <p>x dB -6.00 dB</p>  |
| <p>GFSK<br/>Mid channel</p>  |  <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.440000000 GHz</p> <p>Ref Offset 7.01 dB<br/>Ref 27.01 dBm</p> <p>Mkr3 2.440322 GHz<br/>-4.7949 dBm</p> <p>Center 2.44 GHz<br/>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 3 MHz<br/>Sweep 1 ms</p> <p>Occupied Bandwidth 1.0271 MHz</p> <p>Total Power 7.99 dBm</p> <p>Transmit Freq Error -3.478 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 651.2 kHz</p> <p>x dB -6.00 dB</p>  |
| <p>GFSK<br/>High channel</p> |  <p>Agilent Spectrum Analyzer - Occupied BW</p> <p>Center Freq 2.480000000 GHz</p> <p>Ref Offset 7.05 dB<br/>Ref 27.05 dBm</p> <p>Mkr3 2.480321 GHz<br/>-4.3647 dBm</p> <p>Center 2.48 GHz<br/>#Res BW 100 kHz</p> <p>#VBW 300 kHz</p> <p>Span 3 MHz<br/>Sweep 1 ms</p> <p>Occupied Bandwidth 1.0236 MHz</p> <p>Total Power 8.49 dBm</p> <p>Transmit Freq Error -2.919 kHz</p> <p>OBW Power 99.00 %</p> <p>x dB Bandwidth 648.6 kHz</p> <p>x dB -6.00 dB</p> |

## 7. Maximum Peak Output Power

### 7.1.Limit


Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

| FCC Part15 (15.247) , Subpart C |                   |                 |                       |        |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section                         | Test Item         | Limit           | Frequency Range (MHz) | Result |
| 15.247(b)(3)                    | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           | PASS   |

### 7.2.Test Setup



### 7.3.Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW  $\geq$  DTS bandwidth.
- Set VBW  $\geq 3 \times$  RBW.
- Set span  $\geq 3 \times$  RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

## 7.4.Test Result

| Mode | Channel. | Maximum Output Power [dBm] | Limit[dBm] | Verdict |
|------|----------|----------------------------|------------|---------|
| GFSK | LCH      | 0.948                      | 30         | PASS    |
|      | MCH      | 1.781                      | 30         | PASS    |
|      | HCH      | 2.161                      | 30         | PASS    |

### Duty Cycle

| Mode | Channel. | Duty Cycle(%) | Correction Factor (dB) |
|------|----------|---------------|------------------------|
| GFSK | LCH      | 53.97         | 2.68                   |
|      | MCH      | 56.45         | 2.48                   |
|      | HCH      | 57.72         | 2.39                   |

Note: Duty Cycle Factor=  $10 \log (1/x)$ , x is Duty Cycle.

Test Graph:

|                              |                                                                                                                                                                                                                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>GFSK<br/>Low channel</p>  |  <p>Agilent Spectrum Analyzer - Sweep SA<br/>Center Freq 2.40200000 GHz<br/>Ref Offset 6.99 dB<br/>Ref 20.00 dBm<br/>Mkr1 2.40192 GHz<br/>0.948 dBm<br/>Span 10.00 MHz<br/>Sweep 1.000 ms (1001 pts)</p>   |
| <p>GFSK<br/>Mid channel</p>  |  <p>Agilent Spectrum Analyzer - Sweep SA<br/>Center Freq 2.44000000 GHz<br/>Ref Offset 7.01 dB<br/>Ref 20.00 dBm<br/>Mkr1 2.44024 GHz<br/>1.781 dBm<br/>Span 10.00 MHz<br/>Sweep 1.000 ms (1001 pts)</p>  |
| <p>GFSK<br/>High channel</p> |  <p>Agilent Spectrum Analyzer - Sweep SA<br/>Center Freq 2.48000000 GHz<br/>Ref Offset 7.05 dB<br/>Ref 20.00 dBm<br/>Mkr1 2.48008 GHz<br/>2.161 dBm<br/>Span 10.00 MHz<br/>Sweep 1.000 ms (1001 pts)</p> |

Duty Cycle  
Test Graph:



## 8. Power Spectral density


### 8.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;  
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

| FCC Part15 (15.247) , Subpart C |                        |           |                       |        |
|---------------------------------|------------------------|-----------|-----------------------|--------|
| Section                         | Test Item              | Limit     | Frequency Range (MHz) | Result |
| 15.247                          | Power Spectral Density | 8dBm/3kHz | 2400-2483.5           | PASS   |

### 8.2.Test Setup




### 8.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

#### 8.4.Test Result

| Mode | Channel. | Power Spectral Density (dBm/3KHz) | Limit(dBm/3KHz) | Verdict |
|------|----------|-----------------------------------|-----------------|---------|
| GFSK | LCH      | -15.096                           | 8               | PASS    |
| GFSK | MCH      | -14.092                           | 8               | PASS    |
| GFSK | HCH      | -13.682                           | 8               | PASS    |

Test Graph



## 9. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

This product has a External antenna, and the maximum antenna gain is 3.49dBi, fulfill the requirement of this section.

## 10. TEST SETUP & EUT PHOTOGRAPH

Reference to EUT photo attachment for details.

----- End of Report -----