

# TEST REPORT

Applicant : Shenzhen Aotuolang Technology Co.,Ltd.  
Address : 401, No. 88 Hekan Village, Wuhe Community, Bantian  
Street,Longgang District, Shenzhen, China  
Manufacturer : DONGGUAN TANGXI ELECTRONICS TECHNOLOGY CO.,LTD  
Address : NO.1 HENGSHAN ROAD, SHIPAI TOWN ,DONGGUAN,  
GUANGDONG PROVINCE,CHINA  
Product Name : Vintage Retro Portable Radio  
Model Number : JX1107, JX1107-1, JX1107-2, JX1107-3  
Trademark : N/A  
FCC ID : 2BXOZ-JX1107  
Test Date : Jul. 17, 2026 to Jul. 31, 2026  
Date of Report : Jul. 31, 2026  
Test Result : This device described above has been tested by NTT, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.


## Test Procedure Used:

Standards : FCC CFR Title 47 Part 15 Subpart C Section 15.247  
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to  
C63.10a-2024  
KDB 558074 D01 15.247 Meas Guidance v05r02

Prepared by(Test Engineer):  
Cindy Qin



Approved(Supervisor):  
Ken Wu



Approved(Manager):  
Abel Yu



**TABLE OF CONTENT**

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>1. General Information .....</b>                             | <b>4</b>  |
| 1.1. Description of Device (EUT).....                           | 4         |
| 1.2. Channel List.....                                          | 4         |
| 1.3. Summary of test result .....                               | 5         |
| 1.4. Special Accessories and Auxiliary Equipment .....          | 5         |
| 1.5. Test mode .....                                            | 5         |
| 1.6. Test configuration .....                                   | 5         |
| 1.7. Block Diagram .....                                        | 6         |
| 1.8. Test Conditions .....                                      | 6         |
| 1.9. Measurement Uncertainty (95% confidence levels, k=2) ..... | 6         |
| 1.10. Test Facility .....                                       | 7         |
| 1.11. Test Equipment.....                                       | 8         |
| <b>2. Conducted emission at the mains terminals test .....</b>  | <b>10</b> |
| 2.1. Limit.....                                                 | 10        |
| 2.2. Test Setup .....                                           | 10        |
| 2.3. Test Procedure .....                                       | 10        |
| 2.4. Test Result .....                                          | 11        |
| <b>3. Radiated Spurious Emissions .....</b>                     | <b>13</b> |
| 3.1. Limit.....                                                 | 13        |
| 3.2. Test Setup .....                                           | 14        |
| 3.3. Test Procedure .....                                       | 16        |
| 3.4. Test Result .....                                          | 17        |
| <b>4. Conducted Spurious Emissions.....</b>                     | <b>21</b> |
| 4.1. Limit.....                                                 | 21        |
| 4.2. Test Setup .....                                           | 22        |
| 4.3. Test Procedure .....                                       | 22        |
| 4.4. Test Result .....                                          | 22        |
| <b>5. Band Edge Measurement .....</b>                           | <b>25</b> |
| 5.1. Limit.....                                                 | 25        |
| 5.2. Test setup .....                                           | 25        |
| 5.3. Test Procedure .....                                       | 25        |
| 5.4. Test Result .....                                          | 26        |
| <b>6. -6 dB Bandwidth and 99% Bandwidth Measurement .....</b>   | <b>28</b> |
| 6.1. Limit.....                                                 | 28        |
| 6.2. Test Setup .....                                           | 28        |
| 6.3. Test Procedure .....                                       | 28        |
| 6.4. Test Result .....                                          | 28        |
| <b>7. Maximum Peak Output Power.....</b>                        | <b>32</b> |
| 7.1. Limit.....                                                 | 32        |
| 7.2. Test Setup .....                                           | 32        |
| 7.3. Test Procedure .....                                       | 32        |
| 7.4. Test Result .....                                          | 33        |
| <b>8. Power Spectral density.....</b>                           | <b>36</b> |
| 8.1. Limit.....                                                 | 36        |
| 8.2. Test Setup .....                                           | 36        |
| 8.3. Test Procedure .....                                       | 36        |
| 8.4. Test Result .....                                          | 37        |
| <b>9. Antenna Requirement.....</b>                              | <b>40</b> |
| <b>10. TEST SETUP &amp; EUT PHOTOGRAPH .....</b>                | <b>41</b> |

## Revision History of This Test Report

[illegible]

## 1. General Information

### 1.1. Description of Device (EUT)

EUT Name : Vintage Retro Portable Radio

Model No. : JX1107, JX1107-1, JX1107-2, JX1107-3

Model Difference : All the model are the same circuit and RF module, only the names are different.  
Test sample model: JX1107

Power supply : DC 5V charging from adapter  
DC 3.7V by battery

Operation frequency : 2402-2480MHz

Modulation : GFSK

Antenna Type : PCB antenna, Maximum Gain is 2.27dBi

Intend use environment : Residential, commercial and light industrial environment

### 1.2. Channel List

| Channel | Frequency<br>(MHz) | Channel   | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) |
|---------|--------------------|-----------|--------------------|---------|--------------------|
| 00      | <b>2402</b>        | 14        | 2430               | 28      | 2458               |
| 01      | 2404               | 15        | 2432               | 29      | 2460               |
| 02      | 2406               | 16        | 2434               | 30      | 2462               |
| 03      | 2408               | 17        | 2436               | 31      | 2464               |
| 04      | 2410               | 18        | 2438               | 32      | 2466               |
| 05      | 2412               | <b>19</b> | <b>2440</b>        | 33      | 2468               |
| 06      | 2414               | 20        | 2442               | 34      | 2470               |
| 07      | 2416               | 21        | 2444               | 35      | 2472               |
| 08      | 2418               | 22        | 2446               | 36      | 2474               |
| 09      | 2420               | 23        | 2448               | 37      | 2476               |
| 10      | 2422               | 24        | 2450               | 38      | 2478               |
| 11      | 2424               | 25        | 2452               | 39      | <b>2480</b>        |
| 12      | 2426               | 26        | 2454               |         |                    |
| 13      | 2428               | 27        | 2456               |         |                    |

### 1.3.Summary of test result

| RF PART                                                                                                                             |                               |        |
|-------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--------|
| Test Items                                                                                                                          | Test Requirement              | Result |
| Antenna requirement                                                                                                                 | FCC part 15.203/15.247 (b)(4) | PASS   |
| AC Power Line Conducted Emission                                                                                                    | FCC part 15.207               | PASS   |
| Conducted Peak Output Power                                                                                                         | FCC part 15.247 (b)(3)        | PASS   |
| Channel Bandwidth& 99% OCB                                                                                                          | FCC part 15.247 (a)(2)        | PASS   |
| Power Spectral Density                                                                                                              | FCC part 15.247 (e)           | PASS   |
| Band Edge                                                                                                                           | FCC part 15.247(d)            | PASS   |
| Spurious Emission                                                                                                                   | FCC part 15.205/15.209        | PASS   |
| Remark:<br>N/A is an abbreviation for Not Applicable.<br>Measurement Uncertainty is not taken into account for conformity statement |                               |        |

### 1.4.Special Accessories and Auxiliary Equipment

| Description | Manufacturer | Model No.     | Hardware Version | Software Version |
|-------------|--------------|---------------|------------------|------------------|
| Adapter     | /            | /             | /                | /                |
| PC          | DELL         | Inspiron 3670 |                  |                  |

### 1.5.Test mode

The special RF test software was used to control EUT work in Continuous BLE TX mode, and select test channel, wireless mode.


| Test mode                                      | Low channel | Middle channel | High channel |
|------------------------------------------------|-------------|----------------|--------------|
| GFSK                                           | 2402MHz     | 2440MHz        | 2480MHz      |
| Note: Only the worst Data Record in the report |             |                |              |

### 1.6. Test configuration


|                                                                                                                                                                                                                                       |                                                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                     | Keep the EUT in continuously transmitting mode. |
| Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. |                                                 |
| Test Software                                                                                                                                                                                                                         | BT_Test_Tool_V1.7.9                             |
| Power level setup                                                                                                                                                                                                                     | 4 dBm                                           |

## 1.7. Block Diagram


### Conducted Emission



### Radiated Emission



### RF Conducted Test



## 1.8. Test Conditions

| Category          | Normal Conditions           | Extreme Conditions |
|-------------------|-----------------------------|--------------------|
| Temperature range | 15-35°C                     | N/A                |
| Humidity range    | 20-75%                      | N/A                |
| Pressure range    | 86-106kPa                   | N/A                |
| Power supply      | DC 5V charging from adapter | N/A                |

Note: N/A is an abbreviation for Not Applicable.

## 1.9. Measurement Uncertainty (95% confidence levels, k=2)

| Parameter                                                                                       | Uncertainty              |
|-------------------------------------------------------------------------------------------------|--------------------------|
| RF output power, conducted                                                                      | ±1.0dB                   |
| Power Spectral Density, conducted                                                               | ±2.2dB                   |
| Radio Frequency                                                                                 | ± 1 x 10 <sup>-6</sup>   |
| Bandwidth                                                                                       | ± 1.5 x 10 <sup>-6</sup> |
| Time                                                                                            | ±2%                      |
| Duty Cycle                                                                                      | ±2%                      |
| Temperature                                                                                     | ±1°C                     |
| Humidity                                                                                        | ±5%                      |
| DC and low frequency voltages                                                                   | ±3%                      |
| Conducted Emissions (150kHz~30MHz)                                                              | ±3.64dB                  |
| Radiated Emission(9KHz~30MHz)                                                                   | ±4.51dB                  |
| Radiated Emission(30MHz~1GHz)                                                                   | ±5.03dB                  |
| Radiated Emission(1GHz~25GHz)                                                                   | ±4.74dB                  |
| Remark: When making a conformity declaration based on test results for regulations/standards or |                          |

specifications,the default is to use Clause 4.2.1of ILAC-G8:09/2019 and the guidelines on decision rules and conformity declaration in IEC Guide 115:2023.

## 1.10.Test Facility

|                                   |   |                                                                                                                                                                                                                 |
|-----------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Site Description                  |   |                                                                                                                                                                                                                 |
| Name of Firm                      | : | Shenzhen NTT Testing Technology Co.,Ltd.                                                                                                                                                                        |
| Site Location                     | : | 1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park, No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, Guangdong, China |
| FCC Designation Number            | : | CN3446                                                                                                                                                                                                          |
| FCC Test Firm Registration Number | : | 129414                                                                                                                                                                                                          |

## 1.11. Test Equipment

### Conducted Test Site

| Name              | Model No.     | Serial No. | Manufacturer | Date of Cal. | Due Date  |
|-------------------|---------------|------------|--------------|--------------|-----------|
| 944 Shielded Room | HSRCE944      | /          | HTEC         | 2025/4/30    | 2028/4/29 |
| EMI Test Receiver | ESPI          | /          | RS           | 2025/9/8     | 2026/9/7  |
| LISN              | NNLK 8129     | 00603      | Schwarzbeck  | 2025/9/8     | 2026/9/7  |
| LISN              | NNHV 8123-400 | 00694      | Schwarzbeck  | 2025/9/8     | 2026/9/7  |
| LISN              | NNHV 8123-400 | 00680      | Schwarzbeck  | 2025/9/8     | 2026/9/7  |
| Cable             | RG223-1500MM  | NA         | RG           | 2025/9/8     | 2026/9/7  |

### Radiated Test Site(Below 1G and Above 1G)&RF Test Site

| Name                                                | Model No.   | Serial No.     | Manufacturer    | Date of Cal. | Due Date  |
|-----------------------------------------------------|-------------|----------------|-----------------|--------------|-----------|
| 966 Shielded Room                                   | 966 Room    | /              | EMToni          | 2025/7/24    | 2028/7/23 |
| EMI Test Receiver                                   | ESCI        | 101018         | RS              | 2025/9/8     | 2026/9/7  |
| Amplifier<br>(30MHz-1GHz)                           | BBV 9718D   | 00042          | SCHWARZBECK     | 2025/9/8     | 2026/9/7  |
| Bilog Antenna<br>(30MHz-1GHz)                       | VULB9168    | 1858           | SCHWARZBECK     | 2025/9/9     | 2026/9/8  |
| Horn antenna<br>(1GHz-18GHz)                        | BBHA 9120 D | 02622          | SCHWARZBECK     | 2025/9/9     | 2026/9/8  |
| Preamplifier<br>(1GHz-18GHz)                        | BBV 9718D   | 0024           | SCHWARZBECK     | 2025/9/8     | 2026/9/7  |
| Spectrum Analyzer<br>(10Hz-40GHz)                   | FSV 40      | 100952         | Rohde & Schwarz | 2025/9/8     | 2026/9/7  |
| Preamplifier<br>(18GHz-40GHz)                       | BBV 9721    | 0056           | SCHWARZBECK     | 2025/9/8     | 2026/9/7  |
| Double Ridge Guide<br>Horn Antenna<br>(18GHz-40GHz) | SAS-574     | 588            | A.H.System      | 2025/9/8     | 2026/9/7  |
| Loop Antenna<br>(9KHz-30MHz)                        | FMZB1519B   | 014            | SCHWARZBECK     | 2025/9/8     | 2026/9/7  |
| Amplifier<br>(9KHz-30MHz)                           | CVP 9222 C  | 00109          | SCHWARZBECK     | 2025/9/8     | 2026/9/7  |
| MXG Signal Analyzer                                 | N9020A      | MY505102<br>02 | Agilent         | 2025/9/8     | 2026/9/7  |

|                             |                   |                |         |          |          |
|-----------------------------|-------------------|----------------|---------|----------|----------|
| MXG Vector Signal Generator | N5182A            | MY501400<br>20 | Agilent | 2025/9/8 | 2026/9/7 |
| MXG Analog Signal Generator | N5181A            | MY474209<br>19 | Agilent | 2025/9/8 | 2026/9/7 |
| Power Sensor                | TR1029-2          | 512364         | Techoy  | 2025/9/8 | 2026/9/7 |
| RF Swith                    | TR1029-1          | 512364         | Techoy  | 2025/9/8 | 2026/9/7 |
| Cable                       | DA800-<br>4000MM  | NA             | DA      | 2025/9/8 | 2026/9/7 |
| Cable                       | DA800-<br>11000MM | NA             | DA      | 2025/9/8 | 2026/9/7 |

## Test software

| Item | Name                         | Manufacturer | Model  | Software version   |
|------|------------------------------|--------------|--------|--------------------|
| 1    | EMC Conduction Test System   | FALA         | EZ-EMC | Ver.EMC-CON 3A1.1+ |
| 2    | EMC radiation test system    | FALA         | EZ-EMC | Ver.FA-03A2 RE+    |
| 3    | RF test system               | TACHOY       | RFTest | V1.0.0             |
| 4    | RF communication test system | TACHOY       | RFTest | V1.0.0             |

## 2. Conducted emission at the mains terminals test


### 2.1.Limit

|                       |                                                                      |
|-----------------------|----------------------------------------------------------------------|
| Test Requirement:     | FCC Part15 C Section 15.207                                          |
| Test Method:          | ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 |
| Test Frequency Range: | 150KHz to 30MHz                                                      |
| Receiver setup:       | RBW=9KHz, VBW=30KHz, Sweep time=auto                                 |

| Frequency<br>MHz | Limits dB(μV)    |               |
|------------------|------------------|---------------|
|                  | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50      | 66 ~ 56*         | 56 ~ 46*      |
| 0.50 ~ 5.00      | 56               | 46            |
| 5.00 ~ 30.00     | 60               | 50            |

Notes: 1. \*Decreasing linearly with logarithm of frequency.  
2. The lower limit shall apply at the transition frequencies.

### 2.2.Test Setup




### 2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. For the actual test configuration, please refer to the related Item - EUT Test Photos.

## 2.4.Test Result

| Conducted Emission At The Mains Terminals Test Data |                                          |                    |            |
|-----------------------------------------------------|------------------------------------------|--------------------|------------|
| Temperature:                                        | 25.1℃                                    | Relative Humidity: | 56%        |
| Pressure:                                           | 1008hPa                                  | Phase :            | Line       |
| Test Voltage :                                      | DC 5V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |




| No. | Mk. | Freq.   | Reading Level | Correct Factor | Measurement | Limit | Over   |          |
|-----|-----|---------|---------------|----------------|-------------|-------|--------|----------|
|     |     | MHz     | dBuV          | dB             | dBuV        | dBuV  | dB     | Detector |
| 1   |     | 0.6540  | 40.89         | 10.46          | 51.35       | 56.00 | -4.65  | QP       |
| 2   | *   | 0.6540  | 33.99         | 10.46          | 44.45       | 46.00 | -1.55  | AVG      |
| 3   |     | 1.9700  | 34.49         | 10.47          | 44.96       | 56.00 | -11.04 | QP       |
| 4   |     | 1.9700  | 27.22         | 10.47          | 37.69       | 46.00 | -8.31  | AVG      |
| 5   |     | 3.6540  | 36.35         | 10.49          | 46.84       | 56.00 | -9.16  | QP       |
| 6   |     | 3.6540  | 24.53         | 10.49          | 35.02       | 46.00 | -10.98 | AVG      |
| 7   |     | 7.1220  | 43.40         | 10.55          | 53.95       | 60.00 | -6.05  | QP       |
| 8   |     | 7.1220  | 30.38         | 10.55          | 40.93       | 50.00 | -9.07  | AVG      |
| 9   |     | 8.0659  | 42.90         | 10.54          | 53.44       | 60.00 | -6.56  | QP       |
| 10  |     | 8.0659  | 31.54         | 10.54          | 42.08       | 50.00 | -7.92  | AVG      |
| 11  |     | 24.0020 | 29.58         | 11.22          | 40.80       | 60.00 | -19.20 | QP       |
| 12  |     | 24.0020 | 25.50         | 11.22          | 36.72       | 50.00 | -13.28 | AVG      |

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(GFSK) in the report

| Conducted Emission At The Mains Terminals Test Data |                                          |                    |            |
|-----------------------------------------------------|------------------------------------------|--------------------|------------|
| Temperature:                                        | 25.1°C                                   | Relative Humidity: | 56%        |
| Pressure:                                           | 1008hPa                                  | Phase :            | Neutral    |
| Test Voltage :                                      | DC 5V from Adapter Input<br>AC 120V/60Hz | Test Mode:         | GFSK(CH00) |



| No. Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|---------|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1       | 0.6540       | 36.02                    | 10.46                   | 46.48                    | 56.00         | -9.52      | QP       |
| 2 *     | 0.6540       | 29.70                    | 10.46                   | 40.16                    | 46.00         | -5.84      | AVG      |
| 3       | 1.9700       | 30.92                    | 10.47                   | 41.39                    | 56.00         | -14.61     | QP       |
| 4       | 1.9700       | 22.51                    | 10.47                   | 32.98                    | 46.00         | -13.02     | AVG      |
| 5       | 3.4740       | 31.35                    | 10.49                   | 41.84                    | 56.00         | -14.16     | QP       |
| 6       | 3.4740       | 23.84                    | 10.49                   | 34.33                    | 46.00         | -11.67     | AVG      |
| 7       | 5.1619       | 35.10                    | 10.51                   | 45.61                    | 60.00         | -14.39     | QP       |
| 8       | 5.1619       | 25.30                    | 10.51                   | 35.81                    | 50.00         | -14.19     | AVG      |
| 9       | 7.1339       | 40.46                    | 10.55                   | 51.01                    | 60.00         | -8.99      | QP       |
| 10      | 7.1339       | 27.48                    | 10.55                   | 38.03                    | 50.00         | -11.97     | AVG      |
| 11      | 24.0020      | 28.37                    | 11.22                   | 39.59                    | 60.00         | -20.41     | QP       |
| 12      | 24.0020      | 23.54                    | 11.22                   | 34.76                    | 50.00         | -15.24     | AVG      |

Note:

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Margin = Reading level + Correct Factor - Limit
3. All the modes have tested and recorded the worst mode(GFSK) in the report

### 3. Radiated Spurious Emissions

#### 3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247  
 Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;  
 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024  
 Test Result: PASS  
 Measurement Distance: 3m

| Frequency    | Detector   | RBW    | VBW    | Value      |
|--------------|------------|--------|--------|------------|
| 9KHz-150KHz  | Quasi-peak | 200Hz  | 600Hz  | Quasi-peak |
| 150KHz-30MHz | Quasi-peak | 9KHz   | 30KHz  | Quasi-peak |
| 30MHz-1GHz   | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
| Above 1GHz   | Peak       | 1MHz   | 3MHz   | Peak       |
|              | Peak       | 1MHz   | 10Hz   | Average    |


Limit:

| Frequency (MHz) | Field Strength        |              | Field Strength Limit at 3m Measurement Dist |                                    |
|-----------------|-----------------------|--------------|---------------------------------------------|------------------------------------|
|                 | uV/m                  | Distance (m) | uV/m                                        | dBuV/m                             |
| 0.009 ~ 0.490   | $2400/F(\text{kHz})$  | 300          | $10000 * 2400/F(\text{kHz})$                | $20\log(2400/F(\text{kHz})) + 80$  |
| 0.490 ~ 1.705   | $24000/F(\text{kHz})$ | 30           | $100 * 24000/F(\text{kHz})$                 | $20\log(24000/F(\text{kHz})) + 40$ |
| 1.705 ~ 30      | 30                    | 30           | $100 * 30$                                  | $20\log(30) + 40$                  |
| 30 ~ 88         | 100                   | 3            | 100                                         | $20\log(100)$                      |
| 88 ~ 216        | 150                   | 3            | 150                                         | $20\log(150)$                      |
| 216 ~ 960       | 200                   | 3            | 200                                         | $20\log(200)$                      |
| Above 960       | 500                   | 3            | 500                                         | $20\log(500)$                      |


### 3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.



The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 3.3.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high - pass filter is used during radiated emissions above 1GHz measurement.


### 3.4.Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 1GHz

| Radiation Emission Test Data |         |                    |            |
|------------------------------|---------|--------------------|------------|
| Temperature:                 | 25.1℃   | Relative Humidity: | 56%        |
| Pressure:                    | 1008hPa | Phase :            | Horizontal |
| Test Voltage :               | DC 5V   | Test Mode:         | GFSK(CH00) |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 47.7422      | 31.19                    | -6.32                   | 24.87                      | 40.00         | -15.13     | QP       |
| 2   |     | 127.4409     | 33.98                    | -6.00                   | 27.98                      | 43.50         | -15.52     | QP       |
| 3   | *   | 174.7301     | 38.43                    | -3.80                   | 34.63                      | 43.50         | -8.87      | QP       |
| 4   |     | 259.2338     | 40.26                    | -4.34                   | 35.92                      | 46.00         | -10.08     | QP       |
| 5   |     | 408.9460     | 36.36                    | -0.74                   | 35.62                      | 46.00         | -10.38     | QP       |
| 6   |     | 585.8157     | 26.32                    | 3.56                    | 29.88                      | 46.00         | -16.12     | QP       |

Note:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(GFSK) in the report

| Radiation Emission Test Data |         |                    |            |
|------------------------------|---------|--------------------|------------|
| Temperature:                 | 25.1°C  | Relative Humidity: | 56%        |
| Pressure:                    | 1008hPa | Phase :            | Vertical   |
| Test Voltage :               | DC 5V   | Test Mode:         | GFSK(CH00) |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   | !   | 41.8596      | 40.65                    | -5.97                   | 34.68                      | 40.00         | -5.32      | QP       |
| 2   |     | 47.7422      | 38.65                    | -6.32                   | 32.33                      | 40.00         | -7.67      | QP       |
| 3   | !   | 167.9992     | 45.77                    | -3.37                   | 42.40                      | 43.50         | -1.10      | QP       |
| 4   | *   | 174.7301     | 46.30                    | -3.80                   | 42.50                      | 43.50         | -1.00      | QP       |
| 5   |     | 225.3080     | 42.99                    | -5.59                   | 37.40                      | 46.00         | -8.60      | QP       |
| 6   |     | 560.6928     | 30.85                    | 2.79                    | 33.64                      | 46.00         | -12.36     | QP       |

Note:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

2. All the modes have tested and recorded the worst mode(GFSK) in the report

1GHz~25GHz

| Polar<br>(H/V)      | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|---------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                     | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| Low Channel:2402MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                   | 4804      | 52.91            | 34.12             | 5.03          | 32.39             | 56.21             | 74       | -17.79 | Pk               |
| V                   | 4804      | 40.01            | 34.12             | 5.03          | 32.39             | 43.31             | 54       | -10.69 | AV               |
| V                   | 7206      | 48.83            | 32.54             | 6.29          | 35.86             | 58.44             | 74       | -15.56 | Pk               |
| V                   | 7206      | 35.47            | 32.54             | 6.29          | 35.86             | 45.08             | 54       | -8.92  | AV               |
| V                   | 9608      | 48.64            | 32.98             | 7.55          | 38.4              | 61.61             | 74       | -12.39 | Pk               |
| V                   | 9608      | 34.37            | 32.98             | 7.55          | 38.4              | 47.34             | 54       | -6.66  | AV               |
| V                   | 12010     | 44.87            | 32.09             | 8.93          | 39                | 60.71             | 74       | -13.29 | Pk               |
| V                   | 12010     | 28.47            | 32.09             | 8.93          | 39                | 44.31             | 54       | -9.69  | AV               |
| H                   | 4804      | 49.20            | 34.12             | 5.03          | 32.39             | 52.50             | 74       | -21.50 | Pk               |
| H                   | 4804      | 40.10            | 34.12             | 5.03          | 32.39             | 43.40             | 54       | -10.60 | AV               |
| H                   | 7206      | 47.40            | 32.54             | 6.29          | 35.86             | 57.01             | 74       | -16.99 | Pk               |
| H                   | 7206      | 33.60            | 32.54             | 6.29          | 35.86             | 43.21             | 54       | -10.79 | AV               |
| H                   | 9608      | 48.64            | 32.98             | 7.55          | 38.4              | 61.61             | 74       | -12.39 | Pk               |
| H                   | 9608      | 31.08            | 32.98             | 7.55          | 38.4              | 44.05             | 54       | -9.95  | AV               |
| H                   | 12010     | 38.60            | 32.09             | 8.93          | 39                | 54.44             | 74       | -19.56 | Pk               |
| H                   | 12010     | 26.64            | 32.09             | 8.93          | 39                | 42.48             | 54       | -11.52 | AV               |

| Polar<br>(H/V)         | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                        | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| Middle Channel:2440MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                      | 4880      | 49.98            | 34.07             | 5.09          | 32.59             | 53.59             | 74       | -20.41 | Pk               |
| V                      | 4880      | 38.34            | 34.07             | 5.09          | 32.59             | 41.95             | 54       | -12.05 | AV               |
| V                      | 7320      | 45.25            | 32.63             | 6.34          | 35.96             | 54.92             | 74       | -19.08 | Pk               |
| V                      | 7320      | 36.15            | 32.63             | 6.34          | 35.96             | 45.82             | 54       | -8.18  | AV               |
| V                      | 9760      | 42.36            | 32.92             | 7.59          | 38.4              | 55.43             | 74       | -18.57 | Pk               |
| V                      | 9760      | 30.49            | 32.92             | 7.59          | 38.4              | 43.56             | 54       | -10.44 | AV               |
| V                      | 12200     | 41.83            | 31.96             | 8.88          | 39.04             | 57.79             | 74       | -16.21 | Pk               |
| V                      | 12200     | 29.13            | 31.96             | 8.88          | 39.04             | 45.09             | 54       | -8.91  | AV               |
| H                      | 4880      | 49.26            | 34.07             | 5.09          | 32.59             | 52.87             | 74       | -21.13 | Pk               |
| H                      | 4880      | 39.13            | 34.07             | 5.09          | 32.59             | 42.74             | 54       | -11.26 | AV               |
| H                      | 7320      | 46.90            | 32.63             | 6.34          | 35.96             | 56.57             | 74       | -17.43 | Pk               |
| H                      | 7320      | 34.64            | 32.63             | 6.34          | 35.96             | 44.31             | 54       | -9.69  | AV               |
| H                      | 9760      | 42.54            | 32.92             | 7.59          | 38.4              | 55.61             | 74       | -18.39 | Pk               |
| H                      | 9760      | 30.05            | 32.92             | 7.59          | 38.4              | 43.12             | 54       | -10.88 | AV               |
| H                      | 12200     | 39.64            | 31.96             | 8.88          | 39.04             | 55.60             | 74       | -18.40 | Pk               |
| H                      | 12200     | 30.72            | 31.96             | 8.88          | 39.04             | 46.68             | 54       | -7.32  | AV               |

| Polar<br>(H/V)       | Frequency | Meter<br>Reading | Pre-ampli<br>fier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|----------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                      | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| High Channel:2480MHz |           |                  |                   |               |                   |                   |          |        |                  |
| V                    | 4960      | 49.01            | 34.02             | 5.15          | 32.8              | 52.94             | 74       | -21.06 | Pk               |
| V                    | 4960      | 35.05            | 34.02             | 5.15          | 32.8              | 38.98             | 54       | -15.02 | AV               |
| V                    | 7440      | 44.61            | 32.71             | 6.4           | 36.05             | 54.35             | 74       | -19.65 | Pk               |
| V                    | 7440      | 36.31            | 32.71             | 6.4           | 36.05             | 46.05             | 54       | -7.95  | AV               |
| V                    | 9920      | 41.80            | 32.86             | 7.62          | 38.4              | 54.96             | 74       | -19.04 | Pk               |
| V                    | 9920      | 31.14            | 32.86             | 7.62          | 38.4              | 44.30             | 54       | -9.70  | AV               |
| V                    | 12400     | 38.28            | 31.82             | 8.84          | 39.08             | 54.38             | 74       | -19.62 | Pk               |
| V                    | 12400     | 27.35            | 31.82             | 8.84          | 39.08             | 43.45             | 54       | -10.55 | AV               |
| H                    | 4960      | 48.91            | 34.02             | 5.15          | 32.8              | 52.84             | 74       | -21.16 | Pk               |
| H                    | 4960      | 38.94            | 34.02             | 5.15          | 32.8              | 42.87             | 54       | -11.13 | AV               |
| H                    | 7440      | 44.96            | 32.71             | 6.4           | 36.05             | 54.70             | 74       | -19.30 | Pk               |
| H                    | 7440      | 30.79            | 32.71             | 6.4           | 36.05             | 40.53             | 54       | -13.47 | AV               |
| H                    | 9920      | 41.39            | 32.86             | 7.62          | 38.4              | 54.55             | 74       | -19.45 | Pk               |
| H                    | 9920      | 27.00            | 32.86             | 7.62          | 38.4              | 40.16             | 54       | -13.84 | AV               |
| H                    | 12400     | 40.64            | 31.82             | 8.84          | 39.08             | 56.74             | 74       | -17.26 | Pk               |
| H                    | 12400     | 29.38            | 31.82             | 8.84          | 39.08             | 45.48             | 54       | -8.52  | AV               |

Note: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
 Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

All the modes have tested and recorded the worst mode(GFSK) in the report.

The 1-25GHz range has been tested, and the report only records the worst performance of the 1-18G range.

## Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

|                                                                                                                            | Polar<br>(H/V)        | Frequenc<br>y<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBuV<br>/m) | Margi<br>n<br>(dB) | Detec<br>tor<br>Type |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------|------------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-----------------------|--------------------|----------------------|
| GFSK                                                                                                                       | Low Channel: 2402MHz  |                        |                            |                           |                       |                             |                               |                       |                    |                      |
|                                                                                                                            | H                     | 2390                   | 57.55                      | 35.17                     | 3.48                  | 27.49                       | 53.35                         | 74                    | -20.65             | PK                   |
|                                                                                                                            | H                     | 2390                   | 51.49                      | 35.17                     | 3.48                  | 27.49                       | 47.29                         | 54                    | -6.71              | AV                   |
|                                                                                                                            | H                     | 2400                   | 61.50                      | 35.16                     | 3.49                  | 27.52                       | 57.35                         | 74                    | -16.65             | PK                   |
|                                                                                                                            | H                     | 2400                   | 49.02                      | 35.16                     | 3.49                  | 27.52                       | 44.87                         | 54                    | -9.13              | AV                   |
|                                                                                                                            | V                     | 2390                   | 59.50                      | 35.17                     | 3.48                  | 27.49                       | 55.30                         | 74                    | -18.70             | PK                   |
|                                                                                                                            | V                     | 2390                   | 52.52                      | 35.17                     | 3.48                  | 27.49                       | 48.32                         | 54                    | -5.68              | AV                   |
|                                                                                                                            | V                     | 2400                   | 59.71                      | 35.16                     | 3.49                  | 27.52                       | 55.56                         | 74                    | -18.44             | PK                   |
|                                                                                                                            | V                     | 2400                   | 51.22                      | 35.16                     | 3.49                  | 27.52                       | 47.07                         | 54                    | -6.93              | AV                   |
|                                                                                                                            | High Channel: 2480MHz |                        |                            |                           |                       |                             |                               |                       |                    |                      |
|                                                                                                                            | H                     | 2483.5                 | 57.93                      | 35.11                     | 3.56                  | 27.75                       | 54.13                         | 74                    | -19.87             | PK                   |
|                                                                                                                            | H                     | 2483.5                 | 48.69                      | 35.11                     | 3.56                  | 27.75                       | 44.89                         | 54                    | -9.11              | AV                   |
|                                                                                                                            | H                     | 2500                   | 61.62                      | 35.1                      | 3.57                  | 27.8                        | 57.89                         | 74                    | -16.11             | PK                   |
|                                                                                                                            | H                     | 2500                   | 49.45                      | 35.1                      | 3.57                  | 27.8                        | 45.72                         | 54                    | -8.28              | AV                   |
|                                                                                                                            | V                     | 2483.5                 | 57.51                      | 35.11                     | 3.56                  | 27.75                       | 53.71                         | 74                    | -20.29             | PK                   |
|                                                                                                                            | V                     | 2483.5                 | 50.23                      | 35.11                     | 3.56                  | 27.75                       | 46.43                         | 54                    | -7.57              | AV                   |
|                                                                                                                            | V                     | 2500                   | 60.22                      | 35.1                      | 3.57                  | 27.8                        | 56.49                         | 74                    | -17.51             | PK                   |
|                                                                                                                            | V                     | 2500                   | 50.12                      | 35.1                      | 3.57                  | 27.8                        | 46.39                         | 54                    | -7.61              | AV                   |
| Remark:<br>1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit |                       |                        |                            |                           |                       |                             |                               |                       |                    |                      |

## 4. Conducted Spurious Emissions

### 4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247  
 Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;


ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to  
C63.10a-2024  
PASS

Test Result:

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

## 4.2. Test Setup



## 4.3. Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
  - a) Set instrument center frequency to DTS channel center frequency.
  - b) Set the span to 1.5 times the DTS bandwidth.
  - c) Set the RBW = 100 kHz.
  - d) Set the VBW  $\geq [3 \times \text{RBW}]$ .
  - e) Detector = peak.
  - f) Sweep time = auto couple.
  - g) Trace mode = max hold.
  - h) Allow trace to fully stabilize.
  - i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

## 4.4. Test Result


1M:

### RF Conducted Spurious Emissions Graphs


GFSK/LCH



GFSK/MCH




GFSK/HCH




2M:

RF Conducted Spurious Emissions Graphs


GFSK/LCH



GFSK/MCH



GFSK/HCH



## 5. Band Edge Measurement

### 5.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;

ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which

the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting

### 5.2.Test setup




### 5.3.Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

## 5.4.Test Result

1M:



2M:




## 6. -6 dB Bandwidth and 99% Bandwidth Measurement

### 6.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

### 6.2.Test Setup



### 6.3.Test Procedure

#### For 6dB Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2.The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1(i.e, RBW= 100 kHz VBW>3 x RBW,and peak detector with maximum hold) is implemented by the instrumentation function.When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.
3. The steps for the first option are as follows:
  - a.Set RBW= shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
  - b.Set the VBW[3 x RBW].
  - c.Detector = peak
  - d.Trace mode = max-hold.
  - e.Sweep = No faster than coupled (auto) time.
  - f.Allow the trace to stabilize.
  - g.Measure the maximum width of the emission by placing two markers, one at the lowest frequencyand the other at the highest frequency of the envelope of the spectral display, such that each markeris at or slightly below the "-6 dB down amplitude". If a marker is below this "-6 dB down amplitude?" value, then it shall be as close as possible to this value.

#### For 99% Bandwidth Measurement

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1%-5% OBW, VBW  $\geq 3$ RBW