FCC TEST REPORT

FCC ID: 2BXRV-T3PRO

Product	:	Multifunctional Portable PA System
Model Name	:	T3 Pro
Brand	:	musiccube
Report No.	:	PTC26073034401E-FC02

Prepared for

Shenzhen Liping Technology CO.,LTD.

9F, Bldg 2, Baolong Specialized & Sophisticated Industrial Park, Longgang, Shenzhen, China

Prepared by

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

1 TEST RESULT CERTIFICATION

Applicant's name	:	Shenzhen Liping Technology CO.,LTD.
Address	:	9F, Bldg 2, Baolong Specialized & Sophisticated Industrial Park, Longgang, Shenzhen, China
Manufacture's name	:	Shenzhen Liping Technology CO.,LTD.
Address	:	9F, Bldg 2, Baolong Specialized & Sophisticated Industrial Park, Longgang, Shenzhen, China
Product name	:	Multifunctional Portable PA System
Model name	:	T3 Pro
Standards	:	FCC CFR47 Part 15 Section 15.247
Test procedure	:	ANSI C63.10-2020
Test Date	:	August 11, 2026 to September 02, 2026
Date of Issue	:	September 11, 2026
Test Result	:	Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

Jack zhou / Engineer

Technical Manager:

Simon Pu / Manager

Contents

Page

1 TEST RESULT CERTIFICATION 2

2 TEST SUMMARY 5

2.1 TEST SITE 6

3 GENERAL INFORMATION 7

3.1 GENERAL DESCRIPTION OF E.U.T. 7

3.2 CHANNEL LIST 8

4 EQUIPMENT DURING TEST 9

4.1 EQUIPMENTS LIST 9

4.2 MEASUREMENT UNCERTAINTY 11

4.3 DESCRIPTION OF SUPPORT UNITS 12

5 CONDUCTED EMISSION 13

5.1 E.U.T. OPERATION 13

5.2 EUT SETUP 13

5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 14

5.4 MEASUREMENT PROCEDURE 14

5.5 CONDUCTED EMISSION LIMIT 14

5.6 MEASUREMENT DESCRIPTION 14

5.7 CONDUCTED EMISSION TEST RESULT 14

6 RADIATED SPURIOUS EMISSIONS 17

6.1 EUT OPERATION 17

6.2 TEST SETUP 18

6.3 SPECTRUM ANALYZER SETUP 20

6.4 TEST PROCEDURE 21

6.5 SUMMARY OF TEST RESULTS 23

7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT 31

7.1 TEST PROCEDURE 31

7.2 TEST SETUP 31

7.3 TEST RESULT 32

8 6DB BANDWIDTH MEASUREMENT 45

TEST PROCEDURE 45

TEST SETUP 45

TEST RESULT 45

9 MAXIMUM PEAK OUTPUT POWER 49

9.1 TEST PROCEDURE 49

9.2TEST SETUP 49

9.3 TEST RESULT 49

10 POWER SPECTRAL DENSITY 53

10.1 TEST PROCEDURE 53

10.2 TEST SETUP 53

10.3 TEST RESULT 53

11 ANTENNA APPLICATION 57

11.1 ANTENNA REQUIREMENT 57

11.2 RESULT 57

12 TEST SETUP 58

13 EUT PHOTOS 60

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS

2.1 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Multifunctional Portable PA System
Model Name	:	T3 Pro
Operating frequency	:	2402-2480MHz
Number of Channels	:	40 channels For DTS
Type of Modulation	:	GFSK, For DTS
Antenna installation	:	PCB antenna
Antenna Gain	:	2.24 dBi
Power Supply	:	Input:26V⎓ 4.8A 260W Adapter: Input:100-240V~ 50/60Hz 2.0A Max Output:26.0V⎓ 4.8A 124.8W
Hardware Version	:	2.0
Software Version	:	2.0
Test sample No.	:	PTC26073034401E-1/2,PTC26073034401E-2/2.

3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2020 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	**2402**	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	**2440**	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	**2480**
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.

4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-26.5GHz	Aug.10, 2026	1 Year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug.10, 2026	1 Year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug.10, 2026	1 Year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug.10, 2026	1 Year
DC power Supply	Agilent	E3642A	MY52420017	0-8V,5A/0-20 ,2.5A	Aug.10, 2026	1 Year
Test S/W	Tonscend	JS1120-3	/	/	/	/
6dB Attenuation	/	DC-3GHz	/	0.09MHz-3GHz	Aug.10, 2026	1 Year

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESPI7	101671	9KHz-7GHz	Aug.10, 2026	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	192	9 KHz -30MHz	Nov.27, 2025	1 Year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep.09, 2025	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	9KHz-1GHz	Mar.21, 2026	1 Year
Cable	IMRO	AK-9515E(9m)	Cable-L	9KHz-3GHz	Aug.10, 2026	1 Year

Spectrum Analyzer	Rohde&Schwarz	FSV40	6625-01-588-5515	9KHz-40GHz	Aug.10, 2026	1 Year
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1246	1GHz-18GHz	Dec.11, 2025	1 Year
Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug.10, 2026	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-1066	15GHz-40GHz	Jun. 11, 2026	1 Year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Jun. 08, 2026	1 Year
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug.10, 2026	1 Year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug.10, 2026	1 Year
Test S/W	Tonscend	TS+	/	/	/	/

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Date	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI3	101417	9KHz-3GHz	Aug.10, 2026	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Oct.29, 2025	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Oct.29, 2025	1 Year
Limiter	R&S	ESH3-Z2	0357.8810.54-102808-NB	0Hz-30MHz	Aug.10, 2026	1 Year
RF Switch	DIAMOND ANTENNA	CX-210	/	0.09MHz-6GHz	Mar. 21,2026	1 Year

Test S/W	Tonscend	JS32-CE	/	/	/	/

4.2 Measurement Uncertainty

Parameter	**Uncertainty**
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10^{-6}
Bandwidth	± 1.5 x 10^{-6}
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9kHz~30MHz)	±3.15dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB

4.3 Description of Support Units

Equipment	Model No.	Series No.	Parameters
N/A	N/A	N/A	N/A

5 Conducted Emission

Test Requirement	:	FCC CFR 47 Part 15 Section 15.207
Test Method	:	ANSI C63.10-2020
Test Result	:	PASS
Frequency Range	:	150kHz to 30MHz
Class/Severity	:	Class B

5.1 E.U.T. Operation

Operating Environment :

Temperature	:	25.5 °C
Humidity	:	51 % RH
Atmospheric Pressure	:	101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10-2020. Insulating material thickness for cables that are normally insulated from the ground >0 mm and ≤12 mm.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, Insulating material thickness for cables that are normally insulated from the ground >0 mm and ≤12 mm.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Pass.

All the modulation modes were tested the data of the worst mode (AC 120V/60Hz, GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Line-AC 120V/60Hz



Final Data List											
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.150	36.80	19.48	56.28	66.00	9.72	25.65	45.13	56.00	10.87	PASS
2	0.186	30.33	19.42	49.75	64.21	14.46	10.05	29.47	54.21	24.74	PASS
3	0.398	27.80	19.37	47.17	57.91	10.74	22.19	41.56	47.91	6.35	PASS
4	0.578	22.39	19.40	41.79	56.00	14.21	8.17	27.57	46.00	18.43	PASS
5	0.654	22.26	19.40	41.66	56.00	14.34	7.91	27.31	46.00	18.69	PASS
6	16.575	26.17	19.82	45.99	60.00	14.01	20.91	40.73	50.00	9.27	PASS

Neutral-AC 120V/60Hz



Final Data List											
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Reading [dBµV]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict
1	0.150	36.47	19.41	55.88	66.00	10.12	25.27	44.68	56.00	11.32	PASS
2	0.398	26.89	19.40	46.29	57.91	11.62	22.64	42.04	47.91	5.87	PASS
3	0.488	27.44	19.41	46.85	56.21	9.36	7.67	27.08	46.21	19.13	PASS
4	0.537	27.11	19.41	46.52	56.00	9.48	9.97	29.38	46.00	16.62	PASS
5	0.596	27.17	19.41	46.58	56.00	9.42	11.49	30.90	46.00	15.10	PASS
6	15.792	25.57	19.77	45.34	60.00	14.66	19.97	39.74	50.00	10.26	PASS

Note:QP Margin[dB]= QP Limit[dBµV]- QP Value[dBµV], AV Margin[dB]= AV Limit[dBµV]- AV Value[dBµV].

6 Radiated Spurious Emissions

Test Requirement	:	FCC CFR47 Part 15 Section 15.209 & 15.247
Test Method	:	ANSI C63.10-2020
Test Result	:	PASS
Measurement Distance	:	3m
Limit	:	See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation

Operating Environment :

Temperature	:	23.5 °C
Humidity	:	51.1 % RH
Atmospheric Pressure	:	101.2kPa

6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value

6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2020.

2. Where floor-standing equipment is not typically installed with its base in direct electrical contact with, or connected to, a metal floor or grid, the EUT shall not be placed in direct electrical contact with the test site (or turntable) reference ground plane. If necessary to prevent direct metallic contact of the EUT and the reference ground plane, insulating material (up to 12 mm thick) shall be placed under the EUT.

3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.

5. Set to the maximum power setting and enable the EUT transmit continuously.

6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.

7. Test Procedure of measurement (For Above 1GHz):

1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).

2) Change the antenna polarization and repeat 1) with vertical polarization.

3) Make a hardcopy of the spectrum.

4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.

5) Change the analyser mode to Clear/ Write and found the cone of emission.

6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.

7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.

8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz

6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (GFSK_2M (CH00: 2402MHz)).

Antenna Polarization: Horizontal GFSK_2M(CH00: 2402MHz)



Final Data List[QP]										
NO.	Freq. [MHz]	QP Reading [dBµV]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	56.43	38.72	-9.29	29.43	40.00	10.57	100	289	Horizonta	PASS
2	139.6	37.05	-9.54	27.51	43.50	15.99	100	59	Horizonta	PASS
3	186.1	44.46	-10.86	33.60	43.50	9.90	100	239	Horizonta	PASS
4	277.5	41.72	-8.27	33.45	46.00	12.55	100	99	Horizonta	PASS
5	311.54	38.78	-7.27	31.51	46.00	14.49	100	329	Horizonta	PASS
6	955.8	30.38	4.57	34.95	46.00	11.05	100	39	Horizonta	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

Antenna Polarization: Vertical GFSK_2M(CH00: 2402MHz)



Final Data List[QP]										
NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	53.52	43.59	-8.95	34.64	40.00	5.36	100	171	Vertical	PASS
2	79.96	48.25	-13.31	34.94	40.00	5.06	100	21	Vertical	PASS
3	103.24	48.88	-12.94	35.94	43.50	7.56	100	301	Vertical	PASS
4	131.61	46.53	-10.23	36.30	43.50	7.20	100	61	Vertical	PASS
5	143.25	47.37	-9.49	37.88	43.50	5.62	100	321	Vertical	PASS
6	188.11	41.53	-11.04	30.49	43.50	13.01	100	151	Vertical	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

Test Frequency 1GHz-25GHz:

Test Mode: CH00 GFSK_2M					Test channel:Low Channel (2402MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	44.52	34.04	6.58	34.09	51.05	74	-22.95	V
7206	41.67	37.11	7.73	34.5	52.01	74	-21.99	V
9608	38.75	39.31	9.23	34.79	52.50	74	-21.50	V
4804	45.15	34.04	6.58	34.09	51.68	74	-22.32	H
7206	37.06	37.11	7.73	34.5	47.40	74	-26.60	H
9608	39.15	39.31	9.23	34.79	52.90	74	-21.10	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	33.82	34.04	6.58	34.09	40.35	54	-13.65	V
7206	26.56	37.11	7.73	34.5	36.90	54	-17.10	V
9608	25.72	39.31	9.23	34.79	39.47	54	-14.53	V
4804	33.81	34.04	6.58	34.09	40.34	54	-13.66	H
7206	29.30	37.11	7.73	34.5	39.64	54	-14.36	H
9608	24.71	39.31	9.23	34.79	38.46	54	-15.54	H

Test Mode: CH19 GFSK_2M					Test channel:Middle Channel (2440MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	43.12	34.38	6.69	34.09	50.10	74	-23.90	V
7320	39.68	37.22	7.78	34.53	50.15	74	-23.85	V
9760	34.12	39.46	9.35	34.8	48.13	74	-25.87	V
4880	41.95	34.38	6.69	34.09	48.93	74	-25.07	H
7320	38.03	37.22	7.78	34.53	48.50	74	-25.50	H
9760	37.08	39.46	9.35	34.8	51.09	74	-22.91	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	34.32	34.38	6.69	34.09	41.30	54	-12.70	V
7320	28.34	37.22	7.78	34.53	38.81	54	-15.19	V
9760	23.62	39.46	9.35	34.8	37.63	54	-16.37	V
4880	32.12	34.38	6.69	34.09	39.10	54	-14.90	H
7320	27.18	37.22	7.78	34.53	37.65	54	-16.35	H
9760	23.52	39.46	9.35	34.8	37.53	54	-16.47	H

Test Mode: CH39 GFSK_2M					Test channel:High Channel (2480MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	43.31	34.72	6.79	34.09	50.73	74	-23.27	V
7440	40.12	37.34	7.82	34.57	50.71	74	-23.29	V
9920	34.70	39.62	9.46	34.81	48.97	74	-25.03	V
4960	40.98	34.72	6.79	34.09	48.40	74	-25.60	H
7440	38.31	37.34	7.82	34.57	48.90	74	-25.10	H
9920	36.93	39.62	9.46	34.81	51.20	74	-22.80	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	34.35	34.72	6.79	34.09	41.77	54	-12.23	V
7440	27.18	37.34	7.82	34.57	37.77	54	-16.23	V
9920	23.72	39.62	9.46	34.81	37.99	54	-16.01	V
4960	31.79	34.72	6.79	34.09	39.21	54	-14.79	H
7440	29.00	37.34	7.82	34.57	39.59	54	-14.41	H
9920	25.53	39.62	9.46	34.81	39.80	54	-14.20	H

Note: 1. The testing has been conformed to 10*2480MHz=24800MHz.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit

Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test Mode: GFSK_2M Channel 2402MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2310	55.42	28.67	6.72	37.26	53.55	74	-20.45	H	Peak
2390	55.77	28.08	6.81	37.12	53.54	74	-20.46	H	Peak
2310	33.79	28.67	6.72	37.26	31.92	54	-22.08	H	AV
2390	34.10	28.08	6.81	37.12	31.87	54	-22.13	H	AV
2310	57.44	28.67	6.72	37.26	55.57	74	-18.43	V	Peak
2390	54.86	28.08	6.81	37.12	52.63	74	-21.37	V	Peak
2310	35.97	28.67	6.72	37.26	34.10	54	-19.90	V	AV
2390	36.19	28.08	6.81	37.12	33.96	54	-20.04	V	AV

Test Mode: GFSK_2M Channel 2480MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.5	53.94	27.38	6.15	36.29	51.18	74	-22.82	H	Peak
2500	53.94	27.43	6.68	36.79	51.26	74	-22.74	H	Peak
2483.5	35.77	27.38	6.15	36.29	33.01	54	-20.99	H	AV
2500	35.16	27.43	6.68	36.79	32.48	54	-21.52	H	AV
2483.5	52.91	27.38	6.15	36.29	50.15	74	-23.85	V	Peak
2500	55.13	27.43	6.68	36.79	52.45	74	-21.55	V	Peak
2483.5	38.50	27.38	6.15	36.29	35.74	54	-18.26	V	AV
2500	38.00	27.43	6.68	36.79	35.32	54	-18.68	V	AV

7 Conduct Band Edge And Spurious Emissions Measurement

Test Requirement	:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	:	ANSI C63.10-2020
Test Limit	:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Setup



7.3 Test Result

Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	-4.81	-4.81	---	PASS
BLE_1M	Ant1	2402	30~1000	-4.81	-54.4	≤-24.81	PASS
BLE_1M	Ant1	2402	1000~26500	-4.81	-41.04	≤-24.81	PASS
BLE_1M	Ant1	2440	0~Reference	-6.27	-6.27	---	PASS
BLE_1M	Ant1	2440	30~1000	-6.27	-54.66	≤-26.27	PASS
BLE_1M	Ant1	2440	1000~26500	-6.27	-42.35	≤-26.27	PASS
BLE_1M	Ant1	2480	0~Reference	-8.09	-8.09	---	PASS
BLE_1M	Ant1	2480	30~1000	-8.09	-54.34	≤-28.09	PASS
BLE_1M	Ant1	2480	1000~26500	-8.09	-42.63	≤-28.09	PASS
BLE_2M	Ant1	2402	0~Reference	-9.83	-9.83	---	PASS
BLE_2M	Ant1	2402	30~1000	-9.83	-54.32	≤-29.83	PASS
BLE_2M	Ant1	2402	1000~26500	-9.83	-41.61	≤-29.83	PASS
BLE_2M	Ant1	2440	0~Reference	-8.01	-8.01	---	PASS
BLE_2M	Ant1	2440	30~1000	-8.01	-55.08	≤-28.01	PASS
BLE_2M	Ant1	2440	1000~26500	-8.01	-42.07	≤-28.01	PASS
BLE_2M	Ant1	2480	0~Reference	-9.61	-9.61	---	PASS
BLE_2M	Ant1	2480	30~1000	-9.61	-54.28	≤-29.61	PASS
BLE_2M	Ant1	2480	1000~26500	-9.61	-42.48	≤-29.61	PASS

Test Graphs：

BLE_1M-Ant1-2402-0~Reference-PASS

BLE_1M-Ant1-2402-30~1000-PASS



BLE_1M-Ant1-2402-1000~26500-PASS



BLE_1M-Ant1-2440-0~Reference-PASS

BLE_1M-Ant1-2440-30~1000-PASS



BLE_1M-Ant1-2440-1000~26500-PASS



BLE_1M-Ant1-2480-0~Reference-PASS

BLE_1M-Ant1-2480-30~1000-PASS



BLE_1M-Ant1-2480-1000~26500-PASS



BLE_2M-Ant1-2402-0~Reference-PASS

BLE_2M-Ant1-2402-30~1000-PASS



BLE_2M-Ant1-2402-1000~26500-PASS



BLE_2M-Ant1-2440-0~Reference-PASS

BLE_2M-Ant1-2440-30~1000-PASS



BLE_2M-Ant1-2440-1000~26500-PASS



BLE_2M-Ant1-2480-0~Reference-PASS

BLE_2M-Ant1-2480-30~1000-PASS



BLE_2M-Ant1-2480-1000~26500-PASS



Band edge:

Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-4.55	-40.69	≤-24.55	PASS
BLE_1M	Ant1	High	2480	-7.84	-41.51	≤-27.84	PASS
BLE_2M	Ant1	Low	2402	-9.20	-39.01	≤-29.2	PASS
BLE_2M	Ant1	High	2480	-8.97	-41.47	≤-28.97	PASS

BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2480-PASS


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.510000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
#Avg Type: RMS
Avg|Hold: 1000/1000
04:32:56 AM Aug 26, 2026
Ref Offset 11.7 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr4 2.543 28 GHz
-41.474 dBm
-28.97 dBm
Start 2.47000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.55000 GHz
Sweep 7.667 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.480 00 GHz -8.972 dBm
2 N 1 f 2.483 50 GHz -43.552 dBm
3 N 1 f 2.500 00 GHz -43.873 dBm
4 N 1 f 2.543 28 GHz -41.474 dBm
Frequency
Auto Tune
Center Freq
2.510000000 GHz
Start Freq
2.470000000 GHz
Stop Freq
2.550000000 GHz
CF Step
8.000000 MHz
Auto
Man
Freq Offset
0 Hz
MSG
STATUS

8 6dB Bandwidth Measurement

Test Requirement	:	FCC CFR47 Part 15 Section 15.247
Test Method	:	ANSI C63.10-2020
Test Limit		Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

Test Setup



Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.712	2401.620	2402.332	0.5	PASS
BLE_1M	Ant1	2440	0.712	2439.628	2440.340	0.5	PASS
BLE_1M	Ant1	2480	0.676	2479.632	2480.308	0.5	PASS
BLE_2M	Ant1	2402	1.136	2401.408	2402.544	0.5	PASS
BLE_2M	Ant1	2440	1.236	2439.336	2440.572	0.5	PASS
BLE_2M	Ant1	2480	1.164	2479.408	2480.572	0.5	PASS