

FCC TEST REPORT

FCC ID:2BXSU-LR-0002

Applicant Name..... : Shenzhen Zhengwei Electronics Co., Ltd.

Address..... : Building 5, Room 309, Hezhou Industrial Zone, Hezhou Village,
Hangcheng Subdistrict, Bao'an District, Shenzhen, China

Manufacturer Name..... : Shenzhen Zhengwei Electronics Co., Ltd.

Address..... : Building 5, Room 309, Hezhou Industrial Zone, Hezhou Village,
Hangcheng Subdistrict, Bao'an District, Shenzhen, China

Product..... : WIRELESS CONTROLLER RECEIVER For PSone/PS1/PS2

Model(s)..... : LR-0002

Additional Model(s)..... : /

Trademark..... : Linkretro

Model Difference..... : /

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai
Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Aug. 17, 2026

Date of Test(s)..... : Aug. 17, 2026 to Sept. 8, 2026

Date of Issue..... : Sept. 8, 2026

Test Requested..... : Select test(s) as requested by the client.

Test Standard(s)..... : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure..... : ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to
C63.10a-2024

In the configuration tested, the EUT complied with the standards specified above.

Prepared by:

Kimi Lu

Kimi Lu/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director



Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.

Table of Contents

	Page
1. TEST SUMMARY	4
2. GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 Test Setup Configuration	7
2.3 Support Equipment	7
2.4 Test Mode	7
3. TEST FACILITY AND TEST INSTRUMENT USED	8
3.1 TEST FACILITY	8
3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
3.3 Testing software	9
3.4 MEASUREMENT UNCERTAINTY	10
4. EMC EMISSION TEST	11
4.1 Conducted emissions	11
4.1.1 POWER LINE CONDUCTED EMISSION Limits	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	11
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 Test Result	13
4.2 Radiated emissions	15
4.2.1 Radiated Emission Limits	15
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
4.2.6 TEST RESULTS	18
5. RADIATED BAND EMISSION MEASUREMENT	26
5.1 Test Requirement	26
5.2 TEST PROCEDURE	26
5.3 DEVIATION FROM TEST STANDARD	27
5.4 TEST SETUP	27
5.5 EUT OPERATING CONDITIONS	27
5.6 TEST RESULT	28
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	30
6.1 Limit	30
6.2 Test Setup	30
6.3 Test procedure	30
6.4 DEVIATION FROM STANDARD	30
6.5 Test Result	31
BAND EDGE	31
BAND EDGE(HOPPING)	38
CONDUCTED RF SPURIOUS EMISSION	45
7. 20DB&99% BANDWIDTH	55
7.1 Test Setup	55
7.2 Limit	55
7.3 Test procedure	55
7.4 DEVIATION FROM STANDARD	55
7.5 Test Result	55
8. MAXIMUM PEAK OUTPUT POWER	66
8.1 Block Diagram Of Test Setup	66
8.2 Limit	66



8.3 Test procedure	66
8.4 DEVIATION FROM STANDARD	66
8.5 Test Result	66
9. HOPPING CHANNEL SEPARATION	67
9.1 Test Setup	72
9.2 Test procedure	72
9.3 DEVIATION FROM STANDARD	72
9.4 Test Result	72
10. NUMBER OF HOPPING FREQUENCY	78
10.1 Test Setup	78
10.2 Test procedure	78
10.3 DEVIATION FROM STANDARD	78
10.4 Test Result	78
11. DWELL TIME	81
11.1 Test Setup	81
11.2 Test procedure	81
11.3 DEVIATION FROM STANDARD	81
11.4 Test Result	82
12. ANTENNA REQUIREMENT	92
13. TEST SETUP PHOTO	93
14. EUT CONSTRUCTIONAL DETAILS	93



1. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	WIRELESS CONTROLLER RECEIVER For PSone/PS1/PS2
Test Model No.:	LR-0002
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz-2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	Chip Antenna
Antenna gain:	1.71dBi
Power supply:	Input:DC 8 V $\pm$ 0.15 A
Sample Number:	260817111YP001
Remark:The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz



2.2 Test Setup Configuration

Conducted Emission




Radiated Emission(30MHz-1GHz)



Radiated Emission(above 1GHz)



RF Conducted Test



2.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo (Beijing) Co., Ltd	ThinkPad E480	/	AE
E-2	USB serial port board	/	/	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) The test software is the FCC Assist 1.0.1.1 which can set the EUT into the individual test modes.TX Power: default value

2.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

3. TEST FACILITY AND TEST INSTRUMENT USED

3.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District
Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	Apr. 24, 2026	Apr. 23, 2027
2	Loop Antenna	TESEQ	HLA6121	58357	July 10, 2026	July 9, 2027
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	Apr. 24, 2026	Apr. 23, 2027
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 8, 2026	May 7, 2027
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	Apr. 25, 2026	Apr. 24, 2027
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	Apr. 25, 2026	Apr. 24, 2027
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	Oct. 20, 2025	Oct. 19, 2026
8	Amplifier	AEROFLEX	100KHz-40GHz	097	Oct. 20, 2025	Oct. 19, 2026
9	Spectrum Analyzer	R&S	FSV40	101413	Apr. 24, 2026	Apr. 23, 2027
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	Apr. 24, 2026	Apr. 23, 2027
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	Apr. 24, 2026	Apr. 23, 2027
12	Single Generator	Agilent	N5182A	MY48180575	Apr. 24, 2026	Apr. 23, 2027
13	Power Sensor	MWRFTest	MW100-RFCB	/	Apr. 24, 2026	Apr. 23, 2027
14	Power Amplifier Shielding Room	EMToni	2m3m3m	/	Apr. 11, 2026	Apr. 10, 2031
15	CABLE	EMToni	DA800-NM-NM-11000MM	/	Apr. 24, 2026	Apr. 23, 2027



Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	Apr. 24, 2026	Apr. 23, 2027
LISN	R&S	ENV216	102794	July 8, 2026	July 7, 2027
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	Apr. 24, 2026	Apr. 23, 2027
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	Apr. 24, 2026	Apr. 23, 2027
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 8, 2026	May 7, 2027
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 8, 2026	May 7, 2027

Conducted Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	Apr. 24, 2026	Apr. 23, 2027
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	Apr. 24, 2026	Apr. 23, 2027
3	Power Sensor	MWRFTest	MW100-RFCB	/	Apr. 24, 2026	Apr. 23, 2027
4	Constant Temperature and Humidity Test Chamber	OJN	OJN-9606	/	Apr. 15, 2026	Apr. 14, 2027
5	DC power supply	R&S	SMB100A	259098	Apr. 15, 2026	Apr. 14, 2027

3.3 Testing software

Project	Software name	Edition
RF Conducted	MTS 8310	4.0.0.0
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+



3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	0.92dB
2	RF conducted power	0.16dB
3	Conducted spurious emissions	0.21dB
4	All radiated emissions (9k-30MHz)	4.68dB
5	All radiated emissions (30-1GHz)	5.1dB
6	All radiated emissions (1-6GHz)	3.9dB
7	All radiated emissions (6GHz-18GHz)	4.3dB
8	All radiated emissions (18-40GHz)	4.65dB
9	Temperature	0.5°C
10	Humidity	2%
11	Occupied Bandwidth	4.96%

Decision Rule

☒ Uncertainty is not included

☐ Uncertainty is included

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen 8.8
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	24.45	9.89	34.34	66.00	-31.66	QP	P	
2	0.1500	11.09	9.89	20.98	56.00	-35.02	AVG	P	
3	0.4126	23.34	9.99	33.33	57.60	-24.27	QP	P	
4	0.4126	10.77	9.99	20.76	47.60	-26.84	AVG	P	
5 *	0.4890	24.29	10.01	34.30	56.18	-21.88	QP	P	
6	0.4890	9.78	10.01	19.79	46.18	-26.39	AVG	P	
7	0.5760	22.53	10.03	32.56	56.00	-23.44	QP	P	
8	0.5760	9.89	10.03	19.92	46.00	-26.08	AVG	P	
9	0.6790	22.86	10.03	32.89	56.00	-23.11	QP	P	
10	0.6790	9.89	10.03	19.92	46.00	-26.08	AVG	P	
11	0.8215	23.49	10.05	33.54	56.00	-22.46	QP	P	
12	0.8215	11.34	10.05	21.39	46.00	-24.61	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case GFSK mode(High Channel:2480MHz).



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.4873	24.16	10.01	34.17	56.21	-22.04	QP	P	
2	0.4873	9.13	10.01	19.14	46.21	-27.07	AVG	P	
3	0.5190	21.76	10.02	31.78	56.00	-24.22	QP	P	
4	0.5190	8.79	10.02	18.81	46.00	-27.19	AVG	P	
5	0.6045	21.04	10.03	31.07	56.00	-24.93	QP	P	
6	0.6045	8.19	10.03	18.22	46.00	-27.78	AVG	P	
7	0.6809	21.44	10.03	31.47	56.00	-24.53	QP	P	
8	0.6809	8.57	10.03	18.60	46.00	-27.40	AVG	P	
9	0.8114	21.53	10.04	31.57	56.00	-24.43	QP	P	
10	0.8114	10.27	10.04	20.31	46.00	-25.69	AVG	P	
11	0.9330	22.91	10.05	32.96	56.00	-23.04	QP	P	
12	0.9330	10.11	10.05	20.16	46.00	-25.84	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case GFSK mode(High Channel:2480MHz).

Test Requirement:	FCC Part15 C Section 15.209, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

Between 30MHz – 1GHz


Temperature:	24.4℃	Relative Humidity:	56.7%
Pressure:	1010kPa	Polarization:	Horizontal
Test Voltage:	AC120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.3534	23.42	-8.77	14.65	40.00	-25.35	QP
2	45.5347	22.59	-8.60	13.99	40.00	-26.01	QP
3	49.7066	22.97	-8.26	14.71	40.00	-25.29	QP
4	53.5052	23.78	-8.65	15.13	40.00	-24.87	QP
5 *	56.9911	24.58	-9.06	15.52	40.00	-24.48	QP
6	62.4313	25.06	-10.25	14.81	40.00	-25.19	QP



Temperature:	24.4℃	Relative Humidity:	56.7%
Pressure:	1010kPa	Polarization:	Vertical
Test Voltage:	AC120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.0782	24.58	-9.47	15.11	40.00	-24.89	QP
2 *	40.1347	24.56	-9.04	15.52	40.00	-24.48	QP
3	43.9658	24.01	-8.73	15.28	40.00	-24.72	QP
4	56.0007	24.21	-8.94	15.27	40.00	-24.73	QP
5	109.7960	28.37	-11.22	17.15	43.50	-26.35	QP
6	116.9492	29.81	-11.86	17.95	43.50	-25.55	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case 8DPSK mode(Low Channel:2402MHz).
- 4.'-'Means the test Degree and Height are not recorded by the test software and only show the worstcase in the test report.



GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	57.8	30.55	5.77	24.66	57.68	74	-16.32	Pk
V	4804.00	44.75	30.55	5.77	24.66	44.63	54	-9.37	AV
V	7206.00	56.4	30.33	6.32	24.55	56.94	74	-17.06	Pk
V	7206.00	44.88	30.33	6.32	24.55	45.42	54	-8.58	AV
V	9608.00	59.08	30.55	5.77	24.66	58.96	74	-15.04	Pk
V	9608.00	43.84	30.55	5.77	24.66	43.72	54	-10.28	AV
V	12010.00	55.86	30.33	6.32	24.55	56.4	74	-17.6	Pk
V	12010.00	41.08	30.33	6.32	24.55	41.62	54	-12.38	AV
H	4804.00	59.32	30.55	5.77	24.66	59.2	74	-14.8	Pk
H	4804.00	41.45	30.55	5.77	24.66	41.33	54	-12.67	AV
H	7206.00	58.25	30.33	6.32	24.55	58.79	74	-15.21	Pk
H	7206.00	44.41	30.33	6.32	24.55	44.95	54	-9.05	AV
H	9608.00	55.97	30.55	5.77	24.66	55.85	74	-18.15	Pk
H	9608.00	41.88	30.55	5.77	24.66	41.76	54	-12.24	AV
H	12010.00	58.38	30.33	6.32	24.55	58.92	74	-15.08	Pk
H	12010.00	41.69	30.33	6.32	24.55	42.23	54	-11.77	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	57.77	30.55	5.77	24.66	57.65	74	-16.35	Pk
V	4882.00	41.59	30.55	5.77	24.66	41.47	54	-12.53	AV
V	7323.00	59.92	30.33	6.32	24.55	60.46	74	-13.54	Pk
V	7323.00	41.18	30.33	6.32	24.55	41.72	54	-12.28	AV
V	9764.00	56.67	30.55	5.77	24.66	56.55	74	-17.45	Pk
V	9764.00	44.1	30.55	5.77	24.66	43.98	54	-10.02	AV
V	12205.00	56.82	30.33	6.32	24.55	57.36	74	-16.64	Pk
V	12205.00	41.81	30.33	6.32	24.55	42.35	54	-11.65	AV
H	4882.00	56.63	30.55	5.77	24.66	56.51	74	-17.49	Pk
H	4882.00	44.28	30.55	5.77	24.66	44.16	54	-9.84	AV
H	7323.00	59.61	30.33	6.32	24.55	60.15	74	-13.85	Pk
H	7323.00	42.38	30.33	6.32	24.55	42.92	54	-11.08	AV
H	9764.00	56.13	30.55	5.77	24.66	56.01	74	-17.99	Pk
H	9764.00	44.38	30.55	5.77	24.66	44.26	54	-9.74	AV
H	12205.00	55.88	30.33	6.32	24.55	56.42	74	-17.58	Pk
H	12205.00	41.79	30.33	6.32	24.55	42.33	54	-11.67	AV



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	56.16	30.55	5.77	24.66	56.04	74	-17.96	Pk
V	4960.00	41.36	30.55	5.77	24.66	41.24	54	-12.76	AV
V	7440.00	55.44	30.33	6.32	24.55	55.98	74	-18.02	Pk
V	7440.00	41.17	30.33	6.32	24.55	41.71	54	-12.29	AV
V	9920.00	56.87	30.55	5.77	24.66	56.75	74	-17.25	Pk
V	9920.00	41.43	30.55	5.77	24.66	41.31	54	-12.69	AV
V	12400.00	59.9	30.33	6.32	24.55	60.44	74	-13.56	Pk
V	12400.00	41.26	30.33	6.32	24.55	41.8	54	-12.2	AV
H	4960.00	57.62	30.55	5.77	24.66	57.5	74	-16.5	Pk
H	4960.00	41.62	30.55	5.77	24.66	41.5	54	-12.5	AV
H	7440.00	57.2	30.33	6.32	24.55	57.74	74	-16.26	Pk
H	7440.00	41.68	30.33	6.32	24.55	42.22	54	-11.78	AV
H	9920.00	57.97	30.55	5.77	24.66	57.85	74	-16.15	Pk
H	9920.00	43.95	30.55	5.77	24.66	43.83	54	-10.17	AV
H	12400.00	58.04	30.33	6.32	24.55	58.58	74	-15.42	Pk
H	12400.00	44.12	30.33	6.32	24.55	44.66	54	-9.34	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

$\pi/4$ DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	55.92	30.55	5.77	24.66	55.8	74	-18.2	Pk
V	4804.00	41.39	30.55	5.77	24.66	41.27	54	-12.73	AV
V	7206.00	59.32	30.33	6.32	24.55	59.86	74	-14.14	Pk
V	7206.00	43.15	30.33	6.32	24.55	43.69	54	-10.31	AV
V	9608.00	55.64	30.55	5.77	24.66	55.52	74	-18.48	Pk
V	9608.00	42.11	30.55	5.77	24.66	41.99	54	-12.01	AV
V	12010.00	57.04	30.33	6.32	24.55	57.58	74	-16.42	Pk
V	12010.00	44.36	30.33	6.32	24.55	44.9	54	-9.1	AV
H	4804.00	55.68	30.55	5.77	24.66	55.56	74	-18.44	Pk
H	4804.00	41.22	30.55	5.77	24.66	41.1	54	-12.9	AV
H	7206.00	55.67	30.33	6.32	24.55	56.21	74	-17.79	Pk
H	7206.00	44.8	30.33	6.32	24.55	45.34	54	-8.66	AV
H	9608.00	59.71	30.55	5.77	24.66	59.59	74	-14.41	Pk
H	9608.00	41.12	30.55	5.77	24.66	41	54	-13	AV
H	12010.00	55.7	30.33	6.32	24.55	56.24	74	-17.76	Pk
H	12010.00	41.84	30.33	6.32	24.55	42.38	54	-11.62	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	55.15	30.55	5.77	24.66	55.03	74	-18.97	Pk
V	4882.00	41.87	30.55	5.77	24.66	41.75	54	-12.25	AV
V	7323.00	57.59	30.33	6.32	24.55	58.13	74	-15.87	Pk
V	7323.00	44.64	30.33	6.32	24.55	45.18	54	-8.82	AV
V	9764.00	55.94	30.55	5.77	24.66	55.82	74	-18.18	Pk
V	9764.00	42.91	30.55	5.77	24.66	42.79	54	-11.21	AV
V	12205.00	59.07	30.33	6.32	24.55	59.61	74	-14.39	Pk
V	12205.00	42.21	30.33	6.32	24.55	42.75	54	-11.25	AV
H	4882.00	59.53	30.55	5.77	24.66	59.41	74	-14.59	Pk
H	4882.00	42.67	30.55	5.77	24.66	42.55	54	-11.45	AV
H	7323.00	56.99	30.33	6.32	24.55	57.53	74	-16.47	Pk
H	7323.00	42.38	30.33	6.32	24.55	42.92	54	-11.08	AV
H	9764.00	56.58	30.55	5.77	24.66	56.46	74	-17.54	Pk
H	9764.00	41	30.55	5.77	24.66	40.88	54	-13.12	AV
H	12205.00	59.82	30.33	6.32	24.55	60.36	74	-13.64	Pk
H	12205.00	44	30.33	6.32	24.55	44.54	54	-9.46	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	57.66	30.55	5.77	24.66	57.54	74	-16.46	Pk
V	4960.00	41.74	30.55	5.77	24.66	41.62	54	-12.38	AV
V	7440.00	57.01	30.33	6.32	24.55	57.55	74	-16.45	Pk
V	7440.00	43.31	30.33	6.32	24.55	43.85	54	-10.15	AV
V	9920.00	56.11	30.55	5.77	24.66	55.99	74	-18.01	Pk
V	9920.00	41.9	30.55	5.77	24.66	41.78	54	-12.22	AV
V	12400.00	58.49	30.33	6.32	24.55	59.03	74	-14.97	Pk
V	12400.00	41.06	30.33	6.32	24.55	41.6	54	-12.4	AV
H	4960.00	59.04	30.55	5.77	24.66	58.92	74	-15.08	Pk
H	4960.00	41.56	30.55	5.77	24.66	41.44	54	-12.56	AV
H	7440.00	59.36	30.33	6.32	24.55	59.9	74	-14.1	Pk
H	7440.00	43.91	30.33	6.32	24.55	44.45	54	-9.55	AV
H	9920.00	56.42	30.55	5.77	24.66	56.3	74	-17.7	Pk
H	9920.00	41.19	30.55	5.77	24.66	41.07	54	-12.93	AV
H	12400.00	56.64	30.33	6.32	24.55	57.18	74	-16.82	Pk
H	12400.00	41.11	30.33	6.32	24.55	41.65	54	-12.35	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



8DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	59.94	30.55	5.77	24.66	59.82	74	-14.18	Pk
V	4804.00	43.62	30.55	5.77	24.66	43.5	54	-10.5	AV
V	7206.00	58.45	30.33	6.32	24.55	58.99	74	-15.01	Pk
V	7206.00	42.48	30.33	6.32	24.55	43.02	54	-10.98	AV
V	9608.00	55.53	30.55	5.77	24.66	55.41	74	-18.59	Pk
V	9608.00	41.23	30.55	5.77	24.66	41.11	54	-12.89	AV
V	12010.00	58.82	30.33	6.32	24.55	59.36	74	-14.64	Pk
V	12010.00	43.27	30.33	6.32	24.55	43.81	54	-10.19	AV
H	4804.00	57.04	30.55	5.77	24.66	56.92	74	-17.08	Pk
H	4804.00	41.59	30.55	5.77	24.66	41.47	54	-12.53	AV
H	7206.00	60	30.33	6.32	24.55	60.54	74	-13.46	Pk
H	7206.00	41.19	30.33	6.32	24.55	41.73	54	-12.27	AV
H	9608.00	55	30.55	5.77	24.66	54.88	74	-19.12	Pk
H	9608.00	41.73	30.55	5.77	24.66	41.61	54	-12.39	AV
H	12010.00	56.68	30.33	6.32	24.55	57.22	74	-16.78	Pk
H	12010.00	41.4	30.33	6.32	24.55	41.94	54	-12.06	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	59.82	30.55	5.77	24.66	59.7	74	-14.3	Pk
V	4882.00	41.34	30.55	5.77	24.66	41.22	54	-12.78	AV
V	7323.00	59.88	30.33	6.32	24.55	60.42	74	-13.58	Pk
V	7323.00	42.81	30.33	6.32	24.55	43.35	54	-10.65	AV
V	9764.00	55.92	30.55	5.77	24.66	55.8	74	-18.2	Pk
V	9764.00	43.81	30.55	5.77	24.66	43.69	54	-10.31	AV
V	12205.00	56.38	30.33	6.32	24.55	56.92	74	-17.08	Pk
V	12205.00	42.2	30.33	6.32	24.55	42.74	54	-11.26	AV
H	4882.00	58.53	30.55	5.77	24.66	58.41	74	-15.59	Pk
H	4882.00	42.65	30.55	5.77	24.66	42.53	54	-11.47	AV
H	7323.00	59.21	30.33	6.32	24.55	59.75	74	-14.25	Pk
H	7323.00	41.08	30.33	6.32	24.55	41.62	54	-12.38	AV
H	9764.00	56.51	30.55	5.77	24.66	56.39	74	-17.61	Pk
H	9764.00	41.52	30.55	5.77	24.66	41.4	54	-12.6	AV
H	12205.00	59.48	30.33	6.32	24.55	60.02	74	-13.98	Pk
H	12205.00	44.47	30.33	6.32	24.55	45.01	54	-8.99	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	55.78	30.55	5.77	24.66	55.66	74	-18.34	Pk
V	4960.00	41.82	30.55	5.77	24.66	41.7	54	-12.3	AV
V	7440.00	59.3	30.33	6.32	24.55	59.84	74	-14.16	Pk
V	7440.00	44.6	30.33	6.32	24.55	45.14	54	-8.86	AV
V	9920.00	59.09	30.55	5.77	24.66	58.97	74	-15.03	Pk
V	9920.00	41.68	30.55	5.77	24.66	41.56	54	-12.44	AV
V	12400.00	56.93	30.33	6.32	24.55	57.47	74	-16.53	Pk
V	12400.00	41.19	30.33	6.32	24.55	41.73	54	-12.27	AV
H	4960.00	59.83	30.55	5.77	24.66	59.71	74	-14.29	Pk
H	4960.00	41.54	30.55	5.77	24.66	41.42	54	-12.58	AV
H	7440.00	57.53	30.33	6.32	24.55	58.07	74	-15.93	Pk
H	7440.00	41.61	30.33	6.32	24.55	42.15	54	-11.85	AV
H	9920.00	58.3	30.55	5.77	24.66	58.18	74	-15.82	Pk
H	9920.00	44.87	30.55	5.77	24.66	44.75	54	-9.25	AV
H	12400.00	55.49	30.33	6.32	24.55	56.03	74	-17.97	Pk
H	12400.00	43.6	30.33	6.32	24.55	44.14	54	-9.86	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margi n (dB)	Detec tor Type	Result
GFSK	Low Channel: 2402MHz										
	H	2390.00	60.03	30.22	4.85	23.98	58.64	74.00	-15.36	PK	PASS
	H	2390.00	47.03	30.22	4.85	23.98	45.64	54.00	-8.36	AV	PASS
	H	2400.00	62.49	30.22	4.85	23.98	61.10	74.00	-12.90	PK	PASS
	H	2400.00	47.15	30.22	4.85	23.98	45.76	54.00	-8.24	AV	PASS
	V	2390.00	60.59	30.22	4.85	23.98	59.20	74.00	-14.80	PK	PASS
	V	2390.00	48.16	30.22	4.85	23.98	46.77	54.00	-7.23	AV	PASS
	V	2400.00	62.95	30.22	4.85	23.98	61.56	74.00	-12.44	PK	PASS
	V	2400.00	46.68	30.22	4.85	23.98	45.29	54.00	-8.71	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	60.48	30.22	4.85	23.98	59.09	74.00	-14.91	PK	PASS
	H	2483.50	47.01	30.22	4.85	23.98	45.62	54.00	-8.38	AV	PASS
	H	2500.00	59.95	30.22	4.85	23.98	58.56	74.00	-15.44	PK	PASS
	H	2500.00	46.90	30.22	4.85	23.98	45.51	54.00	-8.49	AV	PASS
	V	2483.50	59.09	30.22	4.85	23.98	57.70	74.00	-16.30	PK	PASS
	V	2483.50	48.13	30.22	4.85	23.98	46.74	54.00	-7.26	AV	PASS
	V	2500.00	59.69	30.22	4.85	23.98	58.30	74.00	-15.70	PK	PASS
	V	2500.00	48.65	30.22	4.85	23.98	47.26	54.00	-6.74	AV	PASS
$\pi/4$ DQPS K	Low Channel: 2402MHz										
	H	2390.00	59.29	30.22	4.85	23.98	57.90	74.00	-16.10	PK	PASS
	H	2390.00	48.08	30.22	4.85	23.98	46.69	54.00	-7.31	AV	PASS
	H	2400.00	61.67	30.22	4.85	23.98	60.28	74.00	-13.72	PK	PASS
	H	2400.00	48.43	30.22	4.85	23.98	47.04	54.00	-6.96	AV	PASS
	V	2390.00	62.04	30.22	4.85	23.98	60.65	74.00	-13.35	PK	PASS
	V	2390.00	46.69	30.22	4.85	23.98	45.30	54.00	-8.70	AV	PASS
	V	2400.00	61.81	30.22	4.85	23.98	60.42	74.00	-13.58	PK	PASS
	V	2400.00	46.18	30.22	4.85	23.98	44.79	54.00	-9.21	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	62.20	30.22	4.85	23.98	60.81	74.00	-13.19	PK	PASS
	H	2483.50	47.08	30.22	4.85	23.98	45.69	54.00	-8.31	AV	PASS
	H	2500.00	60.33	30.22	4.85	23.98	58.94	74.00	-15.06	PK	PASS
	H	2500.00	48.56	30.22	4.85	23.98	47.17	54.00	-6.83	AV	PASS
	V	2483.50	61.70	30.22	4.85	23.98	60.31	74.00	-13.69	PK	PASS
	V	2483.50	48.27	30.22	4.85	23.98	46.88	54.00	-7.12	AV	PASS
	V	2500.00	62.89	30.22	4.85	23.98	61.50	74.00	-12.50	PK	PASS
	V	2500.00	47.78	30.22	4.85	23.98	46.39	54.00	-7.61	AV	PASS



8DPSK	Low Channel: 2402MHz										
	H	2390.00	59.68	30.22	4.85	23.98	58.29	74.00	-15.71	PK	PASS
	H	2390.00	48.88	30.22	4.85	23.98	47.49	54.00	-6.51	AV	PASS
	H	2400.00	62.83	30.22	4.85	23.98	61.44	74.00	-12.56	PK	PASS
	H	2400.00	47.55	30.22	4.85	23.98	46.16	54.00	-7.84	AV	PASS
	V	2390.00	59.82	30.22	4.85	23.98	58.43	74.00	-15.57	PK	PASS
	V	2390.00	47.65	30.22	4.85	23.98	46.26	54.00	-7.74	AV	PASS
	V	2400.00	60.55	30.22	4.85	23.98	59.16	74.00	-14.84	PK	PASS
	V	2400.00	48.08	30.22	4.85	23.98	46.69	54.00	-7.31	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	59.36	30.22	4.85	23.98	57.97	74.00	-16.03	PK	PASS
	H	2483.50	46.39	30.22	4.85	23.98	45.00	54.00	-9.00	AV	PASS
	H	2500.00	60.65	30.22	4.85	23.98	59.26	74.00	-14.74	PK	PASS
	H	2500.00	47.93	30.22	4.85	23.98	46.54	54.00	-7.46	AV	PASS
	V	2483.50	60.90	30.22	4.85	23.98	59.51	74.00	-14.49	PK	PASS
	V	2483.50	48.23	30.22	4.85	23.98	46.84	54.00	-7.16	AV	PASS
	V	2500.00	59.00	30.22	4.85	23.98	57.61	74.00	-16.39	PK	PASS
	V	2500.00	46.22	30.22	4.85	23.98	44.83	54.00	-9.17	AV	PASS
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 5.5
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

According to RSS-247§5.5 and RSS-Gen§8.9, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) or RSS-Gen is not required.

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD


No deviation.




6.5 Test Result

Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-49.57	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-53.64	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-51.65	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-54.28	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-51.5	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-54.99	-20	Pass




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission




Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-49.04	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-48.93	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-50.27	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-48.38	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-50.32	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-49.52	-20	Pass



Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission




Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission




Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-44.32	-20	Pass
NVNT	1-DH5	2441	Ant1	-38.32	-20	Pass
NVNT	1-DH5	2480	Ant1	-41	-20	Pass
NVNT	2-DH5	2402	Ant1	-45.64	-20	Pass
NVNT	2-DH5	2441	Ant1	-46.69	-20	Pass
NVNT	2-DH5	2480	Ant1	-45.33	-20	Pass
NVNT	3-DH5	2402	Ant1	-45.86	-20	Pass
NVNT	3-DH5	2441	Ant1	-46.12	-20	Pass
NVNT	3-DH5	2480	Ant1	-44.06	-20	Pass




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission

**7. 20DB&99% BANDWIDTH**

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1, RSS-Gen 6.7
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

7.1 Test Setup**7.2 Limit**

There is no corresponding limit requirement for this test item.

7.3 Test procedure


1. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
8. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 100 KHz VBW record the 99% bandwidth.

7.4 DEVIATION FROM STANDARD


No deviation.

7.5 Test Result


Mode	Test channel	20dB Emission Bandwidth (MHz)	99%Bandwidth (MHz)	Result
GFSK	Lowest	1.056	0.96428	Pass
	Middle	1.045	0.97651	
	Highest	1.032	0.95811	
$\pi/4$ DQPSK	Lowest	1.335	1.2195	Pass
	Middle	1.327	1.2297	
	Highest	1.329	1.2441	
8DPSK	Lowest	1.307	1.2188	Pass
	Middle	1.29	1.2217	
	Highest	1.28	1.2164	




-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1







OBW NVNT 1-DH5 2402MHz Ant1




OBW NVNT 1-DH5 2441MHz Ant1




OBW NVNT 1-DH5 2480MHz Ant1




OBW NVNT 2-DH5 2402MHz Ant1




OBW NVNT 2-DH5 2441MHz Ant1




OBW NVNT 2-DH5 2480MHz Ant1



OBW NVNT 3-DH5 2402MHz Ant1



OBW NVNT 3-DH5 2441MHz Ant1



8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1), RSS 247 5.4 (b)
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W.

8.3 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 2MHz. VBW =6MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD


No deviation.

8.5 Test Result


Mode	Test channel	Peak Output Power (dBm)	Peak Output Power Limit (dBm)	Result
GFSK	Lowest	0.56	21.00	Pass
	Middle	1.09		
	Highest	0.45		
$\pi/4$ DQPSK	Lowest	1.34	21.00	Pass
	Middle	1.88		
	Highest	1.27		
8DPSK	Lowest	1.67	21.00	Pass
	Middle	2.22		
	Highest	1.63		




Peak Power NVNT 1-DH5 2402MHz Ant1




Peak Power NVNT 1-DH5 2441MHz Ant1




Peak Power NVNT 1-DH5 2480MHz Ant1




Peak Power NVNT 2-DH5 2402MHz Ant1




Peak Power NVNT 2-DH5 2441MHz Ant1




Peak Power NVNT 2-DH5 2480MHz Ant1



Peak Power NVNT 3-DH5 2402MHz Ant1



Peak Power NVNT 3-DH5 2441MHz Ant1





ZHONGHAN

9. HOPPING CHANNEL SEPARATION

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Receiver setup:	RBW=30KHz, VBW=100KHz, detector=Peak
Limit:	GFSK, $\pi/4$ -DQPSK & 8DSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: GFSK: RBW = 300kHz. VBW = 300kHz , Span = 2.0MHz. $\pi/4$ -DQPSK: RBW = 100kHz. VBW = 100kHz , Span = 2.6MHz. 8DSK: RBW = 100kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 Test Result


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2401.95	2402.998	1.048	0.704	Pass
NVNT	1-DH5	Ant1	2440.924	2442.1	1.176	0.697	Pass
NVNT	1-DH5	Ant1	2478.962	2479.946	0.984	0.688	Pass
NVNT	2-DH5	Ant1	2401.9358	2402.9654	1.0296	0.89	Pass
NVNT	2-DH5	Ant1	2440.8552	2442.1682	1.313	0.885	Pass
NVNT	2-DH5	Ant1	2479.1672	2480.0954	0.9282	0.886	Pass
NVNT	3-DH5	Ant1	2401.967	2402.9186	0.9516	0.871	Pass
NVNT	3-DH5	Ant1	2440.8578	2442.0278	1.17	0.86	Pass
NVNT	3-DH5	Ant1	2479.0034	2479.9472	0.9438	0.853	Pass




CFS NVNT 1-DH5 2402MHz Ant1




CFS NVNT 1-DH5 2441MHz Ant1



CFS NVNT 1-DH5 2480MHz Ant1




CFS NVNT 2-DH5 2402MHz Ant1



CFS NVNT 2-DH5 2441MHz Ant1




CFS NVNT 2-DH5 2480MHz Ant1



CFS NVNT 3-DH5 2402MHz Ant1



CFS NVNT 3-DH5 2441MHz Ant1



10.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii), RSS-247 5.1
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD

No deviation.

11.4 Test Result


Mode	Antenna	Hopping Number	Limit	Verdict
1-DH5	Ant1	79	15	Pass
2-DH5	Ant1	79	15	Pass
3-DH5	Ant1	79	15	Pass



Hopping No. NVNT 1-DH5 2441MHz Ant1



Hopping No. NVNT 2-DH5 2441MHz Ant1



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii), RSS-247 5.1
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.



11.4 Test Result

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.375	117.75	314	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.621	257.739	159	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.88	302.4	105	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.385	120.12	312	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.637	252.098	154	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.879	299.416	104	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.386	121.59	315	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.619	249.326	154	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.886	303.03	105	31600	400	Pass

Remarks:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$


(1 / 2 / 3)-DH1: Dwell time (ms) = Pulse Time (ms) * [1600 / (2 * 79)] * 31.6s

(1 / 2 / 3)-DH3: Dwell time (ms) = Pulse Time (ms) * [1600 / (4 * 79)] * 31.6s

(1 / 2 / 3)-DH5: Dwell time (ms) = Pulse Time (ms) * [1600 / (6 * 79)] * 31.6s




Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated






Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated




Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated






Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated







Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated

12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(b)(4), RSS-Gen 6.8
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (EIRP) limits specified in the applicable standard (RSS) for the licence-exempt apparatus. Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.⁹ When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.	
EUT Antenna:	
The antenna is Chip antenna, the best case gain of the antennas is 1.71 dBi, reference to the appendix II for details	

13. Test Setup Photo

Reference to the appendix I for details.

14. EUT Constructional Details

Reference to the appendix II for details.

***** END OF REPORT *****