



RF Exposure Evaluation

For

Shenzhen Shike Innovation Technology Co., Ltd.

MUZIM L1 Data Hub

Test Model: MUZIM-L1

Prepared for : Shenzhen Shike Innovation Technology Co., Ltd.
Address : Room 704, Block F, Nanshan Zhigu Industrial Park, Xili Subdistrict,
Nanshan District, Shenzhen City

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 05, 2026
Number of tested samples : 2
Sample No. : A260707005-1, A260707005-2
Serial number : Prototype
Date of Test : August 05, 2026 ~ September 10, 2026
Date of Report : September 11, 2026

**RF Exposure Evaluation****Report Reference No.** : LCSA07166032EE**Date of Issue** : September 11, 2026**Testing Laboratory Name** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Address** : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China**Testing Location/ Procedure** : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name** : Shenzhen Shike Innovation Technology Co., Ltd.**Address** : Room 704, Block F, Nanshan Zhigu Industrial Park, Xili Subdistrict,
Nanshan District, Shenzhen City**Test Specification****Standard** : FCC KDB publication 447498 D01 General RF Exposure Guidance
v06

FCC CFR 47 part1 1.1310

FCC CFR 47 part2 2.1091

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF** : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description : MUZIM L1 Data Hub**Trade Mark** : N/A**Test Model** : MUZIM-L1**Ratings** : Please Refer to Page 6**Result** : PASS**Compiled by:**

Vera Deng/ Administrator

Supervised by:

Kevin Huang/ RF Manager

Approved by:

Gavin Liang/ Manager



RF Exposure Evaluation

Test Report No. : LCSA07166032EE	<u>September 11, 2026</u> Date of issue
---	--

EUT.....	: MUZIM L1 Data Hub
Test Model.....	: MUZIM-L1
Applicant.....	: Shenzhen Shike Innovation Technology Co., Ltd.
Address.....	: Room 704, Block F, Nanshan Zhigu Industrial Park, Xili Subdistrict, Nanshan District, Shenzhen City
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shenzhen Shike Innovation Technology Co., Ltd.
Address.....	: Room 704, Block F, Nanshan Zhigu Industrial Park, Xili Subdistrict, Nanshan District, Shenzhen City
Telephone.....	: /
Fax.....	: /
Factory.....	: Shenzhen Jinda Intelligent Innovative Technology Co., Ltd.
Address.....	: 3rd Floor, Factory, No.12 Huanzhen Rd, Xuegang Community, Shajing, Bao'an, Shenzhen
Telephone.....	: /
Fax.....	: /

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 11, 2026	Initial Issue	---



TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION	6
2. EVALUATION METHOD	8
3. LIMIT	8
4. MPE CALCULATION METHOD.....	9
5. ANTENNA INFORMATION.....	9
6. CONDUCTED POWER.....	9
7. MANUFACTURING TOLERANCE	11
8. MEASUREMENT RESULTS.....	16
9. CONCLUSION.....	18
10. DESCRIPTION OF TEST FACILITY	18
11. MEASUREMENT UNCERTAINTY	18



1. Product Information

EUT	: MUZIM L1 Data Hub
Test Model	: MUZIM-L1
Ratings	: Input: 24V $\overline{=}$ 8.75A For AC Adapter: Input: 100-240V~, 50-60Hz, 2.5A Output: 24.0V $\overline{=}$ 8.75A, 210.0W
Hardware Version	: V1.2
Software Version	: V1.0.0
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 40 channels for Bluetooth V5.3 (DTS)
Channel Spacing	: 2MHz for Bluetooth V5.3 (DTS)
Modulation Type	: GFSK for Bluetooth V5.3 (DTS)
Bluetooth Version	: V5.3
Antenna Description	: FPC Antenna 2, 3.27dBi(max.)
2.4G WLAN	:
Frequency Range	: 2412MHz~2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth(2412~2462MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna1: FPC Antenna, 1.71dBi(Max.) Antenna2: FPC Antenna, 3.27dBi(Max.)
5.2G WLAN	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Antenna1: FPC Antenna, 3.30dBi(Max.) Antenna2: FPC Antenna, 2.41dBi(Max.)
5.8G WLAN	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)

TRF-4- E-214 A/0



IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)

Antenna Description : Antenna1: FPC Antenna, 5.42dBi(Max.)
Antenna2: FPC Antenna, 2.45dBi(Max.)
Exposure category : General population/uncontrolled environment
EUT Type : Production Unit
Device Type : Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.



2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density



4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal	FPC Antenna	2400MHz ~ 2500MHz	Bluetooth: 3.27dBi	Bluetooth Antenna 2
	FPC Antenna	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	2.4GWIFI: 1.71dBi 5.2GWIFI: 3.3dBi 5.8GWIFI: 5.42dBi	WIFI Antenna 1
	FPC Antenna	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	2.4GWIFI: 3.27dBi 5.2GWIFI: 2.41dBi 5.8GWIFI: 2.45dBi	WIFI Antenna 2

6. Conducted Power

[BLE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	8.52
	19	2440	8.7
	39	2480	9.04

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11B	1	2412	16.12	17.23
	6	2437	16.75	17.32
	11	2462	16.93	17.58
11G	1	2412	15.16	16.2
	6	2437	15.11	16.02
	11	2462	15.21	15.98
11N20 SISO	1	2412	14.05	14.86
	6	2437	14.13	14.66
	11	2462	14.03	14.88
11AX20 SISO	1	2412	13.43	14.06
	6	2437	13.55	14.6
	11	2462	13.49	14.92



[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	36	5180	13.41	14.06
	40	5200	14.05	14.71
	48	5240	15.25	16.00
11N20 SISO	36	5180	13.63	13.27
	40	5200	13.86	13.92
	48	5240	15.20	15.05
11N40 SISO	38	5190	14.05	13.66
	46	5230	15.38	14.68
11AC20 SISO	36	5180	13.79	13.35
	40	5200	14.20	13.92
	48	5240	15.58	15.01
11AC40 SISO	38	5190	14.18	14.06
	46	5230	15.49	14.71
11AC80 SISO	42	5210	16.18	14.35
11AX20 SISO	36	5180	14.97	14.71
	40	5200	15.06	14.89
	48	5240	16.50	15.85
11AX40 SISO	38	5190	15.04	14.26
	46	5230	16.10	15.55
11AX80 SISO	42	5210	17.45	14.26

[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Ant 1 Max Conducted Power(dBm)	Ant 2 Max Conducted Power(dBm)
11A	149	5745	15.37	14.32
	157	5785	15.91	15.09
	165	5825	15.58	14.90
11N20 SISO	149	5745	14.73	13.54
	157	5785	15.01	14.21
	165	5825	14.85	13.95
11N40 SISO	151	5755	14.12	13.09
	159	5795	14.40	13.53
11AC20 SISO	149	5745	14.76	13.60
	157	5785	15.14	14.27
	165	5825	14.84	14.06
11AC40 SISO	151	5755	14.54	12.85
	159	5795	14.45	13.79
11AC80 SISO	155	5775	14.40	13.33
11AX20 SISO	149	5745	15.77	13.69
	157	5785	15.85	14.42
	165	5825	15.77	14.08
11AX40 SISO	151	5755	14.94	14.20
	159	5795	15.25	14.41
11AX80 SISO	155	5775	14.38	13.23



7. Manufacturing Tolerance

[BLE 1M]

GFSK (Peak)

Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	8.0	8.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant1]

11B (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11G (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11N20 (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11AX20 (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant2]

11B (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	17.0	17.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11G (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16.0	16.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11N20 (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

11AX20 (Average)

Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



[5.2G WIFI Ant1]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	14.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	13.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	15.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	14.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	15.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Average)			
Channel	Channel 42		
Target (dBm)	16.0		
Tolerance $\pm$ (dB)	1.0		
11AX20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	15.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	15.0	16.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX80(Average)			
Channel	Channel 42		
Target (dBm)	17.0		
Tolerance $\pm$ (dB)	1.0		



[5.2G WIFI Ant2]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	13.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	13.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	13.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Average)			
Channel	Channel 42		
Target (dBm)	14.0		
Tolerance $\pm$ (dB)	1.0		
11AX20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.0	14.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	14.0	15.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX80(Average)			
Channel	Channel 42		
Target (dBm)	15.0		
Tolerance $\pm$ (dB)	1.0		



[5.8G WIFI Ant1]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	15.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	15.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	14.0	14.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	14.0		
Tolerance $\pm$ (dB)	1.0		
11AX20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	14.0	15.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AX80 (Average)			
Channel	Channel 155		
Target (dBm)	14.0		
Tolerance $\pm$ (dB)	1.0		



[5.8G WIFI Ant2]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	14.0	15.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	13.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	12.0	13.0	
Tolerance ±(dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	13.0		
Tolerance ±(dB)	1.0		
11AX20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0
11AX40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	14.0	14.0	
Tolerance ±(dB)	1.0	1.0	
11AX80 (Average)			
Channel	Channel 155		
Target (dBm)	13.0		
Tolerance ±(dB)	1.0		



8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT LE	10	10.0000	3.27	2.1232	0.0042	1.0000

[2.4G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	17.0	50.1187	1.71	1.4825	0.0148	1.0000
IEEE 802.11g	16.0	39.8107	1.71	1.4825	0.0117	1.0000
IEEE 802.11n HT20	15.0	31.6228	1.71	1.4825	0.0093	1.0000
IEEE 802.11ax HE20	14.0	25.1189	1.71	1.4825	0.0074	1.0000

[2.4G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	18.0	63.0957	3.27	2.1232	0.0267	1.0000
IEEE 802.11g	17.0	50.1187	3.27	2.1232	0.0212	1.0000
IEEE 802.11n HT20	15.0	31.6228	3.27	2.1232	0.0134	1.0000
IEEE 802.11ax HE20	15.0	31.6228	3.27	2.1232	0.0134	1.0000

[5.2G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	16.0	39.8107	3.3	2.1380	0.0169	1.0000
IEEE 802.11n HT20	16.0	39.8107	3.3	2.1380	0.0169	1.0000
IEEE 802.11n HT40	16.0	39.8107	3.3	2.1380	0.0169	1.0000
IEEE 802.11ac VHT20	16.0	39.8107	3.3	2.1380	0.0169	1.0000
IEEE 802.11ac VHT40	16.0	39.8107	3.3	2.1380	0.0169	1.0000
IEEE 802.11ac VHT80	17.0	50.1187	3.3	2.1380	0.0213	1.0000
IEEE 802.11ax HE20	17.0	50.1187	3.3	2.1380	0.0213	1.0000
IEEE 802.11ax HE40	17.0	50.1187	3.3	2.1380	0.0213	1.0000
IEEE 802.11ax HE80	18.0	63.0957	3.3	2.1380	0.0269	1.0000



[5.2G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	17.0	50.1187	2.41	1.7418	0.0174	1.0000
IEEE 802.11n HT20	16.0	39.8107	2.41	1.7418	0.0138	1.0000
IEEE 802.11n HT40	15.0	31.6228	2.41	1.7418	0.0110	1.0000
IEEE 802.11ac VHT20	16.0	39.8107	2.41	1.7418	0.0138	1.0000
IEEE 802.11ac VHT40	15.0	31.6228	2.41	1.7418	0.0110	1.0000
IEEE 802.11ac VHT80	15.0	31.6228	2.41	1.7418	0.0110	1.0000
IEEE 802.11ax HE20	16.0	39.8107	2.41	1.7418	0.0138	1.0000
IEEE 802.11ax HE40	16.0	39.8107	2.41	1.7418	0.0138	1.0000
IEEE 802.11ax HE80	16.0	39.8107	2.41	1.7418	0.0138	1.0000

[5.8G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	16.0	39.8107	5.42	3.4834	0.0276	1.0000
IEEE 802.11n HT20	16.0	39.8107	5.42	3.4834	0.0276	1.0000
IEEE 802.11n HT40	15.0	31.6228	5.42	3.4834	0.0219	1.0000
IEEE 802.11ac VHT20	16.0	39.8107	5.42	3.4834	0.0276	1.0000
IEEE 802.11ac VHT40	15.0	31.6228	5.42	3.4834	0.0219	1.0000
IEEE 802.11ac VHT80	15.0	31.6228	5.42	3.4834	0.0219	1.0000
IEEE 802.11ax HE20	16.0	39.8107	5.42	3.4834	0.0276	1.0000
IEEE 802.11ax HE40	16.0	39.8107	5.42	3.4834	0.0276	1.0000
IEEE 802.11ax HE80	15.0	31.6228	5.42	3.4834	0.0219	1.0000

[5.8G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	16.0	39.8107	2.45	1.7579	0.0139	1.0000
IEEE 802.11n HT20	15.0	31.6228	2.45	1.7579	0.0111	1.0000
IEEE 802.11n HT40	14.0	25.1189	2.45	1.7579	0.0088	1.0000
IEEE 802.11ac VHT20	15.0	31.6228	2.45	1.7579	0.0111	1.0000
IEEE 802.11ac VHT40	14.0	25.1189	2.45	1.7579	0.0088	1.0000
IEEE 802.11ac VHT80	14.0	25.1189	2.45	1.7579	0.0088	1.0000
IEEE 802.11ax HE20	15.0	31.6228	2.45	1.7579	0.0111	1.0000
IEEE 802.11ax HE40	15.0	31.6228	2.45	1.7579	0.0111	1.0000
IEEE 802.11ax HE80	14.0	25.1189	2.45	1.7579	0.0088	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.



8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BLE, one 2.4G WLAN&5.2G WLAN, another one 2.4G WLAN&5.2G WLAN&5.8G WLAN, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0

<the worst simultaneous transmission operations result-2.4GWIFI>

Bluetooth Antenna Max MPE ratios	2.4GWIFI-Ant 1	2.4GWIFI-Ant 2	$\sum$ MPE ratios	Limit	Results
0.0042	0.0148	0.0267	0.0457	1.0	Pass

<the worst simultaneous transmission operations result-5GWIFI>

Bluetooth Antenna Max MPE ratios	5GWIFI-Ant 1	5GWIFI-Ant 2	$\sum$ MPE ratios	Limit	Results
0.0042	0.0269	0.0174	0.0485	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. $MPE\ values = PG/4\pi R^2$
6. Both 2.4GWIFI and 5GWIFI cannot be transmitter simultaneously.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

11. Measurement Uncertainty

BLE/2.4GWIFI/5.2GWIFI/5.8GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	$\pm 0.57\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

-----THE END OF REPORT-----