

§ 2.1091 RF Exposure

FCC ID: 2BYCG-TW-R120

Applied procedures / limit

According to KDB447498 D01 General RF Exposure Guidance V06

According to §2.1091 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

TEST RESULTS

Protocol	Separation distance (cm)	Field Strength (dBuv/m)	Electric Field Strength (E) (V/m)	Limit (V/m)	Result
134.2kHz	20	89.04	0.0283	614	Pass

$$V/m = 10^{(dBuv/m/20)} \times 10^{-6}$$

Conclusion:

For the max result $\leq$ Limit, compliance with FCC's RF Exposure