

TEST REPORT

FCC Rules Part 15.247

Report Reference No.....: MTEB26090105-R1

FCC ID.....: 2BYEN-ZD01

Compiled by
(position+printed name+signature)..: Ekaterina Zhang



Supervised by
(position+printed name+signature)..: Test Engineer Sunny Deng



Approved by
(position+printed name+signature)..: Manager Yvette Zhou



Date of issue.....: Sep.11, 2026

Representative Laboratory Name.: Shenzhen Most Technology Service Co., Ltd.

Address.....: East A, 1/F., New Aolin Factory Buiding, Langshan Erlu, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Applicant's name.....: Zhen Ding Yun Intelligent Technology (Shenzhen) Co., Ltd.

Address.....: 7/F, Bldg B, Huilongda Industrial Park, Shilong Community, Shiyan St, Bao'an District, Shenzhen

Test specification/ Standard.....: FCC Rules Part 15.247

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Intelligent Watch

Trade Mark: MITOUR

Model/Type reference.....: ZD01

Listed Models: ZD02, ZD03, ZD05, ZD06, ZD07, ZD08, ZD09, ZD11, ZD12

Modulation Type.....: GFSK

Operation Frequency.....: From 2402MHz to 2480MHz

Hardware Version.....: V1.0

Software Version.....: V1.0

Rating.....: DC 3.7V by Battery
DC 5V by USB Port

Result.....: PASS

TEST REPORT

Equipment under Test : Intelligent Watch

Model /Type : ZD01

Listed Models : ZD02, ZD03, ZD05, ZD06, ZD07, ZD08, ZD09, ZD11, ZD12

Remark : Only the model ZD01 was tested, The electrical circuit design, layout, components used and internal wiring are identical, Only the model name and appearance colour are different.

Applicant : Zhen Ding Yun Intelligent Technology (Shenzhen) Co., Ltd.

Address : 7/F, Bldg B, Huilongda Industrial Park, Shilong Community, Shiyan St, Bao'an District, Shenzhen

Manufacturer : Zhen Ding Yun Intelligent Technology (Shenzhen) Co., Ltd.

Address : 7/F, Bldg B, Huilongda Industrial Park, Shilong Community, Shiyan St, Bao'an District, Shenzhen

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. REVISION HISTORY	4
2. TEST STANDARDS	5
3. SUMMARY	6
3.1. General Remarks	6
3.2. Product Description	6
3.3. Equipment Under Test	6
3.4. Short description of the Equipment under Test (EUT)	6
3.5. EUT operation mode	7
3.6. Block Diagram of Test Setup	7
3.7. Test Item (Equipment Under Test) Description*	7
3.8. Auxiliary Equipment (AE) Description	7
3.9. Antenna Information*	8
3.10. EUT configuration	8
3.11. Modifications	8
4. TEST ENVIRONMENT	9
4.1. Address of the test laboratory	9
4.2. Environmental conditions	9
4.3. Test Description	10
4.4. Statement of the measurement uncertainty	10
4.5. Equipments Used during the Test	11
5. TEST CONDITIONS AND RESULTS	12
5.1. AC Power Conducted Emission	12
5.2. Radiated Emission	15
5.3. Maximum Peak Output Power	22
5.4. Power Spectral Density	23
5.5. 6dB Bandwidth and 99% Bandwidth	24
5.6. Band Edge Compliance of RF Emission	25
5.7. Spurious RF Conducted Emission	27
5.8. Antenna Requirement	28
6. TEST SETUP PHOTOS OF THE EUT	29
7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	30
APPENDIX I. Conducted Output Power	31
APPENDIX II. 99% Bandwidth	32
APPENDIX III. 6dB Bandwidth	33
APPENDIX IV. Conducted Spurious & Band Edge Emission	34
APPENDIX V. Duty Cycle	36
APPENDIX VI. Power Spectral Density	37

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2026.09.11	Initial Issue	Ekaterina Zhang

2. TEST STANDARDS

The tests were performed according to following standards:

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024](#) : American National Standard for Testing Unlicensed Wireless Devices

3. SUMMARY

3.1. General Remarks

Date of receipt of test sample	:	2026.09.07
Testing commenced on	:	2026.09.08
Testing concluded on	:	2026.09.10

3.2. Product Description

Product Name:	Intelligent Watch
Model/Type reference:	ZD01
Power Supply:	DC 3.7V by Battery DC 5V by USB Port
Testing sample ID:	MTYP14080
Bluetooth :	
Supported Type:	BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Metal antenna
Antenna gain:	0dBi

3.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 3.7V by Battery
DC 5V by USB Port

3.4. Short description of the Equipment under Test (EUT)

This is a Intelligent Watch For more details, refer to the user's manual of the EUT.


3.5. EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 40 channels provided to the EUT.

Channel 00/19/39 was selected to test.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

3.6. Block Diagram of Test Setup



3.7. Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A	/	/	/	/	/
EUT B	/	/	/	/	/

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8. Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1	adapter	/	MDY-10-EC	/
AE 2	/	/	/	/

3.9. Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	Metal antenna	2.4–2.5 GHz	---	0dBi
Antenna 2	/	/	/	/	/

*: declared by the applicant.

3.10. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

○ - supplied by the manufacturer

● - Supplied by the lab

●	ADAPTER	M/N:	MDY-10-EC
		Manufacturer:	Xiaomi Communications Co.,Ltd

3.11. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

East A, 1/F., New Aolin Factory Building, Langshan Erlu, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2. Environmental conditions

Radiated Emission:

Temperature:	21.6 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	21.6 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

4.3. Test Description

FCC and IC Requirements		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247 (a)(2)	6dB Bandwidth & 99% Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247 (e)	Power Spectral Density	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)
6dB Bandwidth & 99% Bandwidth	/	5%	(1)
Maximum Conducted Output Power	/	0.80dB	(1)
Spurious RF Conducted Emission	/	1.6dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5. Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2026/02/28
2.	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2026/02/28
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2026/02/28
4.	Receiver	R&S	ESPI	101202	V3.0-10-2	2026/02/28
5.	Spectrum analyzer	Agilent	9020A	/	A14.16	2026/02/28
6.	Bilog Antenna	Sunol Sciences	JB3	A121206	/	2025/11/22
7.	Horn antenna	HF Antenna	HF Antenna	/	/	2026/03/08
8.	Loop antenna	Beijing Daze	ZN30900B	/	/	2026/03/28
10.	Wireless Communication Test Set	R&S	CMW500	155873	V3.7.40	2026/02/28
11.	Preamplifier	Millitech	KA-LNA18-40-01	18050001	/	2026/02/28
12.	High gain antenna	A-INFOMW	LB-180400KF	J211060273	/	2026/02/28
13.	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2026/02/28
14.	Pre-amplifier	lenscend	TAP011840	AP21C806124	/	2026/02/28
15.	RF Cable(below1GHz)	Times	9kHz-1GHz	/	/	2026/02/28
16.	RF Cable(above1GHz)	Times	1-18G	/	/	2026/02/28
17.	RF Cable(9KHz-40GHz)	Tonscend	170660	/	/	2026/02/28
18.	vector Signal Generator	ROHDE & SCHWARZ	SMBV100B		/	2026/02/28
19.	Signal Generator	Agilent	5181A		/	2026/02/28
20.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
21.	Humid & Temp Programmable Tester	Haida	HD-2257	110807201	/	2026/02/28
22.	X-series USB Peak and Average Power Sensor	Agilent	U2021XA	MY54080019	/	2026/02/28
23.	4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	TW54063507	/	2026/02/28
24.	splitter	Mini-Circuits	ZAP-50W	NN256400424	/	2026/02/28
25.	Power meter	R&S	NRVS	100444	/	2026/02/28
26.	Testing software	Fala	EZ-EMC(CE)	/	Ver.FA-03A1	/
27.	Testing software	Fala	EZ-EMC(RE)	/	Ver.FA-03A3	/
27.	Testing software	WCS	WCS	/	Ver.23.06.1401	/

Note: 1. The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024..
- 2 Support equipment, if needed, was placed as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.
- 4 The EUT received DC5V, The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For unintentional device, according to RSS Gen 8.8 and § 15.207(a) Line Conducted Emission Limits is as following:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. GFSK modes were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:

Power supply: DC 5V by USB Port Polarization: L



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.249	9.60	34.11	43.71	61.79	18.08	24.74	34.34	51.79	17.45	PASS
2	0.348	9.59	33.24	42.83	59.01	16.18	22.30	31.89	49.01	17.12	PASS
3	0.3615	9.59	32.27	41.86	58.69	16.83	22.08	31.67	48.69	17.02	PASS
4	0.4245	9.59	29.63	39.22	57.36	18.14	21.19	30.78	47.36	16.58	PASS
5	0.537	9.59	34.82	44.41	56.00	11.59	21.37	30.96	46.00	15.04	PASS
6	1.1085	9.60	31.17	40.77	56.00	15.23	17.75	27.35	46.00	18.65	PASS

Note: (1) Level = Reading + Factor


(2) Margin = Limit - Level

Power supply: DC 5V by USB Port

Polarization

N

Test Graph



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2175	9.60	37.16	46.76	62.91	16.15	26.17	35.77	52.91	17.14	PASS
2	0.276	9.59	33.69	43.28	60.94	17.66	23.80	33.39	50.94	17.55	PASS
3	0.321	9.59	31.64	41.23	59.68	18.45	22.29	31.88	49.68	17.80	PASS
4	0.393	9.59	32.47	42.06	58.00	15.94	22.86	32.45	48.00	15.55	PASS
5	0.5325	9.59	32.44	42.03	56.00	13.97	19.55	29.14	46.00	16.86	PASS
6	0.6765	9.60	29.82	39.42	56.00	16.58	19.07	28.67	46.00	17.33	PASS


Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


5.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission

Unwanted emissions that fall into restricted bands shall comply with the limits specified in RSS-Gen; and Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz


**Final Data List**

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Pol	Verdict
1	30.0790	25.54	1.64	27.18	40.00	12.82	Horizontal	PASS
2	38.5123	19.40	7.41	26.81	40.00	13.19	Horizontal	PASS
3	512.3698	22.84	2.7	25.54	46.00	20.46	Horizontal	PASS
4	579.7644	23.58	3.83	27.41	46.00	18.59	Horizontal	PASS
5	661.2188	24.60	3.44	28.04	46.00	17.96	Horizontal	PASS
6	813.1536	28.04	3.39	31.43	46.00	14.57	Horizontal	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Vertical



Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Pol	Verdict
1	30.1054	20.83	2.43	23.26	40.00	16.74	Vertical	PASS
2	39.1247	14.45	11.4	25.85	40.00	14.15	Vertical	PASS
3	42.4100	12.21	14.65	26.86	40.00	13.14	Vertical	PASS
4	68.5567	9.20	14.73	23.93	40.00	16.07	Vertical	PASS
5	715.4865	25.53	3.34	28.87	46.00	17.13	Vertical	PASS
6	840.6909	28.35	3.79	32.14	46.00	13.86	Vertical	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

For 1GHz to 25GHz

GFSK (above 1GHz)

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	56.76	PK	74	17.24	54.86	31.42	6.98	36.5	1.9
4804.00	43	AV	54	11	41.1	31.42	6.98	36.5	1.9
7206.00	50.95	PK	74	23.05	40.35	37.03	8.87	35.3	10.6
7206.00	42.3	AV	54	11.7	31.7	37.03	8.87	35.3	10.6

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	57.62	PK	74	16.38	55.72	31.42	6.98	36.5	1.9
4804.00	42.3	AV	54	11.7	40.4	31.42	6.98	36.5	1.9
7206.00	51.9	PK	74	22.1	41.3	37.03	8.87	35.3	10.6
7206.00	43.28	AV	54	10.72	32.68	37.03	8.87	35.3	10.6

Frequency(MHz):			2440		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4880.00	54.43	PK	74	19.57	52.37	30.98	7.58	36.5	2.06
4880.00	46.63	AV	54	7.37	44.57	30.98	7.58	36.5	2.06
7320.00	53.17	PK	74	20.83	42.25	37.66	8.56	35.3	10.92
7320.00	41.31	AV	54	12.69	30.39	37.66	8.56	35.3	10.92

Frequency(MHz):			2440		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4880.00	56.83	PK	74	17.17	54.77	30.98	7.58	36.5	2.06
4880.00	46.44	AV	54	7.56	44.38	30.98	7.58	36.5	2.06
7320.00	53.77	PK	74	20.23	42.85	37.66	8.56	35.3	10.92
7320.00	42.64	AV	54	11.36	31.72	37.66	8.56	35.3	10.92

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	55.51	PK	74	18.49	52.44	31.47	7.8	36.2	3.07
4960.00	43.73	AV	54	10.27	40.66	31.47	7.8	36.2	3.07
7440.00	55.96	PK	74	18.04	44.22	38.32	8.72	35.3	11.74
7440.00	41.95	AV	54	12.05	30.21	38.32	8.72	35.3	11.74

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	54.38	PK	74	19.62	51.31	31.47	7.8	36.2	3.07
4960.00	44.12	AV	54	9.88	41.05	31.47	7.8	36.2	3.07
7440.00	54.5	PK	74	19.5	42.76	38.32	8.72	35.3	11.74
7440.00	44.06	AV	54	9.94	32.32	38.32	8.72	35.3	11.74

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

5.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2.

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

See Appendix I

5.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 3 kHz.
3. Set the VBW = 10 KHz.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be -8 dBm.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than -8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

See APPENDIX VI

5.5. 6dB Bandwidth and 99% Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW 100 kHz, VBW > 3 x RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be > 6 dB.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS


See Appendix II & Appendix III

5.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was placed on a turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT was 3 meter:
6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

TEST RESULTS***Results of Band Edges Test (Radiated)*****GFSK**

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	56.34	PK	74	17.66	61.75	27.49	3.32	36.22	-5.41
2390.00	39.91	AV	54	14.09	45.32	27.49	3.32	36.22	-5.41
Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	58.96	PK	74	15.04	64.37	27.49	3.32	36.22	-5.41
2390.00	39.74	AV	54	14.26	45.15	27.49	3.32	36.22	-5.41
Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.38	PK	74	18.62	60.89	27.45	3.38	36.34	-5.51
2483.50	41.31	AV	54	12.69	46.82	27.45	3.38	36.34	-5.51
Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	57.14	PK	74	16.86	62.65	27.45	3.38	36.34	-5.51
2483.50	41.92	AV	54	12.08	47.43	27.45	3.38	36.34	-5.51

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.

5.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSIC63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024. with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS

See Appendix IV

5.8. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance



The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an Metal antenna to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6. Test Setup Photos of the EUT



7. External and Internal Photos of the EUT

See related photo report.


APPENDIX I. Conducted Output Power

Test Result


Mode	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
BLE 1M	0	1.76	1.5	None	≤30	PASS
	19	1.33	1.36	None	≤30	PASS
	39	0.27	1.06	None	≤30	PASS

Mode	Channel	Peak Output Power (dBm)	Peak Power Limit (dBm)	ISED EIRP (dBm)	ISED EIRP Limit (dBm)	Max. Avg. Power (dBm)	Result
BLE 1M	0	1.76	≤30	1.759	≤36.02	None	PASS
	19	1.33	≤30	1.328	≤36.02	None	PASS
	39	0.27	≤30	0.27	≤36.02	None	PASS


Test Graphs



Peak Output Power
BLE 1M_Channel 0



Peak Output Power
BLE 1M_Channel 19




Peak Output Power
BLE 1M_Channel 39

APPENDIX II. 99% Bandwidth

Test Result

Mode	Channel	Center Frequency (MHz)	99% BW (MHz)
BLE 1M	0	2402	1.0570
BLE 1M	19	2440	1.0578
BLE 1M	39	2480	1.0587

Test Graphs




APPENDIX III. 6dB Bandwidth

Test Result

Mode	Channel	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
BLE 1M	0	2402	0.6606	≥0.5	PASS
	19	2440	0.6670		PASS
	39	2480	0.6634		PASS

Test Graphs




APPENDIX IV. Conducted Spurious & Band Edge Emission


Test Result

Mode	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
BLE 1M	0	2398.97	-49.102	-18.41	-30.692	PASS
		2400.00	-51.060	-18.41	-32.650	PASS
		4804.30	-46.960	-18.41	-28.550	PASS
		7205.80	-43.510	-18.41	-25.100	PASS
		9607.90	-50.922	-18.41	-32.512	PASS
		24850.2	-36.826	-18.41	-18.416	PASS
	19	4880.42	-47.664	-18.86	-28.804	PASS
		7319.99	-40.032	-18.86	-21.172	PASS
		9760.18	-52.538	-18.86	-33.678	PASS
		24980.0	-35.590	-18.86	-16.730	PASS
	39	2483.50	-51.189	-19.89	-31.299	PASS
		4959.70	-49.213	-19.89	-29.323	PASS
		7439.85	-42.356	-19.89	-22.466	PASS
		9919.99	-50.469	-19.89	-30.579	PASS
		24948.8	-37.374	-19.89	-17.484	PASS


Note: input compensation coefficient (dB)= Cable Loss (dB)

Test Graphs







30.0 MHz - 25000.0 MHz
BLE 1M_Channel 19



In-Band Reference Level
BLE 1M_Channel 39



Out Of Band Emission
BLE 1M_Channel 39




30.0 MHz - 25000.0 MHz
BLE 1M_Channel 39

APPENDIX V. Duty Cycle

Test Result

Mode	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)	1/T
BLE 1M	0	2.136	2.499	85.49	0.8549	0.6808	0.4682
	19	2.136	2.499	85.49	0.8549	0.6808	0.4682
	39	2.135	2.499	85.44	0.8544	0.6834	0.4684

Test Graphs




APPENDIX VI. Power Spectral Density

Test Result

Mode	Channel	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
BLE 1M	0	-14.130	≤ 8	PASS
BLE 1M	19	-14.200	≤ 8	PASS
BLE 1M	39	-15.140	≤ 8	PASS

Test Graphs



.....End of Report.....