



CHANGCHUNSHIXINXINDIANZIYOUXIANGONGSI

acknowledgement

SPECIFICATION FOR APPROVAL

客 戶:
CUSTOMER: CHANGCHUNSHIXINXINDIANZIYOUXIANGONGSI

客 戶 料 號:
CUST P/N: 1.007.00258

內 部 料 號 :
LCX P/N: LCX-KH226TX019

產 品 型 號:
DESC: Ø16.5*39-0.08*105P-11TS-25-43.52LOC-BMJ1.5

日 期:
DATE: 2024/4/12

版 本:
Version: A.0

制作 PREPARED BY	审核 CHECKED BY	批准 APPROVED BY	客戶承認 CUSTOMER APPROVE
Xiong Gang 2024/4/12	Gao Yinghong 2024/4/12		

address: 4F 401, Building 7B, Rongchang Industrial Park, No. 440, Hengkeng Village, Guancheng Community, Guanhu Street, Longhua District, Shenzhen
telephone: 13828741697

产品规格书 <u>SPECIFICATION</u>		edition A/0	manufacture: Xiong Gang 2024/4/12	examine: Gao Yinghong 2024/4/12
Drawing number: LCX-GCQP0001164			Customer code: CUST	KH226
Specification and model	Ø16.5*39-0.08*105P-11TS-25-43.52LOC-BMJ1.5	Customer part number: CUST P/N		1.007.00258
		Internal part number: IN P/N		LCX-KH226TX019

版本变更履历

Version Change History

版本 Rev	变 更 前 Before Change	变 更 后 After Change	更 改 日 期 Change Date	批 准 Approved By
A/0	New issue	-----	2024/4/12	Gao Yinghong

物料清单

Bill of material

NO	Material name	Internal part number	Material specification	unit	dosage	remark
1	coil		Silk-covered wire0.08*105	g	5.5	
2	Hard disk		43.5*5.3*1.0	PCS	1	
3	Foam back glue		43*5.5*1.5	PCS	1	
4	High-temperature tape		9*15*0.03	PCS	1	

产品规格书 <u>SPECIFICATION</u> Drawing number: LCX-GCQP0001164							edition A/0		manufacture: Xiong Gang 2024/4/12			examine: Gao Yinghong 2024/4/12			
									Customer code: CUST			KH226			
Internal part number:			Ø16.5*39-0.08*105P-11TS-25-43.52LOC-BMJ1.5							ustomer part number: CUST P/N			1.007.00258		
										Internal part number: IN P/N			LCX-KH226TX019		
A	B														
2 ±0.5	2.3 ±0.5														

一、尺寸 DIMENSION:(mm) 绕线模具：16.5 线圈单重：5.5



remark:

1. coil winding as shown in Figure 1, structure according to size requirements, can not be scattered, loose line.
2. Figure 2 Hard magnetic disc, specification: 43.5*5.3*0.8
3. as shown in Figure 3, the coil is glued in the center of the magnetic disc, and the lead is inserted into the slot
4. 43*5.5*1.5 foam double-sided tape is affixed to the back of the magnetic disc, and the release paper tape is torn by hand

二、原理图 SCHEMATIC DIAGRAM:					

三、绕线参数 Winding Specification:					
序号 NO	端子 TERMINAL		线径 WIRE	线材分解温度 Temperature	圈数 Turns
L1	S	F	Silk-covered wire0.08*105	180-250 度	11TS
绕线方向 Winding Direction					
anticlockwise					

四、电气特性 ELECTRICAL CHARACTERISTIC: :					
温度 TEMPERATURE:25±10°C,湿度 RELATIVE HUMIDITY:65±20%					
序号 NO	磁片材质 Disk material	inductance LS	impedance DCR	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
L1		3.8uH±10% (Single coil)	50mΩ±10%	100KHz/1.0V	U2832
L2	Hard disk	6.5uH±5% (Fit magnetic disc)	50mΩ±10%	100KHz/1.0V	U2832