TEST REPORT

KCTL Inc.
65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 443-390, Korea
TEL: 82 70 5008 1021
FAX: 82 505 299 8311

http://www.kctl.co.kr

1. Applicant

Name:	Samsung Electronics Co., Ltd.
Address:	19 Chapin Rd. Building D Pine Brook NJ, 07058

2. Sample Description:

FCC ID:	A3LATKM005000
IC ID:	649E-ATKM005000
Type of equipment:	IOT Module
Basic Model:	ATKM005000

3. Date of Test: June 28 ~ July 04, 2016

4. Test standard used: FCC Part 15 Subpart C 15.247
RSS-247 Issue 1 May 2015
RSS GEN Issue 4 November 2014

5. Test Results

Test Item:	Refer to page 7
Result:	Complied (Refer to page 8 ~ page 98)
Measurement Uncertainty:	Refer to page 7

This result shown in this report refer only to the sample(s) tested unless otherwise stated.

Affirmation	Tested by Name: TAE YOUNG, KIM	Technical Manager Name: MIN GI, SON

2016. 07. 07

KCTL Inc.

[Contents]

1. Client information **3**
2. Laboratory information **4**
3. Description of E.U.T. **5**
3.2 General description 5
3.3 Test frequency 6
3.4 Test Voltage 6
4. Summary of test results **7**
4.1 Standards & results 7
4.2 Uncertainty 7
5. Test results **8**
5.1 Antenna Requirement 8
5.2 Maximum Peak Output Power 9
5.3 Peak Power Spectral Density 12
5.4 6 dB Bandwidth(DTS Channel Bandwidth) 24
5.5 Spurious Emission, Band Edge, and Restricted bands 45
5.6 Conducted Emission 96
6. Test equipment used for test **99**

This test report shall not be reproduced, except in full, without the written approval

1. Client information

Applicant:	Samsung Electronics Co., Ltd.
Address:	19 Chapin Rd. Building D Pine Brook NJ, 07058
Telephone number:	+82-31-277-2635
Facsimile number:	+82-31-277-2784
Contact person:	Chan Ho, Youn / jjano.youn@samsung.com

Manufacturer:	Samsung Electronics Co., Ltd.
Address:	19 Chapin Rd. Building D Pine Brook NJ, 07058

This test report shall not be reproduced, except in full, without the written approval

2. Laboratory information

Address

KCTL Inc.
480-5, Sin-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, Korea
Telephone Number: +82-70-5008-1016 Facsimile Number: +82-505-299-8311

Certificate

KOLAS No.: KT231
FCC Site Designation No.: KR0040
FCC Site Registration No.: 687132
VCCI Site Registration No.: R-3327, G-198, C-3706, T-1849
IC Site Registration No.:8035A-2

SITE MAP



This test report shall not be reproduced, except in full, without the written approval

3. Description of E.U.T.

3.1 Basic description

Applicant	Samsung Electronics Co., Ltd.
Address of Applicant	19 Chapin Rd. Building D Pine Brook NJ, 07058
Manufacturer	Samsung Electronics Co., Ltd.
Address of Manufacturer	19 Chapin Rd. Building D Pine Brook NJ, 07058
Type of equipment	IOT Module
Basic Model	ATKM005000
Serial number	N/A

3.2 General description

Frequency Range	2 412 ㎒ ~ 2 462 ㎒ (802.11b/g/n_HT20)
Type of Modulation	802.11b: DSSS, 802.11g/n: OFDM
The number of channels	11 ch (802.11b/g/n_HT20)
Type of Antenna	PIFA antenna
Antenna Gain	2.80 ㏈i
Transmit Power	24.19 ㏈m
Power supply	DC 5 ㏈, DC 12 ㏈
Product SW/HW version	1.1 / 1.1
Radio SW/HW version	1.1 / 1.1
Test SW Version	wl_wiced
RF power setting in TEST SW	802.11b :-1, 802.11g :-1, 802.11n HT20 :-1

Note : The above EUT information was declared by the manufacturer.

This test report shall not be reproduced, except in full, without the written approval

3.3 Test frequency

	Frequency
Lowest frequency	2 412 ㎒
Middle frequency	2 437 ㎒
Highest frequency	2 462 ㎒

3.4 Test Voltage

Mode	Voltage
Norminal Voltage	DC 5 V, DC 12 V

This test report shall not be reproduced, except in full, without the written approval

4. Summary of test results

4.1 Standards & results

FCC Rule Reference	IC Rule Reference	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	-	Antenna Requirement	5.1	C
15.247(b)(3)	RSS-247, 5.4(4)	Maximum Peak Output Power	5.2	C
15.247(e)	RSS-247, 5.2	Peak Power Spectral Density	5.3	C
15.247(a)(2)	RSS-247, 5.2	6 dB Channel Bandwidth	5.4	C
-	RSS-247, 5.2	Occupied Bandwidth	5.4	C
15.247(d), 15.205(a), 15.209(a)	RSS-247, 5.5 RSS-GEN, 8.9, 10	Spurious Emission, Band Edge and Restricted bands	5.5	C
15.207(a)	RSS-GEN, 8.8	Conducted Emissions	5.6	C

Note: C = complies
NC = Not complies
NT = Not tested
NA = Not Applicable

Note : The general test methods used to test this device is ANSI C63.10:2013

4.2 Uncertainty

Measurement Item	Expanded Uncertainty U = *k*Uc (*k* = 2)	
Conducted RF power	1.44 dB	
Conducted Spurious Emissions	1.52 dB	
Radiated Spurious Emissions	30 MHz ~ 300 MHz:	+ 4.94 dB, - 5.06 dB
		+ 4.93 dB, - 5.05 dB
	300 MHz ~ 1 000 MHz:	+ 4.97 dB, - 5.08 dB
		+ 4.84 dB, - 4.96 dB
	1 GHz ~ 25 GHz:	+ 6.03 dB, - 6.05 dB
Conducted Emissions	9 kHz ~ 150 kHz:	3.75 dB
	150 kHz ~ 30 MHz:	3.36 dB

This test report shall not be reproduced, except in full, without the written approval

5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

-Complied

The transmitter has permanently attached PIFA antenna(internal antenna) on PCB.

This test report shall not be reproduced, except in full, without the written approval

5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(b)(3), For systems using digital modulation in the 902-928 ㎒, 2 400-2 483.5 ㎒, and 5 725-5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 ㏈i. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 ㏈i are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in ㏈ that the directional gain of the antenna exceeds 6 ㏈i.

5.2.2 Measurement Procedure

These test measurement settings are specified in section 9.0 of 558074 D01 DTS Meas Guidance.

5.2.2.1 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter.
The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

This test report shall not be reproduced, except in full, without the written approval

5.2.3 Test Result

- Complied

- DC 5 V

- 802.11b

Channel	Frequency [㎒]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	17.07	30.00	12.93	13.63
Middle	2 437	16.97	30.00	13.03	13.52
Highest	2 462	16.87	30.00	13.13	13.46

- 802.11g

Channel	Frequency [㎒]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	23.08	30.00	6.92	12.23
Middle	2 437	23.79	30.00	6.21	12.75
Highest	2 462	23.69	30.00	6.31	12.68

- 802.11n HT20

Channel	Frequency [㎒]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	23.79	30.00	6.21	11.89
Middle	2 437	23.99	30.00	6.01	11.92
Highest	2 462	23.89	30.00	6.11	11.81

NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

- DC 12 V

- 802.11b

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	16.87	30.00	13.13	13.45
Middle	2 437	16.97	30.00	13.03	13.55
Highest	2 462	16.97	30.00	13.03	13.50

- 802.11g

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	23.38	30.00	6.62	12.43
Middle	2 437	24.19	30.00	5.81	12.35
Highest	2 462	23.28	30.00	6.72	12.32

- 802.11n HT20

Channel	Frequency [MHz]	Result [dBm]	Limit [dBm]	Margin [dB]	Average Power [dBm]
Lowest	2 412	23.59	30.00	6.41	11.74
Middle	2 437	23.48	30.00	6.52	11.64
Highest	2 462	23.48	30.00	6.52	11.57

NOTE:
1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

5.3 Peak Power Spectral Density

5.3.1 Regulation

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3.2 Measurement Procedure

These test measurement settings are specified in section 10.0 of 558074 D01 DTS Meas Guidance.

5.3.2.1 Method PKPSD (peak PSD)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1) Set analyzer center frequency to DTS channel center frequency.

2) Set the span to 1.5 times the DTS bandwidth.

3) Set the RBW to: 3 ㎑ ≤ RBW ≤ 100 ㎑.

4) Set the VBW ≥ 3 x RBW.

5) Detector = peak.

6) Sweep time = auto couple.

7) Trace mode = max hold.

8) Allow trace to fully stabilize.

9) Use the peak marker function to determine the maximum amplitude level within the RBW.

10) If measured value exceeds limit, reduce RBW (no less than 3 ㎑) and repeat.

This test report shall not be reproduced, except in full, without the written approval

5.3.3 Test Result

- Complied

- DC 5 V

- 802.11b

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	4.53	-6.86	8	14.86
Middle	4.61	-6.63	8	14.63
Highest	4.40	-6.89	8	14.89

- 802.11g

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	0.33	-7.28	8	15.28
Middle	0.24	-7.47	8	15.47
Highest	0.24	-7.41	8	15.41

- 802.11n HT20

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-0.07	-6.20	8	14.20
Middle	-0.15	-6.20	8	14.20
Highest	-0.03	-6.22	8	14.22

NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

- DC 12 V

- 802.11b

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	4.67	-6.89	8	14.89
Middle	4.58	-7.07	8	15.07
Highest	4.49	-7.35	8	15.35

- 802.11g

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	0.38	-7.50	8	15.50
Middle	0.56	-7.42	8	15.42
Highest	0.47	-7.39	8	15.39

- 802.11n HT20

Channel	Result (RBW=100 ㎑) [dBm]	Result (RBW=3 ㎑) [dBm]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-0.04	-6.68	8	14.68
Middle	-0.09	-6.54	8	14.54
Highest	-0.02	-6.71	8	14.71

NOTE:

2. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

5.3.4 Test Plot

Figure 1. Plot of the Power Density

- DC 5 V

- 802.11b

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11g

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11n HT20

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- DC 12 V

- 802.11b

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11g

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11n HT20

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

5.4 6 dB Bandwidth(DTS Channel Bandwidth)

5.4.1 Regulation

According to §15.247(a)(2) Systems using digital modulation techniques may operate in the 902–928 ㎒, 2 400–2 483.5 ㎒, and 5 725–5 850 ㎒ bands. The minimum 6 ㏈ bandwidth shall be at least 500 ㎑.

5.4.2 Measurement Procedure

These test measurement settings are specified in section 8.0 of 558074 D01 DTS Meas Guidance.

5.4.2.1 DTS Channel Bandwidth-Option 1

1) Set RBW = 100 ㎑.
2) Set the video bandwidth (VBW) ≥ 3 x RBW.
3) Detector = Peak.
4) Trace mode = max hold.
5) Sweep = auto couple.
6) Allow the trace to stabilize.
7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 ㏈ relative to the maximum level measured in the fundamental emission.

5.4.2.2 DTS Channel Bandwidth Measurement Procedure-Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X ㏈ bandwidth mode with X set to 6 ㏈, if the functionality described above (i.e., RBW = 100 ㎑, VBW ≥ 3 x RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 ㏈.

This test report shall not be reproduced, except in full, without the written approval

5.4.3 Test Result

- Complied

- DC 5 V

- 802.11b

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	9.14	0.50	11.79
Middle	2 437	9.09	0.50	11.79
Highest	2 462	9.09	0.50	11.74

- 802.11g

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	16.38	0.50	16.88
Middle	2 437	16.38	0.50	16.88
Highest	2 462	16.38	0.50	16.83

- 802.11n HT20

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	17.63	0.50	17.88
Middle	2 437	17.58	0.50	18.08
Highest	2 462	17.63	0.50	18.08

NOTE:
1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

- DC 12 V

- 802.11b

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	8.64	0.50	11.79
Middle	2 437	8.69	0.50	11.79
Highest	2 462	8.64	0.50	11.79

- 802.11g

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	16.38	0.50	16.88
Middle	2 437	16.38	0.50	16.88
Highest	2 462	16.38	0.50	16.93

- 802.11n HT20

Channel	Frequency [㎒]	6 ㏈ Bandwidth [㎒]	Min. Limit [㎒]	Occupied Bandwidth (99 % BW) [㎒]
Lowest	2 412	17.58	0.50	18.08
Middle	2 437	17.63	0.50	17.93
Highest	2 462	17.58	0.50	18.03

NOTE:
1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

This test report shall not be reproduced, except in full, without the written approval

5.4.4 Test Plot

Figure 2. Plot of the 6 ㏈ Bandwidth & Occupied Bandwidth

- DC 5 V

- 802.11b_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11g_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11n HT20_6 dB Bandwidth

Lowest Channel (2 412 MHz)



Middle Channel (2 437 MHz)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- DC 12 V

- 802.11b_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11g_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11n HT20_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- DC 5 V

- 802.11b_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11g_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11n HT20_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- DC 12 V

- 802.11b_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

- 802.11g_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Highest Channel (2 462 ㎒)



- 802.11n HT20_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



This test report shall not be reproduced, except in full, without the written approval

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



This test report shall not be reproduced, except in full, without the written approval

5.5 Spurious Emission, Band Edge, and Restricted bands

5.5.1 Regulation

According to §15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall notexceed the field strength levels specified in the following table:

Frequency (㎒)	Field strength (㎛/m)	Measurement distance (m)
0.009 - 0.490	2 400/F(㎑)	300
0.490 - 1.705	24 000/F(㎑)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 ㎒, 76–88 ㎒, 174–216 ㎒ or 470–806 ㎒. However, operation within these frequency bands is permItted under other sections of this part, e.g., §§15.231 and 15.241.

This test report shall not be reproduced, except in full, without the written approval

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 – 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 – 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 – 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 – 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 – 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 – 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 – 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 – 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525 25	2 483.5 – 2 500	17.7 - 21.4
8.376 25 - 8.386 75	156.7 - 156.9	2 690 – 2 900	22.01 - 23.12
8.414 25 - 8.414 75	162.012 5 - 167.17	3 260 – 3 267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3 332 – 3 339	31.2 - 31.8
12.519 75 - 12.520 25	240 - 285	3 345.8 – 3 358	36.43 - 36.5
12.576 75 - 12.577 25	322 - 335.4	3 600 – 4 400	Above 38.6
13.36 - 13.41			

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

This test report shall not be reproduced, except in full, without the written approval

5.5.2 Measurement Procedure

5.5.2.1 Band-edge Compliance of RF Conducted Emissions

5.5.2.1.1 Reference Level Measurement

Establish a reference level by using the following procedure:

1) Set instrument center frequency to DTS channel center frequency.
2) Set the span to ≥ 1.5 times the DTS bandwidth.
3) Set the RBW = 100 ㎑.
4) Set the VBW ≥ 3 x RBW.
5) Detector = peak.
6) Sweep time = auto couple.
7) Trace mode = max hold.
8) Allow trace to fully stabilize.
9) Use the peak marker function to determine the maximum PSD level.

5.5.2.1.2 Emissions Level Measurement

1) Set the center frequency and span to encompass frequency range to be measured.
2) Set the RBW = 100 ㎑.
3) Set the VBW ≥ 3 x RBW.
4) Detector = peak.
5) Ensure that the number of measurement points ≥ span/RBW
6) Sweep time = auto couple.
7) Trace mode = max hold.
8) Allow trace to fully stabilize.
9) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

This test report shall not be reproduced, except in full, without the written approval

5.5.2.2 Conducted Spurious Emissions

Set the spectrum analyzer as follows:

1) Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
2) RBW = 100 ㎑
3) VBW ≥ RBW
4) Sweep = auto
5) Detector function = peak
6) Trace = max hold
7) Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
8) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

This test report shall not be reproduced, except in full, without the written approval

5.5.2.3 Radiated Spurious Emissions

1) The preliminary and final rdiated measurements were performed to determine the frequency producing the maximum emissions in at a 10m anechoic chamber. The EUT was tested at a distance 3 meters.
2) The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360˚.
3) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 ㎑ to 30 ㎒ using the loop antenna, and from 30 to 1 000 ㎒ using the TRILOG broadband antenna, and from 1 000 ㎒ to 26 500 ㎒ using the horn antenna.
4) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
5) The 0.8m height is for below 1 G testing, and 1.5m is for above 1G testing.

Note

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 ㎑ for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 ㎓.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 ㎒ for Peak detection and frequency above 1 ㎓.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 ㎒ and the video bandwidth is 3 ㎒ for Average detection (AV) at frequency above 1 ㎓. (Detector = RMS, Averaging type = power)
   A duty cycle correction factor has to be added to the measurement result.

- DC 5 V

- 802.11b



- Note$_{1)}$: period : 8.453 ms, On time : 8.411 ms
- Note$_{2)}$: DCCF = 10 log(1 / x) = 10 log(8.453 / 8.411) = 0.02

This test report shall not be reproduced, except in full, without the written approval

- 802.11g



- Note$_{1)}$: period : 1.443 ms, On time : 1.387 ms
- Note$_{2)}$: DCCF = 10 log(1 / x) = 10 log(1.443 / 1.387) = 0.17

- 802.11n HT20



- Note$_{1)}$: period : 1.352 ms, On time : 1.295 ms
- Note$_{2)}$: DCCF = 10 log(1 / x) = 10 log(1.352 / 1.295) = 0.19

This test report shall not be reproduced, except in full, without the written approval