



683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

Tel: +82-31-321-2664 Fax: +82-31-321-1664

<http://www.digitalemcc.com>

CERTIFICATION OF COMPLIANCE

SAMSUNG ELECTRONICS CO., LTD.
416, Maetan-3Dong, Yeongtong-Gu, Suwon-City,
Gyeonggi-Do, Korea 443-742

Dates of Tests: January 14 ~ 19, 2006
Test Report S/N: DR50110601G
Test Site : DIGITAL EMC CO., LTD.

FCC ID

A3LBTW300

APPLICANT

SAMSUNG ELECTRONICS CO., LTD.

FCC Classification	:	FHSS Sequence Spread Spectrum (FHSS)
Device name	:	2ch Audio Transceiver
Manufacturer	:	Samsung Electronics Huizhou Co., Ltd
Model name	:	BTW300
Test Device Serial number	:	Identical prototype
FCC Rule Part(s)	:	FCC Part 2 and Part 15 Subpart C(15.247)
		RSS-210
Frequency Range	:	2402 ~ 2480 MHz
Max. Output power	:	6.56 mW Conducted
Data of issue	:	January 20, 2006

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



NVLAP LAB CODE 200559-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
2. INFORMATION ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 TRANSMITTER REQUIREMENTS	6
3.2.1 CARRIER FREQUENCY SEPARATION	6
3.2.2 NUMBER OF HOPPING FREQUENCIES	8
3.2.3 20 dB BANDWIDTH	11
3.2.4 TIME OF OCCUPANCY (Dwell Time)	14
3.2.5 PEAK OUTPUT POWER	16
3.2.6 CONDUCTED SPURIOUS EMISSIONS	19
3.2.7 RADIATED EMISSIONS	25
3.2.8 AC CONDUCTED EMISSIONS	31
3.3 RECEIVER REQUIREMENTS	35
3.3.1 AC CONDUCTED EMISSIONS	35
3.3.2 RADIATED EMISSIONS	39
ANNEX TEST EQUIPMENT USED FOR TESTS	41

1. General Information

This report contains the result of tests performed by:

DIGITAL EMC CO., LTD.

Address : 683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080

<http://www.digitalemccom> E-mail : demc@unitel.co.kr

Tel: +82-31-321-2664 Fax: +82-31-321-1664

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200559-0.

Test operator: engineer

January 20, 2006

Won -Jong LEE



Data

Name

Signature

Report Reviewed By: Technical Director

January 20, 2006

Harvey Sung



Data

Name

Signature

Ordering party:

Company name : SAMSUNG ELECTRONICS CO., LTD.

Address : 416, Maetan-3Dong, Yeongtong-Gu

Zip code : 443-742

City/town : Suwon-City

Country : Korea

Date of order : January 3, 2006

2. Information about test item

FCCID: A3LBTW300

IC: 649E-BTW300

2.1 Equipment information

Equipment model name	BTW300
Type of equipment	Bluetooth Equipment
Frequency band	2402 ~ 2480 MHz
Type of Modulation	GFSK
Channel Spacing	1.0 MHz
Type of antenna	SMD Antenna (Max. Gain: 4.4dBi)
Power	DC 5 V

2.2 Tested frequency

Frequency	TX	RX
Low frequency	2402MHz	2402MHz
Middle frequency	2441MHz	2441MHz
High frequency	2480MHz	2480MHz

2.3 Tested environment

Temperature	: 15 ~ 35 (°C)
Relative humidity content	: 20 ~ 75 %
Air pressure	: 86 ~ 103 kPa
Details of power supply	: 5 VDC

2.4 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing

-> none

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
I. Transmit mode(Tx)				
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
	Number of Hopping Frequencies	> 75 hops		C
	20 dB Bandwidth	< 1 MHz		C
	Dwell Time	0.4 seconds within a 30 second period per any frequency		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(c)	Band-edge / Conducted	The radiated emission to any 100 kHz of outband shall be at least 20dB below the highest inband spectral density.		C
	Conducted Spurious Emissions		C	
15.205 15.209	Radiated Emissions	< FCC 15.209 limits	Radiated	C
15.207	AC Conducted Emissions	EN 55022	Line Conducted	C
II. Receive mode(Rx)				
15.207	AC Conducted Emissions	EN 55022	Line Conducted	C
15.209	Radiated Emissions	< FCC 15.209 limits	Radiated	C
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable				

The sample was tested according to the following specification:

RSS-210 ; FCC Parts 15.247 ; ANSI C-63.4-2003

3.2 Transmitter requirements

3.2.1 Carrier Frequency Separation

Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz (1% of the span or more) Sweep = auto

VBW = 30 kHz Detector function = peak

Trace = max hold

Measurement Data: **Complies**

Frequency of marker #1 (MHz)	Frequency of marker #2 (MHz)	Test Results	
		Carrier Frequency Separation (MHz)	Result
2441.025	2242.030	1.005	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup





Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation



3.2.2 Number of Hopping Frequencies

Procedure:

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to:

Frequency range 1: Start = 2389.5MHz, Stop = 2414.5 MHz

2: Start = 2414.5MHz, Stop = 2439.5 MHz

3: Start = 2439.5MHz, Stop = 2464.5 MHz

4: Start = 2464.5MHz, Stop = 2489.5 MHz

RBW = 300 kHz (1% of the span or more) Sweep = auto

VBW = 300 kHz (VBW $\geq$ RBW) Detector function = peak

Trace = max hold Span = 25MHz

Measurement Data: **Complies**

Total number of Hopping Channels	79
---	----

- See next pages for actual measured spectrum plots.



Minimum Standard:

At least 75 hopes



Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Number of Hopping Frequencies



Number of Hopping Frequencies



3.2.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 10 kHz (1% of the 20dB bandwidth or more) Sweep = auto

VBW = 30 kHz ($VBW \geq RBW$) Detector function = peak

Trace = max hold

Measurement Data: **Complies**

Frequency (MHz)	Channel No.	Test Results	
		Measured Bandwidth (MHz)	Result
2402	1	0.740	Complies
2441	40	0.733	Complies
2480	79	0.740	Complies

- See next pages for actual measured spectrum plots.



Minimum Standard:

The transmitter shall have a maximum 20dB bandwidth of 1 MHz.


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

20 dB Bandwidth



20 dB Bandwidth



3.2.4 Time of Occupancy (Dwell Time)

Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW $\geq$ RBW)

Trace = max hold

Detector function = peak

Measurement Data: Complies

Burst duration in one hop (us)	Test Results	
	Dwell Time (ms)	Result
500	160.055	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

0.4 seconds within a 30 second period per any frequency

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Dwell Time for BTW300

The system makes worst case 1600 hops per second or 1 time slot has a length of 625 us with 79 channels. A DH 1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case $1600/2 = 800$ hops per second with 79 channels. So you have each channel $800/79 = 10.13$ times per second and so for a period of $0.4 \times 79 = 31.6$ seconds you have $10.13 \times 31.6 = 320.11$ times of appearance.

Each Tx-time per appearance is 500 us

So we have $320.11 \times 500 \text{ us} = 160.055 \text{ ms}$ per 31.6 seconds.



3.2.5 Peak Output Power

Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 1 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 1 MHz (VBW $\geq$ RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: **Complies**

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	1	8.17	6.56	Complies
2441	40	6.50	4.47	Complies
2480	79	4.67	2.93	Complies



- See next pages for actual measured spectrum plots.

Minimum Standard:	< 1W
--------------------------	------


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Peak Output Power



Peak Output Power



3.2.6 Conducted Spurious Emissions

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 100 MHz

Detector function = peak

Trace = max hold

Sweep = auto



Measurement Data: **Complies**

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
--------------------------	----------



Measurement Setup



Same as the Chapter 3.2.1 (Figure 1)

- Low band with hopping disabled**- Low band with hopping enabled**


- Low channel spurious



- Mid channel ref**- Mid channel spurious**

- High band with hopping disabled**- High band with hopping enabled**

- High channel spurious



3.2.7 Radiated Emissions

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic.

RBW = 120 kHz (30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Trace = max hold

VBW ≥ RBW (Peak)

VBW ≥ 10Hz (Average)

Sweep = auto

Measurement Data: **Complies**


- No emissions were detected at a level greater than 10dB below limit.
- Refer to the next page.

Minimum Standard: FCC Part 15.205(a), 15.205(b), 15.209(a) and (b)


Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.


Restricted Band Edge: Low Channel (Peak, Horizontal)




Restricted Band Edge: Low Channel (Average, Horizontal)







Restricted Band Edge: Low Channel (Peak, Vertical)



Restricted Band Edge: Low Channel (Average, Vertical)



Restricted Band Edge: High Channel (Peak, Horizontal)**Restricted Band Edge: High Channel (Average, Horizontal)**

Restricted Band Edge: High Channel (Peak, Vertical)**Restricted Band Edge: High Channel (Average, Vertical)**

Radiated Spurious Emission Data

<u>Low Channel(2402MHz)</u>										
Frequency (MHz)	ANT Pol. (H/V)	Reading Value (dBuV)		T.F (dB)	Result (dBuV)		Limit (dBuV)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	H	57.47	36.6	8.56	66.03	45.19	74	54	7.97	8.81
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
<u>Middle Channel(2441MHz)</u>										
Frequency (MHz)	ANT Pol. (H/V)	Reading Value (dBuV)		T.F (dB)	Result (dBuV)		Limit (dBuV)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	H	61.97	37.8	8.65	70.62	46.45	74	54	3.38	7.55
7323	H	47.13	31.8	12.83	59.96	44.63	74	54	14.04	9.37
-	-	-	-	-	-	-	-	-	-	-
<u>High Channel(2480MHz)</u>										
Frequency (MHz)	ANT Pol. (H/V)	Reading Value (dBuV)		T.F (dB)	Result (dBuV)		Limit (dBuV)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	H	61.30	38.1	8.75	70.05	46.88	74	54	3.95	7.12
7440	H	46.55	32.5	13.40	59.95	45.87	74	54	14.05	8.13
-	-	-	-	-	-	-	-	-	-	-

Not. 1. “ ** “ : No other emissions were detected at a level greater than 30dB below limit.

2. T.F(Total Factor) = Cable Loss + Ant Factor –AMP Gain

3. Result = Reading Value + T.F

4. Margin = Limit - Result

3.2.8 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: **Complies**

- Refer to the next page.

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Measurement Setup






Figure 2: Measurement setup for AC Conducted Emission

AC Conducted Emissions (Line)



AC Conducted Emissions (Neutral)



AC Conducted Emissions (DATA)

***** DIGITAL EMC *****
 <<CONDUCTED EMISSION>>

16 January, 2006 17:57
 HOPPING.dat

Standard : FCC PART.15
 Manufacturer : SAMSUNG
 Model : BTW300
 Operator : W.J.LEE
 AC Power : 120V 60Hz
 Temp, Humidity : 21 43
 Remark1 : HOPPING MODE
 Remark2 :
 Remark3 :
 :

Final Result

--- N Phase ---

No.	Frequency	Reading QP	Reading AV	c.f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	[MHz]	[dB(μV)]	[dB(μV)]	[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]
1	0.150	43.4	35.4	1.8	45.2	37.2	66.0	56.0	20.8	18.8
2	0.283	43.0	35.7	0.9	43.9	36.6	60.7	50.7	16.8	14.1
3	0.579	41.1	33.0	0.4	41.5	33.4	56.0	46.0	14.5	12.6
4	0.726	41.9	32.7	0.4	42.3	33.1	56.0	46.0	13.7	12.9
5	0.878	39.0	22.8	0.3	39.3	23.1	56.0	46.0	16.7	22.9
6	1.161	39.4	27.0	0.2	39.6	27.2	56.0	46.0	16.4	18.8

--- L1 Phase ---

No.	Frequency	Reading QP	Reading AV	c.f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	[MHz]	[dB(μV)]	[dB(μV)]	[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]
1	0.150	42.6	36.6	1.8	44.4	38.4	66.0	56.0	21.6	17.6
2	0.576	36.2	25.4	0.4	36.6	25.8	56.0	46.0	19.4	20.2
3	0.725	37.6	24.3	0.4	38.0	24.7	56.0	46.0	18.0	21.3
4	1.165	34.4	16.5	0.3	34.7	16.8	56.0	46.0	21.3	29.2

3.3 Receiver requirements

3.3.1 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its receiving function. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: **Complies**

- Refer to the next page.

Minimum Standard: FCC Part 15.107(a)/EN 55022


Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency


Measurement Setup

Same as the Chapter 3.2.9 (Figure 2)

AC Conducted Emissions (Line)



AC Conducted Emissions (Neutral)



AC Conducted Emissions (DATA)

***** DIGITAL EMC *****
 <<CONDUCTED EMISSION>>

16 January, 2006 15:46

idle.dat

Standard : FCC PART.15
 Manufacturer : SAMSUNG
 Model : BTW300
 Operator : W.J.LEE
 AC Power : 120V 60Hz
 Temp, Humidity : 21 43
 Remark1 : RECEIVER MODE
 Remark2 :
 Remark3 :
 :

Final Result

--- N Phase ---

No.	Frequency	Reading QP	Reading AV	c.f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	[MHz]	[dB(μV)]	[dB(μV)]	[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]
1	0.150	48.2	39.9	1.8	50.0	41.7	66.0	56.0	16.0	14.3

--- L1 Phase ---

No.	Frequency	Reading QP	Reading AV	c.f	Result QP	Result AV	Limit QP	Limit AV	Margin QP	Margin AV
	[MHz]	[dB(μV)]	[dB(μV)]	[dB]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB(μV)]	[dB]	[dB]
1	0.150	48.8	40.2	1.8	50.6	42.0	66.0	56.0	15.4	14.0
2	0.294	43.0	32.2	0.9	43.9	33.1	60.4	50.4	16.5	17.3
3	0.595	40.4	23.2	0.4	40.8	23.6	56.0	46.0	15.2	22.4
4	0.740	43.0	24.0	0.4	43.4	24.4	56.0	46.0	12.6	21.6
5	1.177	40.2	25.0	0.3	40.5	25.3	56.0	46.0	15.5	20.7

3.3.2 Radiated Emissions

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in a OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Frequency Range = 30 MHz ~ 10th harmonic.

RBW = 120 kHz (30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Trace = max hold

VBW ≥ RBW (Peak)

VBW ≥ 10Hz (Average)

Sweep = auto

Measurement Data: **Complies**

- Refer to the next page.

Minimum Standard: FCC Part 15.205(a), 15.205(b), 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

Measurement Data:

Frequency (MHz)	ANT Pol. (H/V)	Reading Value (dBuV)		T.F (dB)	Result (dBuV)		Limit (dBuV)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
-	-	-	-	-	-	-	-	-	-	-
No emissions were detected at a level greater than 10dB below limit.										
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

APPENDIX

TEST EQUIPMENT USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment.

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	S/N
01	Spectrum Analyzer	Agilent	E4404B	18/04/06	30601-01-6025569
02	Spectrum Analyzer	H.P	8563E	06/10/06	3551A04634
03	Spectrum Analyzer	Agilent	E4440A	06/10/06	MY45304199
04	Power Meter	H.P	EPM-442A	04/07/06	GB37170413
05	Power Sensor	H.P	8481A	05/07/06	3318A96332
06	Frequency Counter	H.P	5342A	21/10/06	2119A04450
07	Multifunction Synthesizer	H.P	8904A	21/10/06	3633A08404
08	Signal Generator	Rohde Schwarz	SMR20	17/05/06	101251
09	Signal Generator	H.P	E4421A	05/07/06	US37230529
10	Audio Analyzer	H.P	8903B	07/07/06	3011A0944B
11	Modulation Analyzer	H.P	8901B	05/07/06	3028A03029
12	CDMA Mobile Station Test Set	H.P	8924C	21/10/06	US35360688
13	Power Splitter	WEINSCHTEL	1593	25/10/06	332
14	BAND Reject Filter	Microwave Circuits	N0308372	21/10/06	3125-01DC0312
15	BAND Reject Filter	Wainwright	WRCG1750	21/10/06	SN2
16	AC Power supply	DAEKWANG	5KVA	18/04/06	N/A
17	DC Power Supply	H.P	6622A	18/04/06	465487
18	Attenuator (30dB)	H.P	8498A	21/10/06	50101
19	Attenuator (10dB)	WEINSCHTEL	23-10-34	24/10/06	BP4387
20	HORN ANT	EMCO	3115	06/03/07	6419
21	HORN ANT	EMCO	3115	04/25/07	21097
22	HORN ANT	A.H.Systems	SAS-574	09/11/06	154
23	HORN ANT	A.H.Systems	SAS-574	09/11/06	155
24	Dipole Antenna	Schwarzbeck	VHA9103	18/10/06	2116
25	Dipole Antenna	Schwarzbeck	VHA9103	18/10/06	2117
26	Dipole Antenna	Schwarzbeck	UHA9105	18/10/06	2261

	Type	Manufacturer	Model	Cal.Due.Date (dd/mm/yy)	S/N
27	Dipole Antenna	Schwarzbeck	UHA9105	18/10/06	2262
28	RFI/FIELD Intensity Meter	Kyorits	KNM-504D	07/07/06	SN-161-4
29	Frequency Converter	Kyorits	KCV-604C	07/07/06	4-230-3
30	TEMP & HUMIDITY Chamber	JISCO	J-RHC2	13/09/07	021031
31	Log Periodic Antenna	Schwarzbeck	UHALP9108A1	29/09/06	1098
32	Biconical Antenna	Schwarzbeck	VHA9103	28/11/06	VHA91031946
33	Digital Multimeter	H.P	34401A	18/04/06	3146A13475
34	Universal Radio Communication Tester	Rohde Schwarz	CMU200	28/04/06	107631
35	High-Pass Filter	ANRITSU	MP526	12/05/06	MP27756
36	Attenuator (3dB)	Agilent	8491B	11/08/06	MY39260699
37	Amplifier (25dB)	Agilent	8447D	18/04/06	2944A10144
38	Position Controller	TOKIN	5901T	N/A	14173
39	Driver	TOKIN	5902T2	N/A	14174
40	Spectrum Analyzer	H.P	8591E	18/04/06	3649A05889
41	RFI/FIELD Intensity Meter	Kyorits	KNW-2402	04/07/06	4N-170-3
42	LISN	Kyorits	KNW-407	11/08/06	8-317-8
43	LISN	Kyorits	KNW-242	11/08/06	8-654-15
44	CVCF	NF Electronic	4400	N/A	344536 4420064
45	Software	ToYo EMI	EP5/RE	N/A	Ver 2.0.800
46	Software	ToYo EMI	EP5/CE	N/A	Ver 2.0.801
47	Software	AUDIX	e3	N/A	Ver 3.0
48	Software	Agilent	Benchlink	N/A	A.01.09 021211