

**MEASUREMENT REPORT**
FCC Part 27 LTE**Applicant Name:**

Samsung Electronics Co., Ltd.
416 Maetan 3-Dong, Yeongtong-gu
Suwon-si, Gyeonggi-do
443-742, Republic of Korea

Date of Testing:

November 1-8, 2012

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1210311556.A3L

FCC ID: A3LEKGC120**APPLICANT:** SAMSUNG ELECTRONICS CO., LTD.**Application Type:**

Certification

FCC Classification:

Licensed Non-Broadcast Station Transmitter (TNB)

FCC Rule Part(s):

§2; §27

EUT Type:

Portable Camera

Model(s):

EK-GC120

Test Device Serial No.:

identical prototype [S/N: 37195]

Mode	Tx Frequency (MHz)	Emission Designator	Modulation	ERP/EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE Band 13	782	8M96G7D	QPSK	0.124	20.940
LTE Band 13	782	8M92W7D	16QAM	0.101	20.040

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.



Randy Ortanez
President

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 1 of 27

T A B L E O F C O N T E N T S

FCC PART 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 EUT CAPABILITIES	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
3.0 DESCRIPTION OF TESTS	6
3.1 EVALUATION PROCEDURE	6
3.2 BLOCK C FREQUENCY RANGE	6
3.3 OCCUPIED BANDWIDTH EMISSION LIMITS	6
3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	6
3.5 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	7
3.6 FREQUENCY STABILITY / TEMPERATURE VARIATION	8
4.0 TEST EQUIPMENT CALIBRATION DATA	9
5.0 SAMPLE CALCULATIONS	10
6.0 TEST RESULTS	11
6.1 SUMMARY	11
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA	12
6.3 LTE RADIATED MEASUREMENTS	13
6.4 LTE RADIATED MEASUREMENTS IN 1559 – 1610MHZ BAND	14
6.5 LTE FREQUENCY STABILITY MEASUREMENTS	15
7.0 PLOT(S) OF EMISSIONS	17
8.0 CONCLUSION	27

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 2 of 27



MEASUREMENT REPORT

FCC Part 27




§2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 416 Maetan 3-Dong, Yeongtong-gu
 Suwon-si, Gyeonggi-do
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): §2; §27
FCC ID: A3LEKGC120
FCC CLASSIFICATION: Licensed Non-Broadcast Station Transmitter (TNB)
MODULATIONS: QPSK, 16-QAM (Uplink)
FREQUENCY TOLERANCE: Emission must remain in band
Test Device Serial No.: 37195 ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: November 1-8, 2012
TEST REPORT S/N: 0Y1210311556.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 3 of 27

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10' 23" N latitude and 76° 49' 50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 4 of 27

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Camera FCC ID: A3LEKGC120**. The test data contained in this report pertains to the emissions from the EUT's LTE operation.

2.2 EUT Capabilities

Band 13 LTE, 802.11a/b/g/n WLAN with 40MHz Bandwidth (DTS/NII), Bluetooth (1x,EDR, LE)

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 5 of 27

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-C-2004) and “Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems” were used in the measurement of the measurement of the **Samsung Portable Camera FCC ID: A3LEKGC120**.

Deviation from Measurement Procedure.....None

3.2 Block C Frequency Range

§27.5(b)(3)

Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

3.3 Occupied Bandwidth Emission Limits

§2.1049, §27.53(l)(6)

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers’ “occupied bandwidth” measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

3.4 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, §27.53(c)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 6 of 27

3.5 Radiated Power and Radiated Spurious Emissions

§2.1053, §27.53(c)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 27.53.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 7 of 27

3.6 Frequency Stability / Temperature Variation

§2.1055, §27.54

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 8 of 27

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/25/2012	Annual	1/25/2013	N/A
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	7/10/2012	Annual	7/10/2013	N/A
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	2/13/2012	Annual	2/13/2013	N/A
Agilent	8447D	Broadband Amplifier	5/8/2012	Annual	5/8/2013	1937A03348
Agilent	E4432B	ESG-D Series Signal Generator	3/15/2012	Annual	3/15/2013	US40053896
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/5/2012	Annual	4/5/2013	MY45470194
Agilent	E8267C	Vector Signal Generator	10/10/2011	Biennial	10/10/2013	US42340152
Agilent	N9030A	PXA Signal Analyzer	2/23/2012	Annual	2/23/2013	MY49432391
Espec	ESX-2CA	Environmental Chamber	4/4/2012	Annual	4/4/2013	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Annual	5/30/2013	135427
Mini-Circuits	VHF-1200+	High Pass Filter	1/15/2012	Annual	1/15/2013	30923
Mini-Circuits	VHF-3100+	High Pass Filter	1/15/2012	Annual	1/15/2013	30841
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	N/A		N/A	102060
Rohde & Schwarz	RS-PR18	1-18 GHz Pre-Amplifier	6/26/2012	Annual	6/26/2013	100071
Rohde & Schwarz	RS-PR26	18-26.5 GHz Pre-Amplifier	5/30/2012	Annual	5/30/2013	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	12/15/2011	Annual	12/15/2012	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/14/2011	Biennial	11/14/2013	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	11/14/2011	Biennial	11/14/2013	9105-2403
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

Note: Equipment with 'N/A' Calibration dates were used for signaling purposes only and not for calibrated measurements. Care was taken to ensure testing was performed while equipment was in calibration.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 9 of 27

5.0 SAMPLE CALCULATIONS

Note: Bandwidth and ERP values listed below in this section are not representative of actual measurements. They are listed as examples only.

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Amplitude/Angle Modulated

16QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Combination (Audio/Data)

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 10 of 27

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LEKGC120
 FCC Classification: Licensed Non-Broadcast Station Transmitter (TNB)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (Tx)					
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 27.53(c)(2), 27.53(c)(4)	Band Edge / Conducted Spurious Emissions (*)	< 43 + 10log ₁₀ (P[Watts]) < 65 + 10log ₁₀ (P[Watts]) in a 6.25kHz bandwidth for emissions in the 763 – 775MHz and 793 – 805MHz bands		PASS	Section 7.0
2.1055, 27.54	Frequency Stability	Fundamental emissions must stay within the allotted band		PASS	Section 6.5
27.50(b)(10)	Effective Radiated Power	< 3 Watts max. ERP	RADIATED	PASS	Section 6.2
2.1053, 27.53(c)(2), 27.53(c)(4)	Undesirable Out-of-Band Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 6.3
2.1053, 27.53(f)	Undesirable Emissions in the 1559 – 1610MHz band	< -40dBm/MHz EIRP (wideband) < -50dBm EIRP (narrowband)		PASS	Section 6.4

Table 6-1. Summary of Test Results

Notes:

- * - For all out of band conducted spurious emissions (including those at the band edges), the emissions of both QPSK and 16-QAM modulations were investigated. QPSK modulation was the worst case emissions for all out of band emissions. This includes harmonic emissions up to the 10th harmonic, band edge emissions, and emissions inside the 763-775 MHz and 793-805 MHz frequencies per Part 27.53 (c)(4). Band Edge emissions plots were also shown for 16QAM because this was the worst case emissions within all 16QAM tests.
- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in Section 7.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera	Page 11 of 27	

6.2 Effective Radiated Power Output Data

§27.50(b)(10)

Frequency [MHz]	Channel Bandwidth [MHz]	Mod.	Battery	RB Size/Offset	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Margin [dB]
782.00	10	QPSK	Standard	1 / 49	17.00	3.94	H	20.94	0.124	-13.83
782.00	10	16QAM	Standard	1 / 49	16.10	3.94	H	20.04	0.101	-14.73

Table 6-2. Effective Radiated Power Output Data

Notes:

1. This device was tested under all modulations, RB sizes, RB offsets, and channel bandwidth configurations and the worst case emissions are reported with QPSK, RB size = 1, and RB offset = 49.
2. This unit was tested with its standard battery. All spurious emissions were investigated and the worst case emissions were found with the EUT powered by this battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 12 of 27

6.3 LTE Radiated Measurements

§2.1053, §27.53(c)(2)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 782.00 MHz
 MEASURED OUTPUT POWER: 20.94 dBm = 0.124 W
 MODULATION SIGNAL: QPSK
 BANDWIDTH: 10 MHz
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.94 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
2346.00	-39.48	3.59	-35.89	H	56.83
3128.00	-80.46	5.20	-75.26	H	96.20
3910.00	-79.99	6.64	-73.35	H	94.29
4692.00	-80.47	7.48	-72.99	H	93.93
5474.00	-79.98	8.42	-71.56	H	92.50

Table 6-3. Radiated Spurious Data (QPSK Modulation)

Notes:

- This device was tested under all modulations, RB sizes, RB offsets, and channel bandwidth configurations and the worst case emissions are reported with QPSK, RB size = 1, and RB offset = 49.
- This unit was tested with its standard battery. All spurious emissions were investigated and the worst case emissions were found with the EUT powered by this battery.
- The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 13 of 27

6.4 LTE Radiated Measurements in 1559 – 1610MHz Band §2.1053, §27.53(f)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 782.00 MHz
 MEASURED OUTPUT POWER: 20.940 dBm = 0.124 W
 MODULATION SIGNAL: QPSK
 DISTANCE: 3 meters
 NARROWBAND EMISSION LIMIT: -50 dBm
 WIDEBAND EMISSION LIMIT: -40 dBm/MHz

FREQUENCY (MHz)	EMISSION TYPE	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	MARGIN (dB)
1572.60	WIDEBAND	-55.08	7.94	-47.13	H	-7.13

Table 6-4. Radiated Spurious Data

Notes:

- This device was tested under all modulations, RB sizes, RB offsets, and channel bandwidth configurations and the worst case emissions are reported with QPSK, RB size = 1, and RB offset = 49.
- This unit was tested with its standard battery. All spurious emissions were investigated and the worst case emissions were found with the EUT powered by this battery.
- The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 14 of 27

6.5 LTE Frequency Stability Measurements

\$2.1055, \$27.54

OPERATING FREQUENCY: 782,000,000 Hz

CHANNEL: 23230

REFERENCE VOLTAGE: 3.7 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	782,000,012	12	0.000002
100 %		- 30	782,000,004	4	0.000000
100 %		- 20	782,000,008	8	0.000001
100 %		- 10	782,000,017	17	0.000002
100 %		0	782,000,012	12	0.000002
100 %		+ 10	782,000,015	15	0.000002
100 %		+ 20	782,000,015	15	0.000002
100 %		+ 30	782,000,006	6	0.000001
100 %		+ 40	782,000,010	10	0.000001
100 %		+ 50	782,000,018	18	0.000002
115 %	4.26	+ 20	782,000,007	7	0.000001
85 %	3.15	+ 20	782,000,008	8	0.000001

Table 6-5. Frequency Stability Data

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 15 of 27

LTE Frequency Stability Measurements (Cont'd)

§2.1055, §27.54






Figure 6-1. Frequency Stability Graph

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 16 of 27




Plot 7-2. Lower Band Edge Plot (16-QAM – RB Size 50)




Plot 7-3. Lower Band Edge Plot (QPSK – RB Size 1, Offset 0)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 18 of 27




Plot 7-4. Lower Band Edge Plot (16-QAM – RB Size 1, Offset 0)




Plot 7-5. Lower Emission Mask (763 – 775MHz) Plot (QPSK – RB Size 50)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 19 of 27




Plot 7-6. Lower Emission Mask (763 - 775MHz) Plot (QPSK - RB Size 1)




Plot 7-7. Occupied Bandwidth Plot (QPSK - RB Size 50)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 20 of 27




Plot 7-8. Occupied Bandwidth Plot (16-QAM – RB Size 50)




Plot 7-9. Conducted Spurious Plot (QPSK – RB Size 1, RB Offset 0)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 21 of 27




Plot 7-10. Conducted Spurious Plot (QPSK – RB Size 1, RB Offset 0)



Plot 7-11. Conducted Spurious Plot (QPSK – RB Size 50)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 22 of 27



Plot 7-12. Conducted Spurious Plot (QPSK – RB Size 50)




Plot 7-13. Upper Band Edge Plot (QPSK – RB Size 50)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 23 of 27




Plot 7-14. Upper Band Edge Plot (16-QAM – RB Size 50)



Plot 7-15. Upper Band Edge Plot (QPSK – RB Size 1, Offset 49)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 24 of 27




Plot 7-16. Upper Band Edge Plot (16-QAM – RB Size 1, Offset 49)



Plot 7-17. Upper Emission Mask (793 – 805MHz) Plot (QPSK – RB Size 50)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 25 of 27



Plot 7-18. Upper Emission Mask (793 – 805MHz) Plot (QPSK – RB Size 1RB, Offset 49)

FCC ID: A3LEKGC120	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 26 of 27

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Camera FCC ID: A3LEKGC120** complies with all the requirements of Parts 2 and 27 of the FCC rules.

FCC ID: A3LEKGC120		FCC Pt. 27 LTE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210311556.A3L	Test Dates: November 1-8, 2012	EUT Type: Portable Camera		Page 27 of 27