




# PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



## MEASUREMENT REPORT FCC Part 15B

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro,  
Yeongtong-gu, Suwon-si  
Gyeonggi-do, 16677, Korea

**Date of Testing:**

1/30-3/3/2017

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

1M1701230040-06.A3L

**FCC ID:** A3LETWV520

**APPLICANT:** Samsung Electronics Co., Ltd.

**Application Type:** Certification

**EUT Type:** Indoor Access Point

**Model:** ET-WV520

**FCC Rule Part(s):** FCC Part 15 Subpart B

**FCC Classification:** Part 15 Class B Computing Device Peripheral (JBP)

**Test Procedure:** ANSI C63.4-2014

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 (See Test Report). The results shown herein are also deemed satisfactory evidence of compliance with Industry Canada Interference-Causing Equipment Standard ICES-003. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*NVLAP accreditation does not constitute any product endorsement by NVLAP or any agency of the United States Government. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.*

  
Randy Ortanez  
President




|                                                |                                                                                     |                                                           |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LETWV520                      |  | <b>FCC Pt. 15B MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1701230040-06.A3L | <b>Test Dates:</b><br>1/30-3/3/2017                                                 | <b>EUT Type:</b><br>Indoor Access Point                   |                                                                                       | Page 1 of 21                           |

# TABLE OF CONTENTS


|                                                             |    |
|-------------------------------------------------------------|----|
| FCC Class B MEASUREMENT REPORT .....                        | 3  |
| 1.0 INTRODUCTION .....                                      | 4  |
| 1.1 Scope .....                                             | 4  |
| 1.2 PCTEST Test Location .....                              | 4  |
| 2.0 PRODUCT INFORMATION.....                                | 5  |
| 2.1 Equipment Description.....                              | 5  |
| 2.2 Device Capabilities .....                               | 5  |
| 2.3 Test Configuration .....                                | 5  |
| 2.4 EMI Suppression Device(s)/Modifications .....           | 5  |
| 3.0 DESCRIPTION OF TESTS .....                              | 6  |
| 3.1 Evaluation Procedure .....                              | 6  |
| 3.2 AC Line Conducted Emissions .....                       | 6  |
| 3.3 Radiated Emissions.....                                 | 7  |
| 3.4 Environmental Conditions.....                           | 7  |
| 4.0 SAMPLE CALCULATIONS .....                               | 8  |
| 4.1 Conducted Emission Measurement Sample Calculation ..... | 8  |
| 4.2 Radiated Emission Measurement Sample Calculation .....  | 8  |
| 5.0 Measurement Uncertainty .....                           | 9  |
| 6.0 TEST EQUIPMENT CALIBRATION DATA .....                   | 10 |
| 7.0 TEST DATA.....                                          | 11 |
| 7.1 Summary .....                                           | 11 |
| 7.2 Test Support Equipment.....                             | 11 |
| 7.3 Radiated Measurement Data.....                          | 12 |
| 7.4 Line Conducted Measurement Data .....                   | 18 |
| 8.0 CONCLUSION.....                                         | 21 |

|                                                |                                                                                     |                                                           |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LETWV520                      |  | <b>FCC Pt. 15B MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1701230040-06.A3L | <b>Test Dates:</b><br>1/30-3/3/2017                                                 | <b>EUT Type:</b><br>Indoor Access Point                   |                                                                                       | Page 2 of 21                           |



## MEASUREMENT REPORT

### FCC Part 15B – Unintentional Radiators



#### § 2.1033 General Information

**APPLICANT:** Samsung Electronics Co., Ltd.

**APPLICANT ADDRESS:** 129, Samsung-ro,  
Yeongtong-gu, Suwon-si

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA

**FCC RULE PART(S):** FCC Part 15 Subpart B

**FCC ID:** A3LETWV520

**Test Device Serial No.:** 20JAN-2 ☐ Production ☒ Pre-Production ☐ Engineering

**FCC CLASSIFICATION:** FCC Class B Digital Device (JBP)

**DATE(S) OF TEST:** 1/30-3/3/2017

#### Test Methodology

Both conducted and radiated measurements were taken using the methods and procedures described in ANSI C63.4-2014. Radiated testing was performed at an antenna-to-EUT distance of 3 meters.

#### Test Facility / NVLAP Accreditation

Conducted and radiated tests were performed at PCTEST Engineering Lab in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.

|                                                |                                                                                     |                                                           |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LETWV520                      |  | <b>FCC Pt. 15B MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1701230040-06.A3L | <b>Test Dates:</b><br>1/30-3/3/2017                                                 | <b>EUT Type:</b><br>Indoor Access Point                   |                                                                                       | Page 3 of 21                           |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                         |                                               |                                                   |                |                                 |
|-----------------------------------------|-----------------------------------------------|---------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                  | EUT Type:<br>Indoor Access Point                  |                | Page 4 of 21                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Indoor Access Point FCC ID: A3LETWV520**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.

### 2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (LE), Zigbee, Zwave

### 2.3 Test Configuration

The EUT was tested with a laptop PC connected via USB interface port. The EUT was exercised during testing by means of software installed on the PC. Since the EUT is a peripheral device, the host PC was populated with another USB device and an additional peripheral device with a non-USB interface, as shown in Table 7-2, thus satisfying the minimum system requirement of two different I/O interfaces. All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

For more information please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 5 of 21                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2014) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.4. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 6 of 21                    |

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 7 of 21                    |

## 4.0 SAMPLE CALCULATIONS

### 4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

**Class B limit** = 60.0 dB $\mu$ V (Quasi-peak limit)  
**Reading** = - 57.8 dBm (calibrated quasi-peak level)  
**Convert to dB $\mu$ V** = - 57.8 + 107 = 49.2 dB $\mu$ V  
  
**Margin** = 49.2 - 60.0 = - 10.8 dB  
= 10.8 dB below limit

### 4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

**Class B limit** = 100  $\mu$ V/m = 40.0 dB $\mu$ V/m  
**Reading** = - 76.0 dBm (calibrated level)  
**Convert to dB $\mu$ V** = - 76.0 + 107 = 31.0 dB $\mu$ V  
**Antenna Factor + Cable Loss** = 5.8 dB/m  
**Total** = 36.8 dB $\mu$ V/m  
  
**Margin** = 36.8 - 40.0 = - 3.2 dB  
= 3.2 dB below limit

#### Note:

Level [dB $\mu$ V] = 20 log<sub>10</sub> (Level [ $\mu$ V/m])  
Level [dB $\mu$ V] = Level [dBm] + 107

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 8 of 21                    |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                 | Expanded Uncertainty ( $\pm$ dB) |
|------------------------------|----------------------------------|
| Conducted Disturbance        | 3.09                             |
| Radiated Disturbance (<1GHz) | 4.98                             |
| Radiated Disturbance (>1GHz) | 5.07                             |

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 9 of 21                    |

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

| Manufacturer      | Model            | Description                            | Cal Date  | Cal Interval | Cal Due   | Serial Number |
|-------------------|------------------|----------------------------------------|-----------|--------------|-----------|---------------|
| -                 | RE1              | Radiated Emissions Cable Set (UHF/EHF) | 7/11/2016 | Annual       | 7/11/2017 | RE1           |
| Agilent           | N9038A           | MXE EMI Receiver                       | 4/21/2016 | Annual       | 4/21/2017 | MY51210133    |
| Com-Power         | AL-130           | 9kHz - 30MHz Loop Antenna              | 7/30/2015 | Biennial     | 7/30/2017 | 121034        |
| Com-Power         | PAM-103          | Pre-Amplifier (1-1000MHz)              | 7/6/2016  | Annual       | 7/6/2017  | 441119        |
| Emco              | 3115             | Horn Antenna (1-18GHz)                 | 3/10/2016 | Biennial     | 3/10/2018 | 9704-5182     |
| Pasternack        | NMLC-1           | Line Conducted Emissions Cable (NM)    | 4/28/2015 | Biennial     | 4/28/2017 | NMLC-1        |
| PCTEST            | -                | EMC Switch System                      | 7/6/2016  | Annual       | 7/6/2017  | NM2           |
| Rohde & Schwarz   | ESU40            | EMI Test Receiver (40GHz)              | 7/15/2016 | Annual       | 7/15/2017 | 100348        |
| Com-Power         | PAM-118A         | PREAMPLIFIER 500MHZ TO 18GHZ           | 7/26/2016 | Annual       | 7/26/2017 | 551079        |
| Solar Electronics | 8012-50-R-24-BNC | Line Impedance Stabilization Network   | 7/30/2015 | Biennial     | 7/30/2017 | 310233        |
| Sunol             | JB5              | Bi-Log Antenna (30M - 5GHz)            | 3/14/2016 | Biennial     | 3/14/2018 | A051107       |

**Table 6-1. Annual Test Equipment Calibration Schedule**

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  | Page 10 of 21                                                                         |                                 |

## 7.0 TEST DATA

### 7.1 Summary

Test Date(s): 1/30-3/3/2017

Test Engineer:



| FCC Part 15 Section | Description         | Result |
|---------------------|---------------------|--------|
| 15.107              | Conducted Emissions | PASS   |
| 15.109              | Radiated Emissions  | PASS   |

Table 7-1. Summary of Test Results

### 7.2 Test Support Equipment

|   |                         |                                |                                   |
|---|-------------------------|--------------------------------|-----------------------------------|
| 1 | Samsung Data Link Cable | Model: N/A                     | S/N: N/A                          |
| 2 | Ethernet Cable          | Model: N/A                     | S/N: N/A                          |
| 3 | Dell Notebook PC #1     | Model: Vostro 3555 (DoC)       | A/N: PCT80759                     |
|   | w/ Dell AC Adapter      | Model: PA-1600-06D2            | S/N: CN-0928G4-71615-1CE-3447-A01 |
|   |                         | 0.85m Unshielded AC power cord |                                   |
|   |                         | 1.80m Unshielded DC power cord |                                   |
|   |                         | with ferrite bead on notebook  |                                   |
| 4 | Dynex USB PC Camera     | Model: DX-WC101 (DoC)          | S/N: 122D05AC                     |
|   |                         | 2.07m Shielded USB Cable       |                                   |

Table 7-2. Test Support Equipment Used

**Note:** See test setup photographs for actual system test setup.

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 11 of 21                   |

## 7.3 Radiated Measurement Data

\$15.109

### Test Procedures Used

ANSI C63.4-2014

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Peak Field Strength Measurements Above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 12 of 21                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Radiated Test Setup**



**Figure 7-2. Radiated Test Setup Above 1 GHz**


|                                         |                                               |                                                   |                |                                 |
|-----------------------------------------|-----------------------------------------------|---------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                  | EUT Type:<br>Indoor Access Point                  |                | Page 13 of 21                   |

# Notes:


1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 30MHz – 30GHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.109(a).
4. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
5.  $AFCL\ (dB/m) = Antenna\ Factor\ (dB/m) + Cable\ Loss\ (dB)$
6.  $Level\ (dB\mu V/m) = Analyzer\ Reading\ (dBm) + AFCL\ (dB/m) + 107$
7.  $Margin\ (dB) = Field\ strength\ (dB\mu V/m) - Limit\ (dB\mu V/m)$
8. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a RMS detector using a resolution bandwidth of 1MHz and a video bandwidth of 3MHz.
9. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
10. Calibrated low-loss microwaves cables and broadband amplifiers are used.
11. No significant emissions were found above 18GHz.

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 14 of 21                   |

## Radiated Spurious Emission Measurements (Below 1GHz)




**Plot 7-3. Radiated Pre-Scan Plot at 3-meters below 1 GHz ( Ant. Pol. H)**



**Plot 7-4. Radiated Pre-Scan Plot at 3-meters below 1 GHz ( Ant. Pol. V)**


|                                                |                                               |                                                           |                |                                        |
|------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------|----------------|----------------------------------------|
| <b>FCC ID:</b> A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>FCC Pt. 15B MEASUREMENT REPORT<br/>(CERTIFICATION)</b> | <b>SAMSUNG</b> | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1701230040-06.A3L | <b>Test Dates:</b><br>1/30-3/3/2017           | <b>EUT Type:</b><br>Indoor Access Point                   |                | Page 15 of 21                          |

## Radiated Spurious Emission Measurements (Above 1GHz)



Date: 3.MAR.2017 09:02:20

**Plot 7-5. Radiated Pre-Scan Plot at 3-meters above 1 GHz (Ant. Pol. H)**



Date: 3.MAR.2017 09:03:05

**Plot 7-6. Radiated Pre-Scan Plot at 3-meters above 1 GHz (Ant. Pol. V)**

|                                         |                                               |                                                   |                |                                 |
|-----------------------------------------|-----------------------------------------------|---------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                  | EUT Type:<br>Indoor Access Point                  |                | Page 16 of 21                   |

## Radiated Spurious Emission Measurements

| Frequency [MHz] | Detector   | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 47.83           | Quasi-Peak | V               | 100                 | 170                        | -52.38               | -20.22      | 34.40                   | 40.00          | -5.60       |
| 63.20           | Quasi-Peak | V               | 100                 | 251                        | -49.80               | -21.53      | 35.67                   | 40.00          | -4.33       |
| 84.00           | Quasi-Peak | V               | 100                 | 300                        | -51.50               | -20.91      | 34.59                   | 40.00          | -5.41       |
| 129.49          | Quasi-Peak | H               | 170                 | 210                        | -58.44               | -15.28      | 33.28                   | 43.52          | -10.25      |
| 499.46          | Quasi-Peak | H               | 358                 | 334                        | -56.39               | -9.50       | 41.11                   | 46.02          | -4.91       |
| 552.31          | Quasi-Peak | H               | 100                 | 312                        | -58.25               | -8.95       | 39.80                   | 46.02          | -6.22       |

Table 7-7. Radiated Measurements at 3-meters

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 17 of 21                   |

## 7.4 Line Conducted Measurement Data

### §15.107

#### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

***All conducted emissions must not exceed the limits shown in the table below, per Section 15.107.***

| Frequency of emission (MHz) | Conducted Limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15 – 0.5                  | 66 to 56*              | 56 to 46* |
| 0.5 – 5                     | 56                     | 46        |
| 5 – 30                      | 60                     | 50        |

**Table 7-8. Conducted Limits**

\*Decreases with the logarithm of the frequency.

#### Test Procedures Used

ANSI C63.4-2014, Section 7

#### Test Settings

##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


##### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  | Page 18 of 21                                                                         |                                 |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-3. Test Instrument & Measurement Setup**


## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.107.
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.


|                                         |                                               |                                                   |                |                                 |
|-----------------------------------------|-----------------------------------------------|---------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                  | EUT Type:<br>Indoor Access Point                  |                | Page 19 of 21                   |

# Line Conducted Measurement Data

\$15.107



Plot 7-1. Line Conducted Plot (L1)



Plot 7-2. Line Conducted Plot (N)

|                                         |                                               |                                                   |                |                                 |
|-----------------------------------------|-----------------------------------------------|---------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LETWV520                      | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                  | EUT Type:<br>Indoor Access Point                  |                | Page 20 of 21                   |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Indoor Access Point FCC ID: A3LETWV520** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC Rules and Industry Canada Standard ICES-003.

|                                         |                                                                                     |                                                   |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LETWV520                      |  | FCC Pt. 15B MEASUREMENT REPORT<br>(CERTIFICATION) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1701230040-06.A3L | Test Dates:<br>1/30-3/3/2017                                                        | EUT Type:<br>Indoor Access Point                  |                                                                                       | Page 21 of 21                   |