




PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



RF EXPOSURE EVALUATION Maximum Permissible Exposure (MPE)

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

11/23/2016-02/17/2017

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1611161807.A3L

FCC ID: A3LETWV530

APPLICANT: Samsung Electronics Co., Ltd.

Application Type: Certification

Model: ET-WV530

EUT Type: Indoor Access Point

FCC Rule Part(s): FCC Part 1 (§1.1310) and Part 2 (§2.1091)

Test Procedure: KDB 447498 D01 v06

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC KDB 447498 D01 v06. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 1 of 10

© 2017 PCTEST Engineering Laboratory, Inc.

REV 3.2MPE
7/27/2012

© 2017 PCTEST Engineering Laboratory, Inc. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTESTLAB.COM.

TABLE OF CONTENTS

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	Introduction	3
1.2	EUT Description.....	3
1.3	MPE Requirements Overview.....	4
1.4	Procedure	5
1.5	Summary of Results	9
2.0	CONCLUSION.....	10

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 2 of 10

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared on behalf of Samsung Electronics Co., Ltd. to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 EUT Description

The Samsung Model: ET-WV530 is an Indoor Access Point containing four 2.4GHz transmit output ports and four separate 5GHz transmit output ports capable for transmitting 802.11a/b/g/n/ac modes. The device also contains Zigbee, Z-Wave, and Bluetooth transmitters.

EUT:

Model: ET-WV530
Grantee: Samsung Electronics Co., Ltd.
FCC ID: A3LETWV530
Antenna(s): Please see technical description for list of available antenna options

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point	Page 3 of 10	

1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC KDB 447498 D01 v06. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The Samsung Indoor Access Point FCC ID: A3LETWV530 is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 4 of 10

1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements. The conducted powers from each antenna output is measured by a power meter and the powers are recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used for each transmit output, the power density level is calculated at a distance of 20cm

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

π = 3.1416

P_{out} = output power to antenna (mW)

r = distance between observation point and center of the radiator (cm)

G = gain of antenna in linear scale

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

Frequency	2437 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.67 dBm	116.68 mW	
TX Ant Gain (dBi), G =	3.4 dBi		
Power Density (S) =	0.051 mW/cm ²	(at 20cm)	
Minimum Distance =	4.5 cm		

Table 1-2. Calculated MPE Data for WLAN 2.4GHz Band (Antenna 1)

Frequency:	2437 MHz		
Limit:	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	21.07 dBm	127.94 mW	
TX Ant Gain (dBi), G =	2.1 dBi		
Power Density (S) =	0.0413 mW/cm ²	(at 20cm)	
Minimum Distance =	4.1 cm		

Table 1-3. Calculated MPE Data for WLAN 2.4GHz Band (Antenna 2)

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 5 of 10

Frequency:	2437 MHz		
Limit:	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.75 dBm	118.85 mW	
TX Ant Gain (dBi), G =	0.9 dBi		
Power Density (S) =	0.0291 mW/cm ²	(at 20cm)	
Minimum Distance =	3.4 cm		

Table 1-4. Calculated MPE Data for WLAN 2.4GHz Band (Antenna 3)

Frequency:	2437 MHz		
Limit:	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	21.02 dBm	126.47 mW	
TX Ant Gain (dBi), G =	-0.6 dBi		
Power Density (S) =	0.0219 mW/cm ²	(at 20cm)	
Minimum Distance =	3.0 cm		

Table 1-5. Calculated MPE Data for WLAN 2.4GHz Band (Antenna 4)

Frequency	5745 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.94 dBm	124.17 mW	
TX Ant Gain (dB), G =	5 dBi		
Power Density (S) =	0.078 mW/cm ²	(at 20cm)	
Minimum Distance =	5.6 cm		

Table 1-6. Calculated MPE Data for UNII 5GHz Band (Antenna 1)

Frequency	5825 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.86 dBm	121.90 mW	
TX Ant Gain (dB), G =	4.8 dBi		
Power Density (S) =	0.073 mW/cm ²	(at 20cm)	
Minimum Distance =	5.4 cm		

Table 1-7. Calculated MPE Data for UNII 5GHz Band (Antenna 2)

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 6 of 10

Frequency	5825 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.84 dBm	121.34 mW	
TX Ant Gain (dB), G =	3.5 dBi		
Power Density (S) =	0.054 mW/cm ²	(at 20cm)	
Minimum Distance =	4.6 cm		

Table 1-8. Calculated MPE Data for UNII 5GHz Band (Antenna 3)

Frequency	5220 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	20.89 dBm	122.74 mW	
TX Ant Gain (dB), G =	3.6 dBi		
Power Density (S) =	0.056 mW/cm ²	(at 20cm)	
Minimum Distance =	4.7 cm		

Table 1-9. Calculated MPE Data for UNII 5GHz Band (Antenna 4)

Frequency	2440 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	-0.89 dBm	0.81 mW	
TX Ant Gain (dB), G =	3.5 dBi		
Power Density (S) =	0.000 mW/cm ²	(at 20cm)	
Minimum Distance =	0.4 cm		

Table 1-10. Calculated MPE Data for Bluetooth LE

Frequency	2440 MHz		
Limit	1.000 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	17.34 dBm	54.20 mW	
TX Ant Gain (dB), G =	0.0 dBi		
Power Density (S) =	0.011 mW/cm ²	(at 20cm)	
Minimum Distance =	2.1 cm		

Table 1-11. Calculated MPE Data for Zigbee

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 7 of 10

Frequency	908.4 MHz		
Limit	0.606 mW/cm ²		
Distance (cm), R =	20 cm		
Power (dBm), P =	3.44 dBm	2.21 mW	
TX Ant Gain (dB), G =	2.1 dBi		
Power Density (S) =	0.001 mW/cm ²	(at 20cm)	
Minimum Distance =	0.7 cm		

Table 1-12. Calculated MPE Data for Z-Wave

	Power Density (mW/cm ²)	Limit (mW/cm ²)	Percent MPE Used (%)
Transmitter #1	0.051	1.00	5.08
Transmitter #2	0.041	1.00	4.13
Transmitter #3	0.029	1.00	2.91
Transmitter #4	0.022	1.00	2.19
Transmitter #1 (5GHz)	0.078	1.00	7.81
Transmitter #2 (5GHz)	0.073	1.00	7.32
Transmitter #3 (5GHz)	0.054	1.00	5.40
Transmitter #4 (5GHz)	0.056	1.00	5.59
Bluetooth LE	0.000	1.00	0.04
Zigbee	0.011	1.00	1.08
Z-Wave	0.001	0.606	0.17
Total			41.72

Table 1-13. Cumulative Results for Multiple Transmitters

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 8 of 10

1.5 Summary of Results

Transmit Mode	Frequency Band [MHz]	Maximum Antenna Gain [dBi]	MPE @ 20cm (mW/cm ²)	Test Result
2.4GHz 802.11b/g/n	2412 - 2462	3.4	0.051	PASS
2.4GHz 802.11b/g/n	2412 – 2462	2.1	0.0413	PASS
2.4GHz 802.11b/g/n	2412 – 2462	0.9	0.0291	PASS
2.4GHz 802.11b/g/n	2412 – 2462	-0.6	0.219	PASS
5GHz 802.11a/n/ac	5180 – 5240, 5745 - 5825	5.0	0.078	PASS
5GHz 802.11a/n/ac	5180 – 5240, 5745 – 5825	4.8	0.073	PASS
5GHz 802.11a/n/ac	5180 – 5240, 5745 – 5825	3.5	0.054	PASS
5GHz 802.11a/n/ac	5180 – 5240, 5745 - 5825	3.6	0.056	PASS
Bluetooth LE	2402 – 2480	3.5	0.000	PASS
Zigbee	2405 – 2480	0.0	0.011	PASS
Z-Wave	908.4 – 916.4	2.1	0.001	PASS

Table 1-14. Maximum Permissible Exposure Summary Table

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point	Page 9 of 10	

2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: A3LETWV530		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Approved by: Quality Manager
Test Report S/N: 0Y1611161807.A3L	Test Dates: 11/23/2016-02/17/2017	EUT Type: Indoor Access Point		Page 10 of 10