


# FCC SAR Test Report

APPLICANT : Samsung Electronics Co., Ltd.  
EQUIPMENT : MOBILE PHONE  
BRAND NAME : SAMSUNG  
MODEL NAME : GT-C3520I  
FCC ID : A3LGTC3520I  
STANDARD : FCC 47 CFR Part 2 (2.1093)  
ANSI/IEEE C95.1-1992  
IEEE 1528-2003

The product was testing completed on Jan. 24, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C.

## Table of Contents

|                                                          |           |
|----------------------------------------------------------|-----------|
| <b>1. Statement of Compliance .....</b>                  | <b>4</b>  |
| <b>2. Administration Data .....</b>                      | <b>5</b>  |
| 2.1 Testing Laboratory.....                              | 5         |
| 2.2 Applicant .....                                      | 5         |
| 2.3 Manufacturer .....                                   | 5         |
| 2.4 Application Details.....                             | 5         |
| <b>3. General Information .....</b>                      | <b>6</b>  |
| 3.1 Description of Equipment Under Test (EUT) .....      | 6         |
| 3.2 Maximum RF output power among production units ..... | 7         |
| 3.3 Applied Standard.....                                | 8         |
| 3.4 Device Category and SAR Limits .....                 | 8         |
| 3.5 Test Conditions.....                                 | 8         |
| <b>4. Specific Absorption Rate (SAR).....</b>            | <b>9</b>  |
| 4.1 Introduction .....                                   | 9         |
| 4.2 SAR Definition.....                                  | 9         |
| <b>5. SAR Measurement System.....</b>                    | <b>10</b> |
| 5.1 E-Field Probe .....                                  | 11        |
| 5.2 Data Acquisition Electronics (DAE) .....             | 11        |
| 5.3 Robot .....                                          | 12        |
| 5.4 Measurement Server.....                              | 12        |
| 5.5 Phantom.....                                         | 13        |
| 5.6 Device Holder .....                                  | 13        |
| 5.7 Data Storage and Evaluation .....                    | 14        |
| 5.8 Test Equipment List.....                             | 16        |
| <b>6. Tissue Simulating Liquids.....</b>                 | <b>17</b> |
| <b>7. System Verification Procedures .....</b>           | <b>18</b> |
| 7.1 Purpose of System Performance check .....            | 18        |
| 7.2 System Setup.....                                    | 18        |
| 7.3 SAR System Verification Results .....                | 19        |
| <b>8. EUT Testing Position .....</b>                     | <b>20</b> |
| 8.1 Define two imaginary lines on the handset.....       | 20        |
| 8.2 Cheek Position .....                                 | 21        |
| 8.3 Tilted Position.....                                 | 21        |
| 8.4 Body Worn Position.....                              | 22        |
| <b>9. Measurement Procedures .....</b>                   | <b>23</b> |
| 9.1 Spatial Peak SAR Evaluation.....                     | 23        |
| 9.2 Power Reference Measurement.....                     | 24        |
| 9.3 Area & Zoom Scan Procedures.....                     | 24        |
| 9.4 Volume Scan Procedures.....                          | 25        |
| 9.5 SAR Averaged Methods.....                            | 25        |
| 9.6 Power Drift Monitoring.....                          | 25        |
| <b>10. Conducted RF Output Power (Unit: dBm).....</b>    | <b>26</b> |
| <b>11. Antenna Location .....</b>                        | <b>28</b> |
| <b>12. SAR Test Results .....</b>                        | <b>30</b> |
| 12.1 Head SAR .....                                      | 30        |
| 12.2 Body Worn SAR .....                                 | 31        |
| 12.3 Highest SAR Plot .....                              | 32        |
| <b>13. Simultaneous Transmission Analysis.....</b>       | <b>34</b> |
| 13.1 Head Exposure Conditions .....                      | 35        |
| 13.2 Body-Worn Exposure Conditions .....                 | 35        |
| <b>14. Uncertainty Assessment .....</b>                  | <b>36</b> |
| <b>15. References.....</b>                               | <b>38</b> |
| <b>Appendix A. Plots of System Performance Check</b>     |           |
| <b>Appendix B. Plots of SAR Measurement</b>              |           |
| <b>Appendix C. DASY Calibration Certificate</b>          |           |
| <b>Appendix D. SAR System Validation</b>                 |           |
| <b>Appendix E. Test Setup Photos</b>                     |           |



## Revision History

| REPORT NO. | VERSION | DESCRIPTION                                                                                                           | ISSUED DATE   |
|------------|---------|-----------------------------------------------------------------------------------------------------------------------|---------------|
| FA410401   | Rev. 01 | Initial issue of report                                                                                               | Jan. 16, 2014 |
| FA410401   | Rev. 02 | 1. Added a note that indicated measurements of SAR in Mouth area on page 30.<br>2. Retested the mouth area for GSM850 | Jan. 24, 2014 |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |
|            |         |                                                                                                                       |               |

## **1. Statement of Compliance**

The maximum results of Specific Absorption Rate (SAR) found during testing for **Samsung Electronics Co., Ltd. GT-C3520I** are as follows.

### **<Highest SAR Summary>**

| Exposure Position               | Frequency Band | Reported 1g-SAR (W/kg) | Equipment Class | Highest Reported 1g-SAR (W/kg) |
|---------------------------------|----------------|------------------------|-----------------|--------------------------------|
| Head                            | GSM850         | 0.88                   | PCE             | 0.88                           |
|                                 | GSM1900        | 0.13                   |                 |                                |
| Body-worn<br>(Separation 1.5cm) | GSM850         | 0.77                   | PCE             | 0.77                           |
|                                 | GSM1900        | 0.10                   |                 |                                |

### **<Highest Simultaneous transmission SAR>**

| Exposure Position               | Frequency Band | Equipment Class | Highest Reported Simultaneous Transmission 1g-SAR (W/kg) |
|---------------------------------|----------------|-----------------|----------------------------------------------------------|
| Body-worn<br>(Separation 1.5cm) | GSM850         | PCE             | 1.21                                                     |
|                                 | Bluetooth      | DSS             |                                                          |

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

## **2. Administration Data**

### **2.1 Testing Laboratory**

|                           |                                                                                                                                                                |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL (SHENZHEN) INC.                                                                                                                          |
| <b>Test Site Location</b> | No. 101, Complex Building C, Guanlong Village, Xili Town,<br>Nanshan District, Shenzhen, Guangdong, P.R.C.<br>TEL: +86-755-8637-9589<br>FAX: +86-755-8637-9595 |

### **2.2 Applicant**

|                     |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| <b>Company Name</b> | Samsung Electronics Co., Ltd.                                                                      |
| <b>Address</b>      | No.9, WeiWu Rd, Micro-electronics Industrial Park Jingang Highway, Xiqing District, Tianjin, China |

### **2.3 Manufacturer**

|                     |                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------|
| <b>Company Name</b> | Samsung Electronics Co., Ltd.                                                                      |
| <b>Address</b>      | No.9, WeiWu Rd, Micro-electronics Industrial Park Jingang Highway, Xiqing District, Tianjin, China |

### **2.4 Application Details**

|                                      |               |
|--------------------------------------|---------------|
| <b>Date of Start during the Test</b> | Jan. 07, 2014 |
| <b>Date of End during the Test</b>   | Jan. 24, 2014 |

### **3. General Information**

#### **3.1 Description of Equipment Under Test (EUT)**

| Product Feature & Specification                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT</b>                                                                                                                                                                                                                                                                                                                                                                                     | MOBILE PHONE                                                                                                                                                       |
| <b>Brand Name</b>                                                                                                                                                                                                                                                                                                                                                                              | SAMSUNG                                                                                                                                                            |
| <b>Model Name</b>                                                                                                                                                                                                                                                                                                                                                                              | GT-C3520I                                                                                                                                                          |
| <b>FCC ID</b>                                                                                                                                                                                                                                                                                                                                                                                  | A3LGTC3520I                                                                                                                                                        |
| <b>IMEI Code</b>                                                                                                                                                                                                                                                                                                                                                                               | 351891060073886                                                                                                                                                    |
| <b>Wireless Technology and Frequency Range</b>                                                                                                                                                                                                                                                                                                                                                 | GSM850: 824.2 MHz ~ 848.8 MHz<br>GSM1900: 1850.2 MHz ~ 1909.8 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz                                                                |
| <b>Mode</b>                                                                                                                                                                                                                                                                                                                                                                                    | <ul style="list-style-type: none"> <li>• GSM/GPRS</li> <li>• EGPRS (Downlink Only)</li> <li>• Bluetooth v3.0 + EDR</li> </ul>                                      |
| <b>Antenna Type</b>                                                                                                                                                                                                                                                                                                                                                                            | WWAN: Internal Antenna<br>Bluetooth: Ground Antenna                                                                                                                |
| <b>HW Version</b>                                                                                                                                                                                                                                                                                                                                                                              | REV0.1                                                                                                                                                             |
| <b>SW Version</b>                                                                                                                                                                                                                                                                                                                                                                              | C3520I.001                                                                                                                                                         |
| <b>Transfer Mode Category</b>                                                                                                                                                                                                                                                                                                                                                                  | Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network. |
| <b>EUT Stage</b>                                                                                                                                                                                                                                                                                                                                                                               | Identical Prototype                                                                                                                                                |
| <b>Remark:</b> <ol style="list-style-type: none"> <li>1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.</li> <li>2. This device supports GPRS/EGPRS, GPRS operation up to class 12 and EGPRS supports downlink only.</li> <li>3. This device does not support DTM and VoIP operation.</li> </ol> |                                                                                                                                                                    |

**3.2 Maximum RF output power among production units**

| Burst Average Power (dBm) |        |         |
|---------------------------|--------|---------|
| Mode / Band               | GSM850 | GSM1900 |
| Voice (GMSK, 1 Tx slot)   | 33.0   | 30.0    |
| (GMSK, 1 Tx slot)         | 33.0   | 30.0    |
| (GMSK, 2 Tx slots)        | 31.0   | 28.0    |
| (GMSK, 3 Tx slots)        | 30.0   | 27.0    |
| (GMSK, 4 Tx slots)        | 28.0   | 24.5    |

| Bluetooth Average Power (dBm) |     |
|-------------------------------|-----|
| v3.0 + EDR                    | 9.0 |

### **3.3 Applied Standard**

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v05r01
- FCC KDB 648474 D04 Handset SAR v01r02
- FCC KDB 941225 D03 SAR Test Reduction GSM GPRS EDGE v01

### **3.4 Device Category and SAR Limits**

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

### **3.5 Test Conditions**

#### **3.5.1 Ambient Condition**

|                     |             |
|---------------------|-------------|
| Ambient Temperature | 20 to 24 °C |
| Humidity            | < 60 %      |

#### **3.5.2 Test Configuration**

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT.

## **4. Specific Absorption Rate (SAR)**

### **4.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **4.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left( \frac{\delta T}{\delta t} \right)$$


Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

## 5. SAR Measurement System



**Fig 5.1 SPEAG DASY System Configurations**

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Component details are described in in the following sub-sections.

## 5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

### 5.1.1 E-Field Probe Specification

#### <EX3DV4 Probe>

|                      |                                                                                                                                                             |                                                                                     |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Construction</b>  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |  |
| <b>Frequency</b>     | 10 MHz to 6 GHz; Linearity: $\pm 0.2$ dB                                                                                                                    |                                                                                     |
| <b>Directivity</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)                                         |                                                                                     |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to 100 mW/g; Linearity: $\pm 0.2$ dB<br>(noise: typically $< 1$ $\mu$ W/g)                                                                     |                                                                                     |
| <b>Dimensions</b>    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                        |                                                                                     |

**Fig 5.2 Photo of EX3DV4**

### 5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy shall be evaluated and within  $\pm 0.25$ dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

## 5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Fig 5.3 Photo of DAE**

### **5.3 Robot**

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



**Fig 5.4 Photo of DASY5**

### **5.4 Measurement Server**

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



**Fig 5.5 Photo of Server for DASY5**

## 5.5 Phantom

### <SAM Twin Phantom>

|                          |                                                            |                                                                                                                            |
|--------------------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Shell Thickness</b>   | 2 ± 0.2 mm;<br>Center ear point: 6 ± 0.2 mm                | <br><b>Fig 5.6 Photo of SAM Phantom</b> |
| <b>Filling Volume</b>    | Approx. 25 liters                                          |                                                                                                                            |
| <b>Dimensions</b>        | Length: 1000 mm; Width: 500 mm;<br>Height: adjustable feet |                                                                                                                            |
| <b>Measurement Areas</b> | Left Hand, Right Hand, Flat Phantom                        |                                                                                                                            |

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

## 5.6 Device Holder

### <Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



**Fig 5.7 Device Holder**

## 5.7 Data Storage and Evaluation

### 5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### 5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

|                            |                           |                                                                         |
|----------------------------|---------------------------|-------------------------------------------------------------------------|
| <b>Probe parameters :</b>  | - Sensitivity             | Norm <sub>i</sub> , a <sub>i0</sub> , a <sub>i1</sub> , a <sub>i2</sub> |
|                            | - Conversion factor       | ConvF <sub>i</sub>                                                      |
|                            | - Diode compression point | dcp <sub>i</sub>                                                        |
| <b>Device parameters :</b> | - Frequency               | f                                                                       |
|                            | - Crest factor            | cf                                                                      |
| <b>Media parameters :</b>  | - Conductivity            | $\sigma$                                                                |
|                            | - Density                 | $\rho$                                                                  |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)  
 $U_i$  = input signal of channel i, (i = x, y, z)  
 $cf$  = crest factor of exciting field (DASY parameter)  
 $dcp_i$  = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

$$\text{E-field Probes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with  $V_i$  = compensated signal of channel i, (i = x, y, z)  
 $\text{Norm}_i$  = sensor sensitivity of channel i, (i = x, y, z),  $\mu\text{V}/(\text{V/m})^2$  for E-field Probes  
 $\text{ConvF}$  = sensitivity enhancement in solution  
 $a_{ij}$  = sensor sensitivity factors for H-field probes  
 $f$  = carrier frequency [GHz]  
 $E_i$  = electric field strength of channel i in V/m  
 $H_i$  = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g  
 $E_{\text{tot}}$  = total field strength in V/m  
 $\sigma$  = conductivity in [mho/m] or [Siemens/m]  
 $\rho$  = equivalent tissue density in  $\text{g/cm}^3$

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

### 5.8 Test Equipment List

| Manufacturer | Name of Equipment               | Type/Model    | Serial Number | Calibration   |               |
|--------------|---------------------------------|---------------|---------------|---------------|---------------|
|              |                                 |               |               | Last Cal.     | Due Date      |
| SPEAG        | 835MHz System Validation Kit    | D835V2        | 4d091         | Nov. 18, 2011 | Nov. 17, 2014 |
| SPEAG        | 1900MHz System Validation Kit   | D1900V2       | 5d118         | Nov. 21, 2011 | Nov. 20, 2014 |
| SPEAG        | Data Acquisition Electronics    | DAE4          | 1303          | Nov. 22, 2013 | Nov. 21, 2014 |
| SPEAG        | Dosimetric E-Field Probe        | EX3DV4        | 3819          | Nov. 27, 2013 | Nov. 26, 2014 |
| SPEAG        | SAM Twin Phantom                | QD 000 P40 CD | TP-1670       | NCR           | NCR           |
| SPEAG        | SAM Twin Phantom                | QD 000 P40 CD | TP-1671       | NCR           | NCR           |
| SPEAG        | Dielectric Assessment Kit       | DAK-3.5       | 1032          | NCR           | NCR           |
| SPEAG        | Phone Positioner                | N/A           | N/A           | NCR           | NCR           |
| Agilent      | Wireless Communication Test Set | E5515C        | MY50267224    | Oct. 10, 2013 | Oct. 09, 2014 |
| R&S          | Network Analyzer                | ZVB8          | 100106        | Nov. 07, 2013 | Nov. 06, 2014 |
| Anritsu      | Power Meter                     | ML2495A       | 1218010       | Mar. 28, 2013 | Mar. 27, 2014 |
| Anritsu      | Power Sensor                    | MA2411B       | 1207253       | Mar. 28, 2013 | Mar. 27, 2014 |
| ARRA         | Power Divider                   | A3200-2       | N/A           | NA            | NA            |
| Agilent      | Dual Directional Coupler        | 778D          | 50422         | Note 4        |               |
| Woken        | Attenuator 1                    | WK0602-XX     | N/A           | Note 4        |               |
| PE           | Attenuator 2                    | PE7005-10     | N/A           | Note 4        |               |
| PE           | Attenuator 3                    | PE7005- 3     | N/A           | Note 4        |               |
| AR           | Power Amplifier                 | 5S1G4M2       | 328767        | Note 5        |               |
| R&S          | Spectrum Analyzer               | FSP7          | 101045        | Jul. 02, 2013 | Jul. 01, 2014 |

**Table 5.1 Test Equipment List**

**Note:**

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. Referring to KDB 865664 D01v01r02, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole D835V2, SN: 4d091 and D1900V2, SN: 5d118 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.
4. The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
5. In system check we need to monitor the level on the power meter, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1W input power according to the ratio of 1W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the power meter is critical and we do have calibration for it
6. Attenuator 1 insertion loss is calibrated by the network Analyzer, which the calibration is valid, before system check.

## 6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.



**Fig 6.1 Photo of Liquid Height for Head SAR**



**Fig 6.2 Photo of Liquid Height for Body SAR**

The following table gives the recipes for tissue simulating liquid.

| Frequency (MHz)  | Water (%) | Sugar (%) | Cellulose (%) | Salt (%) | Preventol (%) | DGBE (%) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) |
|------------------|-----------|-----------|---------------|----------|---------------|----------|---------------------------|-------------------------------|
| <b>For Head</b>  |           |           |               |          |               |          |                           |                               |
| 835              | 40.3      | 57.9      | 0.2           | 1.4      | 0.2           | 0        | 0.90                      | 41.5                          |
| 1800, 1900, 2000 | 55.2      | 0         | 0             | 0.3      | 0             | 44.5     | 1.40                      | 40.0                          |
| <b>For Body</b>  |           |           |               |          |               |          |                           |                               |
| 835              | 50.8      | 48.2      | 0             | 0.9      | 0.1           | 0        | 0.97                      | 55.2                          |
| 1800, 1900, 2000 | 70.2      | 0         | 0             | 0.4      | 0             | 29.4     | 1.52                      | 53.3                          |

**Table 6.1 Recipes of Tissue Simulating Liquid**

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a SPEAG DAK-3.5 Dielectric Probe Kit and a R&S ZVB8 Network Analyzer.

The following table shows the measuring results for simulating liquid.

| Frequency (MHz) | Tissue Type | Liquid Temp. (°C) | Conductivity ( $\sigma$ ) | Permittivity ( $\epsilon_r$ ) | Conductivity Target ( $\sigma$ ) | Permittivity Target ( $\epsilon_r$ ) | Delta ( $\sigma$ ) (%) | Delta ( $\epsilon_r$ ) (%) | Limit (%) | Date          |
|-----------------|-------------|-------------------|---------------------------|-------------------------------|----------------------------------|--------------------------------------|------------------------|----------------------------|-----------|---------------|
| 835             | Head        | 22.7              | 0.910                     | 42.910                        | 0.90                             | 41.50                                | 1.11                   | 3.40                       | ±5        | Jan. 08, 2014 |
| 835             | Head        | 22.8              | 0.906                     | 42.89                         | 0.90                             | 41.50                                | 0.67                   | 3.35                       | ±5        | Jan. 24, 2014 |
| 1900            | Head        | 22.7              | 1.417                     | 40.994                        | 1.40                             | 40.00                                | 1.21                   | 2.49                       | ±5        | Jan. 07, 2014 |
| 835             | Body        | 22.6              | 1.011                     | 56.243                        | 0.97                             | 55.20                                | 4.23                   | 1.89                       | ±5        | Jan. 08, 2014 |
| 1900            | Body        | 22.6              | 1.533                     | 54.611                        | 1.52                             | 53.30                                | 0.86                   | 2.46                       | ±5        | Jan. 07, 2014 |

**Table 6.2 Measuring Results for Simulating Liquid**

## 7. System Verification Procedures

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

### 7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 7.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole



**Fig 7.2 Photo of Dipole Setup**

### **7.3 SAR System Verification Results**

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.


| Date          | Frequency (MHz) | Tissue Type | Input Power (mW) | Dipole S/N | Probe S/N | DAE S/N | Measured 1g SAR (W/kg) | Target 1g SAR (W/kg) | Normalized 1g SAR (W/kg) | Deviation (%) |
|---------------|-----------------|-------------|------------------|------------|-----------|---------|------------------------|----------------------|--------------------------|---------------|
| Jan. 08, 2014 | 835             | Head        | 250              | 4d091      | 3819      | 1303    | 2.47                   | 9.40                 | 9.88                     | 5.11          |
| Jan. 24, 2014 | 835             | Head        | 250              | 4d091      | 3819      | 1303    | 2.42                   | 9.40                 | 9.68                     | 2.98          |
| Jan. 07, 2014 | 1900            | Head        | 250              | 5d118      | 3819      | 1303    | 9.45                   | 40.30                | 37.8                     | -6.20         |
| Jan. 08, 2014 | 835             | Body        | 250              | 4d091      | 3819      | 1303    | 2.42                   | 9.42                 | 9.68                     | 2.76          |
| Jan. 07, 2014 | 1900            | Body        | 250              | 5d118      | 3819      | 1303    | 10.60                  | 41.80                | 42.4                     | 1.44          |

**Table 7.1 Target and Measurement SAR after Normalized**

## 8. EUT Testing Position

### 8.1 Define two imaginary lines on the handset


- The vertical centerline passes through two points on the front side of the handset - the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



**Fig 8.1 Illustration for Handset Vertical and Horizontal Reference Lines**

## 8.2 Cheek Position


- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 8.2).



**Fig 8.2 Illustration for Cheek Position**

## 8.3 Tilted Position


- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (sees Fig. 8.3).



**Fig 8.3 Illustration for Tilted Position**

#### 8.4 Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm.



**Fig 8.4 Illustration for Body Worn Position**

#### <EUT Setup Photos>

Please refer to Appendix E for the test setup photos.

## 9. Measurement Procedures

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For BT power measurement, use engineering software to configure EUT BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

## 9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

## 9.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r02 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

|                                                                                                                                                                                                                                                                                                      |                                           |                                                                                             | $\leq 3$ GHz                                                                                                                                                                                                                                                           | $> 3$ GHz                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface                                                                                                                                                                                               |                                           |                                                                                             | $5 \pm 1$ mm                                                                                                                                                                                                                                                           | $\frac{1}{2} \delta \ln(2) \pm 0.5$ mm                                        |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location                                                                                                                                                                                                            |                                           |                                                                                             | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                                        |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$                                                                                                                                                                                                               |                                           |                                                                                             | $\leq 2$ GHz: $\leq 15$ mm<br>2 – 3 GHz: $\leq 12$ mm                                                                                                                                                                                                                  | 3 – 4 GHz: $\leq 12$ mm<br>4 – 6 GHz: $\leq 10$ mm                            |
|                                                                                                                                                                                                                                                                                                      |                                           |                                                                                             | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                               |
| Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$                                                                                                                                                                                                               |                                           |                                                                                             | $\leq 2$ GHz: $\leq 8$ mm<br>2 – 3 GHz: $\leq 5$ mm*                                                                                                                                                                                                                   | 3 – 4 GHz: $\leq 5$ mm*<br>4 – 6 GHz: $\leq 4$ mm*                            |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                      | uniform grid: $\Delta z_{\text{Zoom}}(n)$ |                                                                                             | $\leq 5$ mm                                                                                                                                                                                                                                                            | 3 – 4 GHz: $\leq 4$ mm<br>4 – 5 GHz: $\leq 3$ mm<br>5 – 6 GHz: $\leq 2$ mm    |
|                                                                                                                                                                                                                                                                                                      | graded grid                               | $\Delta z_{\text{Zoom}}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4$ mm                                                                                                                                                                                                                                                            | 3 – 4 GHz: $\leq 3$ mm<br>4 – 5 GHz: $\leq 2.5$ mm<br>5 – 6 GHz: $\leq 2$ mm  |
|                                                                                                                                                                                                                                                                                                      |                                           | $\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$                                                                                                                                                                                                                           |                                                                               |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                             | x, y, z                                   |                                                                                             | $\geq 30$ mm                                                                                                                                                                                                                                                           | 3 – 4 GHz: $\geq 28$ mm<br>4 – 5 GHz: $\geq 25$ mm<br>5 – 6 GHz: $\geq 22$ mm |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.                                                                                                                                                    |                                           |                                                                                             |                                                                                                                                                                                                                                                                        |                                                                               |
| * When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                           |                                                                                             |                                                                                                                                                                                                                                                                        |                                                                               |

#### **9.4 Volume Scan Procedures**

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remains in the same test position for all measurements and all volume scans use the same spatial resolution and grid spacing. When all volume scans were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculate the multiband SAR.

#### **9.5 SAR Averaged Methods**

In DASy, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

#### **9.6 Power Drift Monitoring**

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

## 10. Conducted RF Output Power (Unit: dBm)

### <GSM Conducted Power>

#### General Note:

1. Per KDB 447498 D01v05r01, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. For head SAR testing, the EUT was set in GSM Voice for GSM850 and GSM1900.
3. For body worn SAR testing, the EUT was set in GSM Voice for GSM850 and GSM1900.

| Band GSM850             |  | Burst Average Power (dBm) |       |        | Frame-Average Power (dBm) |       |        |
|-------------------------|--|---------------------------|-------|--------|---------------------------|-------|--------|
| TX Channel              |  | 128                       | 189   | 251    | 128                       | 189   | 251    |
| Frequency (MHz)         |  | 824.2                     | 836.4 | 848.8  | 824.2                     | 836.4 | 848.8  |
| GSM (GMSK, 1 Tx slot)   |  | 32.22                     | 32.40 | 32.43  | 23.22                     | 23.40 | 23.43  |
| GPRS (GMSK, 1 Tx slot)  |  | 32.20                     | 32.39 | 32.41  | 23.20                     | 23.39 | 23.41  |
| GPRS (GMSK, 2 Tx slots) |  | 30.50                     | 30.78 | 30.90  | 24.50                     | 24.78 | 24.90  |
| GPRS (GMSK, 3 Tx slots) |  | 29.28                     | 29.61 | 29.75  | 25.02                     | 25.35 | 25.49  |
| GPRS (GMSK, 4 Tx slots) |  | 27.37                     | 27.72 | 27.88  | 24.37                     | 24.72 | 24.88  |
| Band GSM1900            |  | Burst Average Power (dBm) |       |        | Frame-Average Power (dBm) |       |        |
| TX Channel              |  | 512                       | 661   | 810    | 512                       | 661   | 810    |
| Frequency (MHz)         |  | 1850.2                    | 1880  | 1909.8 | 1850.2                    | 1880  | 1909.8 |
| GSM (GMSK, 1 Tx slot)   |  | 29.80                     | 29.58 | 29.74  | 20.80                     | 20.58 | 20.74  |
| GPRS (GMSK, 1 Tx slot)  |  | 29.79                     | 29.52 | 29.71  | 20.79                     | 20.52 | 20.71  |
| GPRS (GMSK, 2 Tx slots) |  | 27.54                     | 27.17 | 27.47  | 21.54                     | 21.17 | 21.47  |
| GPRS (GMSK, 3 Tx slots) |  | 26.70                     | 26.31 | 26.63  | 22.44                     | 22.05 | 22.37  |
| GPRS (GMSK, 4 Tx slots) |  | 24.00                     | 23.66 | 23.94  | 21.00                     | 20.66 | 20.94  |

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

**<Bluetooth Conducted Power>**

| Bluetooth Average Power (dBm) |                 |           |      |      |      |      |      |      |      |      |
|-------------------------------|-----------------|-----------|------|------|------|------|------|------|------|------|
| Channel                       | Frequency (MHz) | Data Rate |      |      |      |      |      |      |      |      |
|                               |                 | DH1       | DH3  | DH5  | 2DH1 | 2DH3 | 2DH5 | 3DH1 | 3DH3 | 3DH5 |
| CH 00                         | 2402            | 7.83      | 7.55 | 7.64 | 5.09 | 5.05 | 4.91 | 5.11 | 5.08 | 4.92 |
| CH 39                         | 2441            | 8.20      | 8.16 | 8.01 | 5.56 | 4.93 | 5.24 | 5.61 | 4.94 | 5.25 |
| CH 78                         | 2480            | 8.59      | 8.55 | 8.40 | 5.94 | 5.78 | 5.64 | 5.92 | 5.81 | 5.65 |

**Note:**

1. Per KDB 447498 D01v05r01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for

1-g SAR and ≤ 7.5 for 10-g extremity SAR


- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- If the test separation distance (antenna-user) is < 5mm, 5mm is used for excluded SAR calculation

| Bluetooth Max Power (dBm) | mW   | Test Distance (mm) | Frequency (GHz) | Exclusion Thresholds |
|---------------------------|------|--------------------|-----------------|----------------------|
| 9                         | 8.00 | 0                  | 2.48            | 2.52                 |

2. Per KDB 447498 D01v05r01 exclusion thresholds is  $2.52 < 3$ , RF exposure evaluation is not required.

## 11. Antenna Location

<Flip-Open Mode>




<Flip-Close Mode>

Top Side

Right Side

Left Side



Back View

Bottom Side

## 12. SAR Test Results

### General Note:

- Per KDB 447498 D01v05r01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
- Per KDB 447498 D01v05r01, for each exposure position, if the highest output channel reported SAR  $\leq 0.8$ W/kg, other channels SAR testing is not necessary.
- Per KDB 865664 D01v01r02, for each frequency band, repeated SAR measurement is required only when the measured SAR is  $\geq 0.8$ W/kg.
- Body-worn accessory testing is typically associated with voice operations. Therefore GSM voice was evaluated for body-worn SAR.
- Per KDB 648474 D04v01r02, when the *reported* SAR for a body-worn accessory measured without a headset connected to the handset is  $\leq 1.2$  W/kg, SAR testing with a headset connected to the handset is not required.

### 12.1 Head SAR

#### <GSM SAR>

| Plot No. | Band    | Mode      | Flip Configuration | Test Position                 | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------|-----------|--------------------|-------------------------------|-----|-------------|---------------------|---------------------|----------------|------------------|------------------------|------------------------|
| #31      | GSM850  | GSM Voice | Open               | Right Cheek                   | 251 | 848.8       | 32.43               | 33                  | 1.140          | 0.08             | 0.103                  | 0.117                  |
| #32      | GSM850  | GSM Voice | Open               | Right Tilted                  | 251 | 848.8       | 32.43               | 33                  | 1.140          | 0.08             | 0.017                  | 0.019                  |
| #33      | GSM850  | GSM Voice | Open               | Left Cheek                    | 251 | 848.8       | 32.43               | 33                  | 1.140          | 0.04             | 0.106                  | 0.121                  |
| #34      | GSM850  | GSM Voice | Open               | Left Tilted                   | 251 | 848.8       | 32.43               | 33                  | 1.140          | 0.01             | 0.019                  | 0.022                  |
| #35      | GSM850  | GSM Voice | Open               | Right Cheek-SAR in mouth area | 251 | 848.8       | 32.43               | 33                  | 1.140          | -0.08            | 0.768                  | 0.876                  |
| #36      | GSM850  | GSM Voice | Open               | Right Cheek-SAR in mouth area | 128 | 824.2       | 32.22               | 33                  | 1.197          | 0.03             | 0.440                  | 0.527                  |
| #37      | GSM850  | GSM Voice | Open               | Right Cheek-SAR in mouth area | 189 | 836.4       | 32.4                | 33                  | 1.148          | 0.08             | 0.562                  | 0.645                  |
| #01      | GSM1900 | GSM Voice | Open               | Right Cheek                   | 512 | 1850.2      | 29.80               | 30                  | 1.047          | -0.1             | 0.110                  | 0.115                  |
| #02      | GSM1900 | GSM Voice | Open               | Right Tilted                  | 512 | 1850.2      | 29.80               | 30                  | 1.047          | -0.08            | 0.050                  | 0.052                  |
| #03      | GSM1900 | GSM Voice | Open               | Left Cheek                    | 512 | 1850.2      | 29.80               | 30                  | 1.047          | 0.02             | 0.124                  | 0.130                  |
| #04      | GSM1900 | GSM Voice | Open               | Left Tilted                   | 512 | 1850.2      | 29.80               | 30                  | 1.047          | 0.03             | 0.049                  | 0.051                  |
| #05      | GSM1900 | GSM Voice | Open               | Right Cheek-SAR in mouth area | 512 | 1850.2      | 29.80               | 30                  | 1.047          | 0.04             | 0.108                  | 0.113                  |

#### Note:

- The device antenna is located near the bottom and the measured head SAR distribution was clipped. According to KDB 648474 v01r02 section 8, EUT was positioned under the flat phantom with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell, the low bottom of the phone was lowered from the phantom to establish the same separation distance at the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone was determined by the straight line passing perpendicularly through the phantom surface. The procedure to determine the separation for EUT positioning under the flat phantom is illustrated in the SAR test setup photo exhibit

**12.2 Body Worn SAR****<GSM SAR>**

| Plot No. | Band    | Mode      | Flip Configuration | Test Position | Gap (cm) | Ch. | Freq. (MHz) | Average Power (dBm) | Tune-Up Limit (dBm) | Scaling Factor | Power Drift (dB) | Measured 1g SAR (W/kg) | Reported 1g SAR (W/kg) |
|----------|---------|-----------|--------------------|---------------|----------|-----|-------------|---------------------|---------------------|----------------|------------------|------------------------|------------------------|
| #41      | GSM850  | GSM Voice | Close              | Front         | 1.5      | 251 | 848.8       | 32.43               | 33                  | 1.140          | -0.04            | 0.143                  | 0.163                  |
| #42      | GSM850  | GSM Voice | Close              | Back          | 1.5      | 251 | 848.8       | 32.43               | 33                  | 1.140          | 0.01             | 0.676                  | 0.771                  |
| #11      | GSM1900 | GSM Voice | Close              | Front         | 1.5      | 512 | 1850.2      | 29.80               | 30                  | 1.047          | -0.07            | 0.066                  | 0.069                  |
| #12      | GSM1900 | GSM Voice | Close              | Back          | 1.5      | 512 | 1850.2      | 29.80               | 30                  | 1.047          | -0.05            | 0.095                  | 0.099                  |

### 12.3 Highest SAR Plot

Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2014.01.08

#### 35 GSM850\_GSM Voice\_SAR in mouth area\_Ch251

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
 Medium: HSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.03 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.686 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.20 W/kg

**SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.483 W/kg**

Maximum value of SAR (measured) = 1.00 W/kg



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab

Date: 2014.01.07

### #03 GSM1900\_GSM Voice\_Left Cheek\_Ch512

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
 Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2 \text{ MHz}$ ;  $\sigma = 1.363 \text{ S/m}$ ;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000 \text{ kg/m}^3$   
 Ambient Temperature :  $23.5 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.7 \text{ }^\circ\text{C}$

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x141x1):** Interpolated grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (interpolated) =  $0.153 \text{ W/kg}$


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $0.423 \text{ V/m}$ ; Power Drift =  $0.02 \text{ dB}$

Peak SAR (extrapolated) =  $0.197 \text{ W/kg}$

**SAR(1 g) =  $0.124 \text{ W/kg}$ ; SAR(10 g) =  $0.074 \text{ W/kg}$**

Maximum value of SAR (measured) =  $0.161 \text{ W/kg}$



### 13. Simultaneous Transmission Analysis

| NO. | Simultaneous Transmission Configurations | Portable Handset Exposure positions |           | Note                |
|-----|------------------------------------------|-------------------------------------|-----------|---------------------|
|     |                                          | Head                                | Body-worn |                     |
| 1.  | GSM(Voice) + Bluetooth                   | Yes                                 | Yes       | -                   |
| 2.  | GPRS(Data) + Bluetooth                   |                                     |           | Bluetooth Tethering |

**General Note:**

1. The reported SAR summation is calculated based on the same configuration and test position.
2. Per KDB 447498 D01v05r01, simultaneous transmission SAR is compliant if,
  - i) Scalar SAR summation  $< 1.6\text{W/kg}$ .
  - ii)  $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$ , where  $(x_1, y_1, z_1)$  and  $(x_2, y_2, z_2)$  are the coordinates of the extrapolated peak SAR locations in the zoom scan.  
If  $\text{SPLSR} \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.
  - iii) Simultaneously transmission SAR measurement, and the reported multi-band SAR  $< 1.6\text{W/kg}$ .

| Bluetooth Estimated SAR (W/kg) |                      |       |           |
|--------------------------------|----------------------|-------|-----------|
| Bluetooth Max power (dBm)      | Exposure Position    | Head  | Body-worn |
|                                | Test separation (mm) | 0     | 15        |
| 9                              | Estimated SAR (W/kg) | 0.336 | 0.112     |

### 13.1 Head Exposure Conditions

#### <WWAN + Bluetooth>

| Position     | WWAN (PCE) |         |            | Bluetooth (DSS)      | Summed SAR (W/kg) | SPLSR $\leq 0.04$ | Case No |
|--------------|------------|---------|------------|----------------------|-------------------|-------------------|---------|
|              | Band       | Plot No | SAR (W/kg) | Estimated SAR (W/kg) |                   |                   |         |
| Right Cheek  | GSM850     | #35     | 0.876      | 0.336                | 1.21              |                   |         |
|              | GSM1900    | #01     | 0.115      | 0.336                | 0.45              |                   |         |
| Right Tilted | GSM850     | #32     | 0.019      | 0.336                | 0.36              |                   |         |
|              | GSM1900    | #02     | 0.052      | 0.336                | 0.39              |                   |         |
| Left Cheek   | GSM850     | #33     | 0.121      | 0.336                | 0.46              |                   |         |
|              | GSM1900    | #03     | 0.130      | 0.336                | 0.47              |                   |         |
| Left Tilted  | GSM850     | #34     | 0.022      | 0.336                | 0.36              |                   |         |
|              | GSM1900    | #04     | 0.051      | 0.336                | 0.39              |                   |         |

### 13.2 Body-Worn Exposure Conditions

#### <WWAN + Bluetooth>

| Position | WWAN (PCE) |         |            | Bluetooth (DSS)      | Summed SAR (W/kg) | SPLSR $\leq 0.04$ | Case No |
|----------|------------|---------|------------|----------------------|-------------------|-------------------|---------|
|          | Band       | Plot No | SAR (W/kg) | Estimated SAR (W/kg) |                   |                   |         |
| Front    | GSM850     | #41     | 0.163      | 0.112                | 0.28              |                   |         |
|          | GSM1900    | #11     | 0.069      | 0.112                | 0.18              |                   |         |
| Back     | GSM850     | #42     | 0.771      | 0.112                | 0.88              |                   |         |
|          | GSM1900    | #12     | 0.099      | 0.112                | 0.21              |                   |         |

**Test Engineer :** Luke Lu

## 14. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 14.1

| Uncertainty Distributions          | Normal                     | Rectangular   | Triangular    | U-Shape       |
|------------------------------------|----------------------------|---------------|---------------|---------------|
| Multi-plying Factor <sup>(a)</sup> | 1/ $\kappa$ <sup>(b)</sup> | 1/ $\sqrt{3}$ | 1/ $\sqrt{6}$ | 1/ $\sqrt{2}$ |

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $\kappa$  is the coverage factor

**Table 14.1. Standard Uncertainty for Assumed Distribution**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

| Error Description                    | Uncertainty Value (±%) | Probability Distribution | Divisor | Ci (1g) | Ci (10g) | Standard Uncertainty (1g) | Standard Uncertainty (10g) |
|--------------------------------------|------------------------|--------------------------|---------|---------|----------|---------------------------|----------------------------|
| <b>Measurement System</b>            |                        |                          |         |         |          |                           |                            |
| Probe Calibration                    | 6.0                    | Normal                   | 1       | 1       | 1        | ± 6.0 %                   | ± 6.0 %                    |
| Axial Isotropy                       | 4.7                    | Rectangular              | √3      | 0.7     | 0.7      | ± 1.9 %                   | ± 1.9 %                    |
| Hemispherical Isotropy               | 9.6                    | Rectangular              | √3      | 0.7     | 0.7      | ± 3.9 %                   | ± 3.9 %                    |
| Boundary Effects                     | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| Linearity                            | 4.7                    | Rectangular              | √3      | 1       | 1        | ± 2.7 %                   | ± 2.7 %                    |
| System Detection Limits              | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| Readout Electronics                  | 0.3                    | Normal                   | 1       | 1       | 1        | ± 0.3 %                   | ± 0.3 %                    |
| Response Time                        | 0.8                    | Rectangular              | √3      | 1       | 1        | ± 0.5 %                   | ± 0.5 %                    |
| Integration Time                     | 2.6                    | Rectangular              | √3      | 1       | 1        | ± 1.5 %                   | ± 1.5 %                    |
| RF Ambient Noise                     | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| RF Ambient Reflections               | 3.0                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| Probe Positioner                     | 0.4                    | Rectangular              | √3      | 1       | 1        | ± 0.2 %                   | ± 0.2 %                    |
| Probe Positioning                    | 2.9                    | Rectangular              | √3      | 1       | 1        | ± 1.7 %                   | ± 1.7 %                    |
| Max. SAR Eval.                       | 1.0                    | Rectangular              | √3      | 1       | 1        | ± 0.6 %                   | ± 0.6 %                    |
| <b>Test Sample Related</b>           |                        |                          |         |         |          |                           |                            |
| Device Positioning                   | 2.9                    | Normal                   | 1       | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| Device Holder                        | 3.6                    | Normal                   | 1       | 1       | 1        | ± 3.6 %                   | ± 3.6 %                    |
| Power Drift                          | 5.0                    | Rectangular              | √3      | 1       | 1        | ± 2.9 %                   | ± 2.9 %                    |
| <b>Phantom and Setup</b>             |                        |                          |         |         |          |                           |                            |
| Phantom Uncertainty                  | 4.0                    | Rectangular              | √3      | 1       | 1        | ± 2.3 %                   | ± 2.3 %                    |
| Liquid Conductivity (Target)         | 5.0                    | Rectangular              | √3      | 0.64    | 0.43     | ± 1.8 %                   | ± 1.2 %                    |
| Liquid Conductivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.64    | 0.43     | ± 1.6 %                   | ± 1.1 %                    |
| Liquid Permittivity (Target)         | 5.0                    | Rectangular              | √3      | 0.6     | 0.49     | ± 1.7 %                   | ± 1.4 %                    |
| Liquid Permittivity (Meas.)          | 2.5                    | Normal                   | 1       | 0.6     | 0.49     | ± 1.5 %                   | ± 1.2 %                    |
| <b>Combined Standard Uncertainty</b> |                        |                          |         |         |          | ± 11.0 %                  | ± 10.8 %                   |
| <b>Coverage Factor for 95 %</b>      |                        |                          |         |         |          | K=2                       |                            |
| <b>Expanded Uncertainty</b>          |                        |                          |         |         |          | ± 22.0 %                  | ± 21.5 %                   |

**Table 14.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz**

## **15. References**

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r02, "SAR Measurement Requirements for 100 MHz to 6 GHz", Dec 2013
- [6] FCC KDB 447498 D01 v05r01, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", May 2013
- [7] FCC KDB 648474 D04 v01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013
- [8] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008



## ***Appendix A. Plots of System Performance Check***

The plots are shown as follows.

**System Check\_Head\_835MHz\_140108****DUT: D835V2 - SN: 4d091**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835\_140108 Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.91$  S/m;  $\epsilon_r = 42.91$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 3.12 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.800 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 3.66 W/kg

**SAR(1 g) = 2.47 W/kg; SAR(10 g) = 1.62 W/kg**

Maximum value of SAR (measured) = 3.13 W/kg



**System Check\_Head\_835MHz\_140124****DUT: Dipole 835 MHz**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835\_140124 Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.906$  S/m;  $\epsilon_r = 42.89$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 3.05 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 59.389 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.56 W/kg

**SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.59 W/kg**

Maximum value of SAR (measured) = 3.05 W/kg



**System Check\_Head\_1900MHz\_140107****DUT: D1900V2 - SN: 5d118**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.417$  S/m;  $\epsilon_r = 40.994$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 13.6 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 96.959 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 17.3 W/kg

**SAR(1 g) = 9.45 W/kg; SAR(10 g) = 4.92 W/kg**

Maximum value of SAR (measured) = 13.4 W/kg



**System Check\_Body\_835MHz\_140108****DUT: D835V2 - SN: 4d091**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_140108 Medium parameters used:  $f = 835$  MHz;  $\sigma = 1.011$  S/m;  $\epsilon_r = 56.243$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.54, 9.54, 9.54); Calibrated: 2013.11.27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM3; Type: QDOVA002AA; Serial: TP:1149
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.61 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 51.095 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.49 W/kg

**SAR(1 g) = 2.42 W/kg; SAR(10 g) = 1.6 W/kg**

Maximum value of SAR (measured) = 2.60 W/kg



**System Check\_Body\_1900MHz\_140107****DUT: D1900V2 - SN: 5d118**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL\_1900\_140107 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.533$  S/m;  $\epsilon_r = 54.611$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(7.55, 7.55, 7.55); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 15.1 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 87.548 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 19.1 W/kg

**SAR(1 g) = 10.6 W/kg; SAR(10 g) = 5.48 W/kg**

Maximum value of SAR (measured) = 15.1 W/kg





## ***Appendix B. Plots of SAR Measurement***

The plots are shown as follows.

**31 GSM850\_GSM Voice\_Right Cheek\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.136 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.434 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.195 W/kg

**SAR(1 g) = 0.103 W/kg; SAR(10 g) = 0.060 W/kg**

Maximum value of SAR (measured) = 0.135 W/kg



**32 GSM850\_GSM Voice\_Right Tilted\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0210 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.413 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.0230 W/kg

**SAR(1 g) = 0.017 W/kg; SAR(10 g) = 0.013 W/kg**

Maximum value of SAR (measured) = 0.0206 W/kg



**33 GSM850\_GSM Voice\_Left Cheek\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.147 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.635 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.175 W/kg

**SAR(1 g) = 0.106 W/kg; SAR(10 g) = n.a.**

Maximum value of SAR (measured) = 0.147 W/kg



**34 GSM850\_GSM Voice\_Left Tilted\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0231 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.505 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.0250 W/kg

**SAR(1 g) = 0.019 W/kg; SAR(10 g) = 0.013 W/kg**

Maximum value of SAR (measured) = 0.0228 W/kg



**35 GSM850\_GSM Voice\_Right Cheek\_SAR in mouth area\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140124 Medium parameters used:  $f = 849$  MHz;  $\sigma = 0.925$  S/m;  $\epsilon_r = 42.729$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.03 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.686 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.20 W/kg

**SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.483 W/kg**

Maximum value of SAR (measured) = 1.00 W/kg



**36 GSM850\_GSM Voice\_Right Cheek\_SAR in mouth area\_Ch128**

Communication System: UID 0, Generic GSM (0); Frequency: 824.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140124 Medium parameters used:  $f = 824.2$  MHz;  $\sigma = 0.899$  S/m;  $\epsilon_r = 43.045$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch128/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.588 W/kg


**Ch128/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.249 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.694 W/kg

**SAR(1 g) = 0.440 W/kg; SAR(10 g) = 0.276 W/kg**

Maximum value of SAR (measured) = 0.575 W/kg



**37 GSM850\_GSM Voice\_Right Cheek\_SAR in mouth area\_Ch189**

Communication System: UID 0, Generic GSM (0); Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_835\_140124 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.912$  S/m;  $\epsilon_r = 42.893$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.68, 9.68, 9.68); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch189/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.754 W/kg


**Ch189/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 1.239 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.876 W/kg

**SAR(1 g) = 0.562 W/kg; SAR(10 g) = 0.353 W/kg**

Maximum value of SAR (measured) = 0.732 W/kg



**01 GSM1900\_GSM Voice\_Right Cheek\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.158 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.551 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.181 W/kg

**SAR(1 g) = 0.110 W/kg; SAR(10 g) = n.a.**

Maximum value of SAR (measured) = 0.155 W/kg



**02 GSM1900\_GSM Voice\_Right Tilted\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0662 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.805 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.0770 W/kg

**SAR(1 g) = 0.050 W/kg; SAR(10 g) = 0.030 W/kg**

Maximum value of SAR (measured) = 0.0635 W/kg



**03 GSM1900\_GSM Voice\_Left Cheek\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.153 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.423 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.197 W/kg

**SAR(1 g) = 0.124 W/kg; SAR(10 g) = 0.074 W/kg**

Maximum value of SAR (measured) = 0.161 W/kg



**04 GSM1900\_GSM Voice\_Left Tilted\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x141x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0651 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 0.428 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.0740 W/kg

**SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.031 W/kg**

Maximum value of SAR (measured) = 0.0618 W/kg



**05 GSM1900\_GSM Voice\_Right Cheek\_SAR in mouth area\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 41.24$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(8, 8, 8); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.144 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.202 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.175 W/kg

**SAR(1 g) = 0.108 W/kg; SAR(10 g) = 0.067 W/kg**

Maximum value of SAR (measured) = 0.142 W/kg



**41 GSM850\_GSM Voice\_Front\_1.5cm\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 1.026$  S/m;  $\epsilon_r = 56.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.54, 9.54, 9.54); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM3; Type: QDOVA002AA; Serial: TP:1149
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.176 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.063 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.199 W/kg

**SAR(1 g) = 0.143 W/kg; SAR(10 g) = 0.103 W/kg**

Maximum value of SAR (measured) = 0.177 W/kg



**42 GSM850\_GSM Voice\_Back\_1.5cm\_Ch251**

Communication System: UID 0, Generic GSM (0); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_835\_140108 Medium parameters used:  $f = 849$  MHz;  $\sigma = 1.026$  S/m;  $\epsilon_r = 56.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(9.54, 9.54, 9.54); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM3; Type: QDOVA002AA; Serial: TP:1149
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch251/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.828 W/kg


**Ch251/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.010 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.936 W/kg

**SAR(1 g) = 0.676 W/kg; SAR(10 g) = 0.463 W/kg**

Maximum value of SAR (measured) = 0.825 W/kg



**11 GSM1900\_GSM Voice\_Front\_1.5cm\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.468$  S/m;  $\epsilon_r = 54.843$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(7.55, 7.55, 7.55); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.0864 W/kg


**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.296 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.104 W/kg

**SAR(1 g) = 0.066 W/kg; SAR(10 g) = 0.041 W/kg**

Maximum value of SAR (measured) = 0.0863 W/kg



**12 GSM1900\_GSM Voice\_Back\_1.5cm\_Ch512**

Communication System: UID 0, Generic GSM (0); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
Medium: MSL\_1900\_140107 Medium parameters used:  $f = 1850.2$  MHz;  $\sigma = 1.468$  S/m;  $\epsilon_r = 54.843$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN3819; ConvF(7.55, 7.55, 7.55); Calibrated: 2013.11.27;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 2013.11.22
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

**Ch512/Area Scan (51x81x1):** Interpolated grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.123 W/kg

**Ch512/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 2.761 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.160 W/kg

**SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.056 W/kg**

Maximum value of SAR (measured) = 0.128 W/kg

