



SAMSUNG ELECTRONICS Co., Ltd.,
Regulatory Compliance Group
IT R&D Center

416, Maetan-3dong,
Yeongtong-gu, Suwon-si,
Gyeonggi-do, Korea 443-742

TEST REPORT ON SAR

Model Tested: GT-E3300L
FCC ID (Requested): A3LGTE3300L
Job No: FJ-148
Report No: FJ-148-S1

- Abstract -

This document reports on SAR Tests carried out in accordance with FCC/OET Bulletin 65, Supplement C(June 2001).

Prepared By

BH JEON - Test Engineer

Authorized By

JD JANG - Technical Manager

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	1 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Contents

1. GENERAL INFORMATION	3
2. DESCRIPTION OF DEVICE	3
3. DESCRIPTION OF TEST EQUIPMENT	4
3.1 SAR Measurement Setup	4
3.2 E-field Probe	5
3.3 Phantom	7
3.4 Brain Simulating Mixture Characterization	9
3.5 Device Holder for Transmitters.....	10
3.6 Validation Dipole	10
3.7 Equipment Calibration.....	11
4. SAR MEASUREMENT PROCEDURE.....	12
5. DESCRIPTION OF TEST POSITION	13
5.1 SAM Phantom Shape	13
5.2 “cheek” Position	13
5.3 “tilted” Position	15
5.4 Body Holster/Belt Clip Configurations	16
6. MEASUREMENT UNCERTAINTY	17
7. SYSTEM VERIFICATION	19
7.1 Tissue Verification	19
7.2 Test System Validation	19
8. SAR MEASUREMENT RESULTS	20
8.1 SAR DATA Summay.....	24
8.2 SAR Note	28
8.3 Simultaneous Transmission	29
9. CONCLUSION	31
10. REFERENCES.....	32

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	2 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

1. GENERAL INFORMATION

Test Dates : May.29, 2012 ~ May.30, 2012
Manufacturer : SAMSUNG ELECTRONICS Co., Ltd.
Address : 416 Maetan3-Dong, Suwon City, Korea
Test Standard : §2.1093; FCC/OET Bulletin 65, Supplement C(June 2001)
FCC Classification : Licensed Portable Transmitter Held to Ear (PCE)
Tested for : FCC/TCB Certification

2. DESCRIPTION OF DEVICE

Test Sample : 850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth
Model Number : GT-E3300L
Serial Number : Identical prototype (S/N : # FJ-148-C)
Tx Freq. Range: 824.20 ~ 848.80 MHz (GSM850)
1850.20 ~ 1909.80 MHz (GSM1900)
826.40 ~ 846.60 MHz (WCDMA850)
1852.4 ~ 1907.6 MHz (WCDMA1900)
2402 ~ 2480 MHz (Bluetooth)
Antenna Manufacturer : Yokowo
Model No.: GT-E3300L
Antenna Dimensions : 40.54 x 18.25 x 5.07 (mm)
Separation distance between
Main and Bluetooth antenna : 32mm

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	3 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

3. DESCRIPTION OF TEST EQUIPMENT

3.1 SAR Measurement Setup

Robotic System

Measurements are performed using the DASY4 (or DASY5) automated dosimetric assessment system. Which is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Stäubli), robot controller, measurement server, Samsung computer, near-field probe, probe alignment sensor, and the SAM twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 3.1).




Figure 3.1 SAR Measurement System Setup

System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control is used to drive the robot motors. The PC consists of the Samsung computer with Windows XP system and SAR Measurement Software DASY4 (or DASY5), LCD monitor, mouse and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the measurement server.

System Electronics

The DAE4(or DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information and an

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	4 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

3.2 E-field Probe



The SAR measurement were conducted with the dosimetric probe ES3DV2, ES3DV3, EX3DV4 and ET3DV6, designed in the classical triangular configuration (see Fig.3.3) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting (see Fig.3.2). The approach is stopped at reaching the maximum.

Figure 3.2 DAE System Probe Specifications

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Basic Broad Band Calibration in air: 10-3000 MHz Conversion Factors (CF) for HSL 900 and HSL 1800 Additional CF for other liquids and frequencies upon request
Frequency	10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Directivity	[ES3DV3], [ET3DV6] ± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)




Figure 3.3 Triangular Probe Configuration

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	5 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

[EX3DV4]

± 0.3 dB in HSL (rotation around probe axis)

± 0.5 dB in tissue material (rotation normal to probe axis)

Dynamic Range [ES3DV3], [ET3DV6]

5μW/g to > 100mW/g; Linearity: ± 0.2dB

[EX3DV4]

10 μW/g to > 100 mW/g; Linearity: ± 0.2 dB

Dimensions [ES3DV3], [ES3DV2]

Overall length: 330 mm (Tip: 20 mm)

Tip diameter: 3.9 mm (Body: 12 mm)

Distance from probe tip to dipole centers: 2.1 mm

[EX3DV4]

Overall length: 330 mm (Tip: 20 mm)

Tip diameter: 2.5 mm (Body: 12 mm)

Typical distance from probe tip to dipole centers: 1 mm



[ES3DV3] ,[ES3DV2]

[ET3DV6]

Overall length: 330mm

Tip length: 16mm

Body diameter: 12mm

Tip diameter: 6.8mm

Distance from probe tip to dipole centers: 2.7mm



[EX3DV4]

Application [ES3DV3], [ES3DV2]

General dosimetry up to 5 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones

[EX3DV4]

High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields).Only probe which enables compliance testing for frequencies up to

6 GHz with precision of better 30 %.



[ET3DV6]

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	6 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

[ET3DV6]

General dosimetry up to 3 GHz

Compliance tests of mobile phones

Fast automatic scanning in arbitrary phantoms

Optical

[ET3DV6]

Surface

± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces

Detection

3.3 Phantom

SAM Twin Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid.

Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (See Figure 3.5)



Figure3.5 SAM Twin Phantom

SAM Twin Phantom Specification

Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, EN 50361:2001 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid.
Shell Thickness	2 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Height: 810 mm; Length: 1000 mm; Width: 500 mm

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	7 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Modular Flat Phantom

The Modular Flat Phantom V5.1 is constructed of a fiberglass shell integrated in a wooden table. Also It consists of three identical flat phantoms (modules) which can be installed and removed separately without emptying the liquid, as well as a wooden support.. It enables the dosimetric evaluation of body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid.

Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (See Figure 3.6)



Figure 3.6 Modular Flat

Modular Flat Phantom Specification

Construction	The shell corresponds to the specifications of IEEE 1528-2003. It enables the dosimetric evaluation of body mounted usage above 800 MHz at the flat phantom region. A cover prevents evaporation of the liquid
Shell Thickness	2 ± 0.2 mm
Filling Volume	Approx. 10 liters
Dimension	Wooden support - Height: 810 mm; Length: 830 mm; Width: 500 mm Each Module - Height:190 mm; Length: 200 mm; width: 300 mm

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	8 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

3.4 Brain Simulating Mixture Characterization

The brain mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 3.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue.




Figure 3.7 Simulated Tissue

Table 3.1 Composition of the Tissue Equivalent Matter


INGREDIENTS	835MHz Brain	835MHz Muscle	1900MHz Brain	1900MHz Muscle
WATER	40.29%	50.75%	55.24%	70.23%
SUGAR	57.90%	48.21%	-	-
SALT	1.38%	0.94%	0.24%	0.21%
TWEEN20	-	-	44.52%	29.56%
BACTERIACIDE	0.18%	0.10%	-	-
HEC	0.25%	-	-	-
Dielectric Constant Target	41.50	55.20	40.00	53.30
Conductivity Target (S/m)	0.900	0.970	1.400	1.520

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	9 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

3.5 Device Holder for Transmitters

In combination with the Twin SAM Phantom V4.0, the Mounting Device (see Fig. 3.7) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be



easily, accurately and repeatedly be positioned according to the EN 50360:2001 and FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

*Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configuration. To produce worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

Figure 3.8 Device Holder

3.6 Validation Dipole

The reference dipole should have a return loss better than -20 dB (measured in the setup) at the resonant frequency to reduce the uncertainty in the power measurement.

Frequency	835, 1900 MHz
Return Loss	< -20 dB at specified validation position
Dimensions	D835V2: dipole length: 161 mm; overall height: 330 mm D1900V2: dipole length: 68 mm; overall height: 300 mm

Note:

Usage of SAR dipoles calibrated less than 2 years ago but more than 1 year ago were confirmed in maintaining return loss (< -20dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibration in KDB 450824

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	10 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

3.7 Equipment Calibration

Table 3.3 Test Equipment Calibration

Type	Calibration Due Date	Serial No.
SPEAG E-Field Probe EX3DV4	Feb.21, 2013	3520
SPEAG DAE4	Sep.21, 2012	533
SPEAG Validation Dipole D1900V2	Jan.26, 2014	5d023
SPEAG Validation Dipole D835V2	Nov.18, 2013	4d111
Stäubli Robot RX90BL	Not Required	F05/51G6A1/A/01
SPEAG SAM Twin Phantom V4.0	Not Required	TP-1364
SPEAG SAM Twin Phantom V4.0	Not Required	TP-1603
SPEAG SAM Twin Phantom V4.0	Not Required	TP-1604
SPEAG SAM Twin Phantom V4.0	Not Required	TP-1425
SPEAG SAM Twin Phantom V4.0	Not Required	TP-1248
Modular Phantom	Not Required	MP-1010
Modular Phantom	Not Required	MP-1007
Modular Phantom	Not Required	MP-1003
E4421B Signal Generator	Oct.12, 2012	MY41000654
BBS3Q7ELU Power Amp	Oct.12, 2012	1007D/C0035
E4419B Power meter	Oct.12, 2012	GB41293847
HP-8753ES Network Analyzer	Apr.16, 2013	US39173712
HP85070C Dielectric Probe Kit	Not Required	US99360087
Digital thermo-hygrometer	Feb.09, 2013	1367
Digital thermo-hygrometer	Feb.09, 2013	SK-L200TH
E4419B Power meter	Feb.25, 2013	MY45103291
E9300B Power sensor	Mar.04, 2013	MY41496209
E9300B Power sensor	Mar.04, 2013	MY41496085
DASY4 S/W (ver 4.7)	Not Required	-
8560E Spectrum Analyzer	Sep.16, 2012	3635A02452
778D Dual Directional Coupler	Dec.02, 2012	50189
777D Dual Directional Coupler	Feb.23, 2013	07523
772D Dual Directional Coupler	Mar.04, 2013	ZA200100954
Pre-Amplifier 84498B	Dec.09, 2012	3008A00691
Base Station Simulator	Dec.19, 2012	GB46490112
Communication tester(E5515C)	Nov.27, 2012	GB42230535
11636B	Jul.05, 2012	51942

NOTE:

The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Validation measurement is performed by Samsung Lab. before each test. (see § 7.2) The brain simulating material is calibrated by Samsung using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material. (see § 7.1)

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	11 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

4. SAR MEASUREMENT PROCEDURE

The evaluation was performed using the following procedure.

STEP 1

The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed location point was measured and used as a reference value.

STEP 2

The SAR distribution at the exposed side of the head was measured at a distance of 3.9mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20mm x 20mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

STEP 3

Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

STEP 4

The SAR value at the same location as in step 1 was again measured.

(If the value changed by more than 5%, the evaluation is repeated.)

STEP 5

For 5GHz testing finer resolution zoom scans were performed as specified by FCC SAR Measurement Requirements for 3 -6 GHz, KDB pub 865664. The 5GHz zoom scan requires a minimum volume of 24mm x 24mm x 20mm and 7 x 7 x 11 points.

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	12 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

5. DESCRIPTION OF TEST POSITION

5.1 SAM Phantom Shape

Figure 5.1 shows the front, back and side views of SAM. The point “M” is the reference point for the center of mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15 mm posterior to the entrance to ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5.2.



Figure 5.1 Front, back and side view of SAM

The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 5.3). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines should be marked on the external phantom shell to facilitate handset positioning. Posterior to the N-F line, the thickness of the phantom shell with the shape of an ear is a flat surface 6 mm thick at the ERPs.




Figure 5.2 Close up side view

5.2 “cheek” Position

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (see Fig. 5.4). The “test device reference point” was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its tip and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	13 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012





Figure 5.3 Side view of the phantom showing relevant markings

5.4 Handset vertical and horizontal reference lines

Step 1

The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 5.5), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom




Figure 5.5 Front, Side and Top View of Cheek/Touch Position

Step 2

The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.

Step 3

While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).

Step 4

Rotate the handset around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	14 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Step 5

While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 5.2.

5.3 “tilted” Position

With the test device aligned in the “cheek” position :

Step 1

Repeat steps 1 to 5 of 5.2 to place the device in the “Cheek/Touch Position”




Figure 5.6 Front, side and Top View of Ear/Tilt 15° Position

Step 2

While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.

Step 3

The phone was then rotated around the horizontal line by 15 degree.

Step 4

While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head.

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	15 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

5.4 Body Holster/Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 5.7). A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains unique metallic component. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), Including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements must be included in the user's manual.

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	16 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

6. MEASUREMENT UNCERTAINTY

Table 6.1 Uncertainty Budget at 835MHz

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	C_i	Standard uncertainty (±%)	v_i^2 or v_{eff}
Measurement System						
Probe Calibration	11.00	normal	2.000	1	5.50	∞
Axial Isotropy	4.70	rectangular	1.732	0.7	1.90	∞
Hemispherical Isotropy	9.60	rectangular	1.732	0.7	3.88	∞
Linearity	4.70	rectangular	1.732	1	2.71	∞
System Detection Limits	0.25	rectangular	1.732	1	0.14	∞
Boundary effects	1.00	rectangular	1.732	1	0.58	∞
Readout electronics	0.30	normal	1.000	1	0.30	∞
Response time	0.80	rectangular	1.732	1	0.46	∞
RF ambient conditions	3.00	rectangular	1.732	1	1.73	∞
Integration time	1.73	rectangular	1.732	1	1.00	∞
Mechanical constrains of robot	1.50	rectangular	1.732	1	0.87	∞
Probe positioning	2.90	rectangular	1.732	1	1.67	∞
Extrapolation and integration	1.00	rectangular	1.732	1	0.58	∞
Test Sample Related						
Test Sample positioning	1.12	normal	1.000	1	1.12	14
Device holded uncertainty	3.44	normal	1.000	1	3.44	∞
Power Drift	5.00	rectangular	1.732	1	2.89	∞
Phantom and Setup						
Modular Phantom uncertainty	5.62	normal	1.000	1	5.62	2
Phantom uncertainty	4.00	rectangular	1.732	1	2.31	∞
Liquid conductivity (deviation from target)	5.00	rectangular	1.732	0.64	1.85	∞
Liquid conductivity (measurement error)	0.38	normal	1.000	0.64	0.24	∞
Liquid permittivity (deviation from target)	5.00	rectangular	1.732	0.6	1.73	∞
Liquid permittivity (measurement error)	5.44	normal	1.000	0.6	3.26	∞
Combined Standard Uncertainty		Normal	-	-	11.84	172776
Extended Standard Uncertainty(K=2.00)					23.69	172776

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	17 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Table 6.2 Uncertainty Budget at 1900MHz

Error Description	Uncertainty Value ($\pm\%$)	Probability Distribution	Divisor	c_i	Standard uncertainty ($\pm\%$)	v_i^2 or v_{eff}
Measurement System						
Probe Calibration	12.00	normal	2.000	1	6.00	∞
Axial Isotropy	4.70	rectangular	1.732	0.7	1.90	∞
Hemispherical Isotropy	9.60	rectangular	1.732	0.7	3.88	∞
Linearity	4.70	rectangular	1.732	1	2.71	∞
System Detection Limits	0.25	rectangular	1.732	1	0.14	∞
Boundary effects	1.00	rectangular	1.732	1	0.58	∞
Readout electronics	0.30	normal	1.000	1	0.30	∞
Response time	0.80	rectangular	1.732	1	0.46	∞
RF ambient conditions	3.00	rectangular	1.732	1	1.73	∞
Integration time	0.00	rectangular	1.732	1	0.00	∞
Mechanical constrains of robot	1.50	rectangular	1.732	1	0.87	∞
Probe positioning	2.90	rectangular	1.732	1	1.67	∞
Extrapolation and integration	1.00	rectangular	1.732	1	0.58	∞
Test Sample Related						
Test Sample positioning	1.50	normal	1.000	1	1.50	14
Device holded uncertainty	3.44	normal	1.000	1	3.44	∞
Power Drift	5.00	rectangular	1.732	1	2.89	∞
Phantom and Setup						
Modular Phantom uncertainty	6.02	normal	1.000	1	6.02	2
Phantom uncertainty	4.00	rectangular	1.732	1	2.31	∞
Liquid conductivity (deviation from target)	5.00	rectangular	1.732	0.64	1.85	∞
Liquid conductivity (measurement error)	1.84	normal	1.000	0.64	1.18	∞
Liquid permittivity (deviation from target)	5.00	rectangular	1.732	0.6	1.73	∞
Liquid permittivity (measurement error)	4.54	normal	1.000	0.6	2.73	∞
Combined Standard Uncertainty		Normal	-	-	12.24	62037
Extended Standard Uncertainty(K=2.00)					24.48	62037

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	18 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

7. SYSTEM VERIFICATION

7.1 Tissue Verification

Table 7.1 MEASURED TISSUE PARAMETERS

	835MHz Head		835MHz Body		1900MHz Head		1900MHz Body	
	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Date	May.30, 2012		May.30, 2012		May.29, 2012		May.29, 2012	
Liquid Temperature(°C)	22.1		22.2		22.3		22.2	
Dielectric Constant: $\hat{\alpha}'$	41.5	42.54	55.2	56.08	40	39.49	53.3	51.83
Conductivity:	0.9	0.93	0.97	1.00	1.4	1.39	1.52	1.54
Tissue Batch Number	835DF1001X		835B1001V		1900F1002F		1900B3001E	

The measured value must be within $\pm 5\%$ of the target value.

7.2 Test System Validation

Prior to assessment, the system is verified to the $\pm 10\%$ of the specification at 835MHz and 1900MHz by using the system validation kit(s). (see Appendix D, Graphic Plot Attached)

Table 7.2 System Validation Results

System Validation Kit	Tissue	Targeted SAR _{1g} (mW/g)	Normalized SAR _{1g} (mW/g)	Measured SAR _{1g} (mW/g)	Deviation (%)	Date	Liquid Temperature(°C)	Ambient Temperature(°C)	Input Power (mW)
4d111	835MHz Brain	9.43	9.52	2.38	0.95%	May.30, 2012	22.1	22.4	250
4d111	835MHz Body	9.54	9.6	2.4	0.63%	May.30, 2012	22.0	22.3	250
5d023	1900MHz Brain	39.0	40.3	4.03	3.33%	May.29, 2012	22.4	22.6	100
5d023	1900MHz Body	38.8	39.6	3.96	2.06%	May.29, 2012	22.2	22.4	100

*Validation was normalized to 1W.




Figure 7.1 Dipole Validation Test Setup

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	19 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

8. SAR MEASUREMENT RESULTS

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode using base station simulator. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

SAR Measurement Conditions for WCDMA

These procedures were followed according to FCC "SAR Measurement Procedures for 3G Devices"v02, October 2007.

Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s". Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes) should be tabulated in the test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations should be clearly identified.

Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4kbps SRB (signaling radio bearer) using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits configured to all "1s". SAR for other spreading codes and multiple DPDCHn, when supported by the DUT, are not required when the maximum average outputs of each RF channel, for each spreading code and DPDCHn configuration, are less than ¼ dB higher than those measured in 12.2 RMC. Otherwise, SAR is measured on the maximum output channel with an applicable RMC configuration

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	20 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

for the corresponding spreading code or DPDCHn using the exposure configuration that results in the highest SAR with 12.2 RMC. When more than 2 DPDCHn are supported by the DUT, it may be necessary to configure the additional DPDCHn for the DUT using FTM(Factory Test Mode) with parameters similar to those used in 384 kbps and 768 kbps RMC.

Table 8.1 Max. Power Output Table for GT-E3300L

Operating Band	Channel	HSDPA Inactive		HSDPA Active
		12.2 kbps RMC	12.2 kbps AMR	12.2 kbps RMC
WCDMA 850 (dBm)	4132	22.22	22.20	21.95
	4183	22.39	22.36	22.23
	4233	22.34	22.35	22.15
WCDMA 1900 (dBm)	9262	22.39	22.35	22.34
	9400	22.13	22.20	22.13
	9538	22.10	22.11	22.14

Table 8.2 HSDPA Max. Power Output Table for GT-E3300L

WCDMA 850 (dBm)	HSDPA	4132	4183	4233	MPR
	Subtest1	21.95	22.23	22.15	0.0
	Subtest2	21.84	22.13	22.02	0.0
	Subtest3	21.00	21.19	21.12	0.5
	Subtest4	21.00	21.17	21.10	0.5
WCDMA 1900 (dBm)	HSDPA	9262	9400	9538	MPR
	Subtest1	22.34	22.13	22.14	0.0
	Subtest2	22.25	22.26	22.18	0.0
	Subtest3	21.21	21.30	21.08	0.5
	Subtest4	21.16	21.24	21.12	0.5

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	21 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated. And all Tx conducted power were also investigated for Body SAR Measurement.

Table 8.3 Conducted Power Table for GT-E3300L

Band	Channel	Voice	GPRS(GMSK)			
		GSM(dBm) CS(1 Tx)	1Tx (dBm)	2Tx (dBm)	3Tx (dBm)	4Tx (dBm)
850	128	32.43	32.36	31.13	29.07	28.01
	190	32.44	32.32	31.14	29.08	28.04
	251	32.51	32.39	31.21	29.17	28.13
1900	512	29.55	29.58	27.51	25.5	24.41
	661	29.35	29.23	27.37	25.39	24.31
	810	29.19	29.06	27.28	25.34	24.27

Table 8.4 Calculated Frame-Averaged Output Power Table for GT-E3300L

Band	Channel	Voice	GPRS (GMSK)			
		GSM(dBm) CS(1 Tx)	1Tx (dBm)	2Tx (dBm)	3Tx (dBm)	4Tx (dBm)
850	128	23.40	23.33	25.11	24.81	25.00
	190	23.41	23.29	25.12	24.82	25.03
	251	23.48	23.36	25.19	24.91	25.12
1900	512	20.52	20.55	21.49	21.24	21.40
	661	20.32	20.20	21.35	21.13	21.30
	810	20.16	20.03	21.26	21.08	21.26

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	22 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. CS1 coding scheme was used in GPRS output power measurements and SAR Testing, as a condition where GMSK modulation was ensured. It was investigated that CS1 - CS4 settings do not have any impact on the output levels in the GPRS modes.
3. The conducted powers are reported and measured by base station simulator E5515C when the equipment was calibrated.

GSM Class : B

GPRS Multislot Class : 10 (max 2 Tx Uplink slots)

EDGE Multislot Class : 10 (max 2 Tx Uplink slots)

DTM Multislot Class : N/A

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	23 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

8.1 SAR DATA Summay

Table 8.5 GSM850 Head SAR Results

Frequency		Mode	Conducted		Side	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
824.2	128	GSM850	32.42	32.43	Right	Cheek/Touch	Intenna	Standard	0.052	0.817
836.6	190	GSM850	32.44	32.45	Right	Cheek/Touch	Intenna	Standard	-0.030	1.01
848.8	251	GSM850	32.50	32.49	Right	Cheek/Touch	Intenna	Standard	0.041	0.898
836.6	190	GSM850	32.43	32.45	Right	Ear/Tilt 15°	Intenna	Standard	-0.012	0.466
824.2	128	GSM850	32.41	32.42	Left	Cheek/Touch	Intenna	Standard	0.004	0.731
836.6	190	GSM850	32.45	32.44	Left	Cheek/Touch	Intenna	Standard	-0.070	0.814
848.8	251	GSM850	32.49	32.52	Left	Cheek/Touch	Intenna	Standard	0.028	0.835
836.6	190	GSM850	32.43	32.45	Left	Ear/Tilt 15°	Intenna	Standard	0.014	0.420
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

Table 8.6 GSM850 Body SAR Results

Frequency		Mode	Conducted		Separation Distance	Test Position	Antenna Type	Battery	Tx GPRS Slots	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End							
836.6	190	GPRS850	31.12	31.15	1.5cm	Back	Intenna	Standard	2	-0.074	0.580
836.6	190	GPRS850	29.09	29.10	1.5cm	Back	Intenna	Standard	3	0.025	0.562
836.6	190	GPRS850	28.04	28.01	1.5cm	Back	Intenna	Standard	4	-0.015	0.584
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram					

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	24 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Table 8.7 GSM1900 Head SAR Results

Frequency		Mode	Conducted		Side	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
1880	661	GSM1900	29.35	29.32	Right	Cheek/Touch	Intenna	Standard	0.026	0.597
1880	661	GSM1900	29.33	29.33	Right	Ear/Tilt 15°	Intenna	Standard	0.005	0.095
1880	661	GSM1900	29.31	29.34	Left	Cheek/Touch	Intenna	Standard	0.047	0.420
1880	661	GSM1900	29.34	29.32	Left	Ear/Tilt 15°	Intenna	Standard	0.056	0.114
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

Table 8.8 GPRS1900 Body SAR Results

Frequency		Mode	Conducted		Separation Distance	Test Position	Antenna Type	Battery	Tx Slots	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End							
1880	661	GPRS1900	27.37	27.34	1.5cm	Back	Intenna	Standard	2	0.011	0.179
1880	661	GPRS1900	25.39	25.35	1.5cm	Back	Intenna	Standard	3	0.015	0.124
1880	661	GPRS1900	24.32	24.36	1.5cm	Back	Intenna	Standard	4	0.010	0.130
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram					

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	25 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Table 8.9 WCDMA850 Head SAR Results

Frequency		Mode	Conducted Power		Side	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
826.4	4132	WCDMA850	22.21	22.24	Right	Cheek/Touch	Intenna	Standard	-0.029	0.959
836.6	4183	WCDMA850	22.37	22.34	Right	Cheek/Touch	Intenna	Standard	-0.014	0.995
846.6	4233	WCDMA850	22.34	22.35	Right	Cheek/Touch	Intenna	Standard	-0.038	1.07
836.6	4183	WCDMA850	22.36	22.36	Right	Ear/Tilt 15°	Intenna	Standard	0.005	0.527
826.4	4132	WCDMA850	22.23	22.24	Left	Cheek/Touch	Intenna	Standard	-0.042	0.917
836.6	4183	WCDMA850	22.35	22.34	Left	Cheek/Touch	Intenna	Standard	-0.039	1.07
846.6	4233	WCDMA850	22.37	22.32	Left	Cheek/Touch	Intenna	Standard	-0.014	0.974
836.6	4183	WCDMA850	22.34	22.31	Left	Ear/Tilt 15°	Intenna	Standard	-0.054	0.546
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

Table 8.10 WCDMA850 Body SAR Results

Frequency		Mode	Conducted Power		Separation Distance	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
836.6	4183	WCDMA850	22.34	22.34	1.5cm	Back	Intenna	Standard	-0.034	0.538
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	26 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Table 8.11 WCDMA1900 Head SAR Results

Frequency		Mode	Conducted		Side	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
1880	9400	WCDMA1900	22.14	22.15	Right	Cheek/Touch	Intenna	Standard	0.063	0.702
1880	9400	WCDMA1900	22.13	22.16	Right	Ear/Tilt 15°	Intenna	Standard	-0.144	0.102
1880	9400	WCDMA1900	22.15	22.13	Left	Cheek/Touch	Intenna	Standard	-0.098	0.505
1880	9400	WCDMA1900	22.11	22.13	Left	Ear/Tilt 15°	Intenna	Standard	-0.161	0.101
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

Table 8.12 WCDMA1900 Body SAR Results

Frequency		Mode	Conducted		Separation Distance	Test Position	Antenna Type	Battery	Drift (dB)	SAR Level (W/kg)
MHz	Ch		Start	End						
1880	9400	WCDMA1900	22.12	22.11	1.5cm	Back	Intenna	Standard	0.066	0.679
ANSI / IEEE C95.1 1992 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure / General Population						1.6W/kg (mW/g) averaged over 1 gram				

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	27 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

8.2 SAR Note

General Note :

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [June 2001].
2. Tissue parameters and temperatures are listed on the SAR plot.
3. Liquid tissue depth is $15.2 \pm 0.2\text{cm}$
4. Battery is fully charged for all readings. The Standard battery was used.
5. Test Configuration ☐ With Holster ☒ Without Holster
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June, 2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15mm was tested because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.

GSM Notes

1. Justification for reduced test configurations per KDB Publication 941225 D03: The source-based time-averaged output power was evaluated for all multi-slot operations. In addition to the worst-case reported, all source-based time-averaged powers within 10% of the worst-case were additionally included in the evaluation for data modes.

WCDMA Notes

1. WCDMA mode in Body SAR was tested under RMC 12.2 kbps with HSDPA Inactive per KDB Publication 941225 D01. HSDPA SAR was not required since the average output power of the HSDPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2W/Kg.

- End of page -

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	28 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

8.3 Simultaneous Transmission

Refer to the FCC OET document, 'SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas' (Feb 2008)

Table 8.11 Output Power Thresholds for Unlicensed Transmitters

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P Ref	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table				

Table 8.12 Summary of SAR Evaluation Requirements for Cell phones with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: Unlicensed only - o when stand-alone 1-g SAR is not required and antenna is > 5 cm from other antennas Licensed & Unlicensed - o when the sum of the 1-g SAR is <1.6 W/kg for all simultaneous transmitting antennas - o when SAR to antenna separation ratio of simultaneous transmitting antenna pair is < 0.3
Unlicensed Transmitters	When there is no simultaneous transmission – - o output < 60/f: SAR not required - o output ≥ 60/f: stand-alone SAR required When there is simultaneous transmission – <u>Stand-alone SAR not required when</u> - o output ≤ 2.P_{Ref} and antenna is > 5.0 cm from other antennas - o output ≤ P_{Ref} and antenna is ≥ 2.5 cm from other antennas - o output ≤ P_{Ref} and antenna is < 2.5 cm from other antennas, each with either output power ≤ P_{Ref} or 1-g SAR < 1.2 W/kg <u>Otherwise stand-alone SAR is required</u> When stand-alone SAR is required - o test SAR on highest output channel for each wireless mode and exposure condition - o if SAR for highest output channel is > 50% of SAR limit, evaluate all channels according to normal procedures	SAR required: Licensed & Unlicensed antenna pairs with SAR to antenna separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in standalone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	29 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Multiple Antenna/Transmission Information for GT-E3300L

The separation between the main antenna and the Bluetooth antennas is 32mm.

RF average conducted power of Bluetooth Tx is 3.52 dBm

Per KDB Publication 648474, Bluetooth SAR was not required based on the maximum conducted power, the Bluetooth/WLAN to main antenna separation distance and Body-SAR of the main antenna.

Simultaneous Transmission Conclusion

The above numerical summed SAR was below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit. Therefore, no volumetric SAR summation is required since the numerical sums are below the limit

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	30 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

9. CONCLUSION

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

The highest reported SAR values are as follows:

GSM850: Head: 1.01W/Kg : Body: 0.584W/Kg

GSM1900: Head: 0.597W/Kg : Body: 0.179W/Kg

WCDMA850: Head: 1.07W/Kg : Body: 0.538W/Kg

WCDMA1900: Head: 0.702W/Kg : Body: 0.679W/Kg

- End of page –

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	31 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

10. REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, June 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [16] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	32 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.

- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Measurement Procedures for 3G Devices KDB 941225
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB 248227
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB 648474
- [29] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, KDB 450824
- [30] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, KDB 616217
- [31] FCC SAR Measurement Requirements for 3 – 6 GHz, KDB 865664
- [32] FCC Mobile Portable RF Exposure Procedure, KDB 447498
- [33] FCC SAR Procedures for Dongle Transmitters, KDB 447498
- [34] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [35] FCC SAR Test Considerations for LTE Handsets and Data Modems, KDB Publication 941225
- [36] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.
- [37] FCC Hot Spot SAR v01, KDB Publication 941225 D06.

FCC ID: A3LGTE3300L	Report Number: FJ-148-S1		Page :	33 of 33
 SAMSUNG Electronics Co. LTD	EUT Type:	850/1900 GSM/GPRS/WCDMA/HSDPA Mobile Phone with Bluetooth	Issue Date :	Jun.15, 2012

APPENDIX A

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (p). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig.

A.1) .

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{p dv} \right)$$

Figure A.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \sigma E^2 / p$$

Where :

- σ = conductivity of the tissue-simulant material (S/m)
- p = mass density of the tissue-simulant material (kg/m³)
- E = Total RMS electric field strength (V/m)

Note: The primary factors that control rate or energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

- End of page -

APPENDIX B

Probe Calibration Process

Dosimetric Assessment Procedure

Each probe is calibrated according to a dosimetric assessment procedure described in **K. Pokovic, T.Schmid, N. Kuster, *Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies*, ICECOM97, Oct. 1997, pp. 120-124** with an accuracy better than +/-10%. The spherical isotropy was evaluated with the procedure described in **K. Pokovic, T.Schmid, N. Kuster, *E-field Probe with improved isotropy in brain simulating liquids*, Proceedings of the ELMAR, Zadar, June 23-25, 1996, pp. 172-175** and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz (see Fig. B.1), and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe (see Fig. B.2).

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds)

C = heat capacity of tissue (brain or muscle).

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;

$$SAR = \frac{|E|^2 \cdot \sigma}{p}$$

where:

σ = simulated tissue conductivity

p = Tissue density (1.25 g/cm³ for brain tissue)




Figure B.1. E-Field and Temperature measurements at 900MHz




Figure B.2. E-Field and temperature measurements at 1.9GHz

APPENDIX C

ANSI/IEEE C95.1 – 1992 RF EXPOSURE LIMITS

Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is the exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table C.1 Safety Limits for Partial Body Exposure

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL PEAK SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

APPENDIX D

The Validation Measurements

DUT: Dipole 835 MHz; Serial: 4d111

Program Name: 835MHz Dipole Validation 2012.05.30

Procedure Name: 835MHz @ 250mW

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.93$ mho/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

835MHz @ 250mW/Area Scan (51x51x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 2.54 mW/g


835MHz @ 250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.5 V/m; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 3.57 W/kg

SAR(1 g) = 2.38 mW/g; SAR(10 g) = 1.55 mW/g

Maximum value of SAR (measured) = 2.58 mW/g



0 dB = 2.58mW/g

DUT: Dipole 835 MHz; Serial: 4d111

Program Name: 835MHz Dipole Validation 2012.05.30

Procedure Name: 835MHz @ 250mW

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 56.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

835MHz @ 250mW/Area Scan (51x51x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 2.69 mW/g


835MHz @ 250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 50.8 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 3.57 W/kg

SAR(1 g) = 2.4 mW/g; SAR(10 g) = 1.57 mW/g

Maximum value of SAR (measured) = 2.60 mW/g



0 dB = 2.60mW/g

DUT: Dipole 1900 MHz; Serial: 5d023

Program Name: 1900MHz Dipole Validation 2012.05.29

Procedure Name: 1900MHz @ 100mW

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

1900MHz @ 100mW/Area Scan (51x51x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 5.26 mW/g


1900MHz @ 100mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 45.4 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 7.36 W/kg

SAR(1 g) = 4.03 mW/g; SAR(10 g) = 2.11 mW/g

Maximum value of SAR (measured) = 4.51 mW/g



0 dB = 4.51mW/g

DUT: Dipole 1900 MHz; Serial: 5d023

Program Name: 1900MHz Dipole Validation 2012.05.29

Procedure Name: 1900MHz @ 100mW

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

1900MHz @ 100mW/Area Scan (51x51x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 5.60 mW/g


1900MHz @ 100mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.8 V/m; Power Drift = -0.191 dB

Peak SAR (extrapolated) = 6.99 W/kg

SAR(1 g) = 3.96 mW/g; SAR(10 g) = 2.09 mW/g

Maximum value of SAR (measured) = 4.42 mW/g



0 dB = 4.42mW/g

APPENDIX E

Plots of The SAR Measurements

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Right (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 824.2 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 824.2 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement

grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.00 mW/g

Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 31.3 V/m ; Power Drift = 0.052 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.817 mW/g ; SAR(10 g) = 0.588 mW/g

Maximum value of SAR (measured) = 0.962 mW/g



0 dB = 0.962mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Right (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2/Area Scan (51x71x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.26 mW/g

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.8 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.719 mW/g

Maximum value of SAR (measured) = 1.18 mW/g



0 dB = 1.18mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Right (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 848.8 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 848.8$ MHz; $\sigma = 0.93$ mho/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.10 mW/g

Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 32.4 V/m; Power Drift = 0.041 dB

Peak SAR (extrapolated) = 1.20 W/kg

SAR(1 g) = 0.898 mW/g; SAR(10 g) = 0.634 mW/g

Maximum value of SAR (measured) = 1.08 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Right (Job No. : FJ-148)

Procedure Name: Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.538 mW/g

Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.8 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 0.619 W/kg

SAR(1 g) = 0.466 mW/g; SAR(10 g) = 0.335 mW/g

Maximum value of SAR (measured) = 0.545 mW/g



0 dB = 0.545mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Left (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 824.2 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 824.2 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.929 mW/g

Cheek/Touch, Ch.128, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 28.7 V/m; Power Drift = 0.004 dB

Peak SAR (extrapolated) = 0.944 W/kg

SAR(1 g) = 0.731 mW/g; SAR(10 g) = 0.525 mW/g

Maximum value of SAR (measured) = 0.852 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Left (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.07 mW/g

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 31.2 V/m ; Power Drift = -0.070 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.814 mW/g ; SAR(10 g) = 0.582 mW/g

Maximum value of SAR (measured) = 0.957 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Left (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 848.8 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 848.8 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.08 mW/g

Cheek/Touch, Ch.251, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 30.6 V/m; Power Drift = 0.028 dB

Peak SAR (extrapolated) = 1.09 W/kg

SAR(1 g) = 0.835 mW/g; SAR(10 g) = 0.596 mW/g

Maximum value of SAR (measured) = 0.986 mW/g



0 dB = 0.986mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Left (Job No. : FJ-148)

Procedure Name: Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 836.6$ MHz; $\sigma = 0.93$ mho/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.456 mW/g

Ear/Tilt, Ch.190, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.0 V/m; Power Drift = 0.014 dB

Peak SAR (extrapolated) = 0.555 W/kg

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.303 mW/g

Maximum value of SAR (measured) = 0.445 mW/g



0 dB = 0.445mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM850 Right (Job No. : FJ-148)

Procedure Name: Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: GSM 850; Frequency: 836.6 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2/Area Scan (51x71x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.26 mW/g

Cheek/Touch, Ch.190, Ant.Intenna, Bat.Standard 2/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.8 V/m; Power Drift = -0.030 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.719 mW/g

Maximum value of SAR (measured) = 1.18 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 2Tx, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: GPRS 850; Frequency: 836.6 MHz;Duty Cycle: 1:4.15

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.1$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 2Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.757 mW/g

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 2Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.6 V/m; Power Drift = -0.074 dB

Peak SAR (extrapolated) = 0.801 W/kg

SAR(1 g) = 0.580 mW/g; SAR(10 g) = 0.406 mW/g

Maximum value of SAR (measured) = 0.693 mW/g



0 dB = 0.693mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 3Tx, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: GPRS 850; Frequency: 836.6 MHz;Duty Cycle: 1:2.767

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.1$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 3Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.858 mW/g

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 3Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.2 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 0.765 W/kg

SAR(1 g) = 0.562 mW/g; SAR(10 g) = 0.395 mW/g

Maximum value of SAR (measured) = 0.668 mW/g



0 dB = 0.668mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: GPRS 850; Frequency: 836.6 MHz;Duty Cycle: 1:2.075

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 56.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm/Area Scan (51x71x1):

Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.772 mW/g

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.7 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.808 W/kg

SAR(1 g) = 0.584 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.699 mW/g



0 dB = 0.699mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: GPRS 850; Frequency: 836.6 MHz;Duty Cycle: 1:2.075

Medium parameters used: $f = 836.6$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 56.1$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.772 mW/g

Body, Ch. 190, Ant. Intenna, Bat. Standard, Back, 4Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.7 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 0.808 W/kg

SAR(1 g) = 0.584 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.699 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM1900 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.661, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: GSM 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.758 mW/g

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.897 W/kg

SAR(1 g) = 0.597 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.755 mW/g



0 dB = 0.755mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM1900 Right (Job No. : FJ-148)

Procedure Name: Tilt, Ch.661, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: GSM 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.661, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.137 mW/g

Tilt, Ch.661, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.59 V/m; Power Drift = 0.005 dB

Peak SAR (extrapolated) = 0.143 W/kg

SAR(1 g) = 0.095 mW/g; SAR(10 g) = 0.059 mW/g

Maximum value of SAR (measured) = 0.118 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM1900 Left (Job No. : FJ-148)

Procedure Name: Cheek, Ch.661, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: GSM 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.466 mW/g

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.625 W/kg

SAR(1 g) = 0.420 mW/g; SAR(10 g) = 0.251 mW/g

Maximum value of SAR (measured) = 0.522 mW/g



0 dB = 0.522mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM1900 Left (Job No. : FJ-148)

Procedure Name: Tilt, Ch.661, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: GSM 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.661, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.154 mW/g

Tilt, Ch.661, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.31 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.174 W/kg

SAR(1 g) = 0.114 mW/g; SAR(10 g) = 0.071 mW/g

Maximum value of SAR (measured) = 0.144 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GSM1900 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.661, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: GSM 1900; Frequency: 1880 MHz;Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.758 mW/g

Cheek, Ch.661, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.897 W/kg

SAR(1 g) = 0.597 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.755 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: Body GPRS ; Frequency: 1880 MHz;Duty Cycle: 1:4.15

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.54 \text{ mho/m}$; $\epsilon_r = 51.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm/Area Scan (51x71x1):

Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.271 mW/g

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.0 V/m ; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.275 W/kg

SAR(1 g) = 0.179 mW/g ; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.228 mW/g



0 dB = 0.228 mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 3Tx, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: Body GPRS ; Frequency: 1880 MHz;Duty Cycle: 1:2.767

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 3Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.185 mW/g

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 3Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.89 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 0.182 W/kg

SAR(1 g) = 0.124 mW/g; SAR(10 g) = 0.071 mW/g

Maximum value of SAR (measured) = 0.156 mW/g



0 dB = 0.156mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 4Tx, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: Body GPRS ; Frequency: 1880 MHz;Duty Cycle: 1:2.075

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 4Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.196 mW/g

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 4Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.2 V/m; Power Drift = 0.010 dB

Peak SAR (extrapolated) = 0.203 W/kg

SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.078 mW/g

Maximum value of SAR (measured) = 0.167 mW/g



0 dB = 0.167mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L GPRS1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: Body GPRS ; Frequency: 1880 MHz;Duty Cycle: 1:4.15

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm/Area Scan (51x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.271 mW/g

Body, Ch.661, Ant.Intenna, Bat.Standard, Back, 2Tx, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.275 W/kg

SAR(1 g) = 0.179 mW/g; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.228 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4132, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 826.4 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 826.4 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4132, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.19 mW/g

Cheek, Ch.4132, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.8 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.959 mW/g; SAR(10 g) = 0.688 mW/g

Maximum value of SAR (measured) = 1.11 mW/g



0 dB = 1.11mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4183, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4183, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.23 mW/g

Cheek, Ch.4183, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 35.0 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.995 mW/g; SAR(10 g) = 0.712 mW/g

Maximum value of SAR (measured) = 1.17 mW/g



0 dB = 1.17mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4233, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 846.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 846.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.34 mW/g

Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 37.2 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.763 mW/g

Maximum value of SAR (measured) = 1.26 mW/g



0 dB = 1.26mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Right (Job No. : FJ-148)

Procedure Name: Tilt, Ch.4183, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6$ MHz; $\sigma = 0.93$ mho/m; $\epsilon_r = 42.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.4183, Ant.Intenna, Bat.Standard/Area Scan (41x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.617 mW/g

Tilt, Ch.4183, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = 0.005 dB

Peak SAR (extrapolated) = 0.695 W/kg

SAR(1 g) = 0.527 mW/g; SAR(10 g) = 0.381 mW/g

Maximum value of SAR (measured) = 0.616 mW/g



0 dB = 0.616mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Left (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4132, Ant.Intenna, Bat.Standard 2

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 826.4 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 826.4 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4132, Ant.Intenna, Bat.Standard 2/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.18 mW/g

Cheek, Ch.4132, Ant.Intenna, Bat.Standard 2/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.8 V/m; Power Drift = -0.042 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.917 mW/g; SAR(10 g) = 0.651 mW/g

Maximum value of SAR (measured) = 1.09 mW/g



0 dB = 1.09mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Left (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4183, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4183, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.39 mW/g

Cheek, Ch.4183, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.9 V/m; Power Drift = -0.039 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.760 mW/g

Maximum value of SAR (measured) = 1.28 mW/g



0 dB = 1.28mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Left (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4233, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 846.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 846.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.26 mW/g

Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 34.2 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.974 mW/g; SAR(10 g) = 0.687 mW/g

Maximum value of SAR (measured) = 1.17 mW/g



0 dB = 1.17mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Left (Job No. : FJ-148)

Procedure Name: Tilt, Ch.4183, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.4183, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.674 mW/g

Tilt, Ch.4183, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


$dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.6 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 0.724 W/kg

SAR(1 g) = 0.546 mW/g; SAR(10 g) = 0.395 mW/g

Maximum value of SAR (measured) = 0.641 mW/g



0 dB = 0.641mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.4233, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.1;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 846.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 846.6 \text{ MHz}$; $\sigma = 0.93 \text{ mho/m}$; $\epsilon_r = 42.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.62, 9.62, 9.62); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1248
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.34 mW/g


Cheek, Ch.4233, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 37.2 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.763 mW/g

Maximum value of SAR (measured) = 1.26 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 56.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm/Area Scan (51x71x1):

Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.651 mW/g

Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.3 V/m ; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 0.728 W/kg

SAR(1 g) = 0.538 mW/g ; SAR(10 g) = 0.380 mW/g

Maximum value of SAR (measured) = 0.638 mW/g



0 dB = 0.638 mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA850 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm

Meas. Ambient Temp(celsius)-22.3,Tissue Temp(celsius)-22.0;Test Date-30/May/2012

Communication System: WCDMA850; Frequency: 836.6 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 836.6 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 56.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(9.72, 9.72, 9.72); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm/Area Scan (51x71x1):

Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.651 mW/g

Body, Ch. 4183, Ant. Intenna, Bat. Standard, Back, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.3 V/m; Power Drift = -0.034 dB

Peak SAR (extrapolated) = 0.728 W/kg

SAR(1 g) = 0.538 mW/g; SAR(10 g) = 0.380 mW/g

Maximum value of SAR (measured) = 0.638 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3/Area Scan (41x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.794 mW/g

Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.2 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.702 mW/g; SAR(10 g) = 0.399 mW/g

Maximum value of SAR (measured) = 0.879 mW/g



0 dB = 0.879mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Right (Job No. : FJ-148)

Procedure Name: Tilt, Ch.9400, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.9400, Ant.Intenna, Bat.Standard/Area Scan (41x81x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.150 mW/g

Tilt, Ch.9400, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.64 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 0.155 W/kg

SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.063 mW/g

Maximum value of SAR (measured) = 0.130 mW/g



0 dB = 0.130mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Left (Job No. : FJ-148)

Procedure Name: Cheek, Ch.9400, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.9400, Ant.Intenna, Bat.Standard/Area Scan (41x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.551 mW/g

Cheek, Ch.9400, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = -0.098 dB

Peak SAR (extrapolated) = 0.757 W/kg

SAR(1 g) = 0.505 mW/g; SAR(10 g) = 0.301 mW/g

Maximum value of SAR (measured) = 0.607 mW/g



0 dB = 0.607mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Left (Job No. : FJ-148)

Procedure Name: Tilt, Ch.9400, Ant.Intenna, Bat.Standard

Meas. Ambient Temp(celsius)-22.6;Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Tilt, Ch.9400, Ant.Intenna, Bat.Standard/Area Scan (41x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.141 mW/g

Tilt, Ch.9400, Ant.Intenna, Bat.Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.07 V/m; Power Drift = -0.161 dB

Peak SAR (extrapolated) = 0.154 W/kg

SAR(1 g) = 0.101 mW/g; SAR(10 g) = 0.063 mW/g

Maximum value of SAR (measured) = 0.130 mW/g



0 dB = 0.130mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Right (Job No. : FJ-148)

Procedure Name: Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3

Meas. Ambient Temp(celsius)-22.6,Tissue Temp(celsius)-22.4;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.54, 8.54, 8.54); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1247
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3/Area Scan (41x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.794 mW/g

Cheek, Ch.9400, Ant.Intenna, Bat.Standard 3/Zoom Scan (5x5x7)/Cube 0: Measurement


grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.2 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.702 mW/g; SAR(10 g) = 0.399 mW/g

Maximum value of SAR (measured) = 0.879 mW/g



DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm/Area Scan (41x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.658 mW/g

Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.679 mW/g; SAR(10 g) = 0.416 mW/g

Maximum value of SAR (measured) = 0.867 mW/g



0 dB = 0.867mW/g

DUT: GT-E3300L; Serial: FJ-148-C

Program Name: GT-E3300L WCDMA1900 Body (Job No. : FJ-148)

Procedure Name: Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm

Meas. Ambient Temp(celsius)-22.4,Tissue Temp(celsius)-22.2;Test Date-29/May/2012

Communication System: WCDMA1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3520; ConvF(8.19, 8.19, 8.19); Calibrated: 2012-02-21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn533; Calibrated: 2011-09-21
- Phantom: Triple Flat Phantom 5.1; Type: Triple Flat Phantom 5.1; Serial: 1003
- Measurement SW: DASY5, V5.0 Build 125; Postprocessing SW: SEMCAD, V13.4 Build 125

Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm/Area Scan (41x71x1):

Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.658 mW/g

Body, Ch. 9400, Ant. Intenna, Bat. Standard Back, 15mm/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.679 mW/g; SAR(10 g) = 0.416 mW/g

Maximum value of SAR (measured) = 0.867 mW/g



APPENDIX F

Probe Calibration



SCS

Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 108

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Samsung (Dymstec)**

Certificate No: **EX3-3520_Mar11**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3520**

Calibration procedure(s) **QA CAL-01.v7, QA CAL-23.v4, QA CAL-25.v3
Calibration procedure for dosimetric E-field probes**

Calibration date: **March 22, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	01-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	01-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	01-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	29-Dec-10 (No. ES3-3013_Dec10)	Dec-11
DAE4	SN: 654	23-Apr-10 (No. DAE4-654_Apr10)	Apr-11
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-10)	In house check: Oct-11

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature
			Issued: March 23, 2011
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 108

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}:** Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}** are numerical linearization parameters in dB assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media.
- VR:** VR is the validity range of the calibration related to the average diode voltage or DAE voltage in mV.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe EX3DV4

SN:3520

Manufactured: March 8, 2004
Calibrated: March 22, 2011

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3520

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.73	0.68	0.66	$\pm 10.1 \%$
DCP (mV) ^B	98.0	101.4	100.7	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dB	C dB	VR mV	Unc ^E (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	107.7	$\pm 2.2 \%$
			Y	0.00	0.00	1.00	136.8	
			Z	0.00	0.00	1.00	108.5	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter; uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY – Parameters of Probe: EX3DV4 – SN:3520

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Uct. (k=2)
850	41.5	0.92	9.52	9.52	9.52	0.63	0.71	± 12.0 %
1750	40.1	1.37	8.25	8.25	8.25	0.78	0.58	± 12.0 %
1900	40.0	1.40	8.07	8.07	8.07	0.80	0.56	± 12.0 %
2300	39.5	1.67	7.61	7.61	7.61	0.75	0.56	± 12.0 %
2450	39.2	1.80	7.25	7.25	7.25	0.80	0.55	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

DASY/EASY - Parameters of Probe: EX3DV4- SN:3520


Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
850	55.2	0.99	9.49	9.49	9.49	0.67	0.72	± 12.0 %
1750	53.4	1.49	8.75	8.75	8.75	0.61	0.76	± 12.0 %
1900	53.3	1.52	8.33	8.33	8.33	0.62	0.72	± 12.0 %
2300	52.9	1.81	7.91	7.91	7.91	0.66	0.66	± 12.0 %
2450	52.7	1.95	7.43	7.43	7.43	0.80	0.56	± 12.0 %

^C Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)


Dynamic Range f(SAR_{head})

(TEM cell, f = 900 MHz)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: EX3DV4 - SN:3520**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm

APPENDIX G

Calibration of The Validation Dipole



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **Samsung (Dymstec)**

Certificate No: **D835V2-4d111_Nov11**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d111**

Calibration procedure(s) **QA CAL-05.v8**
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **November 18, 2011**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	05-Oct-11 (No. 217-01451)	Oct-12
Power sensor HP 8481A	US37292783	05-Oct-11 (No. 217-01451)	Oct-12
Reference 20 dB Attenuator	SN: 5086 (20g)	29-Mar-11 (No. 217-01368)	Apr-12
Type-N mismatch combination	SN: 5047.2 / 06327	29-Mar-11 (No. 217-01371)	Apr-12
Reference Probe ES3DV3	SN: 3205	29-Apr-11 (No. ES3-3205_Apr11)	Apr-12
DAE4	SN: 601	04-Jul-11 (No. DAE4-601_Jul11)	Jul-12
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

	Name	Function	Signature
Calibrated by:	Dimce Iliev	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: November 18, 2011

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.6.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.4 $\pm$ 6 %	0.90 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.36 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	9.43 mW /g $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.55 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	6.20 mW /g $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.3 $\pm$ 6 %	0.99 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.44 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	9.54 mW / g $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	1.60 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	6.29 mW / g $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.2 Ω - 3.1 j Ω
Return Loss	- 28.6 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.1 Ω - 4.7 j Ω
Return Loss	- 25.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.399 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	May 26, 2010

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d111

Communication System: CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.9$ mho/m; $\epsilon_r = 41.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.07, 6.07, 6.07); Calibrated: 29.04.2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.6.2(482); SEMCAD X 14.4.5(3634)

Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.200 V/m; Power Drift = 0.0057 dB


Peak SAR (extrapolated) = 3.474 W/kg

SAR(1 g) = 2.36 mW/g; SAR(10 g) = 1.55 mW/g

Maximum value of SAR (measured) = 2.755 mW/g



Impedance Measurement Plot for Head TSL



Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d111

Communication System: CW; Frequency: 835 MHz

Medium parameters used: $f = 835$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(6.02, 6.02, 6.02); Calibrated: 29.04.2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA; Serial: 1001
- DASY52 52.6.2(482); SEMCAD X 14.4.5(3634)

Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.351 V/m; Power Drift = 0.009 dB


Peak SAR (extrapolated) = 3.538 W/kg

SAR(1 g) = 2.44 mW/g; SAR(10 g) = 1.6 mW/g

Maximum value of SAR (measured) = 2.821 mW/g



Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **Samsung (Dymstec)**

Certificate No: **D1900V2-5d023_Jan12**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d023**

Calibration procedure(s) **QA CAL-05.v8**
 Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **January 26, 2012**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	05-Oct-11 (No. 217-01451)	Oct-12
Power sensor HP 8481A	US37292783	05-Oct-11 (No. 217-01451)	Oct-12
Reference 20 dB Attenuator	SN: 5086 (20g)	29-Mar-11 (No. 217-01368)	Apr-12
Type-N mismatch combination	SN: 5047.2 / 06327	29-Mar-11 (No. 217-01371)	Apr-12
Reference Probe ES3DV3	SN: 3205	30-Dec-11 (No. ES3-3205_Dec11)	Dec-12
DAE4	SN: 601	04-Jul-11 (No. DAE4-601_Jul11)	Jul-12

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-11)	In house check: Oct-12

	Name	Function	Signature
Calibrated by:	Dimce Iliev	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 26, 2012

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.8 $\pm$ 6 %	1.39 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.66 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	39.0 mW / g $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.07 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	20.4 mW / g $\pm$ 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	52.9 $\pm$ 6 %	1.52 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.72 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	38.8 mW / g $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.10 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	20.4 mW / g $\pm$ 16.5 % (k=2)

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$48.9 \Omega + 8.1 j\Omega$
Return Loss	- 21.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$45.3 \Omega + 8.2 j\Omega$
Return Loss	- 20.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.203 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	March 28, 2008

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d023

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.841 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 17.2900


SAR(1 g) = 9.66 mW/g; SAR(10 g) = 5.07 mW/g

Maximum value of SAR (measured) = 11.991 mW/g



0 dB = 11.990mW/g = 21.58 dB mW/g

Impedance Measurement Plot for Head TSL



Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d023

Communication System: CW; Frequency: 1900 MHz

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.62, 4.62, 4.62); Calibrated: 30.12.2011
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.07.2011
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.0(692); SEMCAD X 14.6.4(4989)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.052 V/m; Power Drift = -6.9e-005 dB

Peak SAR (extrapolated) = 17.0640

SAR(1 g) = 9.72 mW/g; SAR(10 g) = 5.1 mW/g

Maximum value of SAR (measured) = 12.349 mW/g



0 dB = 12.350mW/g = 21.83 dB mW/g

Impedance Measurement Plot for Body TSL

