



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

http://www.pctestlab.com



## MEASUREMENT REPORT FCC Part 22 & 24 / IC RSS-132/RSS-133

**Applicant Name:**

Samsung Electronics, Co. Ltd.  
18600 Broadwick St.  
Rancho Dominguez, CA 90220  
United States

**Date of Testing:**

June 2, 2010

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0Y1005270902.A3L

**FCC ID:**

**A3LGTI5800**

**APPLICANT:**

**SAMSUNG ELECTRONICS, CO. LTD.**

**Application Type:**

Certification

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§2; §22(H), §24(E)

**IC Specification(s):**

RSS-132 Issue 2; RSS-133 Issue 5

**EUT Type:**

850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN

**Model(s):**

GT-I5800

**Tx Frequency Range:**

824.20 - 848.80MHz (Cell. GSM) / 1850.20 - 1909.80MHz (PCS GSM)

**Max. RF Output Power:**

1.023 W ERP Cell. GSM (30.1 dBm) / 1.288 W EIRP PCS GSM (31.1 dBm)

0.55 W ERP EDGE850 (27.4 dBm) / 0.646 W EIRP EDGE1900 (28.1 dBm)

**Emission Designator(s):**

243KGXW (Cellular GSM), 244KGXW (PCS GSM) /  
244KG7W (EDGE850), 245KG7W (EDGE1900)

**Test Device Serial No.:**

*identical prototype* [S/N: FH-016-C]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is ERP for Part 22 and EIRP for Part 24.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President



|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 1 of 36                    |

# TABLE OF CONTENTS

|                                                               |    |
|---------------------------------------------------------------|----|
| FCC PART 22 & 24 MEASUREMENT REPORT.....                      | 3  |
| 1.0 INTRODUCTION .....                                        | 4  |
| 1.1 SCOPE.....                                                | 4  |
| 1.2 TESTING FACILITY.....                                     | 4  |
| 2.0 PRODUCT INFORMATION.....                                  | 5  |
| 2.1 EQUIPMENT DESCRIPTION .....                               | 5  |
| 2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....             | 5  |
| 2.3 LABELING REQUIREMENTS.....                                | 5  |
| 3.0 DESCRIPTION OF TESTS .....                                | 6  |
| 3.1 MEASUREMENT PROCEDURE.....                                | 6  |
| 3.2 OCCUPIED BANDWIDTH .....                                  | 6  |
| 3.3 CELLULAR - BASE FREQUENCY BLOCKS .....                    | 6  |
| 3.4 CELLULAR - MOBILE FREQUENCY BLOCKS .....                  | 7  |
| 3.5 PCS - BASE FREQUENCY BLOCKS.....                          | 7  |
| 3.6 PCS - MOBILE FREQUENCY BLOCKS .....                       | 7  |
| 3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL ..... | 7  |
| 3.8 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....      | 8  |
| 3.9 PEAK-AVERAGE RATIO .....                                  | 8  |
| 3.10 FREQUENCY STABILITY / TEMPERATURE VARIATION .....        | 8  |
| 4.0 TEST EQUIPMENT CALIBRATION DATA .....                     | 9  |
| 5.0 SAMPLE CALCULATIONS .....                                 | 10 |
| 6.0 TEST RESULTS .....                                        | 11 |
| 6.1 SUMMARY .....                                             | 11 |
| 6.2 EFFECTIVE RADIATED POWER OUTPUT DATA.....                 | 12 |
| 6.3 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA.....      | 13 |
| 6.4 CELLULAR GSM RADIATED MEASUREMENTS .....                  | 14 |
| 6.5 PCS GSM RADIATED MEASUREMENTS .....                       | 17 |
| 6.6 CELLULAR GSM FREQUENCY STABILITY MEASUREMENTS .....       | 20 |
| 6.7 PCS GSM FREQUENCY STABILITY MEASUREMENTS .....            | 22 |
| 6.8 RECEIVER SPURIOUS EMISSIONS.....                          | 24 |
| 7.0 PLOTS OF EMISSIONS .....                                  | 25 |
| 8.0 CONCLUSION .....                                          | 36 |

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGT15800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 2 of 36                    |



## MEASUREMENT REPORT

### FCC Part 22 & 24



#### §2.1033 General Information

**APPLICANT:** Samsung Electronics, Co. Ltd.  
**APPLICANT ADDRESS:** 18600 Broadwick St.  
 Rancho Dominguez, CA 90220, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22(H), §24(E)  
**IC SPECIFICATION(S):** RSS-132 Issue 2; RSS-133 Issue 5  
**BASE MODEL :** GT-I5800  
**FCC ID:** A3LGTI5800  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**EMISSION DESIGNATOR(S):** 243KGXW (Cellular GSM), 244KGXW (PCS GSM)  
 244KG7W (EDGE850), 245KG7W (EDGE1900)  
**MODE:** GSM / EDGE  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** FH-016-C ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** June 2, 2010  
**TEST REPORT S/N:** 0Y1005270902.A3L

#### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 3 of 36                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 4 of 36                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung 850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN FCC ID: A3LGTI5800**. The EUT consisted of the following component(s):

| Trade Name / Base Model   | FCC ID     | Description                                          |
|---------------------------|------------|------------------------------------------------------|
| Samsung / Model: GT-I5800 | A3LGTI5800 | 850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |

Table 2-1. EUT Equipment Description

### 2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).


Please see attachment for FCC ID label and label location.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 5 of 36                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3 meter test range (See Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure 3-1. Diagram of 3-meter outdoor test range**


**Deviation from Measurement Procedure.....None**

### 3.2 Occupied Bandwidth

**§2.1049, RSS-Gen (4.6.1)**


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

### 3.3 Cellular - Base Frequency Blocks




|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT15800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 6 of 36                    |


### 3.4 Cellular - Mobile Frequency Blocks



### 3.5 PCS - Base Frequency Blocks



### 3.6 PCS - Mobile Frequency Blocks



### 3.7 Spurious and Harmonic Emissions at Antenna Terminal

2.1051, 22.917(a), 24.238(a)(b); RSS-132 (4.5.1), RSS-133 (6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 7 of 36                    |

### 3.8 Radiated Power and Radiated Spurious Emissions

§2.1053, 22.913(a)(2), 22.917(a), 24.232(c), 24.238(a); RSS-132 (4.5.1), RSS-133 (6.5.1)

Radiated power and radiated spurious emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band.

### 3.9 Peak-Average Ratio

§24.232(d); RSS-133 (6.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth.

### 3.10 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235; RSS-132 (4.3) / RSS-133 (6.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.*

#### Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 8 of 36                    |

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer    | Model     | Description                        | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------|-----------|------------------------------------|------------|--------------|------------|---------------|
| -               | 263-10dB  | (DC-18GHz) 10 dB Attenuator        | N/A        |              | N/A        | N/A           |
| -               | No.166    | (1000-26500MHz) Microwave RF Cable | N/A        |              | N/A        | N/A           |
| -               | No.167    | (100kHz - 100MHz) RG58 Coax Cable  | N/A        |              | N/A        | N/A           |
| Agilent         | 11713A    | Attenuation/Switch Driver          | 12/2/2009  | Annual       | 12/2/2010  | 3439A02645    |
| Agilent         | 8449B     | (1-26.5GHz) Pre-Amplifier          | 12/2/2009  | Annual       | 12/2/2010  | 3008A00985    |
| Agilent         | 8495A     | (0-70dB) DC-4GHz Attenuator        | N/A        |              | N/A        | N/A           |
| Agilent         | 85650A    | Quasi-Peak Adapter                 | 12/2/2009  | Annual       | 12/2/2010  | 3303A01872    |
| Agilent         | 8566B     | (100Hz-22GHz) Spectrum Analyzer    | 12/2/2009  | Annual       | 12/2/2010  | 3638A08713    |
| Agilent         | 8648D     | (9kHz-4GHz) Signal Generator       | 9/19/2009  | Biennial     | 9/19/2011  | 3613A00315    |
| Agilent         | E4407B    | ESA Spectrum Analyzer              | 9/28/2009  | Annual       | 9/28/2010  | US39210313    |
| Agilent         | E4432B    | ESG-D Series Signal Generator      | 9/10/2009  | Annual       | 9/10/2010  | US40053896    |
| Agilent         | E4448A    | PSA (3Hz-50GHz) Spectrum Analyzer  | 10/1/2009  | Annual       | 10/1/2010  | US42510244    |
| Agilent         | E5515C    | Wireless Communications Test Set   | 9/10/2009  | Annual       | 9/10/2010  | GB46110872    |
| Agilent         | E5515C    | Wireless Communications Test Set   | 9/11/2009  | Annual       | 9/11/2010  | GB46310798    |
| Agilent         | E5515C    | Wireless Communications Test Set   | 8/25/2009  | Annual       | 8/25/2010  | GB41450275    |
| Agilent         | E8267C    | Vector Signal Generator            | 9/29/2009  | Biennial     | 9/29/2011  | US42340152    |
| Agilent         | N9020A    | MXA Signal Analyzer                | 10/22/2009 | Annual       | 10/22/2010 | US46470561    |
| Anritsu         | ML2495A   | Power Meter                        | 10/12/2009 | Annual       | 10/12/2010 | 941001        |
| Emco            | 3115      | Horn Antenna (1-18GHz)             | 10/14/2009 | Biennial     | 10/14/2011 | 9704-5182     |
| Gigatronics     | 80701A    | (0.05-18GHz) Power Sensor          | 9/9/2009   | Annual       | 9/9/2010   | 1833460       |
| Gigatronics     | 8651A     | Universal Power Meter              | 9/9/2009   | Annual       | 9/9/2010   | 8650319       |
| K & L           | 11SH10    | Band Pass Filter                   | N/A        | Annual       | N/A        | 1300/4000     |
| K & L           | 11SH10    | Band Pass Filter                   | N/A        | Annual       | N/A        | 4000/12000    |
| MiniCircuits    | VHF-1300+ | High Pass Filter                   | N/A        |              | N/A        | 30716         |
| MiniCircuits    | VHF-3100+ | High Pass Filter                   | N/A        |              | N/A        | 30721         |
| Pasternack      | PE2208-6  | Bidirectional Coupler              | N/A        |              | N/A        | N/A           |
| Rohde & Schwarz | CMU200    | Base Station Simulator             | 9/11/2009  | Annual       | 9/11/2010  | 836371/0079   |
| Rohde & Schwarz | CMU200    | Base Station Simulator             | 9/4/2009   | Annual       | 9/4/2010   | 109892        |
| Rohde & Schwarz | CMU200    | Base Station Simulator             | 6/12/2009  | Annual       | 6/12/2010  | 836536/0005   |
| Rohde & Schwarz | FSQ 26    | Spectrum Analyzer                  | 9/19/2009  | Annual       | 9/19/2010  | 200452        |
| Rohde & Schwarz | CMW500    | LTE Base Station Simulator         | 8/25/2009  | Annual       | 8/25/2010  | 100976        |
| Schwarzbeck     | UHA9105   | Dipole Antenna (400 - 1GHz) Rx     | 7/17/2009  | Biennial     | 7/17/2011  | 9105-2404     |
| Schwarzbeck     | UHA9105   | Dipole Antenna (400 - 1GHz) Tx     | 7/17/2009  | Biennial     | 7/17/2011  | 9105-2403     |
| Sunol           | DRH-118   | Horn Antenna (1 - 18GHz)           | 5/14/2009  | Biennial     | 5/14/2011  | A050307       |

Table 4-1. Test Equipment

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 9 of 36                    |

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 250KGXW**

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### Spurious Radiated Emission - PCS Band

**Example: Channel 512 PCS Mode 2<sup>nd</sup> Harmonic (3700.40 MHz)**

The average receive power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 10 of 36                   |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Samsung Electronics, Co. Ltd.  
 FCC ID: A3LGTI5800  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): GSM / EDGE

| FCC Part Section(s)                    | RSS Section(s)                      | Test Description                         | Test Limit                                                                         | Test Condition | Test Result | Reference          |
|----------------------------------------|-------------------------------------|------------------------------------------|------------------------------------------------------------------------------------|----------------|-------------|--------------------|
| TRANSMITTER MODE (TX)                  |                                     |                                          |                                                                                    |                |             |                    |
| 2.1049, 22.917(a), 24.238(a)           | RSS-Gen (4.6.1)<br>RSS-133 (2.3)    | Occupied Bandwidth                       | N/A                                                                                | CONDUCTED      | PASS        | Section 7.0        |
| 2.1051, 22.917(a), 24.238(a)           | RSS-132 (4.5.1)<br>RSS-133 (6.5.1)  | Band Edge / Conducted Spurious Emissions | < 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions |                | PASS        | Section 7.0        |
| 24.232(d)                              | RSS-133 (6.4)                       | Peak-Average Ratio                       | < 13 dB                                                                            |                | PASS        | Section 7.0        |
| 2.1046                                 | RSS-132 (4.4)<br>RSS-133 (4.1)      | Transmitter Conducted Output Power       | N/A                                                                                |                | PASS        | RF Exposure Report |
| 22.913(a)(2)                           | RSS-132 (4.4)<br>[SRSP-503(5.1.3)]  | Effective Radiated Power                 | < 7 Watts max. ERP                                                                 | RADIATED       | PASS        | Section 6.2        |
| 24.232(c)                              | RSS-133 (6.4)<br>[SRSP-510 (5.1.2)] | Equivalent Isotropic Radiated Power      | < 2 Watts max. EIRP                                                                |                | PASS        | Section 6.3        |
| 2.1053, 22.917(a), 24.238(a)           | RSS-132 (4.5.1)<br>RSS-133 (6.5.1)  | Undesirable Emissions                    | < 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions                  |                | PASS        | Sections 6.4, 6.5  |
| 2.1055, 22.355, 24.235                 | RSS-132 (4.3)<br>RSS-133 (6.3)      | Frequency Stability                      | < 2.5 ppm                                                                          |                | PASS        | Sections 6.6, 6.7  |
| RECEIVER MODE (RX) / DIGITAL EMISSIONS |                                     |                                          |                                                                                    |                |             |                    |
| N/A                                    | RSS-132 (4.6)<br>RSS-133 (6.6)      | Receiver Spurious Emissions Limits       | < RSS-Gen limits [Section 6; Table 1]                                              | RADIATED       | PASS        | Section 6.8        |

**Table 6-1. Summary of Test Results**

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN | Page 11 of 36                                                                         |                                 |

## 6.2 Effective Radiated Power Output Data

§22.913(a)(2); RSS-132 (4.4) [SRSP-503(5.1.3)]

| Frequency [MHz] | Mode    | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBd] | Pol [H/V] | ERP [dBm] | ERP [Watts] | Battery Type |
|-----------------|---------|----------------------|------------------------|--------------------|-----------|-----------|-------------|--------------|
| 824.20          | GSM850  | -11.400              | 27.30                  | 0.00               | V         | 27.30     | 0.537       | Standard     |
| 836.60          | GSM850  | -8.700               | 30.00                  | 0.00               | V         | 30.00     | 1.000       | Standard     |
| 848.80          | GSM850  | -8.600               | 30.10                  | 0.00               | V         | 30.10     | 1.023       | Standard     |
| 848.80          | EDGE850 | -11.300              | 27.40                  | 0.00               | V         | 27.40     | 0.550       | Standard     |

**Table 6-2. Effective Radiated Power Output Data**

### **NOTES:**

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worse case test configuration was when the EUT was standing vertical. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 12 of 36                   |

### 6.3 Equivalent Isotropic Radiated Power Output Data

§24.232(c); RSS-133 (6.4) [SRSP-510 (5.1.2)]

| Frequency [MHz] | Mode     | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | EIRP [dBm] | EIRP [Watts] | Battery Type |
|-----------------|----------|----------------------|------------------------|--------------------|-----------|------------|--------------|--------------|
| 1850.20         | GSM1900  | -11.600              | 22.80                  | 8.00               | H         | 30.80      | 1.202        | Standard     |
| 1880.00         | GSM1900  | -12.200              | 22.20                  | 8.00               | H         | 30.20      | 1.047        | Standard     |
| 1909.80         | GSM1900  | -11.300              | 23.10                  | 8.00               | H         | 31.10      | 1.288        | Standard     |
| 1909.80         | EDGE1900 | -14.300              | 20.10                  | 8.00               | H         | 28.10      | 0.646        | Standard     |

**Table 6-3. Equivalent Isotropic Radiated Power Output Data**

#### **NOTES:**

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 13 of 36                   |

## 6.4 Cellular GSM Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 30.100 dBm = 1.023 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  43.10 dBc

| FREQUENCY<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA GAIN<br>(dBd) | SPURIOUS<br>EMISSION<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|--------------------|------------------------------------------|-------------------------------------|----------------------------------------|--------------|-------|
| 1648.40            | -59.12                                   | 6.42                                | -52.71                                 | H            | 82.8  |
| 2472.60            | -59.29                                   | 6.74                                | -52.55                                 | H            | 82.6  |
| 3296.80            | -96.88                                   | 7.55                                | -89.33                                 | H            | 119.4 |
| 4121.00            | -94.22                                   | 7.56                                | -86.67                                 | H            | 116.8 |
| 4945.20            | -94.01                                   | 9.05                                | -84.96                                 | H            | 115.1 |

**Table 6-4. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 14 of 36                   |

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MEASURED OUTPUT POWER: 30.100 dBm = 1.023 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  43.10 dBc

| FREQUENCY<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA GAIN<br>(dBd) | SPURIOUS<br>EMISSION<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|--------------------|------------------------------------------|-------------------------------------|----------------------------------------|--------------|-------|
| 1673.20            | -61.60                                   | 6.43                                | -55.17                                 | H            | 85.3  |
| 2509.80            | -59.83                                   | 6.77                                | -53.06                                 | H            | 83.2  |
| 3346.40            | -96.73                                   | 7.55                                | -89.18                                 | H            | 119.3 |
| 4183.00            | -94.50                                   | 7.81                                | -86.69                                 | H            | 116.8 |
| 5019.60            | -93.67                                   | 9.02                                | -84.65                                 | H            | 114.7 |

Table 6-5. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN | Page 15 of 36                                                                         |                                 |

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 30.100 dBm = 1.023 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  43.10 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1697.60         | -55.48                          | 6.44                          | -49.04                        | H         | 79.1  |
| 2546.40         | -58.83                          | 6.83                          | -52.00                        | H         | 82.1  |
| 3395.20         | -96.57                          | 7.55                          | -89.02                        | H         | 119.1 |
| 4244.00         | -94.76                          | 8.06                          | -86.71                        | H         | 116.8 |
| 5092.80         | -93.21                          | 8.91                          | -84.29                        | H         | 114.4 |

Table 6-6. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 16 of 36                   |

## 6.5 PCS GSM Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 31.100 dBm = 1.288 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.10 dBc

| FREQUENCY<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA GAIN<br>(dBi) | SPURIOUS<br>EMISSION<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|--------------------|------------------------------------------|-------------------------------------|----------------------------------------|--------------|-------|
| 3700.40            | -59.41                                   | 9.49                                | -49.91                                 | H            | 81.0  |
| 5550.60            | -57.28                                   | 10.41                               | -46.88                                 | H            | 78.0  |
| 7400.80            | -89.93                                   | 11.08                               | -78.85                                 | H            | 109.9 |
| 9251.00            | -88.91                                   | 12.26                               | -76.65                                 | H            | 107.8 |
| 11101.20           | -87.07                                   | 13.19                               | -73.88                                 | H            | 105.0 |

**Table 6-7. Radiated Spurious Data (PCS GSM Mode – Ch. 512)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 17 of 36                   |

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 31.100 dBm = 1.288 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.10 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3760.00         | -59.21                          | 9.43                          | -49.78                        | H         | 80.9  |
| 5640.00         | -91.57                          | 10.24                         | -81.33                        | H         | 112.4 |
| 7520.00         | -54.54                          | 11.12                         | -43.42                        | H         | 74.5  |
| 9400.00         | -89.11                          | 12.32                         | -76.78                        | H         | 107.9 |
| 11280.00        | -86.39                          | 13.17                         | -73.22                        | H         | 104.3 |

**Table 6-8. Radiated Spurious Data (PCS GSM Mode – Ch. 661)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 18 of 36                   |

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 31.100 dBm = 1.288 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 44.10$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3819.60         | -58.03                          | 9.37                          | -48.66                        | H         | 79.8  |
| 5729.40         | -91.05                          | 10.08                         | -80.98                        | H         | 112.1 |
| 7639.20         | -89.77                          | 11.21                         | -78.56                        | H         | 109.7 |
| 9549.00         | -89.15                          | 12.38                         | -76.77                        | H         | 107.9 |
| 11458.80        | -85.73                          | 13.15                         | -72.57                        | H         | 103.7 |

Table 6-9. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested in all configurations and the highest power is reported in GSM voice mode while using a Power Control Level of "5" in the Cellular band and "0" in the PCS band. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found when the EUT was lying flat. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 19 of 36                   |

## 6.6 Cellular GSM Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 3.7 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 3.70        | + 20 (Ref) | 836,599,997    | -3              | 0.000000      |
| 100 %          |             | - 30       | 836,600,009    | 9               | 0.000001      |
| 100 %          |             | - 20       | 836,600,017    | 17              | 0.000002      |
| 100 %          |             | - 10       | 836,600,019    | 19              | 0.000002      |
| 100 %          |             | 0          | 836,600,011    | 11              | 0.000001      |
| 100 %          |             | + 10       | 836,600,018    | 18              | 0.000002      |
| 100 %          |             | + 20       | 836,600,010    | 10              | 0.000001      |
| 100 %          |             | + 30       | 836,599,986    | -14             | -0.000002     |
| 100 %          |             | + 40       | 836,599,995    | -5              | -0.000001     |
| 100 %          |             | + 50       | 836,599,998    | -2              | 0.000000      |
| 115 %          | 4.26        | + 20       | 836,600,013    | 13              | 0.000002      |
| BATT. ENDPOINT | 3.40        | + 20       | 836,599,985    | -15             | -0.000002     |

Table 6-10. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

## Cellular GSM Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



**Figure 6-1. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)**

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 21 of 36                   |

## 6.7 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661


REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 3.70        | + 20 (Ref) | 1,880,000,003  | 3               | 0.000000      |
| 100 %          |             | - 30       | 1,879,999,992  | -8              | 0.000000      |
| 100 %          |             | - 20       | 1,879,999,983  | -17             | -0.000001     |
| 100 %          |             | - 10       | 1,880,000,002  | 2               | 0.000000      |
| 100 %          |             | 0          | 1,879,999,994  | -6              | 0.000000      |
| 100 %          |             | + 10       | 1,880,000,015  | 15              | 0.000001      |
| 100 %          |             | + 20       | 1,879,999,992  | -8              | 0.000000      |
| 100 %          |             | + 30       | 1,879,999,980  | -20             | -0.000001     |
| 100 %          |             | + 40       | 1,880,000,004  | 4               | 0.000000      |
| 100 %          |             | + 50       | 1,880,000,011  | 11              | 0.000001      |
| 115 %          | 4.26        | + 20       | 1,879,999,983  | -17             | -0.000001     |
| BATT. ENDPOINT | 3.40        | + 20       | 1,880,000,002  | 2               | 0.000000      |

Table 6-11. Frequency Stability Data (PCS GSM Mode – Ch. 661)

**PCS GSM Frequency Stability Measurements (Cont'd)**  
**§2.1055, 24.235; RSS-133 (6.3)**



**Figure 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)**

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN | Page 23 of 36                                                                         |                                 |

## 6.8 Receiver Spurious Emissions

RSS-132 (4.6), RSS-133 (6.6)

| Frequency [MHz] | Level [dBm] | AFCL [dB] | Pol [H/V] | Height [m] | Azimuth [degrees] | Field Strength [dBmV/m] | Limit [dBmV/m] | Margin [dB] |
|-----------------|-------------|-----------|-----------|------------|-------------------|-------------------------|----------------|-------------|
| 47.00           | -98.93      | 10.48     | V         | 1.3        | 30                | 18.55                   | 40.00          | -21.45      |
| 90.60           | -97.32      | 10.97     | V         | 1.5        | 160               | 20.64                   | 43.52          | -22.88      |
| 114.90          | -93.23      | 12.05     | V         | 1.6        | 120               | 25.82                   | 43.52          | -17.70      |
| 190.10          | -98.19      | 14.03     | V         | 1.3        | 330               | 22.84                   | 43.52          | -20.68      |
| 335.60          | -95.05      | 16.58     | V         | 1.4        | 90                | 28.53                   | 46.02          | -17.49      |
| 721.10          | -96.00      | 23.16     | V         | 1.3        | 230               | 34.16                   | 46.02          | -11.86      |

Table 6-12. Radiated Measurements at 3-meters




Figure 6-3. 3-Meter Limits


### NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The EUT was set to receive mode in the middle channel of operation.
3. Radiated emissions were measured from 30MHz to three times that of the highest tunable frequency or local oscillator.
4. The radiated limits are shown on Figure 6-3. Above 960MHz the limit is 500μV/m.


1. All readings are calibrated by a Signal Generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
2. AFCL = Antenna Factor and Cable Loss
3. Measurements are made using CISPR quasi-peak mode. Average measurements are recorded above 1GHz.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT (CERTIFICATION)       |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 24 of 36                   |

## 7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-2. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 25 of 36                   |




Plot 7-3. Band Edge Plot (Cellular GSM Mode – Ch. 128)



Plot 7-4. Conducted Spurious (Cellular GSM Mode – Ch. 190)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 26 of 36                   |




Plot 7-5. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-6. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 27 of 36                   |




Plot 7-7. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-8. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 28 of 36                   |




Plot 7-9. Band Edge Plot (Cellular GSM Mode – Ch. 251)




Plot 7-10. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 29 of 36                   |




Plot 7-11. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-12. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 30 of 36                   |




Plot 7-13. Band Edge Plot (PCS GSM Mode – Ch. 512)



Plot 7-14. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 31 of 36                   |




Plot 7-15. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-16. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT15800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 32 of 36                   |




Plot 7-17. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 7-18. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 33 of 36                   |




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)




Plot 7-20. Band Edge Plot (PCS GSM Mode – Ch. 810)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 34 of 36                   |



Plot 7-21. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)



Plot 7-22. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

|                                      |                                               |                                                                   |                |                                 |
|--------------------------------------|-----------------------------------------------|-------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI5800                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                   | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                | Page 35 of 36                   |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung 850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN FCC ID: A3LGTI5800** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules and RSS-132 and RSS-133 of the Industry Canada rules.

|                                      |                                                                                     |                                                                   |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI5800                   |  | FCC Pt. 22/24 GSM / EDGE MEASUREMENT REPORT<br>(CERTIFICATION)    |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1005270902.A3L | Test Dates:<br>June 2, 2010                                                         | EUT Type:<br>850/1900 GSM/GPRS/EDGE Phone with Bluetooth and WLAN |                                                                                       | Page 36 of 36                   |