

HCT CO., LTD.

CERTIFICATE OF COMPLIANCE

FCC Certification

Applicant Name: SAMSUNG Electronics Co., Ltd.	Date of Issue: April 30, 2013
Address: 129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do, 443-742 Rep. of Korea	Test Site/Location: HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, Korea
	Report No.: HCTR1304FR34-1
	HCT FRN: 0005866421

FCC ID : A3LGTI8550L

APPLICANT : SAMSUNG Electronics Co., Ltd.

FCC Model(s):	GT-I8550L
EUT Type:	850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only
Max. RF Output Power:	Wi-Fi 802.11b (21.30 dBm) / Wi-Fi 802.11g (20.46 dBm) / Wi-Fi 802.11n (18.37 dBm)
Frequency Range:	2412 MHz -2462 MHz
Modulation type	CCK/DSSS/OFDM
FCC Classification:	Digital Transmission System(DTS)
FCC Rule Part(s):	Part 15.247

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



Report prepared by
: Jong Seok Lee
Test engineer of RF Team



Approved by
: Chang Seok Choi
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT				www.hct.co.kr
FCC PT.15.247 TEST REPORT	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L	

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1304FR34	April 25, 2013	- First Approval Report
HCTR1304FR34-1	April 30, 2013	- Changed Antenna Gain

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	7
7. SUMMARY TEST OF RESULTS	8
8. TEST RESULT	9
8.1 6dB BANDWIDTH (802.11b/g/n)	9
8.2 OUTPUT POWER (802.11b/g/n)	1 6
8.3 POWER SPECTRAL DENSITY (802.11b/g/n).....	8 5
8.4 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS ...	9 2
8.5 RADIATED MEASUREMENT.....	1 1 2
8.5.1 RADIATED SPURIOUS EMISSIONS.....	1 1 2
8.5.2 RADIATED RESTRICTED BAND EDGES	1 2 4
8.6 POWERLINE CONDUCTED EMISSIONS	1 2 6
9. LIST OF TEST EQUIPMENT	1 3 1

1. GENERAL INFORMATION

Applicant: SAMSUNG Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do, 443-742 Rep. of Korea
FCC ID: A3LGTI8550L
EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only
Model name(s): GT-I8550L
Date(s) of Tests: April 22, 2013 ~ April 24, 2013
Place of Tests: HCT Co., Ltd.
 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, KOREA.
 (IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

EUT Type	850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	
FCC Model Name	GT-I8550L	
Power Supply	DC 3.8 V	
Battery type	Li-ion Battery(Standard)	
Frequency Range	TX: 2412 MHz ~ 2462 MHz RX: 2412 MHz ~ 2462 MHz	
Max. RF Output Power	Peak	Wi-Fi 802.11b(21.30 dBm) / Wi-Fi 802.11g (20.46 dBm) / Wi-Fi 802.11n (18.37 dBm)
	Average	Wi-Fi 802.11b(15.55 dBm) / Wi-Fi 802.11g (12.19 dBm) / Wi-Fi 802.11n (10.45 dBm)
Modulation Type	DSSS/CCK(802.11b), OFDM(802.11g, 802.11n)	
Antenna Specification	Manufacturer: partron Antenna type: FPCB Antenna Peak Gain : 1.23 dBi	

3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03 dated April 8, 2013 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) and the measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.4-2003) Operating Under §15.247” were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

FCC PT.15.247 TEST REPORT		FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 21, 2011 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

7. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted < 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.6		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.5.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.5.2		PASS

8. TEST RESULT

8.1 6dB BANDWIDTH (802.11b/g/n)

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION

■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Page 5 in KDB 558074, issued 04/08/2013)

RBW = 100 kHz

VBW $\geq$ 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

■ TEST RESULTS

Conducted 6dB Bandwidth Measurements for 802.11b

802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	10.44	0.500	Pass
2437	6	10.45	0.500	Pass
2462	11	10.45	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11g

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	16.35	0.500	Pass
2437	6	16.34	0.500	Pass
2462	11	16.34	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11n


802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	17.34	0.500	Pass
2437	6	17.32	0.500	Pass
2462	11	17.34	0.500	Pass

RESULT PLOTS

6dB Bandwidth plot (802.11b-CH 1)




6dB Bandwidth plot (802.11b-CH 6)



6dB Bandwidth plot (802.11b-CH 11)




6dB Bandwidth plot (802.11g-CH 1)




6dB Bandwidth plot (802.11g-CH 6)




6dB Bandwidth plot (802.11g-CH 11)




6dB Bandwidth plot (802.11n-CH 1)



6dB Bandwidth plot (802.11n-CH 6)



6dB Bandwidth plot (802.11n-CH 11)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

8.2 OUTPUT POWER (802.11b/g/n)

Test Requirements and limit, §15.247(b)(3)

A transmitter antenna terminal of EUT is connected to the input of a Spectrum Analyzer. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION

■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We use the spectrum analyzer's integrated band power measurement function.

The Spectrum Analyzer is set to

- Peak Power (Procedure 9.1.2 in KDB 558074, issued 04/08/2013)

RBW = 1 MHz

VBW $\geq$ 3 x RBW

SPAN $\geq$ 1.5 x DTS bandwidth

Detector Mode = Peak

Sweep = auto couple

Trace Mode = max hold

Allow trace to fully stabilize.

Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector).

- Average Power (Procedure 9.2.1.4 in KDB 558074, issued 04/08/2013)

Measure the duty cycle

Set span to at least 1.5 times the OBW

RBW = 1-5 % of the OBW, not to exceed 1 MHz.

VBW $\geq$ 3 x RBW.

Number of points in sweep $\geq$ 2 x span / RBW. (This gives bin-to-bin spacing $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

Sweep time = auto.

Detector = RMS(i.e., power averaging)

Do not use sweep triggering. Allow the sweep to "free run".

Trace average at least 100 traces in power averaging(RMS) mode.

Compute power by integrating the spectrum across the OBW of the signal using the instrument's band

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

power measurement function with band limits set equal to the OBW band edges.

Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

■ Sample Calculation

$$\begin{aligned} \text{Output Power} &= \text{Reading Value} + \text{ATT loss} + \text{Cable loss(1 ea)} + \text{Duty Cycle Factor} \\ &= 10 \text{ dBm} + 10 \text{ dB} + 0.8 \text{ dB} + 0.2 \text{ dB} = 21.0 \text{ dBm} \end{aligned}$$

Note :

1. Spectrum reading values are not plot data. The power results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of loss for the attenuator and cable combination is below table.

So, 10.1 dB is offset. And the offset gap in the 2.4 GHz range do not affect the conducted peak power final result.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.11
	2437	10.10
	2462	10.12

(Actual value of loss for the attenuator and cable combination)

■ Duty Cycle Factor

Mode	Data Rate	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor
b	1 Mbps	12.420	12.450	0.99759036	0.010
	2 Mbps	6.300	6.330	0.99526066	0.021
	5.5 Mbps	2.411	2.441	0.98770995	0.054
	11 Mbps	1.302	1.329	0.97968397	0.089
g	6 Mbs	2.055	2.094	0.98137536	0.082
	9 Mbs	1.374	1.413	0.97239915	0.122
	12 Mbs	1.036	1.076	0.96282528	0.165
	18 Mbs	0.695	0.736	0.94375000	0.251
	24 Mbs	0.524	0.564	0.92929293	0.318
	36 Mbs	0.364	0.397	0.91687657	0.377
	48 Mbs	0.277	0.308	0.89935065	0.461
	54 Mbs	0.248	0.281	0.88413547	0.535
n	6.5 Mbs	1.918	1.954	0.98157625	0.081
	13 Mbs	0.978	1.012	0.96669960	0.147
	19.5 Mbs	0.665	0.696	0.95517241	0.199
	26 Mbs	0.508	0.539	0.94213650	0.259
	39 Mbs	0.353	0.385	0.91807542	0.371
	52 Mbs	0.274	0.305	0.89819376	0.466
	58.5 Mbs	0.250	0.281	0.88948307	0.509
	65 Mbs	0.229	0.261	0.87907869	0.560

Note : Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

where, Duty Cycle = T_{on} / T_{total}

■ TEST RESULTS-Peak

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	1 Mbps	18.27	30
		2 Mbps	18.28	30
		5.5 Mbps	19.85	30
		11 Mbps	21.30	30
2437	6	1 Mbps	17.73	30
		2 Mbps	18.09	30
		5.5 Mbps	19.63	30
		11 Mbps	21.10	30
2462	11	1 Mbps	17.30	30
		2 Mbps	17.65	30
		5.5 Mbps	19.17	30
		11 Mbps	20.65	30

Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6 Mbps	19.84	30
		9 Mbps	20.06	30
		12 Mbps	20.46	30
		18 Mbps	20.02	30
		24 Mbps	20.32	30
		36 Mbps	19.88	30
		48 Mbps	19.95	30
		54 Mbps	20.06	30
2437	6	6 Mbps	19.25	30
		9 Mbps	19.51	30
		12 Mbps	19.94	30
		18 Mbps	19.45	30
		24 Mbps	19.79	30
		36 Mbps	19.68	30
		48 Mbps	19.60	30
		54 Mbps	19.30	30
2462	11	6 Mbps	18.80	30
		9 Mbps	19.02	30
		12 Mbps	19.46	30
		18 Mbps	18.95	30
		24 Mbps	19.36	30
		36 Mbps	18.84	30
		48 Mbps	18.88	30
		54 Mbps	19.16	30

Conducted Output Power Measurements (802.11n Mode)

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6.5 Mbps	18.22	30
		13 Mbps	18.37	30
		19.5 Mbps	18.27	30
		26 Mbps	18.01	30
		39 Mbps	17.69	30
		52 Mbps	17.72	30
		58.5 Mbps	17.86	30
		65 Mbps	17.75	30
2437	6	6.5 Mbps	17.70	30
		13 Mbps	17.74	30
		19.5 Mbps	17.82	30
		26 Mbps	17.43	30
		39 Mbps	17.52	30
		52 Mbps	17.37	30
		58.5 Mbps	17.36	30
		65 Mbps	17.22	30
2462	11	6.5 Mbps	17.14	30
		13 Mbps	17.19	30
		19.5 Mbps	17.26	30
		26 Mbps	16.87	30
		39 Mbps	16.54	30
		52 Mbps	16.79	30
		58.5 Mbps	16.81	30
		65 Mbps	16.63	30

■ TEST RESULTS-Average

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	1 Mbps	15.45	0.01	15.46	30
		2 Mbps	15.44	0.02	15.46	30
		5.5 Mbps	15.55	0.05	15.60	30
		11 Mbps	15.47	0.09	15.56	30
2437	6	1 Mbps	15.27	0.01	15.28	30
		2 Mbps	15.27	0.02	15.29	30
		5.5 Mbps	15.36	0.05	15.41	30
		11 Mbps	15.23	0.09	15.32	30
2462	11	1 Mbps	14.83	0.01	14.84	30
		2 Mbps	14.84	0.02	14.86	30
		5.5 Mbps	14.88	0.05	14.93	30
		11 Mbps	14.79	0.09	14.88	30

Conducted Output Power Measurements (802.11g Mode)


802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6 Mbps	12.19	0.08	12.27	30
		9 Mbps	12.16	0.12	12.28	30
		12 Mbps	12.15	0.16	12.31	30
		18 Mbps	12.14	0.25	12.39	30
		24 Mbps	11.79	0.32	12.11	30
		36 Mbps	11.27	0.38	11.65	30
		48 Mbps	10.94	0.46	11.40	30
		54 Mbps	10.92	0.53	11.45	30
2437	6	6 Mbps	11.63	0.08	11.71	30
		9 Mbps	11.60	0.12	11.72	30
		12 Mbps	11.64	0.16	11.80	30
		18 Mbps	11.61	0.25	11.86	30
		24 Mbps	10.82	0.32	11.14	30
		36 Mbps	10.76	0.38	11.14	30
		48 Mbps	10.37	0.46	10.83	30
		54 Mbps	10.30	0.53	10.83	30
2462	11	6 Mbps	11.16	0.08	11.24	30
		9 Mbps	11.12	0.12	11.24	30
		12 Mbps	11.09	0.16	11.25	30
		18 Mbps	10.74	0.25	10.99	30
		24 Mbps	10.40	0.32	10.72	30
		36 Mbps	10.32	0.38	10.70	30
		48 Mbps	9.84	0.46	10.30	30
		54 Mbps	9.83	0.53	10.36	30

Conducted Output Power Measurements (802.11n Mode)

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6.5 Mbps	10.45	0.08	10.53	30
		13 Mbps	10.25	0.15	10.40	30
		19.5 Mbps	9.94	0.20	10.14	30
		26 Mbps	9.36	0.26	9.62	30
		39 Mbps	9.31	0.37	9.68	30
		52 Mbps	9.22	0.47	9.69	30
		58.5 Mbps	9.27	0.51	9.78	30
		65 Mbps	9.21	0.56	9.77	30
2437	6	6.5 Mbps	9.43	0.08	9.51	30
		13 Mbps	9.30	0.15	9.45	30
		19.5 Mbps	9.34	0.20	9.54	30
		26 Mbps	8.41	0.26	8.67	30
		39 Mbps	8.37	0.37	8.74	30
		52 Mbps	8.26	0.47	8.73	30
		58.5 Mbps	8.27	0.51	8.78	30
		65 Mbps	8.10	0.56	8.66	30
2462	11	6.5 Mbps	9.25	0.08	9.33	30
		13 Mbps	9.14	0.15	9.29	30
		19.5 Mbps	9.21	0.20	9.41	30
		26 Mbps	8.10	0.26	8.36	30
		39 Mbps	8.07	0.37	8.44	30
		52 Mbps	8.02	0.47	8.49	30
		58.5 Mbps	8.01	0.51	8.52	30
		65 Mbps	7.97	0.56	8.53	30

RESULT PLOTS-Peak


Conducted Output Power (802.11b-CH 1) 1Mbps




Conducted Output Power (802.11b-CH 1) 2Mbps




Conducted Output Power (802.11b-CH 1) 5.5Mbps




Conducted Output Power (802.11b-CH 1) 11Mbps



Conducted Output Power (802.11b-CH 6) 1Mbps




Conducted Output Power (802.11b-CH 6) 2Mbps




Conducted Output Power (802.11b-CH 6) 5.5Mbps



Conducted Output Power (802.11b-CH 6) 11Mbps




Conducted Output Power (802.11b-CH 11) 1Mbps




Conducted Output Power (802.11b-CH 11) 2Mbps



Conducted Output Power (802.11b-CH 11) 5.5Mbps



Conducted Output Power (802.11b-CH 11) 11Mbps



Conducted Output Power (802.11g-CH 1) 6Mbps



Conducted Output Power (802.11g-CH 1) 9Mbps



Conducted Output Power (802.11g-CH 1) 12Mbps



Conducted Output Power (802.11g-CH 1) 18Mbps



Conducted Output Power (802.11g-CH 1) 24Mbps



Conducted Output Power (802.11g-CH 1) 36Mbps



Conducted Output Power (802.11g-CH 1) 48Mbps




Conducted Output Power (802.11g-CH 1) 54Mbps




Conducted Output Power (802.11g-CH 6) 6Mbps



Conducted Output Power (802.11g-CH 6) 9Mbps




Conducted Output Power (802.11g-CH 6) 12Mbps



Conducted Output Power (802.11g-CH 6) 18Mbps



Conducted Output Power (802.11g-CH 6) 24Mbps




Conducted Output Power (802.11g-CH 6) 36Mbps



Conducted Output Power (802.11g-CH 6) 48Mbps



Conducted Output Power (802.11g-CH 6) 54Mbps



Conducted Output Power (802.11g-CH 11) 6Mbps



Conducted Output Power (802.11g-CH 11) 9Mbps




Conducted Output Power (802.11g-CH 11) 12Mbps



Conducted Output Power (802.11g-CH 11) 18Mbps



Conducted Output Power (802.11g-CH 11) 24Mbps



Conducted Output Power (802.11g-CH 11) 36Mbps



Conducted Output Power (802.11g-CH 11) 48Mbps



Conducted Output Power (802.11g-CH 11) 54Mbps



Conducted Output Power (802.11n-CH 1) 6.5Mbps



Conducted Output Power (802.11n-CH 1) 13Mbps



Conducted Output Power (802.11n-CH 1) 19.5Mbps



Conducted Output Power (802.11n-CH 1) 26Mbps



Conducted Output Power (802.11n-CH 1) 39Mbps



Conducted Output Power (802.11n-CH 1) 52Mbps



Conducted Output Power (802.11n-CH 1) 58.5Mbps



Conducted Output Power (802.11n-CH 1) 65Mbps



Conducted Output Power (802.11n-CH 6) 6.5Mbps



Conducted Output Power (802.11n-CH 6) 13Mbps



Conducted Output Power (802.11n-CH 6) 19.5Mbps



Conducted Output Power (802.11n-CH 6) 26Mbps



Conducted Output Power (802.11n-CH 6) 39Mbps



Conducted Output Power (802.11n-CH 6) 52Mbps



Conducted Output Power (802.11n-CH 6) 58.5Mbps



Conducted Output Power (802.11n-CH 6) 65Mbps




Conducted Output Power (802.11n-CH 11) 6.5Mbps



Conducted Output Power (802.11n-CH 11) 13Mbps



Conducted Output Power (802.11n-CH 11) 19.5Mbps



Conducted Output Power (802.11n-CH 11) 26Mbps



Conducted Output Power (802.11n-CH 11) 39Mbps



Conducted Output Power (802.11n-CH 11) 52Mbps



Conducted Output Power (802.11n-CH 11) 58.5Mbps



Conducted Output Power (802.11n-CH 11) 65Mbps



RESULT PLOTS-Average

Conducted Output Power (802.11b-CH 1) 1Mbps



Conducted Output Power (802.11b-CH 1) 2Mbps



Conducted Output Power (802.11b-CH 1) 5.5Mbps



Conducted Output Power (802.11b-CH 1) 11Mbps



Conducted Output Power (802.11b-CH 6) 1Mbps



Conducted Output Power (802.11b-CH 6) 2Mbps



Conducted Output Power (802.11b-CH 6) 5.5Mbps



Conducted Output Power (802.11b-CH 6) 11Mbps



Conducted Output Power (802.11b-CH 11) 1Mbps



Conducted Output Power (802.11b-CH 11) 2Mbps



Conducted Output Power (802.11b-CH 11) 5.5Mbps



Conducted Output Power (802.11b-CH 11) 11Mbps



Conducted Output Power (802.11g-CH 1) 6Mbps



Conducted Output Power (802.11g-CH 1) 9Mbps



Conducted Output Power (802.11g-CH 1) 12Mbps



Conducted Output Power (802.11g-CH 1) 18Mbps



Conducted Output Power (802.11g-CH 1) 24Mbps



Conducted Output Power (802.11g-CH 1) 36Mbps



Conducted Output Power (802.11g-CH 1) 48Mbps



Conducted Output Power (802.11g-CH 1) 54Mbps



Conducted Output Power (802.11g-CH 6) 6Mbps



Conducted Output Power (802.11g-CH 6) 9Mbps



Conducted Output Power (802.11g-CH 6) 12Mbps



Conducted Output Power (802.11g-CH 6) 18Mbps



Conducted Output Power (802.11g-CH 6) 24Mbps



Conducted Output Power (802.11g-CH 6) 36Mbps



Conducted Output Power (802.11g-CH 6) 48Mbps



Conducted Output Power (802.11g-CH 6) 54Mbps



Conducted Output Power (802.11g-CH 11) 6Mbps



Conducted Output Power (802.11g-CH 11) 9Mbps



Conducted Output Power (802.11g-CH 11) 12Mbps



Conducted Output Power (802.11g-CH 11) 18Mbps



Conducted Output Power (802.11g-CH 11) 24Mbps



Conducted Output Power (802.11g-CH 11) 36Mbps



Conducted Output Power (802.11g-CH 11) 48Mbps



Conducted Output Power (802.11g-CH 11) 54Mbps



Conducted Output Power (802.11n-CH 1) 6.5Mbps



Conducted Output Power (802.11n-CH 1) 13Mbps



Conducted Output Power (802.11n-CH 1) 19.5Mbps



Conducted Output Power (802.11n-CH 1) 26Mbps



Conducted Output Power (802.11n-CH 1) 39Mbps



Conducted Output Power (802.11n-CH 1) 52Mbps



Conducted Output Power (802.11n-CH 1) 58.5Mbps



Conducted Output Power (802.11n-CH 1) 65Mbps



Conducted Output Power (802.11n-CH 6) 6.5Mbps



Conducted Output Power (802.11n-CH 6) 13Mbps



Conducted Output Power (802.11n-CH 6) 19.5Mbps



Conducted Output Power (802.11n-CH 6) 26Mbps



Conducted Output Power (802.11n-CH 6) 39Mbps



Conducted Output Power (802.11n-CH 6) 52Mbps



Conducted Output Power (802.11n-CH 6) 58.5Mbps



Conducted Output Power (802.11n-CH 6) 65Mbps



Conducted Output Power (802.11n-CH 11) 6.5Mbps



Conducted Output Power (802.11n-CH 11) 13Mbps



Conducted Output Power (802.11n-CH 11) 19.5Mbps



Conducted Output Power (802.11n-CH 11) 26Mbps



Conducted Output Power (802.11n-CH 11) 39Mbps



Conducted Output Power (802.11n-CH 11) 52Mbps



Conducted Output Power (802.11n-CH 11) 58.5Mbps



Conducted Output Power (802.11n-CH 11) 65Mbps



8.3 POWER SPECTRAL DENSITY (802.11b/g/n)

Test Requirements and limit, §15.247(e)

The peak power spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ TEST CONFIGURATION

■ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 04/08/2013

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

■ Sample Calculation

$$\begin{aligned} \text{PSD} &= \text{Reading Value} + \text{ATT loss} + \text{Cable loss}(1 \text{ ea}) \\ &= -5 \text{ dBm} + 10 \text{ dB} + 0.8 \text{ dB} = 5.8 \text{ dBm} \end{aligned}$$

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of loss for the attenuator and cable combination is below table.

So, 10.1 dB is offset. And the offset gap in the 2.4 GHz range do not affect the power spectral density final result.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.11
	2437	10.10
	2462	10.12

(Actual value of loss for the attenuator and cable combination)


■ TEST RESULTS

Conducted Power Density Measurements


Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2412	1	802.11b	-8.084	8	Pass
2437	6		-8.722	8	Pass
2462	11		-9.213	8	Pass
2412	1	802.11g	-15.151	8	Pass
2437	6		-15.138	8	Pass
2462	11		-14.870	8	Pass
2412	1	802.11n	-15.571	8	Pass
2437	6		-16.522	8	Pass
2462	11		-17.016	8	Pass

■ RESULT PLOTS


Power Spectral Density (802.11b-CH 1)




Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11b-CH 11)




Power Spectral Density (802.11g-CH 1)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT18550L

Power Spectral Density (802.11g-CH 6)




Power Spectral Density (802.11g-CH11)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

Power Spectral Density (802.11n-CH 1)




Power Spectral Density (802.11n-CH 6)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

Power Spectral Density (802.11n-CH11)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

8.4 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

■ TEST CONFIGURATION

■ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074, issued 04/08/2013)

RBW = 100 kHz(Upon 1 GHz = 1 MHz).

VBW $\geq$ 3 x RBW(Upon 1 GHz = 3 MHz).

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points $\geq$ Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

loss for the attenuator and cable combination is below table.

So, 10.1 dB is offset. And the offset gap in the 2.4 GHz range do not affect the band edge final result.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.11
	2437	10.10
	2462	10.12

(Actual value of loss for the attenuator and cable combination)

4. In case of conducted spurious emissions test, please check factors blow table.

■ FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	10.37
100	10.16
200	10.15
300	10.14
400	10.18
500	10.19
600	10.20
700	10.30
800	10.25
900	10.28
1000	10.29
2000	10.17
2412*	10.11
2437*	10.10
2462*	10.12
3000	10.26
4000	10.31
5000	9.85
6000	10.20
7000	10.60
8000	10.53
9000	10.23
10000	10.41
11000	10.65
12000	11.19
13000	10.97
14000	11.42
15000	12.01
16000	11.77
17000	10.78
18000	10.76
19000	11.15
20000	10.75
21000	10.82
22000	10.82
23000	11.26
24000	11.08
25000	11.18
26000	10.90

Note : 1. ** is fundamental frequency range.

2. Factor = Cable loss + Attenuator loss


FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only	FCC ID: A3LGTI8550L

■ RESULT PLOTS

BandEdge (802.11b-CH1)



BandEdge (802.11b-CH11)



BandEdge (802.11g-CH1)



BandEdge (802.11g-CH11)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT8550L

BandEdge (802.11n-CH1)



BandEdge (802.11n-CH11)




30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b-CH1)



Conducted Spurious Emission (802.11b-CH6)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT18550L

Conducted Spurious Emission (802.11b-CH11)



Conducted Spurious Emission (802.11g-CH1)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT8550L

Conducted Spurious Emission (802.11g-CH6)




Conducted Spurious Emission (802.11g-CH11)



Conducted Spurious Emission (802.11n-CH1)



Conducted Spurious Emission (802.11n-CH6)




Conducted Spurious Emission (802.11n-CH11)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT8550L

1 GHz ~ 10 GHz

Conducted Spurious Emission (802.11b-CH1)




Conducted Spurious Emission (802.11b-CH6)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGT18550L


Conducted Spurious Emission (802.11b-CH11)




Conducted Spurious Emission (802.11g-CH11)




Conducted Spurious Emission (802.11g-CH6)




Conducted Spurious Emission (802.11g-CH11)




Conducted Spurious Emission (802.11n-CH1)



Conducted Spurious Emission (802.11n-CH6)



Conducted Spurious Emission (802.11n-CH11)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

10 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b-CH1)




Conducted Spurious Emission (802.11b-CH6)



Conducted Spurious Emission (802.11b-CH11)




Conducted Spurious Emission (802.11g-CH11)



Conducted Spurious Emission (802.11g-CH6)




Conducted Spurious Emission (802.11g-CH11)



Conducted Spurious Emission (802.11n-CH1)



Conducted Spurious Emission (802.11n-CH6)



Conducted Spurious Emission (802.11n-CH11)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1304FR34-1	Date of Issue: April 30, 2013	EUT Type: 850/1900 GSM/GPRS and Cellular/PCS WCDMA/HSDPA/HSUPA Phone with Bluetooth v3.0 with EDR, WLAN 2.4GHz and Hotspot, EDGE Rx only		FCC ID: A3LGTI8550L

8.5 RADIATED MEASUREMENT.


8.5.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

ANSI C63.4(2003)

Method 12.2.3 in KDB 558074, issued 04/08/2013 (Peak)

Method 12.2.4.1 in KDB 558074, issued 04/08/2013(Average Case 1)

Method 12.2.4.3 in KDB 558074, issued 04/08/2013(Average Case 2)

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW $\geq$ 3 x RBW.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Average

Case 1

If the EUT can be configured or modified to transmit continuously (duty cycle $\geq$ 98 percent then the average emission levels shall be measured using the following method (with EUT transmitting continuously).

RBW = 1 MHz (unless otherwise specified).

VBW $\geq 3 \times$ RBW.

Detector = RMS, if span/(# of points in sweep) $\leq$ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

- 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
- 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

Sweep time = auto.

Perform a trace average of at least 100 traces.

Case 2

If continuous transmission of the EUT (i.e., duty cycle $\geq$ 98 percent) cannot be achieved and the duty cycle is not constant (i.e., duty cycle variations exceed $\pm$ 2 percent), then the following procedure shall be used:

Set RBW = 1 MHz.

Set VBW $\geq 1/T$.

Video bandwidth mode or display mode

- 1) The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).
- 2) As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 times (1/duty cycle) traces.

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4824	54.98	-0.79	V	54.19	74	19.81	PK
4824	47.13	-0.79	V	46.34	54	7.66	AV
7236	50.82	9.08	V	59.9	74	14.10	PK
7236	38.09	9.08	V	47.17	54	6.83	AV
4824	56.56	-0.79	H	55.77	74	18.23	PK
4824	50.10	-0.79	H	49.31	54	4.69	AV
7236	50.90	9.08	H	59.98	74	14.02	PK
7236	38.11	9.08	H	47.19	54	6.81	AV

Operation Mode:	802.11 g
Transfer Rate:	6 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4824	51.62	-0.79	V	50.83	74	23.17	PK
4824	40.90	-0.79	V	40.11	54	13.89	AV
7236	51.05	9.08	V	60.13	74	13.87	PK
7236	38.27	9.08	V	47.35	54	6.65	AV
4824	54.32	-0.79	H	53.53	74	20.47	PK
4824	41.68	-0.79	H	40.89	54	13.11	AV
7236	50.57	9.08	H	59.65	74	14.35	PK
7236	38.10	9.08	H	47.18	54	6.82	AV

Operation Mode:	802.11 n
Transfer Rate:	6.5 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4824	52.06	-0.79	V	51.27	74	22.73	PK
4824	40.20	-0.79	V	39.41	54	14.59	AV
7236	50.49	9.08	V	59.57	74	14.43	PK
7236	38.32	9.08	V	47.4	54	6.60	AV
4824	52.17	-0.79	H	51.38	74	22.62	PK
4824	40.46	-0.79	H	39.67	54	14.33	AV
7236	49.76	9.08	H	58.84	74	15.16	PK
7236	38.11	9.08	H	47.19	54	6.81	AV

Notes:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
- Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
- We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
- We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: 802.11 b
 Transfer Rate: 1 Mbps
 Operating Frequency: 2437
 Channel No. 06 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4874	54.71	-0.37	V	54.34	74	19.66	PK
4874	47.40	-0.37	V	47.03	54	6.97	AV
7311	50.51	8.64	V	59.15	74	14.85	PK
7311	37.96	8.64	V	46.60	54	7.40	AV
4874	55.78	-0.37	H	55.41	74	18.59	PK
4874	49.80	-0.37	H	49.43	54	4.57	AV
7311	49.66	8.64	H	58.30	74	15.70	PK
7311	38.41	8.64	H	47.05	54	6.95	AV

Operation Mode: 802.11 g
 Transfer Rate: 6 Mbps
 Operating Frequency: 2437
 Channel No. 06 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4874	55.71	-0.37	V	55.34	74	18.66	PK
4874	42.98	-0.37	V	42.61	54	11.39	AV
7311	50.71	8.64	V	59.35	74	14.65	PK
7311	37.94	8.64	V	46.58	54	7.42	AV
4874	56.78	-0.37	H	56.41	74	17.59	PK
4874	44.73	-0.37	H	44.36	54	9.64	AV
7311	49.90	8.64	H	58.54	74	15.46	PK
7311	38.35	8.64	H	46.99	54	7.01	AV

Operation Mode:	802.11 n
Transfer Rate:	6.5 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4874	53.60	-0.37	V	53.23	74	20.77	PK
4874	40.70	-0.37	V	40.33	54	13.67	AV
7311	50.46	8.64	V	59.10	74	14.90	PK
7311	37.95	8.64	V	46.59	54	7.41	AV
4874	54.61	-0.37	H	54.24	74	19.76	PK
4874	41.84	-0.37	H	41.47	54	12.53	AV
7311	50.44	8.64	H	59.08	74	14.92	PK
7311	38.36	8.64	H	47.00	54	7.00	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: 802.11 b

Transfer Rate: 1 Mbps

Operating Frequency: 2462

Channel No. 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4924	53.80	-0.15	V	53.65	74	20.35	PK
4924	45.80	-0.15	V	45.65	54	8.35	AV
7386	50.36	9.06	V	59.42	74	14.58	PK
7386	38.51	9.06	V	47.57	54	6.43	AV
4924	54.75	-0.15	H	54.6	74	19.40	PK
4924	47.86	-0.15	H	47.71	54	6.29	AV
7386	50.78	9.06	H	59.84	74	14.16	PK
7386	38.23	9.06	H	47.29	54	6.71	AV

Operation Mode: 802.11 g

Transfer Rate: 6 Mbps

Operating Frequency: 2462

Channel No. 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4924	52.36	-0.15	V	52.21	74	21.79	PK
4924	39.98	-0.15	V	39.83	54	14.17	AV
7386	50.67	9.06	V	59.73	74	14.27	PK
7386	38.50	9.06	V	47.56	54	6.44	AV
4924	52.68	-0.15	H	52.53	74	21.47	PK
4924	40.67	-0.15	H	40.52	54	13.48	AV
7386	50.36	9.06	H	59.42	74	14.58	PK
7386	38.21	9.06	H	47.27	54	6.73	AV

Operation Mode:	802.11 n
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4924	51.02	-0.15	V	50.87	74	23.13	PK
4924	39.42	-0.15	V	39.27	54	14.73	AV
7386	50.38	9.06	V	59.44	74	14.56	PK
7386	38.50	9.06	V	47.56	54	6.44	AV
4924	51.69	-0.15	H	51.54	74	22.46	PK
4924	39.80	-0.15	H	39.65	54	14.35	AV
7386	49.88	9.06	H	58.94	74	15.06	PK
7386	38.20	9.06	H	47.26	54	6.74	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.5.2 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	30.26	33.90	H	64.16	74	9.84	PK
2390.0	15.64	33.90	H	49.54	54	4.46	AV
2390.0	27.51	33.90	V	61.41	74	12.59	PK
2390.0	14.51	33.90	V	48.41	54	5.59	AV
2483.5	30.64	33.99	H	64.63	74	9.37	PK
2483.5	15.88	33.99	H	49.87	54	4.13	AV
2483.5	27.42	33.99	V	61.41	74	12.59	PK
2483.5	14.45	33.99	V	48.44	54	5.56	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	26.53	33.90	H	60.43	74	13.57	PK
2390.0	14.90	33.90	H	48.80	54	5.20	AV
2390.0	26.27	33.90	V	60.17	74	13.83	PK
2390.0	14.20	33.90	V	48.10	54	5.90	AV
2483.5	26.35	33.99	H	60.34	74	13.66	PK
2483.5	15.58	33.99	H	49.57	54	4.43	AV
2483.5	25.74	33.99	V	59.73	74	14.27	PK
2483.5	14.36	33.99	V	48.35	54	5.65	AV

Operation Mode:	802.11n
Transfer Rate:	6.5 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	27.28	33.90	H	61.18	74	12.82	PK
2390.0	14.37	33.90	H	48.27	54	5.73	AV
2390.0	25.66	33.90	V	59.56	74	14.44	PK
2390.0	13.97	33.90	V	47.87	54	6.13	AV
2483.5	26.42	33.99	H	60.41	74	13.59	PK
2483.5	14.38	33.99	H	48.37	54	5.63	AV
2483.5	25.89	33.99	V	59.88	74	14.12	PK
2483.5	13.93	33.99	V	47.92	54	6.08	AV

Notes:

1. Total = Reading Value + Antenna Factor + Cable Loss
2. We have done 802.11b/g/n mode and all data rate. Worst data rate is the lowest data of each mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.6 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. We are performed the AC Power Line Conducted Emission test for 11 Mbps, Ch.1 and 802.11b. Because 802.11b mode is worst case.

RESULT PLOTS

Conducted Emissions (Line 1)


HCT

EMC

EUT: GT-I8550L
 Manufacturer: SAMSUNG
 Operating Condition: WLAN MODE
 Test Site: SHIELD ROOM
 Operator: JS LEE
 Test Specification: FCC PART 15 B
 Comment: H

SCAN TABLE: "FCC PART 15 B(H)"

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

4/24/2013 7:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.261010	38.80	9.8	61	22.6	---	---
0.451010	41.40	9.8	57	15.5	---	---
0.463010	42.80	9.8	57	13.9	---	---
0.896000	40.30	9.8	56	15.7	---	---
0.988000	39.90	9.8	56	16.1	---	---
1.340000	38.30	9.8	56	17.7	---	---
16.100000	31.80	11.1	60	28.2	---	---
16.468000	33.10	11.2	60	26.9	---	---
16.568000	33.00	11.2	60	27.0	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

4/24/2013 7:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.268010	28.60	9.8	51	22.6	---	---
0.366010	23.30	9.8	49	25.3	---	---
0.457010	28.60	9.8	47	18.2	---	---
0.724000	28.50	9.8	46	17.5	---	---
1.016000	28.20	9.8	46	17.8	---	---
1.772000	27.30	9.9	46	18.7	---	---
16.000000	27.50	11.1	50	22.5	---	---
16.100000	22.60	11.1	50	27.4	---	---
16.200000	25.20	11.1	50	24.8	---	---

Conducted Emissions (Line 2)


HCT

EMC

EUT: GT-I8550L
Manufacturer: SAMSUNG
Operating Condition: WLAN MODE
Test Site: SHIELD ROOM
Operator: JS LEE
Test Specification: FCC PART 15 CLASS B
Comment: N

SCAN TABLE: "FCC PART 15 B(N)"

Short Description:			FCC PART 15 CLASS B				Transducer
Start	Stop	Step	Detector	Meas. Time	IF Bandw.		
Frequency	Frequency	Width					
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None	
			Average				



MEASUREMENT RESULT: "PHONE_fin QP"

4/24/2013 7:23PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.266010	33.30	10.0	61	27.9	---	---
0.358010	30.10	9.9	59	28.6	---	---
0.458010	36.10	10.0	57	20.7	---	---
0.820000	34.20	10.0	56	21.8	---	---
1.196000	30.40	10.0	56	25.6	---	---
1.272000	31.40	10.0	56	24.6	---	---
15.572000	36.00	11.3	60	24.0	---	---
15.932000	33.00	11.4	60	27.0	---	---
16.480000	36.70	11.5	60	23.3	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

4/24/2013 7:23PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.258010	21.70	10.0	52	29.8	---	---
0.350010	19.30	9.9	49	29.6	---	---
0.450010	25.00	10.0	47	21.9	---	---
0.708000	24.30	10.0	46	21.7	---	---
0.996000	24.00	10.0	46	22.0	---	---
2.704000	22.50	10.2	46	23.5	---	---
15.932000	25.50	11.4	50	24.5	---	---
16.028000	26.20	11.4	50	23.8	---	---
16.124000	27.10	11.4	50	22.9	---	---

9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ENV216/ LISN	Annual	02/06/2014	100073
Schwarzbeck	VULB 9160/ TRILOG Antenna	Biennial	05/03/2015	3125
Rohde & Schwarz	ESI 40 / EMI TEST RECEIVER	Annual	04/16/2014	831564103
Agilent	E4440A/ Spectrum Analyzer	Annual	05/02/2013	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	Annual	07/31/2013	MY51110020
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/11/2013	10094
MITEQ	AMF-6B-180265-35-10P / POWER AMP	Annual	04/16/2014	667624
CERNEX	CBL26405040 / POWER AMP	Annual	04/16/2014	19660
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	10/17/2013	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	Biennial	10/30/2014	BBHA9170124
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	02/08/2014	839117/011
Agilent	E4416A /Power Meter	Annual	11/07/2013	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	05/02/2013	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	05/02/2013	1
Wainwright Instrument	WHNX6.0/26.5G-6SS / High Pass Filter	Annual	05/02/2013	1
Wainwright Instrument	WHNX7.0/18G-8SS / High Pass Filter	Annual	05/02/2013	29
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	05/02/2013	1
Hewlett Packard	11636B/Power Divider	Annual	11/07/2013	11377
Hewlett Packard	11667B / Power Splitter	Annual	06/05/2013	05001
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	11/07/2013	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	11/07/2013	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	04/24/2014	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	05/02/2013	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/11/2014	9009-2536
MITEQ	AMF-6D-001180-35-20P/ POWER AMP	Annual	07/30/2013	990893
Agilent	8493C / Attenuator(10 dB)	Annual	07/30/2013	76649
WEINSCHL	2-3 / Attenuator(3 dB)	Annual	11/07/2013	BR0617
CERNEX	CBLU1183540 / POWER AMP	Annual	07/27/2013	21691