

REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.**Address:**
129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do,
443-742 Rep. of Korea**Date of Issue:**

November 24, 2014

Test Site/Location:

HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea

Report No.: HCT-R-1411-F018-2**HCT FRN:** 0005866421**FCC ID : A3LGTI9060C****APPLICANT : SAMSUNG Electronics Co., Ltd.**

FCC Model(s): GT-I9060C
EUT Type: Mobile Phone
Max. RF Output Power: 96.64 dBm/m
Frequency Range: 2402 MHz -2480 MHz
Modulation type GFSK
FCC Classification: Low Power communication Device Transmitter(DXX)
FCC Rule Part(s): Part 15.249

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



Report prepared by
: Jong Seok Lee
Test Engineer of RF Team



Approved by
: Chang Seok Choi
Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1411-F018	November 18, 2014	- First Approval Report
HCT-R-1411-F018-1	November 21, 2014	- Revised Frequency Range on Page 23
HCT-R-1411-F018-2	November 24, 2014	- Revised Frequency and the emission level on Page 23.

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	6
7. SUMMARY TEST OF RESULTS	7
8. TEST RESULT	8
8.1 DUTY CYCLE.....	8
8.2 OCCUPIED BANDWIDTH MEASUREMENT	10
8.3 RADIATED MEASUREMENT.....	13
8.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT	13
8.3.2 RADIATED SPURIOUS EMISSIONS.....	15
8.3.3 RADIATED BAND EDGES MEASUREMENTS.....	23
8.4 POWERLINE CONDUCTED EMISSIONS	25
9.LIST OF TEST EQUIPMENT	30
9.1 LIST OF TEST EQUIPMENT (Conducted Test)	30
9.2 LIST OF TEST EQUIPMENT (Radiated Test).....	31

1. GENERAL INFORMATION

Applicant: SAMSUNG Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu Suwon-si, Gyeonggi-do, 443-742 Rep. of Korea
FCC ID: A3LGTI9060C
EUT Type: Mobile Phone
Model name(s): GT-I9060C
Date(s) of Tests: November 07, 2014 ~ November 13, 2014
Place of Tests: HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
(IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

FCC Model Name	GT-I9060C	
EUT Type	Mobile Phone	
Power Supply	DC 3.8 V	
Battery type	Li-ion Battery(Standard)	
Frequency Range	TX: 2402 MHz ~ 2480 MHz RX: 2402 MHz ~ 2480 MHz	
Fundamental Field Strength Level	Peak	96.64 dB μ V/m
	Average	48.16 dB μ V/m
Operating Mode	ANT+	
Modulation Type	GFSK	
Number of Channels	79 Channels	
Antenna Specification	Manufacturer: Partron Antenna type: FPCB Antenna Peak Gain : 0.55 dBi	

3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.4-2003) Operating Under §15.249” were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.249 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 21, 2011 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
Occupied Bandwidth	§2.1049	N/A	CONDUCTED	PASS
Duty Cycle	§15.35(c)	N/A		N/A
Fundamental Field Strength Level	§15.249(a)(e)	< 50 mV/m	RADIATED	PASS
Harmonic Field Strength Level	§15.249(a)(e)	< 500 mV/m		PASS
General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	§15.205, 15.209, 15.249(d)(e)	< 15.209 limits or 50dB below the level of the fundamental		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.4		PASS


8. TEST RESULT

8.1 DUTY CYCLE

Test Requirements §15.35(c)

(c) Unless otherwise specified, e.g. § 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification

▣ TEST CONFIGURATION




▣ TEST RESULTS

$$\begin{aligned} \text{DCCF} &= 20 \cdot \log_{10}(\text{Pulse width} / \text{Period of the pulse train}) \\ &= 20 \cdot \log_{10}(0.236 \text{ ms} / 62.6 \text{ ms}) = -48.4732 \text{ dB} \end{aligned}$$


DCCF
-48.47 dB

▣ TEST RESULTS PLOTS

Pulse Width plot



Period of the Pulse Train




8.2 OCCUPIED BANDWIDTH MEASUREMENT

Test Requirements and limit, §2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

▣ TEST CONFIGURATION



▣ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

RBW = 1% to 3% of the 99% bandwidth.

VBW $\geq$ 3 x RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested Occupied Bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer.

▣ TEST RESULTS

ANT+ Mode		99% Bandwidth (MHz)
Frequency[MHz]	Channel No.	
2402	0	1.0134
2440	39	1.0139
2480	78	1.0135

RESULT PLOTS

Occupied Bandwidth plot (Low-CH 0)



Occupied Bandwidth plot (Mid-CH 39)



Occupied Bandwidth plot (High-CH 78)



8.3 RADIATED MEASUREMENT.

8.3.1 FUNDAMENTAL FIELD STRENGTH LEVEL MEASUREMENT

Test Requirements and limit, §15.249(a)(e)

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHz, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts meter)	Field strength of harmonics (millivolts meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(e) As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

The maximum permissible average field strength level is 50 mV/m (93.98 dBuV/m).

The maximum permissible peak field strength level is 500 mV/m (113.98 dBuV/m).

TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Spectrum Setting

Peak : 1 GHz – 25 GHz, RBW = 1 MHz, VBW ≥3*RBW

□ TEST RESULTS

Frequency [MHz]	Reading [dBuV/m]	A.F.+CL [dB]	Ant. Pol. [H/V]	Duty Cycle Correction [dB]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2402	57.01	33.87	V	0.00	90.88	113.98	23.10	PK
2402	57.01	33.87	V	-48.47	42.41	93.98	51.57	AV
2402	60.41	33.87	H	0.00	94.28	113.98	19.70	PK
2402	60.41	33.87	H	-48.47	45.81	93.98	48.17	AV
2441	57.99	33.94	V	0.00	91.93	113.98	22.05	PK
2441	57.99	33.94	V	-48.47	43.46	93.98	50.52	AV
2441	61.35	33.94	H	0.00	95.29	113.98	18.69	PK
2441	61.35	33.94	H	-48.47	46.82	93.98	47.16	AV
2480	58.07	34.02	V	0.00	92.09	113.98	21.89	PK
2480	58.07	34.02	V	-48.47	43.61	93.98	50.37	AV
2480	62.62	34.02	H	0.00	96.64	113.98	17.34	PK
2480	62.62	34.02	H	-48.47	48.16	93.98	45.82	AV

Note :

1. Average field strength data is determined by applying the duty cycle correction factor(DCCF) found in Section 8.1 to the measured peak field strength values.
2. Peak: Total = Reading Value + Antenna Factor + Cable Loss
Average: Total = Reading Value + Antenna Factor + Cable Loss + Duty Cycle Correction
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.3.2 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209, §15.249(d)(e)


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


(e) As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. Spectrum Setting
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V/m	dBm /m	dBm	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor
5. This test is performed with hopping off.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V/m	dBm /m	dBm	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. This test is performed with hopping off.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode: CH Low (2402 MHz)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	52.48	-4.32	V	48.16	73.98	25.82	PK
4804	41.32	-4.32	V	37.00	53.98	16.98	AV
7206	51.15	5.18	V	56.33	73.98	17.65	PK
7206	39.56	5.18	V	44.74	53.98	9.24	AV
4804	52.95	-4.32	H	48.63	73.98	25.35	PK
4804	41.40	-4.32	H	37.08	53.98	16.90	AV
7206	51.31	5.18	H	56.49	73.98	17.49	PK
7206	39.78	5.18	H	44.96	53.98	9.02	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP G: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH Mid (2441 MHz)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4882	51.68	-3.95	V	47.73	73.98	26.25	PK
4882	39.95	-3.95	V	36.00	53.98	17.98	AV
7323	51.46	5.46	V	56.92	73.98	17.07	PK
7323	40.28	5.46	V	45.74	53.98	8.25	AV
4882	51.92	-3.95	H	47.97	73.98	26.01	PK
4882	40.13	-3.95	H	36.18	53.98	17.80	AV
7323	51.93	5.46	H	57.39	73.98	16.60	PK
7323	40.36	5.46	H	45.82	53.98	8.17	AV

※ A:F: ANTENNA FACTOR

C:L: CABLE LOSS

AMP G: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode: CH High (2480 MHz)

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	51.45	-3.49	V	47.96	73.98	26.02	PK
4960	39.75	-3.49	V	36.26	53.98	17.72	AV
7440	52.45	5.10	V	57.55	73.98	16.43	PK
7440	40.30	5.10	V	45.40	53.98	8.58	AV
4960	51.68	-3.49	H	48.19	73.98	25.79	PK
4960	39.84	-3.49	H	36.35	53.98	17.63	AV
7440	52.56	5.10	H	57.66	73.98	16.32	PK
7440	40.44	5.10	H	45.54	53.98	8.44	AV

※ A:F: ANTENNA FACTOR

C:L: CABLE LOSS

AMP G: AMPLIFIER GAIN

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.3.3 RADIATED BAND EDGES MEASUREMENTS

Test Requirements and limit, §15.205, §15.209, §15.249

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or tho the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Operation Mode	ANT+
Operating Frequency	2402 MHz
Channel No	0 Ch

Frequency [MHz]	Reading [dBuV/m]	A.F.+CL [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2400.0	26.05	33.90	H	59.95	73.98	14.03	PK
2400.0	12.55	33.90	H	46.45	53.98	7.53	AV
2400.0	25.57	33.90	V	59.47	73.98	14.51	PK
2400.0	12.50	33.90	V	46.40	53.98	7.58	AV

※ A.F: ANTENNA FACTOR
C.L: CABLE LOSS

Notes:

- 1.. Frequency range of measurement = 2310 ~ 2400 MHz
2. Total = Fundamental Reading Value + Antenna Factor + Cable Loss
3. Spectrum setting:
 - a. Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - b. AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna

Operation Mode	ANT+
Operating Frequency	2480 MHz
Channel No	78 Ch

Frequency [MHz]	Reading [dBuV/m]	A.F.+CL [dB]	Ant. Pol. [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2483.5	25.50	33.99	H	59.49	73.98	14.49	PK
2483.5	15.28	33.99	H	49.27	53.98	4.71	AV
2483.5	24.68	33.99	V	58.67	73.98	15.31	PK
2483.5	12.01	33.99	V	46.00	53.98	7.98	AV

※ A-F: ANTENNA FACTOR
C-L: CABLE LOSS

Notes:

- Frequency range of measurement = 2483.5 MHz ~ 2500 MHz
- Total = Fundamental Reading Value + Antenna Factor + Cable Loss – Delta Value + Duty Cycle Correction Factor
- Spectrum setting:
 - Peak Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 3 MHz.
 - AV Setting 1 GHz – 25 GHz, RBW = 1 MHz, VBW = 10 kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds.
We performed using a reduced video BW method was done with the analyzer in linear mode.
- We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

8.4 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. We are performed the AC Power Line Conducted Emission test for Ch.79 on ANT+ mode.
Because Ch.79 on ANT+ mode is worst case.

RESULT PLOTS

Conducted Emissions (Line 1)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: GT-I9060C
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: ANT+ MODE
Operator Name: JS LEE

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK
— Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.722000	33.1	9.000	Off	L1	9.7	22.9	56.0
0.870000	34.6	9.000	Off	L1	9.7	21.4	56.0
0.874000	34.9	9.000	Off	L1	9.7	21.1	56.0
0.884000	34.0	9.000	Off	L1	9.7	22.0	56.0
0.890000	34.1	9.000	Off	L1	9.7	21.9	56.0
0.900000	33.7	9.000	Off	L1	9.7	22.3	56.0
1.726000	40.7	9.000	Off	L1	9.8	15.3	56.0
1.820000	40.7	9.000	Off	L1	9.8	15.3	56.0
1.892000	41.4	9.000	Off	L1	9.8	14.6	56.0
2.024000	40.7	9.000	Off	L1	9.8	15.3	56.0
2.048000	41.3	9.000	Off	L1	9.8	14.7	56.0
2.088000	41.0	9.000	Off	L1	9.8	15.0	56.0
21.288000	31.7	9.000	Off	L1	10.5	28.3	60.0
21.360000	32.2	9.000	Off	L1	10.5	27.8	60.0
21.438000	29.4	9.000	Off	L1	10.5	30.6	60.0
21.644000	30.8	9.000	Off	L1	10.5	29.2	60.0

11/13/2014

7:50:15

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
21.758000	32.9	9.000	Off	L1	10.5	27.1	60.0
21.888000	29.2	9.000	Off	L1	10.5	30.8	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.722000	23.3	9.000	Off	L1	9.7	22.7	46.0
0.806000	24.8	9.000	Off	L1	9.7	21.2	46.0
0.874000	24.9	9.000	Off	L1	9.7	21.1	46.0
0.884000	25.1	9.000	Off	L1	9.7	20.9	46.0
0.908000	25.3	9.000	Off	L1	9.7	20.7	46.0
0.914000	25.3	9.000	Off	L1	9.7	20.7	46.0
1.820000	31.6	9.000	Off	L1	9.8	14.4	46.0
1.860000	31.8	9.000	Off	L1	9.8	14.2	46.0
2.024000	31.8	9.000	Off	L1	9.8	14.2	46.0
2.046000	32.3	9.000	Off	L1	9.8	13.7	46.0
2.070000	32.0	9.000	Off	L1	9.8	14.0	46.0
2.216000	31.0	9.000	Off	L1	9.8	15.0	46.0
21.438000	17.9	9.000	Off	L1	10.5	32.1	50.0
21.564000	19.8	9.000	Off	L1	10.5	30.2	50.0
21.644000	21.1	9.000	Off	L1	10.5	28.9	50.0
21.758000	21.1	9.000	Off	L1	10.5	28.9	50.0
21.888000	17.6	9.000	Off	L1	10.5	32.4	50.0
22.008000	19.6	9.000	Off	L1	10.5	30.4	50.0

11/13/2014

7:50:15

Conducted Emissions (Line 2)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: GT-I9060C
Manufacturer: SAMSUNG
Test Site: SHIELD ROOM
Operating Conditions: ANT+ MODE
Operator Name: JS LEE

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK
— Preview Result 2-AVG — Final Result 1-QPK — Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.714000	28.5	9.000	Off	N	9.7	27.5	56.0
0.748000	28.9	9.000	Off	N	9.7	27.1	56.0
0.794000	29.2	9.000	Off	N	9.7	26.8	56.0
0.828000	27.9	9.000	Off	N	9.7	28.1	56.0
0.880000	27.6	9.000	Off	N	9.7	28.4	56.0
0.884000	27.6	9.000	Off	N	9.7	28.4	56.0
1.724000	33.8	9.000	Off	N	9.8	22.2	56.0
2.044000	34.8	9.000	Off	N	9.8	21.2	56.0
2.050000	33.7	9.000	Off	N	9.8	22.3	56.0
2.068000	34.2	9.000	Off	N	9.8	21.8	56.0
2.090000	34.1	9.000	Off	N	9.8	21.9	56.0
2.300000	32.4	9.000	Off	N	9.8	23.6	56.0
12.882000	23.7	9.000	Off	N	10.1	36.3	60.0
13.158000	24.2	9.000	Off	N	10.1	35.8	60.0
13.456000	24.2	9.000	Off	N	10.1	35.8	60.0
13.634000	23.6	9.000	Off	N	10.1	36.4	60.0

11/13/2014

7:58:05

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.840000	23.0	9.000	Off	N	10.1	37.0	60.0
14.748000	22.5	9.000	Off	N	10.2	37.5	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.596000	15.2	9.000	Off	N	9.6	30.8	46.0
0.664000	16.9	9.000	Off	N	9.7	29.1	46.0
0.718000	18.8	9.000	Off	N	9.7	27.2	46.0
0.798000	20.1	9.000	Off	N	9.7	25.9	46.0
0.826000	19.4	9.000	Off	N	9.7	26.6	46.0
0.858000	19.4	9.000	Off	N	9.7	26.6	46.0
1.964000	25.7	9.000	Off	N	9.8	20.3	46.0
2.044000	25.7	9.000	Off	N	9.8	20.3	46.0
2.090000	24.6	9.000	Off	N	9.8	21.4	46.0
2.160000	24.9	9.000	Off	N	9.8	21.1	46.0
2.390000	24.4	9.000	Off	N	9.8	21.6	46.0
2.476000	23.1	9.000	Off	N	9.8	22.9	46.0
12.882000	16.6	9.000	Off	N	10.1	33.4	50.0
13.160000	16.4	9.000	Off	N	10.1	33.6	50.0
13.456000	16.3	9.000	Off	N	10.1	33.7	50.0
13.634000	16.9	9.000	Off	N	10.1	33.1	50.0
13.840000	16.6	9.000	Off	N	10.1	33.4	50.0
14.748000	14.9	9.000	Off	N	10.2	35.1	50.0

11/13/2014

7:58:05

9. LIST OF TEST EQUIPMENT

9.1 LIST OF TEST EQUIPMENT (Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ENV216/ LISN	01/29/2014	Annual	01/29/2015	100073
Agilent	E4440A/ Spectrum Analyzer	04/09/2014	Annual	04/09/2015	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	05/23/2014	Annual	05/23/2015	MY51110063
Agilent	N1911A/Power Meter	01/24/2014	Annual	01/24/2015	MY45100523
Agilent	N1921A /POWER SENSOR	07/09/2014	Annual	07/09/2015	MY45241059
Agilent	87300B/Directional Coupler	12/18/2013	Annual	12/18/2014	3116A03621
Hewlett Packard	11667B / Power Splitter	01/27/2014	Annual	01/27/2015	10545
ITECH	IT6720 / DC POWER SUPPLY	11/04/2014	Annual	11/04/2015	0100021562870011 99
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	04/11/2015	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	05/07/2015	100422
Agilent	8493C / Attenuator(10 dB)	07/21/2014	Annual	07/21/2015	76649

9.2 LIST OF TEST EQUIPMENT (Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Calibration Due	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	12/17/2012	Biennial	12/17/2014	3150
Rohde & Schwarz	ESCI / EMI TEST RECEIVER	01/24/2014	Annual	01/24/2015	100584
HD	MA240/ Antenna Position Tower	N/A	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	09/04/2014	Annual	09/04/2015	10094
CERNEX	CBL18265035 / POWER AMP	07/23/2014	Annual	07/23/2015	22966
CERNEX	CBL26405040 / POWER AMP	04/04/2014	Annual	04/04/2015	19660
Schwarzbeck	BBHA 9120D/ Horn Antenna	07/05/2013	Biennial	07/05/2015	1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	07/05/2013	Biennial	07/05/2015	BBHA9170541
Rohde & Schwarz	FSP / Spectrum Analyzer	01/24/2014	Annual	01/24/2015	839117/011
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	02/03/2014	Annual	02/03/2015	F6
Wainwright Instrument	WHNX6.0/26.5G-6SS / High Pass Filter	04/09/2014	Annual	04/09/2015	1
Wainwright Instrument	WHNX7.0/18G-8SS / High Pass Filter	04/04/2014	Annual	04/04/2015	29
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/17/2014	Annual	06/17/2015	1
TESCOM	TC-3000C / BLUETOOTH TESTER	04/11/2014	Annual	04/11/2015	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	05/07/2014	Annual	05/07/2015	100422
Rohde & Schwarz	LOOP ANTENNA	09/03/2014	Biennial	09/03/2016	1513-175
CERNEX	CBL06185030 / POWER AMP	07/21/2014	Annual	07/21/2015	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2014	Annual	07/21/2015	22964