



**FCC 47 CFR Parts 1 & 2
Published RF Exposure KDB Procedures
IEEE Std 1528-2013**

SAR EVALUATION REPORT


For
GSM/WCDMA Phone + Bluetooth, DTS/UNII a/b/g/n, ANT+ and NFC

**Model: GT-I9158V
FCC ID: A3LGTI9158V**

**Report Number: 14U17788-S8A
Issue Date: 6/13/2014**

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO, 443-742, South Korea**

Prepared by
**UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	6/2/2014	Initial Issue	--
A	6/13/2014	Sec. 1 and 12.6.: Corrected typos.	Devin Chang

Table of Contents

1. Attestation of Test Results.....	5
2. Test Methodology	6
3. Facilities and Accreditation	6
4. Calibration and Uncertainty	7
4.1. Measuring Instrument Calibration	7
4.2. Measurement Uncertainty	7
5. Measurement System Description and Setup.....	8
6. SAR Measurement Procedure.....	9
6.1. Normal SAR Measurement Procedure.....	9
6.2. Volume Scan Procedures	11
7. Device Under Test.....	12
7.1. General Information	12
7.2. Wireless Technologies.....	13
7.3. RF Output Power Tolerance	14
7.4. Simultaneous Transmission Condition	15
8. RF Exposure Conditions	16
8.1. Head Exposure Conditions	16
8.2. Body-worn Accessory Exposure Conditions.....	16
8.3. Hotspot Exposure Conditions and Wi-Fi Direct	16
9. RF Output Power Measurement.....	17
9.1. GSM	17
9.2. W-CDMA	19
9.3. Wi-Fi (2.4 GHz Band).....	25
9.4. Wi-Fi (5 GHz Bands).....	26
9.5. Bluetooth	28
10. Tissue Dielectric Properties	29
10.1. Composition of Ingredients for the Tissue Material Used in the SAR Tests	30
10.2. Tissue Dielectric Parameter Check Results.....	31
11. System Performance Check	33
11.1. System Performance Check Measurement Conditions.....	33
11.2. Reference SAR Values for System Performance Check.....	33
11.3. System Performance Check Results	34

12. SAR Test Results	35
12.1. GSM850.....	36
12.2. GSM1900.....	36
12.3. W-CDMA Band V	36
12.4. W-CDMA Band II.....	37
12.5. Wi-Fi (DTS Band).....	37
12.6. Wi-Fi (UNII Band).....	37
12.7. Bluetooth.....	38
12.7.1. Standalone SAR Test Exclusion Considerations	38
12.7.2. Estimated SAR.....	38
13. SAR Measurement Variability.....	39
13.1. The Highest Measured SAR Configuration in Each Frequency Band	39
13.2. Repeated Measurement Results	39
14. Simultaneous Transmission SAR Analysis.....	40
14.1. Sum of the SAR for GSM850 & Wi-Fi & BT	41
14.2. Sum of the SAR for GSM1900 & Wi-Fi & BT	41
14.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT	42
14.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT	42
15. Appendixes.....	43
15.1. Photos and Antenna Locations.....	43
15.2. System Performance Check Plots	43
15.3. Highest SAR Test Plots.....	43
15.4. Calibration Certificate for E-Field Probe EX3DV4 - SN 3773.....	43
15.5. Calibration Certificate for E-Field Probe EX3DV4 - SN 3871	43
15.6. Calibration Certificate for E-Field Probe EX3DV4 - SN 3936.....	43
15.7. Calibration Certificate for D835V2 - SN 4d142	43
15.8. Calibration Certificate for D1900V2- SN 5d043	43
15.9. Calibration Certificate for D2450V2 - SN 899	43
15.10. Calibration Certificate for D5GHzV2 - SN 1138	43

1. Attestation of Test Results

Applicant	Samsung Electronics			
DUT description	GSM/WCDMA Phone + Bluetooth, DTS/UNII a/b/g/n, ANT+ and NFC			
Model	GT-I9158V			
Test device is	An identical prototype			
Device category	Portable			
Exposure category	General Population/Uncontrolled Exposure			
Date tested	05/19/2014 – 5/29/2014			
The highest reported SAR values	RF exposure condition	Licensed	DTS	UNII
	Head	0.206 W/kg	0.081 W/kg	0.058 W/kg
	Body-worn Accessory	0.813 W/kg	0.174 W/kg	0.351 W/kg
	Wireless Router (Hotspot)	0.813 W/kg	0.174 W/kg	N/A
	Simultaneous Transmission	1.164 W/kg	0.987 W/kg	1.164 W/kg
Applicable Standards	FCC 47 CFR Parts 1 & 2 Published RF Exposure KDB Procedures, and TCB workshop updates IEEE Std 1528-2013			
Test Results	Pass			

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.

Approved & Released By:

Prepared By:




Devin Chang
WiSE Senior Engineer
UL Verification Services Inc.

AJ Newcomer
WiSE Laboratory Technician
UL Verification Services Inc.

2. Test Methodology

The tests documented in this report were performed in accordance with FCC 47 CFR Parts 1 & 2, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures, and TCB workshop updates:

- 447498 D01 General RF Exposure Guidance v05r02
- 648474 D04 Handset SAR v01r02
- 941225 D01 SAR test for 3G devices v02
- 941225 D02 HSPA and 1x Advanced v02r02
- 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- 941225 D04 SAR for GSM E GPRS Dual Xfer Mode v01
- 941225 D06 Hotspot Mode SAR v01r01
- 248227 D01 SAR Meas for 802 11abg v01r02
- 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- 865664 D02 SAR Reporting v01r01
- 690783 D01 SAR Listings on Grants v01r03

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at

47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	
SAR Lab F	
SAR Lab G	
SAR Lab H	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. Calibration and Uncertainty

4.1. Measuring Instrument Calibration

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Tissue Dielectric Properties

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
ENA Network Analyzer	Agilent	E5071B	MY42100131	2/24/2015
Dielectronic Probe kit	SPEAG	DAK-3.5	1082	9/10/2014
Dielectronic Probe kit	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	Control Company	4242	122529162	9/19/2014

System Performance Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Synthesized Signal Generator	Agilent	8665B	3438A0063	6/13/2014
Power Meter	HP	438A	2822A05684	10/10/2014
Power Sensor	Agilent	8481A	2237A31744	10/2/2014
Power Sensor	Agilent	8481A	2349A36506	9/30/2014
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1795093	N/A
Directional coupler	Werlatone	C8060-102	2711	N/A
DC Power Supply	AMETEK	XHR60-18	1308A01935	N/A
Thermometer	EXTECH	445703	T35480662	3/28/2015
E-Field Probe	SPEAG	EX3DV4	3773	4/22/2015
E-Field Probe	SPEAG	EX3DV4	3871	12/11/2014
E-Field Probe	SPEAG	EX3DV4	3936	7/22/2014
Data Acquisition Electronics	SPEAG	DAE3	427	1/21/2015
Data Acquisition Electronics	SPEAG	DAE4	1377	7/15/2014
Data Acquisition Electronics	SPEAG	DAE4	1380	7/15/2014
System Validation Dipole	SPEAG	D835V2	4d142	9/17/2014
System Validation Dipole	SPEAG	D1900V2	5d043	11/12/2014
System Validation Dipole	SPEAG	D2450V2	899	9/10/2014
System Validation Dipole	SPEAG	D5GHzV2	1138	11/19/2014

Others


Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Base Station Simulator	R & S	CMU500	132910	4/25/2015
Base Station Simulator	R & S	CMU200	838114/032	7/23/2014
Power Meter	Agilent	N1912A	MY53040015	7/29/2014
Power Sensor	Agilent	N1921A	MY52020011	5/6/2015

4.2. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

5. Measurement System Description and Setup

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6. SAR Measurement Procedure

6.1. Normal SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

6.2. Volume Scan Procedures

Step 1: Repeat Step 1-4 in Section 6.1

Step 2: Volume Scan

Volume Scans are used to assess peak SAR and averaged SAR measurements in largely extended 3-dimensional volumes within any phantom. This measurement does not need any previous area scan. The grid can be anchored to a user specific point or to the current probe location.

Step 3: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

7. Device Under Test

7.1. General Information

Operating Configuration(s)	Held to head, Body-worn (Voice call)
Mobile Hotspot	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi -enabled devices. ☒ Mobile Hotspot (Wi-Fi 2.4 GHz) ☒ Mobile Hotspot (Wi-Fi 5 GHz) (Mobile AP, FCC: Ch.149~165)
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other ☒ Wi-Fi Direct (Wi-Fi 2.4 GHz) ☒ Wi-Fi Direct (Wi-Fi 5 GHz) (FCC: Ch.149 ~ Ch.165)
Device dimension	Overall (Length x Width): 161 mm x 86mm Overall Diagonal: 171 mm Display Diagonal: 148 mm
Back Cover	☒ Normal Battery Cover ☐ Normal Battery Cover with NFC ☐ Wireless Charger Battery Cover ☐ Wireless Charger Battery Cover with NFC
Accessory	☒ Headset
Battery Options	☒ Standard – Lithium-ion battery, Rating 3.8Vdc, 9.88Wh ☐ Extended (large capacity)

7.2. Wireless Technologies

Wireless Technology and Frequency Bands	GSM: 850 / 1900 W-CDMA Band: V / II Wi-Fi : 2.4 / 5 GHz Bluetooth: 2.4 GHz.
Mode	GSM ☒ Voice (GMSK) ☒ GPRS (GMSK) ☒ EGPRS (8PSK) W-CDMA ☒ UMTS Rel. 99 (Voice & Data) ☒ HSDPA (Rel. 6) ☒ HSUPA (Rel. 7) ☒ DC-HSDPA (Rel. 8) ☒ HSPA+ (Rel. 7) Wi-Fi 2.4GHz (802.11b/g/n) ☒ 802.11b ☒ 802.11g ☒ 802.11n (HT20) Wi-Fi 5GHz (802.11a/n) ☒ 802.11a ☒ 802.11n (HT20) ☒ 802.11n (HT40) Bluetooth ☒ Version 4.0 LE
Duty Cycle	GSM Voice: 12.5%; GPRS 1 Slot: 12.5%; 2 Slots: 25%, 3 Slots: 37.5%, 4 Slots: 50%, W-CDMA: 100% Wi-Fi 802.11a/b/g/n: 100% Bluetooth: 32.25% (DH1), 66.68% (DH3), 77.52% (DH5)
GPRS Multi-Slot Class	☐ Class 8 - One Up ☐ Class 10 - Two Up ☒ Class 12 - Four Up ☐ Class 33 - Four Up
DTM (Dual Transfer Mode)	☐ Supported
VoIP (GPRS)	☒ Supported
SV-LTE & SV-DO	☐ Supported

7.3. RF Output Power Tolerance

Upper limit (dB): 0.5 ~ -1.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
GSM850	Voice	33.0	33.5
	GPRS 1 slot	33.0	33.5
	GPRS 2 slots	31.0	31.5
	GPRS 3 slots	29.0	29.5
	GPRS 4 slots	27.0	27.5
	EGPRS 1 slot	27.0	27.5
	EGPRS 2 slots	26.0	26.5
	EGPRS 3 slots	23.5	24.0
	EGPRS 4 slots	21.5	22.0
GSM1900	Voice	28.5	29.0
	GPRS 1 slot	28.5	29.0
	GPRS 2 slots	28.0	28.5
	GPRS 3 slots	26.5	27.0
	GPRS 4 slots	25.5	26.0
	EGPRS 1 slot	25.0	25.5
	EGPRS 2 slots	23.5	24.0
	EGPRS 3 slots	21.5	22.0
	EGPRS 4 slots	19.5	20.0
W-CDMA Band V	R99	23.0	23.5
	HSDPA	22.0	22.5
	HSUPA	21.5	22.0
	HSPA+	21.5	22.0
	DC-DSPA	22.0	22.5
W-CDMA Band II	R99	21.5	22.0
	HSDPA	20.5	21.0
	HSUPA	20.5	21.0
	HSPA+	20.5	21.0
	DC-DSPA	20.5	21.0

Upper limit (dB): 0.5 ~ -1.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
WiFi 2.4 GHz	802.11b	16.0	16.5
	802.11g	12.0	12.5
	802.11n HT20	12.0	12.5
WiFi 5 GHz	802.11a	12.0	12.5
	802.11n HT20	12.0	12.5
	802.11n HT40	11.0	11.5
Bluetooth		9.0	9.5
Bluetooth LE		1.0	1.5

7.4. Simultaneous Transmission Condition

RF Exposure Condition	Capable Transmit Configurations
Head	1. GSM 850/1900 Voice + Wi-Fi 2.4/5GHz 2. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4/5GHz (VoIP) 3. WCDMA Band V/II + Wi-Fi 2.4/5GHz
Body-worn Accessory	4. GSM 850/1900 Voice + Wi-Fi 2.4/5GHz 5. GSM 850/1900 Voice + BT 6. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4/5GHz (VoIP) 7. GSM 850/1900 (GPRS/EDGE) + BT(VoIP) 8. WCDMA Band V/II + Wi-Fi 2.4/5GHz 9. WCDMA Band V/II + BT
Wireless Router (Hotspot) & Wi-Fi Direct	10. GSM 850/1900 (GPRS/EDGE) + Wi-Fi 2.4/5.8GHz 11. WCDMA Band V/II + Wi-Fi 2.4/5.8GHz
Notes: 1. Wi-Fi 2.4GHz and 5.8 GHz support Hotspot and Wi-Fi Direct. 2. GPRS/EDGE and WCDMA support Hotspot. 3. VoIP is supported in GPRS/EDGE and WCDMA. 4. Wi-Fi 2.4 GHz Radio cannot transmit simultaneously with Bluetooth Radio. 5. Wi-Fi 5 GHz Radio can transmit simultaneously with Bluetooth Radio.	

8. RF Exposure Conditions

Refer to Appendix "Antenna Locations and Separation Distances" for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

8.1. Head Exposure Conditions

For WWAN, LTE and Wi-Fi

Test Configurations	SAR Required	Note
Left Touch	Yes	
Left Tilt (15°)	Yes	
Right Touch	Yes	
Right Tilt (15°)	Yes	

8.2. Body-worn Accessory Exposure Conditions

For WWAN

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	

8.3. Hotspot Exposure Conditions and Wi-Fi Direct

For WWAN

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	
Edge 1 (Top)	140 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR
Edge 2 (Right)	1 mm	Yes	
Edge 3 (Bottom)	1 mm	Yes	
Edge 4 (Left)	52 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	
Edge 1 (Top)	64 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR
Edge 2 (Right)	77 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR
Edge 3 (Bottom)	75 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR
Edge 4 (Left)	4 mm	Yes	

9. RF Output Power Measurement

9.1. GSM

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
850	GSM (Voice)	CS1	1	128	824.2	33.2	24.1
				190	836.6	33.1	24.1
				251	848.8	33.0	24.0
	GPRS (GMSK)	CS1	1	128	824.2	33.2	24.2
				190	836.6	33.1	24.1
				251	848.8	33.0	24.0
			2	128	824.2	31.3	25.3
				190	836.6	31.3	25.3
				251	848.8	31.3	25.2
			3	128	824.2	29.0	24.7
				190	836.6	29.1	24.8
				251	848.8	29.0	24.7
			4	128	824.2	27.0	24.0
				190	836.6	27.1	24.1
				251	848.8	27.2	24.2
	EGPRS (8PSK)	MCS5	1	128	824.2	27.4	18.4
				190	836.6	26.9	17.9
				251	848.8	26.5	17.5
			2	128	824.2	25.8	19.8
				190	836.6	25.3	19.3
				251	848.8	25.1	19.1
			3	128	824.2	23.7	19.4
				190	836.6	23.3	19.0
				251	848.8	23.0	18.7
			4	128	824.2	21.6	18.6
				190	836.6	21.3	18.3
				251	848.8	21.0	18.0

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
1900	GSM (Voice)	CS1	1	512	1850.2	28.8	19.8
				661	1880.0	28.6	19.6
				810	1909.8	28.3	19.3
	GPRS (GMSK)	CS1	1	512	1850.2	28.8	19.8
				661	1880.0	28.6	19.6
				810	1909.8	28.3	19.3
			2	512	1850.2	28.1	22.1
				661	1880.0	27.9	21.9
				810	1909.8	27.6	21.6
			3	512	1850.2	27.0	22.7
				661	1880.0	26.8	22.5
				810	1909.8	26.6	22.3
			4	512	1850.2	26.0	23.0
				661	1880.0	25.7	22.7
				810	1909.8	25.4	22.4
	EGPRS (8PSK)	MCS5	1	512	1850.2	25.4	16.4
				661	1880.0	25.1	16.1
				810	1909.8	24.8	15.8
			2	512	1850.2	23.7	17.7
				661	1880.0	23.4	17.4
				810	1909.8	23.1	17.1
			3	512	1850.2	21.6	17.3
				661	1880.0	21.4	17.1
				810	1909.8	21.1	16.8
			4	512	1850.2	19.6	16.6
				661	1880.0	19.4	16.4
				810	1909.8	19.1	16.1

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 4 time slots, based on the output power measurements above
- SAR is not required for EGPRS (8PSK) mode because its output power is less than that of GPRS Mode

9.2. W-CDMA

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
W-CDMA Band V	Rel 99 (RMC, 12.2 kbps)	4132	826.4	23.2
		4183	836.6	23.1
		4233	846.6	23.0
W-CDMA Band II	Rel 99 (RMC, 12.2 kbps)	9262	1852.4	21.8
		9400	1880.0	21.6
		9538	1907.6	21.7

HSDPA

The following 4 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121-1. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR (dB)	0	0	0.5	0.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	22.3
		4183	836.6	0	22.1
		4233	846.6	0	22.1
	Subtest 2	4132	826.4	0	22.4
		4183	836.6	0	22.2
		4233	846.6	0	22.0
	Subtest 3	4132	826.4	0.5	21.8
		4183	836.6	0.5	21.6
		4233	846.6	0.5	21.6
	Subtest 4	4132	826.4	0.5	21.8
		4183	836.6	0.5	21.6
		4233	846.6	0.5	21.5
W-CDMA Band II	Subtest 1	9262	1852.4	0	20.5
		9400	1880.0	0	20.4
		9538	1907.6	0	20.1
	Subtest 2	9262	1852.4	0	20.3
		9400	1880.0	0	20.4
		9538	1907.6	0	19.6
	Subtest 3	9262	1852.4	0.5	20.1
		9400	1880.0	0.5	19.9
		9538	1907.6	0.5	19.6
	Subtest 4	9262	1852.4	0.5	20.2
		9400	1880.0	0.5	19.9
		9538	1907.6	0.5	19.5

Maximum output power levels that are possible for all subtests reported.

HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	11/15	15/9	2/15	15/0
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15 47/15	56/75	47/15
	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	$A_{hs} = \beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
	Reference E-TFCI PO	27	27	27	27	27
	Maximum Channelisation Codes	2xSF2				SF4

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	22.0
		4183	836.6	0	21.7
		4233	846.6	0	21.8
	Subtest 2	4132	826.4	2	21.0
		4183	836.6	2	21.1
		4233	846.6	2	21.0
	Subtest 3	4132	826.4	1	21.0
		4183	836.6	1	21.0
		4233	846.6	1	21.0
	Subtest 4	4132	826.4	2	21.4
		4183	836.6	2	21.7
		4233	846.6	2	21.5
	Subtest 5	4132	826.4	0	22.0
		4183	836.6	0	22.0
		4233	846.6	0	22.0
W-CDMA Band II	Subtest 1	9262	1852.4	0	20.0
		9400	1880.0	0	20.2
		9538	1907.6	0	20.1
	Subtest 2	9262	1852.4	2	19.0
		9400	1880.0	2	19.0
		9538	1907.6	2	18.6
	Subtest 3	9262	1852.4	1	19.7
		9400	1880.0	1	19.1
		9538	1907.6	1	19.0
	Subtest 4	9262	1852.4	2	19.0
		9400	1880.0	2	19.0
		9538	1907.6	2	19.0
	Subtest 5	9262	1852.4	0	20.8
		9400	1880.0	0	20.4
		9538	1907.6	0	20.0

DC-HSDPA

The following 4 Sub-tests were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121-1, since DC-HSDPA has only one transmitting uplink. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	MPR (dB)	0	0	0.5	0.5
	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	22.4
		4183	836.6	0	22.2
		4233	846.6	0	22.0
	Subtest 2	4132	826.4	0	22.4
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 3	4132	826.4	0.5	21.8
		4183	836.6	0.5	21.6
		4233	846.6	0.5	21.5
	Subtest 4	4132	826.4	0.5	21.8
		4183	836.6	0.5	21.6
		4233	846.6	0.5	21.5
W-CDMA Band II	Subtest 1	9262	1852.4	0	20.5
		9400	1880.0	0	20.4
		9538	1907.6	0	20.1
	Subtest 2	9262	1852.4	0	20.3
		9400	1880.0	0	20.4
		9538	1907.6	0	19.6
	Subtest 3	9262	1852.4	0.5	20.1
		9400	1880.0	0.5	19.9
		9538	1907.6	0.5	19.6
	Subtest 4	9262	1852.4	0.5	20.2
		9400	1880.0	0.5	19.9
		9538	1907.6	0.5	19.5

HSPA+

Since 16QAM is not used for uplink, the uplink Category and release is same as HSUPA, i.e., CAT 6 Rel 6. Therefore, the RF conducted power is not measured.

9.3. Wi-Fi (2.4 GHz Band)

Required Test Channels per KDB 248227 D01

Mode	Band	GHz	Channel	"Default Test Channels"	
				802.11b	802.11g
802.11b/g	2.4 GHz	2.412	1 [#]	√	▽
		2.437	6	√	▽
		2.462	11 [#]	√	▽

Notes:

√ = "default test channels"

▽ = possible 802.11g channels with maximum average output ¼ dB ≥ the "default test channels"

[#] = when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
2.4 (DTS)	802.11b	1 Mbps	1	2412	15.7	Yes
			6	2437	16.5	
			11	2462	15.8	
	802.11g	6 Mbps	1	2412	12.0	No
			6	2437	12.5	
			11	2462	12.4	
	802.11n (HT20)	MCS0	1	2412	12.0	No
			6	2437	12.5	
			11	2462	12.4	

Note(s):

Per KDB 248227 D01, SAR is not required for 802.11g/HT20 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.

Power measurements to determine worst-case data rates

Mode	Ch #	Freq. (MHz)	Data Rate	Avg Pwr (dBm)	SAR test (Yes/No)
802.11b	6	2437	1 Mbps	16.5	Yes
			2 Mbps	16.5	No
			5.5 Mbps	16.5	No
			11 Mbps	16.5	No

9.4. Wi-Fi (5 GHz Bands)

Required Test Channels per KDB 248227 D01

Mode		Band	GHz	Channel	"Default Test Channels"	
					802.11a	
802.11a	UNII (15.407)	5.2 GHz	5.180	36	√	
			5.200	40		*
			2.220	44		*
			5.240	48	√	
		5.3 GHz	5.260	52	√	
			5.280	56		*
			5.300	60		*
			5.320	64	√	
		5.5 GHz	5.500	100		
			5.520	104	√	
			5.540	108		*
			5.560	112		*
			5.580	116	√	
			5.600	120		*
			5.620	124	√	
			5.640	128		*
			5.660	132		*
			5.680	136	√	
			5.700	140		*
	DTS (15.247)	5.8 GHz	5.745	149	√	
			5.765	153		*
			5.785	157	√	
			5.805	161		*
			5.825	165	√	

√ = "default test channels"

* = possible 802.11a channels with maximum average output > the "default test channels"

= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
5.2 (UNII)	802.11a	6 Mbps	36	5180	12.3	Yes
			40	5200	12.1	
			44	5220	12.5	
			48	5240	12.1	
	802.11n (HT20)	MCS0	36	5180	12.5	No
			40	5200	12.0	
			48	5240	12.5	
	802.11n (HT40)	MCS0	38	5190	11.3	No
			46	5230	11.2	
5.3 (UNII)	802.11a	6 Mbps	52	5260	12.3	Yes
			56	5280	12.3	
			60	5300	12.5	
			64	5320	12.5	
	802.11n (HT20)	MCS0	52	5260	12.3	No
			60	5300	12.5	
			64	5320	12.5	
	802.11n (HT40)	MCS0	54	5270	11.4	No
			62	5310	11.4	
Band (GHz)	Mode	Mode	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
5.5 (UNII)	802.11a	6 Mbps	100	5500	12.5	Yes
			104	5520	12.5	
			108	5540	12.5	
			112	5560	12.0	
			116	5580	12.5	
			120	5600	12.0	
			124	5620	12.0	
			128	5640	12.5	
			132	5660	12.5	
			136	5680	12.0	
			140	5700	12.2	
	802.11n (HT20)	MCS0	100	5500	12.5	No
			116	5580	12.5	
			140	5700	12.3	
	802.11n (HT40)	MCS0	102	5510	11.0	No
			110	5550	11.0	
			134	5670	11.0	
5.8 (DTS)	802.11a	6 Mbps	149	5745	12.5	Yes
			153	5765	12.2	
			157	5785	12.5	
			161	5805	12.4	
			165	5825	12.5	
	802.11n (HT20)	MCS0	149	5745	12.5	No
			157	5785	12.5	
			161	5805	12.0	
	802.11n (HT40)	MCS0	151	5755	12.2	No
			159	5795	12.0	

Note(s):

Per KDB 248227, SAR is not required for 802.11n HT20/HT40 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11a channels.

Power measurements to determine worst-case data rates

Band	Mode	Ch #	Freq. (MHz)	Data Rate	Avg Pwr (dBm)	SAR test (Yes/No)
5.2 GHz (UNII)	802.11a	44	5220	6 Mbps	12.5	Yes
				9 Mbps	12.2	No
				12 Mbps	12.3	No
				18 Mbps	12.2	No
				24 Mbps	12.4	No
				36 Mbps	12.5	No
				48 Mbps	12.5	No
				54 Mbps	12.5	No
5.3 GHz (UNII)	802.11a	64	5320	6 Mbps	12.5	Yes
				9 Mbps	12.5	No
				12 Mbps	12.5	No
				18 Mbps	12.5	No
				24 Mbps	12.5	No
				36 Mbps	12.5	No
				48 Mbps	12.5	No
				54 Mbps	12.5	No
5.5 GHz (UNII)	802.11a	116	5580	6 Mbps	12.5	Yes
				9 Mbps	12.4	No
				12 Mbps	12.4	No
				18 Mbps	12.4	No
				24 Mbps	12.5	No
				36 Mbps	12.5	No
				48 Mbps	12.5	No
				54 Mbps	12.4	No
5.8 GHz (DTS)	802.11a	149	5745	6 Mbps	12.5	Yes
				9 Mbps	12.5	No
				12 Mbps	12.5	No
				18 Mbps	12.5	No
				24 Mbps	12.5	No
				36 Mbps	12.5	No
				48 Mbps	12.5	No
				54 Mbps	12.5	No

9.5. Bluetooth

Maximum tune-up tolerance limit is 9.5 dBm from the rated nominal maximum output power. This power level qualifies for exclusion of SAR testing.

Refer to Standalone SAR Test Exclusion Considerations Section.

10. Tissue Dielectric Properties

IEEE Std 1528-2013

Target Frequency (MHz)	Head	
	ϵ_r	σ (S/m)
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	40.4	1.23
1640	40.2	1.31
1750	40.1	1.37
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	39.8	1.49
2300	39.5	1.67
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

10.1. Composition of Ingredients for the Tissue Material Used in the SAR Tests

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ+ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether

MSL/HSL750 (Body and Head liquids for 700 – 800 MHz)

Item	Head Tissue Simulation Liquids HSL750 Muscle (body) Tissue Simulation Liquids MSL750
Type No	SL AAH 075
Manufacturer	SPEAG
The item is composed of the following ingredients:	
H ₂ O	Water, 35 – 58%
Sucrose	Sugar, white, refined, 40-60%
NaCl	Sodium Chloride, 0-6%
Hydroxyethyl-cellulose	Medium Viscosity (CAS# 9004-62-0), <0.3%
Preventol-D7	Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyl-3(2H)-isothiazolone, 0.1-0.7%

MSL/HSL1750 (Body and Head liquids for 1700 – 1800 MHz)

Item	Head Tissue Simulation Liquids HSL1750 Muscle (body) Tissue Simulation Liquids MSL1750
Type No	SL AAM 175
Manufacturer	SPEAG
-The item is composed of the following ingredients:	
H ₂ O	Water, 52 – 75%
C8H18O3	Diethylene glycol monobutyl ether (DGBE), 25-48%
NaCl	Sodium Chloride, <1.0%

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

10.2. Tissue Dielectric Parameter Check Results

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

SAR Room 1

	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/19/2014	Body 835	e'	55.2900	Relative Permittivity (ε _r):	55.29	55.20	0.16	5
		e"	21.8500	Conductivity (σ):	1.01	0.97	4.58	5
	Body 820	e'	55.3500	Relative Permittivity (ε _r):	55.35	55.28	0.13	5
		e"	21.9000	Conductivity (σ):	1.00	0.97	3.10	5
	Body 850	e'	55.1500	Relative Permittivity (ε _r):	55.15	55.16	-0.01	5
		e"	21.8300	Conductivity (σ):	1.03	0.99	4.52	5
5/20/2014	Head 835	e'	41.4600	Relative Permittivity (ε _r):	41.46	41.50	-0.10	5
		e"	19.5400	Conductivity (σ):	0.91	0.90	0.80	5
	Head 820	e'	41.6500	Relative Permittivity (ε _r):	41.65	41.60	0.11	5
		e"	19.5900	Conductivity (σ):	0.89	0.90	-0.59	5
	Head 850	e'	41.2700	Relative Permittivity (ε _r):	41.27	41.50	-0.55	5
		e"	19.5000	Conductivity (σ):	0.92	0.92	0.72	5
5/20/2014	Body 5180	e'	50.0800	Relative Permittivity (ε _r):	50.08	49.05	2.11	5
		e"	17.5400	Conductivity (σ):	5.05	5.27	-4.16	5
	Body 5200	e'	50.0400	Relative Permittivity (ε _r):	50.04	49.02	2.08	5
		e"	17.5500	Conductivity (σ):	5.07	5.29	-4.16	5
	Body 5600	e'	49.4900	Relative Permittivity (ε _r):	49.49	48.48	2.09	5
		e"	17.8400	Conductivity (σ):	5.55	5.76	-3.58	5
	Body 5800	e'	49.2400	Relative Permittivity (ε _r):	49.24	48.20	2.16	5
		e"	18.0200	Conductivity (σ):	5.81	6.00	-3.14	5
	Body 5825	e'	49.2200	Relative Permittivity (ε _r):	49.22	48.20	2.12	5
		e"	18.0500	Conductivity (σ):	5.85	6.00	-2.56	5
5/21/2014	Head 5180	e'	37.5100	Relative Permittivity (ε _r):	37.51	36.01	4.16	5
		e"	15.6600	Conductivity (σ):	4.51	4.63	-2.59	5
	Head 5200	e'	37.4800	Relative Permittivity (ε _r):	37.48	35.99	4.14	5
		e"	15.6700	Conductivity (σ):	4.53	4.65	-2.58	5
	Head 5600	e'	36.9200	Relative Permittivity (ε _r):	36.92	35.53	3.90	5
		e"	15.8800	Conductivity (σ):	4.94	5.06	-2.28	5
	Head 5800	e'	36.6600	Relative Permittivity (ε _r):	36.66	35.30	3.85	5
		e"	16.0100	Conductivity (σ):	5.16	5.27	-2.03	5
	Head 5825	e'	36.6200	Relative Permittivity (ε _r):	36.62	35.30	3.74	5
		e"	16.0400	Conductivity (σ):	5.20	5.27	-1.42	5

Tissue Dielectric Parameter Check Results (continued)

SAR Room 3

	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/20/2014	Head 2450	e'	40.2700	Relative Permittivity (ϵ_r):	40.27	39.20	2.73	5
		e"	13.3200	Conductivity (σ):	1.81	1.80	0.81	5
	Head 2410	e'	40.4100	Relative Permittivity (ϵ_r):	40.41	39.28	2.88	5
		e"	13.2200	Conductivity (σ):	1.77	1.76	0.63	5
	Head 2475	e'	40.1800	Relative Permittivity (ϵ_r):	40.18	39.17	2.58	5
		e"	13.4100	Conductivity (σ):	1.85	1.83	1.01	5
5/20/2014	Body 2450	e'	52.0900	Relative Permittivity (ϵ_r):	52.09	52.70	-1.16	5
		e"	14.7700	Conductivity (σ):	2.01	1.95	3.18	5
	Body 2410	e'	52.2300	Relative Permittivity (ϵ_r):	52.23	52.76	-1.00	5
		e"	14.6100	Conductivity (σ):	1.96	1.91	2.64	5
	Body 2475	e'	52.0100	Relative Permittivity (ϵ_r):	52.01	52.67	-1.25	5
		e"	14.8700	Conductivity (σ):	2.05	1.99	3.08	5

SAR Room 4

	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/28/2014	Body 1900	e'	53.5900	Relative Permittivity (ϵ_r):	53.59	53.30	0.54	5
		e"	14.9200	Conductivity (σ):	1.58	1.52	3.70	5
	Body 1850	e'	53.7900	Relative Permittivity (ϵ_r):	53.79	53.30	0.92	5
		e"	14.7900	Conductivity (σ):	1.52	1.52	0.09	5
	Body 1910	e'	53.5500	Relative Permittivity (ϵ_r):	53.55	53.30	0.47	5
		e"	14.9300	Conductivity (σ):	1.59	1.52	4.32	5
5/28/2014	Head 1900	e'	40.9500	Relative Permittivity (ϵ_r):	40.95	40.00	2.38	5
		e"	13.6200	Conductivity (σ):	1.44	1.40	2.78	5
	Head 1850	e'	41.1700	Relative Permittivity (ϵ_r):	41.17	40.00	2.93	5
		e"	13.5000	Conductivity (σ):	1.39	1.40	-0.81	5
	Head 1910	e'	40.9100	Relative Permittivity (ϵ_r):	40.91	40.00	2.27	5
		e"	13.6400	Conductivity (σ):	1.45	1.40	3.47	5

11. System Performance Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

11.1. System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ± 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

11.2. Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (mW/g)		
				1g/10g	Head	Body
D835V2	4d142	9/17/2013	835	1g	9.44	9.36
				10g	6.12	6.20
D1900V2	5d043	11/12/2013	1900	1g	40.1	39.0
				10g	21.1	20.8
D2450V2	899	9/10/2013	2450	1g	51.3	49.7
				10g	23.9	23.3
D5GHzV2	1138	11/19/2013	5200	1g	78.5	72.9
				10g	22.5	20.4
			5500	1g	82.7	78.3
				10g	23.5	21.7
			5800	1g	78.3	72.8
				10g	22.4	20.1

11.3. System Performance Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Room 1

Date Tested	System Dipole		T.S. Liquid	Measured Results			Target (Ref. Value)	Delta $\pm 10\%$	Est./Zoom Ratio	Plot No.
	Type	Serial #		Area Scan	Zoom Scan	Normalize to 1 W				
5/19/2014	D835V2	4d142	Body	1g	1.00	0.98	9.8	9.36	4.27	2.20
				10g	0.67	0.64	6.4	6.20	3.71	
5/20/2014	D835V2	4d142	Head	1g	0.97	0.95	9.5	9.44	0.53	2.47
				10g	0.657	0.620	6.2	6.12	1.31	
5/20/2014	D5GHzV2 5.2GHz	1138	Body	1g	6.59	6.85	68.5	72.9	-6.04	-3.95
				10g	1.890	1.930	19.3	20.4	-5.39	
5/20/2014	D5GHzV2 5.6GHz	1138	Body	1g	8.52	7.94	79.4	78.3	1.40	6.81
				10g	2.370	2.200	22.0	21.7	1.38	
5/20/2014	D5GHzV2 5.8GHz	1138	Body	1g	7.25	6.77	67.7	72.8	-7.01	6.62
				10g	2.020	1.870	18.7	20.1	-6.97	
5/21/2014	D5GHzV2 5.2GHz	1138	Head	1g	6.90	7.37	73.7	72.9	1.10	-6.81
				10g	1.990	2.120	21.2	20.4	3.92	
5/21/2014	D5GHzV2 5.6GHz	1138	Head	1g	6.65	7.30	73.0	78.3	-6.77	-9.77
				10g	1.880	2.080	20.8	21.7	-4.15	
5/21/2014	D5GHzV2 5.8GHz	1138	Head	1g	6.31	6.90	69.0	72.8	-5.22	-9.35
				10g	1.780	1.960	19.6	20.1	-2.49	

SAR Room 3

Date Tested	System Dipole		T.S. Liquid	Measured Results			Target (Ref. Value)	Delta $\pm 10\%$	Est./Zoom Ratio	Plot No.
	Type	Serial #		Area Scan	Zoom Scan	Normalize to 1 W				
5/20/2014	D2450V2	899	Head	1g	5.01	4.92	49.2	51.3	-4.09	1.80
				10g	2.19	2.23	22.3	23.9	-6.69	
5/20/2014	D2450V2	899	Body	1g	5.26	5.31	53.1	49.7	6.84	-0.95
				10g	2.28	2.45	24.5	23.3	5.15	

SAR Room 4

Date Tested	System Dipole		T.S. Liquid	Measured Results			Target (Ref. Value)	Delta $\pm 10\%$	Est./Zoom Ratio	Plot No.
	Type	Serial #		Area Scan	Zoom Scan	Normalize to 1 W				
5/28/2014	D1900V2	5d043	Head	1g	4.08	3.97	39.7	40.1	-1.00	2.70
				10g	2.10	2.06	20.6	21.1	-2.37	
5/28/2014	D1900V2	5d043	Body	1g	4.05	4.04	40.4	39.0	3.59	0.25
				10g	2.04	2.11	21.1	20.8	1.44	

12. SAR Test Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:

With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

KDB 941225 D01 SAR test for 3G devices:

Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least $\frac{1}{4}$ dB higher than that measured without HSPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2.

KDB 648474 D04 Handset SAR:

Additional 1-g SAR testing at 5 mm is not required. For hotspot mode, 10-g extremity SAR is not required for the surfaces and edges since all 1-g reported SAR < 1.2 W/kg.

12.1. GSM850

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	190	836.6	33.5	33.1	0.104	0.114	1
			Left Tilt	190	836.6	33.5	33.1	0.054	0.059	
			Right Touch	190	836.6	33.5	33.1	0.104	0.114	
			Rightt Tilt	190	836.6	33.5	33.1	0.055	0.060	
Head VoIP	GPRS 2 Slots	0	Left Touch	190	836.6	31.5	31.3	0.197	0.206	2
			Left Tilt	190	836.6	31.5	31.3	0.096	0.100	
			Right Touch	190	836.6	31.5	31.3	0.181	0.190	
			Rightt Tilt	190	836.6	31.5	31.3	0.100	0.104	
Body-worn	Voice	10	Rear	190	836.6	33.5	33.1	0.305	0.334	3
			Front	190	836.6	33.5	33.1	0.114	0.125	
Body-worn(VoIP) & Hotspot	GPRS 2 Slots	10	Rear	190	836.6	31.5	31.3	0.511	0.535	4
			Front	190	836.6	31.5	31.3	0.193	0.202	
			Edge 2	190	836.6	31.5	31.3	0.124	0.130	
Hotspot			Edge 3	190	836.6	31.5	31.3	0.251	0.263	

12.2. GSM1900

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	661	1880.0	29.0	28.6	0.059	0.065	
			Left Tilt	661	1880.0	29.0	28.6	0.043	0.047	
			Right Touch	661	1880.0	29.0	28.6	0.086	0.095	5
			Rightt Tilt	661	1880.0	29.0	28.6	0.039	0.043	
Head VoIP	GPRS 4 Slots	0	Left Touch	661	1880.0	26.0	25.7	0.100	0.107	
			Left Tilt	661	1880.0	26.0	25.7	0.076	0.081	
			Right Touch	661	1880.0	26.0	25.7	0.158	0.169	6
			Rightt Tilt	661	1880.0	26.0	25.7	0.072	0.077	
Body-worn	Voice	10	Rear	661	1880.0	29.0	28.6	0.401	0.440	7
			Front	661	1880.0	29.0	28.6	0.230	0.252	
Body-worn(VoIP) & Hotspot	GPRS 4 Slots	10	Rear	512	1850.2	26.0	26.0	0.792	0.792	
				661	1880.0	26.0	25.7	0.753	0.807	
				810	1909.8	26.0	25.4	0.708	0.813	8
			Front	661	1880.0	26.0	25.7	0.446	0.478	
Hotspot			Edge 2	661	1880.0	26.0	25.7	0.219	0.235	
			Edge 3	661	1880.0	26.0	25.7	0.475	0.509	

12.3. W-CDMA Band V

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	4183	836.6	23.5	23.1	0.103	0.113	9
			Left Tilt	4183	836.6	23.5	23.1	0.055	0.060	
			Right Touch	4183	836.6	23.5	23.1	0.099	0.109	
			Rightt Tilt	4183	836.6	23.5	23.1	0.057	0.062	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	4183	836.6	23.5	23.1	0.308	0.338	10
			Front	4183	836.6	23.5	23.1	0.118	0.129	
Hotspot	Rel 99 RMC	10	Edge 2	4183	836.6	23.5	23.1	0.090	0.099	
			Edge 3	4183	836.6	23.5	23.1	0.150	0.164	

12.4. W-CDMA Band II

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	9400	1880.0	22.0	21.6	0.079	0.086	
			Left Tilt	9400	1880.0	22.0	21.6	0.062	0.067	
			Right Touch	9400	1880.0	22.0	21.6	0.124	0.135	11
			Right Tilt	9400	1880.0	22.0	21.6	0.061	0.066	
Body-worn & Hotspot	Rel 99 RMC	10	Rear	9400	1880.0	22.0	21.6	0.722	0.786	12
			Front	9400	1880.0	22.0	21.6	0.389	0.424	
Hotspot	Rel 99 RMC	10	Edge 2	9400	1880.0	22.0	21.6	0.191	0.208	
			Edge 3	9400	1880.0	22.0	21.6	0.376	0.409	

12.5. Wi-Fi (DTS Band)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	802.11b 1 Mbps	0	Left Touch	6	2437.0	16.5	16.5	0.081	0.081	13
			Left Tilt	6	2437.0	16.5	16.5	0.023	0.023	
			Right Touch	6	2437.0	16.5	16.5	0.054	0.054	
			Right Tilt	6	2437.0	16.5	16.5	0.024	0.024	
Body-worn & Hotspot	802.11b 1 Mbps	10	Rear	6	2437.0	16.5	16.5	0.174	0.174	14
			Front	6	2437.0	16.5	16.5	0.009	0.009	
Hotspot	802.11b 1 Mbps	10	Edge 4	6	2437.0	16.5	16.5	0.058	0.058	

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	802.11a 6 Mbps	0	Left Touch	157	5785.0	12.5	12.5	0.010	0.010	
			Left Tilt	157	5785.0	12.5	12.5	0.003	0.003	
			Right Touch	157	5785.0	12.5	12.5	0.013	0.013	15
			Right Tilt	157	5785.0	12.5	12.5	0.008	0.008	
Body-worn & Hotspot	802.11a 6 Mbps	10	Rear	157	5785.0	12.5	12.5	0.135	0.135	16
			Front	157	5785.0	12.5	12.5	<0.001	<0.001	
Hotspot	802.11a 6 Mbps	10	Edge 4	157	5785.0	12.5	12.5	0.051	0.051	

12.6. Wi-Fi (UNII Band)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	802.11a 6 Mbps	0	Left Touch	48	5240.0	12.5	12.5	0.039	0.039	17
				64	5320.0	12.5	12.5	0.051	0.051	18
				116	5580.0	12.5	12.5	0.058	0.058	19
			Left Tilt	48	5240.0	12.5	12.5	0.018	0.018	
				64	5320.0	12.5	12.5	0.022	0.022	
				116	5580.0	12.5	12.5	0.018	0.018	
			Right Touch	48	5240.0	12.5	12.5	0.014	0.014	
				64	5320.0	12.5	12.5	0.034	0.034	
				116	5580.0	12.5	12.5	0.038	0.038	
			Right Tilt	48	5240.0	12.5	12.5	0.013	0.013	
				64	5320.0	12.5	12.5	0.024	0.024	
				116	5580.0	12.5	12.5	0.027	0.027	
Body-worn	802.11a 6 Mbps	10	Rear	48	5240.0	12.5	12.5	0.083	0.083	20
				64	5320.0	12.5	12.5	0.144	0.144	21
				116	5580.0	12.5	12.5	0.351	0.351	22
			Front	48	5240.0	12.5	12.5	<0.001	<0.001	
				64	5320.0	12.5	12.5	<0.001	<0.001	
				116	5580.0	12.5	12.5	0.009	0.009	

12.7. Bluetooth

12.7.1. Standalone SAR Test Exclusion Considerations

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Body-worn Accessory Exposure Conditions

Max. tune-up tolerance limit		Min. test separation distance (mm)	Frequency (GHz)	Result
(dBm)	(mW)			
9.5	9	10	2.480	1.4

Conclusion:

The computed value is < 3 ; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

12.7.2. Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}/x}]$ W/kg for test separation distances ≤ 50 mm;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Estimated SAR Result for Body-worn Accessory Conditions:

Test Configuration	Max. tune-up tolerance limit (mW)	Min. test separation distance (mm)	Frequency (GHz)	Estimated 1-g SAR (W/kg)
Rear/Front	9	10	2.480	0.189

13. SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the **ratio of largest to smallest SAR** for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

13.1. The Highest Measured SAR Configuration in Each Frequency Band

Frequency Band (MHz)	Air Interface	Head (W/kg)	Body-worn Accessory (W/kg)	Hotspot/Wi-Fi Direct (W/kg)	Repeated SAR (Yes/No)
850	GSM 850		0.511		No
	WCDMA Band V		0.308		No
1900	GSM 1900		0.792		No
	WCDMA Band II		0.722		No
2400	Wi-Fi 802.11b/g/n		0.174		No
5200	Wi-Fi 802.11a/n		0.083		No
5300	Wi-Fi 802.11a/n		0.144		No
5500	Wi-Fi 802.11a/n		0.351		No
5800	Wi-Fi 802.11a/n		0.135		No

13.2. Repeated Measurement Results

Head Exposure Condition

Not Applicable.

Body-worn Accessory Exposure Condition

Not Applicable.

Hotspot Mode Exposure Conditions

Not Applicable.

Note(s):

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20 .

14. Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance, introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / Ri$$

Where:

SAR₁ is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

Ri is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured for both antennas in the pair, it is determined by the actual x, y, and z coordinates in the 1-g SAR for each SAR Peak Location; based on the extrapolated and interpolated result in the zoom scan measurement using the formula:

$$[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$$

A new threshold of 0.04 is also introduced in the KDB 447498. Thus, in order for a pair of simultaneously transmitting antennas, with the sum of 1-g SAR > 1.6 W/kg, to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / Ri < 0.04$$

14.1. Sum of the SAR for GSM850 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario				Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM850	② Wi-Fi(DTS)	③ Wi-Fi(UNII)	④ Bluetooth		
Head	Left Touch	① + ②	0.206	0.081			0.287	No
		① + ③	0.206		0.058		0.264	No
	Left Tilt	① + ②	0.100	0.023			0.123	No
		① + ③	0.100		0.022		0.122	No
	Right Touch	① + ②	0.190	0.054			0.244	No
		① + ③	0.190		0.038		0.228	No
	Right Tilt	① + ②	0.104	0.024			0.128	No
		① + ③	0.104		0.027		0.131	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.535	0.174			0.709	No
		① + ③	0.535		0.351		0.886	No
		① + ④	0.535			0.189	0.724	No
	Front	① + ②	0.202	0.009			0.211	No
		① + ③	0.202		0.009		0.211	No
		① + ④	0.202			0.189	0.391	No
Hotspot	Edge 1	① + ②					0	No
	Edge 2	① + ②	0.130				0.130	No
	Edge 3	① + ②	0.263				0.263	No
	Edge 4	① + ②		0.058			0.058	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

14.2. Sum of the SAR for GSM1900 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario				Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM 1900	② Wi-Fi(DTS)	③ Wi-Fi(UNII)	④ Bluetooth		
Head	Left Touch	① + ②	0.107	0.081			0.188	No
		① + ③	0.107		0.058		0.165	No
	Left Tilt	① + ②	0.081	0.023			0.104	No
		① + ③	0.081		0.022		0.103	No
	Right Touch	① + ②	0.169	0.054			0.223	No
		① + ③	0.169		0.038		0.207	No
	Right Tilt	① + ②	0.077	0.024			0.101	No
		① + ③	0.077		0.027		0.104	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.813	0.174			0.987	No
		① + ③	0.813		0.351		1.164	No
		① + ④	0.813			0.189	1.002	No
	Front	① + ②	0.478	0.009			0.487	No
		① + ③	0.478		0.009		0.487	No
		① + ④	0.478			0.189	0.667	No
Hotspot	Edge 1	① + ②					0	No
	Edge 2	① + ②	0.235				0.235	No
	Edge 3	① + ②	0.509				0.509	No
	Edge 4	① + ②		0.058			0.058	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

14.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario				Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band V	② Wi-Fi(DTS)	③ Wi-Fi(UNII)	④ Bluetooth		
Head	Left Touch	① + ②	0.113	0.081			0.194	No
		① + ③	0.113		0.058		0.171	No
	Left Tilt	① + ②	0.060	0.023			0.083	No
		① + ③	0.060		0.022		0.082	No
	Right Touch	① + ②	0.109	0.054			0.163	No
		① + ③	0.109		0.038		0.147	No
	Right Tilt	① + ②	0.062	0.024			0.086	No
		① + ③	0.062		0.027		0.089	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.338	0.174			0.512	No
		① + ③	0.338		0.351		0.689	No
		① + ④	0.338			0.189	0.527	No
	Front	① + ②	0.129	0.009			0.138	No
		① + ③	0.129		0.009		0.138	No
		① + ④	0.129			0.189	0.318	No
Hotspot	Edge 1	① + ②					0	No
	Edge 2	① + ②	0.099				0.099	No
	Edge 3	① + ②	0.164				0.164	No
	Edge 4	① + ②		0.058			0.058	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

14.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario				Σ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band II	② Wi-Fi(DTS)	③ Wi-Fi(UNII)	④ Bluetooth		
Head	Left Touch	① + ②	0.086	0.081			0.167	No
		① + ③	0.086		0.058		0.144	No
	Left Tilt	① + ②	0.067	0.023			0.090	No
		① + ③	0.067		0.022		0.089	No
	Right Touch	① + ②	0.135	0.054			0.189	No
		① + ③	0.135		0.038		0.173	No
	Right Tilt	① + ②	0.066	0.024			0.090	No
		① + ③	0.066		0.027		0.093	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.786	0.174			0.960	No
		① + ③	0.786		0.351		1.137	No
		① + ④	0.786			0.189	0.975	No
	Front	① + ②	0.424	0.009			0.433	No
		① + ③	0.424		0.009		0.433	No
		① + ④	0.424			0.189	0.613	No
Hotspot	Edge 1	① + ②					0	No
	Edge 2	① + ②	0.208				0.208	No
	Edge 3	① + ②	0.409				0.409	No
	Edge 4	① + ②		0.058			0.058	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

15. Appendixes

Refer to separated files for the following appendixes.

- 15.1. Photos and Antenna Locations**
- 15.2. System Performance Check Plots**
- 15.3. Highest SAR Test Plots**
- 15.4. Calibration Certificate for E-Field Probe EX3DV4 - SN 3773**
- 15.5. Calibration Certificate for E-Field Probe EX3DV4 - SN 3871**
- 15.6. Calibration Certificate for E-Field Probe EX3DV4 - SN 3936**
- 15.7. Calibration Certificate for D835V2 - SN 4d142**
- 15.8. Calibration Certificate for D1900V2- SN 5d043**
- 15.9. Calibration Certificate for D2450V2 - SN 899**
- 15.10. Calibration Certificate for D5GHzV2 - SN 1138**

END OF REPORT