



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6654  
<http://www.pctestlab.com>



## MEASUREMENT REPORT FCC Part 27 Certification

**Applicant Name:**  
Samsung Electronics, Co. Ltd.  
18600 Broadwick St.  
Rancho Dominguez, CA 90220  
United States

**Date of Testing:**  
10/25/11 - 11/03/11  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1110211867.A3L

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>FCC ID:</b>               | <b>A3LGTI9250M</b>                   |
| <b>IC CERTIFICATION NO.:</b> | <b>649E-GTI9250M</b>                 |
| <b>APPLICANT:</b>            | <b>Samsung Electronics, Co. Ltd.</b> |

**Application Type:** Certification  
**FCC Classification:** PCS Licensed Transmitter Held to Ear (PCE)  
**FCC Rule Part(s):** §2; §27 Subpart L  
**EUT Type:** Portable Handset  
**Model(s):** GT-I9250M  
**Tx Frequency Range:** 1712.4 - 1752.5MHz (WCDMA)  
**Max. RF Output Power:** 0.158 W EIRP WCDMA (21.98 dBm)  
**Emission Designator(s):** 4M08F9W  
**Test Device Serial No.:** *identical prototype* [S/N: FI 262 C]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is EIRP for Part 27.

*PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

  
Randy Ortanez  
President




|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          | Page 1 of 24                                                                          |                                 |

# TABLE OF CONTENTS


|                                                               |    |
|---------------------------------------------------------------|----|
| FCC PART 27 MEASUREMENT REPORT .....                          | 3  |
| 1.0 INTRODUCTION .....                                        | 4  |
| 1.1 SCOPE .....                                               | 4  |
| 1.2 TESTING FACILITY .....                                    | 4  |
| 2.0 PRODUCT INFORMATION .....                                 | 5  |
| 2.1 EQUIPMENT DESCRIPTION .....                               | 5  |
| 2.2 DEVICE CAPABILITIES .....                                 | 5  |
| 2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....             | 5  |
| 2.4 LABELING REQUIREMENTS .....                               | 5  |
| 3.0 DESCRIPTION OF TESTS .....                                | 6  |
| 3.1 MEASUREMENT PROCEDURE .....                               | 6  |
| 3.2 OCCUPIED BANDWIDTH EMISSION LIMITS .....                  | 6  |
| 3.3 AWS - BASE FREQUENCY BLOCKS .....                         | 6  |
| 3.4 AWS - MOBILE FREQUENCY BLOCKS .....                       | 7  |
| 3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL ..... | 7  |
| 3.6 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....      | 7  |
| 3.7 PEAK-AVERAGE RATIO .....                                  | 7  |
| 3.8 FREQUENCY STABILITY / TEMPERATURE VARIATION .....         | 8  |
| 4.0 TEST EQUIPMENT CALIBRATION DATA .....                     | 9  |
| 5.0 SAMPLE CALCULATIONS .....                                 | 10 |
| 6.0 TEST RESULTS .....                                        | 11 |
| 6.1 SUMMARY .....                                             | 11 |
| 6.2 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA .....     | 12 |
| 6.3 AWS WCDMA RADIATED MEASUREMENTS .....                     | 13 |
| 6.4 AWS WCDMA FREQUENCY STABILITY MEASUREMENTS .....          | 16 |
| 7.0 PLOT(S) OF EMISSIONS .....                                | 18 |
| 8.0 CONCLUSION .....                                          | 24 |

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 2 of 24                    |



## MEASUREMENT REPORT

### FCC Part 27




#### §2.1033 General Information

**APPLICANT:** Samsung Electronics, Co. Ltd.  
**APPLICANT ADDRESS:** 18600 Broadwick St.  
 Rancho Dominguez, CA 90220  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §27  
**BASE MODEL:** GT-I9250M  
**FCC ID:** A3LGTI9250M  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
**EMISSION DESIGNATOR(S):** 4M08F9W  
**MODE:** WCDMA  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** FI 262 C ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** 10/25/11 - 11/03/11  
**TEST REPORT S/N:** 0Y1110211867.A3L

#### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 3 of 24                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT19250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 4 of 24                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LGTI9250M**. The test data contained in this report pertains only to the emissions due to the EUT's AWS WCDMA function. The EUT consisted of the following component(s):

| Trade Name / Base Model    | FCC ID      | Description      |
|----------------------------|-------------|------------------|
| Samsung / Model: GT-I9250M | A3LGTI9250M | Portable Handset |

Table 2-1. EUT Equipment Description

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, 802.11a/b/g/n WLAN, 802.11a/n UNII, Bluetooth, NFC

### 2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.4 Labeling Requirements

#### Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase..

#### Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).


Please see attachment for FCC ID label and label location.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 5 of 24                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure 3-1. Diagram of 3-meter outdoor test range**

Deviation from Measurement Procedure.....None


### 3.2 Occupied Bandwidth Emission Limits

§2.1049, §27.53(g)(1)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

### 3.3 AWS - Base Frequency Blocks


§27.5(h)



|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 6 of 24                    |

### 3.4 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 6: 1745 – 1755 MHz (F)

### 3.5 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, §27.53(q)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic.

### 3.6 Radiated Power and Radiated Spurious Emissions

§2.1053, §27.53(q)

Spurious and harmonic radiated emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all configurations and the worst case is reported with HSDPA Active at 12.2 kbps RMC with TPC bits all set to "1".

### 3.7 Peak-Average Ratio

§27.50(d)(5)

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 7 of 24                    |

### 3.8 Frequency Stability / Temperature Variation

§2.1055, §27.54

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.*

#### Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 8 of 24                    |

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer      | Model     | Description                        | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-------------------|-----------|------------------------------------|------------|--------------|------------|---------------|
| -                 | 263-10dB  | (DC-18GHz) 10 dB Attenuator        | N/A        |              | N/A        | N/A           |
| -                 | No.166    | (1000-26500MHz) Microwave RF Cable | N/A        |              | N/A        | N/A           |
| -                 | No.167    | (100kHz - 100MHz) RG58 Coax Cable  | N/A        |              | N/A        | N/A           |
| Agilent           | 8449B     | (1-26.5GHz) Pre-Amplifier          | 2/8/2011   | Annual       | 2/8/2012   | 3008A00985    |
| Agilent           | 85650A    | Quasi-Peak Adapter                 | 4/7/2011   | Annual       | 4/7/2012   | 3303A01872    |
| Agilent           | 85650A    | Quasi-Peak Adapter                 | 4/7/2011   | Annual       | 4/7/2012   | 2043A00301    |
| Agilent           | 8566B     | (100Hz-22GHz) Spectrum Analyzer    | 4/7/2011   | Annual       | 4/7/2012   | 3638A08713    |
| Agilent           | 8648D     | (9kHz-4GHz) Signal Generator       | 10/10/2011 | Annual       | 10/10/2012 | 3613A00315    |
| Agilent           | E4407B    | ESA Spectrum Analyzer              | 4/5/2011   | Annual       | 4/5/2012   | US39210313    |
| Agilent           | E4448A    | PSA (3Hz-50GHz) Spectrum Analyzer  | 11/30/2010 | Annual       | 11/30/2011 | US42510244    |
| Agilent           | E5515C    | Wireless Communications Test Set   | 10/10/2011 | Annual       | 10/10/2012 | GB46110872    |
| Agilent           | E5515C    | Wireless Communications Test Set   | 7/6/2011   | Annual       | 7/6/2012   | GB41450275    |
| Agilent           | E8257D    | (250kHz-20GHz) Signal Generator    | 4/8/2011   | Annual       | 4/8/2012   | MY45470194    |
| Agilent           | E8267C    | Vector Signal Generator            | 10/10/2011 | Annual       | 10/10/2012 | US42340152    |
| Agilent           | N9020A    | MXA Signal Analyzer                | 10/10/2011 | Annual       | 10/10/2012 | US46470561    |
| Agilent           | E5515C    | Wireless Communications Test Set   | 2/8/2011   | Annual       | 2/8/2012   | GB45360985    |
| Agilent           | N9038A    | MXE EMI Receiver                   | 8/5/2011   | Annual       | 8/5/2012   | MY51210133    |
| Anritsu           | MA2411B   | Pulse Sensor                       | 10/13/2011 | Annual       | 10/13/2012 | 1027293       |
| Anritsu           | ML2495A   | Power Meter                        | 10/13/2011 | Annual       | 10/13/2012 | 1039008       |
| Compliance Design | Roberts   | Dipole Set                         | 4/7/2010   | Biennial     | 4/7/2012   | 146           |
| Compliance Design | Roberts   | Dipole Set                         | 4/7/2010   | Biennial     | 4/7/2012   | 147           |
| Emco              | 3115      | Horn Antenna (1-18GHz)             | 4/8/2010   | Biennial     | 4/8/2012   | 9205-3874     |
| Espec             | ESX-2CA   | Environmental Chamber              | 4/21/2011  | Annual       | 4/21/2012  | 17620         |
| Gigatronics       | 80701A    | (0.05-18GHz) Power Sensor          | 10/12/2011 | Annual       | 10/12/2012 | 1833460       |
| Gigatronics       | 8651A     | Universal Power Meter              | 10/12/2011 | Annual       | 10/12/2012 | 8650319       |
| K & L             | 11SH10    | Band Pass Filter                   | N/A        |              | N/A        | 1300/4000     |
| K & L             | 11SH10    | Band Pass Filter                   | N/A        |              | N/A        | 4000/12000    |
| MiniCircuits      | VHF-1300+ | High Pass Filter                   | N/A        |              | N/A        | 30716         |
| MiniCircuits      | VHF-3100+ | High Pass Filter                   | N/A        |              | N/A        | 30721         |
| Pasternack        | PE2208-6  | Bidirectional Coupler              | N/A        |              | N/A        | N/A           |
| Rohde & Schwarz   | CMU200    | Base Station Simulator             | 11/11/2010 | Annual       | 11/11/2011 | 836371/0079   |
| Rohde & Schwarz   | CMU200    | Base Station Simulator             | 6/1/2011   | Annual       | 6/1/2012   | 833855/0010   |
| Rohde & Schwarz   | CMU200    | Base Station Simulator             | 4/19/2011  | Annual       | 4/19/2012  | 107826        |
| Rohde & Schwarz   | CMU200    | Base Station Simulator             | N/A        |              | N/A        | 836536/0005   |
| Rohde & Schwarz   | CMW500    | LTE Radio Communication Tester     | 8/25/2011  | Annual       | 8/25/2012  | 100976        |
| Rohde & Schwarz   | CMW500    | LTE Radio Communication Tester     | 10/7/2011  | Annual       | 10/7/2012  | 103962        |
| Rohde & Schwarz   | CMW500    | LTE Radio Communication Tester     | 8/5/2011   | Annual       | 8/5/2012   | 112347        |
| Schwarzbeck       | UHA 9105  | Dipole Antenna (400 - 1GHz) Tx     | 10/3/2011  | Biennial     | 10/3/2013  | 91052522TX    |
| Schwarzbeck       | UHA 9105  | Dipole Antenna (400 - 1GHz) Rx     | 10/3/2011  | Biennial     | 10/3/2013  | 91052523RX    |
| Sunol             | DRH-118   | Horn Antenna (1 - 18GHz)           | 7/5/2011   | Biennial     | 7/5/2013   | A050307       |
| Sunol             | JB5       | Bi-Log Antenna (30M - 5GHz)        | 12/17/2009 | Biennial     | 12/17/2011 | A051107       |
| Sunol             | DRH-118   | Horn Antenna (1-18 GHz)            | 6/17/2011  | Biennial     | 6/17/2013  | A042511       |

Table 4-1. Test Equipment

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 9 of 24                    |

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 4M15F9W**

WCDMA BW = 4.15 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission – AWS Band

**Example: Channel 1412 AWS Mode 2<sup>nd</sup> Harmonic (3464.80 MHz)**

The spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminal is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3464.80 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 10 of 24                   |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Samsung Electronics, Co. Ltd.  
 FCC ID: A3LGTI9250M  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): WCDMA

| FCC Part Section(s)          | Test Description                         | Test Limit                                                                           | Test Condition | Test Result | Reference          |
|------------------------------|------------------------------------------|--------------------------------------------------------------------------------------|----------------|-------------|--------------------|
| <b>TRANSMITTER MODE (TX)</b> |                                          |                                                                                      |                |             |                    |
| 2.1049, 27.53(g)(1)          | Occupied Bandwidth                       | N/A                                                                                  | CONDUCTED      | PASS        | Section 7.0        |
| 2.1051, 27.53(g)             | Band Edge / Conducted Spurious Emissions | $< 43 + 10\log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions |                | PASS        | Section 7.0        |
| 2.1046                       | Transmitter Conducted Output Power       | N/A                                                                                  |                | PASS        | RF Exposure Report |
| 27.50(d)(2)                  | Equivalent Isotropic Radiated Power      | $< 1$ Watts max. EIRP                                                                | RADIATED       | PASS        | Section 6.2        |
| 2.1053, 27.53(g)             | Undesirable Emissions                    | $< 43 + 10\log_{10}(P[\text{Watts}])$ for all out-of-band emissions                  |                | PASS        | Section 6.3        |
| 2.1055, 27.54                | Frequency Stability                      | $< 2.5$ ppm                                                                          |                | PASS        | Section 6.4        |

**Table 6-1. Summary of Test Results**

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          | Page 11 of 24                                                                         |                                 |

## 6.2 Equivalent Isotropic Radiated Power Output Data

§27.50(d)(2)

| Frequency [MHz] | Mode    | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | EIRP [dBm] | EIRP [Watts] | Battery Type |
|-----------------|---------|----------------------|------------------------|--------------------|-----------|------------|--------------|--------------|
| 1712.40         | AWS1700 | -18.240              | 13.72                  | 8.00               | H         | 21.72      | 0.149        | Standard     |
| 1732.40         | AWS1700 | -19.610              | 12.35                  | 8.00               | H         | 20.35      | 0.108        | Standard     |
| 1752.50         | AWS1700 | -17.980              | 13.98                  | 8.00               | H         | 21.98      | 0.158        | Standard     |

**Table 6-2. Equivalent Isotropic Radiated Power Output Data**

### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the worst case is reported with HSDPA Active at 12.2 kbps RMC with TPC bits all set to "1". This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal configuration. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 12 of 24                   |

### 6.3 AWS WCDMA Radiated Measurements §2.1053, §27.53(g)

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1712.40 MHz  
 CHANNEL: 1312  
 MEASURED OUTPUT POWER: 21.720 dBm = 0.149 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  34.73 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3424.80         | -41.24                          | 9.35                          | -31.90                        | H         | 53.6  |
| 5137.20         | -53.38                          | 10.96                         | -42.42                        | H         | 64.1  |
| 6849.60         | -85.12                          | 10.52                         | -74.60                        | H         | 96.3  |
| 8562.00         | -81.59                          | 11.07                         | -70.52                        | H         | 92.2  |
| 10274.40        | -80.88                          | 12.47                         | -68.41                        | H         | 90.1  |

**Table 6-3. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the worst case is reported with HSDPA Active at 12.2 kbps RMC with TPC bits all set to "1". This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal configuration. The data reported in the table above was measured in this test setup.

|                                     |                                                                                     |                                                        |                                                                                       |                                 |
|-------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                 |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 13 of 24                   |

## AWS WCDMA Radiated Measurements (Cont'd)

### §2.1053, §27.53(g)

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1732.40 MHz  
CHANNEL: 1412  
MEASURED OUTPUT POWER: 20.350 dBm = 0.108 W  
MODULATION SIGNAL: WCDMA (Internal)  
DISTANCE: 3 meters  
LIMIT:  $43 + 10 \log_{10} (W) =$  33.35 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3464.80         | -40.46                          | 9.47                          | -30.99                        | H         | 51.3  |
| 5197.20         | -53.47                          | 10.87                         | -42.60                        | H         | 63.0  |
| 6929.60         | -85.34                          | 10.68                         | -74.66                        | H         | 95.0  |
| 8662.00         | -81.68                          | 11.25                         | -70.43                        | H         | 90.8  |
| 10394.40        | -80.74                          | 12.52                         | -68.22                        | H         | 88.6  |

Table 6-4. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1412)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the worst case is reported with HSDPA Active at 12.2 kbps RMC with TPC bits all set to "1". This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal configuration. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                     |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                       |                                                                                       | Page 14 of 24                   |

## AWS WCDMA Radiated Measurements (Cont'd)

### §2.1053, §27.53(g)

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1752.50 MHz  
 CHANNEL: 1862  
 MEASURED OUTPUT POWER: 21.980 dBm = 0.158 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  34.99 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3505.00         | -46.44                          | 9.58                          | -36.86                        | H         | 58.8  |
| 5257.50         | -51.63                          | 10.57                         | -41.06                        | H         | 63.0  |
| 7010.00         | -85.58                          | 10.86                         | -74.73                        | H         | 96.7  |
| 8762.50         | -81.93                          | 11.50                         | -70.43                        | H         | 92.4  |
| 10515.00        | -80.53                          | 12.55                         | -67.97                        | H         | 90.0  |

Table 6-5. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1862)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the worst case is reported with HSDPA Active at 12.2 kbps RMC with TPC bits all set to "1". This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the horizontal configuration. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          | Page 15 of 24                                                                         |                                 |

## 6.4 AWS WCDMA Frequency Stability Measurements

§2.1055, §27.54

OPERATING FREQUENCY: 1,732,400,000 Hz

CHANNEL: 1412

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm


| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 3.70        | + 20 (Ref) | 1,732,399,989  | -11.00          | -0.000001     |
| 100 %          |             | - 30       | 1,732,399,984  | -16.00          | -0.000001     |
| 100 %          |             | - 20       | 1,732,399,981  | -19.00          | -0.000001     |
| 100 %          |             | - 10       | 1,732,399,980  | -20.00          | -0.000001     |
| 100 %          |             | 0          | 1,732,400,011  | 11.00           | 0.000001      |
| 100 %          |             | + 10       | 1,732,400,015  | 15.00           | 0.000001      |
| 100 %          |             | + 20       | 1,732,400,008  | 8.00            | 0.000000      |
| 100 %          |             | + 30       | 1,732,400,009  | 9.00            | 0.000001      |
| 100 %          |             | + 40       | 1,732,399,990  | -10.00          | -0.000001     |
| 100 %          |             | + 50       | 1,732,399,981  | -19.00          | -0.000001     |
| 115 %          | 4.26        | + 20       | 1,732,399,991  | -9.00           | -0.000001     |
| BATT. ENDPOINT | 3.40        | + 20       | 1,732,399,983  | -17.00          | -0.000001     |

Table 6-6. Frequency Stability Data (AWS WCDMA Mode – Ch. 1412)

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          | Page 16 of 24                                                                         |                                 |

## AWS WCDMA Frequency Stability Measurements (Cont'd)


§2.1055, §27.54




**Figure 6-1. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1412)**

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 17 of 24                   |

## 7.0 PLOT(S) OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-2. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 18 of 24                   |




Plot 7-3. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)



Plot 7-4. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 19 of 24                   |




Plot 7-5. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-6. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT19250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 20 of 24                   |




Plot 7-7. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)



Plot 7-8. Peak-Average Ratio Plot (AWS WCDMA Mode – Ch. 1412)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT9250M                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 21 of 24                   |



Plot 7-9. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)




Plot 7-10. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 22 of 24                   |



Plot 7-11. Band Edge Plot (AWS WCDMA Mode – Ch. 1862)



Plot 7-12. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1862)

|                                      |                                               |                                                        |                |                                 |
|--------------------------------------|-----------------------------------------------|--------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9250M                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11            | EUT Type:<br>Portable Handset                          |                | Page 23 of 24                   |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LGTI9250M** complies with all the requirements of Parts 2 and 27 of the FCC rules.

|                                      |                                                                                     |                                                        |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9250M                  |  | FCC Pt. 27 WCDMA MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1110211867.A3L | Test Dates:<br>10/25/11 - 11/03/11                                                  | EUT Type:<br>Portable Handset                          |                                                                                       | Page 24 of 24                   |