



## MEASUREMENT REPORT

### FCC PART 15.247 / IC RSS-210 Bluetooth

**Applicant Name:**

Samsung Electronics Co., Ltd.  
416 Maetan 3-Dong, Yeongtong-gu  
Suwon-si, Gyeonggi-do  
443-742, Republic of Korea

**Date of Testing:**

04/27 - 05/09/2012

**Test Site/Location:**

PCTEST Lab. Columbia, MD, USA

**Test Report Serial No.:**

0Y1205100658.A3L

**FCC ID:**

A3LGTI9300A

**APPLICANT:**

Samsung Electronics Co., Ltd.

**Application Type:**

Certification

**Model(s):**

GT-I9300

**EUT Type:**

Portable Handset

**Max. RF Output Power:**

7.328 mW (8.65dBm) Conducted

**Frequency Range:**

2402 – 2480MHz (Bluetooth for US)

**Type of Modulation:**

GFSK,  $\pi/4$ -DQPSK, 8DPSK

**FCC Classification:**

FCC Part 15 Spread Spectrum Transmitter (DSS)

**FCC Rule Part(s):**

Part 15 Subpart C (15.247)

**IC Specification(s):**

RSS-210 Issue 8

**Test Procedure(s):**

ANSI C63.4-2003, DA 00-705

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 and DA 00-705. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 1 of 35                    |

## TABLE OF CONTENTS


|                                                       |    |
|-------------------------------------------------------|----|
| FCC PART 15.247 MEASUREMENT REPORT .....              | 3  |
| 1.0 INTRODUCTION.....                                 | 4  |
| 1.1 SCOPE.....                                        | 4  |
| 1.2 PCTEST TEST LOCATION.....                         | 4  |
| 2.0 PRODUCT INFORMATION .....                         | 5  |
| 2.1 EQUIPMENT DESCRIPTION.....                        | 5  |
| 2.2 DEVICE CAPABILITIES.....                          | 5  |
| 2.3 TEST CONFIGURATION .....                          | 5  |
| 2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....      | 5  |
| 2.5 LABELING REQUIREMENTS.....                        | 5  |
| 3.0 DESCRIPTION OF TEST .....                         | 6  |
| 3.1 EVALUATION PROCEDURE.....                         | 6  |
| 3.2 AC LINE CONDUCTED EMISSIONS.....                  | 6  |
| 3.3 RADIATED EMISSIONS .....                          | 7  |
| 4.0 ANTENNA REQUIREMENTS .....                        | 8  |
| 5.0 TEST EQUIPMENT CALIBRATION DATA.....              | 9  |
| 6.0 TEST RESULTS .....                                | 10 |
| 6.1 SUMMARY .....                                     | 10 |
| 6.2 20DB BANDWIDTH MEASUREMENT .....                  | 11 |
| 6.3 OUTPUT POWER MEASUREMENT .....                    | 17 |
| 6.4 BAND EDGE COMPLIANCE.....                         | 18 |
| 6.5 CARRIER FREQUENCY SEPARATION.....                 | 21 |
| 6.6 TIME OF OCCUPANCY .....                           | 22 |
| 6.7 NUMBER OF HOPPING CHANNELS.....                   | 23 |
| 6.8 CONDUCTED SPURIOUS EMISSIONS.....                 | 24 |
| 6.9 RADIATED SPURIOUS EMISSION MEASUREMENTS.....      | 28 |
| 6.10 RADIATED RESTRICTED BAND EDGE MEASUREMENTS ..... | 32 |
| 6.11 LINE CONDUCTED MEASUREMENT DATA .....            | 33 |
| 7.0 CONCLUSION .....                                  | 35 |

|                                             |                                                                                     |                                                                 |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTI9300A                  |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1205100658.A3L | <b>Test Dates:</b><br>04/27 - 05/09/2012                                            | <b>EUT Type:</b><br>Portable Handset                            |                                                                                       | Page 2 of 35                           |



# MEASUREMENT REPORT

## FCC Part 15.247



### § 2.1033 General Information

**APPLICANT:** Samsung Electronics Co., Ltd.

**APPLICANT ADDRESS:** 416 Maetan 3-Dong, Yeongtong-gu  
Suwon-si, Gyeonggi-do, 443-742, Republic of Korea

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA

**FCC RULE PART(S):** Part 15 Subpart C (15.247)

**IC SPECIFICATION(S):** RSS-210 Issue 8

**BASE MODEL:** GT-I9300

**FCC ID:** A3LGTI9300A

**Test Device Serial No.:** PCT-003, PCT-007 ☐ Production ☒ Pre-Production ☐ Engineering

**FCC CLASSIFICATION:** FCC Part 15 Spread Spectrum Transmitter (DSS)

**Method/System:** Frequency Hopping Spread Spectrum (FHSS)

**DATE(S) OF TEST:** 04/27 - 05/09/2012

**TEST REPORT S/N:** 0Y1205100658.A3L

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



|                                             |                                                                                     |                                                             |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTI9300A                  |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1205100658.A3L | <b>Test Dates:</b><br>04/27 - 05/09/2012                                            | <b>EUT Type:</b><br>Portable Handset                        |                                                                                       | Page 3 of 35                           |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 4 of 35                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LGTI9300A**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, 802.11a/b/g/n WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

### 2.3 Test Configuration

The Samsung Portable Handset FCC ID: A3LGTI9300A was tested per the guidance of DA 00-705. See Sections 3.2, 3.3, and 6.1 of this test report for a description of the AC line conducted emissions, radiated emissions, and antenna port conducted emissions test setups, respectively.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2). Please see attachment for FCC ID label and label location.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 5 of 35                    |

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and the "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" (DA 00-705) were used in the measurement of the **Samsung Portable Handset FCC ID: A3LGTI9300A**.

Deviation from measurement procedure.....None

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.11. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.

|                                      |                                                                                     |                                                         |  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |  |                                                                                       | Page 6 of 35                    |

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions. To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. For average measurements above 1GHz, the analyzer was set to peak detector with a reduced VBW setting (RBW = 1MHz, VBW = 10Hz).

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 7 of 35                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Samsung Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The **Samsung Portable Handset FCC ID: A3LGTI9300A** unit complies with the requirement of §15.203.

| Ch. | Frequency (MHz) |
|-----|-----------------|
| 00  | 2402            |
| :   | :               |
| 39  | 2441            |
| :   | :               |
| 78  | 2480            |

**Table 4-1. Frequency/ Channel Operations**

|                                             |                                                                                     |                                                                 |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTI9300A                  |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1205100658.A3L | <b>Test Dates:</b><br>04/27 - 05/09/2012                                            | <b>EUT Type:</b><br>Portable Handset                            |                                                                                       | Page 8 of 35                           |

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer      | Model            | Description                            | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-------------------|------------------|----------------------------------------|------------|--------------|------------|---------------|
| -                 | BT2              | Bluetooth Cable Set                    | 1/15/2012  | Annual       | 1/15/2013  | N/A           |
| -                 | RE1              | Radiated Emissions Cable Set (UHF/EHF) | 6/7/2011   | Annual       | 6/7/2012   | N/A           |
| -                 | RE2              | Radiated Emissions Cable Set (VHF/UHF) | 2/13/2012  | Annual       | 2/13/2013  | N/A           |
| Agilent           | 8447D            | Broadband Amplifier                    | 5/8/2012   | Annual       | 5/8/2013   | 2443A01900    |
| Agilent           | N9020A           | MXA Signal Analyzer                    | 10/10/2011 | Annual       | 10/10/2012 | US46470561    |
| Agilent           | N4010A           | Wireless Connectivity Test Set         | N/A        |              | N/A        | GB46170464    |
| ETS Lindgren      | 3117             | 1-18 GHz DRG Horn (Medium)             | 7/22/2011  | Annual       | 7/22/2012  | 125518        |
| ETS Lindgren      | 3160-09          | 18-26.5 GHz Standard Gain Horn         | 5/31/2011  | Annual       | 5/31/2012  | 135427        |
| Mini-Circuits     | VHF-3100+        | High Pass Filter                       | 1/15/2012  | Annual       | 1/15/2013  | 30841         |
| Rohde & Schwarz   | RS-PR18          | 1-18 GHz Pre-Amplifier                 | 6/9/2011   | Annual       | 6/9/2012   | 100071        |
| Rohde & Schwarz   | RS-PR26          | 18-26.5 GHz Pre-Amplifier              | 6/9/2011   | Annual       | 6/9/2012   | 100040        |
| Rohde & Schwarz   | ESU26            | EMI Test Receiver                      | 12/15/2011 | Annual       | 12/15/2012 | 100342        |
| Solar Electronics | 8012-50-R-24-BNC | LISN                                   | 6/23/2011  | Biennial     | 6/23/2013  | 310233        |
| Sunol             | JB5              | Bi-Log Antenna (30M - 5GHz)            | 1/26/2012  | Biennial     | 1/26/2014  | A051107       |

**Table 5-1. Annual Test Equipment Calibration Schedule**

**Note:**

Equipment used for signaling with a calibration date of "N/A" shown in this list was only used for maintaining a link between the piece of equipment and the EUT. This equipment was not used to make direct calibrated measurements.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 9 of 35                    |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LGTI9300A  
 Method/System: Frequency Hopping Spread Spectrum (FHSS)  
 Number of Channels: 79

| FCC Part Section(s)                        | RSS Section(s)    | Test Description                                                               | Test Limit                                                                                              | Test Condition                   | Test Result | Reference                 |
|--------------------------------------------|-------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|----------------------------------|-------------|---------------------------|
| <b>TRANSMITTER MODE (Tx)</b>               |                   |                                                                                |                                                                                                         |                                  |             |                           |
| 15.247(a)(1)(iii)                          | RSS-210 [A8.1]    | 20dB Bandwidth                                                                 | < 1 MHz only if using less than 15 non-overlapping channels                                             | CONDUCTED                        | PASS        | Section 6.2               |
| 15.247(b)(1)                               | RSS-210 [A8.4(2)] | Peak Transmitter Output Power                                                  | < 1 Watt if $\geq 75$ non-overlapping channels used                                                     |                                  | PASS        | Section 6.3               |
| 15.247(a)(1)                               | RSS-210 [A8.1(2)] | Channel Separation                                                             | > 2/3 of 20 dB BW for systems with Output Power < 125mW                                                 |                                  | PASS        | Section 6.5               |
| 15.247(a)(1)(iii)                          | RSS-210 [A8.1(4)] | Number of Channels                                                             | > 15 Channels                                                                                           |                                  | PASS        | Section 6.7               |
| 15.247(a)(1)(iii)                          | RSS-210 [A8.1(4)] | Time of Occupancy                                                              | < 0.4 sec in 31.6 sec period                                                                            |                                  | PASS        | Section 6.6               |
| 15.247(d)                                  | RSS-210 [A8.5]    | Band Edge / Out-of-Band Emissions                                              | Conducted < 20dBc                                                                                       |                                  | PASS        | Section 6.4, Section 6.8  |
| 15.205<br>15.209                           | RSS-210 [A8.5]    | General Field Strength Limits (Restricted Bands and Radiated Emission Limits)  | Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits) | RADIATED                         | PASS        | Section 6.9, Section 6.10 |
| 15.207                                     | RSS-Gen [7.2.2]   | AC Conducted Emissions 150kHz – 30MHz                                          | < FCC 15.207 limits or < RSS-Gen table 2 limits                                                         | LINE CONDUCTED                   | PASS        | Section 6.11              |
| <b>RECEIVER MODE (Rx) / DIGITAL DEVICE</b> |                   |                                                                                |                                                                                                         |                                  |             |                           |
| 15.107                                     | RSS-Gen [7.2.2]   | AC Conducted Emissions 150kHz – 30MHz                                          | < FCC 15.107 limits or < RSS-Gen table 2 limits                                                         | LINE CONDUCTED                   | PASS        | Part 15B Test Report      |
| 15.109                                     | RSS-Gen [7.2.3.2] | General Field Strength Limits (Restricted Bands and Radiated Emissions Limits) | < FCC 15.109 limits or < RSS-Gen limits [Section 6; Table1]                                             | RADIATED (30MHz-1GHz) (1-25 GHz) | PASS        | Part 15B Test Report      |

**Table 6-1. Summary of Test Results**

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

|                                      |                                                                                     |                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                        |                                                                                       | Page 10 of 35                   |

## 6.2 20dB Bandwidth Measurement

### §15.247 (a)(1)(iii); RSS-210 (A8.1)

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible 20dB bandwidth is 1 MHz, unless more than 15 non-overlapping channels are employed.**

| Frequency [MHz] | Data Rate [Mbps] | Channel No. | 20dB Bandwidth Test Results |           |
|-----------------|------------------|-------------|-----------------------------|-----------|
|                 |                  |             | [kHz]                       | Pass/Fail |
| 2402            | 1.0              | 0           | 946                         | Pass      |
| 2441            | 1.0              | 39          | 946.8                       | Pass      |
| 2480            | 1.0              | 78          | 953.2                       | Pass      |
| 2402            | 2.0              | 0           | 1343                        | Pass      |
| 2441            | 2.0              | 39          | 1342                        | Pass      |
| 2480            | 2.0              | 78          | 1326                        | Pass      |
| 2402            | 3.0              | 0           | 1314                        | Pass      |
| 2441            | 3.0              | 39          | 1315                        | Pass      |
| 2480            | 3.0              | 78          | 1320                        | Pass      |

Table 6-2. Conducted 20dB Bandwidth Measurements





Figure 6-1. Test Instrument & Measurement Setup

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 11 of 35                   |



Plot 6-1. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 0)




Plot 6-2. 20dB Bandwidth Plot (Bluetooth, 1Mbps – Ch. 39)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT9300A                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 12 of 35                   |




Plot 6-3. 20dB Bandwidth Plot (Bluetooth, 1Mbps - Ch. 78)




Plot 6-4. 20dB Bandwidth Plot (Bluetooth, 2Mbps - Ch. 0)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 13 of 35                   |




Plot 6-5. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 39)




Plot 6-6. 20dB Bandwidth Plot (Bluetooth, 2Mbps – Ch. 78)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 14 of 35                   |




Plot 6-7. 20dB Bandwidth Plot (Bluetooth, 3Mbps - Ch. 0)



Plot 6-8. 20dB Bandwidth Plot (Bluetooth, 3Mbps - Ch. 39)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT9300A                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 15 of 35                   |



Plot 6-9. 20dB Bandwidth Plot (Bluetooth, 3Mbps – Ch. 78)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 16 of 35                   |

### 6.3 Output Power Measurement


§15.247 (b)(1); RSS-210 (A8.4 (2))

Measurement is made while the EUT is operating in non-hopping transmission mode. The powers shown below were measured using a spectrum analyzer with a Bluetooth signaling test set (Agilent Model: N4010A) used only to maintain a Bluetooth link with the EUT. Peak power measurements are performed in the analyzers' swept spectrum mode using a peak detector with RBW = VBW = 3MHz. Average power measurements are performed using the analyzer's "burst power" function with RBW = 3MHz. The burst power function triggers on a single burst set to maximum power and measures the maximum average power over the on-time. **The maximum permissible output power is 1 Watt.**

This unit was tested with all possible data rates and the highest peak power is reported with the unit transmitting at 1Mbps.

| Frequency [MHz] | Data Rate [Mbps] | Channel No. | Peak Conducted Power |       |
|-----------------|------------------|-------------|----------------------|-------|
|                 |                  |             | [dBm]                | [mW]  |
| 2402            | 1.0              | 0           | 8.40                 | 6.918 |
| 2441            | 1.0              | 39          | 8.64                 | 7.311 |
| 2480            | 1.0              | 78          | 8.65                 | 7.328 |
| 2402            | 2.0              | 0           | 6.85                 | 4.842 |
| 2441            | 2.0              | 39          | 7.04                 | 5.058 |
| 2480            | 2.0              | 78          | 6.80                 | 4.786 |
| 2402            | 3.0              | 0           | 7.24                 | 5.297 |
| 2441            | 3.0              | 39          | 7.39                 | 5.483 |
| 2480            | 3.0              | 78          | 7.38                 | 5.470 |

**Table 6-3. Conducted Output Power Measurements**



**Figure 6-2. Test Instrument & Measurement Setup**

#### Note

Final results were obtained using calibrated couplers, attenuators and cables. The following formula was used:

Output Power (dBm) = Raw Analyzer Level (dBm) + Cable Loss (dB) + Loss in Directional Coupler/Insertion Loss (dB)


|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 17 of 35                   |

## 6.4 Band Edge Compliance

### §15.247 (d); RSS-210 (A8.5)


Measurement is taken at the highest point located outside of the emission bandwidth. **The maximum permissible emission level is 20 dBc. Any emission lying outside of the emission bandwidth and in a restricted band is subject to a field strength limit specified in Section 15.209 of the Title 47 CFR.**

Out of band conducted spurious emissions at the band edge were investigated for all data rates and the worst case emissions were found with the EUT transmitting at 1Mbps. Band edge emissions were also investigated with the EUT transmitting in all data rates. Plots of the worst case emissions are shown below.



Plot 6-10. Band Edge Plot (Bluetooth with Hopping Disabled, 1Mbps – Ch. 0)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 18 of 35                   |



Plot 6-11. Band Edge Plot (Bluetooth with Hopping Disabled, 1Mbps – Ch. 78)



Plot 6-12. Band Edge Plot (Bluetooth with Hopping Enabled, 1Mbps – Ch. 0)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 19 of 35                   |



Plot 6-13. Band Edge Plot (Bluetooth with Hopping Enabled, 1Mbps – Ch. 78)


|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 20 of 35                   |



## 6.6 Time of Occupancy

§15.247 (a)(1)(iii); RSS-210 (A8.1 (4))

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. *The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.*



Plot 6-15. Time of Occupancy Plot (Bluetooth)

### Time of Occupancy Calculation

Typically, Bluetooth 1.x/EDR mode has a channel hopping rate of 1600 hops/s. With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s with the use of one transmit and receive time slot.


- o 400ms x 20 hopping channels = 8 sec (Time of Occupancy Limit)
- o Worst case BT has 800 hops/second (for AFH)
- o 800 hops/second / 20 channels = 40 hops/second (# of hops/second on one channel)
- o 40 hops/second/channel x 8 seconds = 320 hops (# hops over a 8 second period)
- o 320 hops x 2.92 ms/channel = 934.4ms (worst case dwell time for one channel)

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGT19300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 22 of 35                   |


## 6.7 Number of Hopping Channels

**§15.247 (a)(1)(iii); RSS-210 (A8.1 (4))**

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***



**Plot 6-16. Low End Spectrum Channel Hopping Plot (Bluetooth)**



**Plot 6-17. High End Spectrum Channel Hopping Plot (Bluetooth)**


|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 23 of 35                   |

## 6.8 Conducted Spurious Emissions

### §15.247 (d)


Out of band conducted spurious emissions were investigated for all data rates and the worst case emissions were found with the EUT transmitting at 1Mbps. Plots of the worst case emissions are shown below.

The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.




Plot 6-18. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 24 of 35                   |




Plot 6-19. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 0)




Plot 6-20. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 25 of 35                   |




Plot 6-21. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 39)



Plot 6-22. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 26 of 35                   |



Plot 6-23. Conducted Spurious Plot (Bluetooth, 1Mbps – Ch. 78)

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 27 of 35                   |

## 6.9 Radiated Spurious Emission Measurements

### §15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

The EUT was tested from 9kHz and up to the 10<sup>th</sup> harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average measurement was used, using RBW = 1MHz, VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  is the Bluetooth pulse width in seconds, and linearly polarized horn antennas. All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-5 per Section 15.209. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.

| Frequency         | Field Strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[Meters] |
|-------------------|---------------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                          | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                         | 30                            |
| 1.705 – 30.00 MHz | 30                                    | 30                            |
| 30.00 – 88.00 MHz | 100                                   | 3                             |
| 88.00 – 216.0 MHz | 150                                   | 3                             |
| 216.0 – 960.0 MHz | 200                                   | 3                             |
| Above 960.0 MHz   | 500                                   | 3                             |

**Table 6-5. Radiated Limits**

### Sample Calculation

- o Field Strength Level [ $\text{dB}\mu\text{V/m}$ ] = Analyzer Level [ $\text{dBm}$ ] + 107 + AFCL [ $\text{dB/m}$ ] + Duty Cycle Correction [ $\text{dB}$ ]
- o AFCL [ $\text{dB/m}$ ] = Antenna Factor [ $\text{dB/m}$ ] + Cable Loss [ $\text{dB}$ ]
- o Margin [ $\text{dB}$ ] = Field Strength Level [ $\text{dB}\mu\text{V/m}$ ] – Limit [ $\text{dB}\mu\text{V/m}$ ]
  
- o Duty Cycle Correction Factor Calculation with AFH:
  - o Time to cycle through all channels =  $\Delta t = \tau_{[\text{ms}]} \times 20 \text{ channels} = 58.4\text{ms}$ , where  $\tau$  = pulse width
  - o  $100\text{ms} / \Delta t_{[\text{ms}]} = H \rightarrow$  Round up to next highest integer, to account for worst case,  $H' = 2$
  - o Worst Case Dwell Time =  $\tau_{[\text{ms}]} \times H' = 5.84\text{ms}$
  - o Duty Cycle Correction =  $20\log(\text{Worst Case Dwell Time}/100\text{ms})_{[\text{dB}]} = -24.672\text{dB}$

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 28 of 35                   |

## Radiated Spurious Emission Measurements (Cont'd)

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 1Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2402MHz

Channel: 0

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4804.00         | -111.34              | Avg      | H         | 39.40     | -24.67                     | 10.39                   | 53.98          | -43.59      |
| 4804.00         | -99.79               | Peak     | H         | 39.40     | 0.00                       | 46.61                   | 73.98          | -27.37      |
| 12010.00        | -135.00              | Avg      | H         | 49.39     | 0.00                       | 21.39                   | 53.98          | -32.59      |
| 12010.00        | -125.00              | Peak     | H         | 49.39     | 0.00                       | 31.39                   | 73.98          | -42.59      |

**Table 6-6. Radiated Measurements**

### NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and are below the limit shown in Table 6-5.
2. Average measurements > 1GHz using RBW = 1MHz and VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds. Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 29 of 35                   |

## Radiated Spurious Emission Measurements (Cont'd)

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 1Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2441MHz

Channel: 39

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4882.00         | -111.93              | Avg      | H         | 39.49     | -24.67                     | 9.89                    | 53.98          | -44.09      |
| 4882.00         | -99.36               | Peak     | H         | 39.49     | 0.00                       | 47.13                   | 73.98          | -26.85      |
| 7323.00         | -108.23              | Avg      | H         | 48.06     | -24.67                     | 22.16                   | 53.98          | -31.82      |
| 7323.00         | -99.40               | Peak     | H         | 48.06     | 0.00                       | 55.67                   | 73.98          | -18.31      |
| 12205.00        | -135.00              | Avg      | H         | 50.43     | 0.00                       | 22.43                   | 53.98          | -31.55      |
| 12205.00        | -125.00              | Peak     | H         | 50.43     | 0.00                       | 32.43                   | 73.98          | -41.55      |

**Table 6-7. Radiated Measurements**

### NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and are below the limit shown in Table 6-5.
2. Average measurements > 1GHz using RBW = 1MHz and VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds. Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 30 of 35                   |

## Radiated Spurious Emission Measurements (Cont'd)

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 1Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4960.00         | -111.86              | Avg      | H         | 39.58     | -24.67                     | 10.05                   | 53.98          | -43.93      |
| 4960.00         | -99.79               | Peak     | H         | 39.58     | 0.00                       | 46.80                   | 73.98          | -27.18      |
| 7440.00         | -110.35              | Avg      | H         | 49.59     | -24.67                     | 21.57                   | 53.98          | -32.41      |
| 7440.00         | -99.78               | Peak     | H         | 49.59     | 0.00                       | 56.81                   | 73.98          | -17.17      |
| 12400.00        | -135.00              | Avg      | H         | 51.45     | 0.00                       | 23.45                   | 53.98          | -30.53      |
| 12400.00        | -125.00              | Peak     | H         | 51.45     | 0.00                       | 33.45                   | 73.98          | -40.53      |

**Table 6-8. Radiated Measurements**

### NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and are below the limit shown in Table 6-5.
2. Average measurements > 1GHz using RBW = 1MHz and VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds. Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 31 of 35                   |

## 6.10 Radiated Restricted Band Edge Measurements

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 1Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 2483.50         | -84.15               | Avg      | H         | 36.44     | -24.67                     | 34.62                   | 53.98          | -19.36      |
| 2483.50         | -80.71               | Peak     | H         | 36.44     | 0.00                       | 62.73                   | 73.98          | -11.25      |
| 2483.66         | -86.09               | Avg      | H         | 36.44     | -24.67                     | 32.68                   | 53.98          | -21.30      |
| 2483.66         | -82.21               | Peak     | H         | 36.44     | 0.00                       | 61.23                   | 73.98          | -12.75      |
| 2483.84         | -88.23               | Avg      | H         | 36.44     | -24.67                     | 30.54                   | 53.98          | -23.44      |
| 2483.84         | -83.78               | Peak     | H         | 36.44     | 0.00                       | 59.66                   | 73.98          | -14.32      |

**Table 6-9. Radiated Restricted Band Edge Measurements at 3-meters**


### NOTES:

1. All emissions shown lie in the restricted bands specified in §15.205 and are below the limit shown in Table 6-5.
2. Average measurements > 1GHz using RBW = 1MHz and VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds. Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. No significant emissions were found beyond the fifth harmonic for this device.
6. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
7. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

|                                      |                                                                                     |                                                         |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTI9300A                  |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012                                                   | EUT Type:<br>Portable Handset                           |                                                                                       | Page 32 of 35                   |

## 6.11 Line Conducted Measurement Data

### §15.207; RSS-Gen (7.2.2)



**Plot 6-24. Line-Conducted Test Plot (L1)**

| Frequency MHz | Line | Corr. dB | QuasiPeak dBμV | Limit dBμV | Margin dB | Average dBμV | Limit dBμV | Margin dB |
|---------------|------|----------|----------------|------------|-----------|--------------|------------|-----------|
| 0.192750      | L1   | 0.2      | 36.0           | 63.9       | 27.9      | 25.0         | 53.9       | 28.9      |
| 0.291750      | L1   | 0.1      | 28.4           | 60.5       | 32.0      | 21.3         | 50.5       | 29.2      |
| 0.379500      | L1   | 0.1      | 34.4           | 58.3       | 23.9      | 24.5         | 48.3       | 23.8      |
| 1.509000      | L1   | 0.2      | 33.3           | 56.0       | 22.7      | 23.0         | 46.0       | 23.0      |
| 2.505750      | L1   | 0.2      | 37.7           | 56.0       | 18.3      | 28.1         | 46.0       | 17.9      |
| 2.539500      | L1   | 0.2      | 37.5           | 56.0       | 18.5      | 28.1         | 46.0       | 17.9      |
| 2.611500      | L1   | 0.2      | 37.3           | 56.0       | 18.7      | 27.5         | 46.0       | 18.5      |
| 2.640750      | L1   | 0.2      | 37.5           | 56.0       | 18.5      | 27.5         | 46.0       | 18.5      |
| 2.692500      | L1   | 0.2      | 37.3           | 56.0       | 18.7      | 27.5         | 46.0       | 18.5      |
| 6.463500      | L1   | 0.3      | 37.4           | 60.0       | 22.6      | 27.1         | 50.0       | 22.9      |

**Table 6-10. Line-Conducted Test Data (L1)**


#### Notes:

- All Modes of operation were investigated and the worst-case emissions are reported.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTI9300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 33 of 35                   |

## Line Conducted Measurement Data (Cont'd)

### §15.207; RSS-Gen (7.2.2)



**Plot 6-25. Line-Conducted Test Plot (N)**

| Frequency MHz | Line | Corr. dB | QuasiPeak dBμV | Limit dBμV | Margin dB | Average dBμV | Limit dBμV | Margin dB |
|---------------|------|----------|----------------|------------|-----------|--------------|------------|-----------|
| 0.152250      | N    | 0.2      | 39.7           | 65.9       | 26.1      | 26.8         | 55.9       | 29.1      |
| 0.190500      | N    | 0.2      | 37.0           | 64.0       | 27.0      | 25.9         | 54.0       | 28.1      |
| 0.366000      | N    | 0.1      | 35.2           | 58.6       | 23.4      | 21.7         | 48.6       | 26.9      |
| 0.498750      | N    | 0.1      | 33.6           | 56.0       | 22.4      | 22.0         | 46.0       | 24.0      |
| 1.605750      | N    | 0.2      | 37.1           | 56.0       | 18.9      | 25.8         | 46.0       | 20.2      |
| 2.501250      | N    | 0.2      | 41.5           | 56.0       | 14.5      | 31.0         | 46.0       | 15.0      |
| 2.573250      | N    | 0.2      | 41.4           | 56.0       | 14.6      | 30.9         | 46.0       | 15.1      |
| 2.604750      | N    | 0.2      | 41.1           | 56.0       | 14.9      | 30.5         | 46.0       | 15.5      |
| 2.643000      | N    | 0.2      | 41.8           | 56.0       | 14.2      | 30.5         | 46.0       | 15.5      |
| 2.665500      | N    | 0.2      | 41.3           | 56.0       | 14.7      | 30.7         | 46.0       | 15.3      |

**Table 6-11. Line-Conducted Test Data (N)**

#### Notes:

- All Modes of operation were investigated and the worst-case emissions are reported.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AV Limit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

|                                      |                                               |                                                         |                |                                 |
|--------------------------------------|-----------------------------------------------|---------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGT19300A                  | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1205100658.A3L | Test Dates:<br>04/27 - 05/09/2012             | EUT Type:<br>Portable Handset                           |                | Page 34 of 35                   |

## 7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LGTI9300A** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-210 of the Industry Canada Rules.

|                                             |                                                                                     |                                                                 |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTI9300A                  |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CERTIFICATION)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1205100658.A3L | <b>Test Dates:</b><br>04/27 - 05/09/2012                                            | <b>EUT Type:</b><br>Portable Handset                            |                                                                                       | Page 35 of 35                          |