



## MEASUREMENT REPORT

### FCC PART 15.247 Bluetooth

**Applicant Name:**

Samsung Electronics Co., Ltd.  
129, Samsung-ro, Yeongtong-gu  
Suwon-city, Gyeonggi-do, 443-803  
Republic of Korea

**Date of Testing:**

2/23 - 2/28/2013

**Test Site/Location:**

PCTEST Lab. Columbia, MD, USA

**Test Report Serial No.:**

0Y1302280372.A3L

**FCC ID:**

**A3LGTN5110**

**APPLICANT:**

**Samsung Electronics Co., Ltd.**

**Application Type:**

Class II Permissive Change

**Model(s):**

GT-N5110

**EUT Type:**

Portable Tablet

**Frequency Range:**

2402 – 2480MHz (Bluetooth for US)

**Type of Modulation:**

GFSK,  $\pi/4$ -DQPSK, 8DPSK

**FCC Classification:**

FCC Part 15 Spread Spectrum Transmitter (DSS)

**FCC Rule Part(s):**

Part 15 Subpart C (15.247)

**Test Procedure(s):**

ANSI C63.10-2009, DA 00-705

**Original Grant Date:**

January 25, 2013

**Class II Perm. Change:**

Please see Change Document.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009 and DA 00-705. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


  
Randy Ortanez  
President

|                                             |                                                                                     |                                                                                    |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTN5110                   |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b><br><b>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1302280372.A3L | <b>Test Dates:</b><br>2/23 - 2/28/2013                                              | <b>EUT Type:</b><br>Portable Tablet                                                |                                                                                       | Page 1 of 16                           |

## TABLE OF CONTENTS


|                                                      |    |
|------------------------------------------------------|----|
| FCC PART 15.247 MEASUREMENT REPORT.....              | 3  |
| 1.0 INTRODUCTION.....                                | 4  |
| 1.1 SCOPE.....                                       | 4  |
| 1.2 PCTEST TEST LOCATION.....                        | 4  |
| 2.0 PRODUCT INFORMATION .....                        | 5  |
| 2.1 EQUIPMENT DESCRIPTION.....                       | 5  |
| 2.2 DEVICE CAPABILITIES .....                        | 5  |
| 2.3 TEST CONFIGURATION .....                         | 5  |
| 2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....     | 5  |
| 2.5 LABELING REQUIREMENTS .....                      | 5  |
| 3.0 DESCRIPTION OF TEST .....                        | 6  |
| 3.1 EVALUATION PROCEDURE.....                        | 6  |
| 3.2 RADIATED EMISSIONS .....                         | 6  |
| 4.0 ANTENNA REQUIREMENTS .....                       | 7  |
| 5.0 TEST EQUIPMENT CALIBRATION DATA.....             | 8  |
| 6.0 TEST RESULTS .....                               | 9  |
| 6.1 SUMMARY .....                                    | 9  |
| 6.2 TIME OF OCCUPANCY .....                          | 10 |
| 6.3 RADIATED SPURIOUS EMISSION MEASUREMENTS.....     | 11 |
| 6.4 RADIATED RESTRICTED BAND EDGE MEASUREMENTS ..... | 15 |
| 7.0 CONCLUSION .....                                 | 16 |

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 2 of 16                    |



# MEASUREMENT REPORT

## FCC Part 15.247




### § 2.1033 General Information

**APPLICANT:** Samsung Electronics Co., Ltd.  
**APPLICANT ADDRESS:** 129, Samsung-ro, Yeongtong-gu  
 Suwon-city, Gyeonggi-do, 443-803, Republic of Korea  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** Part 15 Subpart C (15.247)  
**IC SPECIFICATION(S):** RSS-210 Issue 8  
**BASE MODEL:** GT-N5110  
**FCC ID:** A3LGTN5110  
**Test Device Serial No.:** N/A ☐ Production ☒ Pre-Production ☐ Engineering  
**FCC CLASSIFICATION:** FCC Part 15 Spread Spectrum Transmitter (DSS)  
**Method/System:** Frequency Hopping Spread Spectrum (FHSS)  
**DATE(S) OF TEST:** 2/23 - 2/28/2013  
**TEST REPORT S/N:** 0Y1302280372.A3L

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 3 of 16                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                                      |                |                                 |
|--------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTN5110                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013               | EUT Type:<br>Portable Tablet                                         |                | Page 4 of 16                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Tablet FCC ID: A3LGTN5110**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

### 2.2 Device Capabilities

This device contains the following capabilities:

802.11a/b/g/n WLAN (DTS/NII), Bluetooth (1x,EDR, LE)

### 2.3 Test Configuration

The Samsung Portable Tablet FCC ID: A3LGTN5110 was tested per the guidance of ANSI C63.10-2009 and DA 00-705. See Sections 3.2 of this test report for a description of the radiated emissions.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 5 of 16                    |

## 3.0 DESCRIPTION OF TEST

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) and the "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" (DA 00-705) were used in the measurement of the **Samsung Portable Tablet FCC ID: A3LGTN5110**.

Deviation from measurement procedure.....None

### 3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 6 of 16                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Samsung Portable Tablet are **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The **Samsung Portable Tablet FCC ID: A3LGTN5110** unit complies with the requirement of §15.203.

| Ch. | Frequency (MHz) |
|-----|-----------------|
| 00  | 2402            |
| :   | :               |
| 39  | 2441            |
| :   | :               |
| 78  | 2480            |

**Table 4-1. Frequency/ Channel Operations**

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 7 of 16                    |

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer      | Model            | Description                            | Cal Date  | Cal Interval | Cal Due   | Serial Number |
|-------------------|------------------|----------------------------------------|-----------|--------------|-----------|---------------|
| -                 | BT1              | Bluetooth Cable Set                    | 1/17/2013 | Annual       | 1/17/2014 | N/A           |
| -                 | RE1              | Radiated Emissions Cable Set (UHF/EHF) | 7/10/2012 | Annual       | 7/10/2013 | N/A           |
| Agilent           | N9030A           | PXA Signal Analyzer (44GHz)            | 1/11/2013 | Annual       | 1/11/2014 | MY52350166    |
| Agilent           | N9020A           | MXA Signal Analyzer                    | 10/9/2012 | Annual       | 10/9/2013 | US46470561    |
| Agilent           | N4010A           | Wireless Connectivity Test Set         | N/A       | -            | N/A       | GB46170464    |
| Com-Power         | AL-130           | 9kHz - 30MHz Loop Antenna              | 5/10/2012 | Annual       | 5/10/2013 | 121034        |
| ETS Lindgren      | 3117             | 1-18 GHz DRG Horn (Medium)             | 7/22/2011 | Biennial     | 7/22/2013 | 125518        |
| ETS Lindgren      | 3160-09          | 18-26.5 GHz Standard Gain Horn         | 5/30/2012 | Biennial     | 5/30/2014 | 135427        |
| Mini-Circuits     | VHF-3100+        | High Pass Filter                       | 1/17/2013 | Annual       | 1/17/2014 | 30841         |
| Rohde & Schwarz   | CMU200           | Base Station Simulator                 | N/A       | -            | N/A       | 836536/0005   |
| Rohde & Schwarz   | TS-PR18          | 1-18 GHz Pre-Amplifier                 | 6/26/2012 | Annual       | 6/26/2013 | 100071        |
| Rohde & Schwarz   | TS-PR26          | 18-26.5 GHz Pre-Amplifier              | 5/30/2012 | Annual       | 5/30/2013 | 100040        |
| Rohde & Schwarz   | ESU26            | EMI Test Receiver                      | 2/25/2013 | Annual       | 2/25/2014 | 100342        |
| Solar Electronics | 8012-50-R-24-BNC | LISN                                   | 6/23/2011 | Biennial     | 6/23/2013 | 310233        |
| Sunol             | JB5              | Bi-Log Antenna (30M - 5GHz)            | 1/26/2012 | Biennial     | 1/26/2014 | A051107       |

**Table 5-1. Annual Test Equipment Calibration Schedule**

**Note:**

Equipment used for signaling with a calibration date of "N/A" shown in this list was only used for maintaining a link between the piece of equipment and the EUT. This equipment was not used to make direct calibrated measurements.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 8 of 16                    |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Samsung Electronics Co., Ltd.  
 FCC ID: A3LGTN5110  
 Method/System: Frequency Hopping Spread Spectrum (FHSS)  
 Number of Channels: 79

| FCC Part Section(s)          | RSS Section(s)    | Test Description                                                                 | Test Limit                                                                                              | Test Condition | Test Result | Reference                   |
|------------------------------|-------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|----------------|-------------|-----------------------------|
| <b>TRANSMITTER MODE (Tx)</b> |                   |                                                                                  |                                                                                                         |                |             |                             |
| 15.247(a)(1)(iii)            | RSS-210 [A8.1(4)] | Time of Occupancy                                                                | < 0.4 sec in 31.6 sec period                                                                            | CONDUCTED      | PASS        | Section 6.2                 |
| 15.205<br>15.209             | RSS-210 [A8.5]    | General Field Strength Limits<br>(Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits) | RADIATED       | PASS        | Section 6.3,<br>Section 6.4 |

**Table 6-1. Summary of Test Results**

**Notes:**


- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All data included in this report was taken from the parent model FCC ID: A3LGTN5100 as all the circuitry is electrically identical to FCC ID: A3LGTN5110.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 9 of 16                    |

## 6.2 Time of Occupancy

§15.247 (a)(1)(iii); RSS-210 (A8.1 (4))

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. **The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.**



**Plot 6-1. Time of Occupancy Plot (Bluetooth)**

### Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of  $1600 / 6 = 266.67$  hops/s/slot

- o  $400\text{ms} \times 79$  hopping channels = 31.6 sec (Time of Occupancy Limit)
- o Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- o  $266.67 \text{ hops/second} / 79$  channels = 3.38 hops/second (# of hops/second on one channel)
- o  $3.38 \text{ hops/second/channel} \times 31.6$  seconds = 106.67 hops (# hops over a 31.6 second period)
- o  $106.67 \text{ hops} \times 2.90 \text{ ms/channel}$  = 309.34ms (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of  $800 / 6 = 133.3$  hops/s/slot

- o  $400\text{ms} \times 20$  hopping channels = 8 sec (Time of Occupancy Limit)
- o Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- o  $133.3 \text{ hops/s} / 20$  channels = 6.67 hops/second (# of hops/second on one channel)
- o  $6.67 \text{ hops/s} / \text{channel} \times 8$  seconds = 53.34 hops (# hops over a 8 second period)
- o  $53.34 \text{ hops} \times 2.90 \text{ ms/channel}$  = 154.68 ms (worst case dwell time for one channel in AFH mode)

|                                      |                                               |                                                                      |                |                                 |
|--------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LGTN5110                   | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013               | EUT Type:<br>Portable Tablet                                         |                | Page 10 of 16                   |

## 6.3 Radiated Spurious Emission Measurements

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

| Frequency         | Field Strength<br>[μV/m] | Measured Distance<br>[Meters] |
|-------------------|--------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)             | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)            | 30                            |
| 1.705 – 30.00 MHz | 30                       | 30                            |
| 30.00 – 88.00 MHz | 100                      | 3                             |
| 88.00 – 216.0 MHz | 150                      | 3                             |
| 216.0 – 960.0 MHz | 200                      | 3                             |
| Above 960.0 MHz   | 500                      | 3                             |

**Table 6-2. Radiated Limits**

### Sample Calculation

- o Field Strength Level  $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]} + \text{Duty Cycle Correction }_{[dB]}$
- o  $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- o  $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

### Duty Cycle Correction Factor Calculation

- o Channel hop rate = 800 hops/second (AFH Mode)
- o Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- o Time per channel hop =  $1 / 133.33 \text{ hops/second} = 7.5 \text{ ms}$
- o Time to cycle through all channels =  $7.5 \times 20 \text{ channels} = 150 \text{ ms}$
- o Number of times transmitter hits on one channel =  $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- o Worst case dwell time = 7.5 ms
- o Duty cycle correction factor =  $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 11 of 16                   |

### Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-2.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. Average measurements > 1GHz using RBW = 1MHz and VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds. Peak measurements > 1GHz using RBW = 1MHz and VBW = 3MHz. Both average and peak measurements were made using a peak detector.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
6. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported. Emissions whose levels were not within 20dB of the respective limits were not reported.
7. Average levels at -135 dBm and peak levels at -125dBm represent the analyzer noise floor and signify that no emission was detected.

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 12 of 16                   |

## Radiated Spurious Emission Measurements (Cont'd)

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth  
Worst Case Data Rate: 3Mbps  
Measurement Distance: 3 Meters  
Operating Frequency: 2402MHz  
Channel: 0

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4804.00         | -100.96              | Avg      | H         | 39.45     | -22.50                     | 22.99                   | 53.98          | -30.99      |
| 4804.00         | -93.31               | Peak     | H         | 39.45     | 0.00                       | 53.13                   | 73.98          | -20.84      |
| 12010.00        | -135.00              | Avg      | H         | 49.63     | 0.00                       | 21.63                   | 53.98          | -32.35      |
| 12010.00        | -125.00              | Peak     | H         | 49.63     | 0.00                       | 31.63                   | 73.98          | -42.35      |

**Table 6-3. Radiated Measurements**

Worst Case Mode: Bluetooth  
Worst Case Data Rate: 3Mbps  
Measurement Distance: 3 Meters  
Operating Frequency: 2441MHz  
Channel: 39

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4882.00         | -101.99              | Avg      | H         | 39.48     | -22.50                     | 21.99                   | 53.98          | -31.99      |
| 4882.00         | -95.67               | Peak     | H         | 39.48     | 0.00                       | 50.81                   | 73.98          | -23.17      |
| 7323.00         | -135.00              | Avg      | H         | 42.39     | 0.00                       | 14.39                   | 53.98          | -39.59      |
| 7323.00         | -125.00              | Peak     | H         | 42.39     | 0.00                       | 24.39                   | 73.98          | -49.59      |
| 12205.00        | -135.00              | Avg      | H         | 50.35     | 0.00                       | 22.35                   | 53.98          | -31.63      |
| 12205.00        | -125.00              | Peak     | H         | 50.35     | 0.00                       | 32.35                   | 73.98          | -41.63      |

**Table 6-4. Radiated Measurements**

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 13 of 16                   |

## Radiated Spurious Emission Measurements (Cont'd)

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 3Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 4960.00         | -100.81              | Avg      | H         | 39.51     | -22.50                     | 23.20                   | 53.98          | -30.78      |
| 4960.00         | -93.22               | Peak     | H         | 39.51     | 0.00                       | 53.29                   | 73.98          | -20.69      |
| 7440.00         | -135.00              | Avg      | H         | 42.56     | 0.00                       | 14.56                   | 53.98          | -39.42      |
| 7440.00         | -125.00              | Peak     | H         | 42.56     | 0.00                       | 24.56                   | 73.98          | -49.42      |
| 12400.00        | -135.00              | Avg      | H         | 51.07     | 0.00                       | 23.07                   | 53.98          | -30.91      |
| 12400.00        | -125.00              | Peak     | H         | 51.07     | 0.00                       | 33.07                   | 73.98          | -40.91      |

**Table 6-5. Radiated Measurements**

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 14 of 16                   |

## 6.4 Radiated Restricted Band Edge Measurements

§15.205 & §15.209, §15.247 (d); RSS-210 (A8.5)

Worst Case Mode: Bluetooth

Worst Case Data Rate: 3Mbps

Measurement Distance: 3 Meters

Operating Frequency: 2480MHz

Channel: 78

| Frequency [MHz] | Analyzer Level [dBm] | Detector | Pol [H/V] | AFCL [dB] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------------------|----------|-----------|-----------|----------------------------|-------------------------|----------------|-------------|
| 2483.50         | -79.27               | Avg      | H         | 36.39     | -22.50                     | 41.62                   | 53.98          | -12.36      |
| 2483.50         | -75.57               | Peak     | H         | 36.39     | 0.00                       | 67.82                   | 73.98          | -6.16       |
| 2484.10         | -89.27               | Avg      | H         | 36.39     | -22.50                     | 31.62                   | 53.98          | -22.36      |
| 2484.10         | -84.87               | Peak     | H         | 36.39     | 0.00                       | 58.52                   | 73.98          | -15.46      |
| 2484.70         | -95.87               | Avg      | H         | 36.39     | -22.50                     | 25.03                   | 53.98          | -28.95      |
| 2484.70         | -90.27               | Peak     | H         | 36.39     | 0.00                       | 53.13                   | 73.98          | -20.85      |

**Table 6-6. Radiated Restricted Band Edge Measurements**

|                                      |                                                                                     |                                                                      |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LGTN5110                   |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1302280372.A3L | Test Dates:<br>2/23 - 2/28/2013                                                     | EUT Type:<br>Portable Tablet                                         |                                                                                       | Page 15 of 16                   |

## 7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Tablet FCC ID: A3LGTN5110** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

|                                             |                                                                                     |                                                                              |                                                                                       |                                        |
|---------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> A3LGTN5110                   |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1302280372.A3L | <b>Test Dates:</b><br>2/23 - 2/28/2013                                              | <b>EUT Type:</b><br>Portable Tablet                                          |                                                                                       | Page 16 of 16                          |