


OFDM : 802.11n_HT20(MCS0)

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:


Offset (dB) = Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (MHz)	offset (dB)	Reading values (dB m)	Result (dB m)
3 727.5	Noise level	-	-
5 725.0	21.43	-70.84	-49.41
26 093.0	Noise level	-	-
38 983.9	Noise Level	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:

Offset (dB) = Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (MHz)	offset (dB)	Reading values (dB m)	Result (dB m)
3 801.0	Noise level	-	-
26 110.6	Noise level	-	-
37 778.8	Noise Level	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:

Offset (dB) = Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (MHz)	offset (dB)	Reading values (dB m)	Result (dB m)
3 883.7	Noise Level	-	-
5 850.0	21.60	-78.88	-57.28
25 751.5	Noise Level	-	-
38 046.1	Noise Level	-	-


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

OFDM : 802.11n_HT40(MCS0)

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:


Offset (dB) = Attenuator (dB) + Cable loss (dB)

Result (dB m) = Spurious offset (dB) + Reading values (dB m)


Frequency (MHz)	offset (dB)	Reading values (dB m)	Result (dB m)
3 837.5	Noise Level	-	-
5 725.0	21.43	-65.50	-44.07
25 523.8	Noise Level	-	-
39. 169.8	Noise Level	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Note:

Offset (dB) = Attenuator (dB) + Cable loss (dB)


Result (dB m) = Spurious offset (dB) + Reading values (dB m)

Frequency (MHz)	offset (dB)	Reading values (dB m)	Result (dB m)
3 864.1	Noise Level	-	-
5 850.0	21.60	-80.06	-58.46
25 675.0	Noise Level	-	-
38 441.2	Noise Level	-	-

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.6. 6 dB Bandwidth Measurement

3.1. Test Setup



3.2. Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 ~928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 825 MHz bands. The minimum of 6 dB Bandwidth shall be at least 500 kHz

3.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

The test follows section 5.1 of FCC KDB Publication 558074

1. Set resolution bandwidth (RBW) = 1 – 5 % of the emission bandwidth (EBW).
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude point (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Compare the resultant bandwidth with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is 1 – 5 %.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

3.4. Test Results

Ambient temperature : (24 ± 2) °C
Relative humidity : 47 % R.H.

Operation Mode	Data Rate (Mbps)	Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
DSSS (802.11b)	1	Low	2 412	8.75	0.5
		Middle	2 437	9.20	
		High	2 462	9.15	
OFDM (802.11g)	6	Low	2 412	16.10	
		Middle	2 437	16.20	
		High	2 462	16.00	
OFDM (802.11n_HT20)	MCS0	Low	2 412	17.35	
		Middle	2 437	17.25	
		High	2 462	17.45	
OFDM (802.11a)	6	Low	5 745	15.85	
		Middle	5 785	16.05	
		High	5 825	15.90	
OFDM (802.11n_HT20)	MCS0	Low	5 745	17.20	
		Middle	5 785	16.80	
		High	5 825	17.45	
OFDM (802.11n_HT40)	MCS0	Low	5 755	35.90	
		High	5 795	34.20	

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

6 dB Bandwidth

DSSS : 802.11b

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



OFDM : 802.11g

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



High Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

OFDM : 802.11n_HT20

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



OFDM : 802.11a

Low Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel



High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

OFDM : 802.11n_HT20

Low Channel



Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel



OFDM : 802.11n_HT40

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

4. Maximum Peak Output Power Measurement

4.1. Test Setup



4.2. Limit

According to §15.247(b)(3), for systems using digital modulation in the 902 ~ 928 MHz, 2 400 ~2 483.5 MHz, and 5 725 ~ 5 850 MHz band: 1 Watt. As an alternative to a peak power measurement, compliance with the one watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antenna elements. The average must not include any intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), the conducted output power limit specified in paragraph(b) of this section is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in paragraph(c) of this section, if transmitting antenna of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraph (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.3. Test Procedure

- 11b, g, a, n_HT20, HT40

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
3. Test program: (S/W name : R&S Power Viewer, Version : 3.2.0)
4. Measure peak & average power each channel.

4.4. Test Results

Ambient temperature : (24 ± 2) °C
Relative humidity : 47 % R.H.

Mode	Channel	Channel Frequency (MHz)	Data Rate (Mbps)	Attenuator + Cable offset (dB)	Average power Result (dB m)	Peak Power Result (dB m)
DSSS (802.11b)	Low	2 412	1	20.95	15.11	18.06
			2		15.03	17.98
			5.5		14.87	18.05
			11		14.73	18.02
	Middle	2 437	1	21.00	15.45	18.37
			2		15.37	18.33
			5.5		15.22	18.30
			11		15.00	18.29
	High	2 462	1	21.03	15.68	18.62
			2		15.67	18.59
			5.5		15.53	18.60
			11		15.33	18.60
OFDM (802.11g)	Low	2 412	6	20.95	10.61	22.75
			9		10.44	22.49
			12		10.29	21.99
			18		10.03	21.95
			24		9.82	22.16
			36		9.36	21.94
			48		9.05	21.77
			54		8.90	22.06
	Middle	2 437	6	21.00	10.92	23.08
			9		10.83	22.93
			12		10.69	22.45
			18		10.39	22.35
			24		10.15	22.57
			36		9.75	22.42
			48		9.43	22.34
			54		9.27	22.64
	High	2 462	6	21.03	11.11	23.45
			9		11.01	23.22
			12		10.95	22.79
			18		10.64	22.68
			24		10.70	22.95
			36		10.00	22.55
			48		9.73	22.47
			54		9.46	22.67

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Channel	Channel Frequency (MHz)	Data rate (Mbps)	Attenuator + Cable offset (dB)	Average power Result (dB m)	Peak Power Result (dB m)
OFDM (802.11n_HT20)	Low	2 412	MCS0	20.95	9.50	22.06
			MCS1		9.16	22.04
			MCS2		8.90	22.04
			MCS3		8.73	21.53
			MCS4		8.35	21.58
			MCS5		7.98	21.97
			MCS6		7.89	21.56
			MCS7		7.75	21.63
	Middle	2 437	MCS0	21.00	9.88	22.50
			MCS1		9.60	22.43
			MCS2		9.36	22.40
			MCS3		9.10	22.01
			MCS4		8.72	21.88
			MCS5		8.41	22.37
			MCS6		8.23	22.02
			MCS7		8.07	21.62
	High	2 462	MCS0	21.03	10.09	22.69
			MCS1		9.79	22.68
			MCS2		9.55	22.65
			MCS3		9.31	22.27
			MCS4		8.99	22.02
			MCS5		8.55	22.61
			MCS6		8.50	22.22
			MCS7		8.33	21.97

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Channel	Channel Frequency (MHz)	Data Rate (Mbps)	Attenuator + Cable offset (dB)	Average power Result (dB m)	Peak Power Result (dB m)
OFDM (802.11a)	Low	5 745	6	20.95	13.56	24.10
			9		13.25	23.75
			12		13.11	23.66
			18		12.43	23.44
			24		12.22	23.45
			36		12.27	23.59
			48		12.15	23.47
			54		12.04	23.54
	Middle	5 785	6	21.00	13.78	24.26
			9		13.66	24.11
			12		13.45	24.10
			18		13.22	24.05
			24		12.83	23.77
			36		12.47	23.14
			48		12.42	23.33
			54		12.22	23.65
	High	5 825	6	21.02	13.75	24.08
			9		13.66	23.99
			12		13.54	23.85
			18		12.99	23.74
			24		12.83	23.65
			36		12.47	23.66
			48		12.24	23.57
			54		12.22	23.53

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.