

	1	2	3	4	5	6	7	8
A			Rev. No					
B								
C								
D								
E								
F								
G								
H								
I								
J								
K								
L								

Technical Description

1. Use 'FILM' provided by 'SAMSUNG' for letter and contents
2. Background color is 'WHITE', letter color is 'BLACK' (reverse for SAMSUNG LOGO)
3. Put 'release paper' on the back side after the adhesive.
4. No blur and spread for letter
5. Proceed with manufacturing process after the approval of R&D Group
6. The spec. of product must be based on approved limit samples.
7. Stock on as a ROLL
8. Follow drawing instruction above for CE or WEEE mark
9. Unify material and color as one color (blue) for glassine paper

MAT. White polypropylene 80 μ

FIN. Semitransparency OPP Lamination + UVP Coating

TITLE GT-S7250D

LABEL (R)-MAIN-EU

UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION	
TOLERANCE	+0.0 -0.1	jukyun Kim	kyeonghwan jo	junesop kim		
SCALE	N/S					
Manufacture	HANSUNG P&I	11-07-21	11-07-21	11-07-21	SHEET NO	1/1
		Doc. CODE	GH68-00000A			

3. FCC ID Label Location

This label is placed inside the battery compartment.

