



FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

**FOR
GT-S7275~802.11 B/G/N 1X1 HT20, + BT4.0 (LE) + GSM850/1900 AND
WCDMA850MHz BAR PHONE**

MODEL NUMBER: GT-S7275

FCC ID: A3LGTS7275

REPORT NUMBER: 13I15226-5

ISSUE DATE: June 24, 2013

Prepared for
**SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA**

Prepared by
**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	06/24/13	Initial Issue	P. Kim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. SAMPLE CALCULATION	5
4.3. MEASUREMENT UNCERTAINTY.....	5
5. EQUIPMENT UNDER TEST	6
5.1. DESCRIPTION OF EUT	6
5.2. MAXIMUM OUTPUT POWER.....	6
5.3. SOFTWARE AND FIRMWARE.....	6
5.4. MODEL DIFFERNECE	6
5.5. WORST-CASE CONFIGURATION AND MODE.....	6
5.6. MODIFICATIONS	6
5.7. DESCRIPTION OF TEST SETUP.....	7
6. TEST AND MEASUREMENT EQUIPMENT	10
7. RADIATED EMISSION TEST RESULTS.....	11
7.1. LIMITS AND PROCEDURE	11
7.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)	13
7.1.2. TX SPURIOUS EMISSION 30 TO 1000 MHz	14
8. AC MAINS LINE CONDUCTED EMISSIONS.....	17
9. FREQUENCY STABILITY	21
10. SETUP PHOTOS	22

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

EUT DESCRIPTION: GT-S7275~802.11 B/G/N 1X1 HT20, + BT4.0 (LE) +
GSM850/1900 AND WCDMA850MHz BAR PHONE

MODEL: GT-S7275

SERIAL NUMBER: 47901EAF5D9C3077 (RADIATED)
47901EB9147C30DD (CONDUCTED)

DATE TESTED: June 12, 2013

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



PHILIP KIM
WISE PROGRAM MANAGER
UL Verification Services Inc.



THANH NGUYEN
EMC ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

802.11 B/G/N 1X1 HT20, + BT4.0 (LE) + GSM850/1900 AND WCDMA850MHz SMART PHONE

5.2. MAXIMUM OUTPUT POWER

The transmitter maximum E-field at 30m distance is 28.581 dBuV/m

5.3. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was REV 0.1 and the software version was S7275.001.

5.4. MODEL DIFFERNECE

5.5. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that the Y-orientation was the worst-case orientation; therefore all final radiated testing was performed with the EUT in the Y-orientation while generating continuous emissions.

5.6. MODIFICATIONS

No modifications were made during testing.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Radiated Emissions Above 30 MHz, AC Line Conducted Emissions and Frequency Stability:

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	SAMSUNG	ETA0U80EBE		N/A
Headset	SAMSUNG	FK-153-A	N/A	N/A

I/O CABLES

Radiated Emissions Above 30 MHz, AC Line Conducted Emissions and Frequency Stability:


I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	USB	Shielded	1	N/A

TEST SETUP


The EUT is a stand-alone device configured and tested in a worst-case setup.

SETUP DIAGRAM FOR TESTS

Radiated Emissions Below 30 MHz:



Radiated Emissions Above 30 MHz, AC Line Conducted Emissions and Frequency Stability:



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
ESA-E Spectrum Analyzer, 9kHz-26.5 GHz	Agilent / HP	E4407B	C01098	04/04/13	04/04/14
PXA Signal Analyzer, 3Hz-26.5GHz	Agilent / HP	N9030A-544	T458	05/09/13	05/09/14
Antenna, Loop, 30 MHz	EMCO	6502	C00593	02/20/13	02/20/14
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	C01011	03/28/13	03/28/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00558	03/23/13	03/23/14
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	08/08/12	08/08/13
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/13	01/14/14
DMM	Fluke	77-11	N02303	10/31/11	10/31/13
Temperature Chamber	Thermotron	T80	29800	11/01/12	11/01/13

7. RADIATED EMISSION TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMIT

§15.225

IC RSS-210, Section 2.6 (Transmitter)

IC RSS-GEN, Section 6 (Receiver)

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the field strength from µV/m to dBµV/m is:

Limit (dBµV/m) = 20 log limit (µV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE

ANSI C63.4

The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 19.2 MHz. The frequency range was investigated from 30 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)


RESULTS

No non-compliance noted:


7.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)

FCC Part 15, Subpart B & C 10 Meter Distance Measurement At Open Field												
Company:		SAMSUNG										
Project #:		13I15226										
Model #:		NFC; Worst Case Y-Orientation										
Tester:		Thanh Nguyen										
Date:		06/12/13										
Frequency (MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	AF (dB/m)	Distance Correction (dB)	PK Corrected Reading (dBuV/m)	AV Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	PK Margin (dB)	AV Margin (dB)	Notes
Loop Antenna Face On:												
13.56	28.581		N/A	10.56	-19.08	20.05	N/A	84.00	N/A	-63.9	N/A	Fundamental @ 10m Dist
13.41	25.86		N/A	10.54	-19.08	17.32	N/A	50.48	N/A	-33.2	N/A	13.41-13.553MHz Spurious @ 10m
13.525	26.24		N/A	10.55	-19.08	17.71	N/A	50.48	N/A	-32.8	N/A	13.41-13.553MHz Spurious @ 10m
13.7	28.57		N/A	10.57	-19.08	18.06	N/A	40.51	N/A	-22.5	N/A	13.567-13.710MHz Spurious @ 10m
13.57	25.33		N/A	10.57	-19.08	16.06	N/A	40.51	N/A	-22.5	N/A	13.567-13.710MHz Spurious @ 10m
13.17	25.364		N/A	10.52	-19.08	16.80	N/A	40.51	N/A	-23.7	N/A	13.110-13.410MHz Spurious @ 10m
13.2025	22.89		N/A	10.52	-19.08	14.33	N/A	40.51	N/A	-26.2	N/A	13.110-13.410MHz Spurious @ 10m
27.12	20.45		N/A	9.046	-19.08	10.41	N/A	29.54	N/A	-19.1	N/A	14.010-30MHz Spurious @ 10m
Loop Antenna Face Off:												
13.56	25.067		N/A	10.56	-19.08	16.54	N/A	84.00	N/A	-67.5	N/A	Fundamental @ 10m Dist
13.41	19.647		N/A	10.54	-19.08	11.10	N/A	50.48	N/A	-39.4	N/A	13.41-13.553MHz Spurious @ 10m
13.4	22.16		N/A	10.54	-19.08	13.62	N/A	50.48	N/A	-36.9	N/A	13.41-13.553MHz Spurious @ 10m
13.7	21.12		N/A	10.57	-19.08	12.61	N/A	40.51	N/A	-27.9	N/A	13.567-13.710MHz Spurious @ 10m
13.71	18.33		N/A	10.57	-19.08	9.82	N/A	40.51	N/A	-30.7	N/A	13.710-14.010MHz Spurious @ 10m
27.12	17.27		N/A	9.046	-19.08	7.23	N/A	29.54	N/A	-22.3	N/A	14.010-30MHz Spurious @ 10m
* No more emissions were found up to 30MHz												
Note: The emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.												
P.K. = Peak												
Q.P. = Quasi Peak Reading												
A.F. = Antenna factor												
Rev. 10.23.09												

7.1.2. TX SPURIOUS EMISSION 30 TO 1000 MHz



VERTICAL PLOT



HORIZONTAL AND VERTICAL DATA

Project :	13I15226									
Company Name:	SAMSUNG									
Model / Config:	GT-S7275									
Mode:	NFC Test									
Test By:	Thanh Nguyen									
Marker No.	Test Frequency	Meter Reading(dBuV)	Detector	T185 Antenna Factor dB/m	T64 preamp/ cable loss [dB]	Corrected Reading dB(uVolts /meter)	E-Fields [dBuV/m] QPk	Margin (dB)	Height [cm]	Polarity
Horizontal 30 - 1000MHz										
1	128.8659	32.94	PK	14.1	-26.8	20.24	43.52	-23.28	200	Horz
2	143.1626	35.54	PK	12.8	-26.7	21.64	43.52	-21.88	200	Horz
3	206.4077	37.75	PK	11	-26.3	22.45	43.52	-21.07	100	Horz
4	972.1334	30.69	PK	22.9	-22.7	30.89	53.97	-23.08	200	Horz
Vertical 30 - 1000MHz										
5	30	39.38	PK	21	-27.7	32.68	40	-7.32	200	Vert
6	70.9518	40.54	PK	8.1	-27.2	21.44	40	-18.56	200	Vert
7	214.6465	36.23	PK	10.5	-26.1	20.63	43.52	-22.89	200	Vert
PK - Peak detector										
QP - Quasi-Peak detector										
LnAv - Linear Average detector										
LgAv - Log Average detector										
Av - Average detector										

8. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

IC RSS-GEN, Section 7.2.2

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Notes: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

TEST PROCEDURE

ANSI C63.4


RESULTS

No non-compliance noted:


6 WORST EMISSIONS

Project No:13I15226									
Client Name:SAMSUNG									
Model/Device:GT-S7275									
Test Volt/Freq:NFC, 115VAC/60Hz									
Test By:Thanh Nguyen									
Test Frequency	Meter Reading	Detector	T24 IL L1.TXT (dB)	LC Cables 1&3.TXT (dB)	dB(uVolts)	CFR 47 Part 15 Class B QP	Margin	CFR 47 Part 15 Class B Avg	Margin
Line-L1 .15 - 30MHz									
0.4245	46.68	PK	0.1	0	46.78	57.4	-10.62	-	-
0.4245	33.35	Av	0.1	0	33.45	-	-	47.4	-13.95
2.0535	50.37	PK	0.1	0.1	50.57	56	-5.43	-	-
2.0535	32.13	Av	0.1	0.1	32.33	-	-	46	-13.67
13.4565	37.97	PK	0.2	0.2	38.37	60	-21.63	-	-
13.4565	17.98	Av	0.2	0.2	18.38	-	-	50	-31.62
0.213	44.55	PK	0.1	0	44.65	63.1	-18.45	-	-
0.213	33.11	Av	0.1	0	33.21	-	-	53.1	-19.89
1.284	49.7	PK	0.1	0.1	49.9	56	-6.1	-	-
1.284	32.86	Av	0.1	0.1	33.06	-	-	46	-12.94
Line-L2 .15 - 30MHz									
13.5555	49.22	PK	0.2	0.2	49.62	60	-10.38	-	-
13.5555	28.88	Av	0.2	0.2	29.28	-	-	50	-20.72
0.5235	46.04	PK	0.1	0	46.14	56	-9.86	-	-
0.5235	31.18	Av	0.1	0	31.28	-	-	46	-14.72
1.5	50	PK	0.1	0.1	50.2	56	-5.8	-	-
1.5	33.43	Av	0.1	0.1	33.63	-	-	46	-12.37

LINE 1 RESULTS



LINE 2 RESULTS



9. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST PROCEDURE

ANSI / TIA / EIA 603 Clause 2.3.1 and 2.3.2

RESULTS

No non-compliance noted.

Reference Frequency: EUT Channel 13.5605000 MHz @ 20°C				
Limit: ± 100 ppm = 135.575 kHz				
Power Supply (Vac)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
115.00	50	13.5599850	-1.833	± 100
115.00	40	13.5600000	-1.844	± 100
115.00	30	13.5600000	-1.844	± 100
115.00	20	13.5575000	0.000	± 100
115.00	10	13.5597350	-1.649	± 100
115.00	0	13.5600610	-1.889	± 100
115.00	-10	13.5601160	-1.930	± 100
115.00	-20	13.5601590	-1.961	± 100
97.15	20	13.5599610	-1.815	± 100
132.25	20	13.5601960	-1.989	± 100