

# EMC TEST REPORT

|                                         |                                |                                                                                                                                                                                                                              |      |
|-----------------------------------------|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| <b>Project No.</b>                      | <b>LBE20161563</b>             | <b>Revision No.</b>                                                                                                                                                                                                          | None |
| <b>FCC ID</b>                           | <b>A3LLS27E360</b>             |                                                                                                                                                                                                                              |      |
| <b>Applicant</b>                        | <b>Name of organization</b>    | Samsung Electronics Co., Ltd.                                                                                                                                                                                                |      |
|                                         | <b>Address</b>                 | Samsung Electronics America QA Lab<br>19 Chapin Rd. Building D Pine Brook NJ 07058                                                                                                                                           |      |
|                                         | <b>Date of application</b>     | Apr 25, 2016                                                                                                                                                                                                                 |      |
| <b>EUT<br/>Equipment<br/>Under Test</b> | <b>Type of device</b>          | Class B personal computers and peripherals                                                                                                                                                                                   |      |
|                                         | <b>Equipment authorization</b> | <input type="checkbox"/> Declaration of Conformity <input checked="" type="checkbox"/> Certification <input type="checkbox"/> Verification                                                                                   |      |
|                                         | <b>Kind of product</b>         | <b>LCD MONITOR</b>                                                                                                                                                                                                           |      |
|                                         | <b>Model No.</b>               | <b>LS27E36*</b><br>The symbol "*" in the model name can be any alphanumeric character                                                                                                                                        |      |
|                                         |                                | <b>Variant Model No.</b>                                                                                                                                                                                                     | -    |
|                                         | <b>Manufacturer</b>            | Tianjin Samsung Electronics Co., LTD.<br>Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd.<br>Xiqing Dist, Tianjin, 300385 China<br>No.20 Jiangtai Road, the West Zone of TEDA ,Tianjin,<br>People's Republic of China |      |
| <b>Applied Standards</b>                | FCC Part 15, Subpart B class B |                                                                                                                                                                                                                              |      |
|                                         | ANSI C63.4-2014                |                                                                                                                                                                                                                              |      |
| <b>Test period</b>                      | Apr 25, 2016 ~ Apr26, 2016     |                                                                                                                                                                                                                              |      |
| <b>Issue date</b>                       | Apr 26, 2016                   |                                                                                                                                                                                                                              |      |

## Test result : Complied

The equipment under test has found to be compliant with the applied standards.  
(Refer to the attached test result for more detail.)

**Tested by** : Jie Yang



**Reviewed by** : Zhongyuan Gao



The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from CSQAL



TSEC Wei 4 Road, Microelectronics Industrial Park, Jingang High way, Tianjin, China  
Tel: 86 22 23961234, Fax: 86 22 23961234-5214

According to Sec. 2.1077, 47 CFR of the FCC Rules.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

|                           |                                                                                                                                                                                                                              |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Equipment EUT Type</b> | Class B personal computers and peripherals                                                                                                                                                                                   |
| <b>Kind of product</b>    | <b>LCD Monitor</b>                                                                                                                                                                                                           |
| <b>Trade Name</b>         | Samsung Electronics                                                                                                                                                                                                          |
| <b>Model</b>              | <b>LS27E36*</b>                                                                                                                                                                                                              |
| <b>Applied Rules</b>      | FCC Part 15, Subpart B Class B                                                                                                                                                                                               |
|                           | ANSI C63.4-2014                                                                                                                                                                                                              |
| <b>Manufacturer</b>       | Tianjin Samsung Electronics Co., LTD.<br>Weisi Rd. Micro-Electronic Industrial Park, Jingang Rd.<br>Xiqing Dist, Tianjin, 300385 China<br>No.20 Jiangtai Road, the West Zone of TEDA ,Tianjin,<br>People's Republic of China |

We hereby *declare that* the equipment bearing the trade name and model number specified above was tested conforming to the applicable FCC Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the Commission's requirements.

|                               |                                                                                                                                                                                                               |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>U.S. RESPONSIBLE PARTY</b> | Samsung Electronics America QA Lab<br>19 Chapin Rd. Building D Pine Brook NJ 07058                                                                                                                            |
| <b>CONTACT PERSON</b>         | <br><u>Mr. Chan-ho Youn, Manager</u><br>E-Mail : jjano.youn@samsung.com<br>Tel : 1-973-808-6362      Fax : 1-973-808-6361 |

---

# Table of contents

## **1. Report information**

- 1.1 Revision history
- 1.2 Sample calculation

## **2. Summary of test results**

- 2.1 Emission

## **3. General Information**

- 3.1 Test facility

## **4. Test configuration**

- 4.1 Test Peripherals
- 4.2 EUT operating mode
- 4.3 Details of Sampling
- 4.4 Used cable description
- 4.5 EUT Description
- 4.6 Description of the EUT exercising method
- 4.7 Measurement uncertainty

## **5. Result of individual tests**

- 5.1 Conducted disturbance
- 5.2 Radiated disturbance

## **Appendix – EUT photography**

# 1. Report information

## 1.1 Revision history

| No.     | Revised detailed information                                  |
|---------|---------------------------------------------------------------|
| Issue 0 | There are no revisions and this version is basic test report. |

## 1.2 Sample calculation

### 1.2.1 Conducted disturbance (at 10 MHz)

- Class B limit = 60 dB $\mu$ V (Quasi-peak limit)
- Level (50 dB $\mu$ V) = Meter Reading (40.2 dB $\mu$ V) + factor ( 9.8 dB, AMN factor 9.7 dB + Cable loss 0.1 dB)
- Margin (10 dB) = Limit (60 dB $\mu$ V) – Level (50 dB $\mu$ V) = 10 dB below limit

### 1.2.2 Radiated disturbance (at 100 MHz)

- Class B limit = 40 dB $\mu$ V/m at 3 m
- Level (30 dB $\mu$ V/m) = Meter Reading (50 dB $\mu$ V) + factor (- 20 dB(1/m), antenna factor + cable loss – amplifier gain)
- Margin (10 dB) = Limit (40 dB $\mu$ V/m) – Level (30 dB $\mu$ V/m) = 10 dB below limit

## 2. Summary of test results

The EUT has been tested according to the following specifications:

| Applied                             | Test type                             | Applied standard         | Result   | Remarks             |
|-------------------------------------|---------------------------------------|--------------------------|----------|---------------------|
| <input checked="" type="checkbox"/> | Conducted Disturbance<br>(Mains Port) | FCC Part 15<br>Subpart B | Complied | Meets Class B Limit |
| <input checked="" type="checkbox"/> | Radiated Disturbance                  |                          | Complied | Meets Class B Limit |

- Note : These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

## 3. General Information

### 3.1 Test facility

The following firm has submitted the information required by Section 2.948 of the FCC Rules for measuring devices subject to Certification under Parts 15 & 18. The FCC takes no responsibility regarding the capability of this firm for performing the required measurements. Accordingly, this firm should not advertise or otherwise imply FCC approval of CSQAL.

CHINA SAMSUNG QUALITY ASSURANCE LABORATORY is LOCATED ON Block D, 17 - 19, Wei 4 Road, Microelectronics Industrial Park, Jingang Highway, Tianjin China.

Registration Number: 745769

E-mail Address: zhongyuan.gao@samsung.com

Phone Number: 86-22-2396-1234-5211

All testing are performed in Semi-anechoic chambers conforming to the site attenuation

Characteristics defined by ANSI C63.4, CISPR 22, 16-1 and 16-2 and Shielded rooms.

CSQAL is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

## 4. Test Setup configuration

### 4.1 Test Peripherals

The peripherals which were interconnected to the EUT during the test are as follows:

| Item         | Model No.    | Serial No.                | Manufacturer | Note |
|--------------|--------------|---------------------------|--------------|------|
| LCD Monitor  | LS27E360     | -                         | Samsung      | EUT  |
| Adapter      | A2514_KSM    | CN07BN4400865ASE38H1PY3JX | SEM          |      |
| PC           | DM-V200-PA15 | ZLPZ9WAZ600123A           | Samsung      | -    |
| Printer      | CLP-367W     | Z8TEBJBC800037K           | Samsung      | -    |
| Printer      | CLP-365W     | Z8DLBABC200070K           | Samsung      | -    |
| USB Keyboard | SK-8185      | OY526K                    | Dell         | -    |
| USB Mouse    | MOC5UO       | J0G00G9L                  | Dell         | -    |

### 4.2 EUT operating mode(s)

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

|                         |         |
|-------------------------|---------|
| <b>Operating Mode 1</b> | VGA IN  |
| <b>Operating Mode 2</b> | HDMI IN |

### 4.3 Details of Sampling

Customer selected, single unit.

### 4.4 Cable description

The type(s) of cables which were connected to the ports (of the EUT) are as follows:

| No | Connect Cable | Length [m] | Ferrite core [Y/N] | Remark  |
|----|---------------|------------|--------------------|---------|
| 1  | HDMI IN       | 1.5        | Y                  | To PC   |
| 2  | VGA IN        | 1.5        | Y                  | To PC   |
| 3  | POWER         | 1.8        | N                  | For EUT |

## 4.5 EUT Description

The following features describe EUT represented by this report:

Test model: **LS27E360**

Maximum Clock Frequency: 148.5MHz

Panel Model: CY-MJ270BNLV1V Manufacturer: SDC


| Model Name                   |               | S27E360F                                                                                                                                                  | S27E360H / S27E390H / S27E391H /<br>S27E393H / S27E395H PLUS |
|------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Panel                        | Size          | 27 CLASS<br>27 Inches (68 cm)                                                                                                                             |                                                              |
|                              | Display area  | 597.9 mm (H) x 336.3 mm (V)<br>23.5 Inches (H) x 13.2 Inches (V)                                                                                          |                                                              |
|                              | Pixel Pitch   | 0.3114 mm (H) x 0.3114 mm (V)<br>0.01226 Inches (H) x 0.01226 Inches (V)                                                                                  |                                                              |
| Power Supply                 |               | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz ± 3 Hz<br><br>Refer to the label at the back of the product as the standard voltage can vary in different countries. |                                                              |
| Dimensions (WxHxD) / Weight  | Without Stand | 626.0 x 377.2 x 70.8 mm / 4.58 kg<br>24.6 x 14.9 x 2.8 Inches / 10.1 lbs                                                                                  |                                                              |
|                              | With Stand    | 626.0 x 452.9 x 181.9 mm / 5.14 kg<br>24.6 x 17.8 x 7.2 Inches / 11.3 lbs                                                                                 |                                                              |
| VESA Mounting Interface      |               | 75 mm x 75 mm<br>3.0 Inches x 3.0 Inches<br>(For use with Specialty(Arm) Mounting hardware.)                                                              |                                                              |
| Environmental considerations | Operating     | Temperature : 50 °F – 104 °F (10 °C – 40 °C)<br>Humidity : 10 % – 80 %, non-condensing                                                                    |                                                              |
|                              | Storage       | Temperature : -4 °F – 113 °F (-20 °C – 45 °C)<br>Humidity : 5 % – 95 %, non-condensing                                                                    |                                                              |

**Test Voltage: 110 V, 60 Hz**

## 4.6 Description of the EUT exercising method

The EUT exercise program used during EMI testing was CSQAL standardized test program for MS Windows. The program repetitively sends a screen of H – Character to the display. Connect video output of computer on EUT's PC IN (D-sub), HDMI port and scrolled H – character continuously on EUT's screen.

The EUT system includes a monitor, the operational conditions shown as follows, within the selected area.



- Notes:**
1. Set the brightness control to maximum
  2. Set the contrast control to maximum
  3. Display a pattern of a full screen of scrolling letter-H characters with a font size to get as close as possible to three characters per linear cm and use single line spacing

#### 4.7 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4 and UKAS Lab 34.)

| Test type                                  |            |                | Measurement uncertainty<br>(C.L. 95 %, k = 2) |
|--------------------------------------------|------------|----------------|-----------------------------------------------|
| Disturbance voltage at the mains terminals |            |                | 3.0 dB                                        |
| Radiated Disturbance                       | Horizontal | 30 MHz - 1 GHz | 5.0 dB                                        |
|                                            | Vertical   | 30 MHz - 1 GHz | 5.0 dB                                        |
|                                            | Horizontal | 1GHz - 6 GHz   | 3.7 dB                                        |
|                                            | Vertical   | 1GHz - 6 GHz   | 3.7 dB                                        |

## 4. Results of individual test

### 4.1 Conducted disturbance

Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.

The EUT measured in accordance with the methods described in standards.

#### Limits for conducted disturbance at the mains ports of class B ITE

| Frequency range Limits<br>MHz | Limits dB(μV) |          |
|-------------------------------|---------------|----------|
|                               | Quasi-peak    | Average  |
| 0,15 to 0,50                  | 66 to 56      | 56 to 46 |
| 0,50 to 5                     | 56            | 46       |
| 5 to 30                       | 60            | 50       |

Note 1: 1 μV is regarded as 0 dB.  
 Note 2: The limits shall decreases linearly with the logarithm of the frequency in the range 150 – 500 kHz.  
 Note 3: If the average limit is met in the measurement with quasi-peak detector, the measurement with average detector is unnecessary.  
 Note 4: The lower limit shall apply at the transition frequency.

If the reading on the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 seconds at each measurement frequency, the highest reading shall be recorded, with the exception of any brief isolated high reading (which shall be ignored).

#### 4.1.1 Test instrumentation

Test instrumentation used in the Conducted disturbance test was as follows:

| Test instrumentation     | Model name | Manufacturer | Serial or Firmware (No./Ver.) | Calibration |                  |
|--------------------------|------------|--------------|-------------------------------|-------------|------------------|
|                          |            |              |                               | Date        | Interval (Month) |
| Test Software            | EP5CE      | TOYO         | V 5.4.40                      | N/A         | N/A              |
| Measuring receiver       | ESCI       | R&S          | 101027                        | 2016.03.02  | 12               |
| Artificial mains network | ENV216     | R&S          | 101815                        | 2015.08.03  | 12               |
| Artificial mains network | ENV216     | R&S          | 101122                        | 2015.08.03  | 12               |

#### 4.1.2 Photograph of the test Configuration

(Front)



(Rear)



### 4.1.3 Test results


|                   |                     |         |                   |        |                      |           |
|-------------------|---------------------|---------|-------------------|--------|----------------------|-----------|
| Test date         | 2016.04.26          |         | Test engineer     |        | Jie Yang             |           |
| Climate condition | Ambient temperature | 21±1 °C | Relative humidity | 21±1 % | Atmospheric pressure | 102±0 kPa |
| Test place        | Shielded Room #2    |         |                   |        |                      |           |

### 4.1.4 Test data

#### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum, Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result

##### --- N Phase ---


| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c. f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|-----|-----------------|---------------------|----------------------|-----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| 1   | 0.182           | 43.3                | 35.7                 | 10.0      | 53.3               | 45.7                | 64.4              | 54.4              | 11.1           | 8.7             |
| 2   | 0.2431          | 35.0                | 22.8                 | 9.9       | 44.9               | 32.7                | 62.0              | 52.0              | 17.1           | 19.3            |
| 3   | 0.18222         | 42.7                | 34.5                 | 10.0      | 52.7               | 44.5                | 64.4              | 54.4              | 11.7           | 9.9             |
| 4   | 29.9076         | 30.1                | 28.6                 | 10.3      | 40.4               | 38.9                | 60.0              | 50.0              | 19.6           | 11.1            |

##### --- L1 Phase ---

| No. | Frequency [MHz] | Reading QP [dB(uV)] | Reading CAV [dB(uV)] | c. f [dB] | Result QP [dB(uV)] | Result CAV [dB(uV)] | Limit QP [dB(uV)] | Limit AV [dB(uV)] | Margin QP [dB] | Margin CAV [dB] |
|-----|-----------------|---------------------|----------------------|-----------|--------------------|---------------------|-------------------|-------------------|----------------|-----------------|
| 1   | 0.18108         | 44.1                | 35.8                 | 10.0      | 54.1               | 45.8                | 64.4              | 54.4              | 10.3           | 8.6             |
| 2   | 0.18196         | 44.2                | 36.5                 | 10.0      | 54.2               | 46.5                | 64.4              | 54.4              | 10.2           | 7.9             |
| 3   | 0.24404         | 35.6                | 23.9                 | 10.0      | 45.6               | 33.9                | 62.0              | 52.0              | 16.4           | 18.1            |

### ■ Operating Mode: HDMI IN Display

Set the brightness control to maximum, Set the contrast control to maximum  
Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result

--- N Phase ---

| No. | Frequency<br>[MHz] | Reading<br>QP<br>[dB(uV)] | Reading<br>CAV<br>[dB(uV)] | c. f<br>[dB] | Result<br>QP<br>[dB(uV)] | Result<br>CAV<br>[dB(uV)] | Limit<br>QP<br>[dB(uV)] | Limit<br>AV<br>[dB(uV)] | Margin<br>QP<br>[dB] | Margin<br>CAV<br>[dB] |
|-----|--------------------|---------------------------|----------------------------|--------------|--------------------------|---------------------------|-------------------------|-------------------------|----------------------|-----------------------|
| 1   | 0.18522            | 41.9                      | 35.5                       | 10.0         | 51.9                     | 45.5                      | 64.2                    | 54.2                    | 12.3                 | 8.7                   |
| 2   | 0.2454             | 32.5                      | 20.4                       | 9.9          | 42.4                     | 30.3                      | 61.9                    | 51.9                    | 19.5                 | 21.6                  |
| 3   | 29.9094            | 32.8                      | 31.2                       | 10.3         | 43.1                     | 41.5                      | 60.0                    | 50.0                    | 16.9                 | 8.5                   |
| 4   | 26.91768           | 30.6                      | 29.9                       | 10.3         | 40.9                     | 40.2                      | 60.0                    | 50.0                    | 19.1                 | 9.8                   |

--- L1 Phase ---

| No. | Frequency<br>[MHz] | Reading<br>QP<br>[dB(uV)] | Reading<br>CAV<br>[dB(uV)] | c. f<br>[dB] | Result<br>QP<br>[dB(uV)] | Result<br>CAV<br>[dB(uV)] | Limit<br>QP<br>[dB(uV)] | Limit<br>AV<br>[dB(uV)] | Margin<br>QP<br>[dB] | Margin<br>CAV<br>[dB] |
|-----|--------------------|---------------------------|----------------------------|--------------|--------------------------|---------------------------|-------------------------|-------------------------|----------------------|-----------------------|
| 1   | 0.18448            | 42.4                      | 34.8                       | 10.0         | 52.4                     | 44.8                      | 64.3                    | 54.3                    | 11.9                 | 9.5                   |
| 2   | 0.24674            | 33.8                      | 22.5                       | 10.0         | 43.8                     | 32.5                      | 61.9                    | 51.9                    | 18.1                 | 19.4                  |

Note) Level (Quasi-Peak and/or Average) = Meter Reading (Quasi-Peak and/or Average) +  
Factor (LISN Insertion Loss + Cable Loss)

Margin = Limit – Level (Quasi-Peak and/or Average)

## 4.2 Radiated disturbance

Of those disturbances above ( $L - 20\text{dB}$ ), where  $L$  is the limit level in logarithmic units, record at least the disturbance levels and the frequencies of the six highest disturbances.

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin. All measurements were taken utilizing quasi-peak detection unless stated otherwise.

Measurements were performed at an antenna to EUT distance of 3 meters and elevated between 1 and 4 meters. Both vertical and horizontal antenna polarizations were measured.

Above 1GHz, peak detector function mode was used with resolution bandwidth of 1 MHz and a video bandwidth of 1 MHz. If the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency range Limits<br>MHz                                                      | Quasi-peak Limits (microvolts/meter) |
|------------------------------------------------------------------------------------|--------------------------------------|
|                                                                                    | Class B                              |
| 30 to 88                                                                           | 100                                  |
| 88 to 216                                                                          | 150                                  |
| 216 to 960                                                                         | 200                                  |
| Above 960                                                                          | 500                                  |
| Note 1: The lower limit shall apply at the transition frequency.                   |                                      |
| Note 2: Additional provisions may be required for cases where interference occurs. |                                      |
| Note 3: 1 $\mu\text{V/m}$ is regarded as 0 dB.                                     |                                      |

Measurements above 1GHz were performed at an antenna to EUT distance of 3 meters and elevated 1 to 4 meters in FAC. Both vertical and horizontal antenna polarizations were measured.

The test is performed in a semi-anechoic chamber, use of absorbing material to cover part of the metal ground plane, the dimension of the absorbing material is: 3 x 3 x 0.3 m (W x D x H)

### Limits for radiated disturbance of ITE at a measuring distance of 3 m

| Frequency range Limits<br>MHz                                    | Class A                       |                                  | Class B                       |                                  |
|------------------------------------------------------------------|-------------------------------|----------------------------------|-------------------------------|----------------------------------|
|                                                                  | Peak<br>dB( $\mu\text{V/m}$ ) | Average<br>dB( $\mu\text{V/m}$ ) | Peak<br>dB( $\mu\text{V/m}$ ) | Average<br>dB( $\mu\text{V/m}$ ) |
| 1000 to 3000                                                     | 76                            | 56                               | 70                            | 50                               |
| 3000 to 6000                                                     | 80                            | 60                               | 74                            | 54                               |
| Note 1: The lower limit shall apply at the transition frequency. |                               |                                  |                               |                                  |

## 4.2.1 Test instrumentation

Test instrumentation used in the Radiated disturbance was as follows:

### 30MHz~1GHz

| Test instrumentation | Model name | Manufacturer | Serial or Firmware (No./Ver.) | Calibration |                  |
|----------------------|------------|--------------|-------------------------------|-------------|------------------|
|                      |            |              |                               | Date        | Interval (Month) |
| Test Software        | EP5/RE     | TOYO         | V 5.7.10                      | N/A         | N/A              |
| Bi-con Antenna       | CBL6112D   | TESEQ        | 29069                         | 2015.03.16  | 24               |
| EMI Receiver         | ESCI       | R&S          | 101026                        | 2016.03.02  | 12               |
| AMPLIFIER            | 310N       | SONOMA       | 300911                        | 2015.07.05  | 12               |
| Ant Mast             | MA4000     | INN CO       | -                             | N/A         | N/A              |
| Mast Controller      | CO2000     | INN CO       | -                             | N/A         | N/A              |
| RF Selector          | NS4900N    | TOYO         | -                             | N/A         | N/A              |

### Above 1GHz

| Test instrumentation    | Model name | Manufacturer | Serial or Firmware (No./Ver.) | Calibration |                  |
|-------------------------|------------|--------------|-------------------------------|-------------|------------------|
|                         |            |              |                               | Date        | Interval (Month) |
| Test Software           | EP5/RE     | TOYO         | V 5.7.10                      | N/A         | N/A              |
| Broad-Band Horn Antenna | BBHA9120B  | Schwarzbeck  | 521                           | 2014.04.16  | 24               |
| EMI Receiver            | ESU26      | R&S          | 100244                        | 2016.03.02  | 12               |
| AMPLIFIER               | TPA0108-40 | TOYO         | 1409                          | 2016.03.02  | 12               |
| Ant Mast                | AUDIX      | AUDIX        | -                             | N/A         | N/A              |

## 4.2.2 Photograph of the test Configuration

30MHz~1GHz

(Front)



(Rear)



**Above 1GHz  
(Front)**



**(Rear)**



## 4.2.3 Test results

### 30MHz~1GHz


|                   |                          |         |                   |        |                      |           |
|-------------------|--------------------------|---------|-------------------|--------|----------------------|-----------|
| Test date         | 2016.04.26               |         | Test engineer     |        | Jie Yang             |           |
| Climate condition | Ambient temperature      | 21±1 °C | Relative humidity | 21±1 % | Atmospheric pressure | 102±0 kPa |
| Test place        | 3m Semi-Anechoic Chamber |         |                   |        |                      |           |

#### ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result


| No. | Frequency [MHz] | (P) | Reading QP [dB (μV)] | c. f [dB (1/m)] | Result QP [dB (μV/m)] | Limit QP [dB (μV/m)] | Margin QP [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|----------------------|-----------------|-----------------------|----------------------|----------------|-------------|-----------|
| 1   | 425.182         | V   | 46.5                 | -3.8            | 42.7                  | 46.0                 | 3.3            | 109.0       | 175.5     |
| 2   | 197.980         | H   | 49.4                 | -12.9           | 36.5                  | 43.5                 | 7.0            | 168.0       | 205.7     |
| 3   | 216.728         | H   | 45.6                 | -12.6           | 33.0                  | 46.0                 | 13.0           | 132.0       | 194.5     |
| 4   | 181.441         | V   | 44.9                 | -13.1           | 31.8                  | 43.5                 | 11.7           | 158.0       | 38.9      |
| 5   | 35.578          | V   | 38.5                 | -8.5            | 30.0                  | 40.0                 | 10.0           | 243.0       | 46.0      |
| 6   | 115.602         | V   | 41.8                 | -10.8           | 31.0                  | 43.5                 | 12.5           | 137.0       | 354.4     |

### ■ Operating Mode: HDMI IN Display

Set the brightness control to maximum

Set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result

| No. | Frequency [MHz] | (P) | Reading QP [dB(μV)] | c. f [dB(1/m)] | Result QP [dB(μV/m)] | Limit QP [dB(μV/m)] | Margin QP [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|----------------|----------------------|---------------------|----------------|-------------|-----------|
| 1   | 205.839         | H   | 48.1                | -12.8          | 35.3                 | 43.5                | 8.2            | 142.0       | 191.6     |
| 2   | 130.152         | V   | 39.3                | -10.7          | 28.6                 | 43.5                | 14.9           | 101.0       | 353.6     |
| 3   | 742.466         | H   | 41.7                | 1.2            | 42.9                 | 46.0                | 3.1            | 109.0       | 136.5     |
| 4   | 177.076         | V   | 44.6                | -12.9          | 31.7                 | 43.5                | 11.8           | 156.0       | 44.9      |
| 5   | 180.108         | H   | 43.6                | -13.0          | 30.6                 | 43.5                | 12.9           | 202.0       | 35.6      |
| 6   | 199.508         | H   | 44.1                | -12.8          | 31.3                 | 43.5                | 12.2           | 189.0       | 193.0     |

Note) Receiving antenna polarization : Horizontal and/or Vertical

Test Distance : 3m, Antenna Height : 1 to 4 meters

Result (Quasi-Peak) = Reading QP + C.F (Antenna Factor + Cable Loss - Amp. Gain)

Margin QP (Quasi-Peak) = Limit - Level QP


## Above 1GHz

|                   |                          |         |                   |        |                      |           |
|-------------------|--------------------------|---------|-------------------|--------|----------------------|-----------|
| Test date         | 2016.04.26               |         | Test engineer     |        | Jie Yang             |           |
| Climate condition | Ambient temperature      | 22±1 °C | Relative humidity | 23±1 % | Atmospheric pressure | 102±0 kPa |
| Test place        | 3m Semi-Anechoic Chamber |         |                   |        |                      |           |

## ■ Operating Mode: D-Sub (PC Video IN or Analog) IN Display

Set the brightness control to maximum, set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.




## Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading CAV [dB(μV)] | c. f [dB(1/m)] | Result PK [dB(μV/m)] | Result CAV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin CAV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|----------------------|----------------|----------------------|-----------------------|---------------------|---------------------|----------------|-----------------|-------------|-----------|
| 1   | 1039.450        | V   | 73.0                | 61.1                 | -19.2          | 53.8                 | 41.9                  | 70.0                | 50.0                | 16.2           | 8.1             | 141.0       | 354.8     |
| 2   | 1930.500        | V   | 64.6                | 55.8                 | -18.2          | 46.4                 | 37.6                  | 70.0                | 50.0                | 23.6           | 12.4            | 302.0       | 348.7     |
| 3   | 1930.625        | H   | 65.6                | 59.6                 | -18.2          | 47.4                 | 41.4                  | 70.0                | 50.0                | 22.6           | 8.6             | 157.0       | 336.8     |
| 4   | 1499.875        | V   | 66.2                | 59.4                 | -19.0          | 47.2                 | 40.4                  | 70.0                | 50.0                | 22.8           | 9.6             | 246.0       | 169.7     |
| 5   | 1039.375        | H   | 65.2                | 56.4                 | -19.2          | 46.0                 | 37.2                  | 70.0                | 50.0                | 24.0           | 12.8            | 236.0       | 309.6     |
| 6   | 1500.000        | H   | 64.6                | 57.3                 | -19.0          | 45.6                 | 38.3                  | 70.0                | 50.0                | 24.4           | 11.7            | 179.0       | 110.6     |

### ■ Operating Mode: HDMI IN Display

Set the brightness control to maximum, set the contrast control to maximum

Scan three resolutions (800\*600@60Hz, 1024\*768@60Hz, 1920\*1080@60Hz), then choose the worst one (1920\*1080@60Hz) for final evaluation.



#### Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading CAV [dB(μV)] | c. f [dB(1/m)] | Result PK [dB(μV/m)] | Result CAV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin CAV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|----------------------|----------------|----------------------|-----------------------|---------------------|---------------------|----------------|-----------------|-------------|-----------|
| 1   | 1039.473        | V   | 70.3                | 60.4                 | -19.2          | 51.1                 | 41.2                  | 70.0                | 50.0                | 18.9           | 8.8             | 143.0       | 348.0     |
| 2   | 1039.500        | H   | 65.8                | 60.2                 | -19.2          | 46.6                 | 41.0                  | 70.0                | 50.0                | 23.4           | 9.0             | 167.0       | 350.9     |
| 3   | 1500.000        | V   | 65.9                | 59.9                 | -19.0          | 46.9                 | 40.9                  | 70.0                | 50.0                | 23.1           | 9.1             | 248.0       | 165.6     |
| 4   | 1930.625        | H   | 62.8                | 57.3                 | -18.2          | 44.6                 | 39.1                  | 70.0                | 50.0                | 25.4           | 10.9            | 186.0       | 34.1      |
| 5   | 1930.500        | V   | 63.1                | 54.6                 | -18.2          | 44.9                 | 36.4                  | 70.0                | 50.0                | 25.1           | 13.6            | 248.0       | 39.1      |
| 6   | 1499.750        | H   | 64.9                | 56.1                 | -19.0          | 45.9                 | 37.1                  | 70.0                | 50.0                | 24.1           | 12.9            | 348.0       | 43.6      |

Note1) (P) : Abbreviation of Antenna Polarity

Note2) Reading PK / C/AV : Received raw Peak / C/Average signal

Note3) Factor = Antenna factor + Cable loss – Amplifier gain

Note4) Level PK / C/AV = Reading PK / C/AV + Factor, Real signal Peak / C/Average level

Note5) Margin PK / C/AV = Limit – Level PK / C/AV

PK : Abbreviation of Peak

C/AV : Abbreviation of CISPR Average


## Appendix A – EUT photography (Front)



(Rear)




(Up)




(Down)



(Left)



(Right)




(Panel )




(Main Board )



(MAIN Board )



(Crystal Main Board)



(Power Board)



(Power Board)

