

# TEST REPORT

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,  
Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:

CTK-2025-01906

Page (1) / (221) pages

**1. Applicant**

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, 16677, Korea
- Date of Receipt : 2025-06-04

**2. Manufacturer**

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, 16677, Korea

**3. Use of Report** : For FCC Certification**4. Test Sample / Model:** MMU (MT1602d) / MT1602d-48B**5. Date of Test** : 2025-06-04 to 2025-07-21**6. Test Standard(method) used** : FCC 47 CFR Part 96, ANSI C63.26-2015**7. Testing Environment:** refer to 10 page**8. Test Results** : Compliance**9. Location of Test** : ☒ Permanent Testing Lab ☐ On Site Testing

(Address : 5, Dongbu-ro 221 beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This report cannot be reproduced or copied without the written consent of CTK.

|          |                                                                                                             |                                                                                                                  |
|----------|-------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Approval | Tested by                                                                                                   | Technical Manager                                                                                                |
|          | Du-Jin Kim: (Signature)  | Byung-Kwon In: (Signature)  |

2025-07-21

**CTK Co., Ltd.**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (2) / (221) pages

## TABLE OF CONTENTS

|      |                                                           |     |
|------|-----------------------------------------------------------|-----|
| 1.0  | REVISION RECORD .....                                     | 4   |
| 2.0  | INTRODUCTION .....                                        | 5   |
| 2.1  | Scope .....                                               | 5   |
| 2.2  | Test Location .....                                       | 5   |
| 2.3  | Laboratory Accreditations and Listings .....              | 5   |
| 3.0  | PRODUCT INFORMATION .....                                 | 6   |
| 3.1  | Equipment Description .....                               | 6   |
| 3.2  | Device Capabilities .....                                 | 6   |
| 3.3  | Test Configuration .....                                  | 7   |
| 3.4  | EMI Suppression Device(s)/Modifications .....             | 8   |
| 4.0  | DESCRIPTION OF TESTS .....                                | 9   |
| 4.1  | Measurement Procedure .....                               | 9   |
| 4.2  | Measurement Software .....                                | 10  |
| 4.3  | Environmental Conditions .....                            | 10  |
| 5.0  | MEASUREMENT UNCERTAINTY .....                             | 11  |
| 6.0  | TEST EQUIPMENT CALIBRATION DATA .....                     | 12  |
| 7.0  | SAMPLE CALCULATIONS .....                                 | 13  |
| 8.0  | TEST RESULTS .....                                        | 14  |
| 8.1  | Summary .....                                             | 14  |
| 8.2  | Occupied Bandwidth .....                                  | 15  |
| 8.3  | Modulation Characteristics .....                          | 27  |
| 8.4  | Maximum Power Spectral Density .....                      | 29  |
| 8.5  | Maximum Equivalent Isotropic Radiated Power (EIRP) .....  | 50  |
| 8.6  | Peak To Average Power Ratio (PAPR) .....                  | 70  |
| 8.7  | Channel Edge Emissions at Antenna Terminal .....          | 81  |
| 8.8  | Spurious and Harmonic Emissions at Antenna Terminal ..... | 135 |
| 8.9  | Frequency Stability .....                                 | 192 |
| 8.10 | Radiated spurious emission .....                          | 194 |
| 9.0  | CONCLUSION .....                                          | 206 |
| 10.0 | APPENDIX. A .....                                         | 207 |
| 10.1 | Conducted Average Output Power .....                      | 207 |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (3) / (221) pages

## MEASUREMENT REPORT

### FCC Rule Part 96

| Mode                   | Total Bandwidth (MHz) | Max. PSD (dBm/1MHz) | Max. EIRP (dBm/10MHz) | Max. EIRP /Entire Band Width(dBm) | Max. EIRP /Entire Band Width (W) | Emission Designator | Modulation |
|------------------------|-----------------------|---------------------|-----------------------|-----------------------------------|----------------------------------|---------------------|------------|
| n48_1C_10M             | 10                    | 36.16               | 44.87                 | 44.87                             | 30.69                            | 8M72G7D             | QPSK       |
|                        |                       | 36.44               | 44.98                 | 44.98                             | 31.48                            | 8M71W7D             | QAM        |
| n48_1C_20M             | 20                    | 35.70               | 45.34                 | 48.00                             | 63.10                            | 18M4G7D             | QPSK       |
|                        |                       | 35.91               | 45.40                 | 48.09                             | 64.42                            | 18M4W7D             | QAM        |
| n48_1C_30M             | 30                    | 35.66               | 45.50                 | 49.94                             | 98.63                            | 28M1G7D             | QPSK       |
|                        |                       | 35.74               | 45.43                 | 49.92                             | 98.17                            | 28M0W7D             | QAM        |
| n48_1C_40M             | 40                    | 36.02               | 45.44                 | 51.20                             | 131.83                           | 38M1G7D             | QPSK       |
|                        |                       | 36.24               | 45.57                 | 51.28                             | 134.28                           | 38M1W7D             | QAM        |
| n48_2C_20M+30M         | 50                    | 36.09               | 45.20                 | 51.76                             | 149.97                           | 48M1G7D             | QPSK       |
|                        |                       | 36.13               | 45.87                 | 52.09                             | 161.81                           | 48M1W7D             | QAM        |
| n48_1C_60M             | 60                    | 36.07               | 45.31                 | 52.78                             | 189.67                           | 58M0G7D             | QPSK       |
|                        |                       | 36.11               | 45.44                 | 53.02                             | 200.45                           | 58M1W7D             | QAM        |
| n48_4C_10M+10M+10M+40M | 70                    | 36.43               | 45.21                 | 53.40                             | 218.78                           | 68M2G7D             | QPSK       |
|                        |                       | 36.45               | 45.25                 | 53.52                             | 224.91                           | 68M3W7D             | QAM        |
| n48_1C_80M             | 80                    | 35.89               | 45.31                 | 53.95                             | 248.31                           | 77M7G7D             | QPSK       |
|                        |                       | 36.01               | 45.60                 | 54.24                             | 265.46                           | 77M7W7D             | QAM        |

**EUT Overview**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (4) / (221) pages

## 1.0 REVISION RECORD

| Issue Number   | Issued Date | Revision History |
|----------------|-------------|------------------|
| CTK-2025-01906 | 07/21/2025  | Initial Issue    |
|                |             |                  |
|                |             |                  |

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (5) / (221) pages

## 2.0 INTRODUCTION

### 2.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 2.2 Test Location

These measurement tests were conducted at the CTK Co., Ltd. facility located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

### 2.3 Laboratory Accreditations and Listings

| Country | Agency | Registration Number           |
|---------|--------|-------------------------------|
| USA     | FCC    | 805871                        |
| CANADA  | ISED   | CN : 8737A<br>CAB ID : KR0025 |
| KOREA   | NRRA   | KR0025                        |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (6) / (221) pages

## 3.0 PRODUCT INFORMATION

### 3.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung MMU(MT1602d) FCC ID: A3LMT1602D-48B**.  
The test data contained in this report pertains only to the emissions due to the EUT's licensed transmitters that operate under the provisions of Part 96.

Except when testing for equipment authorization purposes, the subject radio does not operate in standalone n48 (3.5 GHz) band mode.

### 3.2 Device Capabilities

This device supports the following conditional features and filter information:

|                                                               |                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC ID                                                        | A3LMT1602D-48B                                                                                                                                                                                                                                                                                             |
| EUT Type                                                      | MMU(MT1602d)                                                                                                                                                                                                                                                                                               |
| Model Name                                                    | MT1602d-48B                                                                                                                                                                                                                                                                                                |
| Device Capabilities:                                          | 5G NR                                                                                                                                                                                                                                                                                                      |
| Operating Band/Frequency Range:                               | n48: 3 550 MHz to 3 700 MHz<br>n77: 3 700 MHz to 3 980 MHz                                                                                                                                                                                                                                                 |
| Supported Modulation                                          | QPSK, 16QAM, 64QAM, 256QAM                                                                                                                                                                                                                                                                                 |
| n48 Supported Number of Carriers and Channel Bandwidth        | 10, 20, 30, 40, 60 and 80MHz bandwidth for n48 with up to 4CC aggregated of Max. Bandwidth 80 MHz                                                                                                                                                                                                          |
| n77 Supported Number of Carriers and Channel Bandwidth        | 40, 60, 80 and 100MHz bandwidth for n77 with up to 2CC aggregated of Max. Bandwidth 200 MHz                                                                                                                                                                                                                |
| Multi-Band Supported Number of Carriers and Channel Bandwidth | n48 and n77 with up to 6CC aggregated of Max. Bandwidth 280 MHz                                                                                                                                                                                                                                            |
| Maximum Output Power                                          | n48 : Max 7.5W/unit<br>n77 : Max 90W/unit<br>Multi-Band: 90W/unit (n48: 7.5W + n77: 82.5W)                                                                                                                                                                                                                 |
| Occupied Bandwidth (OBW)/ Instantaneous Bandwidth (IBW)       | n48: 80 MHz / 150 MHz<br>n77: 200 MHz / 200 MHz                                                                                                                                                                                                                                                            |
| Number of Antenna ports                                       | 16T16R                                                                                                                                                                                                                                                                                                     |
| Supported Configurations                                      | Single carrier, Multi-carrier, Multi-Band                                                                                                                                                                                                                                                                  |
| Input Voltage:                                                | 100~240V AC                                                                                                                                                                                                                                                                                                |
| Maximum antenna gain                                          | n48: User specific beam Max 20.3 dBi (19.8 dBi ± 0.5 dB tolerance)<br>Common Beam Max 14.8 dBi (14.3 dBi ± 0.5 dB tolerance)<br>n77: User specific beam Max 20.7 dBi (20.2 dBi ± 0.5 dB tolerance)<br>Common Beam Max 15.6 dBi (15.1 dBi ± 0.5 dB tolerance)<br>Antenna gain declared by the manufacturer. |



## CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (7) / (221) pages

### 3.3 Test Configuration

The setup is as follows:

- The EUT "MMU(MT1602d)" and a Data Unit (DU) are each powered by 120 VAC and -48V DC power supply.
- The DU is connected to a test laptop via an ethernet cable acting as backhaul.
- DU connects to the EUT through a fiber optic cable.
- An RF cable connects the signal analyzer and the EUT Ports for respective measurements.

The EUT was tested per the guidance of ANSI C63.26-2015 and KDB 971168 D01 v03r01. See Section 8.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

Distribution unit (DU) which were used in test, that authorized under the SDoC procedure.

The following information is about configurations of carrier frequency and output power per port declared by the manufacturer.

\* Abbreviations:

- 1C: single carrier
- 2C: Contiguous 2 carriers in multi-carrier operation
- 2NC: Non-Contiguous 2 carriers in multi-carrier operation

| Configuration                                                      | No. of Carriers | Total Carrier Bandwidth (MHz) | Carrier Frequency Configuration (MHz) |        |       | Rated Conducted Power (W/unit) |
|--------------------------------------------------------------------|-----------------|-------------------------------|---------------------------------------|--------|-------|--------------------------------|
|                                                                    |                 |                               | Low                                   | Middle | High  |                                |
| n48_1C_10M                                                         | 1               | 10                            | 3 555                                 | 3 625  | 3 695 | 29.7                           |
| n48_1C_20M                                                         | 1               | 20                            | 3 560                                 | 3 625  | 3 690 | 32.7                           |
| n48_1C_30M                                                         | 1               | 30                            | 3 565                                 | 3 625  | 3 685 | 34.4                           |
| n48_1C_40M                                                         | 1               | 40                            | 3 570                                 | 3 625  | 3 680 | 35.7                           |
| n48_2C_20M+30M                                                     | 2               | 50                            | 3 575                                 | 3 625  | 3 675 | 36.7                           |
| n48_2NC_20M+30M                                                    |                 |                               | 3 560 + 3 685                         |        |       |                                |
| n48_1C_60M                                                         | 1               | 60                            | 3 580                                 | 3 625  | 3 670 | 37.5                           |
| n48_4C_10M+10M+10M+40M                                             | 4               | 70                            | 3 585                                 | 3 625  | 3 665 | 38.2                           |
| n48_4NC_10M+10M+10M+40M                                            |                 |                               | 3 555 + 3 590 + 3 625+ 3 680          |        |       |                                |
| n48_1C_80M                                                         | 1               | 80                            | 3 590                                 | 3 625  | 3 660 | 38.7                           |
| Multi-band operation<br>n48_1C_80M +<br>n77_1C_60M                 | 2               | 140                           | 3 590 + 3 730                         |        |       | 49.5                           |
| Multi-band operation<br>n48_4C_20M+20M+20M+20M<br>n77_2C_100M+100M | 6               | 280                           | 3 560+3 580+3 600+3 620+3 750+3 850   |        |       | 49.5                           |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (8) / (221) pages

**Notes:**

1. Multi-band operation was tested using the worst-case modulation for each band based on single-carrier results.

**3.4 EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added, and no modifications were made during testing.



## CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (9) / (221) pages

## 4.0 DESCRIPTION OF TESTS

### 4.1 Measurement Procedure

The measurement procedures described in the document titled “American National Standard for Compliance Testing of Transmitter Used in Licensed Radio Service” (ANSI C63.26-2015) and the guidance provided in KDB 971168 D01 v03r01, and KDB 662911 D01 v02r01 and KDB 940660 D01 v03 were used in the measurement of the EUT.

#### Occupied Bandwidth:

KDB 971168 D01 v03r01 – Section 4.3

ANSI C63.26-2015 – Section 5.4.4

#### Modulation Characteristics:

ANSI C63.26 - Section 5.3

#### Conducted Power Measurement and EIRP and PSD

KDB 971168 D01 v03r01 – Section 5.3

KDB 971168 D01 v03r01 – Section 5.4

KDB 662911 D01 v02r01 – Section E)1) In-Band Power Measurements

ANSI C63.26-2015 – Section 5.2.5

ANSI C63.26-2015 – Section 5.2.4

#### Peak-to-Average Power Ratio:

KDB 971168 D01 v03r01 – Section 5.7

ANSI C63.26-2015 – Section 5.2.3.4

#### Channel Edge Emissions at Antenna Terminal

KDB 971168 D01 v03r01 – Section 6

KDB 662911 D01 v02r01 – Section E)3) Out-of-Band and Spurious Emission Measurements

a) Absolute Emission Limits

iii) Measure and add  $10 \log(N_{ANT})$  dB

ANSI C63.26-2015 – Section 5.7

#### Spurious and Harmonic Emissions at Antenna Terminal

KDB 971168 D01 v03r01 – Section 6

KDB 662911 D01 v02r01 – Section E)3) Out-of-Band and Spurious Emission Measurements

a) Absolute Emission Limits

iii) Measure and add  $10 \log(N_{ANT})$  dB

ANSI C63.26-2015 – Section 5.7

#### Radiated unwanted emission

KDB 971168 D01 v03r01 – Section 7

ANSI C63.26-2015 – Section 5.8

#### Frequency Stability / Temperature Variation

KDB 971168 D01 v03r01 – Section 9

ANSI C63.26-2015 – Section 5.6

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (10) / (221) pages

## 4.2 Measurement Software

| Test item             | Name              | Version |
|-----------------------|-------------------|---------|
| Conducted Measurement | Node B automation | 1.0     |
| Radiated Measurement  | EP5RE             | 6.0.1.0 |
|                       | ES10              | 10.001  |

## 4.3 Enviromental Conditions

The temperature is controlled within the range of 15°C to 35°C. The relative humidity is controlled within the range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (11) / (221) pages

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Description                                         | Uncertainty                            |
|-----------------------------------------------------|----------------------------------------|
| Conducted Power Measurement and EIRP                | 1.5 dB (C.L. : Approx. 95%, $k = 2$ )  |
| Occupied bandwidth                                  | 0.1 MHz (C.L. : Approx. 95%, $k = 2$ ) |
| Peak-to-average power ratio                         | 1.0 dB (C.L. : Approx. 95%, $k = 2$ )  |
| Band Edge Emissions at Antenna Terminal             | 3.0 dB (C.L. : Approx. 95%, $k = 2$ )  |
| Spurious and Harmonic Emissions at Antenna Terminal | 3.0 dB (C.L. : Approx. 95%, $k = 2$ )  |
| Radiated Emissions ( $f \leq 1$ GHz)                | 4.11 dB (C.L. : Approx. 95%, $k = 2$ ) |
| Radiated Emissions ( $f > 1$ GHz)                   | 4.64 dB (C.L. : Approx. 95%, $k = 2$ ) |
| Frequency Stability                                 | 0.1 kHz (C.L. : Approx. 95%, $k = 2$ ) |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (12) / (221) pages

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacture     | Model            | Description                 | Cal Date   | Cal interval | Cal Due    | Serial Number       |
|-----------------|------------------|-----------------------------|------------|--------------|------------|---------------------|
| Rohde & Schwarz | FSV30            | SIGNAL ANALYZER             | 2024-11-26 | Annual       | 2025-11-26 | 100925              |
| Rohde & Schwarz | FSV40            | SPECTRUM ANALYZER           | 2025-01-10 | Annual       | 2026-01-10 | 101574              |
| Rohde & Schwarz | ESW44            | EMI TEST RECEIVER           | 2025-04-28 | Annual       | 2026-04-28 | 102039              |
| TESEQ           | CBL6111D         | Bilog Antenna               | 2024-08-21 | Annual       | 2025-08-21 | 60654               |
| PASTERNAK       | PE7AP006-06      | Attenuator                  | 2024-07-31 | Annual       | 2025-07-31 | L20210504000<br>023 |
| SONOMA          | 310N             | AMPLIFIER                   | 2024-07-31 | Annual       | 2025-07-31 | 411011              |
| Agilent         | 8449B            | Preamplifier                | 2025-03-11 | Annual       | 2026-03-11 | 3008A00620          |
| ETS-Lindgren    | 3115             | DOUBLE RIDGED GUIDE ANTENNA | 2025-03-13 | Annual       | 2026-03-13 | 00078895            |
| ESPEC           | EBE-2E20W6P3T-38 | Temperature Chamber         | 2025-04-28 | Annual       | 2026-04-28 | 3015007507          |
| Agilent         | 6674A            | SYSTEM DC POWER SUPPLY      | 2025-03-13 | Annual       | 2026-03-13 | US36372372          |
| Keysight        | N9030B           | Signal Analyzer             | 2025-03-28 | Annual       | 2026-03-28 | MY57142018          |
| Rohde & Schwarz | FSW              | Signal & Spectrum Analyzer  | 2025-03-28 | Annual       | 2026-03-28 | 101250              |
| INSJOY          | RFX0132R         | RF SWITCH SYSTEM            | 2024-10-08 | Annual       | 2025-10-08 | RFS01               |
| AC POWER SUPPLY | ACPD-60150       | DC POWER SUPPLY             | 2025-04-04 | Annual       | 2026-04-04 | DC-1                |

**Table 6-1. Test Equipment**

**Notes:**

1. For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
2. All testing was performed before the calibration due date.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (13) / (221) pages

## 7.0 SAMPLE CALCULATIONS

### **Emission Designator**

#### **QPSK Modulation**

**Emission Designator = 8M72G7D**

Occupied Bandwidth = 8.72 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

#### **QAM Modulation**

**Emission Designator = 8M71W7D**

Occupied Bandwidth = 8.71 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (14) / (221) pages

## 8.0 TEST RESULTS

### 8.1 Summary

Company Name: SAMSUNG Electronics Co., Ltd.  
FCC ID: A3LMT1602D-48B  
Type of Radio Equipment: Citizens Band Category A Devices (CBD)  
Mode(s): 5G NR

| FCC Part Section(s) | Test Description                           | Test Limit                                                                                                                                                                                                                                                                              | Test Condition | Test Result | Reference                  |
|---------------------|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------|----------------------------|
| 2.1049              | Occupied Bandwidth                         | N/A                                                                                                                                                                                                                                                                                     | Conducted      | PASS        | Section 8.2                |
| 2.1046<br>96.41(a)  | Modulation Characteristics                 | Digital modulation                                                                                                                                                                                                                                                                      |                | PASS        | Section 8.3                |
| 2.1046<br>96.41(b)  | Power Spectral Density (PSD)               | Category B CBSD<br>37 dBm/MHz (PSD)                                                                                                                                                                                                                                                     |                | PASS        | Section 8.4                |
| 2.1046<br>96.41(b)  | Equivalent Isotropic Radiated Power (EIRP) | Category B CBSD<br>47 dBm/10MHz (EIRP)                                                                                                                                                                                                                                                  |                | PASS        | Section 8.5                |
| 96.41(g)            | Peak-Average Ratio                         | ≤ 13 dB                                                                                                                                                                                                                                                                                 |                | PASS        | Section 8.6                |
| 2.1051<br>96.41(e)  | Out of Band Emissions                      | Within 0 MHz to 10 MHz above and below the assigned channel ≤ -13 dBm/MHz<br><br>Greater than 10 MHz above and below the assigned channel ≤ -25 dBm/MHz<br><br>Any emission below 3530 MHz and above 3720 MHz ≤ -40 dBm/MHz                                                             |                | PASS        | Section 8.7<br>Section 8.8 |
| Waiver<br>DA 25-387 |                                            | each radio, when operated in 3.5 GHz band-only mode for equipment authorization testing, must comply with section 96.41(e)(2) in its entirety, except the radio's OOB may be limited to a conducted power level of no greater than -25 dBm/MHz for frequencies between 3.72 and 4.0 GHz |                | PASS        |                            |
| 2.1055              | Frequency Stability                        | Fundamental emissions stay within authorized frequency block                                                                                                                                                                                                                            | Radiated       | PASS        | Section 8.9                |
| 2.1051<br>96.41(e)  | Radiated unwanted emission                 | < -40dBm/MHz                                                                                                                                                                                                                                                                            |                | PASS        | Section 8.10               |

**Table 8-1. Summary of Test Results**

- 1) Equipment Authorization test under DA 25-387 Waiver.
- 2) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 3) The analyzer plots were all taken with a correction table loaded into the analyzer.
- 4) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 8.2 Occupied Bandwidth

### Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be. All measured modes of operation were investigated, and the worst case configuration results are reported in this section.

### Test Procedure Used

ANSI C63.26 - Section 5.4.4  
 KDB 971168 D01 v03r01 - Section 4.3


### Test Setting

The measurement was made using a direct connection between the RF output of the EUT and the spectrum analyzer. The spectrum analyzer settings were as follows:

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 8-1. Test Instrument & Measurement Setup**

### Limit

N/A

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (16) / (221) pages

| Channel | Port | OBW (MHz)   |       |             |        |
|---------|------|-------------|-------|-------------|--------|
|         |      | QPSK        | 16QAM | 64QAM       | 256QAM |
| Low     | 0    | 8.69        | 8.63  | 8.68        | 8.67   |
|         | 1    | 8.68        | 8.71  | 8.67        | 8.68   |
|         | 2    | 8.68        | 8.67  | 8.68        | 8.66   |
|         | 3    | 8.67        | 8.66  | 8.67        | 8.69   |
|         | 4    | 8.65        | 8.64  | 8.68        | 8.66   |
|         | 5    | 8.66        | 8.64  | 8.70        | 8.68   |
|         | 6    | 8.67        | 8.66  | 8.67        | 8.68   |
|         | 7    | 8.67        | 8.67  | 8.70        | 8.66   |
|         | 8    | 8.66        | 8.69  | 8.69        | 8.66   |
|         | 9    | 8.67        | 8.66  | 8.70        | 8.71   |
|         | 10   | 8.71        | 8.64  | 8.67        | 8.66   |
|         | 11   | 8.66        | 8.67  | 8.66        | 8.65   |
|         | 12   | 8.69        | 8.70  | 8.70        | 8.66   |
|         | 13   | 8.66        | 8.66  | <b>8.71</b> | 8.65   |
|         | 14   | 8.68        | 8.65  | 8.68        | 8.67   |
| Mid     | 0    | 8.66        | 8.69  | 8.66        | 8.68   |
|         | 1    | 8.70        | 8.65  | 8.68        | 8.68   |
|         | 2    | 8.71        | 8.67  | 8.64        | 8.68   |
|         | 3    | 8.67        | 8.66  | 8.64        | 8.63   |
|         | 4    | 8.67        | 8.66  | 8.67        | 8.65   |
|         | 5    | 8.66        | 8.66  | 8.66        | 8.67   |
|         | 6    | 8.68        | 8.67  | 8.68        | 8.67   |
|         | 7    | 8.67        | 8.67  | 8.66        | 8.65   |
|         | 8    | 8.69        | 8.66  | 8.67        | 8.67   |
|         | 9    | <b>8.72</b> | 8.63  | 8.65        | 8.64   |
|         | 10   | 8.69        | 8.63  | 8.68        | 8.67   |
|         | 11   | 8.67        | 8.67  | 8.67        | 8.70   |
|         | 12   | 8.70        | 8.66  | 8.67        | 8.67   |
|         | 13   | 8.68        | 8.66  | 8.67        | 8.65   |
|         | 14   | 8.66        | 8.64  | 8.67        | 8.68   |
| High    | 0    | 8.67        | 8.65  | 8.66        | 8.68   |
|         | 1    | 8.67        | 8.68  | 8.66        | 8.68   |
|         | 2    | 8.69        | 8.66  | 8.65        | 8.66   |
|         | 3    | 8.65        | 8.66  | 8.66        | 8.64   |
|         | 4    | 8.66        | 8.66  | 8.67        | 8.64   |
|         | 5    | 8.63        | 8.66  | 8.66        | 8.66   |
|         | 6    | 8.66        | 8.65  | 8.68        | 8.65   |
|         | 7    | 8.64        | 8.65  | 8.68        | 8.68   |
|         | 8    | 8.68        | 8.64  | 8.66        | 8.66   |
|         | 9    | 8.66        | 8.66  | 8.67        | 8.67   |
|         | 10   | 8.67        | 8.67  | 8.69        | 8.64   |
|         | 11   | 8.67        | 8.68  | 8.64        | 8.66   |
|         | 12   | 8.71        | 8.66  | 8.69        | 8.65   |
|         | 13   | 8.65        | 8.64  | 8.69        | 8.68   |
|         | 14   | 8.65        | 8.66  | 8.64        | 8.65   |
|         | 15   | 8.66        | 8.64  | 8.66        | 8.66   |

**Table 8-2. Occupied Bandwidth Summary Data (n48\_1C\_10M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (17) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 18.34        | 18.31 | 18.33        | 18.34  |
|         | 1    | 18.33        | 18.31 | 18.26        | 18.27  |
|         | 2    | 18.28        | 18.32 | 18.33        | 18.22  |
|         | 3    | 18.26        | 18.26 | 18.29        | 18.28  |
|         | 4    | 18.26        | 18.30 | 18.29        | 18.32  |
|         | 5    | <b>18.40</b> | 18.36 | 18.26        | 18.23  |
|         | 6    | 18.28        | 18.28 | 18.32        | 18.32  |
|         | 7    | 18.26        | 18.30 | 18.29        | 18.34  |
|         | 8    | 18.32        | 18.26 | 18.29        | 18.32  |
|         | 9    | 18.30        | 18.28 | 18.30        | 18.24  |
|         | 10   | 18.26        | 18.32 | 18.31        | 18.33  |
|         | 11   | 18.32        | 18.28 | 18.31        | 18.33  |
|         | 12   | 18.32        | 18.30 | 18.28        | 18.27  |
|         | 13   | 18.26        | 18.30 | 18.35        | 18.29  |
|         | 14   | 18.30        | 18.28 | 18.33        | 18.26  |
|         | 15   | 18.31        | 18.25 | 18.27        | 18.30  |
| Mid     | 0    | 18.29        | 18.30 | 18.33        | 18.38  |
|         | 1    | 18.28        | 18.34 | 18.32        | 18.28  |
|         | 2    | 18.32        | 18.30 | 18.34        | 18.33  |
|         | 3    | 18.34        | 18.30 | 18.28        | 18.26  |
|         | 4    | 18.31        | 18.32 | 18.35        | 18.25  |
|         | 5    | 18.38        | 18.29 | 18.30        | 18.28  |
|         | 6    | 18.28        | 18.29 | 18.31        | 18.27  |
|         | 7    | 18.27        | 18.27 | 18.30        | 18.28  |
|         | 8    | 18.28        | 18.30 | 18.33        | 18.33  |
|         | 9    | 18.29        | 18.28 | 18.34        | 18.31  |
|         | 10   | 18.32        | 18.32 | 18.32        | 18.26  |
|         | 11   | 18.29        | 18.30 | 18.25        | 18.35  |
|         | 12   | 18.33        | 18.37 | 18.30        | 18.27  |
|         | 13   | 18.31        | 18.32 | 18.29        | 18.28  |
|         | 14   | 18.24        | 18.28 | 18.32        | 18.26  |
|         | 15   | 18.31        | 18.26 | 18.37        | 18.29  |
| High    | 0    | 18.33        | 18.30 | 18.28        | 18.34  |
|         | 1    | 18.27        | 18.28 | <b>18.39</b> | 18.32  |
|         | 2    | 18.29        | 18.32 | 18.32        | 18.30  |
|         | 3    | 18.28        | 18.34 | 18.29        | 18.31  |
|         | 4    | 18.31        | 18.32 | 18.34        | 18.30  |
|         | 5    | 18.33        | 18.28 | 18.32        | 18.28  |
|         | 6    | 18.29        | 18.29 | 18.33        | 18.33  |
|         | 7    | 18.34        | 18.30 | 18.34        | 18.29  |
|         | 8    | 18.30        | 18.29 | 18.28        | 18.28  |
|         | 9    | 18.28        | 18.31 | 18.34        | 18.28  |
|         | 10   | 18.29        | 18.26 | 18.26        | 18.20  |
|         | 11   | 18.29        | 18.31 | 18.32        | 18.28  |
|         | 12   | 18.26        | 18.30 | 18.25        | 18.29  |
|         | 13   | 18.35        | 18.34 | 18.31        | 18.29  |
|         | 14   | 18.33        | 18.30 | 18.31        | 18.24  |
|         | 15   | 18.31        | 18.30 | 18.29        | 18.31  |

**Table 8-3. Occupied Bandwidth Summary Data (n48\_1C\_20M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (18) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 27.99        | 27.99 | 27.89        | 27.96  |
|         | 1    | 27.94        | 27.96 | 27.97        | 27.99  |
|         | 2    | 28.02        | 28.02 | 28.01        | 27.96  |
|         | 3    | 27.94        | 27.97 | 27.98        | 27.97  |
|         | 4    | 27.96        | 27.95 | 27.94        | 27.88  |
|         | 5    | 28.02        | 27.96 | 27.96        | 27.94  |
|         | 6    | 27.93        | 27.92 | 28.04        | 27.93  |
|         | 7    | 27.94        | 27.93 | 28.02        | 27.98  |
|         | 8    | 27.94        | 27.91 | 27.99        | 27.94  |
|         | 9    | 27.95        | 27.94 | 28.00        | 27.98  |
|         | 10   | 27.97        | 27.86 | 28.04        | 27.95  |
|         | 11   | 28.05        | 27.91 | 27.95        | 27.95  |
|         | 12   | 27.87        | 27.92 | 28.01        | 27.99  |
|         | 13   | 27.91        | 27.96 | 27.92        | 27.96  |
|         | 14   | 28.00        | 27.96 | 27.96        | 28.00  |
|         | 15   | 28.00        | 27.89 | 27.92        | 27.97  |
| Mid     | 0    | 27.92        | 27.91 | 27.96        | 27.98  |
|         | 1    | 27.93        | 27.99 | 27.98        | 27.99  |
|         | 2    | 27.90        | 27.95 | 27.93        | 27.95  |
|         | 3    | 28.02        | 27.96 | 27.97        | 27.98  |
|         | 4    | 27.90        | 27.95 | 27.89        | 27.89  |
|         | 5    | 27.96        | 27.95 | 27.91        | 27.93  |
|         | 6    | 27.87        | 27.93 | 27.94        | 28.02  |
|         | 7    | 27.96        | 27.90 | 27.94        | 27.95  |
|         | 8    | 27.94        | 27.96 | 27.95        | 27.99  |
|         | 9    | 27.98        | 27.99 | 27.94        | 27.97  |
|         | 10   | 27.95        | 27.93 | 27.94        | 27.98  |
|         | 11   | 27.91        | 27.97 | 28.02        | 27.98  |
|         | 12   | 27.95        | 27.90 | 27.96        | 27.87  |
|         | 13   | 27.90        | 27.96 | 27.96        | 27.89  |
|         | 14   | 27.92        | 27.96 | 27.88        | 27.97  |
|         | 15   | 28.03        | 28.02 | 27.93        | 27.98  |
| High    | 0    | 27.92        | 27.96 | 28.03        | 27.91  |
|         | 1    | 27.94        | 27.94 | 28.02        | 28.00  |
|         | 2    | 27.93        | 27.98 | 27.91        | 27.91  |
|         | 3    | 27.91        | 27.95 | 27.96        | 27.89  |
|         | 4    | 27.92        | 27.97 | 28.02        | 27.92  |
|         | 5    | 28.00        | 27.99 | 27.95        | 28.03  |
|         | 6    | <b>28.05</b> | 27.99 | 27.96        | 27.94  |
|         | 7    | 27.88        | 27.91 | <b>28.04</b> | 28.02  |
|         | 8    | 27.91        | 27.96 | 27.91        | 27.92  |
|         | 9    | 27.90        | 27.95 | 27.97        | 27.98  |
|         | 10   | 27.98        | 28.00 | 27.97        | 28.02  |
|         | 11   | 27.93        | 27.97 | 27.87        | 27.99  |
|         | 12   | 27.96        | 27.89 | 28.02        | 27.99  |
|         | 13   | 27.91        | 27.98 | 27.99        | 27.99  |
|         | 14   | 27.97        | 27.98 | 27.93        | 27.92  |
|         | 15   | 27.94        | 27.97 | 27.89        | 27.96  |

**Table 8-4. Occupied Bandwidth Summary Data (n48\_1C\_30M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (19) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 37.98        | 37.89 | 37.88        | 37.96  |
|         | 1    | 37.89        | 37.88 | 37.89        | 37.91  |
|         | 2    | 37.94        | 37.98 | 37.98        | 37.98  |
|         | 3    | 37.87        | 37.90 | 38.01        | 37.97  |
|         | 4    | 37.96        | 37.82 | 37.96        | 37.88  |
|         | 5    | 37.98        | 37.88 | 37.93        | 37.93  |
|         | 6    | 37.90        | 37.90 | 37.89        | 37.91  |
|         | 7    | 37.92        | 37.90 | 37.89        | 38.02  |
|         | 8    | 37.95        | 37.94 | 38.01        | 37.97  |
|         | 9    | 37.89        | 37.91 | 37.93        | 38.02  |
|         | 10   | 37.89        | 37.95 | 37.93        | 37.88  |
|         | 11   | 38.02        | 37.87 | 37.88        | 37.90  |
|         | 12   | 37.91        | 37.96 | 38.05        | 37.98  |
|         | 13   | 37.98        | 37.91 | 37.92        | 37.95  |
|         | 14   | 37.93        | 37.90 | 37.98        | 37.89  |
|         | 15   | 37.93        | 38.00 | 37.96        | 37.81  |
| Mid     | 0    | 38.04        | 37.89 | 37.95        | 37.98  |
|         | 1    | 37.90        | 37.98 | 37.96        | 37.81  |
|         | 2    | 37.93        | 38.03 | <b>38.10</b> | 37.95  |
|         | 3    | 37.85        | 37.87 | 37.94        | 37.85  |
|         | 4    | 37.95        | 37.92 | 37.90        | 37.91  |
|         | 5    | 37.94        | 37.94 | 37.89        | 37.96  |
|         | 6    | 37.95        | 37.91 | 38.00        | 38.03  |
|         | 7    | 37.98        | 37.95 | 37.97        | 37.99  |
|         | 8    | 37.92        | 37.88 | 37.97        | 37.88  |
|         | 9    | 37.90        | 37.94 | 37.95        | 37.87  |
|         | 10   | 37.92        | 37.88 | 37.93        | 38.05  |
|         | 11   | 37.90        | 37.89 | 37.85        | 38.08  |
|         | 12   | 37.93        | 37.93 | 37.91        | 37.89  |
|         | 13   | 37.99        | 37.90 | 37.99        | 37.97  |
|         | 14   | 37.92        | 37.92 | 37.98        | 37.98  |
|         | 15   | 37.89        | 37.94 | 37.89        | 37.93  |
| High    | 0    | 37.98        | 37.89 | 37.94        | 37.96  |
|         | 1    | 37.87        | 37.97 | 37.94        | 37.93  |
|         | 2    | 37.96        | 37.94 | 37.98        | 37.96  |
|         | 3    | 37.91        | 37.95 | 37.96        | 37.96  |
|         | 4    | 38.02        | 37.99 | 37.94        | 37.99  |
|         | 5    | <b>38.06</b> | 38.00 | 37.92        | 38.03  |
|         | 6    | 37.96        | 37.95 | 38.01        | 37.97  |
|         | 7    | 37.95        | 38.03 | 37.92        | 37.97  |
|         | 8    | 37.96        | 37.95 | 38.03        | 37.97  |
|         | 9    | 37.88        | 37.94 | 37.93        | 37.88  |
|         | 10   | 38.05        | 37.94 | 38.00        | 37.97  |
|         | 11   | 37.92        | 37.86 | 37.97        | 37.95  |
|         | 12   | 37.96        | 37.94 | 37.95        | 37.99  |
|         | 13   | 37.99        | 37.92 | 37.93        | 37.88  |
|         | 14   | 37.95        | 37.91 | 38.01        | 37.94  |
|         | 15   | 37.97        | 37.85 | 37.94        | 37.96  |

**Table 8-5. Occupied Bandwidth Summary Data (n48\_1C\_40M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (20) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 47.86        | 47.87 | 47.95        | 47.95  |
|         | 1    | 47.85        | 47.84 | 47.99        | 47.88  |
|         | 2    | 47.79        | 47.91 | 47.89        | 47.90  |
|         | 3    | 47.78        | 47.94 | 48.01        | 47.89  |
|         | 4    | 47.82        | 47.94 | 47.93        | 47.95  |
|         | 5    | 47.95        | 47.91 | 47.91        | 47.90  |
|         | 6    | 47.90        | 47.87 | 47.92        | 47.84  |
|         | 7    | 47.92        | 47.90 | 47.93        | 47.95  |
|         | 8    | 47.90        | 47.90 | 48.01        | 47.93  |
|         | 9    | 47.81        | 48.00 | 47.99        | 47.97  |
|         | 10   | 47.94        | 47.88 | 48.02        | 47.92  |
|         | 11   | 47.85        | 47.91 | 47.88        | 47.92  |
|         | 12   | 48.01        | 47.91 | 47.96        | 47.93  |
|         | 13   | 47.89        | 47.87 | 47.89        | 47.92  |
|         | 14   | 47.92        | 47.95 | 47.98        | 47.99  |
| Mid     | 15   | 47.85        | 47.93 | 47.89        | 47.90  |
|         | 0    | 48.04        | 48.00 | 48.00        | 47.92  |
|         | 1    | 47.85        | 47.97 | 47.95        | 47.99  |
|         | 2    | 47.89        | 48.02 | 47.90        | 48.02  |
|         | 3    | 47.96        | 47.85 | 47.91        | 47.95  |
|         | 4    | 47.88        | 48.01 | 47.95        | 47.90  |
|         | 5    | 47.89        | 47.97 | 47.91        | 47.90  |
|         | 6    | 47.98        | 47.96 | 47.90        | 47.92  |
|         | 7    | 47.89        | 47.90 | 47.99        | 48.09  |
|         | 8    | <b>48.06</b> | 47.88 | 48.08        | 47.93  |
|         | 9    | 48.04        | 47.95 | 47.98        | 47.99  |
|         | 10   | 47.93        | 47.92 | 47.99        | 47.94  |
|         | 11   | 47.92        | 47.96 | 47.89        | 47.97  |
|         | 12   | 47.96        | 47.90 | 47.87        | 47.85  |
|         | 13   | 47.85        | 47.94 | 47.97        | 47.94  |
| High    | 14   | 47.84        | 47.97 | 47.76        | 47.95  |
|         | 15   | 47.99        | 47.87 | 48.02        | 47.96  |
|         | 0    | 47.88        | 48.00 | 47.86        | 47.89  |
|         | 1    | 47.95        | 47.91 | 47.96        | 48.02  |
|         | 2    | 47.96        | 47.96 | 47.98        | 47.98  |
|         | 3    | 47.91        | 47.97 | 47.92        | 47.96  |
|         | 4    | 48.05        | 47.84 | 47.84        | 47.98  |
|         | 5    | 47.92        | 48.10 | 47.98        | 47.89  |
|         | 6    | 48.00        | 47.92 | 47.98        | 47.98  |
|         | 7    | 48.00        | 47.99 | 48.01        | 47.88  |
|         | 8    | 47.91        | 47.92 | 47.91        | 47.85  |
|         | 9    | 47.90        | 48.01 | 47.97        | 47.92  |
|         | 10   | 47.97        | 48.02 | 48.00        | 47.95  |
|         | 11   | 47.93        | 47.93 | 48.01        | 48.01  |
|         | 12   | 47.89        | 47.91 | 47.95        | 47.94  |
|         | 13   | 47.92        | 47.98 | 48.00        | 47.96  |
|         | 14   | 47.90        | 47.92 | 48.00        | 48.01  |
|         | 15   | 47.99        | 47.91 | <b>48.10</b> | 48.00  |

**Table 8-6. Occupied Bandwidth Summary Data (n48\_2C\_20M+30M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (21) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 57.76        | 57.91 | 57.88        | 57.94  |
|         | 1    | 57.84        | 57.91 | 57.96        | 57.90  |
|         | 2    | 57.83        | 57.82 | 57.83        | 57.89  |
|         | 3    | 57.82        | 57.83 | 57.72        | 57.79  |
|         | 4    | 57.83        | 57.94 | 57.88        | 57.78  |
|         | 5    | 57.88        | 57.82 | 57.75        | 57.94  |
|         | 6    | 57.79        | 57.85 | 57.74        | 57.88  |
|         | 7    | 57.65        | 57.84 | 57.84        | 57.86  |
|         | 8    | 57.87        | 57.84 | 57.89        | 57.83  |
|         | 9    | 57.86        | 57.81 | 57.71        | 57.65  |
|         | 10   | 57.76        | 57.90 | 57.79        | 57.94  |
|         | 11   | 57.85        | 57.75 | 57.83        | 57.90  |
|         | 12   | 57.85        | 57.85 | 57.88        | 57.75  |
|         | 13   | 57.93        | 57.76 | 57.89        | 57.88  |
|         | 14   | 57.79        | 57.93 | 57.83        | 57.79  |
|         | 15   | 57.81        | 57.73 | 57.71        | 57.86  |
| Mid     | 0    | 57.99        | 57.87 | 57.96        | 57.97  |
|         | 1    | 57.92        | 57.77 | 57.92        | 57.89  |
|         | 2    | 57.94        | 57.91 | 58.01        | 57.81  |
|         | 3    | 57.96        | 57.78 | 58.03        | 57.80  |
|         | 4    | 57.85        | 57.90 | 57.95        | 57.85  |
|         | 5    | 58.02        | 57.86 | 57.84        | 57.89  |
|         | 6    | 57.88        | 57.79 | 57.92        | 57.80  |
|         | 7    | 57.91        | 57.85 | 57.99        | 57.74  |
|         | 8    | 57.89        | 57.89 | 57.88        | 58.07  |
|         | 9    | 57.77        | 57.87 | 57.84        | 57.86  |
|         | 10   | 57.86        | 57.96 | 57.86        | 57.82  |
|         | 11   | 57.94        | 57.81 | 57.94        | 57.81  |
|         | 12   | 57.84        | 57.85 | 57.82        | 57.78  |
|         | 13   | 57.94        | 57.90 | 57.85        | 57.91  |
|         | 14   | 57.96        | 57.91 | 57.90        | 57.91  |
|         | 15   | 57.90        | 57.92 | 57.89        | 57.85  |
| High    | 0    | 57.85        | 57.86 | 57.93        | 57.81  |
|         | 1    | 57.94        | 57.92 | 57.91        | 57.98  |
|         | 2    | 57.87        | 57.85 | 57.87        | 57.93  |
|         | 3    | 57.96        | 57.88 | 58.01        | 57.80  |
|         | 4    | 57.86        | 57.92 | 57.86        | 57.84  |
|         | 5    | 57.91        | 57.89 | 58.04        | 57.82  |
|         | 6    | 57.86        | 57.93 | 57.98        | 57.87  |
|         | 7    | 57.82        | 57.89 | 57.89        | 57.87  |
|         | 8    | 58.01        | 57.79 | 57.97        | 57.94  |
|         | 9    | 57.84        | 57.77 | 57.92        | 57.90  |
|         | 10   | 57.96        | 57.84 | 57.89        | 57.97  |
|         | 11   | 57.85        | 57.84 | <b>58.10</b> | 57.91  |
|         | 12   | 57.89        | 57.88 | 57.99        | 57.93  |
|         | 13   | 57.88        | 57.91 | 57.88        | 57.88  |
|         | 14   | <b>58.02</b> | 57.94 | 57.80        | 57.89  |
|         | 15   | 57.79        | 57.85 | 57.85        | 57.97  |

**Table 8-7. Occupied Bandwidth Summary Data (n48\_1C\_60M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (22) / (221) pages

| Channel | Port | OBW (MHz)    |       |              |        |
|---------|------|--------------|-------|--------------|--------|
|         |      | QPSK         | 16QAM | 64QAM        | 256QAM |
| Low     | 0    | 68.02        | 67.88 | 68.12        | 67.87  |
|         | 1    | 68.01        | 68.02 | <b>68.27</b> | 68.01  |
|         | 2    | 67.92        | 68.23 | 68.00        | 67.93  |
|         | 3    | 67.90        | 68.02 | 67.90        | 67.94  |
|         | 4    | 67.93        | 68.13 | 68.07        | 67.75  |
|         | 5    | 67.97        | 67.94 | 68.04        | 67.99  |
|         | 6    | 67.91        | 68.01 | 68.00        | 68.09  |
|         | 7    | 68.05        | 67.94 | 68.06        | 67.98  |
|         | 8    | 68.07        | 67.94 | 67.95        | 67.96  |
|         | 9    | 67.83        | 67.94 | 68.09        | 68.11  |
|         | 10   | 68.00        | 68.11 | 67.90        | 67.99  |
|         | 11   | <b>68.22</b> | 67.97 | 68.03        | 68.01  |
|         | 12   | 67.91        | 67.96 | 68.00        | 68.02  |
|         | 13   | 67.93        | 68.01 | 67.98        | 67.94  |
|         | 14   | 67.86        | 68.07 | 68.08        | 67.97  |
| Mid     | 0    | 68.12        | 67.85 | 68.13        | 67.95  |
|         | 1    | 67.98        | 68.01 | 68.06        | 67.95  |
|         | 2    | 67.96        | 68.05 | 68.04        | 68.12  |
|         | 3    | 68.08        | 68.07 | 68.14        | 68.12  |
|         | 4    | 67.98        | 67.93 | 67.98        | 67.87  |
|         | 5    | 67.99        | 68.04 | 68.15        | 68.04  |
|         | 6    | 68.08        | 67.93 | 68.13        | 68.05  |
|         | 7    | 68.09        | 68.07 | 68.09        | 68.00  |
|         | 8    | 67.77        | 68.01 | 68.00        | 68.03  |
|         | 9    | 67.99        | 68.01 | 68.09        | 68.02  |
|         | 10   | 67.84        | 67.95 | 67.93        | 68.12  |
|         | 11   | 67.96        | 68.16 | 68.04        | 67.99  |
|         | 12   | 67.99        | 67.98 | 68.11        | 68.07  |
|         | 13   | 67.92        | 68.02 | 67.99        | 68.02  |
|         | 14   | 67.98        | 67.97 | 68.09        | 68.04  |
| High    | 0    | 68.17        | 67.99 | 68.00        | 68.09  |
|         | 1    | 68.13        | 68.07 | 67.98        | 68.09  |
|         | 2    | 68.03        | 68.13 | 68.08        | 67.96  |
|         | 3    | 67.96        | 68.04 | 68.04        | 68.14  |
|         | 4    | 67.95        | 68.02 | 67.93        | 67.97  |
|         | 5    | 67.96        | 67.91 | 67.98        | 68.01  |
|         | 6    | 68.03        | 68.03 | 67.92        | 68.01  |
|         | 7    | 67.97        | 68.00 | 68.01        | 68.04  |
|         | 8    | 67.93        | 68.06 | 67.97        | 68.11  |
|         | 9    | 67.97        | 68.04 | 67.98        | 68.07  |
|         | 10   | 68.09        | 67.97 | 68.17        | 68.04  |
|         | 11   | 68.06        | 67.99 | 68.19        | 68.01  |
|         | 12   | 68.02        | 68.07 | 68.15        | 68.01  |
|         | 13   | 68.19        | 68.09 | 68.07        | 68.12  |
|         | 14   | 68.01        | 67.99 | 68.06        | 68.06  |
|         | 15   | 68.03        | 68.03 | 67.98        | 68.13  |

**Table 8-8. Occupied Bandwidth Summary Data (n48\_4C\_10M+10M+10M+40M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (23) / (221) pages

| Channel | Port | OBW (MHz)    |       |       |              |
|---------|------|--------------|-------|-------|--------------|
|         |      | QPSK         | 16QAM | 64QAM | 256QAM       |
| Low     | 0    | 77.52        | 77.31 | 77.52 | 77.28        |
|         | 1    | 77.27        | 77.43 | 77.35 | 77.47        |
|         | 2    | 77.47        | 77.48 | 77.57 | 77.35        |
|         | 3    | 77.36        | 77.48 | 77.39 | 77.48        |
|         | 4    | 77.43        | 77.42 | 77.44 | 77.58        |
|         | 5    | 77.37        | 77.36 | 77.44 | 77.44        |
|         | 6    | 77.51        | 77.38 | 77.32 | 77.55        |
|         | 7    | 77.31        | 77.45 | 77.34 | 77.42        |
|         | 8    | 77.38        | 77.49 | 77.49 | 77.40        |
|         | 9    | 77.49        | 77.46 | 77.33 | 77.39        |
|         | 10   | 77.56        | 77.44 | 77.40 | 77.55        |
|         | 11   | 77.51        | 77.32 | 77.29 | 77.49        |
|         | 12   | 77.27        | 77.37 | 77.55 | 77.35        |
|         | 13   | 77.33        | 77.36 | 77.54 | 77.44        |
|         | 14   | 77.37        | 77.43 | 77.40 | 77.42        |
| Mid     | 0    | 77.57        | 77.50 | 77.52 | 77.47        |
|         | 1    | 77.57        | 77.50 | 77.61 | <b>77.73</b> |
|         | 2    | 77.53        | 77.61 | 77.45 | 77.55        |
|         | 3    | 77.42        | 77.40 | 77.55 | 77.48        |
|         | 4    | 77.61        | 77.46 | 77.48 | 77.34        |
|         | 5    | 77.52        | 77.49 | 77.51 | 77.54        |
|         | 6    | 77.44        | 77.53 | 77.45 | 77.48        |
|         | 7    | 77.48        | 77.41 | 77.55 | 77.65        |
|         | 8    | 77.50        | 77.43 | 77.50 | 77.47        |
|         | 9    | 77.31        | 77.50 | 77.53 | 77.36        |
|         | 10   | 77.57        | 77.33 | 77.50 | 77.54        |
|         | 11   | 77.43        | 77.48 | 77.47 | 77.54        |
|         | 12   | 77.45        | 77.63 | 77.56 | 77.42        |
|         | 13   | 77.64        | 77.44 | 77.59 | 77.56        |
|         | 14   | <b>77.69</b> | 77.41 | 77.33 | 77.48        |
| High    | 0    | 77.56        | 77.43 | 77.40 | 77.46        |
|         | 1    | 77.65        | 77.69 | 77.53 | 77.64        |
|         | 2    | 77.55        | 77.48 | 77.65 | 77.48        |
|         | 3    | 77.49        | 77.54 | 77.51 | 77.45        |
|         | 4    | 77.33        | 77.54 | 77.58 | 77.58        |
|         | 5    | 77.52        | 77.53 | 77.48 | 77.41        |
|         | 6    | 77.50        | 77.48 | 77.63 | 77.36        |
|         | 7    | 77.42        | 77.49 | 77.62 | 77.62        |
|         | 8    | 77.47        | 77.48 | 77.49 | 77.58        |
|         | 9    | 77.48        | 77.61 | 77.43 | 77.49        |
|         | 10   | 77.59        | 77.50 | 77.51 | 77.71        |
|         | 11   | 77.54        | 77.47 | 77.60 | 77.54        |
|         | 12   | 77.50        | 77.51 | 77.47 | 77.49        |
|         | 13   | 77.52        | 77.61 | 77.59 | 77.54        |
|         | 14   | 77.42        | 77.53 | 77.47 | 77.47        |
|         | 15   | 77.63        | 77.49 | 77.62 | 77.52        |


**Table 8-9. Occupied Bandwidth Summary Data (n48\_1C\_80M)**




# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501


REPORT No.:  
CTK-2025-01906  
Page (24) / (221) pages




Plot 8-1. Occupied Bandwidth Plot  
(n48 1C 10M QPSK- Mid Channel, Port 9)




Plot 8-2. Occupied Bandwidth Plot  
(n48 1C 10M 64QAM - Low Channel, Port 13)




Plot 8-3. Occupied Bandwidth Plot  
(n48 1C 20M QPSK - Low Channel, Port 5)



Plot 8-4. Occupied Bandwidth Plot  
(n48 1C 20M 64QAM - High Channel, Port 1)



Plot 8-5. Occupied Bandwidth Plot  
(n48 1C 30M QPSK - High Channel, Port 6)




Plot 8-6. Occupied Bandwidth Plot  
(n48 1C 30M 64QAM - High Channel, Port 7)




# CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501


REPORT No.:  
CTK-2025-01906  
Page (25) / (221) pages




Plot 8-7. Occupied Bandwidth Plot  
(n48\_1C\_40M\_QPSK - High Channel, Port 5)




Plot 8-8. Occupied Bandwidth Plot  
(n48\_1C\_40M\_64QAM - Mid Channel, Port 2)




Plot 8-9. Occupied Bandwidth Plot  
(n48\_2C\_20M+30M\_QPSK - Mid Channel, Port 8)



Plot 8-10. Occupied Bandwidth Plot  
(n48\_2C\_20M+30M\_64QAM - High Channel, Port 15)



Plot 8-11. Occupied Bandwidth Plot  
(n48\_1C\_60M\_QPSK - High Channel, Port 14)







Plot 8-12. Occupied Bandwidth Plot  
(n48\_1C\_60M\_64QAM - High Channel, Port 11)



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (26) / (221) pages



### 8.3 Modulation Characteristics

#### Test Overview

Verification of a curve or equivalent data that shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

#### Test Procedure Used


ANSI C63.26 - Section 5.3

#### Test Setting

The measurement was made using a direct connection between the RF output of the EUT and the spectrum analyzer. The spectrum analyzer setting was modulation analyzer mode.

#### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 8-2. Test Instrument & Measurement Setup**

#### Limit

96.41(a)

Systems operating in the Citizens Broadband Radio Service must use digital modulation techniques.

#### Test Notes


Systems operating in the Citizens Broadband Radio Service use digital modulation techniques of QPSK and QAM




**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501


REPORT No.:  
CTK-2025-01906  
Page (28) / (221) pages




Plot 8-17. Modulation Characteristics Plot  
(n48\_1C\_10M\_QPSK Modulation)



Plot 8-18. Modulation Characteristics Plot  
(n48\_1C\_10M\_16QAM Modulation)



Plot 8-19. Modulation Characteristics Plot  
(n48\_1C\_10M\_64QAM Modulation)



Plot 8-20. Modulation Characteristics Plot  
(n48\_1C\_10M\_256QAM Modulation)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (29) / (221) pages

## 8.4 Maximum Power Spectral Density

### Test Overview

A transmitter port of EUT is connected to the input of a signal analyzer. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

### Test Procedure Used

ANSI C63.26 - Section 5.2.4  
ANSI C63.26 - Section 5.2.5  
KDB 971168 D01 v03r01 - Section 5.3

ANSI C63.26 - Section 6.4.3.2.3  
KDB 662911 D01 v02r01  
- Section E)2) In-Band Power Spectral Density (PSD) Measurements  
b) Measure and sum spectral maxima across the outputs.

### Test Setting

The measurement was made using a direct connection between the RF output of the EUT and the spectrum analyzer. The spectrum analyzer settings were as follows:


The PSD is measured following the same procedures described in 5.2.4.4 of ANSI C63.26 for measuring the total average power, but with the RBW set to the reference bandwidth specified by the applicable regulatory requirement, and by using the marker function to identify the maximum PSD instead of summing the power across the OBW. If the fundamental measurement condition cannot be realized, then one of the alternative procedures in 5.2.4.4.2 or 5.2.4.4.3 should be selected, based on whether the transmitter duty cycle is constant (variations  $\leq \pm 2\%$ ) or non-constant (variations  $> \pm 2\%$ ), respectively.

1. Conducted power measurements are performed using the signal analyzer's "SA mode" measurement capability for signals with continuous operation.
2. Set span to  $2 \times$  to  $3 \times$  the OBW.
3. Set RBW = 1 MHz (the reference bandwidth)
4. Set VBW  $\geq 3 \times$  RBW.
5. Set number of measurement points in sweep  $\geq 2 \times$  span / RBW.
6. Sweep time:
  - a) Set  $\geq$  auto-couple, and enable trace averaging, or
  - b) Set  $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$  and enable a single sweep (automation-compatible) measurement. The sweep time should never be faster than the auto-coupled sweep time.
7. Detector = power averaging (rms).
8. The trace was allowed to stabilize
9. Use the peak marker function to determine the maximum amplitude level. ( $=P_{\text{Meas}}$ )
10. The relevant equation for determining the maximum EIRP from the measured RF output power is given in Equation as follows:  
$$\text{EIRP} = P_{\text{Meas}} + G_T$$

where  
GT: gain of the transmitting antenna, in dBi (EIRP).

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 8-3. Test Instrument & Measurement Setup**

## Limit

§ 96.41 (b) Maximum PSD  
 Category B CBSD : 37 dBm/MHz

## Test Notes

- Consider the following factors for MIMO Power Spectral Density:  
 The power spectral density is measured as dBm / MHz, with the resolution bandwidth of 1 MHz PSDs are summed up in linear using the measure-and-sum technique defined in KDB 971168 D01 v03r01 - Section E) 2).
- Periodic trigger was used with gating ON. Gate sweep time, Gate delay and gate length were set accordingly to capture ON time of the transmission.
- PSD per port (dBm/MHz) is converted to a linear value (mW). A summation of linear powers for all ports gives us the total MIMO conducted Power (mW). We convert this back to logarithmic scale for further PSD calculations.
- Tested for Common beam mode to perform RF testing that can get maximum Tx power setting.
- Applied antenna gain as below:

| Mode               | NR 10MHz |      |        | NR 20MHz |      |        | NR 30MHz |      |        |
|--------------------|----------|------|--------|----------|------|--------|----------|------|--------|
|                    | SU       | MU   | Common | SU       | MU   | Common | SU       | MU   | Common |
| Tx Power Max(dBm)  | 25.2     | 21.7 | 30.7   | 28.2     | 24.7 | 33.7   | 29.9     | 26.4 | 35.4   |
| Max. Gain (dBi)    | 20.3     | 20.3 | 14.8   | 20.3     | 20.3 | 14.8   | 20.3     | 14.8 | 14.45  |
| Beam EIRP Sum (dB) | 0        | 3    | 0      | 0        | 3    | 0      | 0        | 3    | 0      |
| Max. EIRP (dBm)    | 45.5     | 45   | 45.5   | 48.5     | 48   | 48.5   | 50.2     | 44.2 | 49.9   |
| Mode               | NR 40MHz |      |        | NR 60MHz |      |        | NR 80MHz |      |        |
|                    | SU       | MU   | Common | SU       | MU   | Common | SU       | MU   | Common |
| Tx Power Max(dBm)  | 31.2     | 27.7 | 36.7   | 33       | 29.5 | 38.5   | 34.2     | 30.7 | 39.7   |
| Max. Gain (dBi)    | 20.3     | 20.3 | 14.8   | 20.3     | 20.3 | 14.8   | 20.3     | 20.3 | 14.8   |
| Beam EIRP Sum (dB) | 0        | 3    | 0      | 0        | 3    | 0      | 0        | 3    | 0      |
| Max. EIRP (dBm)    | 51.5     | 51   | 51.5   | 53.3     | 52.8 | 53.3   | 54.5     | 54   | 54.5   |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (31) / (221) pages

**6. Sample Calculation:**

Let us assume the following numbers:

- a) Total MIMO Conducted PSD as 121.46 mW
- b) Antenna Gain = 14.80 dBi

| Factors                                |                          | Value  | Unit    |
|----------------------------------------|--------------------------|--------|---------|
| Summed MIMO Conducted PSD (linear sum) |                          | 121.46 | mW      |
| Summed MIMO Conducted PSD (dBm)        | $= 10 * \log (121.46) =$ | 20.84  | dBm/MHz |
| Antenna Gain                           |                          | 14.80  | dB      |
| <b>e.i.r.p PSD</b>                     |                          | 35.64  | dBm/MHz |
| <b>Limit</b>                           |                          | 37.00  | dBm/MHz |
| <b>Margin = Limit - e.i.r.p PSD</b>    | $= 35.64 - 37.00 =$      | -1.36  | dB      |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (32) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM       |
|------------------------------------|------|--------|--------|--------|--------------|
| Low                                | 0    | 8.33   | 8.51   | 8.52   | 8.46         |
|                                    | 1    | 8.65   | 8.84   | 8.80   | 8.73         |
|                                    | 2    | 9.01   | 9.19   | 9.16   | 9.09         |
|                                    | 3    | 8.72   | 8.90   | 8.91   | 8.85         |
|                                    | 4    | 8.82   | 8.95   | 8.95   | 8.85         |
|                                    | 5    | 8.77   | 8.94   | 8.93   | 8.86         |
|                                    | 6    | 9.23   | 9.37   | 9.38   | 9.28         |
|                                    | 7    | 9.11   | 9.32   | 9.32   | 9.23         |
|                                    | 8    | 8.83   | 9.01   | 9.02   | 8.92         |
|                                    | 9    | 8.63   | 8.79   | 8.82   | 8.73         |
|                                    | 10   | 9.22   | 9.38   | 9.40   | 9.29         |
|                                    | 11   | 8.70   | 8.83   | 8.91   | 8.80         |
|                                    | 12   | 8.66   | 8.76   | 8.80   | 8.69         |
|                                    | 13   | 8.84   | 8.92   | 9.02   | 8.90         |
|                                    | 14   | 8.77   | 8.94   | 8.92   | 8.81         |
|                                    | 15   | 8.49   | 8.66   | 8.69   | 8.58         |
| Total MIMO Conducted PSD (mW/MHz)  |      | 121.46 | 125.99 | 126.42 | 123.79       |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.84  | 21.00  | 21.02  | 20.93        |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80        |
| e.i.r.p PSD (dBm/MHz)              |      | 35.64  | 35.80  | 35.82  | 35.73        |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00        |
| Margin (dB)                        |      | -1.36  | -1.20  | -1.18  | -1.27        |
| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM       |
| Mid                                | 0    | 8.88   | 9.00   | 9.22   | 9.13         |
|                                    | 1    | 9.18   | 9.42   | 9.47   | 9.41         |
|                                    | 2    | 9.47   | 9.71   | 9.79   | 9.72         |
|                                    | 3    | 9.18   | 9.40   | 9.49   | 9.48         |
|                                    | 4    | 9.25   | 9.47   | 9.58   | 9.60         |
|                                    | 5    | 9.31   | 9.53   | 9.62   | 9.64         |
|                                    | 6    | 9.86   | 10.06  | 10.13  | <b>10.18</b> |
|                                    | 7    | 9.64   | 9.91   | 9.98   | 9.73         |
|                                    | 8    | 9.28   | 9.49   | 9.63   | 9.38         |
|                                    | 9    | 9.17   | 9.36   | 9.52   | 9.24         |
|                                    | 10   | 9.66   | 9.89   | 10.04  | 9.77         |
|                                    | 11   | 9.21   | 9.47   | 9.57   | 9.31         |
|                                    | 12   | 9.12   | 9.32   | 9.45   | 9.21         |
|                                    | 13   | 9.49   | 9.68   | 9.52   | 9.57         |
|                                    | 14   | 9.27   | 9.51   | 9.34   | 9.36         |
|                                    | 15   | 9.07   | 9.30   | 9.13   | 9.16         |
| Total MIMO Conducted PSD (mW/MHz)  |      | 136.87 | 143.88 | 145.92 | 142.61       |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.36  | 21.58  | 21.64  | 21.54        |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80        |
| e.i.r.p PSD (dBm/MHz)              |      | 36.16  | 36.38  | 36.44  | 36.34        |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00        |
| Margin (dB)                        |      | -0.84  | -0.62  | -0.56  | -0.66        |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (33) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------|--------|--------|--------|
| High                               | 0    | 8.10   | 8.08   | 8.19   | 8.29   |
|                                    | 1    | 8.58   | 8.77   | 8.74   | 8.77   |
|                                    | 2    | 8.78   | 8.97   | 8.83   | 8.91   |
|                                    | 3    | 8.62   | 8.77   | 8.71   | 8.75   |
|                                    | 4    | 8.48   | 8.72   | 8.66   | 8.70   |
|                                    | 5    | 8.59   | 8.79   | 8.73   | 8.76   |
|                                    | 6    | 8.98   | 9.27   | 9.21   | 9.26   |
|                                    | 7    | 8.99   | 9.19   | 9.11   | 9.17   |
|                                    | 8    | 8.47   | 8.73   | 8.64   | 8.70   |
|                                    | 9    | 8.56   | 8.77   | 8.70   | 8.70   |
|                                    | 10   | 8.87   | 9.21   | 9.12   | 9.11   |
|                                    | 11   | 8.59   | 8.77   | 8.64   | 8.62   |
|                                    | 12   | 8.28   | 8.45   | 8.38   | 8.37   |
|                                    | 13   | 8.78   | 8.98   | 8.87   | 8.84   |
|                                    | 14   | 8.44   | 8.70   | 8.53   | 8.52   |
|                                    | 15   | 8.37   | 8.58   | 8.49   | 8.45   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 115.85 | 121.51 | 119.39 | 120.06 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.64  | 20.85  | 20.77  | 20.79  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.44  | 35.65  | 35.57  | 35.59  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.56  | -1.35  | -1.43  | -1.41  |

**Table 8-10. Power Spectral Density Table (n48\_1C\_10M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (34) / (221) pages

| Channel                            | Port | QPSK   | 16QAM       | 64QAM  | 256QAM |
|------------------------------------|------|--------|-------------|--------|--------|
| Low                                | 0    | 8.34   | 8.41        | 8.33   | 8.35   |
|                                    | 1    | 8.64   | 8.69        | 8.62   | 8.67   |
|                                    | 2    | 8.91   | 8.91        | 8.83   | 8.91   |
|                                    | 3    | 8.75   | 8.79        | 8.71   | 8.75   |
|                                    | 4    | 8.75   | 8.79        | 8.72   | 8.75   |
|                                    | 5    | 8.76   | 8.82        | 8.76   | 8.79   |
|                                    | 6    | 9.10   | 9.12        | 9.09   | 9.12   |
|                                    | 7    | 9.11   | 9.11        | 9.10   | 9.13   |
|                                    | 8    | 8.79   | 8.79        | 8.79   | 8.82   |
|                                    | 9    | 8.63   | 8.65        | 8.60   | 8.63   |
|                                    | 10   | 8.78   | 8.77        | 8.76   | 8.78   |
|                                    | 11   | 8.71   | 8.74        | 8.70   | 8.72   |
|                                    | 12   | 8.60   | 8.63        | 8.59   | 8.63   |
|                                    | 13   | 8.79   | 8.86        | 8.83   | 8.83   |
|                                    | 14   | 8.71   | 8.77        | 8.73   | 8.78   |
|                                    | 15   | 8.42   | 8.47        | 8.42   | 8.46   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 119.75 | 120.66      | 119.33 | 120.35 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.78  | 20.82       | 20.77  | 20.80  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80       | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.58  | 35.62       | 35.57  | 35.60  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00       | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.42  | -1.38       | -1.43  | -1.40  |
| Channel                            | Port | QPSK   | 16QAM       | 64QAM  | 256QAM |
| Mid                                | 0    | 8.54   | 8.63        | 8.48   | 8.61   |
|                                    | 1    | 8.73   | 8.95        | 8.80   | 8.90   |
|                                    | 2    | 8.90   | 9.14        | 8.99   | 9.10   |
|                                    | 3    | 8.76   | 8.99        | 8.82   | 8.88   |
|                                    | 4    | 8.81   | 9.05        | 8.86   | 8.95   |
|                                    | 5    | 8.87   | 9.10        | 8.93   | 9.01   |
|                                    | 6    | 9.30   | <b>9.54</b> | 9.40   | 9.49   |
|                                    | 7    | 9.23   | 9.47        | 9.29   | 9.40   |
|                                    | 8    | 8.88   | 9.12        | 8.96   | 9.05   |
|                                    | 9    | 8.68   | 8.97        | 8.75   | 8.85   |
|                                    | 10   | 8.85   | 9.07        | 8.97   | 9.02   |
|                                    | 11   | 8.80   | 9.04        | 8.86   | 8.94   |
|                                    | 12   | 8.71   | 8.88        | 8.78   | 8.83   |
|                                    | 13   | 9.05   | 9.22        | 9.11   | 9.15   |
|                                    | 14   | 8.91   | 9.07        | 8.93   | 9.03   |
|                                    | 15   | 8.64   | 8.81        | 8.72   | 8.77   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 123.00 | 129.13      | 124.76 | 127.20 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.90  | 21.11       | 20.96  | 21.04  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80       | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.70  | 35.91       | 35.76  | 35.84  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00       | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.30  | -1.09       | -1.24  | -1.16  |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (35) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM       |
|------------------------------------|------|--------|--------|--------|--------------|
| High                               | 0    | 7.89   | 8.16   | 8.22   | 8.28         |
|                                    | 1    | 8.34   | 8.64   | 8.67   | 8.71         |
|                                    | 2    | 8.51   | 8.77   | 8.82   | 8.87         |
|                                    | 3    | 8.33   | 8.66   | 8.71   | 8.71         |
|                                    | 4    | 8.34   | 8.65   | 8.65   | 8.69         |
|                                    | 5    | 8.37   | 8.66   | 8.71   | 8.75         |
|                                    | 6    | 8.82   | 9.09   | 9.11   | 9.17         |
|                                    | 7    | 8.80   | 9.10   | 9.12   | 9.19         |
|                                    | 8    | 8.33   | 8.62   | 8.63   | 8.68         |
|                                    | 9    | 8.29   | 8.62   | 8.63   | 8.73         |
|                                    | 10   | 8.40   | 8.70   | 8.72   | 8.80         |
|                                    | 11   | 8.35   | 8.65   | 8.65   | 8.73         |
|                                    | 12   | 8.07   | 8.33   | 8.34   | 8.45         |
|                                    | 13   | 8.59   | 8.85   | 8.83   | 8.97         |
|                                    | 14   | 8.26   | 8.52   | 8.54   | 8.63         |
|                                    | 15   | 8.18   | 8.47   | 8.44   | 8.56         |
| Total MIMO Conducted PSD (mW/MHz)  |      | 109.97 | 117.55 | 118.06 | 119.97       |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.41  | 20.70  | 20.72  | 20.79        |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80        |
| e.i.r.p PSD (dBm/MHz)              |      | 35.21  | 35.50  | 35.52  | <b>35.59</b> |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00        |
| Margin (dB)                        |      | -1.79  | -1.50  | -1.48  | -1.41        |

Table 8-11. Power Spectral Density Table (n48\_1C\_20M)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (36) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM      |
|------------------------------------|------|--------|--------|--------|-------------|
| Low                                | 0    | 8.36   | 8.24   | 8.35   | 8.27        |
|                                    | 1    | 8.61   | 8.49   | 8.60   | 8.66        |
|                                    | 2    | 8.88   | 8.74   | 8.83   | 8.91        |
|                                    | 3    | 8.74   | 8.57   | 8.71   | 8.75        |
|                                    | 4    | 8.73   | 8.56   | 8.73   | 8.73        |
|                                    | 5    | 8.75   | 8.70   | 8.73   | 8.76        |
|                                    | 6    | 9.17   | 9.06   | 9.12   | 9.14        |
|                                    | 7    | 9.11   | 9.06   | 9.06   | 9.10        |
|                                    | 8    | 8.81   | 8.77   | 8.78   | 8.81        |
|                                    | 9    | 8.64   | 8.54   | 8.52   | 8.58        |
|                                    | 10   | 8.76   | 8.77   | 8.73   | 8.83        |
|                                    | 11   | 8.66   | 8.71   | 8.68   | 8.78        |
|                                    | 12   | 8.60   | 8.57   | 8.56   | 8.66        |
|                                    | 13   | 8.83   | 8.82   | 8.79   | 8.92        |
|                                    | 14   | 8.77   | 8.93   | 8.74   | 8.83        |
|                                    | 15   | 8.47   | 8.57   | 8.43   | 8.56        |
| Total MIMO Conducted PSD (mW/MHz)  |      | 119.89 | 118.58 | 118.97 | 120.61      |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.79  | 20.74  | 20.75  | 20.81       |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80       |
| e.i.r.p PSD (dBm/MHz)              |      | 35.59  | 35.54  | 35.55  | 35.61       |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00       |
| Margin (dB)                        |      | -1.41  | -1.46  | -1.45  | -1.39       |
| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM      |
| Mid                                | 0    | 8.33   | 8.38   | 8.43   | 8.42        |
|                                    | 1    | 8.57   | 8.73   | 8.79   | 8.67        |
|                                    | 2    | 8.82   | 8.91   | 8.94   | 8.88        |
|                                    | 3    | 8.62   | 8.72   | 8.74   | 8.79        |
|                                    | 4    | 8.70   | 8.82   | 8.81   | 8.77        |
|                                    | 5    | 8.74   | 8.85   | 8.87   | 8.88        |
|                                    | 6    | 9.21   | 9.30   | 9.34   | <b>9.40</b> |
|                                    | 7    | 9.19   | 9.23   | 9.27   | 9.36        |
|                                    | 8    | 8.86   | 8.83   | 8.87   | 8.96        |
|                                    | 9    | 8.72   | 8.70   | 8.70   | 8.79        |
|                                    | 10   | 8.81   | 8.82   | 8.89   | 8.99        |
|                                    | 11   | 8.78   | 8.74   | 8.89   | 8.91        |
|                                    | 12   | 8.63   | 8.64   | 8.74   | 8.72        |
|                                    | 13   | 9.18   | 8.97   | 9.12   | 9.16        |
|                                    | 14   | 9.06   | 9.00   | 8.97   | 8.94        |
|                                    | 15   | 8.79   | 8.73   | 8.71   | 8.70        |
| Total MIMO Conducted PSD (mW/MHz)  |      | 121.92 | 122.53 | 123.76 | 124.29      |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.86  | 20.88  | 20.93  | 20.94       |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80       |
| e.i.r.p PSD (dBm/MHz)              |      | 35.66  | 35.68  | 35.73  | 35.74       |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00       |
| Margin (dB)                        |      | -1.34  | -1.32  | -1.27  | -1.26       |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (37) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------|--------|--------|--------|
| High                               | 0    | 7.96   | 7.93   | 7.96   | 8.03   |
|                                    | 1    | 8.37   | 8.31   | 8.34   | 8.36   |
|                                    | 2    | 8.57   | 8.51   | 8.53   | 8.60   |
|                                    | 3    | 8.39   | 8.33   | 8.36   | 8.41   |
|                                    | 4    | 8.38   | 8.31   | 8.37   | 8.43   |
|                                    | 5    | 8.42   | 8.40   | 8.43   | 8.43   |
|                                    | 6    | 8.86   | 8.83   | 8.85   | 8.94   |
|                                    | 7    | 8.83   | 8.82   | 8.84   | 8.85   |
|                                    | 8    | 8.38   | 8.34   | 8.40   | 8.43   |
|                                    | 9    | 8.27   | 8.27   | 8.31   | 8.36   |
|                                    | 10   | 8.43   | 8.39   | 8.45   | 8.53   |
|                                    | 11   | 8.35   | 8.33   | 8.39   | 8.43   |
|                                    | 12   | 8.01   | 7.99   | 8.07   | 8.12   |
|                                    | 13   | 8.59   | 8.59   | 8.64   | 8.60   |
|                                    | 14   | 8.24   | 8.24   | 8.32   | 8.36   |
|                                    | 15   | 8.17   | 8.19   | 8.24   | 8.22   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 110.53 | 109.85 | 110.99 | 111.98 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.43  | 20.41  | 20.45  | 20.49  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.23  | 35.21  | 35.25  | 35.29  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.77  | -1.79  | -1.75  | -1.71  |

Table 8-12. Power Spectral Density Table (n48\_1C\_30M)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (38) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM       | 256QAM |
|------------------------------------|------|--------|--------|-------------|--------|
| Low                                | 0    | 8.80   | 8.73   | 8.94        | 8.91   |
|                                    | 1    | 9.02   | 9.01   | 9.26        | 9.22   |
|                                    | 2    | 9.28   | 9.30   | 9.51        | 9.46   |
|                                    | 3    | 9.17   | 9.18   | 9.37        | 9.31   |
|                                    | 4    | 9.15   | 9.16   | 9.35        | 9.32   |
|                                    | 5    | 9.19   | 9.19   | 9.39        | 9.34   |
|                                    | 6    | 9.65   | 9.64   | <b>9.82</b> | 9.76   |
|                                    | 7    | 9.54   | 9.55   | 9.76        | 9.71   |
|                                    | 8    | 9.25   | 9.26   | 9.48        | 9.40   |
|                                    | 9    | 9.01   | 9.02   | 9.24        | 9.15   |
|                                    | 10   | 9.14   | 9.18   | 9.40        | 9.35   |
|                                    | 11   | 9.19   | 9.15   | 9.39        | 9.28   |
|                                    | 12   | 8.99   | 9.05   | 9.21        | 9.18   |
|                                    | 13   | 9.31   | 9.29   | 9.53        | 9.44   |
|                                    | 14   | 9.18   | 9.18   | 9.44        | 9.35   |
|                                    | 15   | 8.92   | 8.92   | 9.17        | 9.07   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 132.46 | 132.49 | 139.23      | 137.17 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.22  | 21.22  | 21.44       | 21.37  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80       | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.02  | 36.02  | 36.24       | 36.17  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00       | 37.00  |
| Margin (dB)                        |      | -0.98  | -0.98  | -0.76       | -0.83  |
| Channel                            | Port | QPSK   | 16QAM  | 64QAM       | 256QAM |
| Mid                                | 0    | 8.71   | 8.51   | 8.62        | 8.53   |
|                                    | 1    | 8.93   | 8.75   | 8.87        | 8.73   |
|                                    | 2    | 9.19   | 9.01   | 9.15        | 8.97   |
|                                    | 3    | 8.99   | 8.79   | 8.93        | 8.75   |
|                                    | 4    | 9.12   | 8.91   | 9.06        | 8.89   |
|                                    | 5    | 9.13   | 8.95   | 9.12        | 8.95   |
|                                    | 6    | 9.65   | 9.42   | 9.66        | 9.42   |
|                                    | 7    | 9.52   | 9.33   | 9.49        | 9.33   |
|                                    | 8    | 9.18   | 8.98   | 9.12        | 8.95   |
|                                    | 9    | 8.96   | 8.80   | 8.97        | 8.81   |
|                                    | 10   | 9.11   | 8.88   | 9.09        | 8.93   |
|                                    | 11   | 9.07   | 8.89   | 9.06        | 8.89   |
|                                    | 12   | 8.96   | 8.78   | 8.93        | 8.77   |
|                                    | 13   | 9.26   | 9.09   | 9.28        | 9.14   |
|                                    | 14   | 9.12   | 8.93   | 9.14        | 8.97   |
|                                    | 15   | 8.83   | 8.65   | 8.79        | 8.70   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 130.42 | 124.84 | 129.65      | 124.95 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.15  | 20.96  | 21.13       | 20.97  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80       | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.95  | 35.76  | 35.93       | 35.77  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00       | 37.00  |
| Margin (dB)                        |      | -1.05  | -1.24  | -1.07       | -1.23  |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (39) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------|--------|--------|--------|
| High                               | 0    | 8.10   | 8.13   | 8.07   | 8.07   |
|                                    | 1    | 8.42   | 8.46   | 8.44   | 8.40   |
|                                    | 2    | 8.62   | 8.65   | 8.60   | 8.67   |
|                                    | 3    | 8.44   | 8.50   | 8.43   | 8.49   |
|                                    | 4    | 8.47   | 8.50   | 8.48   | 8.47   |
|                                    | 5    | 8.49   | 8.52   | 8.49   | 8.54   |
|                                    | 6    | 8.93   | 8.94   | 8.97   | 8.94   |
|                                    | 7    | 8.87   | 8.97   | 8.91   | 8.95   |
|                                    | 8    | 8.45   | 8.51   | 8.47   | 8.49   |
|                                    | 9    | 8.39   | 8.46   | 8.37   | 8.43   |
|                                    | 10   | 8.47   | 8.54   | 8.49   | 8.54   |
|                                    | 11   | 8.39   | 8.47   | 8.45   | 8.54   |
|                                    | 12   | 8.11   | 8.16   | 8.15   | 8.21   |
|                                    | 13   | 8.57   | 8.60   | 8.65   | 8.74   |
|                                    | 14   | 8.36   | 8.39   | 8.39   | 8.41   |
|                                    | 15   | 8.20   | 8.20   | 8.19   | 8.31   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 112.23 | 113.42 | 112.70 | 113.75 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.50  | 20.55  | 20.52  | 20.56  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.30  | 35.35  | 35.32  | 35.36  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.70  | -1.65  | -1.68  | -1.64  |

**Table 8-13. Power Spectral Density Table (n48\_1C\_40M)**

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (40) / (221) pages

| Channel                            | Port | QPSK   | 16QAM       | 64QAM  | 256QAM |
|------------------------------------|------|--------|-------------|--------|--------|
| Low                                | 0    | 8.74   | 8.75        | 8.60   | 8.76   |
|                                    | 1    | 9.14   | 9.16        | 8.96   | 9.09   |
|                                    | 2    | 9.30   | 9.31        | 9.19   | 9.36   |
|                                    | 3    | 9.16   | 9.20        | 9.04   | 9.21   |
|                                    | 4    | 9.29   | 9.28        | 9.09   | 9.32   |
|                                    | 5    | 9.05   | 9.21        | 9.00   | 9.25   |
|                                    | 6    | 9.61   | 9.56        | 9.49   | 9.67   |
|                                    | 7    | 9.62   | 9.62        | 9.40   | 9.66   |
|                                    | 8    | 9.36   | 9.28        | 9.12   | 9.35   |
|                                    | 9    | 9.18   | 9.12        | 8.95   | 9.22   |
|                                    | 10   | 9.22   | 9.19        | 8.99   | 9.32   |
|                                    | 11   | 9.28   | 9.17        | 9.04   | 9.34   |
|                                    | 12   | 9.21   | 9.03        | 8.85   | 9.16   |
|                                    | 13   | 9.49   | 9.46        | 9.13   | 9.43   |
|                                    | 14   | 9.30   | 9.24        | 9.08   | 9.34   |
|                                    | 15   | 9.00   | 8.95        | 8.81   | 9.03   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 134.62 | 133.87      | 128.61 | 135.75 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.29  | 21.27       | 21.09  | 21.33  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80       | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.09  | 36.07       | 35.89  | 36.13  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00       | 37.00  | 37.00  |
| Margin (dB)                        |      | -0.91  | -0.93       | -1.11  | -0.87  |
| Channel                            | Port | QPSK   | 16QAM       | 64QAM  | 256QAM |
| Mid                                | 0    | 8.79   | 8.88        | 8.80   | 8.77   |
|                                    | 1    | 8.96   | 9.07        | 9.02   | 8.99   |
|                                    | 2    | 9.28   | 9.35        | 9.29   | 9.28   |
|                                    | 3    | 9.06   | 9.18        | 9.09   | 9.10   |
|                                    | 4    | 9.19   | 9.29        | 9.21   | 9.19   |
|                                    | 5    | 9.21   | 9.25        | 9.19   | 9.22   |
|                                    | 6    | 9.78   | <b>9.82</b> | 9.72   | 9.74   |
|                                    | 7    | 9.62   | 9.67        | 9.67   | 9.69   |
|                                    | 8    | 9.21   | 9.30        | 9.27   | 9.25   |
|                                    | 9    | 9.01   | 9.05        | 9.09   | 9.08   |
|                                    | 10   | 9.13   | 8.89        | 9.15   | 9.14   |
|                                    | 11   | 9.16   | 8.95        | 9.22   | 9.22   |
|                                    | 12   | 8.99   | 8.83        | 9.01   | 8.99   |
|                                    | 13   | 9.41   | 9.16        | 9.39   | 9.36   |
|                                    | 14   | 9.24   | 9.01        | 9.27   | 9.20   |
|                                    | 15   | 8.91   | 8.66        | 8.96   | 8.91   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 132.83 | 131.76      | 133.54 | 133.15 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.23  | 21.20       | 21.26  | 21.24  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80       | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.03  | 36.00       | 36.06  | 36.04  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00       | 37.00  | 37.00  |
| Margin (dB)                        |      | -0.97  | -1.00       | -0.94  | -0.96  |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (41) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------|--------|--------|--------|
| High                               | 0    | 8.41   | 8.18   | 8.40   | 8.40   |
|                                    | 1    | 8.69   | 8.48   | 8.71   | 8.76   |
|                                    | 2    | 8.87   | 8.70   | 8.95   | 8.94   |
|                                    | 3    | 8.70   | 8.56   | 8.77   | 8.78   |
|                                    | 4    | 8.81   | 8.63   | 8.84   | 8.83   |
|                                    | 5    | 8.72   | 8.60   | 8.81   | 8.81   |
|                                    | 6    | 9.27   | 9.12   | 9.26   | 9.33   |
|                                    | 7    | 9.19   | 9.08   | 9.23   | 9.26   |
|                                    | 8    | 8.76   | 8.63   | 8.76   | 8.78   |
|                                    | 9    | 8.68   | 8.54   | 8.68   | 8.75   |
|                                    | 10   | 8.76   | 8.64   | 8.78   | 8.78   |
|                                    | 11   | 8.78   | 8.63   | 8.83   | 8.77   |
|                                    | 12   | 8.45   | 8.32   | 8.43   | 8.42   |
|                                    | 13   | 8.94   | 8.83   | 8.93   | 8.90   |
|                                    | 14   | 8.71   | 8.56   | 8.70   | 8.68   |
|                                    | 15   | 8.49   | 8.33   | 8.51   | 8.49   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 120.54 | 116.47 | 121.19 | 121.36 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.81  | 20.66  | 20.83  | 20.84  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.61  | 35.46  | 35.63  | 35.64  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.39  | -1.54  | -1.37  | -1.36  |

Table 8-14. Power Spectral Density Table (n48\_2C\_20M+30M)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
**CTK-2025-01906**  
Page (42) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM       | 256QAM |
|------------------------------------|------|--------|--------|-------------|--------|
| Low                                | 0    | 8.48   | 8.61   | 8.82        | 8.75   |
|                                    | 1    | 9.12   | 8.85   | 9.04        | 9.01   |
|                                    | 2    | 9.32   | 9.15   | 9.38        | 9.27   |
|                                    | 3    | 9.17   | 8.99   | 9.21        | 9.11   |
|                                    | 4    | 9.26   | 9.07   | 9.22        | 9.18   |
|                                    | 5    | 9.23   | 9.04   | 9.28        | 9.13   |
|                                    | 6    | 9.72   | 9.56   | <b>9.75</b> | 9.61   |
|                                    | 7    | 9.62   | 9.45   | 9.69        | 9.51   |
|                                    | 8    | 9.30   | 9.13   | 9.35        | 9.19   |
|                                    | 9    | 9.08   | 8.88   | 9.10        | 9.00   |
|                                    | 10   | 9.23   | 9.05   | 9.23        | 9.13   |
|                                    | 11   | 9.22   | 9.00   | 9.25        | 9.11   |
|                                    | 12   | 9.13   | 8.91   | 9.08        | 9.00   |
|                                    | 13   | 9.41   | 9.20   | 9.40        | 9.25   |
|                                    | 14   | 9.27   | 9.12   | 9.32        | 9.19   |
|                                    | 15   | 9.04   | 8.86   | 9.06        | 8.95   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 134.08 | 128.85 | 135.16      | 131.65 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.27  | 21.10  | 21.31       | 21.19  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80       | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.07  | 35.90  | 36.11       | 35.99  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00       | 37.00  |
| Margin (dB)                        |      | -0.93  | -1.10  | -0.89       | -1.01  |
| Channel                            | Port | QPSK   | 16QAM  | 64QAM       | 256QAM |
| Mid                                | 0    | 8.67   | 8.53   | 8.46        | 8.26   |
|                                    | 1    | 8.67   | 8.71   | 8.69        | 8.55   |
|                                    | 2    | 8.93   | 8.94   | 8.95        | 8.74   |
|                                    | 3    | 8.69   | 8.75   | 8.78        | 8.54   |
|                                    | 4    | 8.83   | 8.90   | 8.91        | 8.65   |
|                                    | 5    | 8.83   | 8.89   | 8.87        | 8.68   |
|                                    | 6    | 9.37   | 9.42   | 9.42        | 9.16   |
|                                    | 7    | 9.20   | 9.31   | 9.24        | 9.01   |
|                                    | 8    | 8.89   | 9.01   | 8.96        | 8.68   |
|                                    | 9    | 8.69   | 8.76   | 8.75        | 8.56   |
|                                    | 10   | 8.80   | 8.86   | 8.83        | 8.60   |
|                                    | 11   | 8.79   | 8.87   | 8.79        | 8.60   |
|                                    | 12   | 8.70   | 8.77   | 8.71        | 8.50   |
|                                    | 13   | 9.00   | 9.02   | 8.97        | 8.83   |
|                                    | 14   | 8.93   | 8.93   | 8.92        | 8.71   |
|                                    | 15   | 8.59   | 8.60   | 8.58        | 8.43   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 122.88 | 124.10 | 123.37      | 117.51 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.89  | 20.94  | 20.91       | 20.70  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80       | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.69  | 35.74  | 35.71       | 35.50  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00       | 37.00  |
| Margin (dB)                        |      | -1.31  | -1.26  | -1.29       | -1.50  |

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (43) / (221) pages

| Channel                            | Port | QPSK   | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------|--------|--------|--------|
| High                               | 0    | 8.02   | 8.15   | 8.14   | 8.33   |
|                                    | 1    | 8.33   | 8.43   | 8.46   | 8.70   |
|                                    | 2    | 8.53   | 8.66   | 8.66   | 8.87   |
|                                    | 3    | 8.31   | 8.48   | 8.46   | 8.69   |
|                                    | 4    | 8.42   | 8.55   | 8.54   | 8.70   |
|                                    | 5    | 8.38   | 8.44   | 8.53   | 8.70   |
|                                    | 6    | 8.86   | 8.95   | 9.00   | 9.14   |
|                                    | 7    | 8.78   | 8.86   | 8.92   | 9.19   |
|                                    | 8    | 8.41   | 8.47   | 8.56   | 8.80   |
|                                    | 9    | 8.28   | 8.39   | 8.46   | 8.75   |
|                                    | 10   | 8.39   | 8.48   | 8.55   | 8.83   |
|                                    | 11   | 8.35   | 8.43   | 8.49   | 8.73   |
|                                    | 12   | 8.16   | 8.18   | 8.26   | 8.46   |
|                                    | 13   | 8.62   | 8.67   | 8.71   | 8.94   |
|                                    | 14   | 8.42   | 8.47   | 8.51   | 8.72   |
|                                    | 15   | 8.17   | 8.23   | 8.27   | 8.52   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 110.87 | 113.16 | 114.25 | 120.24 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 20.45  | 20.54  | 20.58  | 20.80  |
| Ant. Gain (dBi)                    |      | 14.80  | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 35.25  | 35.34  | 35.38  | 35.60  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00  | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -1.75  | -1.66  | -1.62  | -1.40  |

Table 8-15. Power Spectral Density Table (n48\_1C\_60M)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do,  
17142, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

REPORT No.:  
CTK-2025-01906  
Page (44) / (221) pages

| Channel                            | Port | QPSK         | 16QAM  | 64QAM  | 256QAM |
|------------------------------------|------|--------------|--------|--------|--------|
| Low                                | 0    | 9.11         | 9.16   | 8.85   | 8.87   |
|                                    | 1    | 9.33         | 9.36   | 9.08   | 9.09   |
|                                    | 2    | 9.64         | 9.71   | 9.36   | 9.47   |
|                                    | 3    | 9.61         | 9.67   | 9.37   | 9.39   |
|                                    | 4    | 9.43         | 9.48   | 9.30   | 9.27   |
|                                    | 5    | 9.45         | 9.56   | 9.19   | 9.31   |
|                                    | 6    | 9.96         | 10.05  | 9.74   | 9.77   |
|                                    | 7    | 9.79         | 9.96   | 9.56   | 9.65   |
|                                    | 8    | 9.50         | 9.63   | 9.28   | 9.38   |
|                                    | 9    | 9.30         | 9.44   | 9.09   | 9.18   |
|                                    | 10   | 9.55         | 9.66   | 9.33   | 9.36   |
|                                    | 11   | 9.37         | 9.51   | 9.12   | 9.21   |
|                                    | 12   | 9.54         | 9.67   | 9.31   | 9.38   |
|                                    | 13   | 9.58         | 9.71   | 9.37   | 9.46   |
|                                    | 14   | 9.47         | 9.60   | 9.25   | 9.34   |
|                                    | 15   | 9.33         | 9.43   | 9.09   | 9.15   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 142.66       | 146.11 | 135.30 | 137.28 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.54        | 21.65  | 21.31  | 21.38  |
| Ant. Gain (dBi)                    |      | 14.80        | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.34        | 36.45  | 36.11  | 36.18  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00        | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -0.66        | -0.55  | -0.89  | -0.82  |
| Channel                            | Port | QPSK         | 16QAM  | 64QAM  | 256QAM |
| Mid                                | 0    | 9.11         | 9.07   | 8.91   | 9.05   |
|                                    | 1    | 9.33         | 9.32   | 9.15   | 9.31   |
|                                    | 2    | 9.63         | 9.61   | 9.43   | 9.60   |
|                                    | 3    | 9.46         | 9.45   | 9.22   | 9.42   |
|                                    | 4    | 9.63         | 9.64   | 9.50   | 9.59   |
|                                    | 5    | 9.55         | 9.54   | 9.44   | 9.50   |
|                                    | 6    | <b>10.08</b> | 10.08  | 9.94   | 10.01  |
|                                    | 7    | 10.00        | 10.02  | 9.88   | 9.95   |
|                                    | 8    | 9.64         | 9.62   | 9.51   | 9.58   |
|                                    | 9    | 9.39         | 9.42   | 9.43   | 9.35   |
|                                    | 10   | 9.59         | 9.60   | 9.56   | 9.47   |
|                                    | 11   | 9.55         | 9.56   | 9.65   | 9.44   |
|                                    | 12   | 9.54         | 9.45   | 9.60   | 9.49   |
|                                    | 13   | 9.80         | 9.79   | 9.92   | 9.75   |
|                                    | 14   | 9.63         | 9.61   | 9.73   | 9.59   |
|                                    | 15   | 9.39         | 9.40   | 9.24   | 9.33   |
| Total MIMO Conducted PSD (mW/MHz)  |      | 145.50       | 145.25 | 143.12 | 143.65 |
| Total MIMO Conducted PSD (dBm/MHz) |      | 21.63        | 21.62  | 21.56  | 21.57  |
| Ant. Gain (dBi)                    |      | 14.80        | 14.80  | 14.80  | 14.80  |
| e.i.r.p PSD (dBm/MHz)              |      | 36.43        | 36.42  | 36.36  | 36.37  |
| e.i.r.p PSD Limit (dBm/MHz)        |      | 37.00        | 37.00  | 37.00  | 37.00  |
| Margin (dB)                        |      | -0.57        | -0.58  | -0.64  | -0.63  |