FCC CFR47 PART 18 SUBPART C
ISM EQUIPMENT

TEST REPORT

FOR

1200W MICROWAVE OVEN

MODEL: MW1255WA

FCC ID: A3LMW1255

PROJECT NUMBER: 00U0567-1

ISSUE DATE: NOVEMBER 8, 2000

Prepared for
SAMSUNG ELECTRONICS CO., LTD. -3
85 WEST TASMAN DRIVE
SAN JOSE, CA 95134 USA

Prepared by
COMPLIANCE CERTIFICATION SERVICES, INC.
561 F MONTEREY ROAD ROUTE 2
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888

LAB CODE:200065-0

TABLE OF CONTENTS **PAGE**

1. VERIFICATION OF COMPLIANCE.....1

2. PRODUCT DESCRIPTION.....2

3. TEST FACILITY.....2

4. ACCREDITATION AND LISTING.....2

5. RADIO NOISE EMISSIONS MEASURMENTS PROCEDURE/RESULTS.....2

5.1 RADIATION HAZARD MEASUREMENT.....2

5.2 INPUT POWER 3

5.3 RF OUPUT POWER MEASUREMENT.....4

5.4 OPERATING FREQUENCY MEASUREMENTS.....5

5.5 VARIATION IN OPERATING FREQUENCY WITH TIME.....5

5.6 VARIATION IN OPERATING FREQUENCY WITH VOLTAGE.....6

5.7 RADIATION EMISSIONS 7

6. MEASUREMENT EQUIPMENT LIST.....9

7.. EUT SETUP PHOTOS.....10

ATTACHMENTS:

- **RADIATED EMISSION DATA**
- **VARIATION IN OPERATING FREQUENCY WITH VOLTAGE PLOTS**
- **VARIATION IN OPERATING FREQUENCY WITH TIME PLOTS**
- **VAIATION IN OPEREATING FREQUENCY WITH VOLTAGE PLOTS**
- **PROPOSED FCC ID LABEL**
- **USER MANUAL AND SCHEMATICS**
- **EUT PHOTOGRAPHS**

This report shall not be reproduced except in full, without the written approval of CCS.

1. VERIFICATION OF COMPLIANCE

COMPANY NAME : SAMSUNG ELECTRONICS CO., LTD. -3
85 WEST TASMAN DRIVE
SAN JOSE, CA 95134 USA

CONTACT PERSON : WALLACE OH / MANAGER

TELEPHONE NO : (408) 828-8833

EUT DESCRIPTION: 1200W MICROWAVE OVEN

MODEL NO/NAME : MW 1255WA

DATE TESTED : NOVEMBER 8, 2000

TYPE OF EQUIPMENT:	CONSUMER ISM EQUIPMENT
TECHNICAL LIMIT:	FCC PART 18 SUBPART C
FCC RULES:	PART 18
MEASUREMENT PROCEDURE	MP-5
EQUIPMENT AUTHORIZATION PROCEDURE	CERTIFICATION
MODIFICATIONS MADE ON EUT	☐ YES ☒ NO

The above equipment was tested by Compliance Certification Services for compliance with the requirements set forth in the FCC CFR 47, PART 18. This said equipment in this configuration described in this report shows that maximum emission levels emanating from equipment are within the compliance requirements.

WARNING: This report documents conditions under which testing was conducted and the results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Tested and Reviewed By:

STEVE CHENG
SENIOR EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

Released For CCS By:

PETE KREBILL
ASSOCIATE EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888

This report shall not be reproduced except in full, without the written approval of CCS.

2. PRODUCT DESCRIPTION

The equipment under test is a microwave oven sold for consumer use. Models: MW 1255WA is 1200W microwave oven with digital controls. Magnetron Model: OM75P (31) Serial (0OAC096486 by Samsung-0567-1.

3. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

4. ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code:200065-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT (1300B3) and 31040/SIT(1300F2))

5. RADIO NOISE EMISSION MEASUREMENTS PROCEDURES/RESULTS

5.1 RADIATION HAZARD MEASUREMENT



Radiation Hazard Measurements

A 1000-ml water load was placed in the center of the oven. The power setting was set to 10(100%) maximum power. While the oven was operating, the Microwave probe was moved slowly around the door seams to check for leakage.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888
This report shall not be reproduced except in full, without the written approval of CCS.



fig.1 .17 mW/cm²

LOCATION	**MAXIMUM LEAKAGE (mW/cm²)**	**LIMIT (mW/cm²)**
Fig.1 shows the locations of maximum leakage	.17	1.0
All others	.1	1.0

5.2 INPUT POWER

Input power and current were measured using a voltmeter and a ampmeter. A 700 ml water load was placed in the center of the oven and the oven was set to 10(100%) maximum power. A 700-ml water load was chosen for its compatibility. Manufacturers to determine their input ratings commonly use this procedure.

	Input Voltage (Vac)	**Input Current (amps)**	**Measured Input power (watts)**
1650W:	111.6	15.8	1763.28

Based on the measured input power, the EUT was found to be operating within the intended specifications.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888

This report shall not be reproduced except in full, without the written approval of CCS.

5.3 RF OUTPUT POWER MEASUREMENT

The Caloric Method was used to determine maximum output power. The initial temperature of a 1000-ml water load was measured.

The water load was placed in the center of the oven. The oven was operated at maximum output power for 120 seconds. Then the temperature of the water was re-measured.

Quantity of water (ml)	Starting Temperature (C°)	Final Temperature (C°)	Elapsed Time (seconds)	RF Power (watts)
1000	23.89	48.89	120	875
1000	20.0	44.44	120	855.54
1000	20.0	45	120	875

Average of 3 Trials: 868.51 W

$$\text{Power} = \frac{(4.2\ \text{Joules/Cal}) \times (\text{Volume in ml}) \times (\text{Temp. Rise})}{\text{Time in seconds}}$$

The measured output was found to be above 500 Watts. Therefore, the limit was calculated by the formula:
25xSQRT(868.51w/500)=32.94mv/m@300m.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888
This report shall not be reproduced except in full, without the written approval of CCS.

5.4 OPERATING FREQUENCY MEASUREMENTS



Figure 1. Operating Frequency Measurement Set-up

5.5 VARIATION IN OPERATING FREQUENCY WITH TIME

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000-ml water load was placed in the center of the oven and the oven was operated at maximum output power.

The fundamental operating frequency was monitor until the water load was reduced to 20% of the original load.

The results of this test are as follows.

Initial load: 1000 ml
Load at completion of test: 200 ml

Maximum frequency observed: 2469 MHz
Maximum frequency allowed: 2500 MHz

Minimum frequency observed: 2417 MHz
Minimum frequency allowed: 2400 MHz

Refer to spectrum analyzer plot under ATTACHMENTS: **VARIATION IN OPERATING FREQUENCY WITH TIME PLOT** for details of frequency variation with operating time.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888
This report shall not be reproduced except in full, without the written approval of CCS.

5.6 VARIATION IN OPERATING FREQUENCY WITH VOLTAGE

Following the above test, after operating the oven long enough to assure that stable operating temperature were obtained, the operating frequency was monitored as the input voltage was varied between 80 to 125 percent of the nominal rating.

The water load was maintained at 200 ml for the duration of the test.

The results of this test are as follows:

Line voltage varied from 96Vac to 150Vac.

150Vac Maximum frequency observed: 2470 MHz
Maximum frequency allowed: **2500** MHz

Minimum frequency observed: 2418 MHz
Minimum frequency allowed: **2400** MHz

120Vac Maximum frequency observed: 2469 MHz
Maximum frequency allowed: **2500** MHz

Minimum frequency observed: 2417 MHz
Minimum frequency allowed: **2400** MHz

96Vac Maximum frequency observed: 2470 MHz
Maximum frequency allowed: **2500** MHz

Minimum frequency observed: 2418 MHz
Minimum frequency allowed: **2400** MHz

Refer to spectrum analyzer plots under ATTACHMENTS: **VARIATION IN OPERATING FREQUENCY WITH VOLTAGE PLOTS** for details of Frequency variation with operating voltage.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888

This report shall not be reproduced except in full, without the written approval of CCS.

5.7 RADIATED EMISSIONS

Radiated emissions were measured over an inclusive frequency range to 30MHz through the 10th harmonic of the operating frequency. For this test, a 1-meter high wooden table in an open laboratory area supported the device under test. The table was placed on a turntable.

The measurement antenna was placed 3 meters for measurements from 30 - 1000MHz and 1 meter for measurements from 1000 - 25,000MHz, respectively, for the device under test. The indicated frequency range was swept as the device under test was rotated along its vertical axis in 90° increments.

During the preliminary tests, the load consisted of 700-ml tap water placed in the center of the oven. The emissions were observed while the device under test was operated at maximum output power.

The level of the emissions near the edge of the designated ISM frequency band was measured. For this test, the load consisted of 700-ml water load located in the center of the oven.

The levels of the second and third harmonic were measured inclusively with a 300 ml and 700 ml water load alternately placed in the center and right front corner of the oven. Harmonics beyond the third were measured with a 700-ml load placed in the center of the oven. The data obtained during these tests is contained on the attached spreadsheet.

The maximum of all other out-of-band emissions were measured while a 700-ml load was placed in the center of the oven. Maximum readings were recorded after variations in antenna polarizations, height, device orientation, load position, and size. For frequencies above 1 GHz, the video bandwidth of the spectrum analyzer was set to simulate a linear average detection mode (10Hz).

For all emissions the equivalent 300 meters intensity was calculated assuming a linear decrease in the intensity of the RFI field with increased distance. In the operating modes and conditions described, there were no over-limit emissions discovered.

This report shall not be reproduced except in full, without the written approval of CCS.



Figure 2. Radiated Emissions Configuration

There were no emissions detected from the EUT in the 30 - 1000 MHz region. Emissions detected in the 1000 - 25,000 MHz region are reported in a spreadsheet under ATTACHMENTS: **RADIATION EMISSION DATA**.

COMPLIANCE CERTIFICATION SERVICES DOCUMENT NO:CCSUP4002D
561 F MONTERY RD MORGAN HILL, CA 95037 USA TEL: (408) 463-0885 FAX: (408) 463-0888

This report shall not be reproduced except in full, without the written approval of CCS.

6. MEASUREMENT EQUIPMENT LIST

Equipment	Manufacturer	Model No.	Serial No.	Site	Cal Date	Due Date
Spectrum Analyzer	**H.P.**(100Hz-22GHz)	**8566B**	**214A01296**	**A**	**12/99**	**12/00**
Spectrum Display	**H.P.**	**85662A**	**2152A03066**	**A**	**12/99**	**12/00**
Quasi-Peak Detector	**H.P.** (9KHz-1GHz)	**85650A**	**2811A01155**	**A**	**12/99**	**12/00**
Per-Amp	**H.P.**(0.1-1300MHz)	**8447D**	**2944A06833**	**A**	**10/99**	**10/00**
BILOG Antenna	**Chase**	**CBL6112**	**2049**	**A**	**11/99**	**11/00**
EMC Receiver	**H.P.**(9KHz-26.5GHz)	**8593EM**	**3710A00205**	**A**	**5/00**	**5/01**
Pre-Amp	**H.P.** (1-26.5GHz)	**8449B**	**3008A00369**	**A**	**4/00**	**4/01**
Horn Antenna	**EMCO**(1-18GHz)	**3115**	**9001-3245**	**A**	**12/98**	**12/99**
Ac Power Source	**Advanced Central Systems**	**AFC-10K-AFC2**	**J1568**	**A**	**N.C.R.**	**N.C.R.**
Variac(0 – 280Vac)	**Powerstat**	**N/A**	**N/A**	**A**	**N.C.R.**	**N.C.R.**

This report shall not be reproduced except in full, without the written approval of CCS.

7. EUT SETUP PHOTOS

RADIATED HAZARD TEST

This report shall not be reproduced except in full, without the written approval of CCS.

FREQUENCY VS. TIME SETUP

This report shall not be reproduced except in full, without the written approval of CCS.

RF POWER OUTPUT TEST

This report shall not be reproduced except in full, without the written approval of CCS.

FREQUENCY VS. VOLTAGE TEST SETUP

This report shall not be reproduced except in full, without the written approval of CCS.

POWER INPUT SETUP

This report shall not be reproduced except in full, without the written approval of CCS.

ATTACHMENTS

This report shall not be reproduced except in full, without the written approval of CCS.

RADIATED EMISSION DATA

This report shall not be reproduced except in full, without the written approval of CCS.

COMPLIANCE
Certification Services

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

561 F MONTEREY ROAD, MORGAN HILL CA 95037
PHONE: (408) 463-0885 FAX: (408) 463-0888

Project #: 00U0567-1
Report #: 001108A1
Date& Time: 11/08/00 3:59 PM
Test Engr: Steve & Thu

Company: Samsung Electronics Co., Ltd.
EUT Description: Microwave Oven
Test Configuration : EUT
Type of Test: FCC 18
Mode of Operation: Harmonic's Measurement

(●) A-Site ( ) B-Site ( ) C-Site ( ) F-Site | 6 Worst Data | Descending

Freq. (MHz)	Reading (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Dist dB	Other dB	Level (dBuV/m)	Limit FCC_18	Margin (dB)	Pol (H/V)
2353	30.30	27.76	3.00	0.00	49.50	0.00	11.56	30.40	-18.84	H
2393	32.40	27.83	3.09	0.00	49.50	0.00	13.82	30.40	-16.58	H
4971	65.40	32.85	6.24	31.25	49.50	1.00	22.74	30.40	-7.66	H
7396	61.30	37.16	7.63	31.25	49.50	1.00	24.34	30.40	-6.06	H
9846	57.70	37.65	9.05	31.25	49.50	1.00	22.65	30.40	-7.75	H
12296	52.00	39.18	9.07	31.25	49.50	1.00	18.50	30.40	-11.90	H
14746	50.40	40.18	11.66	31.25	49.50	1.00	20.49	30.40	-9.91	H
17176	50.00	43.26	13.26	31.25	49.50	1.00	24.77	30.40	-5.63	H
19480	42.50	32.09	14.54	31.25	49.50	1.00	7.38	30.40	-23.02	H
21915	42.30	32.50	15.76	31.25	49.50	1.00	8.81	30.40	-21.59	H
2353	29.90	27.76	3.00	0.00	49.50	0.00	11.16	30.40	-19.24	V
2393	32.10	27.83	3.09	0.00	49.50	0.00	13.52	30.40	-16.88	V
4971	63.90	32.85	6.24	31.25	49.50	1.00	21.24	30.40	-9.16	V
7396	61.50	37.16	7.63	31.25	49.50	1.00	24.54	30.40	-5.86	V
9846	50.90	37.65	9.05	31.25	49.50	1.00	15.85	30.40	-14.55	V
12296	45.10	39.18	9.07	31.25	49.50	1.00	11.60	30.40	-18.80	V
14746	43.60	40.18	11.66	31.25	49.50	1.00	13.69	30.40	-16.71	V
17176	41.60	43.26	13.26	31.25	49.50	1.00	16.37	30.40	-14.03	V
19480	42.60	32.09	14.54	31.25	49.50	1.00	7.48	30.40	-22.92	V
21915	42.40	32.50	15.76	31.25	49.50	1.00	8.91	30.40	-21.49	V

Total data #: 19
V.2a

Peak: RBW=VBW=1MHz
Average: RBW=1MHz, VBW=10Hz
***DIST**: Correction to extrapolate reading to 1m specifications distance*
20dB log(dm/Ds) where dm = meas. Dist, Ds = specification distance
OTHER: High pass filter insertion loss
Limit (dBuV) = 20*log(25*SQR(868.51/500)) = 30.4

This report shall not be reproduced except in full, without the written approval of CCS.

VARIATION IN OPERATING FREQUENCY WITH VOLTAGE PLOTS (96VAC)

This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.

VARIATION IN OPERATING FREQUENCY WITH TIME PLOTS (120VAC)

This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.

VARIATION IN OPERATING FREQUENCY WITH VOLTAGE PLOTS (150VAC)

This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.



This report shall not be reproduced except in full, without the written approval of CCS.