ELEMENT WASHINGTON DC LLC
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.381.1520
http://www.element.com

MEASUREMENT REPORT
FCC PART 15.407 802.11ax/be (OFDMA)

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:
7/30/2024 – 8/26/2024
Test Report Issue Date:
8/27/2024
Test Site/Location:
Element lab., Columbia, MD, USA
Test Report Serial No.:
1M2407080057-07.A3L

FCC ID:	**A3LNP750XQA**
APPLICANT:	**Samsung Electronics Co., Ltd.**

Application Type:	Certification
Model:	NP750XQA
Additional Model(s)	NP754XQA
EUT Type:	Portable Computing Device
Frequency Range:	5180 – 5885MHz
Modulation Type:	OFDMA
FCC Equipment Class:	Unlicensed National Information Infrastructure TX (NII)
FCC Rule Part(s):	Part 15 Subpart E (15.407)
Test Procedure(s):	ANSI C63.10-2013, KDB 648474 D03 v01r04

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President

ACCREDITED
CERT #2041.01

© 2024 ELEMENT
V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

TABLE OF CONTENTS

1.0 INTRODUCTION 4
1.1 Scope 4
1.2 Element Test Location 4
1.3 Test Facility / Accreditations 4
2.0 PRODUCT INFORMATION 5
2.1 Equipment Description 5
2.2 Device Capabilities 5
2.3 Antenna Description 8
2.4 Test Configuration 8
2.5 Software and Firmware 8
2.6 EMI Suppression Device(s) / Modifications 8
3.0 DESCRIPTION OF TESTS 9
3.1 Evaluation Procedure 9
3.2 Radiated Emissions 9
3.3 Environmental Conditions 9
4.0 ANTENNA REQUIREMENTS 10
5.0 MEASUREMENT UNCERTAINTY 11
6.0 TEST EQUIPMENT CALIBRATION DATA 12
7.0 TEST RESULTS 13
7.1 Summary 13
7.2 26dB Bandwidth Measurement 14
7.2.1 MIMO Antenna-1 26dB Bandwidth Measurements 17
7.2.2 MIMO Antenna-2 26dB Bandwidth Measurements 32
7.3 6dB Bandwidth Measurement 47
7.3.1 MIMO Antenna-1 6dB Bandwidth Measurements 50
7.3.2 MIMO Antenna-2 6dB Bandwidth Measurements 60
7.4 UNII Output Power Measurement 70
7.5 Maximum Power Spectral Density 74
7.5.1 MIMO Antenna-1 Power Spectral Density Measurements 78
7.5.2 MIMO Antenna-2 Power Spectral Density Measurements 103
7.6 Radiated Emission Measurements 129
7.6.1 MIMO Radiated Spurious Emission Measurements (26 Tones) 135
7.6.2 MIMO Radiated Spurious Emission Measurements (242 Tones) 143
7.6.3 MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T) 151
7.6.4 MIMO Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T) 157
7.6.5 MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T) 160
7.6.6 MIMO Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T) 163
7.6.7 MIMO Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T) 169
8.0 CONCLUSION 175

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Channel Bandwidth [MHz]	UNII Band	Tx Frequency [MHz]	MIMO	
			Max. Power [mW]	Max. Power [dBm]
20	1	5180 - 5240	32.70	15.15
	2A	5260 - 5320	32.35	15.10
	2C	5500 - 5720	32.07	15.06
	3	5745 - 5825	31.36	14.96
	4	5845 - 5885	43.09	16.34
40	1	5190 - 5230	29.93	14.76
	2A	5270 - 5310	29.97	14.77
	2C	5510 - 5710	27.79	14.44
	3	5755 - 5795	27.79	14.44
	4	5835 - 5875	38.47	15.85
80	1	5210	30.17	14.80
	2A	5290	29.78	14.74
	2C	5530 - 5690	32.83	15.16
	3	5775	30.79	14.88
	4	5855	38.47	15.85
160	1/2A	5250	32.11	15.07
	2C	5570	31.05	14.92
	3/4	5815	42.02	16.23

EUT Overview

Note: The UNII Band 4 max power values shown in the above table are e.i.r.p values.

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.

- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).

- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.

- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Computing Device FCC ID: A3LNP750XQA**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

Test Device Serial No.: 0721L, 0677B, 0671Z

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ac/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE)

Band 1

Ch.	Frequency (MHz)
36	5180
:	:
40	5200
:	:
48	5240

Band 2A

Ch.	Frequency (MHz)
52	5260
:	:
56	5280
:	:
64	5320

Band 2C

Ch.	Frequency (MHz)
100	5500
:	:
120	5600
:	:
144	5720

Band 3

Ch.	Frequency (MHz)
149	5745
:	:
157	5785
:	:
165	5825

Band 3/4

	Ch.	Frequency (MHz)
	169	5845
	:	:
	173	5865
	:	:
	177	5885

Table 2-1. 802.11ax/be (20MHz) Frequency / Channel Operations

Band 1

Ch.	Frequency (MHz)
38	5190
:	:
46	5230

Band 2A

Ch.	Frequency (MHz)
54	5270
:	:
62	5310

Band 2C

Ch.	Frequency (MHz)
102	5510
:	:
118	5590
:	:
142	5710

Band 3

Ch.	Frequency (MHz)
151	5755
:	:
159	5795

Band 3/4

Ch.	Frequency (MHz)
167	5835
:	:
175	5875

Table 2-2. 802.11ax/be (40MHz BW) Frequency / Channel Operations

Band 1

Ch.	Frequency (MHz)
42	5210

Band 2A

Ch.	Frequency (MHz)
58	5290

Band 2C

Ch.	Frequency (MHz)
106	5530
:	:
122	5610
:	:
138	5690

Band 3

Ch.	Frequency (MHz)
155	5775

Band 3/4

Ch.	Frequency (MHz)
167	5835

Table 2-3. 802.11ax/be (80MHz BW) Frequency / Channel Operations

Band 1/2A

Ch.	Frequency (MHz)
50	5250

Band 2C

Ch.	Frequency (MHz)
114	5570

Band 3/4

Ch.	Frequency (MHz)
163	5815

Table 2-4. 802.11ax/be (160MHz BW) Frequency / Channel Operations

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Notes:

1. 5GHz NII operation is possible in 20MHz, 40MHz, 80MHz, and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Band	Bandwidth	Tone Type	Tone Size	MIMO (1+2)	
				Duty Cycle [%]	DCCF [dB]
5GHz	20MHz	RU	26T	99.53	N/A
			52T	99.61	N/A
			106T	99.25	N/A
			242T	98.34	N/A
		MRU	52+26T	99.46	N/A
			106+26T	99.12	N/A
	40MHz	RU	26T	99.43	N/A
			52T	99.47	N/A
			106T	98.96	N/A
			242T	98.33	N/A
			484T	97.46	0.11
		MRU	52+26T	99.49	N/A
			106+26T	99.12	N/A
	80MHz	RU	26T	99.57	N/A
			52T	99.21	N/A
			106T	99.07	N/A
			242T	98.50	N/A
			484T	97.01	0.13
			996T	97.23	0.12
		MRU	52+26T	99.28	N/A
			106+26T	99.12	N/A
			484+242T	98.05	N/A
	160MHz	RU	26T	99.55	N/A
			52T	99.39	N/A
			106T	98.96	N/A
			242T	98.18	N/A
			484T	97.14	0.13
			996T	96.85	0.14
			2x996T	99.62	N/A
		MRU	52+26T	99.49	N/A
			106+26T	99.16	N/A
			484+242T	97.98	0.09
			996+484T	97.76	0.10

Table 2-5. Measured Duty Cycles

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SISO		SDM		CDD	
		ANT1	ANT2	ANT1	ANT2	ANT1	ANT2
5GHz	11ax	×	×	✓	✓	✓	✓
	11be	×	×	✓	✓	✓	✓

Table 2-6. Frequency / Channel Operations

✓= Support; × = NOT Support
SISO = Single Input Single Output
SDM = Spatial Diversity Multiplexing – MIMO function
CDD = Cyclic Delay Diversity – 2Tx Function

3. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	OFDMA (802.11ax)																				
		26T			52T			106T			242T			484T			996T			2x996T		
HE		0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI	0.8µs GI	1.6µs GI	3.2µs GI
0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6	72.1	68.1	61.3
1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5
2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9	216.2	204.2	183.8
3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245
4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5
5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490
6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6	648.5	612.5	551.3
7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3	720.6	680.6	612.5
8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735
9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3	960.8	907.4	816.7
10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4	1080.9	1020.8	918.8
11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4	1201	1134.3	1020.8
0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3	144.1	136.1	122.5
1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5	288.2	272.2	245
2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8	432.4	408.3	367.5
3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245	576.5	544.4	490
4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5	864.7	816.7	735
5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	275.3	260	234	576.5	544.4	490	1152.9	1088.9	980
6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3	1297.1	1225	1102.5
7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5	1441.2	1361.1	1225
8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735	1729.4	1633.3	1470
9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7	1921.6	1814.8	1633.3
10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8	2161.8	2041.7	1837.5
11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8	2402	2268.5	2041.7

Table 2-7. Supported Data Rates

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

2.3 Antenna Description

The following antenna gains were used for the testing.

Frequency [MHz]	Antenna 1 Gain (dBi)	Antenna 2 Gain (dBi)	Directional Gain (dBi)
5200	-0.13	-1.07	2.42
5300	-0.16	-1.11	2.39
5600	-0.08	-0.56	2.69
5800	-1.16	-1.55	1.66
5900	-1.59	-1.51	1.46

Table 2-8. Antenna Peak Gain

2.4 Test Configuration

ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See 5GHz UNII OFDM report for AC line conducted emissions test setups, 7.6 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

2.5 Software and Firmware

The test was conducted with software/firmware version Windows 11 installed on the EUT.

2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT**.**

Deviation from measurement procedure……..…….....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:
"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antennas of the EUT are **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (±dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	WL25-1	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	4/2/2024	Annual	4/2/2025	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	4/2/2024	Annual	4/2/2025	WL40-1
	AP1-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	AP1-002
-	ETS-001	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-001
-	ETS-002	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	ETS-002
	MD 1M 18-40	EMC Cable and Switch System	4/2/2024	Annual	4/2/2025	MD 1M 18-40
Anritsu	MA24406A	Microwave Peak Power Sensor	9/7/2023	Annual	9/7/2024	11240
Emco	3116	Horn Antenna (18 - 40GHz)	8/8/2022	Biennial	8/8/2024	9203-2178
Rohde & Schwarz	TC-TA18	Vivaldi Antenna	2/23/2023	Biennial	2/23/2025	26040036
Rohde & Schwarz	FSW26	Signal and spectrum analyzer	3/8/2024	Annual	3/8/2025	103187
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	4/2/2024	Annual	4/2/2025	NMLC-2
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	4/9/2024	Annual	4/9/2025	MY52350166
Keysight Technologies	N9020A	MXA Signal Analyzer	4/11/2024	Annual	4/11/2025	MY54500644
Keysight Technologies	N9030A	PXA Signal Analyzer	2/29/2024	Annual	3/1/2025	MY55410501
Keysight Technologies	N9030B	PXA Signal Analyzer, Multi-touch	9/7/2023	Annual	9/7/2024	MY57141001
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	9/25/2023	Annual	9/25/2024	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	9/11/2023	Annual	9/11/2024	100348
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	4/5/2024	Annual	4/5/2025	101716
Rohde & Schwarz	FSW26	Signal and spectrum analyze (26.5GHz)	3/8/2024	Annual	3/8/2025	103187
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	2/15/2024	Annual	2/15/2025	103200
Sunol	JB6	JB6 Antenna	3/2/2023	Biennial	3/2/2025	A082816
Sunol	JB5	Bi-Log Antenna (30M-5GHz)	8/30/2022	Biennial	8/30/2024	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
FCC ID: A3LNP750XQA
FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
N/A	26dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
15.407(e)	6dB Bandwidth	>500kHz (5725-5850MHz and 5850 – 5895MHz)		PASS	Section 7.3
15.407 (a)(1)(iv), (a)(2), (a)(3)	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a)		PASS	Section 7.4
15.407 (a)(1)(iv), (a)(2), (a)(3)	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a)		PASS	Section 7.5
15.407(h)	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b)(1), (b)(2), (b)(3), (b)(4)	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b)	RADIATED	PASS	Section 7.6
15.205, 15.407(b)(1), (b)(4), (b)(5), (b)(6)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209		PASS	Section 7.6, 7.7

Table 7-1. Summary of Test Results

Notes:

1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "EMC Software Tool," Version 2.3.0.
5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 1.5.0.
6) 802.11be OFDMA testing was performed for all signal tone configurations as specified by the 802.11be standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
7) Only one RU index could be selected at a time, so no contiguous or non-contiguous RUs were considered for testing.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2 26dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

ANSI C63.10-2013 – Section 12.4

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

Figure 7-1. Test Instrument & Measurement Setup

Test Notes

The 26dB Bandwidth measurement for each channel was measured with the RU index showing the highest conducted power.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

MIMO 26dB Bandwidth Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 1	5180	be (20MHz)	36	17.29	18.09
	5200	be (20MHz)	40	17.70	17.39
	5240	be (20MHz)	48	16.70	18.31
	5190	be (40MHz)	38	24.12	23.21
	5230	be (40MHz)	46	24.16	26.54
	5210	be (80MHz)	42	32.35	30.19
Band 1/2A	5250	be (160MHz)	50	40.43	35.24
Band 2A	5260	be (20MHz)	52	17.39	18.23
	5280	be (20MHz)	56	18.11	18.21
	5320	be (20MHz)	64	19.80	19.99
	5270	be (40MHz)	54	25.37	25.31
	5310	be (40MHz)	62	20.74	22.53
	5290	be (80MHz)	58	29.03	35.77
Band 2C	5500	be (20MHz)	100	17.76	18.22
	5600	be (20MHz)	120	19.60	19.48
	5720	be (20MHz)	144	19.66	18.69
	5510	be (40MHz)	102	23.33	25.99
	5590	be (40MHz)	118	24.59	24.26
	5710	be (40MHz)	142	21.58	24.02
	5530	be (80MHz)	106	27.46	34.98
	5610	be (80MHz)	122	19.91	27.25
	5690	be (80MHz)	138	33.53	28.62
	5570	be (160MHz)	114	40.09	34.27

Table 7-2. Bands 1, 2A, 2C Conducted 26dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 1	5180	be (20MHz)	36	21.22	21.19
	5200	be (20MHz)	40	21.37	21.16
	5240	be (20MHz)	48	21.25	21.55
	5190	be (40MHz)	38	42.06	42.15
	5230	be (40MHz)	46	42.07	42.70
	5210	be (80MHz)	42	86.98	85.12
Band 1/2A	5250	be (160MHz)	50	172.20	174.91
Band 2A	5260	be (20MHz)	52	21.44	21.42
	5280	be (20MHz)	56	21.45	21.57
	5320	be (20MHz)	64	21.41	21.32
	5270	be (40MHz)	54	42.77	42.97
	5310	be (40MHz)	62	42.43	43.22
	5290	be (80MHz)	58	87.67	85.65
Band 2C	5500	be (20MHz)	100	21.33	21.51
	5600	be (20MHz)	120	21.77	21.14
	5720	be (20MHz)	144	21.14	21.09
	5510	be (40MHz)	102	42.11	42.97
	5590	be (40MHz)	118	41.81	42.27
	5710	be (40MHz)	142	41.74	42.17
	5530	be (80MHz)	106	91.64	88.71
	5610	be (80MHz)	122	92.32	89.34
	5690	be (80MHz)	138	91.46	89.29
	5570	be (160MHz)	114	173.93	176.18

Table 7-3. Bands 1, 2A, 2C Conducted 26dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	MRU Configuration	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 1	5200	be (20MHz)	40	106+26T	20.12	17.67
	5210	be (80MHz)	42	484+242T	85.99	84.94
Band 1/2A	5250	be (160MHz)	50	996+484T	176.90	175.60
Band 2A	5280	be (20MHz)	56	106+26T	19.64	19.90
	5290	be (80MHz)	58	484+242T	85.90	86.03
Band 2C	5600	be (20MHz)	120	106+26T	20.14	20.07
	5610	be (80MHz)	122	484+242T	90.10	90.11
	5570	be (160MHz)	114	996+484T	176.50	175.50

Table 7-4. Bands 1, 2A, 2C Conducted 26dB Bandwidth Measurements MIMO ANT1/2 (MRU)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.1 MIMO Antenna-1 26dB Bandwidth Measurements



Plot 7-1. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 40)



Plot 7-2. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 38)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-3. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 42)



Plot 7-4. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 1/2A) – Ch. 50)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-5. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 56)



Plot 7-6. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 54)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-7. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 58)



Plot 7-8. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 120)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Plot 7-9. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 118)



Plot 7-10. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 122)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-11. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 114)



Plot 7-12. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 1) – Ch. 40)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-13. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 1) – Ch. 38)



Plot 7-14. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 1) – Ch. 42)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-15. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 2x996 Tones (UNII Band 1/2A) – Ch. 50)



Plot 7-16. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 2A) – Ch. 56)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-17. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 2A) – Ch. 54)



Plot 7-18. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 2A) – Ch. 58)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-19. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 2C) – Ch. 120)



Plot 7-20. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 2C) – Ch. 118)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-21. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 2C) – Ch. 122)



Plot 7-22. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 2x996 Tones (UNII Band 2C) – Ch. 114)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-23. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 106+26T Tones (UNII Band 1) – Ch. 40)



Plot 7-24. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 484+242 Tones (UNII Band 1) – Ch. 42)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-25. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 996+484 Tones (UNII Band 1/2A) – Ch. 50)



Plot 7-26. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 106+26 Tones (UNII Band 2A) – Ch. 56)

© 2024 ELEMENT
V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-27. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 484+242 Tones (UNII Band 2A) – Ch. 58)



Plot 7-28. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 106+26 Tones (UNII Band 2C) – Ch. 120)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-29. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 484+242 Tones (UNII Band 2C) – Ch. 122)



Plot 7-30. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 996+484 Tones (UNII Band 2C) – Ch. 114)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.2.2 MIMO Antenna-2 26dB Bandwidth Measurements



Plot 7-31. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 40)



Plot 7-32. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 38)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-33. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 42)



Plot 7-34. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 1/2A) – Ch. 50)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-35. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 56)



Plot 7-36. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 54)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-37. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 58)



Plot 7-38. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 120)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-39. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 118)



Plot 7-40. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 122)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-41. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 114)



Plot 7-42. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 1) – Ch. 40)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-43. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 1) – Ch. 38)



Plot 7-44. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 1) – Ch. 42)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-45. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 2x996 Tones (UNII Band 1/2A) – Ch. 50)



Plot 7-46. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 2A) – Ch. 56)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-47. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 2A) – Ch. 54)



Plot 7-48. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 2A) – Ch. 58)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-49. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 2C) – Ch. 120)



Plot 7-50. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 2C) – Ch. 118)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-51. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 2C) – Ch. 122)



Plot 7-52. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 2x996 Tones (UNII Band 2C) – Ch. 114)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-53. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 106+26T Tones (UNII Band 1) – Ch. 40)



Plot 7-54. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 484+242 Tones (UNII Band 1) – Ch. 42)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-55. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 996+484 Tones (UNII Band 1/2A) – Ch. 50)



Plot 7-56. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 106+26 Tones (UNII Band 2A) – Ch. 56)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-57. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 484+242 Tones (UNII Band 2A) – Ch. 58)



Plot 7-58. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 106+26 Tones (UNII Band 2C) – Ch. 120)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-59. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 484+242 Tones (UNII Band 2C) – Ch. 122)



Plot 7-60. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 996+484 Tones (UNII Band 2C) – Ch. 114)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3 6dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 6dB bandwidth.

In the 5.725 – 5.850GHz and 5.850-5.895GHz bands, the 6dB bandwidth must be ≥ 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 6.9.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW ≥ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

Figure 7-2. Test Instrument & Measurement Setup

Test Notes

The 6dB Bandwidth measurement for each channel was measured with the RU index showing the highest conducted power.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

MIMO 6dB Bandwidth Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3	5745	be (20MHz)	149	2.09	2.14
	5785	be (20MHz)	157	2.09	2.13
	5825	be (20MHz)	165	2.72	2.70
	5755	be (40MHz)	151	2.18	2.21
	5795	be (40MHz)	159	2.22	2.20
	5775	be (80MHz)	155	2.30	2.25

Table 7-5. Band 3 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3/4	5845	be (20MHz)	169	2.66	2.68
Band 4	5865	be (20MHz)	173	2.70	2.70
	5885	be (20MHz)	177	2.65	2.64
Band 3/4	5835	be (40MHz)	167	2.18	2.17
Band 4	5875	be (40MHz)	175	2.16	2.26
Band 3/4	5855	be (80MHz)	171	2.27	2.27
Band 4	5815	be (160MHz)	163	2.76	2.62

Table 7-6. Bands 3/4 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3	5745	be (20MHz)	149	19.03	19.00
	5785	be (20MHz)	157	19.03	19.06
	5825	be (20MHz)	165	19.01	19.08
	5755	be (40MHz)	151	38.27	38.15
	5795	be (40MHz)	159	36.92	37.57
	5775	be (80MHz)	155	75.45	72.76

Table 7-7. Band 3 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3/4	5845	be (20MHz)	169	18.99	18.96
Band 4	5865	be (20MHz)	173	18.87	18.98
	5885	be (20MHz)	177	18.98	19.00
Band 3/4	5835	be (40MHz)	167	36.95	37.75
Band 4	5875	be (40MHz)	175	37.52	37.55
Band 3/4	5855	be (80MHz)	171	75.22	78.21
	5815	be (160MHz)	163	158.08	158.36

Table 7-8. Bands 3/4 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	MRU Configuration	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3/4	5785	be (20MHz)	157	106+26T	15.92	17.17
	5775	be (80MHz)	155	484+242T	75.34	75.09
Band 4	5865	be (20MHz)	173	106+26T	14.66	17.12
Band 3/4	5855	be (80MHz)	171	484+242T	75.32	74.77
	5815	be (160MHz)	163	996+484T	157.50	158.00

Table 7-9. Bands 3/4 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (MRU)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3.1 MIMO Antenna-1 6dB Bandwidth Measurements



Plot 7-61. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 157)



Plot 7-62. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 151)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-63. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 155)



Plot 7-64. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 4) – Ch. 173)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-65. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 167)



Plot 7-66. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 171)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-67. 6dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 163)



Plot 7-68. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 3) – Ch. 157)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-69. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 3) – Ch. 151)



Plot 7-70. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 3) – Ch. 155)

© 2024 ELEMENT
V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-71. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 4) – Ch. 173)



Plot 7-72. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 3/4) – Ch. 167)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-73. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 3/4) – Ch. 171)



Plot 7-74. 6dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 996*2 Tones (UNII Band 3/4) – Ch. 163)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-75. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 106+26 Tones (UNII Band 3) – Ch. 157)



Plot 7-76. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 484+242 Tones (UNII Band 3) – Ch. 155)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-77. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 106+26 Tones (UNII Band 4) – Ch. 173)



Plot 7-78. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 484+242 Tones (UNII Band 3/4) – Ch. 171)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-79. 6dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 996+484T Tones (UNII Band 3/4) – Ch. 163)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.3.2 MIMO Antenna-2 6dB Bandwidth Measurements



Plot 7-80. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 157)



Plot 7-81. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 151)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-82. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 155)



Plot 7-83. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 4) – Ch. 173)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-84. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 167)



Plot 7-85. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 171)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-86. 6dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 163)



Plot 7-87. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 3) – Ch. 157)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-88. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 3) – Ch. 151)



Plot 7-89. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 3) – Ch. 155)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-90. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 4) – Ch. 173)



Plot 7-91. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 3/4) – Ch. 167)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-92. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 3/4) – Ch. 171)



Plot 7-93. 6dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 996*2 Tones (UNII Band 3/4) – Ch. 163)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-94. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 106+26 Tones (UNII Band 3) – Ch. 157)



Plot 7-95. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 484+242 Tones (UNII Band 3) – Ch. 155)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-96. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 106+26 Tones (UNII Band 4) – Ch. 173)



Plot 7-97. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 484+242 Tones (UNII Band 3/4) – Ch. 171)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-98. 6dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 996+484T Tones (UNII Band 3/4) – Ch. 163)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.4 UNII Output Power Measurement

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies.

The output power limits are specified in the tables below.

UNII Band	Frequency Range	Maximum Conducted Power Limit	Maximum e.i.r.p
		FCC	FCC
UNII 1	5.15 – 5.25GHz	23.98dBm (250mW)	N/A
UNII 2A	5.25 – 5.35GHz	The lesser of 23.98dBm (250mW) **or** 11dBm + $10\log_{10}B$	N/A
UNII 2C	5.47 – 5.725GHz		
UNII 3	5.725 – 5.850GHz	30dBm (1W)	N/A
UNII 4	5.850 – 5.895GHz	N/A	30dBm (1W)

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.3.2 Method PM-G
ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

MIMO Conducted Output Power Measurements

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 0 ANT1	0 ANT2	0 MIMO	4 ANT1	4 ANT2	4 MIMO	8 ANT1	8 ANT2	8 MIMO	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
20MHz BW	1	5180	36	26T	5.8	5.0	8.42	6.0	5.1	8.58	5.6	4.6	8.12	23.98	-15.40	2.42	11.00	30.0	-19.00
		5200	40	26T	5.70	5.20	8.47	5.98	5.04	8.55	5.59	4.46	8.07	23.98	-15.43	2.42	10.97	30.0	-19.03
		5240	48	26T	5.28	4.80	8.06	5.94	4.80	8.42	5.90	4.60	8.31	23.98	-15.56	2.42	10.84	30.0	-19.16
	2A	5260	52	26T	5.72	4.80	8.29	5.99	5.00	8.53	5.60	4.30	8.01	23.98	-15.45	2.39	10.92	30.0	-19.08
		5280	56	26T	5.86	4.67	8.32	5.98	4.80	8.44	5.70	4.20	8.02	23.98	-15.54	2.39	10.83	30.0	-19.17
		5320	64	26T	5.99	4.53	8.33	5.70	4.30	8.07	5.80	4.01	8.01	23.98	-15.65	2.39	10.72	30.0	-19.28
	2C	5500	100	26T	5.46	4.77	8.14	5.61	5.39	8.51	5.66	4.61	8.18	23.98	-15.47	2.69	11.21	30.0	-18.79
		5600	120	26T	5.80	4.90	8.38	5.40	4.70	8.07	5.79	4.20	8.08	23.98	-15.60	2.69	11.08	30.0	-18.92
		5720	144	26T	5.90	4.40	8.22	5.60	4.50	8.10	5.88	4.24	8.15	23.98	-15.76	2.69	10.92	30.0	-19.08
	3	5745	149	26T	5.99	4.44	8.29	5.49	4.45	8.01	5.90	4.14	8.12	30	-21.71	1.66	9.95	36.0	-26.05
		5785	157	26T	5.98	4.30	8.23	5.99	4.12	8.17	5.98	4.10	8.15	30	-21.77	1.66	9.89	36.0	-26.11
		5825	165	26T	5.97	4.06	8.13	5.87	4.30	8.17	5.99	4.02	8.13	30	-21.83	1.66	9.82	36.0	-26.18
	4	5845	169	26T	5.99	4.02	8.13	5.98	4.01	8.12	5.99	4.02	8.13	-	-	1.46	9.59	30.0	-20.41
		5865	173	26T	5.81	4.20	8.09	5.97	4.30	8.23	5.90	4.10	8.10	-	-	1.46	9.69	30.0	-20.31
		5885	177	26T	5.83	4.10	8.06	5.96	4.40	8.26	5.79	4.09	8.03	-	-	1.46	9.72	30.0	-20.28

Table 7-10. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (26 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 37 ANT1	37 ANT2	37 MIMO	39 ANT1	39 ANT2	39 MIMO	40 ANT1	40 ANT2	40 MIMO	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
20MHz BW	1	5180	36	52T	8.90	8.80	11.86	9.45	9.20	12.34	9.28	8.92	12.11	23.98	-11.64	2.42	14.76	30.0	-15.24
		5200	40	52T	8.91	8.87	11.90	9.17	8.76	11.98	9.25	8.86	12.07	23.98	-11.91	2.42	14.49	30.0	-15.51
		5240	48	52T	8.86	8.50	11.69	9.10	8.47	11.81	9.25	8.47	11.89	23.98	-12.09	2.42	14.31	30.0	-15.69
	2A	5260	52	52T	8.91	8.63	11.78	9.11	8.60	11.87	9.29	8.57	11.96	23.98	-12.02	2.39	14.34	30.0	-15.66
		5280	56	52T	9.10	8.50	11.82	9.30	8.40	11.88	9.49	8.31	11.95	23.98	-12.03	2.39	14.34	30.0	-15.66
		5320	64	52T	9.30	8.35	11.86	9.42	8.35	11.93	9.20	7.85	11.59	23.98	-12.05	2.39	14.32	30.0	-15.68
	2C	5500	100	52T	9.00	9.00	12.01	9.40	9.27	12.35	9.35	8.83	12.11	23.98	-11.63	2.69	15.04	30.0	-14.96
		5600	120	52T	9.38	8.79	12.11	9.45	8.86	12.18	9.30	8.48	11.92	23.98	-11.80	2.69	14.87	30.0	-15.13
		5720	144	52T	8.98	8.00	11.53	8.96	8.04	11.53	9.40	8.32	11.90	23.98	-12.08	2.69	14.60	30.0	-15.40
	3	5745	149	52T	9.40	8.32	11.90	9.44	8.49	12.00	9.38	8.12	11.81	30	-18.00	1.66	13.66	36.0	-22.34
		5785	157	52T	9.49	7.90	11.78	9.46	7.94	11.78	9.28	7.70	11.57	30	-18.22	1.66	13.44	36.0	-22.56
		5825	165	52T	9.19	7.83	11.57	9.20	7.89	11.60	9.37	7.51	11.55	30	-18.40	1.66	13.26	36.0	-22.74
	4	5845	169	52T	9.40	7.66	11.63	9.34	7.66	11.59	9.30	7.55	11.52	-	-	1.46	13.09	30.0	-16.91
		5865	173	52T	9.40	8.37	11.93	9.45	8.33	11.94	9.13	8.23	11.71	-	-	1.46	13.40	30.0	-16.60
		5885	177	52T	9.33	8.45	11.92	9.34	8.50	11.95	9.10	8.25	11.71	-	-	1.46	13.41	30.0	-16.59

Table 7-11. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (52 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 53 ANT1	53 ANT2	53 MIMO	54 ANT1	54 ANT2	54 MIMO	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
20MHz BW	1	5180	36	106T	11.80	10.10	14.04	11.61	10.60	14.14	23.98	-9.84	2.42	16.57	30.0	-13.43
		5200	40	106T	11.73	11.45	14.60	11.60	10.98	14.31	23.98	-9.38	2.42	17.03	30.0	-12.97
		5240	48	106T	11.78	11.35	14.58	11.50	10.92	14.23	23.98	-9.40	2.42	17.00	30.0	-13.00
	2A	5260	52	106T	11.79	11.45	14.63	11.55	10.94	14.27	23.98	-9.35	2.39	17.02	30.0	-12.98
		5280	56	106T	11.91	11.33	14.64	11.72	10.70	14.25	23.98	-9.34	2.39	17.03	30.0	-12.97
		5320	64	106T	11.62	10.57	14.14	11.96	10.66	14.37	23.98	-9.61	2.39	16.76	30.0	-13.24
	2C	5500	100	106T	11.88	11.52	14.71	11.62	11.00	14.33	23.98	-9.27	2.69	17.41	30.0	-12.59
		5600	120	106T	11.46	11.17	14.33	11.50	10.80	14.17	23.98	-9.65	2.69	17.02	30.0	-12.98
		5720	144	106T	11.70	10.81	14.29	11.52	10.50	14.05	23.98	-9.69	2.69	16.98	30.0	-13.02
	3	5745	149	106T	11.94	11.20	14.60	11.72	11.00	14.39	30	-15.40	1.66	16.25	36.0	-19.75
		5785	157	106T	11.60	10.30	14.01	11.93	10.44	14.26	30	-15.74	1.66	15.92	36.0	-20.08
		5825	165	106T	11.95	10.20	14.17	11.73	10.22	14.05	30	-15.83	1.66	15.83	36.0	-20.17
	4	5845	169	106T	11.99	10.33	14.25	11.83	10.27	14.13	-	-	1.46	15.71	30.0	-14.29
		5865	173	106T	11.55	10.65	14.13	11.79	11.00	14.42	-	-	1.46	15.88	30.0	-14.12
		5885	177	106T	11.99	11.04	14.55	11.80	10.89	14.38	-	-	1.46	16.01	30.0	-13.99

Table 7-12. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (106 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 61 ANT1	61 ANT2	61 MIMO	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
20MHz BW	1	5180	36	242T	11.90	11.51	14.72	23.98	-9.26	2.42	17.14	30.0	-12.86
		5200	40	242T	11.81	11.39	14.62	23.98	-9.36	2.42	17.04	30.0	-12.96
		5240	48	242T	11.81	11.27	14.56	23.98	-9.42	2.42	16.98	30.0	-13.02
	2A	5260	52	242T	11.86	11.31	14.60	23.98	-9.38	2.39	16.99	30.0	-13.01
		5280	56	242T	11.96	11.17	14.59	23.98	-9.39	2.39	16.98	30.0	-13.02
		5320	64	242T	11.68	10.48	14.13	23.98	-9.85	2.39	16.52	30.0	-13.48
	2C	5500	100	242T	11.84	11.32	14.60	23.98	-9.38	2.69	17.29	30.0	-12.71
		5600	120	242T	11.85	11.20	14.55	23.98	-9.43	2.69	17.24	30.0	-12.76
		5720	144	242T	11.48	10.52	14.04	23.98	-9.94	2.69	16.73	30.0	-13.27
	3	5745	149	242T	11.67	10.96	14.34	30	-15.66	1.66	16.00	36.0	-20.00
		5785	157	242T	11.94	10.42	14.26	30	-15.74	1.66	15.91	36.0	-20.09
		5825	165	242T	11.72	10.20	14.04	30	-15.96	1.66	15.69	36.0	-20.31
	4	5845	169	242T	11.83	10.20	14.10	-	-	1.46	15.56	30.0	-14.44
		5865	173	242T	11.52	10.90	14.23	-	-	1.46	15.69	30.0	-14.31
		5885	177	242T	11.80	10.75	14.32	-	-	1.46	15.78	30.0	-14.22

Table 7-13. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (242 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 65 ANT1	65 ANT2	65 MIMO	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
40MHz BW	1	5190	38	484T	11.80	11.70	14.76	23.98	-9.22	2.42	17.18	30.0	-12.82
		5230	46	484T	11.75	11.60	14.69	23.98	-9.29	2.42	17.11	30.0	-12.89
	2A	5270	54	484T	11.99	11.51	14.77	23.98	-9.21	2.39	17.16	30.0	-12.84
		5310	62	484T	11.58	10.60	14.13	23.98	-9.85	2.39	16.52	30.0	-13.48
	2C	5510	102	484T	11.98	11.35	14.69	23.98	-9.29	2.69	17.38	30.0	-12.62
		5590	118	484T	11.80	11.35	14.59	23.98	-9.39	2.69	17.28	30.0	-12.72
		5710	142	484T	11.60	10.80	14.23	23.98	-9.75	2.69	16.92	30.0	-13.08
	3	5755	151	484T	11.56	11.00	14.30	30	-15.70	1.66	15.96	36.0	-20.04
		5795	159	484T	11.86	10.95	14.44	30	-15.56	1.66	16.10	36.0	-19.90
	4	5835	167	484T	11.63	10.72	14.21	-	-	1.46	15.67	30.0	-14.33
		5875	175	484T	11.73	11.00	14.39	-	-	1.46	15.85	30.0	-14.15

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

80MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 67			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					ANT1	ANT2	MIMO						
	1	5210	42	996T	11.54	11.52	14.54	23.98	-9.44	2.42	16.96	30.0	-13.04
	2A	5290	58	996T	11.73	11.32	14.54	23.98	-9.44	2.39	16.93	30.0	-13.07
	2C	5530	106	996T	11.60	10.80	14.23	23.98	-9.75	2.69	16.92	30.0	-13.08
		5610	122	996T	11.72	11.37	14.56	23.98	-9.42	2.69	17.25	30.0	-12.75
		5690	138	996T	11.65	10.75	14.23	23.98	-9.75	2.69	16.93	30.0	-13.07
	3	5775	155	996T	11.55	10.60	14.11	30	-15.89	1.66	15.77	36.0	-20.23
	4	5855	171	996T	11.63	10.65	14.18	-	-	1.46	15.64	30.0	-14.36

Table 7-15. MIMO 80MHz BW (UNII) Maximum Conducted Output Power (996 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) RU Index 68			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					ANT1	ANT2	MIMO						
	1/2A	5250	50	2x996T	11.30	10.99	14.16	23.98	-9.82	2.42	16.58	30.0	-13.42
	2C	5570	114	2x996T	11.40	10.91	14.17	23.98	-9.81	2.69	16.87	30.0	-13.13
	3/4	5815	163	2x996T	11.35	10.65	14.02	-	-	1.46	15.48	30.0	-14.52

Table 7-16. MIMO 160MHz BW (UNII) Maximum Conducted Output Power (2x996 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) MRU Index 71			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					ANT1	ANT2	MIMO						
	1	5200	40	52+26T	12.10	12.17	15.15	23.98	-8.83	2.42	17.57	30.0	-12.43
	2A	5280	56	52+26T	12.27	11.90	15.10	23.98	-8.88	2.39	17.49	30.0	-12.51
	2C	5600	120	52+26T	12.10	12.00	15.06	23.98	-8.92	2.69	17.75	30.0	-12.25
	3	5785	157	52+26T	12.34	11.53	14.96	30	-15.04	1.66	16.62	36.0	-19.38
	4	5865	173	52+26T	12.30	11.40	14.88	-	-	1.46	16.34	30.0	-13.66

Table 7-17. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (52 + 26 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) MRU Index						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					82			83								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
	1	5200	40	106T	9.30	9.40	12.36	9.50	9.50	12.51	23.98	-11.47	2.42	14.93	30.0	-15.07
	2A	5280	56	106T	9.40	8.90	12.17	9.70	8.95	12.35	23.98	-11.63	2.39	14.74	30.0	-15.26
	2C	5600	120	106T	9.50	9.36	12.44	9.56	9.12	12.36	23.98	-11.54	2.69	15.13	30.0	-14.87
	3	5785	157	106T	9.56	8.70	12.16	9.40	8.43	11.95	30	-17.84	1.66	13.82	36.0	-22.18
	4	5865	173	106T	9.66	8.60	12.17	9.46	8.45	11.99	-	-	1.46	13.63	30.0	-16.37

Table 7-18. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (106 + 26 Tones)

80MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) MRU Index						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					90			91								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
	1	5210	42	484+242T	11.80	11.77	14.80	11.74	11.69	14.73	23.98	-9.18	2.42	17.22	30.0	-12.78
	2A	5290	58	484+242T	11.90	11.55	14.74	11.94	11.50	14.74	23.98	-9.24	2.39	17.13	30.0	-12.87
	2C	5530	106	484+242T	12.10	11.00	14.60	11.90	11.00	14.48	23.98	-9.38	2.69	17.29	30.0	-12.71
		5610	122	484+242T	12.20	11.50	14.87	12.10	11.46	14.80	23.98	-9.11	2.69	17.57	30.0	-12.43
		5690	138	484+242T	12.53	11.74	15.16	12.37	11.60	15.01	23.98	-8.82	2.69	17.86	30.0	-12.14
	3	5775	155	484+242T	12.30	11.40	14.88	12.30	11.30	14.84	30	-15.12	1.66	16.54	36.0	-19.46
	4	5855	171	484+242T	12.40	11.50	14.98	12.30	11.37	14.87	-	-	1.46	16.44	30.0	-13.56

Table 7-19. MIMO 80MHz BW (UNII) Maximum Conducted Output Power (484 + 242 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm) MRU Index						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					94			95								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
	1/2A	5250	50	996+484T	12.70	11.30	15.07	12.50	11.10	14.87	23.98	-8.91	2.42	17.49	30.0	-12.51
	2C	5570	114	996+484T	12.20	11.60	14.92	11.90	11.40	14.67	23.98	-9.06	2.69	17.61	30.0	-12.39
	3/4	5815	163	996+484T	12.10	11.40	14.77	11.90	11.20	14.57	-	-	1.46	16.23	30.0	-13.77

Table 7-20. MIMO 160MHz BW (UNII) Maximum Conducted Output Power (996 + 484 Tones)

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Note:

Per ANSI C63.10-2013 and KDB 662911 v02r01 Section E)1), the conducted powers at Antenna 1 and Antenna 2 were first measured separately during MIMO transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT}, the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \ldots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi}$$

Sample MIMO Calculation:

At 5180MHz in 802.11be (20MHz BW) mode, the average conducted output power was measured to be 6.00 dBm for Antenna 1 and 5.10 dBm for Antenna 2.

Antenna 1 + Antenna 2 = MIMO

(6.00 dBm + 5.10 dBm) = (3.981 mW + 3.235 mW) = 7.216 mW = 8.58 dBm

Sample e.i.r.p. Calculation:

At 5180MHz in 802.11be (20MHz BW) mode, the average MIMO conducted power was calculated to be 8.58 dBm with directional gain of 2.42 dBi.

e.i.r.p. (dBm) = Conducted Power (dBm) + Ant gain (dBi)

8.58 dBm + 2.42 dBi = 11 dBm

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.5 Maximum Power Spectral Density

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. Method SA-1, as defined in ANSI C63.10-2013, was used to measure the power spectral density.
The output power density limits are as specified in the tables below.

UNII Band	Frequency Range	Maximum Conducted Power Limit
		FCC
UNII 1	5.15 – 5.25GHz	11dBm/MHz
UNII 2A	5.25 – 5.35GHz	
UNII 2C	5.47 – 5.725GHz	
UNII 3	5.725 – 5.850GHz	30dBm/500kHz
UNII 4	5.850 – 5.895GHz	14dBm/MHz e.i.r.p

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.2.2 (Method SA-1)
ANSI C63.10-2013 – Section 14.3.2.2 Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq$ 2 x (span/RBW)
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.

Figure 7-4. Test Instrument & Measurement Setup

Test Notes

The power spectral density for each channel was measured with the RU index showing the highest conducted power.

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Summed MIMO Power Spectral Density Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5180	be (20MHz)	36	0.85	0.84	3.85	11.00	-7.15
	5200	be (20MHz)	40	0.58	0.60	3.60	11.00	-7.40
	5240	be (20MHz)	48	1.26	0.69	3.99	11.00	-7.01
	5190	be (40MHz)	38	2.39	2.33	5.37	11.00	-5.63
	5230	be (40MHz)	46	2.04	2.01	5.04	11.00	-5.96
	5210	be (80MHz)	42	1.64	2.15	4.91	11.00	-6.09
Band 1/2A	5250	be (160MHz)	50	1.68	1.34	4.53	11.00	-6.47
Band 2A	5260	be (20MHz)	52	1.73	0.53	4.18	11.00	-6.82
	5280	be (20MHz)	56	1.71	0.01	3.95	11.00	-7.05
	5320	be (20MHz)	64	1.99	0.55	4.34	11.00	-6.66
	5270	be (40MHz)	54	2.24	1.13	4.73	11.00	-6.27
	5310	be (40MHz)	62	1.21	0.45	3.86	11.00	-7.14
	5290	be (80MHz)	58	2.06	1.92	5.00	11.00	-6.00
Band 2C	5500	be (20MHz)	100	1.33	1.61	4.48	11.00	-6.52
	5600	be (20MHz)	120	3.09	1.77	5.49	11.00	-5.51
	5720	be (20MHz)	144	3.14	1.86	5.56	11.00	-5.44
	5510	be (40MHz)	102	2.17	2.22	5.21	11.00	-5.79
	5590	be (40MHz)	118	3.30	2.71	6.02	11.00	-4.98
	5710	be (40MHz)	142	4.00	3.01	6.54	11.00	-4.46
	5530	be (80MHz)	106	2.20	2.17	5.19	11.00	-5.81
	5610	be (80MHz)	122	3.31	2.34	5.86	11.00	-5.14
	5690	be (80MHz)	138	3.29	2.45	5.90	11.00	-5.10
	5570	be (160MHz)	114	2.44	1.74	5.11	11.00	-5.89

Table 7-21. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5745	be (20MHz)	149	0.09	-0.98	2.60	28.28	-25.68
	5785	be (20MHz)	157	0.52	-1.26	2.73	28.28	-25.55
	5825	be (20MHz)	165	0.57	-1.48	2.68	28.28	-25.60
	5755	be (40MHz)	151	0.82	0.09	3.48	28.28	-24.80
	5795	be (40MHz)	159	0.97	-0.59	3.27	28.28	-25.01
	5775	be (80MHz)	155	0.52	-0.20	3.19	28.28	-25.09

Table 7-22. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 3/4	5845	be (20MHz)	169	2.52	0.20	1.46	5.99	14.00	-8.01
Band 4	5865	be (20MHz)	173	2.20	0.41	1.46	5.87	14.00	-8.13
	5885	be (20MHz)	177	4.74	4.06	1.46	8.88	14.00	-5.12
Band 3/4	5835	be (40MHz)	167	3.94	1.94	1.46	7.52	14.00	-6.48
Band 4	5875	be (40MHz)	175	4.07	3.20	1.46	8.12	14.00	-5.88
Band 3/4	5855	be (80MHz)	171	3.67	2.35	1.46	7.53	14.00	-6.47
Band 4	5815	be (160MHz)	163	2.72	1.35	1.46	6.56	14.00	-7.44

Table 7-23. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5180	be (20MHz)	36	-1.22	-1.69	0.00	1.56	11.00	-9.44
	5200	be (20MHz)	40	-1.34	-1.65	0.00	1.52	11.00	-9.48
	5240	be (20MHz)	48	-0.82	-1.89	0.00	1.68	11.00	-9.32
	5190	be (40MHz)	38	-3.96	-3.95	0.11	-0.84	11.00	-11.84
	5230	be (40MHz)	46	-3.82	-4.64	0.11	-1.09	11.00	-12.09
	5210	be (80MHz)	42	-6.50	-6.44	0.12	-3.34	11.00	-14.34
Band 1/2A	5250	be (160MHz)	50	-10.20	-11.01	0.00	-7.57	11.00	-18.57
Band 2A	5260	be (20MHz)	52	-0.57	-2.00	0.00	1.78	11.00	-9.22
	5280	be (20MHz)	56	-0.37	-2.20	0.00	1.82	11.00	-9.18
	5320	be (20MHz)	64	-0.35	-2.11	0.00	1.87	11.00	-9.13
	5270	be (40MHz)	54	-3.57	-4.67	0.11	-0.97	11.00	-11.97
	5310	be (40MHz)	62	-3.53	-5.09	0.11	-1.12	11.00	-12.12
	5290	be (80MHz)	58	-5.82	-6.77	0.12	-3.14	11.00	-14.14
Band 2C	5500	be (20MHz)	100	-0.23	-1.07	0.00	2.38	11.00	-8.62
	5600	be (20MHz)	120	-0.52	-1.06	0.00	2.23	11.00	-8.77
	5720	be (20MHz)	144	-0.66	-1.05	0.00	2.16	11.00	-8.84
	5510	be (40MHz)	102	-3.40	-4.38	0.11	-0.74	11.00	-11.74
	5590	be (40MHz)	118	-3.49	-3.66	0.11	-0.45	11.00	-11.45
	5710	be (40MHz)	142	-3.11	-3.40	0.11	-0.14	11.00	-11.14
	5530	be (80MHz)	106	-6.67	-8.11	0.12	-4.20	11.00	-15.20
	5610	be (80MHz)	122	-6.31	-7.54	0.12	-3.75	11.00	-14.75
	5690	be (80MHz)	138	-6.15	-7.12	0.12	-3.47	11.00	-14.47
	5570	be (160MHz)	114	-9.89	-10.65	0.00	-7.24	11.00	-18.24

Table 7-24. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5745	be (20MHz)	149	-3.62	-3.85	-0.72	28.28	-29.00
	5785	be (20MHz)	157	-3.38	-4.19	-0.76	28.28	-29.04
	5825	be (20MHz)	165	-3.28	-4.91	-1.01	28.28	-29.29
	5755	be (40MHz)	151	-6.82	-7.20	-3.88	28.28	-32.16
	5795	be (40MHz)	159	-5.99	-6.69	-3.20	28.28	-31.48
	5775	be (80MHz)	155	-8.38	-9.40	-5.68	28.28	-33.96

© 2024 ELEMENT V 11.1 08/28/2023

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Table 7-25. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 3/4	5845	be (20MHz)	169	-0.19	-2.24	1.46	3.37	14.00	-10.63
Band 4	5865	be (20MHz)	173	-0.37	-1.72	1.46	3.48	14.00	-10.52
	5885	be (20MHz)	177	2.04	1.27	1.46	6.14	14.00	-7.86
Band 3/4	5835	be (40MHz)	167	-3.12	-4.40	1.46	0.88	14.00	-13.12
Band 4	5875	be (40MHz)	175	-2.72	-3.69	1.46	1.42	14.00	-12.58
Band 3/4	5855	be (80MHz)	171	-5.49	-7.86	1.46	-1.87	14.00	-15.87
	5815	be (160MHz)	163	-9.92	-10.94	1.46	-5.73	14.00	-19.73

Table 7-26. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	MRU Configuration	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5200	be (20MHz)	40	52+26T	4.25	3.57	6.93	11.00	-4.07
	5210	be (80MHz)	42	484+242T	-1.59	-2.89	0.82	11.00	-10.18
Band 1/2A	5250	be (160MHz)	50	996+484T	-5.50	-5.98	-2.72	11.00	-13.72
Band 2A	5280	be (20MHz)	56	52+26T	4.47	3.57	7.06	11.00	-3.94
	5290	be (80MHz)	58	484+242T	-2.57	-3.47	0.02	11.00	-10.98
Band 2C	5600	be (20MHz)	120	52+26T	5.26	5.28	8.28	11.00	-2.72
	5610	be (80MHz)	122	484+242T	-10.67	-1.76	-1.11	11.00	-12.11
	5570	be (160MHz)	114	996+484T	-4.97	-4.51	-1.72	11.00	-12.72

Table 7-27. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (MRU)

	Frequency [MHz]	802.11 MODE	Channel	MRU Configuration	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5785	be (20MHz)	157	52+26T	2.58	1.78	5.21	30.00	-24.79
	5775	be (80MHz)	155	484+242T	-13.80	-4.58	-4.09	30.00	-34.09

Table 7-28. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (MRU)

	Frequency [MHz]	802.11 MODE	Channel	MRU Configuration	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 4	5865	be (20MHz)	173	52+26T	5.59	5.88	1.46	10.21	14.00	-3.79
Band 3/4	5775	be (80MHz)	171	484+242T	-1.12	-1.36	1.46	5.23	14.00	-8.77
	5815	be (160MHz)	163	996+484T	-4.73	-4.88	1.46	2.67	14.00	-11.33

Table 7-29. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (MRU)

© 2024 ELEMENT V 11.1 08/28/2023
Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.