

**ELEMENT WASHINGTON DC LLC**

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.381.1520

<http://www.element.com>**MEASUREMENT REPORT**
FCC PART 15.407 802.11ax/be (OFDMA)**Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

03/14/2023 - 04/17/2024

Test Report Issue Date:

05/02/2024

Test Site/Location:

Element lab., Columbia, MD, USA

Test Report Serial No.:

1M2401250007-06-R1.A3L

FCC ID:**A3LNP960XMA****APPLICANT:****Samsung Electronics Co., Ltd.****Application Type:**

Certification

Model:

NP960XMA

Additional Models:

NP960XMB, NP964XMA, NP964XMB

EUT Type:

Portable Computing Device

Frequency Range:

5180 – 5885MHz

Modulation Type:

OFDMA

FCC Equipment Class:

Unlicensed National Information Infrastructure TX (NII)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

Test Procedure(s):

ANSI C63.10-2013, KDB 484596 D01 v02r03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2401250007-06-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2401250007-06.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 1 of 163

T A B L E O F C O N T E N T S

1.0	INTRODUCTION.....	4
1.1	Scope.....	4
1.2	Element Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description.....	5
2.2	Device Capabilities.....	5
2.3	Antenna Description.....	8
2.4	Test Configuration.....	8
2.5	Software and Firmware.....	8
2.6	EMI Suppression Device(s) / Modifications.....	8
3.0	DESCRIPTION OF TESTS.....	9
3.1	Evaluation Procedure.....	9
3.2	Radiated Emissions.....	9
3.3	Environmental Conditions.....	9
4.0	ANTENNA REQUIREMENTS.....	10
5.0	MEASUREMENT UNCERTAINTY.....	11
6.0	TEST EQUIPMENT CALIBRATION DATA.....	12
7.0	TEST RESULTS.....	13
7.1	Summary.....	13
7.2	26dB Bandwidth Measurement.....	15
7.2.1	MIMO Antenna-1 26dB Bandwidth Measurements.....	18
7.2.2	MIMO Antenna-2 26dB Bandwidth Measurements.....	29
7.3	6dB Bandwidth Measurement.....	40
7.3.1	MIMO Antenna-1 6dB Bandwidth Measurements.....	43
7.3.2	MIMO Antenna-2 6dB Bandwidth Measurements.....	50
7.4	UNII Output Power Measurement.....	57
7.5	Maximum Power Spectral Density.....	61
7.5.1	MIMO Antenna-1 Power Spectral Density Measurements.....	66
7.5.2	MIMO Antenna-2 Power Spectral Density Measurements.....	93
7.6	Radiated Emission Measurements.....	121
7.6.1	MIMO Radiated Spurious Emission Measurements (26 Tones).....	126
7.6.2	MIMO Radiated Spurious Emission Measurements (242 Tones).....	134
7.6.3	MIMO Radiated Band Edge Measurements (20MHz BW – Partial Tone – 106T).....	142
7.6.4	MIMO Radiated Band Edge Measurements (20MHz BW – Full Tone – 242T).....	145
7.6.5	MIMO Radiated Band Edge Measurements (40MHz BW – Full Tone – 484T).....	148
7.6.6	MIMO Radiated Band Edge Measurements (80MHz BW – Partial Tones – 484 + 242T).....	151
7.6.7	MIMO Radiated Band Edge Measurements (80MHz BW – Full Tone – 996T).....	154
7.6.8	MIMO Radiated Band Edge Measurements (160MHz BW – Partial Tones – 996 + 484T).....	157
7.6.9	MIMO Radiated Band Edge Measurements (160MHz BW – Full Tone – 2x996T).....	160
8.0	CONCLUSION.....	163

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 2 of 163

MEASUREMENT REPORT

Channel Bandwidth [MHz]	UNII Band	MIMO	
		Max. Power [mW]	Max. Power [dBm]
20	1	47.81	16.80
	2A	46.32	16.66
	2C	48.42	16.85
	3	48.33	16.84
	4	40.59	16.08
40	1	42.44	16.28
	2A	42.34	16.27
	2C	43.46	16.38
	3	43.46	16.38
	4	40.00	16.02
80	1	48.15	16.83
	2A	44.95	16.53
	2C	45.84	16.61
	3	42.69	16.30
	4	40.00	16.02
160	1/2A	45.14	16.55
	3/4	39.98	16.02

EUT Overview

Note: The UNII Band 4 max power values shown in the above table are e.i.r.p values.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 3 of 163

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 4 of 163

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Computing Device FCC ID: A3LNP960XMA**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

Test Device Serial No.: 0126X, 0150P, 1224R, 1123F

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n/ax/be WLAN, 802.11a/n/ac/ax/be UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE)

Band 1		Band 2A		Band 2C		Band 3		Band 3/4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745	169	5845
:	:	:	:	:	:	:	:	:	:
40	5200	56	5280	120	5600	157	5785	173	5865
:	:	:	:	:	:	:	:	:	:
48	5240	64	5320	144	5720	165	5825	177	5885

Table 2-1. 802.11ax/be (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3		Band 3/4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755	167	5835
:	:	:	:	:	:	:	:	:	:
46	5230	62	5310	118	5590	159	5795	175	5875
				:	:				
				142	5710				

Table 2-2. 802.11ax/be (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3		Band 3/4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775	167	5835
				:	:				
				122	5610				
				:	:				
				138	5690				

Table 2-3. 802.11ax/be (80MHz BW) Frequency / Channel Operations

Band 1/2A		Band 2C		Band 3/4	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
50	5250	114	5570	163	5815

Table 2-4. 802.11ax/be (160MHz BW) Frequency / Channel Operations

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 5 of 163

Notes:

- 5GHz NII operation is possible in 20MHz, 40MHz, 80MHz, and 160MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Band	Bandwidth	Tone Type	Tone Size	MIMO (1+2)
				Duty Cycle [%]
5GHz	20MHz	RU	26T	99.61
			52T	99.57
			106T	99.28
			242T	98.42
		MRU	52+26T	99.49
			106+26T	99.16
	40MHz	RU	26T	98.90
			52T	99.45
			106T	99.18
			242T	98.50
			484T	97.32
	80MHz	RU	26T	99.47
			52T	99.59
			106T	99.28
			242T	98.58
			484T	97.32
			996T	97.29
		MRU	484+242T	97.98
	160MHz	RU	26T	99.35
			52T	99.61
			106T	99.17
			242T	98.50
			484T	97.32
			996T	97.33
			2x996T	99.67
		MRU	996+484T	97.80

Table 2-5. Measured Duty Cycles – 11ax/be

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 6 of 163

2. The device employs MIMO technology. Below are the possible configurations.

WiFi Configurations		SDM		CDD	
		ANT1	ANT2	ANT1	ANT2
5GHz	11a	✗	✗	✓	✓
	11n	✓	✓	✓	✓
	11ac	✓	✓	✓	✓
	11ax	✓	✓	✓	✓
	11be	✓	✓	✓	✓

Table 2-6. Frequency / Channel Operations

✓ = Support; ✗ = NOT Support

SISO = Single Input Single Output

SDM = Spatial Diversity Multiplexing – MIMO function

CDD = Cyclic Delay Diversity – 2Tx Function

3. The device supports the following data rates (shown in Mbps):

MCS Index	Spatial Stream	OFDMA (802.11ax)																	
		26T			52T			106T			242T			484T			996T		
		0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI	0.8μs GI	1.6μs GI	3.2μs GI
0	1	0.9	0.8	0.8	1.8	1.7	1.5	3.8	3.5	3.2	8.6	8.1	7.3	17.2	16.3	14.6	36	34	30.6
1	1	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3
2	1	2.6	2.5	2.3	5.3	5	4.5	11.3	10.6	9.6	25.8	24.4	21.9	51.6	48.8	43.9	108.1	102.1	91.9
3	1	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5
4	1	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8
5	1	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245
6	1	7.9	7.5	6.8	15.9	15	13.5	33.8	31.9	28.7	77.4	73.1	65.8	154.9	146.3	131.6	324.3	306.3	275.6
7	1	8.8	8.3	7.5	17.6	16.7	15	37.5	35.4	31.9	86	81.3	73.1	172.1	162.5	146.3	360.3	340.3	306.3
8	1	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5
9	1	11.8	11.1	10	23.5	22.2	20	50	47.2	42.5	114.7	108.3	97.5	229.4	216.7	195	480.4	453.7	408.3
10	1	13.2	12.5	11.3	26.5	25	22.5	56.3	53.1	47.8	129	121.9	109.7	258.1	243.8	219.4	540.4	510.4	459.4
11	1	14.7	13.9	12.5	29.4	27.8	25	62.5	59	53.1	143.4	135.4	121.9	286.8	270.8	243.8	600.5	567.1	510.4
0	2	1.8	1.7	1.5	3.5	3.3	3	7.5	7.1	6.4	17.2	16.3	14.6	34.4	32.5	29.3	72.1	68.1	61.3
1	2	3.5	3.3	3	7.1	6.7	6	15	14.2	12.8	34.4	32.5	29.3	68.8	65	58.5	144.1	136.1	122.5
2	2	5.3	5	4.5	10.6	10	9	22.5	21.3	19.1	51.6	48.8	43.9	103.2	97.5	87.8	216.2	204.2	183.8
3	2	7.1	6.7	6	14.1	13.3	12	30	28.3	25.5	68.8	65	58.5	137.6	130	117	288.2	272.2	245
4	2	10.6	10	9	21.2	20	18	45	42.5	38.3	103.2	97.5	87.8	206.5	195	175.5	432.4	408.3	367.5
5	2	14.1	13.3	12	28.2	26.7	24	60	56.7	51	137.6	130	117	275.3	260	234	576.5	544.4	490
6	2	15.9	15	13.5	31.8	30	27	67.5	63.8	57.4	154.9	146.3	131.6	309.7	292.5	263.3	648.5	612.5	551.3
7	2	17.6	16.7	15	35.3	33.3	30	75	70.8	63.8	172.1	162.5	146.3	344.1	325	292.5	720.6	680.6	612.5
8	2	21.2	20	18	42.4	40	36	90	85	76.5	206.5	195	175.5	412.9	390	351	864.7	816.7	735
9	2	23.5	22.2	20	47.1	44.4	40	100	94.4	85	229.4	216.7	195	458.8	433.3	390	960.8	907.4	816.7
10	2	26.5	25	22.5	52.9	50	45	112.5	106.3	95.6	258.1	243.8	219.4	516.2	487.5	438.8	1080.9	1020.8	918.8
11	2	29.4	27.8	25	58.8	55.6	50	125	118.1	106.3	286.8	270.8	243.8	573.5	541.7	487.5	1201	1134.3	1020.8

Table 2-7. Supported Data Rates

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 7 of 163

4. This device supports simultaneous transmission operation, which allows for two SISO channels to operate independent of one another in the 2.4GHz (WLAN & BT) and 5GHz bands simultaneously on each antenna. The following tables show the worst case configurations determined during testing. The data for these configurations is contained in this test report. The BT + 5GHz case is not considered as worst case since the BT power is lower than the 2.4GHz WLAN power.

Configuration 1: MIMO transmitting in 2.4GHz mode and MIMO in 5GHz mode

Description	2.4 GHz Emission	5 GHz Emission
Antenna	1, 2	1, 2
Channel	6	100
Operating Frequency (MHz)	2437	5500
Data Rate (Mbps)	1Mbps	6Mbps
Mode	802.11b	802.11a

Table 2-8. Config-1 (MIMO 2.4GHz & MIMO 5GHz)

Configuration 2: MIMO transmitting in 2.4GHz mode and MIMO in 6GHz mode

Description	2.4 GHz Emission	6 GHz Emission
Antenna	1, 2	1, 2
Channel	6	22
Operating Frequency (MHz)	2437	5935
Data Rate (Mbps)	1Mbps	6Mbps
Mode	802.11b	802.11a

Table 2-9. Config-2 (MIMO 2.4GHz & MIMO 6GHz)

2.3 Antenna Description

This device is only used with its integral antennas as shown in the documentation of this filing. The antenna gains for this device are as shown in the table below:

Frequency [GHz]	Antenna 1 Gain [dBi]	Antenna 2 Gain [dBi]	Directional Ant. Gain [dBi]
5.20	-3.44	-3.51	-0.46
5.30	-3.38	-3.16	-0.26
5.60	-3.56	-3.04	-0.29
5.80	-3.64	-3.14	-0.38
5.90	-4.16	-3.37	-0.75

Table 2-10. Antenna Peak Gain

2.4 Test Configuration

ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See 5GHz UNII OFDM report for AC line conducted emissions test setups, 7.6 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

2.5 Software and Firmware

The test was conducted with software version Windows 11 and firmware version REV0.1 installed on the EUT.

2.6 EMI Suppression Device(s) / Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 8 of 163

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 9 of 163

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 10 of 163

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 11 of 163

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
N/A	WL25-1	Conducted Cable Set (25GHz)	11/15/2023	Annual	11/15/2024	WL25-1
N/A	WL25-2	Conducted Cable Set (25GHz)	11/15/2023	Annual	11/15/2024	WL25-2
N/A	WL40-1	Conducted Cable Set (40GHz)	11/15/2023	Annual	11/15/2024	WL40-1
N/A	ETS-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	ETS-001
N/A	ETS-002	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	ETS-002
N/A	AP1-002	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP1-002
N/A	AP2-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP2-001
N/A	AP2-001	EMC Cable and Switch Systems	11/15/2023	Annual	11/15/2024	AP2-001
Anritsu	MA2411B	Pulse Power Sensor	11/8/2023	Annual	11/8/2024	1027293
Anritsu	MA2411B	Pulse Power Sensor	6/14/2023	Annual	6/14/2024	1911105
Com-Power	AL-130	9kHz-30MHz Loop Antenna	4/13/2022	Biennial	4/13/2025	121034
Keysight Technologies	N9038A	MXE EMI Reciever	8/30/2023	Annual	8/30/2024	MY51210133
Keysight Technologies	N9038A	PXA Signal Analyzer	2/29/2023	Annual	3/1/2025	MY55410501
Keysight Technologies	N6020A	MXA Signal Analyzer	3/22/2024	Annual	3/22/2025	US46470561
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	11/15/2023	Annual	11/15/2024	NMLC-2
Rohde & Schwarz	ESU26	EMI Test Reciever (26.5GHz)	9/25/2023	Annual	9/25/2023	100342
Rohde & Schwarz	ESU40	EMI Test Reciever (40GHz)	9/11/2023	Annual	9/11/2024	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	2/15/2024	Annual	2/15/2025	103200
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	3/15/2023	Annual	3/15/2025	102136
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	3/15/2023	Annual	3/15/2025	102132
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	1/11/2024	Annual	1/11/2025	102151
Sunol Sciences	DRH-118	Horn (Small)	2/21/2024	Biennial	2/21/2026	A050307
Sunol Sciences	JB5	Bi-Log Antenna (30M-5GHz)	8/30/2022	Biennial	8/30/2024	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 12 of 163

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
FCC ID: A3LNP960XMA
FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
N/A	26dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
15.407(e)	6dB Bandwidth	>500kHz (5725-5850MHz and 5850 – 5895MHz)		PASS	Section 7.3
15.407 (a)(1)(iv), (a)(2), (a)(3)	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.4
15.407 (a)(1)(iv), (a)(2), (a)(3)	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.5
15.407(h)	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b)(1), (b)(2), (b)(3), (b)(4)	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])	RADIATED	PASS	Section 7.6
15.205, 15.407(b)(1), (b)(4), (b)(5), (b)(6)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.6, 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “EMC Software Tool,” Version 1.2.1.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.6.4.
- 6) 802.11ax/be OFDMA testing was performed for all signal tone configurations as specified by the 802.11ax standard. Worst case results are determined and reported per the guidance provided at the October 2018 TCB Workshop.
- 7) Only one RU index could be selected at a time, so no contiguous or non-contiguous RUs were considered for testing.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 13 of 163

- 8) Data was leveraged from model NP960XMA for the certification of NP960XMB. See Table 7-2 for spot-check results.

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: NP960XMA	Variant Model: NP960XMB	Deviation	Max Deviation	Pass/Fail
2.1046, 15.407(a)(8)	Conducted Output Power	20MHz, Ch.40, 802.11a, MIMO	dBm	N/A	16.51	16.20	0.31	3	PASS
15.209, 15.407(b)(1), 15.407(b)(2), 15.407(b)(3), 15.407(b)(4)	Radiated Spurious Emissions	20MHz, Ch.40, 802.11a, MIMO	dBm	53.98	39.13	41.68	2.55	3	PASS
15.209	Radiated Band Edge Emissions	20MHz, Ch.36, 802.11ac, MIMO	dBm	53.98	46.39	47.56	1.17	3	PASS

Table 7-2. Summary of Spot-checks


5GHz WIFI (20MHz 802.11a MIMO)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Directional Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]								
			ANT1	ANT2	MIMO						
UNII-1	5200	40	13.27	13.11	16.20	23.98	-7.78	-0.46	15.74	30.00	-14.26

Table 7-3. Conducted Output Power Measurements (Spot-check)


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dBm]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	1	40	5200	*	15600.00	Average	H	-	-	-93.20	27.88	0.00	41.68	53.98	-12.30
					*	15600.00	Peak	H	-	-	-72.33	27.88	0.00	62.55	73.98	-11.43

Table 7-4. Radiated Measurements MIMO (Spot-check)

Worst Case Mode: 802.11ac
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5180MHz
Channel: 36



Plot 7-1. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1)



Plot 7-2. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1)

- 9) Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.
- 10) All test cases were performed to verify the variant EUT is still in compliance with the spot checked results to the reference device and was performed using the guidance of ANSI C63.10-2013.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 14 of 163

7.2 26dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

ANSI C63.10-2013 – Section 12.4

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

The 26dB Bandwidth measurement for each channel was measured with the RU index showing the highest conducted power.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 15 of 163

MIMO 26dB Bandwidth Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 1	5180	be (20MHz)	36	18.40	18.26
	5200	be (20MHz)	40	20.25	19.91
	5240	be (20MHz)	48	18.84	18.23
	5190	be (40MHz)	38	23.66	23.85
	5230	be (40MHz)	46	23.67	23.22
	5210	be (80MHz)	42	34.05	34.11
Band 1/2A	5250	be (160MHz)	50	42.67	32.65
Band 2A	5260	be (20MHz)	52	18.51	18.28
	5280	be (20MHz)	56	20.00	20.01
	5320	be (20MHz)	64	20.08	20.19
	5270	be (40MHz)	54	23.55	23.54
	5310	be (40MHz)	62	22.54	22.88
	5290	be (80MHz)	58	35.41	32.68
Band 2C	5500	be (20MHz)	100	18.37	18.39
	5600	be (20MHz)	120	19.96	20.07
	5720	be (20MHz)	144	18.65	18.32
	5510	be (40MHz)	102	24.17	23.44
	5590	be (40MHz)	118	23.68	23.20
	5710	be (40MHz)	142	23.85	23.45
	5530	be (80MHz)	106	35.04	34.07
	5610	be (80MHz)	122	36.29	34.25
	5690	be (80MHz)	138	34.82	33.69
	5570	be (160MHz)	114	43.50	35.77

Table 7-5. Bands 1, 2A, 2C Conducted 26dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 16 of 163

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 26dB Bandwidth [MHz]	Antenna-2 26dB Bandwidth [MHz]
Band 1	5180	be (20MHz)	36	25.46	21.82
	5200	be (20MHz)	40	25.79	21.61
	5240	be (20MHz)	48	21.54	21.60
	5190	be (40MHz)	38	42.72	43.23
	5230	be (40MHz)	46	42.59	42.90
	5210	be (80MHz)	42	87.01	85.92
Band 1/2A	5250	be (160MHz)	50	178.20	175.70
Band 2A	5260	be (20MHz)	52	21.41	21.65
	5280	be (20MHz)	56	21.52	21.89
	5320	be (20MHz)	64	21.99	21.73
	5270	be (40MHz)	54	42.14	42.48
	5310	be (40MHz)	62	42.41	42.47
	5290	be (80MHz)	58	87.36	85.44
Band 2C	5500	be (20MHz)	100	21.75	21.81
	5600	be (20MHz)	120	21.59	21.61
	5720	be (20MHz)	144	21.73	21.64
	5510	be (40MHz)	102	43.66	42.76
	5590	be (40MHz)	118	43.16	42.75
	5710	be (40MHz)	142	43.08	42.07
	5530	be (80MHz)	106	87.31	91.88
	5610	be (80MHz)	122	91.50	85.86
	5690	be (80MHz)	138	87.25	85.82
	5570	be (160MHz)	114	176.26	174.72


Table 7-6. Bands 1, 2A, 2C Conducted 26dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 17 of 163

7.2.1 MIMO Antenna-1 26dB Bandwidth Measurements




Plot 7-3. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 40)




Plot 7-4. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 18 of 163




Plot 7-5. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 42)




Plot 7-6. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 19 of 163




Plot 7-7. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 56)




Plot 7-8. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 20 of 163




Plot 7-9. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 58)




Plot 7-10. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 120)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 21 of 163




Plot 7-11. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 118)




Plot 7-12. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 122)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 22 of 163




Plot 7-13. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 114)




Plot 7-14. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 1) – Ch. 40)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 23 of 163




Plot 7-15. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 1) – Ch. 38)




Plot 7-16. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 1) – Ch. 42)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 24 of 163




Plot 7-17. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 2x996 Tones (UNII Band 1/2A) – Ch. 50)




Plot 7-18. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 2A) – Ch. 56)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 25 of 163




Plot 7-19. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 2A) – Ch. 54)




Plot 7-20. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 2A) – Ch. 58)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 26 of 163




Plot 7-21. 26dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 2C) – Ch. 120)




Plot 7-22. 26dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 2C) – Ch. 118)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 27 of 163




Plot 7-23. 26dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 2C) – Ch. 122)




Plot 7-24. 26dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 2x996 Tones (UNII Band 2C) – Ch. 114)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 28 of 163

7.2.2 MIMO Antenna-2 26dB Bandwidth Measurements




Plot 7-25. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 40)




Plot 7-26. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 29 of 163




Plot 7-27. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 42)




Plot 7-28. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 30 of 163




Plot 7-29. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 56)




Plot 7-30. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 31 of 163




Plot 7-31. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 58)




Plot 7-32. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 120)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 32 of 163




Plot 7-33. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 118)




Plot 7-34. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 122)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 33 of 163




Plot 7-35. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 114)




Plot 7-36. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 1) – Ch. 40)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 34 of 163




Plot 7-37. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 1) – Ch. 38)




Plot 7-38. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 1) – Ch. 42)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 35 of 163




Plot 7-39. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 2x996 Tones (UNII Band 1/2A) – Ch. 50)




Plot 7-40. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 2A) – Ch. 56)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 36 of 163




Plot 7-41. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 2A) – Ch. 54)




Plot 7-42. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 2A) – Ch. 58)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 37 of 163




Plot 7-43. 26dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 2C) – Ch. 120)




Plot 7-44. 26dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 2C) – Ch. 118)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 38 of 163



Plot 7-45. 26dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 2C) – Ch. 122)



Plot 7-46. 26dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 2x996 Tones (UNII Band 2C) – Ch. 114)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 39 of 163

7.3 6dB Bandwidth Measurement

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 6dB bandwidth.

In the 5.725 – 5.850GHz and 5.850-5.895GHz bands, the 6dB bandwidth must be ≥ 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 6.9.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes

The 6dB Bandwidth measurement for each channel was measured with the RU index showing the highest conducted power.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 40 of 163

MIMO 6dB Bandwidth Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3	5745	be (20MHz)	149	2.67	2.73
	5785	be (20MHz)	157	2.69	2.69
	5825	be (20MHz)	165	2.13	2.13
	5755	be (40MHz)	151	2.23	2.27
	5795	be (40MHz)	159	2.22	2.20
	5775	be (80MHz)	155	2.32	2.29

Table 7-7. Band 3 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3/4	5845	be (20MHz)	169	2.70	2.71
Band 4	5865	be (20MHz)	173	2.11	2.15
	5885	be (20MHz)	177	2.71	2.72
Band 3/4	5835	be (40MHz)	167	2.22	2.27
Band 4	5875	be (40MHz)	175	2.21	2.24
Band 3/4	5855	be (80MHz)	171	2.28	2.30
	5815	be (160MHz)	163	2.68	2.69

Table 7-8. Bands 3/4 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3	5745	be (20MHz)	149	19.06	18.99
	5785	be (20MHz)	157	19.01	18.99
	5825	be (20MHz)	165	18.99	18.91
	5755	be (40MHz)	151	38.18	37.04
	5795	be (40MHz)	159	36.80	35.80
	5775	be (80MHz)	155	78.05	75.44

Table 7-9. Band 3 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)


FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 41 of 163

	Frequency [MHz]	802.11 MODE	Channel	Antenna-1 6dB Bandwidth [MHz]	Antenna-2 6dB Bandwidth [MHz]
Band 3/4	5845	be (20MHz)	169	19.00	18.89
Band 4	5865	be (20MHz)	173	18.82	18.95
	5885	be (20MHz)	177	18.95	18.96
Band 3/4	5835	be (40MHz)	167	37.94	37.09
Band 4	5875	be (40MHz)	175	38.01	37.67
Band 3/4	5855	be (80MHz)	171	75.41	75.38
	5815	be (160MHz)	163	157.49	157.90


Table 7-10. Bands 3/4 Conducted 6dB Bandwidth Measurements MIMO ANT1/2 (Full Tones)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 42 of 163

7.3.1 MIMO Antenna-1 6dB Bandwidth Measurements




Plot 7-47. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be - 26 Tones (UNII Band 3) - Ch. 157)




Plot 7-48. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be - 26 Tones (UNII Band 3) - Ch. 151)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 43 of 163




Plot 7-49. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 155)




Plot 7-50. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 4) – Ch. 173)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 44 of 163




Plot 7-51. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 167)




Plot 7-52. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 171)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 45 of 163




Plot 7-53. 6dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 163)




Plot 7-54. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 3) – Ch. 157)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 46 of 163




Plot 7-55. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 3) – Ch. 151)




Plot 7-56. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 3) – Ch. 155)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 47 of 163



Plot 7-57. 6dB Bandwidth Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 4) – Ch. 173)




Plot 7-58. 6dB Bandwidth Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 3/4) – Ch. 167)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 48 of 163




Plot 7-59. 6dB Bandwidth Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 3/4) – Ch. 171)




Plot 7-60. 6dB Bandwidth Plot MIMO ANT1 (160MHz BW 802.11be – 996*2 Tones (UNII Band 3/4) – Ch. 163)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 49 of 163

7.3.2 MIMO Antenna-2 6dB Bandwidth Measurements



Plot 7-61. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 157)




Plot 7-62. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 151)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 50 of 163



Plot 7-63. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 155)




Plot 7-64. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 26 Tones (UNII Band 4) – Ch. 173)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 51 of 163




Plot 7-65. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 167)




Plot 7-66. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 171)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 52 of 163




Plot 7-67. 6dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 163)




Plot 7-68. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 3) – Ch. 157)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 53 of 163




Plot 7-69. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 3) – Ch. 151)




Plot 7-70. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 3) – Ch. 155)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 54 of 163




Plot 7-71. 6dB Bandwidth Plot MIMO ANT2 (20MHz BW 802.11be – 242 Tones (UNII Band 4) – Ch. 173)




Plot 7-72. 6dB Bandwidth Plot MIMO ANT2 (40MHz BW 802.11be – 484 Tones (UNII Band 3/4) – Ch. 167)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 55 of 163



Plot 7-73. 6dB Bandwidth Plot MIMO ANT2 (80MHz BW 802.11be – 996 Tones (UNII Band 3/4) – Ch. 171)



Plot 7-74. 6dB Bandwidth Plot MIMO ANT2 (160MHz BW 802.11be – 996*2 Tones (UNII Band 3/4) – Ch. 163)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 56 of 163

7.4 UNII Output Power Measurement

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies.

The output power limits are specified in the tables below.

UNII Band	Frequency Range	Maximum Conducted Power Limit		Maximum e.i.r.p	
		FCC	ISED	FCC	ISED
UNII 1	5.15 – 5.25GHz	23.98dBm (250mW)	N/A	N/A	The lesser of 23.01dBm (200mW) or 10dBm + 10log ₁₀ B
UNII 2A	5.25 – 5.35GHz	The lesser of 23.98dBm (250mW) or 11dBm + 10log ₁₀ B		N/A	The lesser of 30dBm (1W) or 17dBm + 10log ₁₀ B
UNII 2C	5.47 – 5.725GHz				
UNII 3	5.725 – 5.850GHz	30dBm (1W)		N/A	N/A
UNII 4	5.850 – 5.895GHz	N/A		30dBm (1W)	30dBm (1W)

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.3.2 Method PM-G

ANSI C63.10-2013 – Section 14.2 Measure-and-Sum Technique

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 57 of 163

MIMO Conducted Output Power Measurements

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)												Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index																	
					0						8											
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
20MHz BW	1	5180	36	26T	10.22	10.40	13.32	10.2	10.4	13.33	10.2	10.4	13.32	23.98	-10.65	-0.46	12.86	30.0	-17.14			
		5200	40	26T	10.24	10.39	13.33	10.22	10.37	13.31	10.23	10.36	13.31	23.98	-10.65	-0.46	12.86	30.0	-17.14			
		5240	48	26T	10.11	10.41	13.27	10.10	10.43	13.28	10.12	10.45	13.30	23.98	-10.72	-0.46	12.83	30.0	-17.17			
		5260	52	26T	9.96	10.42	13.21	9.95	10.44	13.21	9.94	10.43	13.20	23.98	-10.67	-0.26	12.95	30.0	-17.05			
	2A	5280	56	26T	10.42	10.44	13.44	10.46	10.43	13.46	10.42	10.41	13.43	23.98	-10.52	-0.26	13.20	30.0	-16.80			
		5320	64	26T	10.54	10.32	13.44	10.51	10.33	13.43	10.52	10.27	13.41	23.98	-10.54	-0.26	13.18	30.0	-16.82			
		5500	100	26T	10.91	9.83	13.41	10.95	9.81	13.43	10.97	9.84	13.45	23.98	-10.53	-0.29	13.17	30.0	-16.83			
		5600	120	26T	10.40	9.98	13.21	10.42	9.99	13.22	10.45	9.99	13.24	23.98	-10.74	-0.29	12.95	30.0	-17.05			
	2C	5720	144	26T	10.97	10.24	13.63	10.98	10.22	13.63	10.99	10.23	13.64	23.98	-10.54	-0.29	13.35	30.0	-16.65			
		5745	149	26T	10.93	10.36	13.66	10.92	10.33	13.65	10.99	10.33	13.68	30	-16.32	-0.38	13.31	36.0	-22.69			
		5785	157	26T	10.68	10.49	13.60	10.73	10.49	13.62	10.66	10.10	13.40	30	-16.38	-0.38	13.25	36.0	-22.75			
		5825	165	26T	10.80	10.77	13.80	10.83	10.75	13.82	10.88	10.77	13.84	30	-16.16	-0.38	13.46	36.0	-22.54			
4	5845	169	26T	10.21	10.51	13.37	10.22	10.51	13.36	10.20	10.49	13.36	-	-	-0.75	12.63	30.0	-17.37				
	5865	173	26T	9.94	10.44	13.21	9.93	10.40	13.18	9.93	10.45	13.21	-	-	-0.75	12.46	30.0	-17.54				
	5885	177	26T	9.83	10.94	13.43	9.83	10.94	13.43	9.81	10.92	13.41	-	-	-0.75	12.68	30.0	-17.52				

Table 7-11. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (26 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)												Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index																	
					37						40											
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
20MHz BW	1	5180	36	52T	13.17	13.63	16.42	13.14	13.63	16.41	13.14	13.63	16.40	23.98	-7.56	-0.46	15.95	30.0	-14.05			
		5200	40	52T	13.20	13.65	16.44	13.18	13.63	16.42	13.21	13.65	16.45	23.98	-7.53	-0.46	15.98	30.0	-14.02			
		5240	48	52T	13.28	13.81	16.56	13.28	13.80	16.56	13.18	13.85	16.54	23.98	-7.42	-0.46	16.10	30.0	-13.90			
		5260	52	52T	13.11	13.81	16.48	13.11	13.83	16.50	13.14	13.84	16.51	23.98	-7.47	-0.26	16.14	30.0	-13.74			
	2A	5280	56	52T	13.29	13.69	16.50	13.29	13.70	16.51	13.28	13.68	16.49	23.98	-7.47	-0.26	16.25	30.0	-13.76			
		5320	64	52T	13.34	13.66	16.51	13.33	13.61	16.48	13.34	13.61	16.49	23.98	-7.47	-0.26	16.25	30.0	-13.75			
		5500	100	52T	13.79	13.84	16.83	13.84	13.85	13.83	13.84	13.83	16.84	23.98	-7.13	-0.29	16.56	30.0	-13.44			
		5600	120	52T	13.34	13.58	16.47	13.33	13.59	16.47	13.34	13.59	16.48	23.98	-7.50	-0.29	16.19	30.0	-13.81			
	2C	5720	144	52T	13.53	13.45	16.50	13.58	13.46	16.53	13.53	13.40	16.48	23.98	-7.45	-0.29	16.24	30.0	-13.76			
		5745	149	52T	13.67	13.72	16.71	13.67	13.74	16.72	13.68	13.70	16.70	30	-13.28	-0.38	16.34	36.0	-19.66			
		5785	157	52T	13.47	13.82	16.66	13.57	13.84	16.72	13.55	13.82	16.70	30	-13.28	-0.38	16.34	36.0	-19.66			
		5825	165	52T	13.08	13.56	16.34	13.00	13.58	16.31	12.98	13.58	16.30	30	-13.66	-0.38	15.96	36.0	-20.04			
3	5845	169	52T	12.95	13.67	16.34	12.94	13.70	16.35	12.95	13.69	16.35	-	-	-0.75	15.60	30.0	-14.40				
	5865	173	52T	12.73	13.52	16.15	12.72	13.53	16.15	12.74	13.52	16.16	-	-	-0.75	15.41	30.0	-14.59				
	5885	177	52T	12.74	13.94	16.39	12.74	13.95	16.40	12.72	13.94	16.38	-	-	-0.75	15.65	30.0	-14.35				

Table 7-12. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (52 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index														
					53			54											
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO									
	1	5180	36	106T	13.51	13.35	16.44	13.49	13.49	12.44	16.01	23.98	-7.54	-0.46	15.98	30.0	-14.02		
		5200	40	106T	13.24	13.20	16.28	13.84	12.82	16.37	23.98	-7.61	-0.46	15.91	30.0	-14.09			
		5240	48	106T	12.96	13.31	16.15	13.46	12.98	16.24	23.98	-7.74	-0.46	15.77	30.0	-14.23			
		5260	52	106T	12.68	13.36	16.04	13.17	13.03	16.11	23.98	-7.87	-0.26	15.85	30.0	-14.15			
	2A	5280	56	106T	13.25	13.43	16.35	13.79	13.04	16.44	23.98	-7.54	-0.26	16.18	30.0	-13.82			
		5320	64	106T	13.08	13.19	16.15	13.48	12.95	16.23	23.98	-7.75	-0.26	15.97	30.0	-14.03			
		5500	100	106T	13.45	13.09	16.28	13.42	13.18	16.31	23.98	-7.67	-0.29	16.03	30.0	-13.97			
	2C	5600	120	106T	13.58	12.59	16.12	13.45	12.78	16.14	23.98	-7.84	-0.29	15.85	30.0	-14.15			
		5720	144	106T	13.54	13.98	16.78	13.63	12.25	16.00	23.98	-7.20	-0.29	16.49	30.0	-13.51			
		5745	149	106T	13.97	12.16	16.17	13.76	12.44	16.16	30	-13.83	-0.38	15.79	36.0	-20.21			
	3	5785	157	106T	13.83	12.81	16.36	13.64	13.08	16.38	30	-13.62	-0.38	16.00	36.0	-20.00			
		5825	165	106T	13.58	13.22	16.41	13.45	13.54	16.51	30	-13.49	-0.38	16.13	36.0	-19.87			
		5845	169	106T	13.59	13.32	16.47	13.36	13.74	16.56	-	-	-	15.82	30.0	-14.18			
	4	5865	173	106T	13.57	13.32	16.46	13.46	13.79	16.64	-	-	-	15.89	30.0	-14.11			
		5885	177	106T	13.57	13.86	16.73	12.93	13.75	16.37	-	-	-	15.98	30.0	-14.02			

Table 7-13. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (106 Tones)

	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index								
					61								
					ANT1	ANT2	MIMO						
20MHz BW	1	5180	36	242T	13.16	13.25	16.22	23.98	-7.76	-0.46	15.75	30.0	-14.25
		5200	40	242T	13.14	13.34	16.26	23.98	-7.72	-0.46	15.80	30.0	-14.20
		5240	48	242T	13.48	14.07	16.80	23.98	-7.18	-0.46	16.33	30.0	-13.67
		5260	52	242T	13.18	14.07	16.66	23.98	-7.32	-0.26	16.40	30.0	-13.60
	2A	5280	56	242T	13.27	13.88	16.60	23.98	-7.38	-0.26	16.34	30.0	-13.66
		5320	64	242T	13.13	13.76	16.47	23.98	-7.51	-0.26	16.21	30.0	-13.79
		5500	100	242T	13.15	13.35	16.26	23.98	-7.72	-0.29	15.98	30.0	-14.02
		5600	120	242T	13.03	13.33	16.19	23.98	-7.79	-0.29	15.91	30.0	-14.09
	2C	5720	144	242T	14.07	13.09	16.62	23.98	-7.36	-0.33	16.33	30.0	-13.67
		5745	149	242T	14.19	13.24	16.80	30	-13.20	-0.38	16.42	36.0	-19.58
		5785	157	242T	14.10	13.48	16.81	30	-13.19	-0.38	16.44	36.0	-19.56
		5825	165	242T	13.95	13.71	16.84	30	-13.16	-0.38	16.47	36.0	-19.53
	3	5845	169	242T	13.88	13.74	16.82	-	-	-0.75	16.08	30.0	-13.92
		5865	173	242T	13.81	13.83	16.83	-	-	-0.75	16.08	30.0	-13.92
		5885	177	242T	13.13	13.90	16.54	-	-	-0.75	15.80	30.0	-14.20
		5885	177	242T	13.13	13.90	16.54	-	-	-0.75	15.80	30.0	-14.20

80MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index								
					67								
					ANT1	ANT2	MIMO						
	1	5210	42	996T	13.34	13.42	16.39	23.98	-7.59	-0.46	15.93	30.0	-14.07
	2A	5290	58	996T	13.08	13.55	16.33	23.98	-7.65	-0.26	16.07	30.0	-13.93
5530		106	996T	13.16	13.50	16.34	23.98	-7.64	-0.29	16.06	30.0	-13.94	
	2C	5610	122	996T	13.12	13.07	16.11	23.98	-7.87	-0.29	15.82	30.0	-14.18
		5690	138	996T	13.93	12.96	16.48	23.98	-7.50	-0.29	16.20	30.0	-13.80
	3	5775	155	996T	13.92	12.01	16.08	30	-13.92	-0.38	15.70	36.0	-20.30
	4	5855	171	996T	13.85	13.32	16.60	-	-	-0.75	15.86	30.0	-14.14

Table 7-16. MIMO 80MHz BW (UNII) Maximum Conducted Output Power (996 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)			Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					RU Index								
					68								
					ANT1	ANT2	MIMO						
1/2A	5250	50	2x996T	12.86	13.51	16.21	23.98	-7.77	-0.46	15.74	30.0	-14.26	
2C	5570	114	2x996T	13.14	13.36	16.26	23.98	-7.72	-0.29	15.98	30.0	-14.02	
3/4	5815	163	2x996T	13.82	13.30	16.58	-	-	-0.75	15.83	30.0	-14.17	

Table 7-17. MIMO 160MHz BW (UNII) Maximum Conducted Output Power (2x996 Tones)

MRU Index	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dB]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index														
					70			71			72								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
20	1	5200	40	52+26T	12.96	13.64	16.32	13.11	13.78	16.47	13.60	13.42	16.52	23.98	-7.46	-0.46	16.06	30.0	-13.94
	2A	5200	56	52+26T	12.60	13.69	16.19	12.60	13.81	16.26	13.17	13.52	16.36	23.98	-7.62	-0.26	16.10	30.0	-13.90
	2C	5600	120	52+26T	13.09	13.31	16.21	13.34	13.87	16.62	12.89	13.67	16.31	23.98	-7.36	-0.29	16.34	30.0	-13.66
	3	5785	157	52+26T	13.95	12.58	16.33	13.87	12.57	16.28	13.58	13.12	16.37	30	-13.63	-0.38	15.99	36.0	-20.01
4	3	5865	173	52+26T	13.82	13.17	16.32	13.89	13.71	16.81	13.20	13.25	16.24	-	-	-0.75	16.07	30.0	-13.93

Table 7-18. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (52 + 26 Tones)

20MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)						Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index											
					82			83								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
1	5200	40	106+26T	13.28	13.91	16.62	13.29	13.30	16.31	23.98	-7.36	-0.46	16.15	30.0	-13.85	
2A	5280	56	106+26T	12.48	13.69	16.14	12.88	13.43	16.17	23.98	-7.81	-0.26	15.91	30.0	-14.09	
3C	5600	120	106+26T	13.33	13.78	16.57	12.76	13.54	16.18	23.98	-7.41	-0.29	16.29	30.0	-13.71	
3	5785	157	106+26T	13.75	12.42	16.15	13.72	13.04	16.40	30	-13.60	-0.38	16.03	36.0	-19.97	
4	5865	173	106+26T	13.76	12.89	16.36	13.64	13.47	16.57	-	-	-0.75	15.82	30.0	-14.18	

Table 7-19. MIMO 20MHz BW (UNII) Maximum Conducted Output Power (106 + 26 Tones)

MRU Index	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index														
					90			92			93								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
1	5210	42	484+242T	13.68	13.70	16.70	13.77	13.86	16.83	13.77	13.80	16.80	23.98	-7.15	-0.46	16.36	30.0	-13.64	
2A	5290	58	484+242T	13.22	13.55	16.40	13.38	13.65	16.53	13.40	13.63	16.53	23.98	-7.45	-0.26	16.27	30.0	-13.73	
3	5380	106	484+242T	13.56	13.30	16.44	13.73	13.43	16.59	13.70	13.45	16.59	23.98	-7.39	-0.29	16.31	30.0	-13.69	
	5610	122	484+242T	13.46	13.74	16.61	13.44	13.74	16.60	13.43	13.65	16.55	23.98	-7.37	-0.29	16.33	30.0	-13.67	
	5690	138	484+242T	13.71	12.75	16.27	13.73	12.80	16.30	13.72	12.84	16.31	23.98	-7.67	-0.29	16.03	30.0	-13.97	
	5715	155	484+242T	13.67	12.42	16.10	13.89	12.53	16.27	13.92	12.56	16.30	30	-13.70	-0.38	15.93	36.0	-20.07	
4	5855	171	484+242T	13.67	12.95	16.34	13.75	12.98	16.39	13.72	13.00	16.39	-	-	-0.75	15.65	30.0	-14.35	

Table 7-20. MIMO 80MHz BW (UNII) Maximum Conducted Output Power (484 + 242 Tones)

160MHz BW	Band	Freq [MHz]	Channel	Tones	Average Conducted Power (dBm)									Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Dir. Ant. Gain [dBi]	Max e.i.r.p [dBm]	e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
					MRU Index														
					94			95			1095								
					ANT1	ANT2	MIMO	ANT1	ANT2	MIMO	ANT1	ANT2	MIMO						
1/2A	5250	50	996+484T	12.86	13.68	16.30	12.94	13.77	16.39	13.16	13.88	16.55	23.98	-7.43	-0.46	16.08	30.0	-13.92	
2C	5570	114	996+484T	13.26	13.62	16.45	13.37	13.71	16.55	13.30	13.66	16.49	23.98	-7.43	-0.29	16.27	30.0	-13.73	
3/4	5815	163	996+484T	13.92	13.58	16.76	13.63	13.08	16.87	13.67	13.03	16.87	-	-	-0.75	16.02	30.0	-13.98	

Table 7-21. MIMO 160MHz BW (UNII) Maximum Conducted Output Power (996 + 484 Tones)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 59 of 163

Note:

Per ANSI C63.10-2013 and KDB 662911 v02r01 Section E1), the conducted powers at Antenna 1 and Antenna 2 were first measured separately during MIMO transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10-2013 Section 14.4.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi}$$

Sample MIMO Calculation:

At 5180MHz in 802.11be (20MHz BW 242T) mode, the average conducted output power was measured to be 13.16 dBm for Antenna 1 and 13.25 dBm for Antenna 2.

Antenna 1 + Antenna 2 = MIMO

$$(13.16 \text{ dBm} + 13.25 \text{ dBm}) = (20.70 \text{ mW} + 21.13 \text{ mW}) = 41.83 \text{ mW} = 16.22 \text{ dBm}$$

Sample e.i.r.p. Calculation:

At 5180MHz in 802.11be (20MHz BW 242T) mode, the average MIMO conducted power was calculated to be 16.22 dBm with directional gain of -0.46 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$16.22 \text{ dBm} + -0.46 \text{ dBi} = 15.75 \text{ dBm}$$

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 60 of 163

7.5 Maximum Power Spectral Density

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013, and at the appropriate frequencies. Method SA-1, as defined in ANSI C63.10-2013, was used to measure the power spectral density.

The output power density limits are as specified in the tables below.

UNII Band	Frequency Range	Maximum Power Spectral Density	
		FCC	ISED
UNII 1	5.15 – 5.25GHz	11dBm/MHz	10dBm/MHz e.i.r.p
UNII 2A	5.25 – 5.35GHz	11dBm/MHz	
UNII 2C	5.47 – 5.725GHz		
UNII 3	5.725 – 5.850GHz	30dBm/500kHz	
UNII 4	5.850 – 5.895GHz	14dBm/MHz e.i.r.p	

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.2.2 (Method SA-1)

ANSI C63.10-2013 – Section 14.3.2.2 Measure-and-Sum Technique

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span}/\text{RBW})$
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

The power spectral density for each channel was measured with the RU index showing the highest conducted power.

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 61 of 163

Summed MIMO Power Spectral Density Measurements

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5180	be (20MHz)	36	4.89	4.84	0.00	7.87	11.00	-3.13
	5200	be (20MHz)	40	5.59	5.69	0.00	8.65	11.00	-2.35
	5240	be (20MHz)	48	5.37	5.96	0.00	8.69	11.00	-2.31
	5190	be (40MHz)	38	6.08	4.98	0.00	8.58	11.00	-2.42
	5230	be (40MHz)	46	6.45	5.62	0.00	9.06	11.00	-1.94
	5210	be (80MHz)	42	6.35	6.42	0.00	9.40	11.00	-1.60
Band 1/2A	5250	be (160MHz)	50	3.84	4.76	0.00	7.34	11.00	-3.66
Band 2A	5260	be (20MHz)	52	5.07	5.83	0.00	8.48	11.00	-2.52
	5280	be (20MHz)	56	5.69	6.60	0.00	9.18	11.00	-1.82
	5320	be (20MHz)	64	6.42	6.44	0.00	9.44	11.00	-1.56
	5270	be (40MHz)	54	6.32	7.25	0.00	9.82	11.00	-1.18
	5310	be (40MHz)	62	6.44	7.17	0.00	9.83	11.00	-1.17
	5290	be (80MHz)	58	6.11	7.07	0.00	9.63	11.00	-1.37
Band 2C	5500	be (20MHz)	100	5.19	5.88	0.00	8.56	11.00	-2.44
	5600	be (20MHz)	120	6.60	6.20	0.00	9.41	11.00	-1.59
	5720	be (20MHz)	144	4.57	5.27	0.00	7.95	11.00	-3.05
	5510	be (40MHz)	102	6.26	7.35	0.00	9.85	11.00	-1.15
	5590	be (40MHz)	118	6.04	7.43	0.00	9.80	11.00	-1.20
	5710	be (40MHz)	142	6.06	6.58	0.00	9.34	11.00	-1.66
	5530	be (80MHz)	106	6.05	6.66	0.00	9.37	11.00	-1.63
	5610	be (80MHz)	122	5.81	7.00	0.00	9.46	11.00	-1.54
	5690	be (80MHz)	138	4.83	5.45	0.00	8.16	11.00	-2.84
	5570	be (160MHz)	114	4.66	5.82	0.00	8.29	11.00	-2.71

Table 7-22. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5745	be (20MHz)	149	3.24	3.70	0.00	6.48	30.00	-23.52
	5785	be (20MHz)	157	2.98	2.97	0.00	5.99	30.00	-24.01
	5825	be (20MHz)	165	3.77	4.44	0.00	7.13	30.00	-22.87
	5755	be (40MHz)	151	4.00	4.72	0.00	7.39	30.00	-22.61
	5795	be (40MHz)	159	4.10	4.36	0.00	7.24	30.00	-22.76
	5775	be (80MHz)	155	4.22	5.05	0.00	7.66	30.00	-22.34

Table 7-23. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device		Page 62 of 163

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
and 3/4	5845	be (20MHz)	169	4.50	5.11	0.00	-0.38	7.44	14.00	-6.56
Band 4	5865	be (20MHz)	173	4.82	5.04	0.00	-0.75	7.19	14.00	-6.81
	5885	be (20MHz)	177	4.56	5.17	0.00	-0.75	7.14	14.00	-6.86
and 3/4	5835	be (40MHz)	167	4.85	5.23	0.00	-0.38	7.67	14.00	-6.33
Band 4	5875	be (40MHz)	175	5.06	5.08	0.00	-0.75	7.33	14.00	-6.67
Band 3/4	5855	be (80MHz)	171	4.94	5.13	0.00	-0.38	7.67	14.00	-6.33
	5815	be (160MHz)	163	4.37	4.86	0.00	-0.37	7.26	14.00	-6.74

Table 7-24. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (26 Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5180	be (20MHz)	36	3.64	3.92	0.00	6.79	11.00	-4.21
	5200	be (20MHz)	40	3.91	4.02	0.00	6.97	11.00	-4.03
	5240	be (20MHz)	48	3.90	4.20	0.00	7.06	11.00	-3.94
	5190	be (40MHz)	38	-2.96	-2.83	0.00	0.11	11.00	-10.89
	5230	be (40MHz)	46	-2.94	-2.72	0.00	0.18	11.00	-10.82
	5210	be (80MHz)	42	-0.58	-0.58	0.00	2.43	11.00	-8.57
Band 2A	5250	be (160MHz)	50	-10.07	-9.82	0.00	-6.93	11.00	-17.93
Band 2A	5260	be (20MHz)	52	3.93	4.17	0.00	7.06	11.00	-3.94
	5280	be (20MHz)	56	4.31	4.44	0.00	7.38	11.00	-3.62
	5320	be (20MHz)	64	4.21	4.46	0.00	7.35	11.00	-3.65
	5270	be (40MHz)	54	-2.96	-2.55	0.00	0.26	11.00	-10.74
	5310	be (40MHz)	62	-2.97	-2.46	0.00	0.30	11.00	-10.70
	5290	be (80MHz)	58	-0.89	-0.83	0.00	2.15	11.00	-8.85
Band 2C	5500	be (20MHz)	100	4.53	4.28	0.00	7.42	11.00	-3.58
	5600	be (20MHz)	120	3.76	3.92	0.00	6.85	11.00	-4.15
	5720	be (20MHz)	144	4.40	4.47	0.00	7.44	11.00	-3.56
	5510	be (40MHz)	102	-2.89	-2.34	0.00	0.41	11.00	-10.59
	5590	be (40MHz)	118	-2.88	-2.66	0.00	0.24	11.00	-10.76
	5710	be (40MHz)	142	-2.33	-2.15	0.00	0.77	11.00	-10.23
	5530	be (80MHz)	106	-1.31	-1.22	0.00	1.74	11.00	-9.26
	5610	be (80MHz)	122	-1.44	-1.04	0.00	1.78	11.00	-9.22
	5690	be (80MHz)	138	-1.69	-1.69	0.00	1.32	11.00	-9.68
	5570	be (160MHz)	114	-9.63	-9.20	0.00	-6.40	11.00	-17.40

Table 7-25. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm/500kHz]	Margin [dB]
Band 3	5745	be (20MHz)	149	1.89	1.79	0.00	4.85	30.00	-25.15
	5785	be (20MHz)	157	1.41	1.47	0.00	4.45	30.00	-25.55
	5825	be (20MHz)	165	1.78	2.26	0.00	5.04	30.00	-24.96
	5755	be (40MHz)	151	-4.82	-4.69	0.00	-1.74	30.00	-31.74
	5795	be (40MHz)	159	-5.21	-4.41	0.00	-1.78	30.00	-31.78
	5775	be (80MHz)	155	-3.27	-3.26	0.00	-0.26	30.00	-30.26

Table 7-26. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT						Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device				Page 63 of 163	

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 3/4	5845	be (20MHz)	169	4.52	5.55	0.00	-0.38	7.70	14.00	-6.30
Band 4	5865	be (20MHz)	173	4.58	4.86	0.00	-0.38	7.35	14.00	-6.65
	5885	be (20MHz)	177	4.15	5.40	0.00	-0.38	7.45	14.00	-6.55
Band 3/4	5835	be (40MHz)	167	-2.38	-1.88	0.00	-0.38	0.51	14.00	-13.49
Band 4	5875	be (40MHz)	175	-3.56	-2.49	0.00	-0.38	-0.36	14.00	-14.36
Band 3/4	5855	be (80MHz)	171	-0.78	-0.07	0.00	-0.38	2.22	14.00	-11.78
	5815	be (160MHz)	163	-9.20	-9.55	0.00	-0.38	-6.74	14.00	-20.74

Table 7-27. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (Full Tones)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5200	be (20MHz)	40	4.36	4.83	0.00	7.61	11.00	-3.39
Band 2A	5280	be (20MHz)	56	4.88	4.95	0.00	7.92	11.00	-3.08
Band 2C	5600	be (20MHz)	120	4.41	5.19	0.00	7.83	11.00	-3.17
Band 3	5785	be (20MHz)	157	2.40	2.75	0.00	5.59	30.00	-24.41

Table 7-28. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (52+26T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 4	5865	be (20MHz)	173	5.18	4.63	0.00	-0.75	7.17	14.00	-6.83

Table 7-29. Band 4 MIMO Conducted Power Spectral Density Measurements MIMO (52+26T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5200	be (20MHz)	40	2.59	2.63	0.00	5.62	11.00	-5.38
Band 2A	5280	be (20MHz)	56	2.26	2.63	0.00	5.46	11.00	-5.54
Band 2C	5600	be (20MHz)	120	2.43	2.72	0.00	5.59	11.00	-5.41

Table 7-30. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (26+106T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5785	be (20MHz)	157	0.23	0.52	0.00	3.39	30.00	-26.61

Table 7-31. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (26+106T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	Antenna Gain [dBi]	DCCF [dB]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 4	5865	be (20MHz)	173	3.47	3.62	-0.75	0.00	5.81	14.00	-8.19

Table 7-32. Bands 4 MIMO Conducted Power Spectral Density Measurements MIMO (26+106T)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT							Approved by: Technical Manager		
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024		EUT Type: Portable Computing Device					Page 64 of 163		

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1	5210	be (80MHz)	42	-2.27	-2.45	0.00	0.66	11.00	-10.34
Band 2A	5290	be (80MHz)	58	-3.00	-2.61	0.00	0.21	11.00	-10.79
Band 2C	5530	be (80MHz)	106	-2.60	-3.14	0.00	0.15	11.00	-10.85
	5610	be (80MHz)	122	-3.17	-2.99	0.00	-0.07	11.00	-11.07
	5690	be (80MHz)	138	-2.24	-2.50	0.00	0.64	11.00	-10.36

Table 7-33. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (242+484T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 3	5775	be (80MHz)	155	-4.89	-4.90	0.00	-1.88	30.00	-31.88

Table 7-34. Band 3 MIMO Conducted Power Spectral Density Measurements MIMO (242+484T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 3/4	5855	be (80MHz)	171	-2.62	-1.92	0.00	-0.38	0.37	14.00	-13.63

Table 7-35. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (242+484T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	MIMO Summed PSD [dBm]	Max Conducted PSD [dBm]	Margin [dB]
Band 1/2A	5250	be (160MHz)	50	-7.41	-7.28	0.00	-4.33	11.00	-15.33
Band 2C	5570	be (160MHz)	114	-7.09	-7.06	0.00	-4.07	11.00	-15.07


Table 7-36. Bands 1, 2A, 2C MIMO Conducted Power Spectral Density Measurements MIMO (484+996T)

	Frequency [MHz]	802.11 MODE	Channel	Antenna 1 PSD [dBm]	Antenna 2 PSD [dBm]	DCCF [dB]	Antenna Gain [dBi]	MIMO Summed EIRP PSD [dBm]	Max EIRP PSD [dBm]	Margin [dB]
Band 3/4	5815	be (160MHz)	163	-6.91	-6.25	0.00	-0.38	-3.94	14.00	-17.94


Table 7-37. Bands 3/4 MIMO Conducted Power Spectral Density Measurements MIMO (484+996T)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT			Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device		Page 65 of 163

7.5.1 MIMO Antenna-1 Power Spectral Density Measurements




Plot 7-75. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 40)




Plot 7-76. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 66 of 163




Plot 7-77. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 1) – Ch. 42)




Plot 7-78. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 67 of 163




Plot 7-79. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 56)




Plot 7-80. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 68 of 163




Plot 7-81. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2A) – Ch. 58)




Plot 7-82. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 120)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 69 of 163




Plot 7-83. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 118)




Plot 7-84. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 122)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 70 of 163




Plot 7-85. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 2C) – Ch. 114)




Plot 7-86. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 157)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 71 of 163




Plot 7-87. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 151)




Plot 7-88. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3) – Ch. 155)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 72 of 163




Plot 7-89. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 26 Tones (UNII Band 4) – Ch. 173)




Plot 7-90. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 167)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 73 of 163




Plot 7-91. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 171)




Plot 7-92. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be – 26 Tones (UNII Band 3/4) – Ch. 163)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 74 of 163




Plot 7-93. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 1) – Ch. 40)




Plot 7-94. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 1) – Ch. 38)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 75 of 163




Plot 7-95. Power Spectral Density Plot MIMO ANT1 (80MHz BW 802.11be – 996 Tones (UNII Band 1) – Ch. 42)




Plot 7-96. Power Spectral Density Plot MIMO ANT1 (160MHz BW 802.11be – 2x996 Tones (UNII Band 1/2A) – Ch. 50)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1-A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 76 of 163



Plot 7-97. Power Spectral Density Plot MIMO ANT1 (20MHz BW 802.11be – 242 Tones (UNII Band 2A) – Ch. 56)



Plot 7-98. Power Spectral Density Plot MIMO ANT1 (40MHz BW 802.11be – 484 Tones (UNII Band 2A) – Ch. 54)

FCC ID: A3LNP960XMA	MEASUREMENT REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401250007-06-R1.A3L	Test Dates: 03/14/2023 - 04/17/2024	EUT Type: Portable Computing Device	Page 77 of 163