

4.2 Input Power Measurement

Input power and current were measured using a Power Analyzer.

A 700ml water load was placed in the center of the oven and the oven set to maximum power. A 700 ml water load was chosen for its compatibility.

Manufacturers to determine their input ratings commonly use this procedure.



Fig. 2 Test Setup for Input power

The results of this test are as follows.

Input Voltage [Vac]	Input Current [amps]	Measured Input power [watts]	EUT Spec. Input power [watts]
120	13.86	1603	1650

Based on the measured input power, the EUT was found to be operating within the intended specifications.

4.3 RF Output Power Measurement

The Caloric Method was used to determine maximum output power. The initial temperature of a 1000-ml water load was measured. The water load was placed in the center of the oven. The oven was operated at maximum output power for 120 seconds. Then the temperature of the water re-measured.



Fig.3 Test Setup for RF output power

Quantity of water [ml]	Starting Temperature [centigrade]	Final Temperature [centigrade]	Elapsed Time [seconds]	RF Power [watts]
1000	10	20.1	120	987.0
1000	10	20.1	120	984.0
1000	10	20	120	969.0
Average RF Power of 3 Trials				980.0

$$\text{Power [W]} = \frac{(4.187) * L_w * (T_f - T_i) + 0.55 * B_i * (T_f - T_r)}{t}$$

Magnetron type: OM-75P

L_w : Mass of the water, in grams

B_i : Mass of the container, in grams

T_f : Final temperature of the water, in °C

T_i : Initial temperature of the water, in °C

T_r : Ambient temperature, in °C

t : Heating time in seconds, excluding the magnetron filament heat-up time.

The measured output was found to be **ABOVE 500Watts**. Therefore, in accordance with section 18.305 of Subpart C, the measured out-of-band emissions were compared to the $25 \times \text{SQRT}(\text{power}/500)$ [uV/m] @ 300M limit.