

### 3.5 EUT Description

The following features describe EUT represented by this report:

| Item                                               | Specification                                                                                                                                                             | Remarks |
|----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>Power Rating</b>                                | 110 ~ 127 VAC, 6.4A, 50/60 Hz                                                                                                                                             | -       |
| <b>Power Consumption</b>                           | Average :520W<br>Power Save mode : Less than 20 W                                                                                                                         | -       |
| <b>Display</b>                                     | 16 characters x 2 lines                                                                                                                                                   | -       |
| <b>Toner cartridge life</b>                        | 4,000 or 8,000 pages at ISO 19752 5% coverage                                                                                                                             | -       |
| <b>Package weight</b>                              | 3.5 kg                                                                                                                                                                    | -       |
| <b>Memory</b>                                      | 96 MB (max. 320 MB)                                                                                                                                                       | -       |
| <b>External dimension</b>                          | 466 x 435,4 x 458 mm (W x D x H)                                                                                                                                          | -       |
| <b>Weight</b>                                      | 18,5 Kg (including consumables)                                                                                                                                           | -       |
| <b>Printing method</b>                             | Laser Beam Printing                                                                                                                                                       | -       |
| <b>Printing speed</b>                              | Up to 28 ppm in A4 (30 ppm in Letter)                                                                                                                                     | -       |
| <b>Duplex printing speed<br/>(SCX-5530FN ONLY)</b> | Up to 19 ipm in A4 (21 ipm in Letter)                                                                                                                                     | -       |
| <b>Print resolution</b>                            | Up to 1,200 x 1,200 dpi effective output                                                                                                                                  | -       |
| <b>Interface</b>                                   | High Speed USB 2.0<br>Ethernet 10/100 Base TX(Embedded type)                                                                                                              | -       |
| <b>Scanning method</b>                             | ADF and Flat-bed Color CCD (Charge Coupled Device)                                                                                                                        | -       |
| <b>Scan Resolution</b>                             | Optical: 600 x 1,200 dpi (mono and color)<br>Enhanced: 4,800 x 4,800 dpi                                                                                                  | -       |
| <b>Copy speed</b>                                  | Up to 28 ppm in A4 (30 ppm in Letter)                                                                                                                                     | -       |
| <b>Copy resolution</b>                             | Scan: up to 600 x 300 (text, text/photo)<br>up to 600 x 600 (photo using platen)<br>up to 600 x 300 (photo using ADF)<br>Print: up to 600 x 600 (text, text/photo, photo) | -       |
| <b>Modem speed</b>                                 | 33,6 Kbps                                                                                                                                                                 | -       |
| <b>Fax Resolution</b>                              | Standard:203 x 98 dpi<br>Fine: 203 x 196 dpi<br>Super Fine: 300 x 300 dpi<br>Photo: 203 x 196 dpi<br>Color: 200 x 200 dpi                                                 | -       |
| <b>Fax Memory</b>                                  | 6 MB                                                                                                                                                                      | -       |
| <b>Fax Data coding</b>                             | MH/MR/MMR/JPEG/ECM (Error Correction Mode)                                                                                                                                | -       |