



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. +1.410.290.6652 / Fax +1.410.290.6654

<http://www.pctestlab.com>



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

07/11/16 - 08/16/16

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

OY1607081234.A3L

FCC ID:

A3LSC01J

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SC-01J

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)	10 gm Phablet (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.18	0.33	0.57	N/A
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	< 0.1	0.14	0.22	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.20	0.34	0.61	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	0.14	0.29	0.48	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A			
PCE	LTE Band 13	779.5 - 784.5 MHz	0.17	0.42	0.64	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.19	0.33	0.61	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.13	0.24	0.91	N/A
PCE	LTE Band 41	2498.5 - 2687.5 MHz	0.10	0.26	0.97	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.88	0.12	0.44	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A			
NII	U-NII-2A	5260 - 5320 MHz	0.16	0.22	N/A	0.78
NII	U-NII-2C	5500 - 5720 MHz	0.14	0.51	N/A	1.69
NII	U-NII-3	5745 - 5825 MHz	0.29	0.51	0.51	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A			
Simultaneous SAR per KDB 690783 D01v01r03:			1.51	1.41	1.59	2.63

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 1 of 70	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS	14
6	TEST CONFIGURATION POSITIONS	15
7	RF EXPOSURE LIMITS	18
8	FCC MEASUREMENT PROCEDURES.....	19
9	RF CONDUCTED POWERS	24
10	SYSTEM VERIFICATION.....	40
11	SAR DATA SUMMARY	44
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	55
13	SAR MEASUREMENT VARIABILITY	63
14	ADDITIONAL TUNER TESTING PER FCC GUIDANCE	64
15	EQUIPMENT LIST	65
16	MEASUREMENT UNCERTAINTIES.....	67
17	CONCLUSION.....	68
18	REFERENCES	69
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 2 of 70

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz
MST	Data	1 - 8.3 kHz

1.2 Power Reduction for SAR

This device utilizes a single step power reduction mechanism for SAR compliance under portable hotspot conditions for some wireless modes and bands. All hotspot SAR evaluations for this device were performed at the maximum allowed output power when hotspot is enabled. Detailed descriptions of the power reduction mechanism are included in the operational description.

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

The reduced powers for the power reduction mechanisms were confirmed via conducted power measurements at the RF port (See Section 9)

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 3 of 70

1.3.1 Maximum PCE Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	33.5	33.5	30.0	27.5	27.0	27.0	26.0	24.0	23.0
	Nominal	33.0	33.0	29.5	27.0	26.5	26.5	25.5	23.5	22.5
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	28.0	27.5	25.5	26.5	25.5	23.5	22.5
	Nominal	30.0	30.0	27.5	27.0	25.0	26.0	25.0	23.0	22.0

Mode / Band		Modulated Average (dBm)		
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA
UMTS Band 5 (850 MHz)	Maximum	24.0	23.5	23.5
	Nominal	23.5	23.0	23.0
Mode / Band		Modulated Average (dBm)		
LTE Band 12	Maximum	24.0		
	Nominal	23.5		
LTE Band 17	Maximum	24.0		
	Nominal	23.5		
LTE Band 13	Maximum	24.0		
	Nominal	23.5		
LTE Band 5 (Cell)	Maximum	24.0		
	Nominal	23.5		
LTE Band 4 (AWS)	Maximum	23.0		
	Nominal	22.5		
LTE Band 41	Maximum	25.0		
	Nominal	24.5		

1.3.2 Reduced PCE Power – Hotspot Mode Activated

Mode / Band		Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GPRS/EDGE 1900	Maximum	27.0	26.0	23.5	22.5	26.5	25.5	23.5	22.5
	Nominal	26.5	25.5	23.0	22.0	26.0	25.0	23.0	22.0

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234 A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 4 of 70

1.3.3 Maximum WLAN/BT Power

Mode / Band		Modulated Average - Single Tx Chain (dBm)	
IEEE 802.11b (2.4 GHz)	Maximum	20.5	
	Nominal	20.0	
IEEE 802.11g (2.4 GHz)		Ch 1, 11	Ch 2-10
	Maximum	17.5	18.0
	Nominal	17.0	17.5
IEEE 802.11n (2.4 GHz)	Maximum	17.5	
	Nominal	17.0	
Bluetooth	Maximum	12.0	
	Nominal	11.5	
Bluetooth LE	Maximum	8.5	
	Nominal	8.0	

Mode / Band		Modulated Average - Single Tx Chain (dBm)									
		20 MHz Bandwidth			40 MHz Bandwidth			80 MHz Bandwidth			
		Ch 36	Ch 40 - 165								
IEEE 802.11a (5 GHz)	Maximum	13.5	15.5								
	Nominal	13.0	15.0								
		Ch 36, 100	Ch 64	Ch 40-60, 104-165	Ch 38, 102	Ch 62	Ch 46, 54, 110-159				
IEEE 802.11n (5 GHz)	Maximum	13.5	14.5	15.5	11.5	12.5	14.5	Ch 42	Ch 58	Ch 106	Ch 122, 138, 155
	Nominal	13.0	14.0	15.0	11.0	12.0	14.0				
IEEE 802.11ac (5 GHz)	Maximum	13.5	14.5	15.5	11.5	12.5	14.5	7.5	10.5	9.5	11.5
	Nominal	13.0	14.0	15.0	11.0	12.0	14.0	7.0	10.0	9.0	11.0
Mode / Band		Modulated Average - MIMO (dBm)									
		20 MHz Bandwidth			40 MHz Bandwidth			80 MHz Bandwidth			
IEEE 802.11g (2.4 GHz)	Maximum	20.5									
	Nominal	20.0									
IEEE 802.11n (2.4 GHz)	Maximum	20.5									
	Nominal	20.0									
IEEE 802.11a (5 GHz)		Ch 36	Ch 40 - 165								
	Maximum	16.5	18.5								
	Nominal	16.0	18.0								
		Ch 36, 100	Ch 64	Ch 40-60, 104-165	Ch 38, 102	Ch 62	Ch 46, 54, 110-159				
IEEE 802.11n (5 GHz)	Maximum	16.5	17.5	18.5	14.5	15.5	17.5	Ch 42	Ch 58	Ch 106	Ch 122, 138, 155
	Nominal	16.0	17.0	18.0	14.0	15.0	17.0				
IEEE 802.11ac (5 GHz)	Maximum	16.5	17.5	18.5	14.5	15.5	17.5	10.5	13.5	12.5	14.5
	Nominal	16.0	17.0	18.0	14.0	15.0	17.0	10.0	13.0	12.0	14.0

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 5 of 70

1.3.4 Reduced WLAN/BT Power –Held to Ear

		Mode / Band		Modulated Average - Single Tx Chain (dBm)				
		IEEE 802.11b (2.4 GHz)	Maximum	15.5				
			Nominal	15.0				
		IEEE 802.11g (2.4 GHz)	Maximum	15.5				
			Nominal	15.0				
		IEEE 802.11n (2.4 GHz)	Maximum	15.5				
Nominal	15.0							
Mode / Band		Modulated Average - Single Tx Chain (dBm)						
		20 MHz Bandwidth	40 MHz Bandwidth		80 MHz Bandwidth			
IEEE 802.11a (5 GHz)	Maximum	9.5						
	Nominal	9.0						
IEEE 802.11n (5 GHz)	Maximum	9.5	8.5	Ch 42	Ch 58-155			
	Nominal	9.0	8.0					
IEEE 802.11ac (5 GHz)	Maximum	9.5	8.5	7.5	8.5			
	Nominal	9.0	8.0	7.0	8.0			
Mode / Band		Modulated Average - MIMO (dBm)						
		20 MHz Bandwidth	40 MHz Bandwidth	80 MHz Bandwidth				
IEEE 802.11g (2.4 GHz)	Maximum	18.5						
	Nominal	18.0						
IEEE 802.11n (2.4 GHz)	Maximum	18.5						
	Nominal	18.0						
IEEE 802.11a (5 GHz)	Maximum	12.5						
	Nominal	12.0						
IEEE 802.11n (5 GHz)	Maximum	12.5				11.5	Ch 42	Ch 58-155
	Nominal	12.0				11.0		
IEEE 802.11ac (5 GHz)	Maximum	12.5	11.5	10.5	11.5			
	Nominal	12.0	11.0	10.0	11.0			

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 6 of 70

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a “phablet.”

Table 1-1
Device Edges/Sides for SAR Testing

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	Yes	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 41	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-1, U-NII-2A, U-NII-2C operations are disabled. Therefore, U-NII-1, U-NII-2A, U-NII-2C operations are not considered in this section.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 7 of 70

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet
1	GSM voice + 2.4 GHz WI-FI	Yes	Yes	N/A	Yes
2	GSM voice + 5 GHz WI-FI	Yes	Yes	N/A	Yes
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes
4	GSM voice + 2.4 GHz WI-FI MIMO	Yes	Yes	N/A	Yes
5	GSM voice + 5 GHz WI-FI MIMO	Yes	Yes	N/A	Yes
6	GSM voice + 2.4 GHz WI-FI + 5 GHz WI-FI	Yes	Yes	N/A	Yes
7	UMTS + 2.4 GHz WI-FI	Yes	Yes	Yes	Yes
8	UMTS + 5 GHz WI-FI	Yes	Yes	Yes	Yes
9	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes
10	UMTS + 2.4 GHz WI-FI MIMO	Yes	Yes	Yes	Yes
11	UMTS + 5 GHz WI-FI MIMO	Yes	Yes	Yes	Yes
12	UMTS + 2.4 GHz WI-FI + 5 GHz WI-FI	Yes	Yes	Yes	Yes
13	LTE + 2.4 GHz WI-FI	Yes	Yes	Yes	Yes
14	LTE + 5 GHz WI-FI	Yes	Yes	Yes	Yes
15	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	Yes
16	LTE + 2.4 GHz WI-FI MIMO	Yes	Yes	Yes	Yes
17	LTE + 5 GHz WI-FI MIMO	Yes	Yes	Yes	Yes
18	LTE + 2.4 GHz WI-FI + 5 GHz WI-FI	Yes	Yes	Yes	Yes
19	GPRS/EDGE + 2.4 GHz WI-FI	N/A	N/A	Yes	Yes
20	GPRS/EDGE + 5 GHz WI-FI	N/A	N/A	Yes	Yes
21	GPRS/EDGE + 2.4 GHz Bluetooth	N/A	N/A	N/A	Yes
22	GPRS/EDGE + 2.4 GHz WI-FI MIMO	N/A	N/A	Yes	Yes
23	GPRS/EDGE + 5 GHz WI-FI MIMO	N/A	N/A	Yes	Yes
24	GPRS/EDGE + 2.4 GHz WI-FI + 5 GHz WI-FI	N/A	N/A	Yes	Yes

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. 2.4GHz WLAN, 5GHz WLAN, and 2.4GHz BT cannot all transmit simultaneously.
3. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
4. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
5. 5 GHz Wireless Router is only supported for the U-NII-3 by S/W, therefore U-NII-1, U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
6. This device supports 2x2 MIMO Tx for WLAN 802.11n/ac. Each WLAN antenna can transmit independently or together when operating with MIMO.
7. This device supports VOLTE and VOWIFI.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
Page 8 of 70		

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-1, U-NII-2A & U-NII-2C WIFI, only 2.4 GHz and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

Per FCC KDB 447498 D01v06, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(16/15) * \sqrt{2.480}] = 1.7 < 3.0$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Per FCC KDB 447498 D01v06, the 10g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 7.5$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, phablet Bluetooth SAR was not required; $[(16/5) * \sqrt{2.480}] = 5.0 < 7.5$. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-1, U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for 2.4 GHz and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 9 of 70

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

This device supports both LTE B12 and LTE B17. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B12.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluated for licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number	Phablet Serial Number
GSM/GPRS/EDGE 850	852D0	852F1	852F1	-
GSM/GPRS/EDGE 1900	252D4	852F1	852F1	-
UMTS 850	852D4	852F1	852F1	-
LTE Band 12	C9186	C9186	C9186	-
LTE Band 13	252D4	853E5	853E5	-
LTE Band 5 (Cell)	852D4	852F1	852F1	-
LTE Band 4 (AWS)	252D4	252D4	252D4	-
LTE Band 41	852BF	852D0	852D0	-
2.4 GHz WLAN	852D9	252D4	252D4	-
5 GHz WLAN	852D9	853E5	853E5	853E5

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 10 of 70

2

LTE INFORMATION

LTE Information					
FCC ID	A3LSC01J				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
Channel Bandwidths	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
Channel Numbers and Frequencies (MHz)	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	Low	Low-Mid	Mid	Mid-High	High
	LTE Band 12: 1.4 MHz	699.7 (23017)	707.5 (23095)	715.3 (23173)	
	LTE Band 12: 3 MHz	700.5 (23025)	707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)	707.5 (23095)	713.5 (23155)		
LTE Band 12: 10 MHz	704 (23060)	707.5 (23095)	711 (23130)		
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)		
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)		
LTE Band 13: 5 MHz	779.5 (23205)	782 (23230)	784.5 (23255)		
LTE Band 13: 10 MHz	N/A	782 (23230)	N/A		
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)		
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)		
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)		
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)		
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)		
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)		
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)		
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)		
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)		
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)		
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	6				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Release 10 Additional Information	This device does not support full CA features on 3GPP Release 10. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 10 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, MDH, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 11 of 70	

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 12 of 70

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 13 of 70

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 14 of 70

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 15 of 70



Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 16 of 70

metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6.8 Phablet Configurations

For smart phones with a display diagonal dimension $> 150 \text{ mm}$ or an overall diagonal dimension $> 160 \text{ mm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna $\leq 25 \text{ mm}$ from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR $> 1.2 \text{ W/kg}$.

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 17 of 70

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 18 of 70

8 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 19 of 70

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”. The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

8.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 20 of 70

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 21 of 70

achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.6.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 22 of 70

8.6.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.6.6). When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.6.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 23 of 70

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

Table 9-1
Maximum Conducted Powers

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.67	32.65	28.90	27.03	26.41	26.37	25.43	23.55	22.99
	190	32.72	32.74	28.63	27.06	26.20	26.29	25.33	23.60	22.97
	251	32.66	32.75	28.65	26.95	26.22	26.24	25.25	23.44	23.00
GSM 1900	512	29.10	29.12	26.43	25.64	24.10	25.43	24.36	22.55	21.38
	661	29.31	29.24	26.45	25.87	24.07	25.62	24.45	22.68	21.45
	810	29.42	29.41	26.84	25.99	24.25	25.65	24.63	22.84	21.66
Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.64	23.62	22.88	22.77	23.40	17.34	19.41	19.29	19.98
	190	23.69	23.71	22.61	22.80	23.19	17.26	19.31	19.34	19.96
	251	23.63	23.72	22.63	22.69	23.21	17.21	19.23	19.18	19.99
GSM 1900	512	20.07	20.09	20.41	21.38	21.09	16.40	18.34	18.29	18.37
	661	20.28	20.21	20.43	21.61	21.06	16.59	18.43	18.42	18.44
	810	20.39	20.38	20.82	21.73	21.24	16.62	18.61	18.58	18.65
GSM 850	Frame	23.97	23.97	23.48	22.74	23.49	17.47	19.48	19.24	19.49
GSM 1900	Avg.Targets:	20.97	20.97	21.48	22.74	21.99	16.97	18.98	18.74	18.99

Table 9-2
Reduced Conducted Powers – Hotspot Mode Active

Maximum Burst-Averaged Output Power									
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	25.88	24.74	22.42	21.14	25.43	24.36	22.55	21.38
	661	25.92	24.83	22.49	21.28	25.62	24.45	22.68	21.45
	810	26.06	24.92	22.65	21.35	25.65	24.63	22.84	21.66
Calculated Maximum Frame-Averaged Output Power									
		GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 1900	512	16.85	18.72	18.16	18.13	16.40	18.34	18.29	18.37
	661	16.89	18.81	18.23	18.27	16.59	18.43	18.42	18.44
	810	17.03	18.90	18.39	18.34	16.62	18.61	18.58	18.65
GSM 1900	Frame Avg.Targets:	17.47	19.48	18.74	18.99	16.97	18.98	18.74	18.99

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 24 of 70

Note:

1. Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
2. GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
3. EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B

GPRS Multislot class: 12 (Max 4 Tx uplink slots)

EDGE Multislot class: 12 (Max 4 Tx uplink slots)

DTM Multislot Class: N/A



Figure 9-1
Power Measurement Setup

9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	
99	WCDMA	12.2 kbps RMC	23.56	23.61	23.28	-
99		12.2 kbps AMR	23.61	23.47	23.25	-
6	HSDPA	Subtest 1	22.05	21.85	21.78	0
6		Subtest 2	22.13	21.94	21.78	0
6		Subtest 3	21.59	21.45	21.20	0.5
6		Subtest 4	21.62	21.40	21.29	0.5
6	HSUPA	Subtest 1	22.16	21.87	21.80	0
6		Subtest 2	20.23	20.02	19.85	2
6		Subtest 3	21.10	21.15	20.83	1
6		Subtest 4	20.22	20.08	19.90	2
6		Subtest 5	22.12	22.02	21.80	0

This device does not support DC-HSDPA.

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 25 of 70

9.3 LTE Conducted Powers

9.3.1 LTE Band 12

Table 9-3
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.36	0	0
	1	25	23.37		0
	1	49	23.28		0
	25	0	22.50	0-1	1
	25	12	22.48		1
	25	25	22.41		1
16QAM	50	0	22.48	0-1	1
	1	0	22.49		1
	1	25	22.49		1
	1	49	22.44	0-2	1
	25	0	21.46		2
	25	12	21.45		2
	25	25	21.41	0-2	2
	50	0	21.38		2

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-4
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.53	23.30	23.37	0	0
	1	12	23.55	23.26	23.40		0
	1	24	23.50	23.25	23.35		0
	12	0	22.45	22.38	22.38	0-1	1
	12	6	22.48	22.38	22.35		1
	12	13	22.44	22.34	22.29		1
	25	0	22.44	22.36	22.28		1
16QAM	1	0	22.87	22.72	22.73	0-1	1
	1	12	22.83	22.69	22.60		1
	1	24	22.82	22.65	22.69		1
	12	0	21.58	21.48	21.40	0-2	2
	12	6	21.54	21.50	21.38		2
	12	13	21.57	21.43	21.31		2
	25	0	21.50	21.44	21.39		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 26 of 70

Table 9-5
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.40	23.39	23.22	0	0
	1	7	23.47	23.42	23.29		0
	1	14	23.37	23.31	23.18		0
	8	0	22.45	22.38	22.33	0-1	1
	8	4	22.47	22.40	22.30		1
	8	7	22.46	22.37	22.23		1
	15	0	22.44	22.40	22.27		1
16QAM	1	0	22.72	22.45	22.45	0-1	1
	1	7	22.85	22.50	22.47		1
	1	14	22.71	22.39	22.36		1
	8	0	21.40	21.30	21.39	0-2	2
	8	4	21.42	21.33	21.37		2
	8	7	21.42	21.29	21.35		2
	15	0	21.50	21.40	21.26		2

Table 9-6
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.36	23.29	23.30	0	0
	1	2	23.42	23.33	23.36		0
	1	5	23.33	23.30	23.30		0
	3	0	23.46	23.36	23.24		0
	3	2	23.49	23.43	23.27		0
	3	3	23.45	23.40	23.22		0
	6	0	22.38	22.35	22.18	0-1	1
16QAM	1	0	22.45	22.44	22.14	0-1	1
	1	2	22.47	22.49	22.17		1
	1	5	22.46	22.48	22.15		1
	3	0	22.56	22.31	22.22		1
	3	2	22.61	22.36	22.28		1
	3	3	22.58	22.31	22.20		1
	6	0	21.43	21.38	21.35	0-2	2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 				Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset			Page 27 of 70

9.3.2

LTE Band 13

Table 9-7
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.41	0	0
	1	25	23.48		0
	1	49	23.28		0
	25	0	22.53	0-1	1
	25	12	22.55		1
	25	25	22.35		1
	50	0	22.50		1
16QAM	1	0	22.59	0-1	1
	1	25	22.55		1
	1	49	22.28		1
	25	0	21.61	0-2	2
	25	12	21.54		2
	25	25	21.38		2
	50	0	21.50		2

Table 9-8
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.33	0	0
	1	12	23.30		0
	1	24	23.25		0
	12	0	22.48	0-1	1
	12	6	22.45		1
	12	13	22.33		1
	25	0	22.44		1
16QAM	1	0	22.79	0-1	1
	1	12	22.76		1
	1	24	22.67		1
	12	0	21.52	0-2	2
	12	6	21.48		2
	12	13	21.37		2
	25	0	21.43		2

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 28 of 70

9.3.3

LTE Band 5 (Cell)

Table 9-9
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	23.40	0	0
	1	25	23.46		0
	1	49	23.37		0
	25	0	22.62	0-1	1
	25	12	22.57		1
	25	25	22.50		1
	50	0	22.54		1
16QAM	1	0	22.78	0-1	1
	1	25	22.81		1
	1	49	22.68		1
	25	0	21.65	0-2	2
	25	12	21.59		2
	25	25	21.49		2
	50	0	21.52		2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-10
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.60	23.36	23.49	0	0
	1	12	23.58	23.29	23.41		0
	1	24	23.56	23.26	23.25		0
	12	0	22.55	22.47	22.46	0-1	1
	12	6	22.52	22.45	22.44		1
	12	13	22.48	22.40	22.41		1
	25	0	22.50	22.44	22.38		1
16QAM	1	0	22.99	22.84	22.82	0-1	1
	1	12	22.88	22.80	22.77		1
	1	24	22.92	22.76	22.56		1
	12	0	21.65	21.50	21.48	0-2	2
	12	6	21.57	21.51	21.44		2
	12	13	21.53	21.43	21.38		2
	25	0	21.50	21.46	21.44		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 29 of 70

Table 9-11
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.49	23.36	23.36	0	0
	1	7	23.53	23.41	23.43		0
	1	14	23.41	23.30	23.16		0
	8	0	22.48	22.45	22.38	0-1	1
	8	4	22.54	22.49	22.36		1
	8	7	22.46	22.41	22.33		1
	15	0	22.53	22.44	22.38		1
16QAM	1	0	22.82	22.62	22.50	0-1	1
	1	7	22.92	22.62	22.59		1
	1	14	22.74	22.52	22.30		1
	8	0	21.45	21.50	21.24	0-2	2
	8	4	21.48	21.49	21.23		2
	8	7	21.42	21.48	21.22		2
	15	0	21.54	21.39	21.31		2

Table 9-12
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.44	23.28	23.46	0	0
	1	2	23.49	23.31	23.48		0
	1	5	23.35	23.27	23.16		0
	3	0	23.56	23.37	23.33		0
	3	2	23.53	23.44	23.29		0
	3	3	23.49	23.41	23.16		0
	6	0	22.36	22.36	22.26	0-1	1
16QAM	1	0	22.52	22.47	22.25	0-1	1
	1	2	22.59	22.52	22.25		1
	1	5	22.51	22.50	22.19		1
	3	0	22.67	22.32	22.29		1
	3	2	22.62	22.37	22.41		1
	3	3	22.61	22.32	22.33		1
	6	0	21.38	21.34	21.34	0-2	2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 				Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset			Page 30 of 70

9.3.4

LTE Band 4 (AWS)

Table 9-13
LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 4 (AWS) 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20175 (1732.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	22.82	0	0
	1	50	22.43		0
	1	99	22.62		0
	50	0	21.71	0-1	1
	50	25	21.57		1
	50	50	21.59		1
	100	0	21.63		1
16QAM	1	0	21.92	0-1	1
	1	50	21.78		1
	1	99	21.80		1
	50	0	20.71	0-2	2
	50	25	20.60		2
	50	50	20.58		2
	100	0	20.63		2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-14
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 4 (AWS) 15 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20025 (1717.5 MHz)	20175 (1732.5 MHz)	20325 (1747.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.81	22.99	22.99	0	0
	1	36	22.79	22.68	22.93		0
	1	74	22.82	22.79	22.90		0
	36	0	21.94	21.97	21.69	0-1	1
	36	18	21.90	21.73	21.79		1
	36	37	21.86	21.85	21.93		1
	75	0	21.91	21.93	21.92		1
16QAM	1	0	21.87	22.00	21.91	0-1	1
	1	36	21.88	21.93	21.96		1
	1	74	21.95	21.94	22.00		1
	36	0	21.00	21.00	20.89	0-2	2
	36	18	20.87	20.79	20.94		2
	36	37	20.98	20.92	20.83		2
	75	0	20.98	20.77	20.86		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 31 of 70

Table 9-15
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 4 (AWS) 10 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20000 (1715.0 MHz)	20175 (1732.5 MHz)	20350 (1750.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.82	22.71	22.69	0	0
	1	25	22.42	22.35	22.65		0
	1	49	22.55	22.36	22.84		0
	25	0	21.69	21.68	21.78	0-1	1
	25	12	21.61	21.54	21.68		1
	25	25	21.63	21.53	21.76		1
	50	0	21.62	21.60	21.72		1
16QAM	1	0	22.00	21.96	21.79	0-1	1
	1	25	21.93	21.56	21.66		1
	1	49	21.96	21.59	21.83		1
	25	0	20.72	20.70	20.75	0-2	2
	25	12	20.63	20.55	20.69		2
	25	25	20.67	20.56	20.73		2
	50	0	20.67	20.59	20.72		2

Table 9-16
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 4 (AWS) 5 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19975 (1712.5 MHz)	20175 (1732.5 MHz)	20375 (1752.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.71	22.69	22.58	0	0
	1	12	22.62	22.49	22.60		0
	1	24	22.56	22.48	22.63		0
	12	0	21.60	21.57	21.65	0-1	1
	12	6	21.55	21.51	21.72		1
	12	13	21.51	21.41	21.72		1
	25	0	21.55	21.47	21.76		1
16QAM	1	0	22.00	21.96	21.97	0-1	1
	1	12	21.94	21.83	22.00		1
	1	24	21.87	21.89	21.90		1
	12	0	20.69	20.60	20.73	0-2	2
	12	6	20.63	20.56	20.80		2
	12	13	20.62	20.48	20.78		2
	25	0	20.59	20.56	20.76		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 32 of 70

Table 9-17
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 4 (AWS) 3 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19965 (1711.5 MHz)	20175 (1732.5 MHz)	20385 (1753.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.45	22.45	22.76	0	0
	1	7	22.53	22.48	22.82		0
	1	14	22.35	22.26	22.73		0
	8	0	21.56	21.51	21.72	0-1	1
	8	4	21.57	21.48	21.70		1
	8	7	21.52	21.39	21.68		1
	15	0	21.56	21.45	21.76		1
16QAM	1	0	21.86	21.68	21.86	0-1	1
	1	7	21.95	21.64	21.92		1
	1	14	21.78	21.47	21.72		1
	8	0	20.55	20.57	20.63	0-2	2
	8	4	20.55	20.53	20.62		2
	8	7	20.52	20.52	20.59		2
	15	0	20.61	20.46	20.72		2

Table 9-18
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 4 (AWS) 1.4 MHzBandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			19957 (1710.7 MHz)	20175 (1732.5 MHz)	20393 (1754.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	22.43	22.39	22.82	0	0
	1	2	22.48	22.46	22.86		0
	1	5	22.36	22.35	22.79		0
	3	0	22.52	22.40	22.70		0
	3	2	22.57	22.53	22.72		0
	3	3	22.52	22.47	22.66		0
	6	0	21.46	21.38	21.62	0-1	1
16QAM	1	0	21.51	21.46	21.60	0-1	1
	1	2	21.59	21.52	21.63		1
	1	5	21.57	21.47	21.60		1
	3	0	21.68	21.37	21.65		1
	3	2	21.71	21.40	21.76		1
	3	3	21.66	21.36	21.69		1
	6	0	20.50	20.41	20.75	0-2	2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 33 of 70

9.3.5

LTE Band 41

Table 9-19
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.43	24.50	24.45	24.07	23.88	0	0
	1	50	24.35	24.43	24.49	24.04	23.83		0
	1	99	24.42	24.05	24.56	24.14	23.82		0
	50	0	23.46	23.50	23.48	23.15	22.95	0-1	1
	50	25	23.49	23.53	23.62	23.08	22.93		1
	50	50	23.51	23.58	23.66	23.09	22.85		1
	100	0	23.50	23.57	23.63	23.07	22.87		1
16QAM	1	0	23.52	23.66	23.18	23.06	22.56	0-1	1
	1	50	23.43	23.61	23.20	22.97	22.50		1
	1	99	23.66	23.26	23.31	23.08	22.51		1
	50	0	22.53	22.60	22.53	22.14	21.93	0-2	2
	50	25	22.52	22.63	22.61	22.09	21.90		2
	50	50	22.53	22.68	22.63	22.10	21.87		2
	100	0	22.54	22.65	22.59	22.08	21.90		2

Table 9-20
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.97	24.00	24.13	23.68	23.65	0	0
	1	36	23.86	24.10	24.06	23.81	23.54		0
	1	74	24.12	23.72	24.13	23.94	23.50		0
	36	0	23.01	23.02	23.32	22.86	22.63	0-1	1
	36	18	23.19	23.05	23.22	22.80	22.66		1
	36	37	23.09	23.26	23.15	22.69	22.65		1
	75	0	23.03	23.23	23.14	22.85	22.47		1
16QAM	1	0	23.06	23.36	23.47	22.82	22.22	0-1	1
	1	36	23.09	23.26	23.39	22.59	22.19		1
	1	74	23.25	22.87	23.45	22.72	22.26		1
	36	0	22.22	22.18	22.20	21.80	21.60	0-2	2
	36	18	22.15	22.32	22.21	21.77	21.50		2
	36	37	22.08	22.19	22.20	21.84	21.58		2
	75	0	22.14	22.22	22.15	21.81	21.55		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 34 of 70

Table 9-21
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.89	24.14	24.14	23.75	23.61	0	0
	1	25	23.78	24.29	24.25	23.89	23.54		0
	1	49	24.31	23.85	24.12	23.89	23.54		0
	25	0	23.06	23.11	23.42	22.82	22.55	0-1	1
	25	12	23.34	23.22	23.23	23.00	22.63		1
	25	25	23.23	23.36	23.09	22.74	22.61		1
	50	0	23.18	23.32	23.20	22.77	22.52		1
16QAM	1	0	23.00	23.35	23.55	22.89	22.36	0-1	1
	1	25	23.01	23.27	23.36	22.58	22.30		1
	1	49	23.32	22.94	23.62	22.89	22.41		1
	25	0	22.18	22.19	22.11	21.91	21.55	0-2	2
	25	12	22.24	22.38	22.13	21.97	21.41		2
	25	25	22.23	22.19	22.14	21.97	21.60		2
	50	0	22.22	22.22	22.11	21.82	21.62		2

Table 9-22
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	24.06	24.12	24.16	23.65	23.60	0	0
	1	12	23.85	24.29	24.35	24.04	23.45		0
	1	24	24.47	23.83	24.02	23.93	23.63		0
	12	0	23.16	23.23	23.47	22.86	22.48	0-1	1
	12	6	23.42	23.40	23.13	22.97	22.78		1
	12	13	23.29	23.38	23.03	22.65	22.80		1
	25	0	23.37	23.30	23.38	22.90	22.63		1
16QAM	1	0	23.18	23.30	23.45	22.88	22.38	0-1	1
	1	12	23.10	23.17	23.40	22.74	22.34		1
	1	24	23.30	23.11	23.77	23.05	22.58		1
	12	0	22.28	22.26	22.28	21.87	21.65	0-2	2
	12	6	22.41	22.52	22.26	21.90	21.52		2
	12	13	22.24	22.10	22.24	21.95	21.52		2
	25	0	22.28	22.38	22.22	21.74	21.72		2

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
Page 35 of 70		

9.4 WLAN Conducted Powers

Table 9-23
2.4 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	19.45	16.56	17.28
2437	6	19.71	17.78	16.58
2462	11	19.65	16.91	16.62

Table 9-24
2.4 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	19.92	17.05	17.02
2437	6	19.25	17.35	17.24
2462	11	20.27	17.11	16.89

Table 9-25
2.4 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	13.62	14.25	14.19
2437	6	14.56	14.77	14.79
2462	11	13.52	14.11	13.76

Table 9-26
2.4 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

Freq [MHz]	Channel	2.4GHz Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11b	802.11g	802.11n
2412	1	14.18	14.75	14.57
2437	6	15.45	15.49	15.48
2462	11	14.15	14.37	14.26

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 36 of 70

Table 9-27
5 GHz WLAN Maximum Average RF Power – Antenna 1

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	13.21	13.05	13.05
5200	40	14.95	14.78	15.06
5220	44	14.88	14.72	14.95
5240	48	14.72	14.61	14.89
5260	52	14.76	14.68	14.89
5280	56	14.63	14.58	14.83
5300	60	14.71	14.62	14.86
5320	64	14.62	13.72	13.64
5500	100	14.71	13.38	13.18
5600	120	15.11	15.09	15.33
5620	124	15.16	15.15	15.37
5720	144	15.45	15.35	15.49
5745	149	14.85	14.77	15.06
5785	157	15.02	14.93	15.19
5825	165	15.19	15.10	15.39

Table 9-28
5 GHz WLAN Maximum Average RF Power – Antenna 2

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	13.15	12.97	12.94
5200	40	15.01	14.84	14.92
5220	44	14.91	14.92	14.83
5240	48	14.88	14.89	14.82
5260	52	14.91	14.72	15.02
5280	56	14.95	14.74	14.95
5300	60	14.84	14.63	14.90
5320	64	14.85	13.56	13.59
5500	100	15.00	12.92	12.87
5600	120	14.85	14.79	14.72
5620	124	14.89	14.79	14.70
5720	144	15.39	15.32	15.26
5745	149	15.25	15.25	15.16
5785	157	14.95	14.89	14.85
5825	165	14.71	14.71	14.65

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 37 of 70

Table 9-29
5 GHz WLAN Reduced Average RF Power – Antenna 1 (Held to Ear)

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	8.52	8.17	9.05
5200	40	8.30	8.11	8.85
5220	44	8.37	8.07	9.08
5240	48	8.20	8.09	9.15
5260	52	9.45	9.19	9.04
5280	56	9.28	9.23	9.17
5300	60	9.29	9.12	9.08
5320	64	9.23	9.20	9.24
5500	100	8.87	8.71	8.71
5600	120	8.93	8.87	8.81
5620	124	8.95	8.86	8.85
5720	144	9.02	8.75	8.82
5745	149	8.69	8.50	8.61
5785	157	8.87	8.65	8.70
5825	165	8.79	8.68	8.76

Table 9-30
5 GHz WLAN Reduced Average RF Power – Antenna 2 (Held to Ear)

Freq [MHz]	Channel	5GHz (20MHz) Conducted Power [dBm]		
		IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	9.15	9.03	8.86
5200	40	9.09	8.85	8.91
5220	44	9.21	8.88	9.20
5240	48	9.25	9.02	8.85
5260	52	8.88	8.90	8.92
5280	56	9.05	9.02	9.01
5300	60	9.01	9.17	8.99
5320	64	8.99	8.97	8.91
5500	100	8.83	8.56	8.65
5600	120	8.76	8.80	8.66
5620	124	8.79	8.80	8.65
5720	144	8.77	8.58	8.58
5745	149	8.95	8.51	8.75
5785	157	8.80	8.55	8.70
5825	165	8.60	8.48	8.20

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 38 of 70

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 39 of 70

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties - Head

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
7/17/2016	750H	21.1	740	0.884	41.265	0.893	41.994	-1.01%	-1.74%
			755	0.898	41.067	0.894	41.916	0.45%	-2.03%
			770	0.913	40.850	0.895	41.838	2.01%	-2.36%
			785	0.925	40.690	0.896	41.760	3.24%	-2.56%
8/8/2016	750H	22.2	700	0.846	41.334	0.889	42.201	-4.84%	-2.05%
			710	0.855	41.213	0.890	42.149	-3.93%	-2.22%
			740	0.882	40.855	0.893	41.994	-1.23%	-2.71%
			755	0.896	40.628	0.894	41.916	0.22%	-3.07%
7/12/2016	835H	22.1	820	0.895	41.897	0.899	41.578	-0.44%	0.77%
			835	0.908	41.718	0.900	41.500	0.89%	0.53%
			850	0.923	41.525	0.916	41.500	0.76%	0.06%
7/27/2016	835H	20.5	820	0.885	40.538	0.899	41.578	-1.56%	-2.50%
			835	0.899	40.348	0.900	41.500	-0.11%	-2.78%
			850	0.913	40.153	0.916	41.500	-0.33%	-3.25%
7/19/2016	1750H	22.0	1710	1.341	39.466	1.348	40.142	-0.52%	-1.68%
			1750	1.382	39.267	1.371	40.079	0.80%	-2.03%
			1790	1.421	39.094	1.394	40.016	1.94%	-2.30%
7/11/2016	1900H	22.2	1850	1.410	39.142	1.400	40.000	0.71%	-2.14%
			1880	1.439	39.029	1.400	40.000	2.79%	-2.43%
			1910	1.466	38.883	1.400	40.000	4.71%	-2.79%
7/20/2016	2450H	21.9	2400	1.827	38.681	1.756	39.289	4.04%	-1.55%
			2450	1.884	38.488	1.800	39.200	4.67%	-1.82%
			2500	1.938	38.287	1.855	39.136	4.47%	-2.17%
7/18/2016	2600H	24.5	2500	1.894	40.095	1.855	39.136	2.10%	2.45%
			2550	1.951	39.871	1.909	39.073	2.20%	2.04%
			2600	2.011	39.700	1.964	39.009	2.39%	1.77%
			2650	2.067	39.483	2.018	38.945	2.43%	1.38%
			2700	2.132	39.284	2.073	38.882	2.85%	1.03%
07/15/2016	5200H-5800H	21.8	5240	4.565	36.748	4.696	35.940	-2.79%	2.25%
			5260	4.588	36.674	4.717	35.917	-2.73%	2.11%
			5280	4.603	36.660	4.737	35.894	-2.83%	2.13%
			5500	4.827	36.368	4.963	35.643	-2.74%	2.03%
			5600	4.938	36.230	5.065	35.529	-2.51%	1.97%
			5700	5.049	36.080	5.168	35.414	-2.30%	1.88%
			5745	5.097	36.009	5.214	35.363	-2.24%	1.83%
			5765	5.141	35.976	5.234	35.340	-1.78%	1.80%
			5785	5.159	35.955	5.255	35.317	-1.83%	1.81%

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 40 of 70

Table 10-2
Measured Tissue Properties - Body

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
7/22/2016	750B	21.5	740	0.959	55.132	0.963	55.570	-0.42%	-0.79%
			755	0.973	54.987	0.964	55.512	0.93%	-0.95%
			770	0.988	54.833	0.965	55.453	2.38%	-1.12%
			785	1.003	54.679	0.966	55.395	3.83%	-1.29%
8/16/2016	750B	21.8	700	0.924	56.004	0.959	55.726	-3.65%	0.50%
			710	0.934	55.917	0.960	55.687	-2.71%	0.41%
			740	0.962	55.627	0.963	55.570	-0.10%	0.10%
			755	0.976	55.480	0.964	55.512	1.24%	-0.06%
7/17/2016	835B	22.1	820	0.983	53.045	0.969	55.258	1.44%	-4.00%
			835	0.995	52.923	0.970	55.200	2.58%	-4.13%
			850	1.011	52.685	0.988	55.154	2.33%	-4.48%
7/18/2016	1750B	21.6	1710	1.457	52.284	1.463	53.537	-0.41%	-2.34%
			1750	1.501	52.164	1.488	53.432	0.87%	-2.37%
			1790	1.550	51.992	1.514	53.326	2.38%	-2.50%
7/21/2016	1750B	21.7	1710	1.451	51.823	1.463	53.537	-0.82%	-3.20%
			1750	1.496	51.664	1.488	53.432	0.54%	-3.31%
			1790	1.539	51.480	1.514	53.326	1.65%	-3.46%
7/11/2016	1900B	22.8	1850	1.527	52.150	1.520	53.300	0.46%	-2.16%
			1880	1.561	52.091	1.520	53.300	2.70%	-2.27%
			1910	1.589	51.937	1.520	53.300	4.54%	-2.56%
7/14/2016	1900B	22.3	1850	1.515	51.874	1.520	53.300	-0.33%	-2.68%
			1880	1.549	51.795	1.520	53.300	1.91%	-2.82%
			1910	1.575	51.672	1.520	53.300	3.62%	-3.05%
7/21/2016	2450B-2600B	23.2	2400	1.886	53.004	1.902	52.767	-0.84%	0.45%
			2450	1.956	52.816	1.950	52.700	0.31%	0.22%
			2500	2.023	52.656	2.021	52.636	0.10%	0.04%
			2550	2.090	52.462	2.092	52.573	-0.10%	-0.21%
			2600	2.163	52.299	2.163	52.509	0.00%	-0.40%
			2650	2.223	52.103	2.234	52.445	-0.49%	-0.65%
7/19/2016	2600B	23.0	2700	2.293	51.912	2.305	52.382	-0.52%	-0.90%
			2500	2.027	52.895	2.021	52.636	0.30%	0.49%
			2550	2.094	52.709	2.092	52.573	0.10%	0.26%
			2600	2.164	52.532	2.163	52.509	0.05%	0.04%
			2650	2.235	52.314	2.234	52.445	0.04%	-0.25%
08/01/2016	5200B-5800B	21.8	2700	2.304	52.140	2.305	52.382	-0.04%	-0.46%
			5240	5.424	47.742	5.346	48.960	1.46%	-2.49%
			5260	5.451	47.849	5.369	48.933	1.53%	-2.22%
			5280	5.474	47.835	5.393	48.906	1.50%	-2.19%
			5600	5.888	47.282	5.766	48.471	2.12%	-2.45%
			5700	6.069	47.124	5.883	48.336	3.16%	-2.51%
			5745	6.099	46.999	5.936	48.275	2.75%	-2.64%
			5765	6.104	46.916	5.959	48.248	2.43%	-2.76%
			5825	6.225	46.888	6.029	48.166	3.25%	-2.65%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 41 of 70

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-3
System Verification Results -1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	07/17/2016	21.5	21.1	0.200	1046	7409	1.540	8.200	7.700	-6.10%
G	750	HEAD	08/08/2016	23.0	22.2	0.200	1054	3334	1.640	8.220	8.200	-0.24%
G	835	HEAD	07/12/2016	23.2	22.1	0.200	4d119	3334	1.790	9.140	8.950	-2.08%
J	835	HEAD	07/27/2016	20.3	20.5	0.200	4d119	3318	1.810	9.140	9.050	-0.98%
G	1750	HEAD	07/19/2016	23.5	22.0	0.100	1051	3334	3.810	36.100	38.100	5.54%
G	1900	HEAD	07/11/2016	21.8	22.4	0.100	5d141	3334	3.770	38.500	37.700	-2.08%
D	2450	HEAD	07/20/2016	22.0	21.9	0.100	882	3213	5.380	50.500	53.800	6.53%
G	2600	HEAD	07/18/2016	23.0	23.0	0.100	1071	3334	5.170	55.900	51.700	-7.51%
D	5250	HEAD	07/15/2016	23.0	21.8	0.050	1120	3914	3.650	78.700	73.000	-7.24%
D	5600	HEAD	07/15/2016	23.0	21.8	0.050	1120	3914	3.860	82.300	77.200	-6.20%
D	5750	HEAD	07/15/2016	23.0	21.8	0.050	1120	3914	3.690	79.100	73.800	-6.70%
F	750	BODY	07/22/2016	21.3	20.8	0.200	1046	3209	1.780	8.770	8.900	1.48%
F	750	BODY	08/16/2016	21.6	21.8	0.200	1054	3209	1.750	8.560	8.750	2.22%
I	835	BODY	07/17/2016	23.6	22.1	0.200	4d119	3333	1.930	9.140	9.650	5.58%
E	1750	BODY	07/18/2016	21.1	21.6	0.100	1008	7406	3.780	37.300	37.800	1.34%
E	1750	BODY	07/21/2016	21.9	21.7	0.100	1008	7406	3.740	37.300	37.400	0.27%
H	1900	BODY	07/11/2016	22.7	22.8	0.100	5d141	3319	4.200	39.600	42.000	6.06%
H	1900	BODY	07/14/2016	22.9	22.3	0.100	5d141	3319	4.190	39.600	41.900	5.81%
E	2450	BODY	07/21/2016	22.3	23.2	0.100	719	7406	5.100	51.900	51.000	-1.73%
E	2600	BODY	07/19/2016	23.5	23.0	0.100	1071	7406	5.690	54.900	56.900	3.64%
E	2600	BODY	07/21/2016	22.3	23.2	0.100	1071	7406	5.650	54.900	56.500	2.91%
D	5250	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	3.710	75.600	74.200	-1.85%
D	5600	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	3.890	80.800	77.800	-3.71%
D	5750	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	3.560	76.500	71.200	-6.93%

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 42 of 70

Table 10-4
System Verification Results -10g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{10g} (W/kg)	1 W Target SAR _{10g} (W/kg)	1 W Normalized SAR _{10g} (W/kg)	Deviation _{10g} (%)
D	5250	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	1.050	21.200	21.000	-0.94%
D	5600	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	1.100	22.600	22.000	-2.65%
D	5750	BODY	08/01/2016	21.8	22.3	0.050	1120	3914	1.010	21.300	20.200	-5.16%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
Page 43 of 70		

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.72	0.03	Right	Cheek	852D0	1:8.3	0.150	1.197	0.180	A1
836.60	190	GSM 850	GSM	33.5	32.72	0.07	Right	Tilt	852D0	1:8.3	0.069	1.197	0.083	
836.60	190	GSM 850	GSM	33.5	32.72	-0.01	Left	Cheek	852D0	1:8.3	0.101	1.197	0.121	
836.60	190	GSM 850	GSM	33.5	32.72	-0.08	Left	Tilt	852D0	1:8.3	0.082	1.197	0.098	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-2
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	30.5	29.31	0.06	Right	Cheek	252D4	1:8.3	0.048	1.315	0.063	
1880.00	661	GSM 1900	GSM	30.5	29.31	0.10	Right	Tilt	252D4	1:8.3	0.040	1.315	0.053	
1880.00	661	GSM 1900	GSM	30.5	29.31	0.02	Left	Cheek	252D4	1:8.3	0.060	1.315	0.079	A2
1880.00	661	GSM 1900	GSM	30.5	29.31	-0.04	Left	Tilt	252D4	1:8.3	0.037	1.315	0.049	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-3
UMTS 850 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Ant. State	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	24.0	23.61	-0.09	Right	Cheek	2	852D4	1:1	0.181	1.094	0.198	A3
836.60	4183	UMTS 850	RMC	24.0	23.61	0.09	Right	Tilt	2	852D4	1:1	0.077	1.094	0.084	
836.60	4183	UMTS 850	RMC	24.0	23.61	-0.02	Left	Cheek	2	852D4	1:1	0.114	1.094	0.125	
836.60	4183	UMTS 850	RMC	24.0	23.61	0.09	Left	Tilt	2	852D4	1:1	0.082	1.094	0.090	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 44 of 70

Table 11-4
LTE Band 12 Head SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Ant. State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	0.02	0	Right	Cheek	56	QPSK	1	25	C9186	1:1	0.122	1.156	0.141	A4
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	-0.05	1	Right	Cheek	56	QPSK	25	0	C9186	1:1	0.092	1.122	0.103	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.14	0	Right	Tilt	56	QPSK	1	25	C9186	1:1	0.023	1.156	0.027	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.02	1	Right	Tilt	56	QPSK	25	0	C9186	1:1	0.018	1.122	0.020	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.04	0	Left	Cheek	56	QPSK	1	25	C9186	1:1	0.058	1.156	0.067	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.08	1	Left	Cheek	56	QPSK	25	0	C9186	1:1	0.043	1.122	0.048	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	0.05	0	Left	Tilt	56	QPSK	1	25	C9186	1:1	0.022	1.156	0.025	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.03	1	Left	Tilt	56	QPSK	25	0	C9186	1:1	0.017	1.122	0.019	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-5
LTE Band 13 Head SAR

MEASUREMENT RESULTS																				
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Ant. State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
																	(W/kg)		(W/kg)	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.03	0	Right	Cheek	2	QPSK	1	25	252D4	1:1	0.150	1.127	0.169	A5
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	-0.03	1	Right	Cheek	2	QPSK	25	12	252D4	1:1	0.119	1.109	0.132	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.20	0	Right	Tilt	2	QPSK	1	25	252D4	1:1	0.058	1.127	0.065	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	0.07	1	Right	Tilt	2	QPSK	25	12	252D4	1:1	0.050	1.109	0.055	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.07	0	Left	Cheek	2	QPSK	1	25	252D4	1:1	0.115	1.127	0.130	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	0.05	1	Left	Cheek	2	QPSK	25	12	252D4	1:1	0.091	1.109	0.101	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.18	0	Left	Tilt	2	QPSK	1	25	252D4	1:1	0.048	1.127	0.054	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	0.01	1	Left	Tilt	2	QPSK	25	12	252D4	1:1	0.040	1.109	0.044	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Head										
Spatial Peak										1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population										averaged over 1 gram										

Table 11-6
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Ant. State	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.46	0.05	0	Right	Cheek	2	QPSK	1	25	852D4	1:1	0.168	1.132	0.190	A6
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.62	-0.06	1	Right	Cheek	2	QPSK	25	0	852D4	1:1	0.136	1.091	0.148	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.46	0.16	0	Right	Tilt	2	QPSK	1	25	852D4	1:1	0.092	1.132	0.104	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.62	0.02	1	Right	Tilt	2	QPSK	25	0	852D4	1:1	0.078	1.091	0.085	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.46	0.03	0	Left	Cheek	2	QPSK	1	25	852D4	1:1	0.087	1.132	0.098	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.62	0.20	1	Left	Cheek	2	QPSK	25	0	852D4	1:1	0.077	1.091	0.084	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.46	0.02	0	Left	Tilt	2	QPSK	1	25	852D4	1:1	0.086	1.132	0.097	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.62	-0.02	1	Left	Tilt	2	QPSK	25	0	852D4	1:1	0.074	1.091	0.081	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 45 of 70

Table 11-7
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	-0.04	0	Right	Cheek	QPSK	1	0	252D4	1:1	0.069	1.042	0.072	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.12	1	Right	Cheek	QPSK	50	0	252D4	1:1	0.057	1.069	0.061	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.03	0	Right	Tilt	QPSK	1	0	252D4	1:1	0.051	1.042	0.053	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.13	1	Right	Tilt	QPSK	50	0	252D4	1:1	0.040	1.069	0.043	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.03	0	Left	Cheek	QPSK	1	0	252D4	1:1	0.126	1.042	0.131	A7
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.02	1	Left	Cheek	QPSK	50	0	252D4	1:1	0.092	1.069	0.098	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.06	0	Left	Tilt	QPSK	1	0	252D4	1:1	0.056	1.042	0.058	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.14	1	Left	Tilt	QPSK	50	0	252D4	1:1	0.046	1.069	0.049	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-8
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.08	0	Right	Cheek	QPSK	1	99	852BF	1:1.58	0.070	1.107	0.077	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.10	1	Right	Cheek	QPSK	50	50	852BF	1:1.58	0.057	1.081	0.062	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	0.03	0	Right	Tilt	QPSK	1	99	852BF	1:1.58	0.071	1.107	0.079	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.03	1	Right	Tilt	QPSK	50	50	852BF	1:1.58	0.060	1.081	0.065	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	0.03	0	Left	Cheek	QPSK	1	99	852BF	1:1.58	0.093	1.107	0.103	A8
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.07	1	Left	Cheek	QPSK	50	50	852BF	1:1.58	0.071	1.081	0.077	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	0.08	0	Left	Tilt	QPSK	1	99	852BF	1:1.58	0.034	1.107	0.038	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	-0.03	1	Left	Tilt	QPSK	50	50	852BF	1:1.58	0.026	1.081	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-9
DTS Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2412	1	802.11b	DSSS	22	15.5	13.62	0.12	Right	Cheek	1	852D9	1	99.3	0.579	0.491	1.542	1.007	0.762	
2437	6	802.11b	DSSS	22	15.5	14.56	0.04	Right	Cheek	1	852D9	1	99.3	0.747	0.705	1.242	1.007	0.882	A9
2437	6	802.11b	DSSS	22	15.5	14.56	-0.11	Right	Tilt	1	852D9	1	99.3	0.591	0.513	1.242	1.007	0.642	
2437	6	802.11b	DSSS	22	15.5	14.56	0.02	Left	Cheek	1	852D9	1	99.3	0.376	-	1.242	1.007	-	
2437	6	802.11b	DSSS	22	15.5	14.56	0.03	Left	Tilt	1	852D9	1	99.3	0.251	-	1.242	1.007	-	
2437	6	802.11b	DSSS	22	15.5	15.45	-0.17	Right	Cheek	2	852D9	1	99.3	0.534	0.376	1.012	1.007	0.383	
2437	6	802.11b	DSSS	22	15.5	15.45	0.02	Right	Tilt	2	852D9	1	99.3	0.612	0.420	1.012	1.007	0.428	
2437	6	802.11b	DSSS	22	15.5	15.45	0.03	Left	Cheek	2	852D9	1	99.3	0.227	-	1.012	1.007	-	
2437	6	802.11b	DSSS	22	15.5	15.45	-0.03	Left	Tilt	2	852D9	1	99.3	0.254	-	1.012	1.007	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 46 of 70

**Table 11-10
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	9.5	9.45	0.06	Right	Cheek	1	852D9	6	99.2	0.290	-	1.012	1.008	-	
5260	52	802.11a	OFDM	20	9.5	9.45	0.07	Right	Tilt	1	852D9	6	99.2	0.309	0.160	1.012	1.008	0.163	
5260	52	802.11a	OFDM	20	9.5	9.45	0.01	Left	Cheek	1	852D9	6	99.2	0.220	-	1.012	1.008	-	
5260	52	802.11a	OFDM	20	9.5	9.45	-0.03	Left	Tilt	1	852D9	6	99.2	0.242	-	1.012	1.008	-	
5280	56	802.11a	OFDM	20	9.5	9.05	0.02	Right	Cheek	2	852D9	6	99.2	0.063	-	1.109	1.008	-	
5280	56	802.11a	OFDM	20	9.5	9.05	0.03	Right	Tilt	2	852D9	6	99.2	0.072	0.035	1.109	1.008	0.039	
5280	56	802.11a	OFDM	20	9.5	9.05	0.15	Left	Cheek	2	852D9	6	99.2	0.062	-	1.109	1.008	-	
5280	56	802.11a	OFDM	20	9.5	9.05	0.03	Left	Tilt	2	852D9	6	99.2	0.045	-	1.109	1.008	-	
5720	144	802.11a	OFDM	20	9.5	9.02	0.14	Right	Cheek	1	852D9	6	99.2	0.132	0.063	1.117	1.008	0.071	
5720	144	802.11a	OFDM	20	9.5	9.02	0.03	Right	Tilt	1	852D9	6	99.2	0.110	-	1.117	1.008	-	
5720	144	802.11a	OFDM	20	9.5	9.02	0.07	Left	Cheek	1	852D9	6	99.2	0.076	-	1.117	1.008	-	
5720	144	802.11a	OFDM	20	9.5	9.02	0.02	Left	Tilt	1	852D9	6	99.2	0.058	-	1.117	1.008	-	
5500	100	802.11a	OFDM	20	9.5	8.83	0.03	Right	Cheek	2	852D9	6	99.2	0.281	-	1.167	1.008	-	
5500	100	802.11a	OFDM	20	9.5	8.83	0.20	Right	Tilt	2	852D9	6	99.2	0.295	0.116	1.167	1.008	0.136	
5500	100	802.11a	OFDM	20	9.5	8.83	-0.04	Left	Cheek	2	852D9	6	99.2	0.143	-	1.167	1.008	-	
5500	100	802.11a	OFDM	20	9.5	8.83	0.03	Left	Tilt	2	852D9	6	99.2	0.152	-	1.167	1.008	-	
5785	157	802.11a	OFDM	20	9.5	8.87	0.15	Right	Cheek	1	852D9	6	99.2	0.142	0.064	1.156	1.008	0.075	
5785	157	802.11a	OFDM	20	9.5	8.87	0.03	Right	Tilt	1	852D9	6	99.2	0.126	-	1.156	1.008	-	
5785	157	802.11a	OFDM	20	9.5	8.87	0.02	Left	Cheek	1	852D9	6	99.2	0.079	-	1.156	1.008	-	
5785	157	802.11a	OFDM	20	9.5	8.87	0.16	Left	Tilt	1	852D9	6	99.2	0.091	-	1.156	1.008	-	
5745	149	802.11a	OFDM	20	9.5	8.95	0.04	Right	Cheek	2	852D9	6	99.2	0.510	-	1.135	1.008	-	
5745	149	802.11a	OFDM	20	9.5	8.95	0.08	Right	Tilt	2	852D9	6	99.2	0.539	0.255	1.135	1.008	0.292	A10
5745	149	802.11a	OFDM	20	9.5	8.95	0.06	Left	Cheek	2	852D9	6	99.2	0.372	-	1.135	1.008	-	
5745	149	802.11a	OFDM	20	9.5	8.95	0.03	Left	Tilt	2	852D9	6	99.2	0.363	-	1.135	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram											

11.2 Standalone Body-Worn SAR Data

**Table 11-11
GSM/UMTS Body-Worn SAR Data**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maxim um Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Ant. State	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	33.5	32.72	0.03	15 mm	N/A	852F1	1	1:8.3	back	0.272	1.197	0.326	A11
1880.00	661	GSM 1900	GSM	30.5	29.31	-0.04	15 mm	N/A	852F1	1	1:8.3	back	0.107	1.315	0.141	A13
836.60	4183	UMTS 850	RMC	24.0	23.61	0.01	15 mm	2	852F1	N/A	1:1	back	0.313	1.094	0.342	A15
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 				Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset			Page 47 of 70

Table 11-12
LTE Body-Worn SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maxim um Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant. State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	0.01	0	56	C9186	QPSK	1	25	15 mm	back	1:1	0.252	1.156	0.291	A17
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.00	1	56	C9186	QPSK	25	0	15 mm	back	1:1	0.196	1.122	0.220	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.03	0	2	853E5	QPSK	1	25	15 mm	back	1:1	0.373	1.127	0.420	A19
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	-0.01	1	2	853E5	QPSK	25	12	15 mm	back	1:1	0.300	1.109	0.333	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.0	23.46	0.01	0	2	852F1	QPSK	1	25	15 mm	back	1:1	0.287	1.132	0.325	A21
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.62	0.00	1	2	852F1	QPSK	25	0	15 mm	back	1:1	0.230	1.091	0.251	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	-0.02	0	N/A	252D4	QPSK	1	0	15 mm	back	1:1	0.234	1.042	0.244	A23
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.03	1	N/A	252D4	QPSK	50	0	15 mm	back	1:1	0.188	1.069	0.201	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.02	0	N/A	852D0	QPSK	1	99	15 mm	back	1:1.58	0.231	1.107	0.256	A25
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.02	1	N/A	852D0	QPSK	50	50	15 mm	back	1:1.58	0.194	1.081	0.210	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-13
DTS Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																		
2437	6	802.11b	DSSS	22	20.5	19.71	0.03	15 mm	1	252D4	1	back	99.3	0.150	0.096	1.199	1.007	0.116	
2462	11	802.11b	DSSS	22	20.5	20.27	0.10	15 mm	2	252D4	1	back	99.3	0.162	0.106	1.054	1.007	0.113	A27
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-14
NII Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan W/kg	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Plot #
MHz	Ch.																		
5260	52	802.11a	OFDM	20	15.5	14.76	0.02	10 mm	1	853E5	6	back	99.2	0.399	0.187	1.186	1.008	0.224	
5280	56	802.11a	OFDM	20	15.5	14.95	-0.04	10 mm	2	853E5	6	back	99.2	0.155	0.088	1.135	1.008	0.101	
5720	144	802.11a	OFDM	20	15.5	15.45	0.04	10 mm	1	853E5	6	back	99.2	0.569	0.280	1.012	1.008	0.286	
5720	144	802.11a	OFDM	20	15.5	15.39	-0.06	10 mm	2	853E5	6	back	99.2	0.829	0.491	1.026	1.008	0.508	A29
5825	165	802.11a	OFDM	20	15.5	15.19	0.09	10 mm	1	853E5	6	back	99.2	0.942	0.444	1.074	1.008	0.481	
5745	149	802.11a	OFDM	20	15.5	15.25	-0.06	10 mm	2	853E5	6	back	99.2	0.943	0.474	1.059	1.008	0.506	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 48 of 70

11.3 Standalone Hotspot SAR Data

Table 11-15
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Ant. State	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.												(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	33.5	32.74	0.05	10 mm	N/A	852F1	1	1:8.3	back	0.459	1.191	0.547	
836.60	190	GSM 850	GPRS	33.5	32.74	-0.08	10 mm	N/A	852F1	1	1:8.3	front	0.476	1.191	0.567	A12
836.60	190	GSM 850	GPRS	33.5	32.74	-0.01	10 mm	N/A	852F1	1	1:8.3	bottom	0.280	1.191	0.333	
836.60	190	GSM 850	GPRS	33.5	32.74	-0.01	10 mm	N/A	852F1	1	1:8.3	right	0.221	1.191	0.263	
836.60	190	GSM 850	GPRS	33.5	32.74	-0.01	10 mm	N/A	852F1	1	1:8.3	left	0.101	1.191	0.120	
1880.00	661	GSM 1900	GPRS	26.0	24.83	-0.05	10 mm	N/A	852F1	2	1:4.15	back	0.122	1.309	0.160	
1880.00	661	GSM 1900	GPRS	26.0	24.83	-0.02	10 mm	N/A	852F1	2	1:4.15	front	0.123	1.309	0.161	
1880.00	661	GSM 1900	GPRS	26.0	24.83	-0.01	10 mm	N/A	852F1	2	1:4.15	bottom	0.167	1.309	0.219	A14
1880.00	661	GSM 1900	GPRS	26.0	24.83	-0.13	10 mm	N/A	852F1	2	1:4.15	right	0.044	1.309	0.058	
1880.00	661	GSM 1900	GPRS	26.0	24.83	-0.07	10 mm	N/A	852F1	2	1:4.15	left	0.027	1.309	0.035	
836.60	4183	UMTS 850	RMC	24.0	23.61	0.04	10 mm	2	852F1	N/A	1:1	back	0.555	1.094	0.607	A16
836.60	4183	UMTS 850	RMC	24.0	23.61	-0.03	10 mm	2	852F1	N/A	1:1	front	0.553	1.094	0.605	
836.60	4183	UMTS 850	RMC	24.0	23.61	-0.04	10 mm	2	852F1	N/A	1:1	bottom	0.345	1.094	0.377	
836.60	4183	UMTS 850	RMC	24.0	23.61	-0.03	10 mm	2	852F1	N/A	1:1	right	0.263	1.094	0.288	
836.60	4183	UMTS 850	RMC	24.0	23.61	0.01	10 mm	2	852F1	N/A	1:1	left	0.122	1.094	0.133	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body									
Spatial Peak							1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population							averaged over 1 gram									

Table 11-16
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant. State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	0.00	0	56	C9186	QPSK	1	25	10 mm	back	1:1	0.378	1.156	0.437	A18
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	-0.03	1	56	C9186	QPSK	25	0	10 mm	back	1:1	0.297	1.122	0.333	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.03	0	56	C9186	QPSK	1	25	10 mm	front	1:1	0.417	1.156	0.482	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.00	1	56	C9186	QPSK	25	0	10 mm	front	1:1	0.321	1.122	0.360	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.01	0	56	C9186	QPSK	1	25	10 mm	bottom	1:1	0.181	1.156	0.209	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	0.00	1	56	C9186	QPSK	25	0	10 mm	bottom	1:1	0.138	1.122	0.155	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.01	0	56	C9186	QPSK	1	25	10 mm	right	1:1	0.139	1.156	0.161	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	-0.01	1	56	C9186	QPSK	25	0	10 mm	right	1:1	0.111	1.122	0.125	
707.50	23095	Mid	LTE Band 12	10	24.0	23.37	-0.03	0	56	C9186	QPSK	1	25	10 mm	left	1:1	0.078	1.156	0.090	
707.50	23095	Mid	LTE Band 12	10	23.0	22.50	-0.03	1	56	C9186	QPSK	25	0	10 mm	left	1:1	0.057	1.122	0.064	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram													

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 49 of 70

Table 11-17
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant. State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.00	0	2	853E5	QPSK	1	25	10 mm	back	1:1	0.530	1.127	0.597	A20
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	-0.01	1	2	853E5	QPSK	25	12	10 mm	back	1:1	0.429	1.109	0.476	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.01	0	2	853E5	QPSK	1	25	10 mm	front	1:1	0.568	1.127	0.640	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	0.01	1	2	853E5	QPSK	25	12	10 mm	front	1:1	0.463	1.109	0.513	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.11	0	2	853E5	QPSK	1	25	10 mm	bottom	1:1	0.330	1.127	0.372	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	-0.08	1	2	853E5	QPSK	25	12	10 mm	bottom	1:1	0.267	1.109	0.296	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	-0.09	0	2	853E5	QPSK	1	25	10 mm	right	1:1	0.203	1.127	0.229	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	-0.01	1	2	853E5	QPSK	25	12	10 mm	right	1:1	0.166	1.109	0.184	
782.00	23230	Mid	LTE Band 13	10	24.0	23.48	0.02	0	2	853E5	QPSK	1	25	10 mm	left	1:1	0.168	1.127	0.189	
782.00	23230	Mid	LTE Band 13	10	23.0	22.55	0.02	1	2	853E5	QPSK	25	12	10 mm	left	1:1	0.136	1.109	0.151	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body												
Spatial Peak								1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population								averaged over 1 gram												

Table 11-18
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Ant. State	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.															(W/kg)		(W/kg)		
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.46	0.00	0	2	852F1	QPSK	1	25	10 mm	back	1:1	0.500	1.132	0.566	A22
836.50	20525	Md	LTE Band 5 (Cell)	10	23.0	22.62	0.02	1	2	852F1	QPSK	25	0	10 mm	back	1:1	0.402	1.091	0.439	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.46	-0.02	0	2	852F1	QPSK	1	25	10 mm	front	1:1	0.536	1.132	0.607	
836.50	20525	Md	LTE Band 5 (Cell)	10	23.0	22.62	-0.03	1	2	852F1	QPSK	25	0	10 mm	front	1:1	0.429	1.091	0.468	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.46	0.00	0	2	852F1	QPSK	1	25	10 mm	bottom	1:1	0.319	1.132	0.361	
836.50	20525	Md	LTE Band 5 (Cell)	10	23.0	22.62	-0.02	1	2	852F1	QPSK	25	0	10 mm	bottom	1:1	0.254	1.091	0.277	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.46	-0.08	0	2	852F1	QPSK	1	25	10 mm	right	1:1	0.237	1.132	0.268	
836.50	20525	Md	LTE Band 5 (Cell)	10	23.0	22.62	0.01	1	2	852F1	QPSK	25	0	10 mm	right	1:1	0.201	1.091	0.219	
836.50	20525	Md	LTE Band 5 (Cell)	10	24.0	23.46	0.03	0	2	852F1	QPSK	1	25	10 mm	left	1:1	0.109	1.132	0.123	
836.50	20525	Md	LTE Band 5 (Cell)	10	23.0	22.62	0.02	1	2	852F1	QPSK	25	0	10 mm	left	1:1	0.082	1.091	0.089	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body												
Spatial Peak								1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population								averaged over 1 gram												

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 50 of 70

Table 11-19
LTE Band 4 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	-0.01	0	252D4	QPSK	1	0	10 mm	back	1:1	0.456	1.042	0.475	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.00	1	252D4	QPSK	50	0	10 mm	back	1:1	0.376	1.069	0.402	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.03	0	252D4	QPSK	1	0	10 mm	front	1:1	0.435	1.042	0.453	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.05	1	252D4	QPSK	50	0	10 mm	front	1:1	0.351	1.069	0.375	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	-0.05	0	252D4	QPSK	1	0	10 mm	bottom	1:1	0.829	1.042	0.864	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	-0.02	1	252D4	QPSK	50	0	10 mm	bottom	1:1	0.657	1.069	0.702	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	-0.02	1	252D4	QPSK	100	0	10 mm	bottom	1:1	0.650	1.089	0.708	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.12	0	252D4	QPSK	1	0	10 mm	right	1:1	0.074	1.042	0.077	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	0.01	1	252D4	QPSK	50	0	10 mm	right	1:1	0.062	1.069	0.066	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	0.00	0	252D4	QPSK	1	0	10 mm	left	1:1	0.160	1.042	0.167	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.71	-0.05	1	252D4	QPSK	50	0	10 mm	left	1:1	0.129	1.069	0.138	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	22.82	-0.03	0	252D4	QPSK	1	0	10 mm	bottom	1:1	0.872	1.042	0.909	A24
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement.

Table 11-20
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.04	0	852D0	QPSK	1	99	10 mm	back	1:1.58	0.472	1.107	0.523	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.02	1	852D0	QPSK	50	50	10 mm	back	1:1.58	0.396	1.081	0.428	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.01	0	852D0	QPSK	1	99	10 mm	front	1:1.58	0.452	1.107	0.500	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.00	1	852D0	QPSK	50	50	10 mm	front	1:1.58	0.355	1.081	0.384	
2506.00	39750	Low	LTE Band 41	20	25.0	24.43	-0.08	0	852D0	QPSK	1	0	10 mm	bottom	1:1.58	0.750	1.140	0.855	
2549.50	40185	Low-Mid	LTE Band 41	20	25.0	24.50	-0.03	0	852D0	QPSK	1	0	10 mm	bottom	1:1.58	0.818	1.122	0.918	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.01	0	852D0	QPSK	1	99	10 mm	bottom	1:1.58	0.860	1.107	0.952	
2636.50	41055	Mid-High	LTE Band 41	20	25.0	24.14	-0.06	0	852D0	QPSK	1	99	10 mm	bottom	1:1.58	0.738	1.219	0.900	
2680.00	41490	High	LTE Band 41	20	25.0	23.88	0.11	0	852D0	QPSK	1	0	10 mm	bottom	1:1.58	0.691	1.294	0.894	
2506.00	39750	Low	LTE Band 41	20	24.0	23.51	-0.01	1	852D0	QPSK	50	50	10 mm	bottom	1:1.58	0.633	1.119	0.708	
2549.50	40185	Low-Mid	LTE Band 41	20	24.0	23.58	-0.02	1	852D0	QPSK	50	50	10 mm	bottom	1:1.58	0.757	1.102	0.834	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	-0.05	1	852D0	QPSK	50	50	10 mm	bottom	1:1.58	0.722	1.081	0.780	
2636.50	41055	Mid-High	LTE Band 41	20	24.0	23.15	-0.01	1	852D0	QPSK	50	0	10 mm	bottom	1:1.58	0.606	1.216	0.737	
2680.00	41490	High	LTE Band 41	20	24.0	22.95	0.01	1	852D0	QPSK	50	0	10 mm	bottom	1:1.58	0.584	1.274	0.744	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.63	-0.02	1	852D0	QPSK	100	0	10 mm	bottom	1:1.58	0.726	1.089	0.791	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.01	0	852D0	QPSK	1	99	10 mm	right	1:1.58	0.069	1.107	0.076	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	0.13	1	852D0	QPSK	50	50	10 mm	right	1:1.58	0.054	1.081	0.058	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	-0.01	0	852D0	QPSK	1	99	10 mm	left	1:1.58	0.356	1.107	0.394	
2593.00	40620	Mid	LTE Band 41	20	24.0	23.66	-0.02	1	852D0	QPSK	50	50	10 mm	left	1:1.58	0.289	1.081	0.312	
2593.00	40620	Mid	LTE Band 41	20	25.0	24.56	0.00	0	852D0	QPSK	1	99	10 mm	bottom	1:1.58	0.876	1.107	0.970	A26
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Note: Blue entry represents variability measurement.

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 51 of 70	

**Table 11-21
WLAN Hotspot SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	20.5	19.71	0.16	10 mm	1	252D4	1	back	99.3	0.345	0.217	1.199	1.007	0.262	
2437	6	802.11b	DSSS	22	20.5	19.71	0.05	10 mm	1	252D4	1	front	99.3	0.262	-	1.199	1.007	-	
2437	6	802.11b	DSSS	22	20.5	19.71	-0.03	10 mm	1	252D4	1	top	99.3	0.179	-	1.199	1.007	-	
2437	6	802.11b	DSSS	22	20.5	19.71	0.02	10 mm	1	252D4	1	left	99.3	0.177	-	1.199	1.007	-	
2462	11	802.11b	DSSS	22	20.5	20.27	0.02	10 mm	2	252D4	1	back	99.3	0.467	0.278	1.054	1.007	0.295	
2462	11	802.11b	DSSS	22	20.5	20.27	0.11	10 mm	2	252D4	1	front	99.3	0.293	-	1.054	1.007	-	
2462	11	802.11b	DSSS	22	20.5	20.27	0.03	10 mm	2	252D4	1	top	99.3	0.607	0.410	1.054	1.007	0.435	A28
2462	11	802.11b	DSSS	22	20.5	20.27	0.04	10 mm	2	252D4	1	left	99.3	0.194	-	1.054	1.007	-	
5825	165	802.11a	OFDM	20	15.5	15.19	0.09	10 mm	1	853E5	6	back	99.2	0.942	0.444	1.074	1.008	0.481	
5825	165	802.11a	OFDM	20	15.5	15.19	0.04	10 mm	1	853E5	6	front	99.2	0.149	0.078	1.074	1.008	0.084	
5825	165	802.11a	OFDM	20	15.5	15.19	0.03	10 mm	1	853E5	6	top	99.2	0.215	0.103	1.074	1.008	0.112	
5825	165	802.11a	OFDM	20	15.5	15.19	0.02	10 mm	1	853E5	6	left	99.2	0.175	-	1.074	1.008	-	
5745	149	802.11a	OFDM	20	15.5	15.25	-0.06	10 mm	2	853E5	6	back	99.2	0.943	0.474	1.059	1.008	0.506	A30
5745	149	802.11a	OFDM	20	15.5	15.25	0.05	10 mm	2	853E5	6	front	99.2	0.299	0.149	1.059	1.008	0.159	
5745	149	802.11a	OFDM	20	15.5	15.25	0.02	10 mm	2	853E5	6	top	99.2	0.435	0.199	1.059	1.008	0.212	
5745	149	802.11a	OFDM	20	15.5	15.25	0.05	10 mm	2	853E5	6	left	99.2	0.254	-	1.059	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

11.4 Standalone Phablet SAR Data

**Table 11-22
WLAN Phablet SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maxim um Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5260	52	802.11a	OFDM	20	15.5	14.76	0.11	0 mm	1	853E5	6	back	99.2	6.066	0.615	1.186	1.008	0.735	
5260	52	802.11a	OFDM	20	15.5	14.76	0.02	0 mm	1	853E5	6	front	99.2	2.905	-	1.186	1.008	-	
5260	52	802.11a	OFDM	20	15.5	14.76	0.12	0 mm	1	853E5	6	top	99.2	0.847	-	1.186	1.008	-	
5260	52	802.11a	OFDM	20	15.5	14.76	0.17	0 mm	1	853E5	6	left	99.2	0.975	-	1.186	1.008	-	
5280	56	802.11a	OFDM	20	15.5	14.95	0.08	0 mm	2	853E5	6	back	99.2	4.156	0.677	1.135	1.008	0.775	
5280	56	802.11a	OFDM	20	15.5	14.95	0.10	0 mm	2	853E5	6	front	99.2	0.924	-	1.135	1.008	-	
5280	56	802.11a	OFDM	20	15.5	14.95	0.02	0 mm	2	853E5	6	top	99.2	0.870	-	1.135	1.008	-	
5280	56	802.11a	OFDM	20	15.5	14.95	0.02	0 mm	2	853E5	6	left	99.2	0.585	-	1.135	1.008	-	
5720	144	802.11a	OFDM	20	15.5	15.45	0.02	0 mm	1	853E5	6	back	99.2	11.374	0.924	1.012	1.008	0.943	
5720	144	802.11a	OFDM	20	15.5	15.45	0.04	0 mm	1	853E5	6	front	99.2	2.991	-	1.012	1.008	-	
5720	144	802.11a	OFDM	20	15.5	15.45	0.02	0 mm	1	853E5	6	top	99.2	1.488	-	1.012	1.008	-	
5720	144	802.11a	OFDM	20	15.5	15.45	0.08	0 mm	1	853E5	6	left	99.2	0.635	-	1.012	1.008	-	
5720	144	802.11a	OFDM	20	15.5	15.39	-0.07	0 mm	2	853E5	6	back	99.2	19.525	1.630	1.026	1.008	1.686	A31
5720	144	802.11a	OFDM	20	15.5	15.39	0.03	0 mm	2	853E5	6	front	99.2	5.813	0.549	1.026	1.008	0.568	
5720	144	802.11a	OFDM	20	15.5	15.39	-0.04	0 mm	2	853E5	6	top	99.2	2.752	-	1.026	1.008	-	
5720	144	802.11a	OFDM	20	15.5	15.39	0.02	0 mm	2	853E5	6	left	99.2	1.021	-	1.026	1.008	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet											
Spatial Peak								4.0 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 10 grams											

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 52 of 70

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.
11. This device supports dynamic antenna tuning for some bands. Per FCC Guidance, SAR was measured according to the normally required SAR measurement configurations with the tuner active. The auto-tune state determined by the device was verified before and after each SAR measurement and is listed in the tables above. Please see Section 14 for supplemental data.
12. This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.3. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 53 of 70

- Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

- LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.5.4.
- MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
- A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
- Per FCC KDB Publication 447498 D01v06, when the reported (scaled) for LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was > 0.6 W/kg, testing at the other channels was required for such test configurations.
- TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

WLAN Notes:

- For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.6.5 for more information.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.6.6 for more information.
- Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06. Please see Section 12 for complete analysis.
- When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
- When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
- The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 54 of 70

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

When standalone SAR is not required to be measured, per FCC KDB 447498 D01v06 4.3.2 b), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{18.75} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)	Separation Distance (Phablet)	Estimated SAR (Phablet)
	[MHz]	[dBm]	[mm]	[W/kg]	[mm]	[W/kg]
Bluetooth	2480	12.00	15	0.224	5	0.269

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v06, the maximum power of the channel was rounded to the nearest mW before calculation.

Main antenna SAR testing was not required for phablet exposure conditions per FCC KDB 648474 D04v01r03. Therefore, no further analysis was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 55 of 70

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.180	0.882	0.428	1.062	0.608	1.490
	GSM 1900	0.079	0.882	0.428	0.961	0.507	1.389
	UMTS 850	0.198	0.882	0.428	1.080	0.626	1.508
	LTE Band 12	0.141	0.882	0.428	1.023	0.569	1.451
	LTE Band 13	0.169	0.882	0.428	1.051	0.597	1.479
	LTE Band 5 (Cell)	0.190	0.882	0.428	1.072	0.618	1.500
	LTE Band 4 (AWS)	0.131	0.882	0.428	1.013	0.559	1.441
	LTE Band 41	0.103	0.882	0.428	0.985	0.531	1.413

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.180	0.163	0.292	0.343	0.472	0.635
	GSM 1900	0.079	0.163	0.292	0.242	0.371	0.534
	UMTS 850	0.198	0.163	0.292	0.361	0.490	0.653
	LTE Band 12	0.141	0.163	0.292	0.304	0.433	0.596
	LTE Band 13	0.169	0.163	0.292	0.332	0.461	0.624
	LTE Band 5 (Cell)	0.190	0.163	0.292	0.353	0.482	0.645
	LTE Band 4 (AWS)	0.131	0.163	0.292	0.294	0.423	0.586
	LTE Band 41	0.103	0.163	0.292	0.266	0.395	0.558

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.180	0.882	0.292	1.062	0.472	1.354
	GSM 1900	0.079	0.882	0.292	0.961	0.371	1.253
	UMTS 850	0.198	0.882	0.292	1.080	0.490	1.372
	LTE Band 12	0.141	0.882	0.292	1.023	0.433	1.315
	LTE Band 13	0.169	0.882	0.292	1.051	0.461	1.343
	LTE Band 5 (Cell)	0.190	0.882	0.292	1.072	0.482	1.364
	LTE Band 4 (AWS)	0.131	0.882	0.292	1.013	0.423	1.305
	LTE Band 41	0.103	0.882	0.292	0.985	0.395	1.277

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 56 of 70

Table 12-5
Simultaneous Transmission Scenario with 5 GHz Ant 1 and 2.4 GHz Ant 2 WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM 850	0.180	0.163	0.428	0.343	0.608	0.771
	GSM 1900	0.079	0.163	0.428	0.242	0.507	0.670
	UMTS 850	0.198	0.163	0.428	0.361	0.626	0.789
	LTE Band 12	0.141	0.163	0.428	0.304	0.569	0.732
	LTE Band 13	0.169	0.163	0.428	0.332	0.597	0.760
	LTE Band 5 (Cell)	0.190	0.163	0.428	0.353	0.618	0.781
	LTE Band 4 (AWS)	0.131	0.163	0.428	0.294	0.559	0.722
	LTE Band 41	0.103	0.163	0.428	0.266	0.531	0.694

12.4 Body-Worn Simultaneous Transmission Analysis

Note: For SAR summation for body-worn back side at 15mm, the SAR values at 10mm for 5 GHz WLAN were used since the 10mm test distance was more conservative.

Table 12-6
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.326	0.116	0.113	0.442	0.439	0.555
	GSM 1900	0.141	0.116	0.113	0.257	0.254	0.370
	UMTS 850	0.342	0.116	0.113	0.458	0.455	0.571
	LTE Band 12	0.291	0.116	0.113	0.407	0.404	0.520
	LTE Band 13	0.420	0.116	0.113	0.536	0.533	0.649
	LTE Band 5 (Cell)	0.325	0.116	0.113	0.441	0.438	0.554
	LTE Band 4 (AWS)	0.244	0.116	0.113	0.360	0.357	0.473
	LTE Band 41	0.256	0.116	0.113	0.372	0.369	0.485

Table 12-7
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.326	0.481	0.508	0.807	0.834	1.315
	GSM 1900	0.141	0.481	0.508	0.622	0.649	1.130
	UMTS 850	0.342	0.481	0.508	0.823	0.850	1.331
	LTE Band 12	0.291	0.481	0.508	0.772	0.799	1.280
	LTE Band 13	0.420	0.481	0.508	0.901	0.928	1.409
	LTE Band 5 (Cell)	0.325	0.481	0.508	0.806	0.833	1.314
	LTE Band 4 (AWS)	0.244	0.481	0.508	0.725	0.752	1.233
	LTE Band 41	0.256	0.481	0.508	0.737	0.764	1.245

FCC ID: A3LSC01J	 	SAR EVALUATION REPORT	Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 57 of 70

Table 12-8

Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.326	0.116	0.508	0.442	0.834	0.950
	GSM 1900	0.141	0.116	0.508	0.257	0.649	0.765
	UMTS 850	0.342	0.116	0.508	0.458	0.850	0.966
	LTE Band 12	0.291	0.116	0.508	0.407	0.799	0.915
	LTE Band 13	0.420	0.116	0.508	0.536	0.928	1.044
	LTE Band 5 (Cell)	0.325	0.116	0.508	0.441	0.833	0.949
	LTE Band 4 (AWS)	0.244	0.116	0.508	0.360	0.752	0.868
	LTE Band 41	0.256	0.116	0.508	0.372	0.764	0.880

Table 12-9

Simultaneous Transmission Scenario with 5 GHz Ant 1 and 2.4 GHz Ant 2 WLAN (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM 850	0.326	0.481	0.113	0.807	0.439	0.920
	GSM 1900	0.141	0.481	0.113	0.622	0.254	0.735
	UMTS 850	0.342	0.481	0.113	0.823	0.455	0.936
	LTE Band 12	0.291	0.481	0.113	0.772	0.404	0.885
	LTE Band 13	0.420	0.481	0.113	0.901	0.533	1.014
	LTE Band 5 (Cell)	0.325	0.481	0.113	0.806	0.438	0.919
	LTE Band 4 (AWS)	0.244	0.481	0.113	0.725	0.357	0.838
	LTE Band 41	0.256	0.481	0.113	0.737	0.369	0.850

Table 12-10

Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.5 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM 850	0.326	0.224	0.550
	GSM 1900	0.141	0.224	0.365
	UMTS 850	0.342	0.224	0.566
	LTE Band 12	0.291	0.224	0.515
	LTE Band 13	0.420	0.224	0.644
	LTE Band 5 (Cell)	0.325	0.224	0.549
	LTE Band 4 (AWS)	0.244	0.224	0.468
	LTE Band 41	0.256	0.224	0.480

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 58 of 70

12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

(*) For test positions that were not required to be evaluated for WLAN SAR per FCC KDB Publication 248227, the worst case WLAN Hotspot SAR result was used for simultaneous transmission analysis.

Table 12-11
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.567	0.262	0.435	0.829	1.002	1.264
	GPRS 1900	0.219	0.262	0.435	0.481	0.654	0.916
	UMTS 850	0.607	0.262	0.435	0.869	1.042	1.304
	LTE Band 12	0.482	0.262	0.435	0.744	0.917	1.179
	LTE Band 13	0.640	0.262	0.435	0.902	1.075	1.337
	LTE Band 5 (Cell)	0.607	0.262	0.435	0.869	1.042	1.304
	LTE Band 4 (AWS)	0.909	0.262	0.435	1.171	1.344	See Note 1
	LTE Band 41	0.970	0.262	0.435	1.232	1.405	See Note 1

Table 12-12
Simultaneous Transmission Scenario with 5 GHz WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.567	0.481	0.506	1.048	1.073	1.554
	GPRS 1900	0.219	0.481	0.506	0.700	0.725	1.206
	UMTS 850	0.607	0.481	0.506	1.088	1.113	1.594
	LTE Band 12	0.482	0.481	0.506	0.963	0.988	1.469
	LTE Band 13	0.640	0.481	0.506	1.121	1.146	See Note 1
	LTE Band 5 (Cell)	0.607	0.481	0.506	1.088	1.113	1.594
	LTE Band 4 (AWS)	0.909	0.481	0.506	1.390	1.415	See Note 1
	LTE Band 41	0.970	0.481	0.506	1.451	1.476	See Note 1

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 59 of 70

Table 12-13
Simultaneous Transmission Scenario with 2.4 GHz Ant 1 and 5 GHz Ant 2 WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.567	0.262	0.506	0.829	1.073	1.335
	GPRS 1900	0.219	0.262	0.506	0.481	0.725	0.987
	UMTS 850	0.607	0.262	0.506	0.869	1.113	1.375
	LTE Band 12	0.482	0.262	0.506	0.744	0.988	1.250
	LTE Band 13	0.640	0.262	0.506	0.902	1.146	1.408
	LTE Band 5 (Cell)	0.607	0.262	0.506	0.869	1.113	1.375
	LTE Band 4 (AWS)	0.909	0.262	0.506	1.171	1.415	See Note 1
	LTE Band 41	0.970	0.262	0.506	1.232	1.476	See Note 1

Table 12-14
Simultaneous Transmission Scenario with 5 GHz Ant 1 and 2.4 GHz Ant 2 WLAN (Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.567	0.481	0.435	1.048	1.002	1.483
	GPRS 1900	0.219	0.481	0.435	0.700	0.654	1.135
	UMTS 850	0.607	0.481	0.435	1.088	1.042	1.523
	LTE Band 12	0.482	0.481	0.435	0.963	0.917	1.398
	LTE Band 13	0.640	0.481	0.435	1.121	1.075	1.556
	LTE Band 5 (Cell)	0.607	0.481	0.435	1.088	1.042	1.523
	LTE Band 4 (AWS)	0.909	0.481	0.435	1.390	1.344	See Note 1
	LTE Band 41	0.970	0.481	0.435	1.451	1.405	See Note 1

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
Page 60 of 70		

Note 1: Itemized Simultaneous SAR Tables

Table 12-15
Simultaneous Transmission Scenario with LTE B13 and WLAN (Hotspot at 1.0 cm)

Simult Tx	Configuration	LTE Band 13 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Hotspot SAR	Back	0.597	0.481	0.506	1.584
	Front	0.640	0.084	0.159	0.883
	Top	-	0.112	0.212	0.324
	Bottom	0.372	-	-	0.372
	Right	0.229	-	-	0.229
	Left	0.189	0.481*	0.506*	1.176

Table 12-16
Simultaneous Transmission Scenario with LTE B4 and WLAN (Hotspot at 1.0 cm)

Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Hotspot SAR	Back	0.475	0.262	0.295	1.032	Hotspot SAR	Back	0.475	0.481	0.506	1.462
	Front	0.453	0.262*	0.435*	1.150		Front	0.453	0.084	0.159	0.696
	Top	-	0.262*	0.435	0.697		Top	-	0.112	0.212	0.324
	Bottom	0.909	-	-	0.909		Bottom	0.909	-	-	0.909
	Right	0.077	-	-	0.077		Right	0.077	-	-	0.077
	Left	0.167	0.262*	0.435*	0.864		Left	0.167	0.481*	0.506*	1.154
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Hotspot SAR	Back	0.475	0.262	0.506	1.243	Hotspot SAR	Back	0.475	0.481	0.295	1.251
	Front	0.453	0.262*	0.159	0.874		Front	0.453	0.084	0.435*	0.972
	Top	-	0.262*	0.212	0.474		Top	-	0.112	0.435	0.547
	Bottom	0.909	-	-	0.909		Bottom	0.909	-	-	0.909
	Right	0.077	-	-	0.077		Right	0.077	-	-	0.077
	Left	0.167	0.262*	0.506*	0.935		Left	0.167	0.481*	0.435*	1.083

Table 12-17
Simultaneous Transmission Scenario with LTE B41 and WLAN (Hotspot at 1.0 cm)

Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Hotspot SAR	Back	0.523	0.262	0.295	1.080	Hotspot SAR	Back	0.523	0.481	0.506	1.510
	Front	0.500	0.262*	0.435*	1.197		Front	0.500	0.084	0.159	0.743
	Top	-	0.262*	0.435	0.697		Top	-	0.112	0.212	0.324
	Bottom	0.970	-	-	0.970		Bottom	0.970	-	-	0.970
	Right	0.076	-	-	0.076		Right	0.076	-	-	0.076
	Left	0.394	0.262*	0.435*	1.091		Left	0.394	0.481*	0.506*	1.381
Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 41 SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3			1	2	3	1+2+3
Hotspot SAR	Back	0.523	0.262	0.506	1.291	Hotspot SAR	Back	0.523	0.481	0.295	1.299
	Front	0.500	0.262*	0.159	0.921		Front	0.500	0.084	0.435*	1.019
	Top	-	0.262*	0.212	0.474		Top	-	0.112	0.435	0.547
	Bottom	0.970	-	-	0.970		Bottom	0.970	-	-	0.970
	Right	0.076	-	-	0.076		Right	0.076	-	-	0.076
	Left	0.394	0.262*	0.506*	1.162		Left	0.394	0.481*	0.435*	1.310

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 61 of 70

12.6 Phablet SAR Simultaneous Transmission Analysis

Main antenna, 2.4 GHz WIFI SAR testing was not required for extremity exposure conditions per FCC KDB648474 D04v01r02. Therefore, no further analysis beyond Table 12-12 was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 62 of 70

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1750	1732.50	20175	LTE Band 4 (AWS), 20 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	bottom	10 mm	0.829	0.872	1.05	N/A	N/A	N/A	N/A
2600	2593.00	40620	LTE Band 41, 20 MHz Bandwidth	QPSK, 1 RB, 99 RB Offset	bottom	10 mm	0.860	0.876	1.02	N/A	N/A	N/A	N/A

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 63 of 70

14 ADDITIONAL TUNER TESTING PER FCC GUIDANCE

The following test procedures were followed to demonstrate that the SAR results in Section 11 represented the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR was measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements were evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.

To evaluate all of the tuner states, the 144 tuner states were divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement was measured among the configurations. Single point time-sweep measurements were performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. The tuner state was able to be established remotely so that the device was not moved for the entire series of single point SAR for the tuner states in each combination. The SAR probe remained stationary at the same position throughout the entire series of single point measurements for each combination.

The operational description contains more information about the design and implementation of the dynamic antenna tuning.

**Table 14-1
Supplemental Head SAR Data**

Supplemental Head ERM Data																												
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 58)	Default (State 56)	State 2	State 3	State 5	State 11	State 27	State 35	State 43	State 51	State 59	State 62	State 67	State 75	State 83	State 91	State 107	State 115	State 124	State 131
LTE B 12	QPSK	707.5	23095	1	25	Right Cheek	N/A	0.122	0.140	0.139	0.086	0.080	0.068	0.036	0.070	0.021	0.078	0.017	0.119	0.094	0.043	0.112	0.058	0.131	0.019	0.094	0.028	0.124
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 4	State 9	State 12	State 20	State 28	State 36	State 44	State 52	State 66	State 68	State 76	State 84	State 92	State 100	State 116	State 132	State 137	State 141
LTE B 13	QPSK	782	23230	1	25	Right Cheek	N/A	0.150	0.180	0.184	0.165	0.114	0.077	0.151	0.074	0.012	0.164	0.044	0.078	0.051	0.120	0.049	0.153	0.107	0.081	0.136	0.078	0.043
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 13	State 16	State 21	State 29	State 37	State 45	State 53	State 61	State 69	State 77	State 85	State 93	State 101	State 117	State 125	State 133	State 139	State 141
LTE B5	QPSK	836.5	20525	1	25	Right Cheek	N/A	0.168	0.188	0.193	0.106	0.063	0.164	0.105	0.140	0.161	0.055	0.162	0.070	0.144	0.075	0.150	0.122	0.106	0.028	0.146	0.084	0.054
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 1	State 14	State 22	State 30	State 38	State 46	State 54	State 70	State 78	State 86	State 87	State 94	State 110	State 118	State 123	State 126	State 134	State 141
UMTS B5	RMF	836.6	4183	N/A	N/A	Right Cheek	N/A	0.181	0.209	0.212	0.207	0.099	0.171	0.103	0.199	0.172	0.042	0.058	0.157	0.070	0.058	0.171	0.162	0.112	0.051	0.024	0.170	0.046

**Table 14-2
Supplemental Body SAR Data**

Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 96)	Default (State 96)	State 7	State 15	State 23	State 31	State 39	State 47	State 55	State 63	State 71	State 79	State 87	State 95	State 103	State 111	State 119	State 127	State 135	State 143
LTE B 12	QPSK	707.5	23095	1	25	Front Side	10 mm	0.417	0.453	0.450	0.216	0.074	0.328	0.155	0.381	0.144	0.414	0.291	0.069	0.308	0.400	0.361	0.165	0.391	0.214	0.378	0.316	0.076
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 24	State 32	State 48	State 50	State 56	State 64	State 72	State 80	State 88	State 102	State 104	State 109	State 112	State 120	State 122	State 128	State 136	State 144
LTE B 13	QPSK	782	23230	1	25	Front Side	10 mm	0.568	0.664	0.655	0.469	0.167	0.406	0.301	0.599	0.448	0.282	0.377	0.098	0.311	0.215	0.042	0.449	0.191	0.135	0.542	0.391	0.065
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 6	State 17	State 19	State 25	State 33	State 41	State 49	State 57	State 65	State 73	State 81	State 89	State 99	State 105	State 108	State 113	State 121	State 129
LTE B5	QPSK	836.5	20525	1	25	Front Side	10 mm	0.536	0.544	0.543	0.484	0.163	0.493	0.471	0.210	0.510	0.315	0.487	0.413	0.471	0.415	0.135	0.483	0.230	0.101	0.459	0.242	0.457
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																			
									Auto-Tune (State 2)	Default (State 2)	State 8	State 10	State 18	State 26	State 34	State 40	State 42	State 58	State 60	State 74	State 82	State 90	State 96	State 98	State 106	State 114	State 130	State 138
UMTS B5	RMTC	836.6	4183	N/A	N/A	Back Side	10 mm	0.555	0.659	0.660	0.465	0.410	0.127	0.458	0.171	0.530	0.507	0.495	0.499	0.513	0.385	0.097	0.492	0.499	0.178	0.442	0.465	0.356

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 64 of 70

15 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
SPEAG	D750V3	750 MHz SAR Dipole	2/16/2016	Annual	2/16/2017	1046
SPEAG	D750V3	750 MHz SAR Dipole	3/16/2016	Annual	3/16/2017	1054
SPEAG	D835V2	835 MHz SAR Dipole	4/14/2016	Annual	4/14/2017	4d119
SPEAG	D1750V2	1750 MHz SAR Dipole	4/13/2016	Annual	4/13/2017	1051
SPEAG	D1765V2	1765 MHz SAR Dipole	5/11/2016	Annual	5/11/2017	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	4/12/2016	Annual	4/12/2017	5d141
SPEAG	D2450V2	2450 MHz SAR Dipole	8/20/2015	Annual	8/20/2016	719
SPEAG	D2450V2	2450 MHz SAR Dipole	2/18/2016	Annual	2/18/2017	882
SPEAG	D2600V2	2600 MHz SAR Dipole	10/21/2015	Annual	10/21/2016	1071
SPEAG	DSGH2V2	5 GHz SAR Dipole	2/25/2016	Annual	2/25/2017	1120
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/19/2016	Annual	2/19/2017	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/11/2016	Annual	5/11/2017	859
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/18/2016	Annual	2/18/2017	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/27/2015	Annual	10/27/2016	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/14/2016	Annual	3/14/2017	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2016	Annual	4/14/2017	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/11/2015	Annual	11/11/2016	1415
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3209
SPEAG	ES3DV3	SAR Probe	2/19/2016	Annual	2/19/2017	3213
SPEAG	ES3DV3	SAR Probe	2/19/2016	Annual	2/19/2017	3318
SPEAG	ES3DV3	SAR Probe	3/18/2016	Annual	3/18/2017	3319
SPEAG	ES3DV3	SAR Probe	10/29/2015	Annual	10/29/2016	3333
SPEAG	ES3DV3	SAR Probe	11/17/2015	Annual	11/17/2016	3334
SPEAG	EX3DV4	SAR Probe	2/22/2016	Annual	2/22/2017	3914
SPEAG	EX3DV4	SAR Probe	4/19/2016	Annual	4/19/2017	7406
SPEAG	EX3DV4	SAR Probe	5/17/2016	Annual	5/17/2017	7409
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2016	Annual	5/10/2017	1070
SPEAG	DAK-12	Dielectric Assessment Kit (10MHz - 3GHz)	3/1/2016	Annual	3/1/2017	1102
Rohde & Schwarz	CMU200	Base Station Simulator	12/2/2015	Annual	12/2/2016	833855/0010
Rohde & Schwarz	CMW500	Radio Communication Tester	6/3/2016	Annual	6/3/2017	108843
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Pasternack	NC-100	Torque Wrench	5/21/2015	Biennial	5/21/2017	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-53W2	Attenuator (3dB)	CBT	N/A	CBT	120
Mitutoyo	CD-6°CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R897950903
Mini-Circuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Gigatronics	80701A	(0.05-18GHz) Power Sensor	11/4/2015	Annual	11/4/2016	1833460
Gigatronics	8651A	Universal Power Meter	11/4/2015	Annual	11/4/2016	8650319
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150194979
Control Company	4040	Digital Thermometer	3/18/2015	Biennial	3/18/2017	150194982
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053059
Control Company	4353	Long Stem Thermometer	1/22/2015	Biennial	1/22/2017	150053081
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261694
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
Anritsu	ML2438A	Power Meter	3/3/2016	Annual	3/3/2017	1070030
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2496A	Power Meter	2/28/2016	Annual	2/28/2017	1306009
Anritsu	MA2481A	Power Sensor	3/3/2016	Annual	3/3/2017	5318
Anritsu	MA2411B	Pulse Power Sensor	2/28/2016	Annual	2/28/2017	1207470
Anritsu	MT8820C	Radio Communication Analyzer	9/1/2015	Annual	9/1/2016	620144419
Anritsu	MA24106A	USB Power Sensor	3/28/2016	Annual	3/28/2017	1344554
Anritsu	MA24106A	USB Power Sensor	3/4/2016	Annual	3/4/2017	1344555
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433978
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/2/2016	Annual	3/2/2017	MY45470194
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/2/2016	Annual	3/2/2017	JP38020182
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	E4438C	ESG Vector Signal Generator	3/2/2016	Annual	3/2/2017	MY47270002
Agilent	E4432B	ESG-D Series Signal Generator	3/5/2016	Annual	3/5/2017	US40053896
Agilent	N9020A	MXA Signal Analyzer	11/5/2015	Annual	11/5/2016	US46470561
Agilent	N5182A	MXG Vector Signal Generator	11/6/2015	Annual	11/6/2016	MY47420603
Agilent	8753ES	S-Parameter Network Analyzer	3/3/2016	Annual	3/3/2017	US39170122
Agilent	E5515C	Wireless Communications Test Set	1/29/2016	Biennial	1/29/2018	GB46310798
Agilent	N4010A	Wireless Connectivity Test Set	CBT	N/A	CBT	GB44450273

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are

FCC ID: A3LSC01J		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset		Page 65 of 70

made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 66 of 70

16 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 67 of 70

17 CONCLUSION

17.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset
		Page 68 of 70

18 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 69 of 70

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSC01J	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: 0Y1607081234.A3L	Test Dates: 07/11/16 - 08/16/16	DUT Type: Portable Handset	Page 70 of 70

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D0

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.91 \text{ S/m}$; $\epsilon_r = 41.697$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-12-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.36 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.188 W/kg

SAR(1 g) = 0.150 W/kg



0 dB = 0.162 W/kg = -7.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.439 \text{ S/m}$; $\epsilon_r = 39.029$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-11-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(5.18, 5.18, 5.18); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.728 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0950 W/kg

SAR(1 g) = 0.060 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D4

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 40.327$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-27-2016; Ambient Temp: 20.3°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.77 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.227 W/kg

SAR(1 g) = 0.181 W/kg



0 dB = 0.195 W/kg = -7.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: C9186

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.853 \text{ S/m}$; $\epsilon_r = 41.243$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 08-08-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3334; ConvF(6.56, 6.56, 6.56); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Right Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.97 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.125 W/kg

SAR(1 g) = 0.122 W/kg



0 dB = 0.113 W/kg = -9.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.923 \text{ S/m}$; $\epsilon_r = 40.722$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-17-2016; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(10.73, 10.73, 10.73); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Right Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.35 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.177 W/kg

SAR(1 g) = 0.150 W/kg



0 dB = 0.167 W/kg = -7.77 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D4

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.9 \text{ S/m}$; $\epsilon_r = 40.328$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-27-2016; Ambient Temp: 20.3°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.67 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.168 W/kg



0 dB = 0.182 W/kg = -7.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.364 \text{ S/m}$; $\epsilon_r = 39.354$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-19-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(5.39, 5.39, 5.39); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.40 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.194 W/kg

SAR(1 g) = 0.126 W/kg



0 dB = 0.148 W/kg = -8.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852BF

Communication System: UID 0, LTE Band 41; Frequency: 2593 MHz; Duty Cycle: 1:1.58

Medium: 2600 Head Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.003 \text{ S/m}$; $\epsilon_r = 39.724$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-18-2016; Ambient Temp: 23.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(4.46, 4.46, 4.46); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Left Head, Cheek, Mid.ch, QPSK
20 MHz Bandwidth, 1 RB, 99 RB Offset


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.943 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.173 W/kg

SAR(1 g) = 0.093 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D9

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.869 \text{ S/m}$; $\epsilon_r = 38.538$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-20-2016; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3213; ConvF(4.58, 4.58, 4.58); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek, Ch 6, 1 Mbps, Antenna 1


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.777 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.705 W/kg



0 dB = 0.906 W/kg = -0.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D9

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 5.097 \text{ S/m}$; $\epsilon_r = 36.009$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-15-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(4.74, 4.74, 4.74); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth

Right Head, Tilt, Ch 149, 6 Mbps, Antenna 2


Area Scan (13x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 4.199 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.255 W/kg



0 dB = 0.685 W/kg = -1.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.898$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.11 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.370 W/kg

SAR(1 g) = 0.272 W/kg



0 dB = 0.301 W/kg = -5.21 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, GSM GPRS; 1 Tx slot; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.898$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Front side, Mid.ch, 1 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.76 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.780 W/kg

SAR(1 g) = 0.476 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.561 \text{ S/m}$; $\epsilon_r = 52.091$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-11-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.832 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.172 W/kg

SAR(1 g) = 0.107 W/kg



0 dB = 0.129 W/kg = -8.89 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, GSM GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.549 \text{ S/m}$; $\epsilon_r = 51.795$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-14-2016; Ambient Temp: 22.9°C; Tissue Temp: 22.3°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 2 Tx Slots


Area Scan (10x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.87 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.278 W/kg

SAR(1 g) = 0.167 W/kg



0 dB = 0.206 W/kg = -6.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.898$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 18.47 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.424 W/kg

SAR(1 g) = 0.313 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.898$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.03 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.877 W/kg

SAR(1 g) = 0.555 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: C9186

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 55.939$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-16-2016; Ambient Temp: 21.6°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Back side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.19 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.361 W/kg

SAR(1 g) = 0.252 W/kg



0 dB = 0.288 W/kg = -5.41 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: C9186

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.932 \text{ S/m}$; $\epsilon_r = 55.939$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-16-2016; Ambient Temp: 21.6°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 12, Body SAR, Front side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.34 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.688 W/kg

SAR(1 g) = 0.417 W/kg



0 dB = 0.501 W/kg = -3.00 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 853E5

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 54.71$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-22-2016; Ambient Temp: 21.3°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Body SAR, Back side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.23 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.533 W/kg

SAR(1 g) = 0.373 W/kg



0 dB = 0.426 W/kg = -3.71 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 853E5

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 1 \text{ S/m}$; $\epsilon_r = 54.71$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-22-2016; Ambient Temp: 21.3°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 13, Body SAR, Front side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.09 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.939 W/kg

SAR(1 g) = 0.568 W/kg



0 dB = 0.682 W/kg = -1.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.899$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.70 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.391 W/kg

SAR(1 g) = 0.287 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852F1

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.997 \text{ S/m}$; $\epsilon_r = 52.899$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 5 (Cell.), Body SAR, Front side, Mid.ch
10 MHz Bandwidth, QPSK, 1 RB, 25 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.65 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.873 W/kg

SAR(1 g) = 0.536 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.482 \text{ S/m}$; $\epsilon_r = 52.216$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-18-2016; Ambient Temp: 21.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.09 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.370 W/kg

SAR(1 g) = 0.234 W/kg



0 dB = 0.323 W/kg = -4.91 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5$ MHz; $\sigma = 1.476$ S/m; $\epsilon_r = 51.734$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2016; Ambient Temp: 21.9°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (11x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.56 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.872 W/kg



0 dB = 1.29 W/kg = 1.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D0

Communication System: UID 0, LTE Band 4; Frequency: 2593 MHz; Duty Cycle: 1:1.58

Medium: 2600 Body Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.154 \text{ S/m}$; $\epsilon_r = 52.557$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-19-2016; Ambient Temp: 23.5°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Body SAR, Back side, Mid.ch

20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.70 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.457 W/kg

SAR(1 g) = 0.231 W/kg



0 dB = 0.364 W/kg = -4.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 852D0

Communication System: UID 0, LTE Band 41; Frequency: 2593 MHz; Duty Cycle: 1:1.58

Medium: 2600 Body Medium parameters used (interpolated):

$f = 2593 \text{ MHz}$; $\sigma = 2.153 \text{ S/m}$; $\epsilon_r = 52.322$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2016; Ambient Temp: 22.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 41, Body SAR, Bottom Edge, Mid.ch
20 MHz Bandwidth, QPSK, 1 RB, 99 RB Offset


Area Scan (11x11x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.24 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.79 W/kg

SAR(1 g) = 0.876 W/kg



0 dB = 1.43 W/kg = 1.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.972 \text{ S/m}$; $\epsilon_r = 52.778$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-21-2016; Ambient Temp: 22.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Back Side, Antenna 2


Area Scan (11x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.100 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.208 W/kg

SAR(1 g) = 0.106 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 252D4

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.972 \text{ S/m}$; $\epsilon_r = 52.778$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2016; Ambient Temp: 22.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 11, 1 Mbps, Top Edge, Antenna 2


Area Scan (11x11x1): Measurement grid: dx=5mm, dy=12mm

Zoom Scan (8x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.20 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.822 W/kg

SAR(1 g) = 0.410 W/kg



0 dB = 0.632 W/kg = -1.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 853E5

Communication System: UID 0, IEEE 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5720 \text{ MHz}$; $\sigma = 6.082 \text{ S/m}$; $\epsilon_r = 47.068$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, UNII-2C, 20 MHz Bandwidth, Antenna 2

Body SAR, Ch 144, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 8.336 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.82 W/kg

SAR(1 g) = 0.491 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 853E5

Communication System: UID 0, IEEE 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5745 \text{ MHz}$; $\sigma = 6.099 \text{ S/m}$; $\epsilon_r = 46.999$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, UNII-3, 20 MHz Bandwidth, Antenna 2

Body SAR, Ch 149, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 8.766 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 0.474 W/kg



0 dB = 1.14 W/kg = 0.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSC01J; Type: Portable Handset; Serial: 853E5

Communication System: UID 0, IEEE 802.11a; Frequency: 5720 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5720 \text{ MHz}$; $\sigma = 6.082 \text{ S/m}$; $\epsilon_r = 47.068$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, UNII-2C, 20 MHz Bandwidth, Antenna 2
Phablet SAR, Ch 144, 6 Mbps, Back Side


Area Scan (13x22x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 37.33 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 49.6 W/kg

SAR(10 g) = 1.63 W/kg



0 dB = 24.0 W/kg = 13.80 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.893 \text{ S/m}$; $\epsilon_r = 41.133$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-17-2016; Ambient Temp: 21.5°C; Tissue Temp: 21.1°C

Probe: EX3DV4 - SN7409; ConvF(10.73, 10.73, 10.73); Calibrated: 5/17/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/11/2016

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.29 W/kg

SAR(1 g) = 1.54 W/kg

Deviation(1 g) = -6.10 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.891 \text{ S/m}$; $\epsilon_r = 40.704$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-08-2016; Ambient Temp: 23.0°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3334; ConvF(6.56, 6.56, 6.56); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.41 W/kg

SAR(1 g) = 1.64 W/kg

Deviation(1 g) = -0.24%'



0 dB = 1.90 W/kg = 2.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.908 \text{ S/m}$; $\epsilon_r = 41.718$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-12-2016; Ambient Temp: 23.2°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3334; ConvF(6.37, 6.37, 6.37); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.69 W/kg

SAR(1 g) = 1.79 W/kg

Deviation(1 g) = -2.08%



0 dB = 2.06 W/kg = 3.14 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.899 \text{ S/m}$; $\epsilon_r = 40.348$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-27-2016; Ambient Temp: 20.3°C; Tissue Temp: 20.5°C

Probe: ES3DV3 - SN3318; ConvF(6.23, 6.23, 6.23); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/19/2016

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.80 W/kg

SAR(1 g) = 1.81 W/kg

Deviation(1 g) = -0.98%



0 dB = 2.16 W/kg = 3.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.382$ S/m; $\epsilon_r = 39.267$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-19-2016; Ambient Temp: 23.5°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3334; ConvF(5.39, 5.39, 5.39); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.89 W/kg

SAR(1 g) = 3.81 W/kg

Deviation(1 g) = 5.54%



0 dB = 4.74 W/kg = 6.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 38.932$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3334; ConvF(5.18, 5.18, 5.18); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.88 W/kg

SAR(1 g) = 3.77 W/kg

Deviation(1 g) = -2.08%



0 dB = 4.79 W/kg = 6.80 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 882

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.884 \text{ S/m}$; $\epsilon_r = 38.488$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-20-2016; Ambient Temp: 22.0°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3213; ConvF(4.58, 4.58, 4.58); Calibrated: 2/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.3 W/kg

SAR(1 g) = 5.38 W/kg

Deviation(1 g) = 6.53%



0 dB = 7.13 W/kg = 8.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Head Medium parameters used:

$f = 2600$ MHz; $\sigma = 2.011$ S/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-18-2016; Ambient Temp: 23.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3334; ConvF(4.46, 4.46, 4.46); Calibrated: 11/17/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 11/11/2015

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.6 W/kg

SAR(1 g) = 5.17 W/kg

Deviation(1 g) = -7.51%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.577 \text{ S/m}$; $\epsilon_r = 36.711$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-15-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(5.07, 5.07, 5.07); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.5 W/kg

SAR(1 g) = 3.65 W/kg

Deviation(1 g) = -7.24%



0 dB = 8.43 W/kg = 9.26 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.938 \text{ S/m}$; $\epsilon_r = 36.23$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-15-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(4.66, 4.66, 4.66); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 3.86 W/kg

Deviation(1 g) = -6.20%



0 dB = 9.10 W/kg = 9.59 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.108 \text{ S/m}$; $\epsilon_r = 36.001$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-15-2016; Ambient Temp: 23.0°C; Tissue Temp: 21.8°C

Probe: EX3DV4 - SN3914; ConvF(4.74, 4.74, 4.74); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.0 W/kg

SAR(1 g) = 3.69 W/kg

Deviation(1 g) = -6.70%



0 dB = 8.80 W/kg = 9.44 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1046

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.968 \text{ S/m}$; $\epsilon_r = 55.035$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-22-2016; Ambient Temp: 21.3°C; Tissue Temp: 20.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 03/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.59 W/kg

SAR(1 g) = 1.78 W/kg

Deviation(1 g) = 1.48%



0 dB = 2.07 W/kg = 3.16 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1054

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.971 \text{ S/m}$; $\epsilon_r = 55.529$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 08-16-2016; Ambient Temp: 21.6°C; Tissue Temp: 21.8°C

Probe: ES3DV3 - SN3209; ConvF(6.19, 6.19, 6.19); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 11/11/2015

Phantom: SAM Left; Type: SAM; Serial: 1688

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.56 W/kg

SAR(1 g) = 1.75 W/kg

Deviation(1 g) = 2.22%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.995 \text{ S/m}$; $\epsilon_r = 52.923$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-17-2016; Ambient Temp: 23.6°C; Tissue Temp: 22.1°C

Probe: ES3DV3 - SN3333; ConvF(6.25, 6.25, 6.25); Calibrated: 10/29/2015;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 10/27/2015

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.81 W/kg

SAR(1 g) = 1.93 W/kg

Deviation(1 g) = 5.58%



0 dB = 2.24 W/kg = 3.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750$ MHz; $\sigma = 1.501$ S/m; $\epsilon_r = 52.164$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-18-2016; Ambient Temp: 21.1°C; Tissue Temp: 21.6°C

Probe: EX3DV4 - SN7406; ConvF(7.78, 7.78, 7.78); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.80 W/kg

SAR(1 g) = 3.78 W/kg

Deviation(1 g) = 1.34%



0 dB = 5.65 W/kg = 7.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.58 \text{ S/m}$; $\epsilon_r = 51.988$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-11-2016; Ambient Temp: 22.7°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3319; ConvF(4.7, 4.7, 4.7); Calibrated: 3/18/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/14/2016

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 7.61 W/kg

SAR(1 g) = 4.2 W/kg

Deviation(1 g) = 6.06%



0 dB = 5.30 W/kg = 7.24 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 719

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.956 \text{ S/m}$; $\epsilon_r = 52.816$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2016; Ambient Temp: 22.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN7406; ConvF(7.24, 7.24, 7.24); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.7 W/kg

SAR(1 g) = 5.1 W/kg

Deviation(1 g) = -1.73%



0 dB = 8.51 W/kg = 9.30 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1071

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.164 \text{ S/m}$; $\epsilon_r = 52.532$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-19-2016; Ambient Temp: 23.5°C; Tissue Temp: 23.0°C

Probe: EX3DV4 - SN7406; ConvF(6.94, 6.94, 6.94); Calibrated: 4/19/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/14/2016

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.5 W/kg

SAR(1 g) = 5.69 W/kg

Deviation(1 g) = 3.64%



0 dB = 9.82 W/kg = 9.92 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.438 \text{ S/m}$; $\epsilon_r = 47.795$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(4.32, 4.32, 4.32); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 14.9 W/kg

SAR(1 g) = 3.71 W/kg; SAR(10 g) = 1.05 W/kg

Deviation(1 g) = -1.85%; Deviation(10 g) = -0.94%



0 dB = 8.67 W/kg = 9.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.888 \text{ S/m}$; $\epsilon_r = 47.282$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.63, 3.63, 3.63); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4;

Peak SAR (extrapolated) = 15.9 W/kg

SAR(1 g) = 3.89 W/kg; SAR(10 g) = 1.1 W/kg

Deviation(1 g) = -3.71%; Deviation(10 g) = -2.65%



0 dB = 9.24 W/kg = 9.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1120

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.1 \text{ S/m}$; $\epsilon_r = 46.978$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2016; Ambient Temp: 21.8°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3914; ConvF(3.86, 3.86, 3.86); Calibrated: 2/22/2016;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/18/2016

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 15.2 W/kg

SAR(1 g) = 3.56 W/kg; SAR(10 g) = 1.01 W/kg

Deviation(1 g) = -6.93%; Deviation(10 g) = -5.16%



0 dB = 8.53 W/kg = 9.31 dBW/kg

APPENDIX C: PROBE CALIBRATION



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **EX3-7409_May16**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7409**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

Calibration date: **May 17, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	06-Apr-16 (No. 217-02288/02289)	Apr-17
Power sensor NRP-Z91	SN: 103244	06-Apr-16 (No. 217-02288)	Apr-17
Power sensor NRP-Z91	SN: 103245	06-Apr-16 (No. 217-02289)	Apr-17
Reference 20 dB Attenuator	SN: S5277 (20x)	05-Apr-16 (No. 217-02293)	Apr-17
Reference Probe ES3DV2	SN: 3013	31-Dec-15 (No. ES3-3013_Dec15)	Dec-16
DAE4	SN: 660	23-Dec-15 (No. DAE4-660_Dec15)	Dec-16
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (No. 217-02285/02284)	In house check: Jun-16
Power sensor E4412A	SN: MY41498087	06-Apr-16 (No. 217-02285)	In house check: Jun-16
Power sensor E4412A	SN: 000110210	06-Apr-16 (No. 217-02284)	In house check: Jun-16
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Apr-13)	In house check: Jun-16
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-15)	In house check: Oct-16

Calibrated by:	Name Michael Weber	Function Laboratory Technician	Signature 
Approved by:	Katja Pokovic	Technical Manager	
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			Issued: May 18, 2016



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe EX3DV4

SN:7409

Manufactured: November 24, 2015
Calibrated: May 17, 2016

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7409

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$) ^A	0.39	0.34	0.39	± 10.1 %
DCP (mV) ^B	106.3	102.2	99.4	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	141.2	±3.3 %
		Y	0.0	0.0	1.0		127.3	
		Z	0.0	0.0	1.0		131.8	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	0.39	53.8	5.5	10.00	42.5	±1.2 %
		Y	0.55	54.7	5.9		41.8	
		Z	0.85	58.7	9.1		41.6	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	3.55	75.3	22.2	1.87	149.7	±0.7 %
		Y	3.32	72.6	21.0		139.7	
		Z	2.84	68.8	19.0		144.7	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	5.98	66.6	19.3	5.67	113.6	±0.9 %
		Y	6.17	66.7	19.4		107.1	
		Z	6.13	66.1	18.8		110.9	
10103-CAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.59	66.2	21.1	9.29	123.5	±1.4 %
		Y	7.27	67.9	22.1		121.1	
		Z	7.01	66.4	21.1		119.9	
10108-CAC	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	5.72	66.1	19.2	5.80	111.4	±1.2 %
		Y	6.34	67.6	20.0		149.2	
		Z	6.02	65.9	19.0		109.0	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.27	66.1	21.2	9.28	116.8	±1.4 %
		Y	6.89	67.6	22.1		114.7	
		Z	6.69	66.0	21.0		116.4	
10154-CAC	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	5.37	65.9	19.1	5.75	107.3	±1.2 %
		Y	5.98	67.2	19.9		143.3	
		Z	6.01	66.7	19.4		149.2	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	5.76	66.2	19.2	5.82	109.5	±1.2 %
		Y	6.43	67.6	20.0		148.3	
		Z	6.05	65.6	18.7		107.5	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	4.24	65.6	19.3	5.73	127.4	±0.9 %
		Y	4.54	66.4	19.8		120.4	
		Z	4.62	65.9	19.3		123.8	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	4.91	68.0	22.7	9.21	126.7	±1.4 %
		Y	5.24	68.8	23.3		124.0	
		Z	5.35	68.1	22.5		125.0	
10175-CAC	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.27	65.8	19.4	5.72	128.9	±0.9 %
		Y	4.52	66.2	19.7		121.2	
		Z	4.63	65.9	19.3		125.2	

10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	4.26	65.7	19.4	5.72	125.9	±0.9 %
		Y	4.47	66.0	19.5		120.6	
		Z	4.60	65.7	19.2		123.0	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.89	67.9	22.6	9.21	125.9	±1.7 %
		Y	5.26	69.0	23.4		123.8	
		Z	5.32	67.8	22.3		124.3	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.04	66.8	21.7	9.24	149.2	±1.4 %
		Y	6.64	68.1	22.6		148.9	
		Z	6.48	66.5	21.4		147.5	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.27	66.1	21.2	9.30	119.1	±1.4 %
		Y	6.88	67.4	22.0		115.9	
		Z	6.73	66.1	21.1		117.6	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	5.71	66.0	19.2	5.81	110.7	±0.9 %
		Y	6.41	67.8	20.2		149.8	
		Z	5.98	65.7	18.9		107.9	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.23	66.3	19.4	6.06	112.8	±0.9 %
		Y	6.51	66.6	19.5		107.4	
		Z	6.49	66.1	19.0		109.4	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 6 and 7).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7409

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	10.73	10.73	10.73	0.62	0.83	± 12.0 %
835	41.5	0.90	10.04	10.04	10.04	0.45	0.93	± 12.0 %
1750	40.1	1.37	8.05	8.05	8.05	0.38	0.80	± 12.0 %
1900	40.0	1.40	7.69	7.69	7.69	0.41	0.80	± 12.0 %
2300	39.5	1.67	7.22	7.22	7.22	0.25	0.92	± 12.0 %
2450	39.2	1.80	6.90	6.90	6.90	0.30	0.93	± 12.0 %
2600	39.0	1.96	6.77	6.77	6.77	0.32	0.83	± 12.0 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7409

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	9.46	9.46	9.46	0.52	0.80	± 12.0 %
835	55.2	0.97	9.33	9.33	9.33	0.34	1.04	± 12.0 %
1750	53.4	1.49	7.72	7.72	7.72	0.44	0.80	± 12.0 %
1900	53.3	1.52	7.47	7.47	7.47	0.43	0.80	± 12.0 %
2300	52.9	1.81	7.22	7.22	7.22	0.36	0.85	± 12.0 %
2450	52.7	1.95	7.10	7.10	7.10	0.39	0.80	± 12.0 %
2600	52.5	2.16	6.83	6.83	6.83	0.39	0.86	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ, ϑ), f = 900 MHz



DASY/EASY - Parameters of Probe: EX3DV4 - SN:7409**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	36.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PG Test**

Certificate No: **ES3-3334_Nov15**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3334**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-12.v9, QA CAL-23.v5, QA CAL-25.v6**
Calibration procedure for dosimetric E-field probes

BV ✓
 11/24/15

Calibration date: **November 17, 2015**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	01-Apr-15 (No. 217-02128)	Mar-16
Power sensor E4412A	MY41498087	01-Apr-15 (No. 217-02128)	Mar-16
Reference 3 dB Attenuator	SN: S5054 (3c)	01-Apr-15 (No. 217-02129)	Mar-16
Reference 20 dB Attenuator	SN: S5277 (20x)	01-Apr-15 (No. 217-02132)	Mar-16
Reference 30 dB Attenuator	SN: S5129 (30b)	01-Apr-15 (No. 217-02133)	Mar-16
Reference Probe ES3DV2	SN: 3013	30-Dec-14 (No. ES3-3013_Dec14)	Dec-15
DAE4	SN: 660	14-Jan-15 (No. DAE4-660_Jan15)	Jan-16
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US3739J585	18-Oct-01 (in house check Oct-15)	In house check: Oct-16

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature

Issued: November 17, 2015

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
$NORM_{x,y,z}$	sensitivity in free space
$ConvF$	sensitivity in TSL / $NORM_{x,y,z}$
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- $NORM_{x,y,z}$: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). $NORM_{x,y,z}$ are only intermediate values, i.e., the uncertainties of $NORM_{x,y,z}$ does not affect the E^2 -field uncertainty inside TSL (see below $ConvF$).
- $NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response$ (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of $ConvF$.
- $DCP_{x,y,z}$: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- $A_{x,y,z}$; $B_{x,y,z}$; $C_{x,y,z}$; $D_{x,y,z}$; $VR_{x,y,z}$; A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- $ConvF$ and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to $NORM_{x,y,z} * ConvF$ whereby the uncertainty corresponds to that given for $ConvF$. A frequency dependent $ConvF$ is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the $NORM_x$ (no uncertainty required).

Probe ES3DV3

SN:3334

Manufactured: January 24, 2012
Calibrated: November 17, 2015

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3334

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.03	1.03	0.99	$\pm 10.1 \%$
DCP (mV) ^B	107.6	105.3	107.9	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	192.1	$\pm 2.7 \%$
		Y	0.0	0.0	1.0		183.6	
		Z	0.0	0.0	1.0		183.3	
10010- CAA	SAR Validation (Square, 100ms, 10ms)	X	2.27	60.1	10.2	10.00	38.6	$\pm 1.4 \%$
		Y	1.99	59.3	10.2		38.4	
		Z	5.38	67.8	12.9		37.2	
10011- CAB	UMTS-FDD (WCDMA)	X	3.40	68.0	18.9	2.91	131.7	$\pm 0.5 \%$
		Y	3.27	67.0	18.2		130.2	
		Z	3.41	68.3	19.1		148.5	
10012- CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	2.93	68.9	18.7	1.87	132.9	$\pm 0.7 \%$
		Y	3.12	69.6	18.8		130.2	
		Z	3.24	71.1	19.7		128.2	
10013- CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	X	10.90	70.3	23.0	9.46	133.5	$\pm 3.3 \%$
		Y	10.53	69.0	22.1		124.6	
		Z	11.14	71.2	23.6		147.1	
10021- DAB	GSM-FDD (TDMA, GMSK)	X	15.05	91.0	24.4	9.39	139.5	$\pm 1.9 \%$
		Y	10.11	85.5	23.3		131.9	
		Z	11.84	87.6	23.4		130.0	
10023- DAB	GPRS-FDD (TDMA, GMSK, TN 0)	X	10.42	84.9	22.6	9.57	131.5	$\pm 3.0 \%$
		Y	13.29	89.7	24.6		141.1	
		Z	14.17	90.2	24.2		148.7	
10024- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1)	X	11.26	83.1	19.4	6.56	140.7	$\pm 1.9 \%$
		Y	26.29	95.5	23.8		134.7	
		Z	16.82	88.9	21.3		131.6	
10027- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	X	64.74	99.9	22.2	4.80	131.5	$\pm 2.2 \%$
		Y	56.71	99.8	22.7		124.7	
		Z	63.10	99.9	22.2		124.1	
10028- DAB	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	X	62.11	99.6	21.6	3.55	146.1	$\pm 1.9 \%$
		Y	77.61	99.8	21.2		132.0	
		Z	72.33	99.7	21.2		133.3	
10032- CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	X	96.24	92.7	15.9	1.16	137.2	$\pm 1.7 \%$
		Y	95.69	93.1	16.2		129.5	
		Z	98.67	94.1	16.4		149.7	
10100- CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.14	66.8	19.2	5.67	126.2	$\pm 1.7 \%$
		Y	6.21	66.8	19.1		139.9	
		Z	6.41	67.9	19.9		145.9	

10103-CAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	10.07	75.4	25.8	9.29	138.2	±2.5 %
		Y	9.54	73.3	24.5		130.5	
		Z	9.84	75.1	25.8		130.6	
10108-CAC	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.34	67.6	19.8	5.80	149.5	±1.4 %
		Y	6.13	66.6	19.1		132.1	
		Z	6.19	67.2	19.7		137.8	
10117-CAB	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	X	10.13	68.9	21.2	8.07	138.8	±2.7 %
		Y	10.16	68.9	21.1		149.6	
		Z	9.96	68.7	21.1		127.1	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	9.42	74.4	25.5	9.28	132.9	±3.0 %
		Y	9.50	74.0	25.0		143.7	
		Z	9.01	73.4	25.0		126.5	
10154-CAC	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.03	67.1	19.6	5.75	145.5	±1.4 %
		Y	5.81	66.0	18.9		128.9	
		Z	5.91	66.8	19.5		135.1	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.19	66.5	19.2	5.82	126.7	±1.4 %
		Y	6.20	66.4	19.0		132.8	
		Z	6.39	67.5	19.8		141.1	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	5.05	67.6	20.0	5.73	146.8	±1.4 %
		Y	4.82	66.2	19.2		132.2	
		Z	4.96	67.4	20.0		143.8	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	8.88	79.7	28.3	9.21	147.9	±3.0 %
		Y	8.00	76.1	26.2		138.9	
		Z	8.39	78.5	27.8		141.5	
10175-CAC	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	4.99	67.3	19.9	5.72	140.7	±1.2 %
		Y	4.80	66.2	19.1		131.3	
		Z	4.90	67.1	19.8		136.1	
10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	4.99	67.3	19.9	5.72	145.4	±1.4 %
		Y	4.81	66.2	19.2		130.9	
		Z	4.89	67.1	19.8		136.0	
10196-CAB	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	X	9.78	68.8	21.3	8.10	131.0	±2.5 %
		Y	9.73	68.4	21.0		140.7	
		Z	9.94	69.4	21.6		146.6	
10225-CAB	UMTS-FDD (HSPA+)	X	6.88	66.9	19.3	5.97	133.9	±1.7 %
		Y	6.96	67.1	19.3		144.8	
		Z	6.71	66.6	19.2		125.7	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	9.00	80.2	28.5	9.21	148.2	±3.0 %
		Y	7.73	75.1	25.7		131.6	
		Z	8.27	78.2	27.7		136.1	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	9.59	76.3	26.7	9.24	144.1	±2.7 %
		Y	8.74	72.9	24.5		133.4	
		Z	9.14	75.2	26.1		136.9	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	9.25	73.9	25.3	9.30	124.8	±3.0 %
		Y	9.40	73.7	24.9		142.1	
		Z	9.86	76.1	26.5		145.3	

10275-CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	X	4.38	66.9	18.7	3.96	133.3	±0.9 %
		Y	4.44	66.9	18.6		148.2	
		Z	4.30	66.7	18.6		128.9	
10291-AAB	CDMA2000, RC3, SQ55, Full Rate	X	3.68	67.3	18.7	3.46	145.8	±0.7 %
		Y	3.58	66.6	18.2		136.3	
		Z	3.62	67.3	18.8		139.4	
10292-AAB	CDMA2000, RC3, SQ32, Full Rate	X	3.73	68.0	19.1	3.39	147.5	±0.7 %
		Y	3.55	66.7	18.3		138.5	
		Z	3.60	67.6	18.9		143.0	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.30	67.4	19.7	5.81	141.4	±1.2 %
		Y	6.11	66.5	19.1		130.3	
		Z	6.17	67.0	19.5		136.8	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.88	68.0	20.1	6.06	147.0	±1.7 %
		Y	6.68	67.1	19.5		136.0	
		Z	6.75	67.7	20.0		141.6	
10400-AAC	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	X	9.97	68.8	21.4	8.37	126.9	±2.7 %
		Y	10.07	68.9	21.4		143.6	
		Z	10.21	69.7	22.0		147.4	
10403-AAB	CDMA2000 (1xEV-DO, Rev. 0)	X	4.77	68.5	18.8	3.76	134.9	±0.5 %
		Y	4.69	68.1	18.5		126.7	
		Z	4.74	68.8	18.9		129.4	
10404-AAB	CDMA2000 (1xEV-DO, Rev. A)	X	4.72	68.7	18.8	3.77	132.9	±0.7 %
		Y	4.78	68.9	18.9		147.4	
		Z	4.63	68.7	18.9		127.1	
10415-AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	X	2.72	68.9	18.8	1.54	131.9	±0.5 %
		Y	2.65	68.0	18.1		145.9	
		Z	2.72	69.3	19.0		127.3	
10416-AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	X	9.81	68.6	21.2	8.23	131.6	±2.7 %
		Y	9.90	68.7	21.2		144.1	
		Z	9.97	69.3	21.7		146.0	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 7 and 8).

^B Numerical linearization parameter: uncertainty not required.

^C Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3334

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^e	Conductivity (S/m) ^e	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth (mm) ^g	Unc (k=2)
6	55.5	0.75	6.13	6.13	6.13	0.00	1.00	± 13.3 %
13	55.5	0.75	5.76	5.76	5.76	0.00	1.00	± 13.3 %
750	41.9	0.89	6.56	6.56	6.56	0.24	2.36	± 12.0 %
835	41.5	0.90	6.37	6.37	6.37	0.37	1.70	± 12.0 %
1750	40.1	1.37	5.39	5.39	5.39	0.58	1.32	± 12.0 %
1900	40.0	1.40	5.18	5.18	5.18	0.77	1.20	± 12.0 %
2300	39.5	1.67	4.85	4.85	4.85	0.71	1.28	± 12.0 %
2450	39.2	1.80	4.58	4.58	4.58	0.79	1.17	± 12.0 %
2600	39.0	1.96	4.46	4.46	4.46	0.80	1.26	± 12.0 %

^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^e At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3334

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^g (mm)	Unc (k=2)
750	55.5	0.96	6.37	6.37	6.37	0.74	1.22	± 12.0 %
835	55.2	0.97	6.24	6.24	6.24	0.31	1.94	± 12.0 %
1750	53.4	1.49	5.03	5.03	5.03	0.50	1.57	± 12.0 %
1900	53.3	1.52	4.84	4.84	4.84	0.50	1.58	± 12.0 %
2300	52.9	1.81	4.61	4.61	4.61	0.74	1.23	± 12.0 %
2450	52.7	1.95	4.45	4.45	4.45	0.74	1.20	± 12.0 %
2600	52.5	2.16	4.29	4.29	4.29	0.80	1.20	± 12.0 %


^c Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^f At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Frequency Response of E-Field

(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\theta = 0^\circ$




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3334

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	17.4
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **ES3-3318_Feb16**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3318**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

BN ✓
05/01/2016

Calibration date: **February 19, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	01-Apr-15 (No. 217-02128)	Mar-16
Power sensor E4412A	MY41498087	01-Apr-15 (No. 217-02128)	Mar-16
Reference 3 dB Attenuator	SN: S5054 (3c)	01-Apr-15 (No. 217-02129)	Mar-16
Reference 20 dB Attenuator	SN: S5277 (20x)	01-Apr-15 (No. 217-02132)	Mar-16
Reference 30 dB Attenuator	SN: S5129 (30b)	01-Apr-15 (No. 217-02133)	Mar-16
Reference Probe ES3DV2	SN: 3013	31-Dec-15 (No. ES3-3013_Dec15)	Dec-16
DAE4	SN: 660	23-Dec-15 (No. DAE4-660_Dec15)	Dec-16
Secondary Standards	ID	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-13)	In house check: Apr-16
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-15)	In house check: Oct-16

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
			Issued: February 20, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below **ConvF**).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of **ConvF**.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Probe ES3DV3

SN:3318

Manufactured: January 10, 2012
Calibrated: February 19, 2016

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.16	0.93	1.29	$\pm 10.1 \%$
DCP (mV) ^B	102.2	104.2	103.7	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	199.2	$\pm 3.5 \%$
		Y	0.0	0.0	1.0		176.5	
		Z	0.0	0.0	1.0		194.6	
10010-CAA	SAR Validation (Square, 100ms, 10ms)	X	3.19	63.2	12.6	10.00	42.3	$\pm 1.4 \%$
		Y	19.74	82.9	18.6		35.5	
		Z	4.87	67.6	14.6		43.3	
10012-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	X	2.99	68.6	18.5	1.87	141.3	$\pm 0.9 \%$
		Y	3.46	71.1	19.6		145.1	
		Z	3.19	70.2	19.5		144.7	
10100-CAB	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	6.30	67.0	19.4	5.67	128.2	$\pm 1.4 \%$
		Y	6.32	67.0	19.2		129.9	
		Z	6.36	67.5	19.8		131.3	
10103-CAB	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	X	11.31	78.0	27.3	9.29	146.7	$\pm 3.5 \%$
		Y	9.35	72.8	24.3		141.3	
		Z	11.02	76.9	26.7		131.7	
10108-CAC	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	6.22	66.7	19.4	5.80	126.2	$\pm 1.4 \%$
		Y	6.20	66.5	19.1		128.1	
		Z	6.27	67.1	19.7		131.1	
10151-CAB	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	10.46	76.6	26.8	9.28	138.8	$\pm 3.3 \%$
		Y	8.80	72.0	24.0		134.3	
		Z	10.01	75.0	25.9		122.1	
10154-CAC	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	6.12	67.0	19.6	5.75	146.0	$\pm 1.7 \%$
		Y	6.15	67.1	19.5		148.7	
		Z	5.95	66.5	19.4		127.4	
10160-CAB	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	X	6.33	66.7	19.4	5.82	127.2	$\pm 1.4 \%$
		Y	6.33	66.6	19.2		128.2	
		Z	6.38	67.1	19.7		133.6	
10169-CAB	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	5.10	67.2	20.0	5.73	147.9	$\pm 1.2 \%$
		Y	4.85	66.3	19.3		127.1	
		Z	4.97	66.7	19.8		133.9	
10172-CAB	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	8.71	78.3	27.8	9.21	127.5	$\pm 3.0 \%$
		Y	7.52	74.8	25.7		144.7	
		Z	10.09	81.9	29.5		136.4	
10175-CAC	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	5.09	67.2	20.0	5.72	146.9	$\pm 1.2 \%$
		Y	4.97	66.9	19.6		140.9	
		Z	4.95	66.6	19.7		133.1	

10181-CAB	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	X	5.11	67.3	20.0	5.72	146.8	±1.2 %
		Y	5.03	67.2	19.8		147.0	
		Z	5.00	66.8	19.8		135.0	
10237-CAB	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	X	8.73	78.3	27.8	9.21	126.7	±3.0 %
		Y	7.60	75.1	25.9		146.1	
		Z	10.76	83.8	30.4		143.4	
10252-CAB	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	X	9.61	75.3	26.2	9.24	129.4	±3.3 %
		Y	8.55	72.3	24.3		143.1	
		Z	11.05	79.1	28.1		146.1	
10267-CAB	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	X	10.44	76.5	26.8	9.30	137.7	±3.3 %
		Y	8.62	71.3	23.6		125.8	
		Z	10.24	75.6	26.2		125.3	
10297-AAA	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	X	6.51	67.8	20.0	5.81	148.5	±1.7 %
		Y	6.42	67.3	19.6		144.3	
		Z	6.31	67.3	19.8		134.7	
10311-AAA	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	X	6.80	67.4	19.9	6.06	128.6	±1.4 %
		Y	6.69	66.9	19.4		125.3	
		Z	6.91	68.0	20.3		140.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 6 and 7).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	6.48	6.48	6.48	0.54	1.35	± 12.0 %
835	41.5	0.90	6.23	6.23	6.23	0.70	1.21	± 12.0 %
1750	40.1	1.37	5.34	5.34	5.34	0.72	1.27	± 12.0 %
1900	40.0	1.40	5.13	5.13	5.13	0.80	1.18	± 12.0 %
2300	39.5	1.67	4.78	4.78	4.78	0.76	1.29	± 12.0 %
2450	39.2	1.80	4.57	4.57	4.57	0.59	1.49	± 12.0 %
2600	39.0	1.96	4.40	4.40	4.40	0.80	1.31	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	6.19	6.19	6.19	0.50	1.51	± 12.0 %
835	55.2	0.97	6.11	6.11	6.11	0.47	1.56	± 12.0 %
1750	53.4	1.49	5.02	5.02	5.02	0.49	1.55	± 12.0 %
1900	53.3	1.52	4.81	4.81	4.81	0.80	1.24	± 12.0 %
2300	52.9	1.81	4.55	4.55	4.55	0.80	1.27	± 12.0 %
2450	52.7	1.95	4.45	4.45	4.45	0.80	1.16	± 12.0 %
2600	52.5	2.16	4.18	4.18	4.18	0.80	1.13	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid Error (ϕ, ϑ), $f = 900\text{ MHz}$



DASY/EASY - Parameters of Probe: ES3DV3 - SN:3318**Other Probe Parameters**

Sensor Arrangement	Triangular
Connector Angle (°)	76.5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm