



PCTEST ENGINEERING LABORATORY, INC.

6660 – B Dobbin Road • Columbia, MD 21045 • USA

Telephone 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com> (email: randy@pctestlab.com)

CERTIFICATE OF COMPLIANCE (SAR EVALUATION)



APPLICANT NAME & ADDRESS:

Samsung Electronics Co., Ltd.
416 Maetan-3 Dong, Paldal-Ku
Suwon City Kyungki-Do
441-742, KOREA
Attn: Wallace Oh

DATE & LOCATION OF TESTING:

Dates of Tests: Feb. 20 - Mar.1, 2002
Test Report S/N: SAR.220219075.A3L
Test Site: PCTEST Lab, Columbia, MD USA

FCC ID:

A3LSCHA310

APPLICANT:

Samsung Electronics Co., Ltd.

EUT Type:

Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)

Tx Frequency:

**824.04 – 848.97 MHz (AMPS) / 824.70 – 848.31 MHz (CDMA)
1851.25 – 1908.75 MHz (PCS CDMA)**

Rx Frequency:

**869.04 – 893.97 MHz (AMPS) / 869.70 – 893.31 MHz (CDMA)
1931.25 – 1988.75 MHz (PCS CDMA)**

Max. RF Output Power:

**0.400W ERP AMPS (26.023dBm);
0.315W ERP Cellular CDMA (24.983dBm);
0.285W EIRP PCS CDMA (24.551dBm)**

Max. SAR Measurement:

**1.361mW/g AMPS Head SAR; 0.731mW/g AMPS Body SAR;
0.989mW/g Cell. CDMA Head SAR; 0.35mW/g Cell. CDMA Body SAR;
1.357mW/g PCS CDMA Head SAR; 1.030mW/g PCS CDMA Body SAR**

Trade Name/Model(s):

SCH-A310

FCC Classification:

Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s):

§2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]

Application Type:

Certification

Test Device Serial No.:

Identical prototype

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1992 and IEEE Std. 1528-200X (Draft 6.4, July 2001).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President



PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT		SAR.220219075.A3L	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 1 of 33

1.	INTRODUCTION	3
	SAR DEFINITION	3
2.	SAR MEASUREMENT SETUP	4
	Robotic System	4
	System Hardware	4
	System Electronics.....	4
3.	DASY3 E-FIELD PROBE SYSTEM.....	5
	Probe Measurement System	5
	Probe Specifications.....	5
4.	Probe Calibration Process	6
	Dosimetric Assessment Procedure.....	6
	Free Space Assessment.....	6
	Temperature Assessment.....	6
5.	PHANTOM & EQUIVALENT TISSUES	7
	SAM Phantom	7
	Brain & Muscle Simulating Mixture Characterization.....	7
	Device Holder	7
6.	TEST SYSTEM SPECIFICATIONS	8
	Automated Test System Specifications.....	8
7.	DOSIMETRIC ASSESSMENT & PHANTOM SPECS.....	9
	Measurement Procedure	9
	Specific Anthropomorphic Mannequin (SAM) Specifications	9
8.	DEFINITION OF REFERENCE POINTS	10
	EAR Reference Point	10
	Handset Reference Points	10
9.	TEST CONFIGURATION POSITIONS.....	11
	Positioning for Cheek/Touch	11
	Positioning for Ear / 15° Tilt.....	12
	Body Holster /Belt Clip Configurations.....	13
10.	ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS	14
	Uncontrolled Environment.....	14
	Controlled Environment	14
11.	MEASUREMENT UNCERTAINTIES	15
12.	SYSTEM VERIFICATION	16
	Tissue Verification.....	16
	Test System Verification	16
13.	SAR TEST DATA SUMMARY.....	17
	See Measurement Result Data Pages	17
	Procedures Used To Establish Test Signal.....	17
	Device Test Conditions	17
	EUT Handset Reference Points.....	17
14.	SAR DATA SUMMARY	18-30
15.	SAR TEST EQUIPMENT	31
	Equipment Calibration	31
16.	CONCLUSION	32
	Measurement Conclusion	32
17.	REFERENCES.....	33

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 2 of 33

1. INTRODUCTION / SAR DEFINITION

The FCC has adopted the guidelines for evaluating the environmental effects of radiofrequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in *IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz*. (c) 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.[2] The measurement procedure described in *IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave*[3] is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in *Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields*, NCRP Report No. 86 (c) NCRP, 1986, Bethesda, MD 20814.[6] SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1.1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1.1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \sigma E^2 / \rho$$

where:

$$\begin{aligned} \sigma &= \text{conductivity of the tissue-simulant material (S/m)} \\ \rho &= \text{mass density of the tissue-simulant material (kg/m}^3\text{)} \\ E &= \text{Total RMS electric field strength (V/m)} \end{aligned}$$

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 3 of 33

2. SAR MEASUREMENT SETUP

Robotic System

Measurements are performed using the ALIDX-500 automated dosimetric assessment system. The ALIDX-500 is made by IDX Robotics, Inc. (IDX) in the United States and consists of high precision robotics system (CRS), robot controller, Pentium 4 computer, near-field probe, probe alignment sensor, and the Left and Right SAM phantoms containing the head/brain equivalent tissue, and the flat phantoms for body/muscle equivalent. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 2.1).

System Hardware

The Robot table consists of the power supply, robot controller, safety computer, teach pendant (Joystick), six-axis robot arm, and the probe. The cell controller consists of DELL Dimension 4300 Pentium-4 1.6 GHz computer with Windows 2000 system and SAR Measurement software, National Instruments analog card, monitor, keyboard, and mouse. The robot controller is connected to the cell controller to communicate between the two computers. The probe data is connected to the cell controller via data acquisition cables.

System Electronics




Figure 2.1
SAR Measurement System Setup

When the Robot is in the home position, the Y-axis of the coordinate system parallels the line of intersection between the tabletop and the long axis of the Robot's Large Shoulder. The Teach Pendant may be used to establish the X,Y coordinate directions by depressing the 0-X and 0-Y MOTOR/AXIS switches while in axis mode.

The robot is first taught to position the probe sensor following a specific pattern of points. In the first sweep the sensor enclosure touches the inside of the phantom head. The SAR is measured on a defined grid of points that are concentrated on the surface of the head closest to the antenna of the transmitting device (EUT).

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 4 of 33

3. ALIDX-500 E-FIELD PROBE SYSTEM

Probe Measurement System



Fig 3.1
IDX System

The near-field probe is an implantable isotropic E-field probe that measures the voltages proportional to the $|E|^2$ (electric) or $|H|^2$ (magnetic) fields. The probe is enclosed in a hollow glass protective cylinder 9-mm. outer diameter, 0.5 mm. thickness and 30 cm. in length. The E-probe contains three electrically small array of orthogonal dipoles strategically placed to provide greater accuracy and to compensate for near-field spatial gradients. The probe contains diodes that are placed over the gap of the dipoles to improve RF detection. The electrical signal detected by each diode is amplified by three DC amplifiers and are contained in a shielded container in the robot end effector so its performance is not affected by the presence of incident electromagnetic fields (see Fig. 3.1).

Probe Specifications

Frequency Range:	10 kHz – 3.0 GHz
Calibration:	In air from 10 MHz to 3.0 GHz In brain and muscle simulating tissue at Frequencies of 835 MHz, 1900MHz and 2450MHz
Sensitivity:	3.5 mV/mW/cm ² (air – typical)
DC Resistance:	300 kohm
Isotropic Response:	0.25 dB
Dynamic Range:	10 mW/kg – 100 W/kg
Resistance to Pull:	25 N
Probe Length:	290 mm
Probe Tip Material:	Glass
Probe Tip Length:	40 mm
Probe Tip Diameter:	7 ± 0.2 mm
Application:	SAR Dosimetry Testing HAC (Hearing Aid Compatibility) Compliance tests of mobile phones




Figure 3.2
Triangular Probe Configuration




Figure 3.3
Probe Characteristics

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 5 of 33

4. Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe amplifier combination has unique calibration parameters. A TEM calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the Probe to a known E-field density (1mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter. The SAR measurement software is used for Probe calibration.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or some other methodologies above 1 GHz for free space. For the free space calibration, we place the probe in the volumetric center of the cavity and at the proper orientation with the field. We then rotate the probe 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe (see Fig. 4.2).

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = simulated tissue conductivity,

ρ = Tissue density (1.25 g/cm³ for brain tissue)




Figure 4.1 E-Field and Temperature measurements at 900MHz [7]




Figure 4.2 E-Field and temperature measurements at 1.9GHz [7]

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT	SAMSUNG	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310
			Page 6 of 33

5. PHANTOM & EQUIVALENT TISSUES

SAM Phantom



Figure 5.1
SAM Phantoms

The Left and Right SAM Phantoms are constructed of a vivac composite integrated in a corian stand. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

Brain & Muscle Simulating Mixture Characterization



Figure 5.2
Head Simulated Tissue

The brain and muscle mixtures consist of a viscous gel using hydroxyethylcellulose (HEC) gelling agent and saline solution (see Table 6.1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrrove [13].(see Table 5.1)

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7

Salt: 99% Pure Sodium Chloride
Water: De-ionized, 16 MΩ resistivity
DGBE: 99% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl] ether
Sugar: 98% Pure Sucrose
HEC: Hydroxyethyl Cellulose

Table 5.1

Composition of the Brain & Muscle Tissue Equivalent Matter

Device Holder



Figure 5.4
Device Positioner

In combination with the SAM Phantom, the EUT Holder (see Fig. 6.2) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. Device positioning is accurate and repeatable according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations [12]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

PCTEST™ SAR TEST REPORT	SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 7 of 33

6. TEST SYSTEM SPECIFICATIONS

Automated Test System Specifications

Positioner

Robot: CRS Robotics, Inc. Robot Model: F3
Repeatability: ± 0.05 mm (0.002 in.)
No. Of axes: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium 4
Clock Speed: 1.6 GHz
Operating System: Windows 2000™ Professional
Data Card: NI DAQ Card (in CPU)

Data Converter

Software: IDX Flexware
Connecting Lines: Data Acquisition Cable
 RS-232 Host Interface Cable
Sampling Rate: 6000 samples/sec



Figure 6.1
ALIDX-500 Test System

E-Field Probes

Model: E-010 S/N: PCT001
Construction: Triangular core absolute encoder system
Frequency: 10 MHz to 3.0 GHz

Phantom

Phantom: SAM Phantoms (Left & Right)
Shell Material: Vivac Composite
Thickness: 2.0 ± 0.2 mm

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 8 of 33

7. DOSIMETRIC ASSESSMENT & PHANTOM SPECS

Measurement Procedure

The measurement procedure consists of the process parameters, probe parameters, EUT product data, and measurement scans (teach points). The measurement procedure is a set of predefined points to be scanned and measured by the probe, DC amplified and processed by the cell controller. The corresponding voltages determined by the electric and magnetic fields are extrapolated to determine peak SAR value.

The SAR Measurement System measures field strength by employing two different types of systematic measurement scans; a coarse scan and a fine scan. Coarse and fine scans measure field strength in a rectangular area within the XY plane (a plane parallel to the top of the Robot Table). The measurement area is divided into a grid of small squares defined by equally spaced grid lines. During an actual measurement process, the probe moves along grid lines systematically recording the field strength at grid line intersections. Typically, after a coarse scan is completed, a fine scan is conducted at the peak field strength value (hot spot) that was measured in the coarse scan. The fine scan has a greater resolution (smaller grid squares) than the coarse scan, and covers only a fraction of the measurement area in the coarse scan.

Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Fig. 7.1). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface. The SAM shell thickness is 2.0 ± 0.2 mm.



Figure 7.1
Left and Right SAM Phantom shells

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 9 of 33

8. DEFINITION OF REFERENCE POINTS

EAR Reference Point (ERP)

Figure 8.1 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 9.2. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8.2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 8.2 Close-up side view of ERPs




Figure 8.1 Front, back and side view of SAM Twin Phantom

Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 8.3). The “test device reference point” was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at it’s top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 8.3 Handset Vertical Center & Horizontal Line Reference Points

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT	SAMSUNG	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310
			Page 10 of 33

9. TEST CONFIGURATION POSITIONS

Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 9.1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 9.2)




Figure 9.2 Side view w/ relevant markings

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 11 of 33

9. TEST CONFIGURATION POSITIONS (Continued)

Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact were at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9.3).




Figure 9.3 Front, Side and Top View of Ear/15° Tilt Position




Figure 9.4 Side view w/ relevant markings

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 12 of 33

9. TEST CONFIGURATION POSITIONS (Continued)

Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.5). A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.



Figure 9.5 Body Belt Clip & Holster Configurations

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used. All test position spacings are documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing.

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements must be included in the user's manual.

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 13 of 33

10. ANSI/IEEE C95.1 - 1992 RF EXPOSURE LIMITS

Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 10.1. Safety Limits for Partial Body Exposure [2]

	HUMAN EXPOSURE LIMITS	
	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00

- 1 The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- 2 The Spatial Average value of the SAR averaged over the whole body.
- 3 The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

PCTEST™ SAR TEST REPORT	SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 14 of 33

11. MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = cxf/e	i = cxg/e	k
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	c_i (1 - g)	c_i (10 - g)	1 - g u_i (± %)	10 - g u_i (± %)	v_i
Measurement System									
Probe Calibration	E1.1	3.0	N	1	1	1	3.0	3.0	∞
Axial Isotropy	E1.2	4.88	R	$\sqrt{3}$	$(1-c_p)^{1/2}$	$(1-c_p)^{1/2}$	2.0	2.0	∞
Hemishperical Isotropy	E1.2	9.6	R	$\sqrt{3}$	$\sqrt{c_p}$	$\sqrt{c_p}$	3.9	3.9	∞
Boundary Effect	E1.3	11.0	R	$\sqrt{3}$	1	1	6.4	6.4	∞
Linearity	E1.4	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limits	E1.5	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	E1.6	1.0	R	1	1	1	1.0	1.0	∞
Response Time	E1.7	0.8	R	$\sqrt{3}$	1	1	0.3	0.3	∞
Integration Time	E1.8	1.7	R	$\sqrt{3}$	1	1	1.0	1.0	∞
RF Ambient Conditions	E5.1	1.2	R	$\sqrt{3}$	1	1	0.7	0.7	∞
Probe Positioner Mechanical Tolerance	E5.2	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning w/ respect to Phantom Shell	E5.3	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
Extrapolation, Interpolation & Integration Algorithms for Max. SAR Evaluation	E4.2	3.9	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Test Sample Related									
Test Sample Positioning	E3.2.1		R	$\sqrt{3}$	1	1	6.0	6.0	11
Device Holder Uncertainty	E3.1.1		R	$\sqrt{3}$	1	1	5.0	5.0	8
Output Power Variation - SAR drift measurement	5.6.2	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E2.1	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E2.2	5.0	R	$\sqrt{3}$	0.7	0.5	2.0	1.4	∞
Liquid Conductivity - measurement uncertainty	E2.2	10.0	R	$\sqrt{3}$	0.7	0.5	4.0	2.9	∞
Liquid Permittivity - deviation from target values	E2.2	5.0	R	$\sqrt{3}$	0.6	0.5	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E2.2	5.0	R	$\sqrt{3}$	0.6	0.5	1.7	1.4	∞
Combined Standard Uncertainty			RSS				13.7	13.3	
Expanded Uncertainty (95% CONFIDENCE LEVEL)							27.4	26.6	

The above measurement uncertainties are according to IEEE Std. 1528-200x (July, 2001)

PCTEST™ SAR TEST REPORT	SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 15 of 33

12. SYSTEM VERIFICATION

Tissue Verification

Table 12.1 Simulated Tissue Verification

MEASURED TISSUE PARAMETERS									
Date(s)	02/18/02	835MHz Brain		835MHz Muscle		1900MHz Brain		1900MHz Muscle	
Liquid Temperature (°C)	23.5	Target	Measured	Target	Measured	Target	Measured	Target	Measured
Dielectric Constant: ϵ		41.50	43.44	55.20	55.54	40.00	40.29	53.30	53.95
Conductivity: σ		0.900	0.87	0.970	0.990	1.400	1.44	1.520	1.56

Test System Validation

Prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at 835MHz and 1900MHz by using the system validation kit(s). (Graphic Plots Attached)

Table 12.2 System Validation

Date(s)	02/20/02	SYSTEM DIPOLE VALIDATION TARGET & MEASURED			
Liquid Temperature (°C)	23.0				
System Validation Kit: D-835S, S/N: 103		835MHz Brain	Targeted SAR _{1g} (mW/g) 2.375	Measured SAR _{1g} (mW/g) 2.56	Deviation (%) + 7.2
System Validation Kit: D-1900S, S/N: 104		1900MHz Brain	Targeted SAR _{1g} (mW/g) 9.925	Measured SAR _{1g} (mW/g) 10.72	Deviation (%) + 7.4





Figure 12.1 Dipole Validation Test Setup

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT	SAMSUNG	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310
© 2002 PCTEST Engineering Laboratory, Inc.			Page 16 of 33

13. SAR TEST DATA SUMMARY

[See Measurement Result Data Pages](#)

Procedures Used To Establish Test Signal

The handset was placed into simulated call mode (AMPS, Cellular CDMA & PCS CDMA modes) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

EUT Handset Reference Points




Figure 13.1 Handset Reference Points

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT	SAMSUNG	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310
			Page 17 of 33

SAR DATA SUMMARY

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44

Conductivity: 0.87

14.1 MEASUREMENT RESULTS (AMPS Right Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	27.0	27.0	Extended	Cheek / Touch	In	1.3378
824.04	0991	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	1.0746
836.49	0383	AMPS	27.0	27.0	Extended	Cheek / Touch	In	0.9055
836.49	0383	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	0.7923
848.97	0799	AMPS	27.0	27.0	Extended	Cheek / Touch	In	0.9325
848.97	0799	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	0.8065
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].

2. All modes of operation were investigated, and worst-case results are reported.

3. Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

[‡]Power Measured

☒ Conducted

☐ ERP

☐ EIRP

4. SAR Measurement System

☐ DASY3

☒ IDX

☐

Phantom Configuration

☐ Left Head

☐ Flat Phantom

☒ Right Head

5. SAR Configuration

☒ Head

☐ Body

☐ Hand

6. Test Signal Call Mode

☒ Manu. Test Codes

☐ Base Station Simulator


Randy Ortanez
President



**Figure 14.1 Right Head SAR Test Setup
-- Cheek / Touch Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 18 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44

Conductivity: 0.87

14.2 MEASUREMENT RESULTS (AMPS Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	27.0	27.0	Extended	Ear / 15° Tilt	In	0.4513
824.04	0991	AMPS	27.0	27.0	Extended	Ear / 15° Tilt	Out	0.2924
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator


Randy Ortanez
President



Figure 14.2 Right Head SAR Test Setup
-- Ear / 15° Tilt Position --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 19 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44

Conductivity: 0.87

14.3 MEASUREMENT RESULTS (AMPS Left Head SAR - Touch)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	27.0	27.0	Extended	Cheek / Touch	In	1.3615
824.04	0991	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	1.1698
836.49	0383	AMPS	27.0	27.0	Extended	Cheek / Touch	In	0.8810
836.49	0383	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	0.9482
848.97	0799	AMPS	27.0	27.0	Extended	Cheek / Touch	In	1.0542
848.97	0799	AMPS	27.0	27.0	Extended	Cheek / Touch	Out	1.1915
824.04	0991	AMPS	27.0	27.0	Standard	Cheek / Touch	In	1.3416
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Brain 1.6 W/kg (mW/g) averaged over 1 gram		
Spatial Peak								
Uncontrolled Exposure/General Population								

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator


Randy Ortanez
President



Figure 14.3 Left Head SAR Test Setup
-- Cheek / Touch Position --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 20 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44

Conductivity: 0.87

14.4 MEASUREMENT RESULTS (AMPS Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	27.0	27.0	Extended	Ear / 15° Tilt	In	0.4030
824.04	0991	AMPS	27.0	27.0	Extended	Ear / 15° Tilt	Out	0.2915
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- | | | | |
|---------------------------|--|---|-------------------------------------|
| *Power Measured | ☒ Conducted | ☐ ERP | ☐ EIRP |
| 4. SAR Measurement System | ☐ DASY3 | ☒ IDX | ☐ |
| Phantom Configuration | ☒ Left Head | ☐ Flat Phantom | ☐ Right Head |
| 5. SAR Configuration | ☒ Head | ☐ Body | ☐ Hand |
| 6. Test Signal Call Mode | ☒ Manu. Test Codes | ☐ Base Station Simulator | |


Randy Ortanez
President



**Figure 14.4 Left Head SAR Test Setup
-- Ear / 15° Tilt Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 21 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44

Conductivity: 0.87

14.5 MEASUREMENT RESULTS (CELLULAR CDMA Left Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.70	1013	CDMA	26.0	26.0	Extended	Cheek / Touch	In	0.9887
824.70	1013	CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.8502
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Brain 1.6 W/kg (mW/g) averaged over 1 gram		
Spatial Peak								
Uncontrolled Exposure/General Population								

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- | | | | |
|---------------------------|--|---|-------------------------------------|
| *Power Measured | ☒ Conducted | ☐ ERP | ☐ EIRP |
| 4. SAR Measurement System | ☐ DASY3 | ☒ IDX | ☐ |
| Phantom Configuration | ☒ Left Head | ☐ Flat Phantom | ☐ Right Head |
| 5. SAR Configuration | ☒ Head | ☐ Body | ☐ Hand |
| 6. Test Signal Call Mode | ☒ Manu. Test Codes | ☐ Base Station Simulator | |


Randy Ortanez
President



**Figure 14.5 Left Head SAR Test Setup
-- Cheek / Touch Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 22 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Brain

Dielectric Constant: 43.44


Conductivity: 0.87

14.6 MEASUREMENT RESULTS (CELLULAR CDMA Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.70	1013	CDMA	26.0	26.0	Extended	Ear / 15° Tilt	In	0.3041
824.70	1013	CDMA	26.0	26.0	Extended	Ear / 15° Tilt	Out	0.2106
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Brain		
Spatial Peak						1.6 W/kg (mW/g)		
Uncontrolled Exposure/General Population						averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and worst-case results are reported.
 - Battery is fully charged for all readings. *Standard & Extended Batteries are options.*
- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☒ Left Head ☐ Flat Phantom ☐ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator


Randy Ortanez
President



**Figure 14.6 Left Head SAR Test Setup
-- Ear / 15° Tilt Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 23 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain
Dielectric Constant: 40.29
Conductivity: 1.44


14.7 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Touch)


FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
0025	1851.25	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	1.1355
0025	1851.25	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.1807
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	1.2745
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.2595
1175	1908.75	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	0.7117
1175	1908.75	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.1354
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☐ Left Head ☐ Flat Phantom ☒ Right Head
5. SAR Configuration ☒ Head ☐ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator


Randy Ortanez
President



**Figure 14.7 Right Head SAR Test Setup
-- Cheek / Touch Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 24 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain

Dielectric Constant: 40.29

Conductivity: 1.44

14.8 MEASUREMENT RESULTS (PCS CDMA Right Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Ear / 15° Tilt	In	0.07
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Ear / 15° Tilt	Out	0.09
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- | | | | |
|---------------------------|--|---|--|
| *Power Measured | ☒ Conducted | ☐ ERP | ☐ EIRP |
| 4. SAR Measurement System | ☐ DASY3 | ☒ IDX | ☐ |
| Phantom Configuration | ☐ Left Head | ☐ Flat Phantom | ☒ Right Head |
| 5. SAR Configuration | ☒ Head | ☐ Body | ☐ Hand |
| 6. Test Signal Call Mode | ☒ Manu. Test Codes | ☐ Base Station Simulator | |


Randy Ortanez
President



**Figure 14.8 Right Head SAR Test Setup
-- Ear / Tilt Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 25 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain
Dielectric Constant: 40.29
Conductivity: 1.44

14.9 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Touch)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
0025	1851.25	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	1.2116
0025	1851.25	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.2921
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	1.1195
0600	1880.00	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.2006
1175	1908.75	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	In	1.3572
1175	1908.75	PCS CDMA	26.0	26.0	Extended	Cheek / Touch	Out	0.2126
1175	1908.75	PCS CDMA	26.0	26.0	Standard	Cheek / Touch	In	1.3540
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- | | | | |
|---------------------------|--|---|-------------------------------------|
| *Power Measured | ☒ Conducted | ☐ ERP | ☐ EIRP |
| 4. SAR Measurement System | ☐ DASY3 | ☒ IDX | ☐ |
| Phantom Configuration | ☒ Left Head | ☐ Flat Phantom | ☐ Right Head |
| 5. SAR Configuration | ☒ Head | ☐ Body | ☐ Hand |
| 6. Test Signal Call Mode | ☒ Manu. Test Codes | ☐ Base Station Simulator | |


Randy Ortanez
President



Figure 14.9 Left Head SAR Test Setup
-- Cheek / Touch Position --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 26 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Brain
Dielectric Constant: 40.29
Conductivity: 1.44

14.10 MEASUREMENT RESULTS (PCS CDMA Left Head SAR – Tilt)

FREQUENCY		Modulation	Begin / End POWER [‡]			Device Test Position	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
1175	1908.75	PCS CDMA	26.0	26.0	Extended	Ear / 15° Tilt	In	0.18
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Brain 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- All modes of operation were investigated, and worst-case results are reported.
- Battery is fully charged for all readings. *Standard & Extended Batteries are options.*

- | | | | |
|---------------------------|--|---|-------------------------------------|
| *Power Measured | ☒ Conducted | ☐ ERP | ☐ EIRP |
| 4. SAR Measurement System | ☐ DASY3 | ☒ IDX | ☐ |
| Phantom Configuration | ☒ Left Head | ☐ Flat Phantom | ☐ Right Head |
| 5. SAR Configuration | ☒ Head | ☐ Body | ☐ Hand |
| 6. Test Signal Call Mode | ☒ Manu. Test Codes | ☐ Base Station Simulator | |


Randy Ortanez
President



**Figure 14.10 Left Head SAR Test Setup
-- Ear / Tilt Position --**

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 27 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

Dielectric Constant: 55.54

Conductivity: 0.9955

14.11 MEASUREMENT RESULTS (AMPS Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER [†]			Separation Distance (cm) ^{††}	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
824.04	0991	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	In	0.6483
824.04	0991	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	Out	0.4929
836.49	0383	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	In	0.5392
836.49	0383	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	Out	0.5103
848.97	0799	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	In	0.6270
848.97	0799	AMPS	27.0	27.0	Standard	1.5 [w/o Holster]	Out	0.7312
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Muscle 1.6 W/kg (mW/g) averaged over 1 gram		
Spatial Peak								
Uncontrolled Exposure/General Population								

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and worst-case results are reported.
 - Battery is fully charged for all readings. *Standard & Extended Batteries are options.*
- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
5. SAR Configuration ☐ Head ☒ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
7. ^{‡‡}Test Configuration ☐ With Holster ☒ Without Holster
8. Both sides of the phone were tested and the worst-case side is reported.


Randy Ortañez
President



Figure 14.11 Body SAR Test Setup
-- w/o Holster --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 28 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 835MHz Muscle

Dielectric Constant: 55.54

Conductivity: 0.9955

14.12 MEASUREMENT RESULTS (CELLULAR CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER [†]			Separation Distance (cm) ^{††}	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
848.31	0777	CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	In	0.35
848.31	0777	CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	Out	0.31
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Muscle 1.6 W/kg (mW/g) averaged over 1 gram		
Spatial Peak								
Uncontrolled Exposure/General Population								

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and worst-case results are reported.
 - Battery is fully charged for all readings. *Standard & Extended Batteries are options.*
- [†]Power Measured ☒ Conducted ☐ ERP ☐ EIRP
^{††}SAR Measurement System ☐ DASY3 ☒ IDX ☐
 Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
 SAR Configuration ☐ Head ☒ Body ☐ Hand
 Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
 Test Configuration ☐ With Holster ☒ Without Holster
- Both sides of the phone were tested and the worst-case side is reported.


Randy Ortanez
President



Figure 14.12 Body SAR Test Setup
-- w/o Holster --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 29 of 33

SAR DATA SUMMARY (Continued)

Mixture Type: 1900MHz Muscle

Dielectric Constant: 53.95

Conductivity: 1.56

14.13 MEASUREMENT RESULTS (PCS CDMA Body SAR w/o Holster)

FREQUENCY		Modulation	Begin / End POWER [‡]			Separation Distance (cm) ^{‡‡}	Antenna Position	SAR (W/kg)
MHz	Ch.		(dBm)		Battery			
0025	1851.25	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	In	0.86
0025	1851.25	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	Out	0.88
0600	1880.00	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	In	1.03
0600	1880.00	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	Out	0.83
1175	1908.75	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	In	0.80
1175	1908.75	PCS CDMA	26.0	26.0	Standard	1.5 [w/o Holster]	Out	0.88
0600	1880.00	PCS CDMA	26.0	26.0	Extended	1.5 [w/o Holster]	Out	1.01
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Muscle 1.6 W/kg (mW/g) averaged over 1 gram		
Spatial Peak								
Uncontrolled Exposure/General Population								

NOTES:

- The test data reported are the worst-case SAR value with the antenna-head position set in atypical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
 - All modes of operation were investigated, and worst-case results are reported.
 - Battery is fully charged for all readings. *Standard & Extended Batteries are options.*
- *Power Measured ☒ Conducted ☐ ERP ☐ EIRP
4. SAR Measurement System ☐ DASY3 ☒ IDX ☐
- Phantom Configuration ☐ Left Head ☒ Flat Phantom ☐ Right Head
5. SAR Configuration ☐ Head ☒ Body ☐ Hand
6. Test Signal Call Mode ☒ Manu. Test Codes ☐ Base Station Simulator
7. ^{‡‡}Test Configuration ☐ With Holster ☒ Without Holster
8. Both sides of the phone were tested and the worst-case side is reported.


Randy Ortanez
President



Figure 14.13 Body SAR Test Setup
-- w/o Holster --

PCTEST™ SAR TEST REPORT	PCTEST SAR EVALUATION REPORT		SAMSUNG	Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 30 of 33

15. SAR TEST EQUIPMENT

Equipment Calibration

Table 15.1 Test Equipment Calibration

EQUIPMENT SPECIFICATIONS		
Type	Calibration Date	Serial Number
CRS Robot F3	February 2002	RAF0134133
CRS C500C Motion Controller	February 2002	RCB0003303
CRS Teach Pendant (Joystick)	February 2002	STP0132231
DELL Computer, Pentium 4 1.6 GHz, Windows 2000™	February 2002	
E-Field Probe E-010	February 2002	PCT001
Right Ear SAM Phantom (P-SAM-R)	February 2002	
Left Ear SAM Phantom (P-SAM-L)	February 2002	
IDX Robot End Effector (EE-103-C)	February 2002	07111223
IDX Probe Amplifier	February 2002	07111113
Validation Dipole D-835S	February 2002	PCT640
Validation Dipole D-1900S	February 2002	PCT639
Brain Equivalent Matter (835MHz)	February 2002	PCTBEM101
Brain Equivalent Matter (1900MHz)	February 2002	PCTBEM301
Muscle Equivalent Matter (835MHz)	February 2002	PCTMEM201
Muscle Equivalent Matter (1900MHz)	February 2002	PCTMEM401
Microwave Amp. Model: 5S1G4, (800MHz - 4.2GHz)	January 2002	22332
Gigatronics 8651A Power Meter	January 2002	1835299
HP-8648D (9kHz ~ 4GHz) Signal Generator	January 2002	PCT530
Amplifier Research 5S1G4 Power Amp	January 2002	PCT540
HP-8753E (30kHz ~ 3GHz) Network Analyzer	January 2002	PCT552
HP85070B Dielectric Probe Kit	January 2002	PCT501
Ambient Noise/Reflection, etc.	<12mW/kg/<3%of SAR	January 2002

NOTE:

The E-field probe was calibrated by IDX, by temperature measurement procedure. Dipole Validation measurement is performed by PCTEST Lab. before each test. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

PCTEST™ SAR TEST REPORT	SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 31 of 33

16. CONCLUSION

Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.[3]

PCTEST™ SAR TEST REPORT	SAR EVALUATION REPORT			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 32 of 33

17. REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1 - 1991, *American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz*, New York: IEEE, Aug. 1992.
- [3] ANSI/IEEE C95.3 - 1991, *IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave*, New York: IEEE, 1992.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), *Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields*, July 2001.
- [5] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-200X (Draft 6.1 – July 2001), *Draft Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques*.
- [6] NCRP, National Council on Radiation Protection and Measurements, *Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields*, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, *Automated E-field scanning system for dosimetric assessments*, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, *Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies*, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Poković, T. Schmid, and N. Kuster, *E-field Probe with improved isotropy in brain simulating liquids*, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, *The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz*, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, *Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz*, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, *Simulated Biological Materials for Electromagnetic Radiation Absorption Studies*, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., *Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones*, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, *Computermathematick*, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, *Numerical Recepies in C*, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, *Dosimetric evaluation of mobile communications equipment with known precision*, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), *Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz*, Jan. 1995.
- [20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, *Dosimetric Evaluation of the Cellular Phone*.

PCTEST™ SAR TEST REPORT	 SAR EVALUATION REPORT 			Reviewed by: Quality Manager
SAR Filename: SAR.220219075.A3L	Test Dates: Feb. 20 - Mar.1, 2002	Phone Type: Tri-Mode Dual-Band	FCC ID: A3LSCHA310	Page 33 of 33

SAR Data Report 02013108

Start : 31-Jan-02 12:18:27 pm
End : 31-Jan-02 12:30:11 pm
Code Version : 4.03
Robot Version: 4.07

Product Data:

Type : Validation
Model Number :
Serial Number : 1
Frequency : 835
Peak Trans. Pwr : 0.250 W
Start Trans. Pwr : 0.250 W
Antenna Type : Dipole
Antenna Posn. :

Scan Data:

Phantom Name : SAM-FLAT
Phantom Type : Uniphantom
Mixture Type : Brain
Mixture Dielectric : 43.440
Mixture Conductivity : 0.870
Mixture Density : 1.000
Robot Name : CRS

Probe Data:

Probe Name : PCT001
Probe Type : E Fld Triangle
Frequency : 835
Mixture Type : Brain
Calibrated Dielectric : 40.700
Calibrated Conductivity : 0.890
Calibrated Density : 1.000
Probe Offset : 2.400 mm
Conversion Factor : 5.800
Probe Sensitivity : 3.597 3.474 3.049
Amplifier Gains : 20.00 20.00 20.00

Sample:

Rate: 6000 Samples/Sec
Count: 100 Samples
NIDAQ Gain: 5

Comments:

835 MHz Brain Validation

Area Scan - Max Peak SAR Value at -1.0 1.0 = 2.411361

Zoom Scan - Max Peak SAR Value at -1.0 0.0 0.0 = 3.901480


Max 1g SAR at -1.0 2.0 0.0 = 2.563772

Max 10g SAR at -1.0 2.0 0.0 = 1.595803


Validation Results:

Peak Nominal = 3.5, Error: 9.65 %
1g Nominal = 2.4, Error: 7.36 %
10g Nominal = 1.6, Error: 2.87 %

SAR - Z Axis
at Hotspot x:-1.0 y:0.0



1g SAR Values





SAR Data Report 02022011

Start : 20-Feb-02 02:10:21 pm
End : 20-Feb-02 02:22:16 pm
Code Version : 4.03
Robot Version: 4.07

Product Data:

Type : Validation
Model Number :
Frequency : 1900
Peak Trans. Pwr : 0.250 W
Peak Trans. Pwr : 0.250 W
Antenna Type : Dipole
Antenna Posn. :

Measurement Data:

Phantom Name : SAM-FLAT
Phantom Type : Uniphantom
Tissue Type : Brain
Tissue Dielectric : 40.290
Tissue Conductivity : 1.440
Tissue Density : 1.000
Robot Name : CRS

Probe Data:

Probe Name : PCT001
Probe Type : E Fld Triangle
Frequency : 1900
Tissue Type : Brain
Calibrated Dielectric : 40.200
Calibrated Conductivity : 1.410
Calibrated Density : 1.000
Probe Offset : 2.400 mm
Conversion Factor : 4.700
Probe Sensitivity : 3.000 2.995 2.653 mV/(mW/cm^2)
Amplifier Gains : 20.00 20.00 20.00

Sample:

Rate: 6000 Samples/Sec
Count: 100 Samples
NIDAQ Gain: 5

Comments:

1900 MHz Validation

Area Scan - Max Peak SAR Value at -1.0 -3.0 = 10.157430

Zoom Scan - Max Peak SAR Value at -1.0 -2.0 0.0 = 18.698346


Max 1g SAR at -1.0 -2.0 0.0 = 10.724172

Max 10g SAR at -1.0 -2.0 0.0 = 5.483933


Validation Results:


Peak Nominal = 18.0, Error: 3.74 %
1g Nominal = 9.9, Error: 8.05 %
10g Nominal = 5.1, Error: 7.00 %


SAR - Z Axis
at Hotspot x:-1.0 y:-2.0



1g SAR Values







Probe E-009

SN: PCT001

Manufactured:

October 19, 2001


Calibrated:

February 1, 2002

Calibrated for the IDX System


PCTEST Calibration Laboratory

Approved By:




Alfred Cirwithian
Vice President Engineering

File: 02-01-2001.cal
Date: 01-Feb-01 05:30:12 pm
Probe Name: PCT001
Frequency: 835 MHz
Comment: PCTEST TEM CAL
Amp 1 Setting: 20.000
Amp 2 Setting: 20.000
Amp 3 Setting: 20.000



File: 02-01-2001.cal2
Date: 02-Feb-01 04:09:01 pm
Probe Name: PCT001
Frequency: 1900 MHz
Comment: PCTEST TEM CAL
Amp 1 Setting: 20.000
Amp 2 Setting: 20.000
Amp 3 Setting: 20.000



PCT Calibration Laboratory

Calibration Data

Probe: PCT001

OFFSET (cm)	ANGLE (deg)
0.24	54.73

Tissue Type	Freq. (MHz)	Dielectric Constant	Conductivity (S/m)	Conversion Factor
Brain	835	40.7	0.89	5.8
Brain	1900	40.2	1.41	4.7
Muscle	835	55.7	0.99	4.9
Muscle	1900	53.9	1.48	5.0

Frequency	Isotropy	
	%	dB
835	4.06	0.173
1900	5.05	0.148

Calibrated by: *SL* Date: 03-01-2002