# PCTEST Engineering Laboratory, Inc.

*6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.*
*TEL (410) 290-6652 · FAX (410) 290-6654*
*http://www.pctestlab.com*




## CERTIFICATE OF COMPLIANCE
## FCC Part 24 & 22 Certification – Class II Permissive Change

**Samsung Electronics Co., Ltd.**
**3351 Michelson Drive, Suite 290**
**Irvine, CA 92612**

**Dates of Tests: October 29-31, 2003**
**Test Report S/N: 22/24.231029544.A3L**
**Test Site: PCTEST Lab, Columbia MD**

| | |
|---|---|
| **FCC ID** | **A3LSCHA650** |
| **APPLICANT** | **SAMSUNG ELECTRONICS CO., LTD.** |

| | |
|---|---|
| **Classification:** | **Licensed Portable Transmitter Held to Ear (PCE)** |
| **FCC Rule Part(s):** | **§24(E), §22(H), §22.901(d); §2** |
| **EUT Type:** | **Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA)** |
| **Model:** | ***SCH-A650*** |
| **Tx Frequency Range:** | **824.04MHz – 848.97MHz (AMPS) / 824.70 – 848.31MHz (CDMA)**<br>**1851.25MHz – 1908.75MHz (PCS CDMA)** |
| **Rx Frequency Range:** | **869.04MHz – 893.97MHz (AMPS) / 869.70 – 893.31MHz (CDMA)**<br>**1931.25MHz – 1988.75MHz (PCS CDMA)** |
| **Max. RF Output Power:** | **0.322 W ERP AMPS (25.073 dBm) / 0.255 W ERP CDMA (24.063 dBm)**<br>**0.324 W EIRP PCS CDMA (25.091 dBm)** |
| **Max. SAR Measurement:** | **1.33 W/kg AMPS Head SAR; 0.86 W/kg AMPS Body SAR;**<br>**1.04 W/kg CDMA Head SAR; 0.76 W/kg CDMA Body SAR;**<br>**1.47 W/kg PCS CDMA Head SAR; 1.00 W/kg PCS CDMA Body SAR** |
| **Emission Designator(s):** | **40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)** |
| **Test Device Serial No.** | **Identical Prototype [S/N: 3]** |
| **Original Grant Date:** | **October 14, 2003** |
| **Permissive Changes:** | **Changed antenna and antenna angle 4 degrees** |

**This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.**

**I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.**

**Grant conditions: Power output listed is ERP for Part 22 and EIRP for Part 24. SAR compliance for body-worn operating configuration is limited to the specific belt-clip/holster tested for this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance**

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

Alfred Cirwithian
Vice President Engineering

© 2003 PCTEST ENGINEERING LABORATORY, INC.

# TABLE OF CONTENTS


ATTACHMENT A: COVER LETTER(S)

ATTACHMENT B: ATTESTATION STATEMENT(S)

ATTACHMENT C: TEST REPORT

| | |
|---|---|
| 1.1 SCOPE | 3 |
| 2.1 INTRODUCTION | 4 |
| 3.1 INSERTS | 5 |
| 4.1 DESCRIPTION OF TESTS | 6-10 |
| 5.1 EFFECTIVE RADIATED POWER OUTPUT | 11-12 |
| 6.1 EQUIVALENT ISOTROPIC RADIATED POWER | 13 |
| 7.1 RADIATED MEASUREMENTS | 14-22 |
| 8.1 FREQUENCY STABILITY | 23-28 |
| 9.1 PLOTS OF EMISSIONS | 29 |
| 10.1 LIST OF TEST EQUIPMENT | 30 |
| 11.1 SAMPLE CALCULATIONS | 31 |
| 12.1 CONCLUSION | 32 |

ATTACHMENT D: TEST PLOTS

ATTACHMENT E: FCC ID LABEL / LOCATION

ATTACHMENT F: TEST SETUP PHOTOGRAPHS

ATTACHMENT G: EXTERNAL PHOTOGRAPHS

ATTACHMENT H: INTERNAL PHOTOGRAPHS

ATTACHMENT I: BLOCK DIAGRAM(S)

ATTACHMENT J: SCHEMATIC DIAGRAM(S)

ATTACHMENT K: OPERATIONAL / CIRCUIT DESCRIPTION

ATTACHMENT L: PARTS LIST/TUNE UP PROCEDURE

ATTACHMENT M: USER'S MANUAL

ATTACHMENT N: SAR MEASUREMENT REPORT

ATTACHMENT O: SAR TEST DATA

ATTACHMENT P: SAR TEST SETUP PHOTOGRAPHS

ATTACHMENT Q: DIPOLE VALIDATION

ATTACHMENT R: PROBE CALIBRATION




© 2003 PCTEST ENGINEERING LABORATORY, INC.

# MEASUREMENT REPORT



## 1.1 Scope

*Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.*

## §2.1033 General Information

| | |
|---|---|
| **Applicant Name:** | **SAMSUNG ELECTRONICS CO., LTD.** |
| **Address:** | **3351 Michelson Drive, Suite 290** |
| | **Irvine, CA 92612** |

- FCC ID: **A3LSCHA650**
- Quantity: Quantity production is planned
- Emission Designators: 40K0F8W / 40K0F1D (AMPS), 1M25F9W (CDMA)
- Tx Freq. Range: 824.04 – 848.97 MHz (AMPS)<br>824.70 – 848.31 MHz (CDMA)<br>1851.25 – 1908.75 MHz (PCS CDMA)
- Rx Freq. Range: 869.04 – 893.97 MHz (AMPS)<br>869.70 – 893.31 MHz (CDMA)<br>1931.25 – 1988.75 MHz (PCS CDMA)
- Max. Power Rating: 0.322 W ERP AMPS (25.073 dBm) / 0.255 W ERP CDMA (24.063 dBm)<br>0.324 W EIRP PCS CDMA (25.091 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Tri-Mode Dual-Band Analog/PCS Phone
- Modulation(s): AMPS / CDMA
- Frequency Tolerance: ± 0.00025% (2.5 ppm)
- FCC Rule Part(s): § 24(E), §22(H), §22.901(d)
- Dates of Tests: October 29-31, 2003
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22/24.231029544.A3L
- Original Grant Date: October 14, 2003
- Permissive Changes: Changed antenna and antenna angle 4 degrees



© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 2.1 INTRODUCTION




**Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.**

These measurement tests were conducted at ***PCTEST Engineering Laboratory, Inc.*** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.




**Figure 2. Diagram of 3-meter outdoor test range**

### Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 3.1 INSERTS

### Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

### Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

### Operating Instructions

The instruction manual is shown in Attachment M.

### Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

### Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

### Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 4.1 DESCRIPTION OF TESTS

## 4.2 Transmitter Audio Frequency Response

The frequency response of the audio modulating circuit over the frequency range 100 – 5000 Hz is measured. The audio signal generator is connected to the audio input circuit/microphone of the EUT. The audio signal input is adjusted to obtain 50% modulation at 1kHz and this point is taken as the 0dB reference. With the input held constant and below the limit at all frequencies, the audio signal generator is varied from 100 to 50 kHz.

## 4.3 Audio Low Pass Filter Frequency Response

The response in dB relative to 1kHz is measured using the HP8901 a Modulation Analyzer. For the frequency response of the audio low-pass filter, the audio input is connected at the input to the modulation limiter and the modulated stage. The audio output is connected at the output of the modulated stage. The corresponding plots are shown herein.

## 4.4 Modulation Limiting

The audio signal generator is connected to the audio input circuit/microphone of the EUT. The modulation response is measured for each of the three modulating frequencies (300Hz, 1000 Hz, and 3000Hz), and the input voltage is varied from 30% modulation (±3.6kHz deviation) to at least 20dB higher than the saturation point. Measurements of modulation and the plots are attached herein. Measurements were performed for ST, SAT, and wide-band data modulations. The corresponding results are shown herein.

Note: ST, SAT, & Wide-Band data were internally generated by the EUT.




Fig. 3. Transmitter Audio Frequency & Tone Modulation Test Setup.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 4.1 DESCRIPTION OF TESTS (CONTINUED)

## 4.5 Occupied Bandwidth Emission Limits

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

## 4.6 Cellular - Base Frequency Blocks




**BLOCK 1: 869 – 880 MHz (A* Low + A)**

**BLOCK 2: 880 – 890 MHz (B)**

**BLOCK 3: 890 – 891.5 MHz (A* High)**

**BLOCK 4: 891.5 – 894 MHz (B*)**

## 4.7 Cellular - Mobile Frequency Blocks




**BLOCK 1: 824 – 835 MHz (A* Low + A)**

**BLOCK 2: 835 – 845 MHz (B)**

**BLOCK 3: 845 – 846.5 MHz (A* High)**

**BLOCK 4: 846.5 – 849 MHz (B*)**



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 4.1 DESCRIPTION OF TESTS (CONTINUED)

## 4.8 PCS - Base Frequency Blocks




**BLOCK 1: 1930 – 1945 MHz (A)**

**BLOCK 2: 1945 – 1950 MHz (D)**

**BLOCK 3: 1950 – 1965 MHz (B)**

**BLOCK 4: 1965 – 1970 MHz (E)**

**BLOCK 5: 1970 – 1975 MHz (F)**

**BLOCK 6: 1975 – 1990 MHz (C)**

## 4.9 PCS - Mobile Frequency Blocks




**BLOCK 1: 1850 – 1865 MHz (A)**

**BLOCK 2: 1865 – 1870 MHz (D)**

**BLOCK 3: 1870 – 1885 MHz (B)**

**BLOCK 4: 1885 – 1890 MHz (E)**

**BLOCK 5: 1890 – 1895 MHz (F)**

**BLOCK 6: 1895 – 1910 MHz (C)**



© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 4.10 Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is set to ±6kHz deviation. With the level constant, the frequency is set to 2500Hz. Then the audio signal level is increased by 16dB. The occupied bandwidth data is obtained for the SAT (Supervisory Audio Tone), ST (Signaling Tone), WBD (Wideband data), and DTMF (Dual Tone Multi Frequencies). The results are shown on the attached graphs.

Specified Limits:

a. On any frequency removed from the assigned carrier frequency by more than 20 kHz, up to and including 45kHz, the sideband is at least 26dB below the carrier.

b. On any frequency removed from the assigned carrier frequency by more than 45 kHz, up to and including 90kHz, the sideband is at least 45dB below the carrier.

c. On any frequency removed from the assigned carrier frequency by more than 90 kHz, up to the first multiple of the carrier frequency, the sideband is at least 60dB below the carrier or 40 + $\log_{10}$ (mean power output in Watts) dB, whichever is the smaller attenuation.

## 4.11 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

## 4.12 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

## 4.13 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5 ppm) of the center frequency*.

**Time Period and Procedure:**

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

**NOTE: The EUT is tested down to the battery endpoint.**



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 5.1 Test Data

## 5.2 Effective Radiated Power Output

A. POWER: **Low (Analog Mode)**

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) |
|---|---|---|---|---|
| 824.04 | -36.300 | H | 0.003 | 4.973 |
| 836.49 | -36.355 | H | 0.003 | 5.074 |
| 848.97 | -36.550 | H | 0.003 | 5.035 |

B. POWER: **High (Analog Mode)**

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | BATTERY |
|---|---|---|---|---|---|
| 824.04 | -16.300 | H | 0.314 | 24.973 | Standard |
| 836.49 | -16.355 | H | 0.322 | 25.074 | Standard |
| 848.97 | -16.550 | H | 0.319 | 25.035 | Standard |
| 836.49 | -16.360 | H | 0.321 | 25.069 | Extended |

Note: Standard and extended batteries are the only options for this phone

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 5.1 Test Data

## 5.3 Effective Radiated Power Output

A. POWER: **High (CDMA Mode)**

| Freq. Tuned (MHz) | REF. LEVEL (dBm) | POL (H/V) | ERP (W) | ERP (dBm) | BATTERY |
|---|---|---|---|---|---|
| 824.70 | -17.300 | H | 0.250 | 23.973 | Standard |
| 835.89 | -17.370 | H | 0.255 | 24.063 | Standard |
| 848.31 | -17.580 | H | 0.251 | 24.003 | Standard |
| 835.89 | -17.400 | H | 0.253 | 24.033 | Extended |

Note: Standard and extended batteries are the only options for this phone

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 6.1 Test Data

## 6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

**Radiated measurements at 3 meters**

**Supply Voltage: 3.7 VDC**

**Modulation: PCS CDMA**

| FREQ. (MHz) | REF. LEVEL (dBm) | POL (H/V) | Azimuth (o angle) | EIRP (dBm) | EIRP (W) | Battery |
|---|---|---|---|---|---|---|
| 1851.25 | -18.070 | H | 60 | 25.011 | 0.318 | Standard |
| 1880.00 | -18.150 | H | 60 | 25.101 | 0.324 | Standard |
| 1908.75 | -18.400 | H | 60 | 25.021 | 0.319 | Standard |
| 1880.00 | -18.153 | H | 60 | 25.098 | 0.324 | Extended |

Note: Standard and extended batteries are the only options for this phone

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data

## 7.2 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
CHANNEL: 0991 (Low)
MEASURED OUTPUT POWER: 25.074 dBm = 0.322 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 38.07 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1648.08 | -50.68 | 6.10 | -44.58 | H | 69.7 |
| 2472.12 | -63.28 | 6.70 | -56.58 | H | 81.7 |
| 3296.16 | -79.68 | 6.80 | -72.88 | H | 98.0 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.


© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.3 AMPS Radiated Measurements

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz
CHANNEL: 0383 (Mid)
MEASURED OUTPUT POWER: 25.074 dBm = 0.322 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W)$ = 38.07 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1672.98 | -51.98 | 6.10 | -45.88 | H | 71.0 |
| 2509.47 | -64.08 | 6.70 | -57.38 | H | 82.5 |
| 3345.96 | -79.48 | 6.80 | -72.68 | H | 97.8 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.4 AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
CHANNEL: 0799 (High)
MEASURED OUTPUT POWER: 25.074 dBm = 0.322 W
MODULATION SIGNAL: FM (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 38.07 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1697.94 | -53.58 | 6.10 | -47.48 | V | 72.6 |
| 2546.91 | -65.88 | 6.70 | -59.18 | V | 84.3 |
| 3395.88 | -78.28 | 6.80 | -71.48 | V | 96.6 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.5 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| | | | | |
|---|---|---|---|---|
| OPERATING FREQUENCY: | 824.70 | MHz | | |
| CHANNEL: | 1013 (Low) | | | |
| MEASURED OUTPUT POWER: | 24.063 | dBm | = | 0.255 W |
| MODULATION SIGNAL: | CDMA (Internal) | | | |
| DISTANCE: | 3 | meters | | |
| LIMIT: | 43 + 10 $\log_{10}$ (W) = | 37.06 | dBc | |

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1649.40 | -57.38 | 6.10 | -51.28 | V | 75.3 |
| 2474.10 | -66.28 | 6.70 | -59.58 | V | 83.6 |
| 3298.80 | -78.58 | 6.80 | -71.78 | V | 95.8 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.6 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| | | | | |
|---|---|---|---|---|
| OPERATING FREQUENCY: | 835.89 | MHz | | |
| CHANNEL: | 0363 (Mid) | | | |
| MEASURED OUTPUT POWER: | 24.063 | dBm | = | 0.255 W |
| MODULATION SIGNAL: | CDMA (Internal) | | | |
| DISTANCE: | 3 | meters | | |
| LIMIT: | 43 + 10 $\log_{10}$ (W) = | 37.06 | dBc | |

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1671.78 | -51.78 | 6.10 | -45.68 | V | 69.7 |
| 2507.67 | -61.08 | 6.70 | -54.38 | V | 78.4 |
| 3343.56 | -75.48 | 6.80 | -68.68 | V | 92.7 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.7 CELLULAR CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

| | | | | |
|---|---|---|---|---|
| OPERATING FREQUENCY: | 848.31 | MHz | | |
| CHANNEL: | 0777 (High) | | | |
| MEASURED OUTPUT POWER: | 24.063 | dBm | = | 0.255 W |
| MODULATION SIGNAL: | CDMA (Internal) | | | |
| DISTANCE: | 3 | meters | | |
| LIMIT: | 43 + 10 $\log_{10}$ (W) = | 37.06 | dBc | |

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 1696.62 | -51.68 | 6.10 | -45.58 | V | 69.6 |
| 2544.93 | -63.78 | 6.70 | -57.08 | V | 81.1 |
| 3393.24 | -77.08 | 6.80 | -70.28 | V | 94.3 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.8 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
CHANNEL: 0025 (Low)
MEASURED OUTPUT POWER: 25.101 dBm = 0.324 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W)$ = 38.11 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 3702.50 | -37.53 | 8.70 | -28.83 | V | 53.9 |
| 5553.75 | -47.23 | 9.70 | -37.53 | V | 62.6 |
| 7405.00 | -56.43 | 9.90 | -46.53 | V | 71.6 |
| 9256.25 | -69.43 | 11.40 | -58.03 | V | 83.1 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.9 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 0600 (Mid)
MEASURED OUTPUT POWER: 25.101 dBm = 0.324 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W)$ = 38.11 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 3760.00 | -37.23 | 8.70 | -28.53 | V | 53.6 |
| 5640.00 | -43.03 | 9.70 | -33.33 | V | 58.4 |
| 7520.00 | -58.13 | 9.90 | -48.23 | V | 73.3 |
| 9400.00 | -69.23 | 11.40 | -57.83 | V | 82.9 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 7.1 Test Data (Continued)

## 7.10 PCS CDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
CHANNEL: 1175 (High)
MEASURED OUTPUT POWER: 25.101 dBm = 0.324 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 38.11 dBc

| FREQ. (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | CORRECT GENERATOR LEVEL (dBm) | POL (H/V) | (dBc) |
|---|---|---|---|---|---|
| 3817.50 | -38.93 | 8.70 | -30.23 | V | 55.3 |
| 5726.25 | -61.83 | 9.70 | -52.13 | V | 77.2 |
| 7635.00 | -71.93 | 9.90 | -62.03 | V | 87.1 |
| 9543.75 | -77.93 | 11.40 | -66.53 | V | 91.6 |

**NOTES:**

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:
The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.


© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data

## 8.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: 836,490,002 Hz

CHANNEL: 383

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%) | POWER (VDC) | TEMP (ºC) | FREQ. (Hz) | Deviation (%) |
|---|---|---|---|---|
| 100 % | 3.70 | + 20 (Ref) | 836,490,002 | 0.000000 |
| 100 % | | - 30 | 836,489,751 | 0.000030 |
| 100 % | | - 20 | 836,489,701 | 0.000036 |
| 100 % | | - 10 | 836,489,768 | 0.000028 |
| 100 % | | 0 | 836,489,692 | 0.000037 |
| 100 % | | + 10 | 836,489,659 | 0.000041 |
| 100 % | | + 20 | 836,490,002 | 0.000000 |
| 100 % | | + 25 | 836,489,843 | 0.000019 |
| 100 % | | + 30 | 836,489,776 | 0.000027 |
| 100 % | | + 40 | 836,489,709 | 0.000035 |
| 100 % | | + 50 | 836,489,768 | 0.000028 |
| 100 % | | + 60 | 836,489,600 | 0.000048 |
| 85 % | 3.15 | + 20 | 836,490,002 | 0.000000 |
| 115 % | 4.26 | + 20 | 836,490,002 | 0.000000 |
| BATT. ENDPOINT | 2.95 | + 20 | 836,490,002 | 0.000000 |



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data (Continued)

## 8.3 FREQUENCY STABILITY (AMPS)






© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data

## 8.4 FREQUENCY STABILITY (CDMA 800 MHz)

OPERATING FREQUENCY: 835,890,002 Hz

CHANNEL: 363

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%) | POWER (VDC) | TEMP (ºC) | FREQ. (Hz) | Deviation (%) |
|---|---|---|---|---|
| 100 % | 3.70 | + 20 (Ref) | 835,890,002 | 0.000000 |
| 100 % | | - 30 | 835,889,801 | 0.000024 |
| 100 % | | - 20 | 835,889,735 | 0.000032 |
| 100 % | | - 10 | 835,889,701 | 0.000036 |
| 100 % | | 0 | 835,889,684 | 0.000038 |
| 100 % | | + 10 | 835,889,852 | 0.000018 |
| 100 % | | + 20 | 835,890,002 | 0.000000 |
| 100 % | | + 25 | 835,889,927 | 0.000009 |
| 100 % | | + 30 | 835,889,902 | 0.000012 |
| 100 % | | + 40 | 835,889,709 | 0.000035 |
| 100 % | | + 50 | 835,889,617 | 0.000046 |
| 100 % | | + 60 | 835,889,598 | 0.000048 |
| 85 % | 3.15 | + 20 | 835,890,002 | 0.000000 |
| 115 % | 4.26 | + 20 | 835,890,002 | 0.000000 |
| BATT. ENDPOINT | 3.10 | + 20 | 835,890,002 | 0.000000 |



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data (Continued)

## 8.5 FREQUENCY STABILITY (CDMA 800 MHz)






© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data (Continued)

## 8.6 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1,880,000,005 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 3.7 VAC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%) | POWER (VDC) | TEMP (ºC) | FREQ. (Hz) | Deviation (%) |
|---|---|---|---|---|
| 100 % | 3.70 | + 20 (Ref) | 1,880,000,005 | 0.000000 |
| 100 % | | - 30 | 1,879,999,742 | 0.000014 |
| 100 % | | - 20 | 1,879,999,460 | 0.000029 |
| 100 % | | - 10 | 1,879,999,347 | 0.000035 |
| 100 % | | 0 | 1,879,999,178 | 0.000044 |
| 100 % | | + 10 | 1,879,999,103 | 0.000048 |
| 100 % | | + 20 | 1,880,000,005 | 0.000000 |
| 100 % | | + 25 | 1,879,999,723 | 0.000015 |
| 100 % | | + 30 | 1,879,999,516 | 0.000026 |
| 100 % | | + 40 | 1,879,999,347 | 0.000035 |
| 100 % | | + 50 | 1,879,999,272 | 0.000039 |
| 100 % | | + 60 | 1,879,999,121 | 0.000047 |
| 85 % | 3.15 | + 20 | 1,880,000,005 | 0.000000 |
| 115 % | 4.26 | + 20 | 1,880,000,005 | 0.000000 |
| BATT. ENDPOINT | 3.05 | + 20 | 1,880,000,005 | 0.000000 |



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 8.1 Test Data (Continued)

## 8.7 FREQUENCY STABILITY (PCS CDMA)






© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 9.1 PLOT(S) OF EMISSIONS

**(SEE ATTACHMENT D)**



© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 10.1 TEST EQUIPMENT

| Type | Model | Cal. Due Date | S/N |
|---|---|---|---|
| Microwave Spectrum Analyzer | HP 8566B (100Hz-22GHz) | 08/15/04 | 3638A08713 |
| Microwave Spectrum Analyzer | HP 8566B (100Hz-22GHz) | 04/17/04 | 2542A11898 |
| Spectrum Analyzer/Tracking Gen. | HP 8591A (100Hz-1.8GHz) | 08/10/04 | 3144A02458 |
| Signal Generator* | HP 8640B (500Hz-1GHz) | 06/03/04 | 2232A19558 |
| Signal Generator* | HP 8640B (500Hz-1GHz) | 06/03/04 | 1851A09816 |
| Signal Generator* | Rohde & Schwarz (0.1-1000MHz) | 09/11/04 | 894215/012 |
| Ailtech/Eaton Receiver | NM 37/57A-SL (30-1000MHz) | 04/12/04 | 0792-03271 |
| Ailtech/Eaton Receiver | NM 37/57A (30-1000MHz) | 03/11/04 | 0805-03334 |
| Ailtech/Eaton Receiver | NM 17/27A (0.1-32MHz) | 09/17/04 | 0608-03241 |
| Quasi-Peak Adapter | HP 85650A | 08/15/04 | 2043A00301 |
| Ailtech/Eaton Adapter | CCA-7 CISPR/ANSI QP Adapter | 03/11/04 | 0194-04082 |
| Gigatronics Universal Power Meter | 8657A | | 1835256 |
| Gigatronics Power Sensor | 80701A (0.05-18GHz) | | 1833460 |
| Signal Generator | HP 8648D (9kHz-4GHz) | | 3613A00315 |
| Amplifier Research | 5S1G4 (5W, 800MHz-4.2GHz) | | 22322 |
| Network Analyzer | HP 8753E (30kHz-3GHz) | | JP38020182 |
| Audio Analyzer | HP 8903B | | 3011A09025 |
| Modulation Analyzer | HP 8901A | | 2432A03467 |
| Power Meter | HP 437B | | 3125U24437 |
| Power Sensor | HP 8482H (30µW-3W) | | 2237A02084 |
| Harmonic/Flicker Test System | HP 6841A (IEC 555-2/3) | | 3531A00115 |
| Broadband Amplifier (2) | HP 8447D | | 1145A00470, 1937A03348 |
| Broadband Amplifier | HP 8447F | | 2443A03784 |
| Horn Antenna | EMCO Model 3115 (1-18GHz) | | 9704-5182 |
| Horn Antenna | EMCO Model 3115 (1-18GHz) | | 9205-3874 |
| Horn Antenna | EMCO Model 3116 (18-40GHz) | | 9203-2178 |
| Biconical Antenna (4) | Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design | | 1295, 1332, 0355 |
| Log-Spiral Antenna (3) | Ailtech/Eaton 93490-1 | | 0608, 1103, 1104 |
| Roberts Dipoles | Compliance Design (1 set) | | |
| Ailtech Dipoles | DM-105A (1 set) | | 33448-111 |
| EMCO LISN (6) | 3816/2 | | 1079 |
| Microwave Preamplifier 40dB Gain | HP 83017A (0.5-26.5GHz) | | 3123A00181 |
| Microwave Cables | MicroCoax (1.0-26.5GHz) | | |
| Ailtech/Eaton Receiver | NM37/57A-SL | | 0792-03271 |
| Spectrum Analyzer | HP 8594A | | 3051A00187 |
| Spectrum Analyzer (2) | HP 8591A | | 3034A01395, 3108A02053 |
| Microwave Survey Meter | Holaday Model 1501 (2.450GHz) | | 80931 |
| Digital Thermometer | Extech Instruments 421305 | | 426966 |
| Attenuator | HP 8495A (0-70dB) DC-4GHz | | |
| Bi-Directional Coax Coupler | Narda 3020A (50-1000MHz) | | |
| Shielded Screen Room | RF Lindgren Model 26-2/2-0 | | 6710 (PCT270) |
| Shielded Semi-Anechoic Chamber | Ray Proof Model S81 | | R2437 (PCT278) |
| Enviromental Chamber | Associated Systems Model 1025 (Temperature/Humidity) | | PCT285 |

* Calibration traceable to the National Institute of Standards and Technology (NIST).



© 2003 PCTEST ENGINEERING LABORATORY, INC.

# 11.1 SAMPLE CALCULATIONS

## A. Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)
(Measured at the 99.75% power bandwidth)

**Emission Designator = 40K0F8W**

Calculation: Voice + SAT
Modulation: Voice is 2.5 kHz and SAT is 6 kHz – Maximum modulation is M = 6 kHz
Deviation: Voice is 12 kHz and SAT is 2 kHz – Maximum deviation is D = 12 + 2 = 14 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

Calculation: Signaling Tone (ST) + SAT
Modulation: ST is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz
Deviation: ST is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

**Emission Designator = 40K0F1D**

Calculation: Voice + SAT
Modulation: Wideband Data is 10 kHz and SAT is 6 kHz – Maximum modulation is M = 10 kHz
Deviation: Wideband Data is 8 kHz and SAT is 2 kHz – Maximum deviation is D = 8 + 2 = 10 kHz
Bn = 2xM + 2xDK with K = 1
Bn = 40 kHz

## B. Spurious Radiated Emission - PCS Band

**Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)**

The receive analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc


© 2003 PCTEST ENGINEERING LABORATORY, INC.

## 12.1 CONCLUSION

The data collected shows that the **Samsung Electronics Co., Ltd. Tri-Mode Dual-Band Analog/PCS Phone (AMPS/CDMA) FCC ID: A3LSCHA650** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.



© 2003 PCTEST ENGINEERING LABORATORY, INC.