



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 22 & 24

Applicant Name:

Samsung Electronics Co., Ltd.
416 Maetan 3-Dong, Yeongtong-gu
Suwon-si, Gyeonggi-do
443-742, Republic of Korea

Date of Testing:

Oct. 8-31, 2012

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1210111496.A3L

FCC ID:**A3LSCHI939D****APPLICANT:****SAMSUNG ELECTRONICS CO., LTD.****Application Type:**

Certification

Model(s):

SCH-I939D

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

§2; §22(H), §24(E)

Test Procedure(s):

ANSI/TIA-603-C-2004, KDB 971168

Test Device Serial No.:

identical prototype [S/N: FJ-256-B, FJ256-D]

Mode	Tx Frequency (MHz)	Emission Designator	ERP/EIRP	
			Max. Power (W)	Max. Power (dBm)
GSM1900	1850.2 - 1909.8	244KGXW	0.552	27.42
EDGE1900	1850.2 - 1909.8	238KG7W	0.381	25.81
CDMA850	824.7 - 848.31	1M27F9W	0.072	18.58
CDMA1900	1851.25 - 1908.75	1M27F9W	0.206	23.14

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortañez
President




FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 1 of 48

TABLE OF CONTENTS

FCC PART 22 & 24 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
3.0 DESCRIPTION OF TESTS	6
3.1 EVALUATION PROCEDURE	6
3.2 CELLULAR - BASE FREQUENCY BLOCKS	6
3.3 CELLULAR - MOBILE FREQUENCY BLOCKS	6
3.4 PCS - BASE FREQUENCY BLOCKS	6
3.5 PCS - MOBILE FREQUENCY BLOCKS	7
3.6 OCCUPIED BANDWIDTH	7
3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	7
3.8 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.9 PEAK-AVERAGE RATIO	9
3.10 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS	12
6.1 SUMMARY	12
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA	13
6.3 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA	14
6.4 CELLULAR CDMA RADIATED MEASUREMENTS	15
6.5 PCS GSM RADIATED MEASUREMENTS	18
6.6 PCS CDMA RADIATED MEASUREMENTS	21
6.7 CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS	24
6.8 PCS GSM FREQUENCY STABILITY MEASUREMENTS	26
6.9 PCS CDMA FREQUENCY STABILITY MEASUREMENTS	28
7.0 PLOTS OF EMISSIONS	30
8.0 CONCLUSION	48

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 2 of 48



MEASUREMENT REPORT

FCC Part 22 & 24




§2.1033 General Information

APPLICANT: Samsung Electronics Co., Ltd.
APPLICANT ADDRESS: 416 Maetan 3-Dong, Yeongtong-gu
 Suwon-si, Gyeonggi-do, 443-742, Republic of Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): §2; §22(H), §24(E)
BASE MODEL: SCH-I939D
FCC ID: A3LSCHI939D
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
MODE: GSM/EDGE/CDMA/EvDO
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: FJ-256-B, FJ256-D ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: Oct. 8-31, 2012
TEST REPORT S/N: 0Y1210111496.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 3 of 48

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 4 of 48

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSCHI939D**. The test data contained in this report pertains only to the emissions due to the EUT's GSM and CDMA transmitters.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0 (BC0, BC1), 1900 GSM/GPRS/EDGE, 802.11a/b/g/n WLAN (DTS/NII), Bluetooth (1x,EDR, LE), NFC

2.3 Test Configuration

The Samsung Portable Handset FCC ID: A3LSCHI939D was tested per the guidance of ANSI/TIA-603-C-2004 and KDB 971168. See Section 3.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 5 of 48


3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure


The measurement procedures described in the "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-C-2004) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" were used in the measurement of the measurement of the **Samsung Portable Handset FCC ID: A3LSCHI939D**.

Deviation from Measurement Procedure.....None


3.2 Cellular - Base Frequency Blocks



3.3 Cellular - Mobile Frequency Blocks




3.4 PCS - Base Frequency Blocks



FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 6 of 48

3.5 PCS - Mobile Frequency Blocks



3.6 Occupied Bandwidth

§2.1049, RSS-Gen (4.6.1)

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The spectrum analyzers' "occupied bandwidth" measurement function was used to record the occupied bandwidth in accordance with KDB 971168.

3.7 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a)(b), 24.238(a)(b); RSS-132 (4.5.1), RSS-133 (6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 7 of 48

3.8 Radiated Power and Radiated Spurious Emissions

§2.1053, 22.913(a)(2), 22.917(a), 24.232(c), 24.238(a); RSS-132 (4.5.1), RSS-133 (6.5.1)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

The equipment under test was transmitting while connected to its integral antenna and is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168.

Per the guidance of ANSI/TIA-603-C-2004, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power}_{\text{[Watts]}})$ specified in 22.917(a) and 24.238(a).

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 8 of 48

3.9 Peak-Average Ratio

§24.232(d); RSS-133 (6.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

For GSM signals, the spectrum analyzer is set to use an internal “RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to 400 μ s to ensure that energy is only captured during a time in which the transmitter is operating at maximum power. For CDMA, the trigger is set to “free run” in the CCDF measurement mode.

3.10 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235; RSS-132 (4.3) / RSS-133 (6.3)

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-C-2004. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 9 of 48

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE2	Radiated Emissions Cable Set (VHF/UHF)	2/13/2012	Annual	2/13/2013	N/A
-	LTx2	Licensed Transmitter Cable Set	2/17/2012	Annual	2/17/2013	N/A
Agilent	N9020A	MXA Signal Analyzer	10/9/2012	Annual	10/9/2013	US46470561
Espec	ESX-2CA	Environmental Chamber	4/4/2012	Annual	4/4/2013	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	7/22/2011	Biennial	7/22/2013	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	5/30/2012	Annual	5/30/2013	135427
Mini-Circuits	VHF-3100+	High Pass Filter	1/15/2012	Annual	1/15/2013	30841
Mini-Circuits	VHF-1300+	High Pass Filter	2/7/2012	Annual	2/7/2013	30716
Rohde & Schwarz	CMU200	Base Station Simulator	N/A		N/A	836371/0079
Rohde & Schwarz	RS-PR18	1-18 GHz Pre-Amplifier	6/26/2012	Annual	6/26/2013	100071
Rohde & Schwarz	RS-PR26	18-26.5 GHz Pre-Amplifier	5/30/2012	Annual	5/30/2013	100040
Rohde & Schwarz	ESU26	EMI Test Receiver	12/15/2011	Annual	12/15/2012	100342
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	11/14/2011	Biennial	11/14/2013	9105-2404
Seekonk	NC-100	Torque Wrench (8" lb)	3/5/2012	Triennial	3/5/2015	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/26/2012	Biennial	1/26/2014	A051107

Table 4-1. Test Equipment

Note:

Equipment used for signaling with a calibration date of "N/A" shown in this list was only used for maintaining a link between the piece of equipment and the EUT. This equipment was not used to make direct calibrated measurements.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 10 of 48

5.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz
 G = Phase Modulation
 X = Cases not otherwise covered
 W = Combination (Audio/Data)

CDMA Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz
 F = Frequency Modulation
 9 = Composite Digital Info
 W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: GSM Channel 512 PCS Mode 2nd Harmonic (3700.40 MHz)

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 11 of 48

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSCHI939D
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM/EDGE/CDMA/EvDO

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
2.1049, 22.917(a), 24.238(a)	RSS-Gen (4.6.1) RSS-133 (2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a), 24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge / Conducted Spurious Emissions	$< 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Section 7.0
24.232(d)	RSS-133 (6.4)	Peak-Average Ratio	$< 13 \text{ dB}$		PASS	Section 7.0
2.1046	RSS-132 (4.4) RSS-133 (4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
22.913(a)(2)	RSS-132 (4.4) [SRSP-503(5.1.3)]	Effective Radiated Power	$< 7 \text{ Watts max. ERP}$	RADIATED	PASS	Section 6.2
24.232(c)	RSS-133 (6.4) [SRSP-510 (5.1.2)]	Equivalent Isotropic Radiated Power	$< 2 \text{ Watts max. EIRP}$		PASS	Section 6.3
2.1053, 22.917(a), 24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Undesirable Emissions	$< 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Sections 6.4, 6.5, 6.6
2.1055, 22.355, 24.235	RSS-132 (4.3) RSS-133 (6.3)	Frequency Stability	$< 2.5 \text{ ppm}$ (Part 22) Emission must remain in band (Part 24)		PASS	Sections 6.7, 6.8, 6.9

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in Section 7.0 were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 12 of 48

6.2 Effective Radiated Power Output Data

§22.913(a)(2); RSS-132 (4.4) [SRSP-503(5.1.3)]

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]
824.70	CDMA850	Standard	13.92	4.66	H	18.58	0.072	38.45	-19.87
836.52	CDMA850	Standard	13.61	4.80	H	18.41	0.069	38.45	-20.04
848.31	CDMA850	Standard	12.92	4.95	H	17.87	0.061	38.45	-20.58

Table 6-2. Effective Radiated Power Output Data (CDMA)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION)					Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset				Page 13 of 48	

6.3 Equivalent Isotropic Radiated Power Output Data

§24.232(c); RSS-133 (6.4) [SRSP-510 (5.1.2)]

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GSM1900	Standard	18.71	8.56	H	27.27	0.533	33.01	-5.74
1880.00	GSM1900	Standard	18.87	8.55	H	27.42	0.552	33.01	-5.59
1909.80	GSM1900	Standard	18.35	8.53	H	26.88	0.488	33.01	-6.13
1800.00	EDGE1900	Standard	17.26	8.55	H	25.81	0.381	33.01	-7.20

Table 6-3. Equivalent Isotropic Radiated Power Output Data (GSM)

Frequency [MHz]	Mode	Battery Type	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1851.25	CDMA1900	Standard	12.30	8.56	H	20.86	0.122	33.01	-12.15
1880.00	CDMA1900	Standard	14.59	8.55	H	23.14	0.206	33.01	-9.87
1908.75	CDMA1900	Standard	14.37	8.53	H	22.90	0.195	33.01	-10.11

Table 6-4. Equivalent Isotropic Radiated Power Output Data (CDMA)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)					Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset				Page 14 of 48	

6.4 Cellular CDMA Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 18.58 dBm = 0.072 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 31.57 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-60.50	2.59	-57.92	H	76.5
2474.10	-90.87	2.89	-87.98	H	106.6
3298.80	-92.84	5.45	-87.39	H	106.0
4123.50	-66.41	7.05	-59.36	H	77.9
4948.20	-92.58	7.87	-84.71	H	103.3

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 15 of 48

Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MEASURED OUTPUT POWER: 18.41 dBm = 0.069 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 31.39 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-58.04	2.34	-55.70	H	74.1
2509.56	-90.52	2.84	-87.69	H	106.1
3346.08	-93.15	5.64	-87.51	H	105.9
4182.60	-66.38	7.14	-59.23	H	77.6
5019.12	-92.53	7.97	-84.56	H	103.0

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 16 of 48

Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 17.87 dBm = 0.061 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 30.85 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-50.63	2.09	-48.54	H	66.4
2544.93	-90.70	3.16	-87.54	H	105.4
3393.24	-93.45	5.83	-87.62	H	105.5
4241.55	-66.13	7.24	-58.89	H	76.8
5089.86	-92.42	8.02	-84.40	H	102.3

Table 6-7. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 17 of 48

6.5 PCS GSM Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 27.27 dBm = 0.533 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.27 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-62.87	8.40	-54.47	H	81.7
5550.60	-60.93	10.62	-50.30	H	77.6
7400.80	-56.28	11.82	-44.46	H	71.7
9251.00	-52.38	13.30	-39.08	H	66.4
11101.20	-48.18	13.50	-34.68	H	62.0

Table 6-8. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 18 of 48

PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 27.42 dBm = 0.552 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.42 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-56.50	8.42	-48.08	H	75.5
5640.00	-57.66	10.66	-47.00	H	74.4
7520.00	-54.76	11.92	-42.84	H	70.3
9400.00	-52.79	13.24	-39.55	H	67.0
11280.00	-55.01	13.49	-41.52	H	68.9

Table 6-9. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 19 of 48

PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 26.88 dBm = 0.488 W
 MODULATION SIGNAL: GSM (GMSK)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.88 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-43.99	8.57	-35.42	H	62.3
5729.40	-58.87	10.69	-48.18	H	75.1
7639.20	-54.53	12.07	-42.46	H	69.3
9549.00	-53.86	13.20	-40.66	H	67.5
11458.80	-49.51	13.42	-36.09	H	63.0

Table 6-10. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 20 of 48

6.6 PCS CDMA Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 20.86 dBm = 0.122 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 33.86 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-41.87	8.40	-33.47	H	54.3
5553.75	-64.40	10.62	-53.78	H	74.6
7405.00	-63.02	11.82	-51.19	H	72.1
9256.25	-62.46	13.30	-49.16	H	70.0
11107.50	-85.85	13.50	-72.35	H	93.2

Table 6-11. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 21 of 48

PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 600
 MEASURED OUTPUT POWER: 23.14 dBm = 0.206 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 36.14 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-45.09	8.42	-36.67	H	59.8
5640.00	-65.33	10.66	-54.67	H	77.8
7520.00	-63.00	11.92	-51.08	H	74.2
9400.00	-62.94	13.24	-49.70	H	72.8
11280.00	-87.66	13.49	-74.17	H	97.3

Table 6-12. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 22 of 48

PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
 CHANNEL: 1175
 MEASURED OUTPUT POWER: 22.90 dBm = 0.195 W
 MODULATION SIGNAL: CDMA
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 35.90 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-37.19	8.57	-28.62	H	51.5
5726.25	-65.16	10.69	-54.47	H	77.4
7635.00	-63.77	12.06	-51.71	H	74.6
9543.75	-61.71	13.20	-48.51	H	71.4
11452.50	-88.19	13.42	-74.77	H	97.7

Table 6-13. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

NOTES:

1. This device supports 2G and 3G technologies. Of the supported 3G technologies (CDMA and EvDO), the highest radiated power and worst case spurious emissions were found in CDMA mode with EvDO FTAP with "All Up" power control bits. In GSM mode, the worst case emissions were found in GPRS mode while transmitting with one slot active.
2. This unit was tested with its standard battery.
3. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the slider-in setup. The data reported in the table above was measured in this test setup.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 23 of 48

6.7 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.8 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	836,600,002	2	0.00000026
100 %		- 30	836,600,005	5	0.00000060
100 %		- 20	836,600,020	20	0.00000244
100 %		- 10	836,600,019	19	0.00000231
100 %		0	836,600,014	14	0.00000166
100 %		+ 10	836,600,029	29	0.00000344
100 %		+ 20	836,600,026	26	0.00000312
100 %		+ 30	836,599,981	-19	-0.00000227
100 %		+ 40	836,600,011	11	0.00000126
100 %		+ 50	836,599,994	-6	-0.00000067
115 %	4.37	+ 20	836,600,003	3	0.00000033
BATT. ENDPOINT	3.20	+ 20	836,600,013	13	0.00000160

Table 6-14. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset			Page 24 of 48

Cellular CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)




Figure 6-1. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 25 of 48

6.8 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,879,999,986	-14	-0.00000076
100 %		- 30	1,880,000,016	16	0.00000085
100 %		- 20	1,880,000,017	17	0.00000088
100 %		- 10	1,880,000,021	21	0.00000111
100 %		0	1,879,999,994	-6	-0.00000034
100 %		+ 10	1,880,000,022	22	0.00000119
100 %		+ 20	1,879,999,997	-3	-0.00000016
100 %		+ 30	1,880,000,023	23	0.00000121
100 %		+ 40	1,880,000,025	25	0.00000131
100 %		+ 50	1,880,000,030	30	0.00000157
115 %	4.37	+ 20	1,879,999,985	-15	-0.00000078
BATT. ENDPOINT	3.20	+ 20	1,880,000,002	2	0.00000009

Table 6-15. Frequency Stability Data (PCS GSM Mode – Ch. 661)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset			Page 26 of 48

PCS GSM Frequency Stability Measurements (Cont'd)
§2.1055, 24.235; RSS-133 (6.3)




Figure 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 27 of 48

6.9 PCS CDMA Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,880,000,020	20	0.00000104
100 %		- 30	1,879,999,982	-18	-0.00000097
100 %		- 20	1,879,999,994	-6	-0.00000031
100 %		- 10	1,879,999,995	-6	-0.00000029
100 %		0	1,879,999,998	-3	-0.00000013
100 %		+ 10	1,880,000,020	20	0.00000107
100 %		+ 20	1,879,999,983	-17	-0.00000088
100 %		+ 30	1,880,000,029	29	0.00000156
100 %		+ 40	1,880,000,029	29	0.00000153
100 %		+ 50	1,879,999,990	-10	-0.00000055
115 %	4.37	+ 20	1,879,999,990	-10	-0.00000055
BATT. ENDPOINT	3.20	+ 20	1,879,999,994	-7	-0.00000035

Table 6-16. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

Note:

Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset			Page 28 of 48

PCS CDMA Frequency Stability Measurements (Cont'd)
§2.1055, 24.235; RSS-133 (6.3)






Figure 6-3. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 29 of 48

7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-2. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 30 of 48




Plot 7-3. Band Edge Plot (PCS GSM Mode – Ch. 512)




Plot 7-4. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 31 of 48




Plot 7-5. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-6. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)

FCC ID: A3LSCHI939D	 FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset	Page 32 of 48




Plot 7-7. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 7-8. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSCHI939D		 FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 33 of 48




Plot 7-9. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)




Plot 7-10. Band Edge Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 34 of 48




Plot 7-11. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)




Plot 7-12. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 35 of 48




Plot 7-13. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)



Plot 7-14. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 36 of 48




Plot 7-15. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-16. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 37 of 48




Plot 7-17. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-18. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 38 of 48




Plot 7-19. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)



Plot 7-20. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 39 of 48



Plot 7-21. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-22. Band Edge Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: A3LSCHI939D		 FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 40 of 48




Plot 7-23. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)



Plot 7-24. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 41 of 48



Plot 7-25. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-26. Band Edge Plot (PCS CDMA Mode – Ch. 25)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 42 of 48




Plot 7-27. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)




Plot 7-28. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 43 of 48




Plot 7-29. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-30. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: A3LSCHI939D	 FCC Pt. 22/24 GSM/EDGE/CDMA/EvDO MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset	Page 44 of 48




Plot 7-31. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)



Plot 7-32. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 45 of 48



Plot 7-33. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-34. Band Edge Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: A3LSCHI939D	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 46 of 48

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSCHI939D** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

FCC ID: A3LSCHI939D		FCC Pt. 22/24 GSM/EDGE/CDMA/EVDO MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111496.A3L	Test Dates: Oct. 8-31, 2012	EUT Type: Portable Handset		Page 48 of 48