

	1	2	3	4	5	6	7	8																																																						
A			Rev. No																																																											
B																																																														
C																																																														
D																																																														
E																																																														
F																																																														
G	Technical Description 1. Use 'FILM' provided by 'SAMSUNG' for letter and contents 2. Background color is 'WHITE', letter color is 'BLACK' (reverse for SAMSUNG LOGO) 3. Put 'release paper' on the back side after the adhesive. 4. No blur and spread for letter 5. Proceed with manufacturing process after the approval of R&D Group 6. The spec. of product must be based on approved limit samples. 7. Stock on as a ROLL 8. Follow drawing instruction above for CE or WEEE mark 9. Unify material and color as one color (blue) for glassine paper				ROLLING																																																									
H																																																														
I																																																														
J																																																														
K																																																														
L	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">MAT.</td> <td colspan="4">White polypropylene 80μ</td> <td style="width: 10%;">FIN.</td> <td colspan="3">Semitransparency OPP Lamination + UVP Coating</td> </tr> <tr> <td>TITLE</td> <td colspan="7">SCH-1939I(CHN)</td> <td rowspan="2" style="text-align: center; vertical-align: middle;"> LABEL (R) - MAIN - EU </td> </tr> <tr> <td>UNIT</td> <td>mm</td> <td>DESIGNED</td> <td>CHECKED</td> <td>APPROVED</td> <td>PROJECTION</td> <td colspan="2"></td> </tr> <tr> <td>TOLERANCE</td> <td>+0.0 -0.1</td> <td rowspan="2">AN DAE GEUN</td> <td></td> <td>junesop kim</td> <td rowspan="2">SHEET NO</td> <td colspan="2" rowspan="2">1/1</td> </tr> <tr> <td>SCALE</td> <td>N/S</td> <td></td> <td></td> </tr> <tr> <td>Manufacture</td> <td>HANSUNG P&I</td> <td>130202</td> <td></td> <td>130202</td> <td colspan="3"></td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> <td>Doc. CODE</td> <td colspan="5" style="text-align: center; font-size: 1.5em;">GH68-</td> </tr> </table>								MAT.	White polypropylene 80 μ				FIN.	Semitransparency OPP Lamination + UVP Coating			TITLE	SCH-1939I(CHN)							LABEL (R) - MAIN - EU	UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION			TOLERANCE	+0.0 -0.1	AN DAE GEUN		junesop kim	SHEET NO	1/1		SCALE	N/S			Manufacture	HANSUNG P&I	130202		130202						Doc. CODE	GH68-				
MAT.	White polypropylene 80 μ				FIN.	Semitransparency OPP Lamination + UVP Coating																																																								
TITLE	SCH-1939I(CHN)							LABEL (R) - MAIN - EU																																																						
UNIT	mm	DESIGNED	CHECKED	APPROVED	PROJECTION																																																									
TOLERANCE	+0.0 -0.1	AN DAE GEUN		junesop kim	SHEET NO	1/1																																																								
SCALE	N/S																																																													
Manufacture	HANSUNG P&I	130202		130202																																																										
		Doc. CODE	GH68-																																																											