

13.1 SAR TEST DATA SUMMARY (CONTINUED)

Ambient TEMPERATURE (°C)	22.0
Relative HUMIDITY (%)	56.0
Atmospheric PRESSURE (kPa)	98.0

Mixture Type: Muscle

Dielectric Constant: 51.70

Conductivity: 1.10 S/m

13.3 Measurement Results (Body SAR)

FREQUENCY		Modulation	POWER * (dBm)	Separation Distance (cm)**	Antenna Position	SAR (W/kg)
MHz	Ch.					
824.70	1013	CDMA	26.0	1.7	IN	1.3472
824.70	1013	CDMA	26.0	1.7	OUT	1.4166
835.89	363	CDMA	26.0	1.7	IN	1.1777
835.89	363	CDMA	26.0	1.7	OUT	1.0869
848.31	777	CDMA	26.0	1.7	IN	1.1547
848.31	777	CDMA	26.0	1.7	OUT	1.1065
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population				Body 1.6 W/kg (mW/g) averaged over 1 gram		

NOTES:

- All modes of operation were investigated and the worst-case are reported.
- Battery condition is fully charged for all readings.
- Battery Type ☒ Standard ☐ Extended
- * Power Measured ☒ Conducted ☐ EIRP ☐ ERP
- SAR Measurement System ☐ SPEAG ☒ IDX
- SAR Configuration ☐ Head ☒ Body ☐ Hand
- ** Test Configuration ☐ Body Holster ☒ Without Body Holster


Randy Ortanez
President & Chief Engineer

