



Samsung Electronics Co., LTD.
129, Samsung-Ro, Yeongtong-gu
Suwon-City, Gyeonggi-do, 443-742, Korea

Date: Feb 13, 2013
PCTEST TCB/CB
Div. of PCTEST Engineering Lab., Inc.
660-B Dobbin Road
Columbia, MD 21045

Subject: Samsung Electronics Co., Ltd.
FCC ID: A3LSCHR830C

To Whom it May Concern

We attest the following regarding FCC ID: A3LSCHR830C

1. MPR is permanently implemented for all channel BWs, modulations, frequency bands and RB sizes:
Supported channel BWs, modulations, frequency bands:
 - a. LTE Band 2 (Channel BW 5,10 MHz)/QPSK & 16QAM
 - b. LTE Band 4 (Channel BW 5,10 MHz)/QPSK & 16QAM
 - c. LTE Band 25 (Channel BW 5,10 MHz)/QPSK & 16QAM
2. MPR is implemented per 3GPP TS 36.101. With the MPR permanently implemented, this device will never operate over than 23.0dBm in QPSK and 16QAM.
3. We confirm the specific MPR targets and tolerances shown below
 - 1) The LTE MPR Targets for Band 2 are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 2	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	2	0-2
	10	16-QAM	50	0	2	0-2

2) The LTE MPR Targets for Band 4 are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 4	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	2	0-2
	10	16-QAM	50	0	2	0-2

3) The LTE MPR Targets for Band 5 are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 25	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	2	0-2
	10	16-QAM	50	0	2	0-2

4. A-MPR was disabled for all SAR test samples for SAR testing purposes only.

5. This device does not implement power back-off schemes for SAR compliance.

Should you have any questions or comments concerning the above, please contact the undersigned.

Sincerely,

A small, square image showing a handwritten signature in blue ink on a light-colored background. The signature is stylized and appears to be 'T. Choi'.

Engineer : Taekkyun Choi

Samsung Electronics CO. LTD

TEL: +82-301-1529

E-mail: daniel.nam@samsung.com