



SAMSUNG ELECTRONICS Co., Ltd.,
Regulatory Compliance Group
IT R&D Center
416 Maetan3-Dong,
Yeongtong-gu, Suwon city,
Gyeonggi-Do, Korea 443-742

FCC CFR47 PART 22 & 24 SUBPART CERTIFICATION REPORT

Model Tested:	SCH-U940
FCC ID (Requested):	A3LSCHU940
Report No:	FF-043-R1
Job No:	FF-043
Date issued:	March 24, 2008

- Abstract -

All measurement reported here in accordance with FCC Rules, 47CFR
Part2, Part22, Part24

Prepared By

JH WOO - Test Engineer

Authorized By

WW JANG - Technical Manager

TABLE OF CONTENT

MEASUREMENT REPORT	Page
1. FCC Certification Information	3
1.1 §2.1033 General Information	3
2. INTRODUCTION	3
2.1 General	3
3. MEASURING INSTRUMENT CALIBRATION	3
4. TEST EQUIPMENT LIST	3
5. DESCRIPTION OF TESTS	3
5.1 Output Power Variation	3
5.2 Effective Radiated Power / Equivalent Isotropic Radiated Power	3
5.3 Radiated Spurious & Harmonic Emission	3
5.4 Occupied Bandwidth	3
5.5 Spurious and Harmonic Emissions at Antenna Terminal	3
5.5.1 Occupied Bandwidth Emission Limits	3
5.5.2 Conducted Spurious Emission	3
5.6 Frequency Stability / Temperature Variation	3
6. TEST DATA	3
6.1 Effective Radiated Power(E.R.P.)	3
6.2 Equivalent Isotropic Radiated Power(E.I.R.P.)	3
6.3 Cellular CDMA Radiated Spurious & Harmonic measurement.....	3
6.4 PCS CDMA Radiated Spurious & Harmonic measurement	3
6.5 CDMA Radiated Spurious & Harmonic Conversion Table	3
6.6 PCS Radiated Spurious & Harmonic Conversion Table	3
6.7 Frequency Stability.....	3
6.7.1 CDMA Frequency Stability Table	3
6.7.2 PCS Frequency Stability Table	3
6.7.3 CDMA Frequency Stability Graph	3
6.7.4 PCS Frequency Stability Graph	3
7. SAMPLE CALCULATION	3
7.1 Emission Designator	3
8. CONCLUSION.....	3
9. TEST PLOTS.....	3



MEASUREMENT REPORT

1. FCC Certification Information

The following information is in accordance with FCC Rules, 47CFR Part2, Subpart J, Sections 2.1033 – 2.1055.

1.1 §2.1033 General Information

- Applicant Name: SAMSUNG ELECTRONICS CO., LTD.
- Address: 416 Maetan3-Dong, Yeongtong-gu, Suwon City
Gyeonggi-Do, Korea 443-742
- Attention: SungJoo KIM, Engineering Manager (QA Lab)
- FCC ID: A3LSCHU940
- Quantity: Quantity production is planned
- Emission Designators: 1M27F9W(CDMA), 1M27F9W(PCS CDMA)
- Tx Freq. Range: 824.70-848.31MHz (CDMA)
1851.25-1908.75MHz (PCS CDMA)
- Rx Freq. Range: 869.70-893.31MHz (CDMA)
1931.25-1988.75MHz (PCS CDMA)
- Max. Power Rating: 0.210 W ERP CDMA (23.23dBm)
0.236 W EIRP PCS (23.72dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Dual-Band CDMA Phone with Bluetooth
- Modulation(s): CDMA
- Frequency Tolerance: $\pm 0.00025\%$ (2.5ppm)
- FCC Rule Part(s): §24(E), §22(H), §2.
- Dates of Test: March 13-14, 2008
- Place of Test: SAMSUNG Lab,
- Test Report S/N: FF-043-R1

2. INTRODUCTION

2.1 General

These measurement test were conducted at **SAMSUNG ELECTRONICS CO., LTD(SUWON)**.
The site address is 416 Maetan3-Dong, Yeongtong-gu, Suwon City, Gyeonggi-Do, Korea 443-742
The site have 1 Fully-anechoic chamber and measurement facility.




Figure1. Map of the Suwon City area.

Measurement Procedure

The radiated and spurious measurements were made Fully-anechoic chamber at a 3-meter test range (see Figure2). The equipment under testing was placed on the rotating device at the same height and at a distance of 3-meters from the receive antenna. The rotating device which can rotate horizontal axis was mounted on the turn unit to facilitate rotation around a vertical axis. The measurement was made for each horizontal/vertical position combination with receive antenna horizontally polarized. This measurement was repeated with receive antenna vertically polarized. The substitution antenna will replace the EUT antenna it the same position and in vertical polarization. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The signal generator, output level, shall be adjusted until an equal or a known related level to what was measured from the EUT is obtained in the spectrum analyzer. This level was recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



Figure2. Photograph of 3m Fully-Anechoic Chamber

3. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

- End of page –

4. TEST EQUIPMENT LIST

Name Of Equipment	Model	Serial No.	Due Date
Spectrum Analyzer	ESI26	836119/010	2008-10-17
	E4440A(3Hz~26.5GHz)	MY41000236	2008-04-14
	E4440A(3Hz~26.5GHz)	MY41000233	2008-07-23
Signal Generator	SMR20	835197/030	2008-12-05
Network Analyzer	8753E	JP38160590	2008-06-26
Power Sensor	8485A	3318A19924	2008-10-01
Power Meter	E4419B	GB41293846	2008-09-06
Pre-Amplifier	8449B	3008A00691	2008-12-24
Communication test set	8960	GB42230535	2009-01-02
	8960	GB42360886	2008-07-03
Controller	CO2000	CO2000/424	Not Required
Turn Unit	CT0800	CT0800/057	Not Required
Rotating Device	DE3600-RH-PR	DE3600-RH-PR/050	Not Required
Antenna Master	MA4000	MA4000/204	Not Required
Horn Antenna	HF906	100134	2008-05-04
Dipole Antenna	3121C-DB4	9007-588	2008-05-29
Communication test set	CMU200	109162	2008-10-17
Receive Antenna	HL040	353255/019	2008-09-20
	HL040	353255/020	2008-04-25
Power Supply	E3640A	MY40003594	2008-06-25
Divider	11636B	51946	Not Required
	11636B	51942	Not Required
High Pass Filter	WHK1.0/15G-10SS	1	Not Required
	WHK3.5/18G-10SS	4	Not Required
Environmental Chamber	SH-241	92000549	2008-11-15
Shielded Fully Anechoic Chamber	CHAMBER	ANT0001	Not Required

5. DESCRIPTION OF TESTS

5.1 Output Power Variation

Test Condition to measure the Output Power

This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with “All Up” power control bits.

The following procedures were followed according to FCC “SAR Measurement Procedures for 3G Devices”, May 2006.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 5-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4 or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 5-2 was applied.
5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

Parameter	Units	Value
$\hat{I}_{or}$	dBm/1.23MHz	-104
Pilot Ec/Ior	dB	-7
Traffic Ec/Ior	dB	-7.4

Table 5-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\hat{I}_{or}$	dBm/1.23MHz	-86
Pilot Ec/Ior	dB	-7
Traffic Ec/Ior	dB	-7.4

Table 5-2
Parameters for Max. Power for RC1

Band	Channel	CDMA2000 RC	1x EV-DO (RTAP)	1x EV-DO (FTAP)	SO2	SO55	TDSO SO32
Cellular	1013	RC1	-	-	25.15	25.16	-
		RC3	25.12	25.04	25.14	25.18	25.15
	384	RC1	-	-	25.48	25.48	-
		RC3	25.47	25.30	25.5	25.52	25.5
	777	RC1	-	-	25.39	25.39	-
		RC3	25.40	25.17	25.45	25.48	25.46
PCS	25	RC1	-	-	25.12	25.13	-
		RC3	25.19	24.95	25.21	25.17	25.18
	600	RC1	-	-	24.97	25	-
		RC3	24.97	24.74	25.09	25.12	25.19
	1175	RC1	-	-	25.05	25	-
		RC3	24.97	24.90	25.14	25.17	25.1

Table 5-3
Maximum Power Output Table for SCH-U940

5.2 Effective Radiated Power / Equivalent Isotropic Radiated Power

Test Set-up for the ERP/EIRP TEST

Effective Radiated Power Output and Equivalent Isotropic Radiated Power output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004




Figure 3. Diagram of ERP/EIRP test Set-up

The EUT was placed on the rotating device at 3-meters from the receive antenna. The turn unit and rotating device was adjusted for the highest reading on the receive spectrum analyzer. **For CDMA & PCS signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz.** A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of dipole is measured. The ERP and EIRP are recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

5.3 Radiated Spurious & Harmonic Emission

Test Set-up for the Radiated Emission TEST

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004




Figure 4. Diagram of Radiated Spurious & Harmonic test Set-up

The EUT was placed on the rotating device at 3-meters from the receive antenna. The turn unit and rotating device was adjusted for the highest reading on the receive spectrum analyzer. The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used, with RBW=VBW=1MHz. The value that we could measure was only reported. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

SAMPLE CALCULATION

Example: Channel 600 PCS Mode 2nd Harmonic(3760MHz)

The receive analyzer reading at 3meters with the EUT on the turntable was -81.0dBm . The gain of the substituted antenna is 8.1dBi . The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0dBm of the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0dB at 3760MHz. So 6.1dB is added to the signal generator reading of -30.9dBm yielding -24.8dBm . The fundamental EIRP was 25.5dBm so this harmonic was $25.5\text{dBm} - (-24.8) = 50.3\text{dBc}$.

- End of page -

5.4 Occupied Bandwidth

Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

Plots of the EUT's occupied bandwidth are shown herein.

5.5 Spurious and Harmonic Emissions at Antenna Terminal

5.5.1 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

– End of page –

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A	1850 – 1865	1930 – 1945
B	1870 – 1885	1950 – 1965
C	1895 – 1910	1975 – 1990
D	1865 – 1870	1945 – 1950
E	1885 – 1890	1965 – 1970
F	1890 – 1895	1970 – 1975

Table 1. Broadband PCS Service Frequency Blocks

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A* Low + A	824 – 835	869 – 880
B	835 – 845	880 – 890
A* High	845 – 846.5	890 – 891.5
B*	846.5 – 849	891.5 – 894

Table 2. Cellular Service Frequency Blocks

5.5.2 Conducted Spurious Emission

Minimum standard:

On any frequency outside a license frequency block, the power of any emission shall be attenuated below the transmitter power(P) by at least $43+10\log(P)$ dB. Limit equivalent to -13 dBm, calculation shown below.

$$43 + 10\log(0.333 \text{ W}) = 38.22 \text{ dB}$$

$$25.22 \text{ dBm} - 38.22 \text{ dB} = -13 \text{ dBm}$$

Test Procedure:

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1% of the emission bandwidth to show compliance with the -13 dBm limit, in the 1MHz bands immediately outside and adjacent to the edge of the frequency block. The measurements are repeated for the EUT's highest channel. For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 10GHz. (PCS Mode : 10MHz to 20GHz). A display line was placed at -13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

Plots are shown herein.

5.6 Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is carried from -30°C to +60°C using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification- The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 ($\pm 2.5\text{ppm}$) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (Usually 14~16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
 - The artificial load is mounted external to the temperature chamber.

NOTE : The EUT is tested down to the battery endpoint.

– End of page –

6. TEST DATA

6.1 Effective Radiated Power(E.R.P.)

Supply Voltage : 3.7VDC

Modulation : CDMA

■ Reference level

Frequency (MHz)	Output (dBm)	Polarization	P/M (dBm)	Ant gain (dBd)	Ref level (dBm)
824.70	22.00	H	-14.49	-0.67	-13.82
		V	-14.65	-0.67	-13.98
836.52	21.00	H	-17.58	-0.73	-16.85
		V	-16.34	-0.73	-15.61
848.31	23.00	H	-19.12	-0.79	-18.33
		V	-16.15	-0.79	-15.36

■ Result (Slide Down)

Frequency (MHz)	From EUT Tested level (dBm)	Polarization (H/V)	Azimuth (angle)	ERP (dBm)	ERP (W)	Battery
824.70	-13.36	H	280/90	22.46	0.176	Standard
836.52	-16.79	H	281/90	21.06	0.128	Standard
848.31	-18.10	H	288/74	23.23	0.210	Standard
848.31	-18.12	H	289/74	23.21	0.209	Extended

- This model only supports call mode with slide down configuration.
- All modes of operation were investigated, and the worst-case results are reported.

Radiated measurements at 3 meters by Substitution Method

6.2 Equivalent Isotropic Radiated Power(E.I.R.P.)

Supply Voltage : 3.7VDC

Modulation : PCS

■ Reference level

Frequency (MHz)	Output (dBm)	Polarization	P/M (dBm)	Ant gain (dBi)	Ref level (dBm)
1851.25	23.00	H	-15.35	9.70	-25.05
		V	-15.39	9.70	-25.09
1880.00	24.00	H	-14.69	9.70	-24.39
		V	-14.43	9.70	-24.13
1908.75	23.00	H	-15.77	9.70	-25.47
		V	-15.41	9.70	-25.11

■ Result (Slide Down)

Frequency (MHz)	From EUT Tested level (dBm)	Polarization (H/V)	Azimuth (angle)	EIRP (dBm)	EIRP (W)	Battery
1851.25	-24.79	H	300/10	23.26	0.212	Standard
1880.00	-24.67	H	260/0	23.72	0.236	Standard
1908.75	-24.97	V	249/90	23.14	0.206	Standard
1880.00	-24.70	H	261/0	23.69	0.234	Extended

- This model only supports call mode with slide down configuration.
- All modes of operation were investigated, and the worst-case results are reported.

Radiated measurements at 3 meters by Substitution Method

6.3 Cellular CDMA Radiated Spurious & Harmonic measurement

Field Strength of SPURIOUS Radiation

Operating Frequency : 824.70 MHz(Low), 836.52MHz(Middle), 848.31MHz(High)

Measured Output Power : 23.23 dBm = 0.210 W

Modulation Signal : CDMA

Limit : $43 + 10\log_{10}(P) = 36.23 \text{ dBc}$

■ Result (Slide Down)

Channel	Harmonic	Frequency (MHz)	From EUT Tested level (dBm)	POL (H/V)	Result (dBc)
1013	2	1649.40	-41.44	H	54.03
	3	2474.10	-49.44	H	57.16
	4	3298.80	-60.33	V	63.82
	5	4123.50	-63.76	V	64.97
	6	4948.20	-64.96	V	63.16
	7	5772.90	-	-	-
384	2	1673.04	-44.43	H	56.35
	3	2509.56	-53.33	H	60.80
	4	3346.08	-63.43	V	67.44
	5	4182.68	-63.54	H	65.01
	6	5019.12	-65.85	V	63.58
	7	5855.64	-	-	-
777	2	1696.62	-48.60	V	60.19
	3	2544.93	-50.84	H	58.89
	4	3393.24	-63.88	V	67.70
	5	4241.55	-66.31	V	67.42
	6	5089.86	-66.85	V	64.47
	7	5938.17	-	-	-

NOTE :

1. "-" Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. The spectrum is measured from 30MHz to the 10th harmonic and All modes of operation were investigated, and the worst-case results are reported. This model only supports call mode with slide down configuration.

Radiated Spurious Emission measurements at 3 meters by Substitution Method

6.4 PCS CDMA Radiated Spurious & Harmonic measurement

Field Strength of SPURIOUS Radiation

Operating Frequency : 1851.25 MHz(Low), 1880.00 MHz(Middle), 1908.75MHz(High)

Measured Output Power : 23.72 dBm = 0.236 W

Modulation Signal : PCS

Limit : $43 + 10\log_{10}(P) = 36.72 \text{ dBc}$

■ Result (Slide Down)

Channel	Harmonic	Frequency (MHz)	From EUT Tested level (dBm)	POL (H/V)	Result (dBc)
25	2	3702.50	-61.54	V	61.11
	3	5553.75	-52.65	V	47.60
	4	7405.55	-63.38	V	55.02
	5	9256.25	-64.51	V	51.77
	6	11107.50	-69.01	H	52.16
	7	12958.75	-	-	-
600	2	3760.00	-57.36	H	56.44
	3	5640.00	-58.55	V	53.51
	4	7520.00	-62.33	V	54.15
	5	9400.00	-62.18	V	49.28
	6	11280.00	-67.54	V	50.13
	7	13160.00	-	-	-
1175	2	3817.50	-54.65	H	54.28
	3	5726.25	-54.66	V	49.14
	4	7635.00	-63.14	V	54.66
	5	9543.75	-67.30	H	54.90
	6	11452.50	-69.00	V	51.37
	7	13361.25	-	-	-

NOTE :

1. "-" Indicates the spurious emission could not be detected due to noise limitations or ambients.
2. The spectrum is measured from 30MHz to the 10th harmonic and All modes of operation were investigated, and the worst-case results are reported. This model only supports call mode with slide down configuration.

Radiated Spurious Emission measurements at 3 meters by Substitution Method

6.5 CDMA Radiated Spurious & Harmonic Conversion Table

Date : 2008.03.14

Test Engineer : JH WOO

Tx Cable loss
Tx Horn Ant Gain
Tx Level to radiate -13dBm
ESI Level received from Tx with -13dBm
Tested Level from EUT
= ERP+2.14 - (-13 + -)

CH	Har	Frequency (MHz)	Tx C/L dB	Tx Horn Gain dBi	Tx Level dBm	ESI Level : H dBm	ESI Level : V dBm	Tested EUT Level : H dBm	Tested EUT Level : V dBm	Result EUT : H (dBc)	Result EUT : V (dBc)
1013	2	1649.40	-7.44	8.25	-13.80	-25.78	-25.24	-41.44	-42.04	54.03	55.17
	3	2474.10	-9.40	9.58	-13.20	-30.65	-30.96	-49.44	-49.87	57.16	57.28
	4	3298.80	-10.62	9.67	-12.10	-34.30	-34.88	-62.74	-60.33	66.81	63.82
	5	4123.50	-12.18	10.59	-11.40	-37.37	-37.16	-64.59	-63.76	65.59	64.97
	6	4948.20	-13.25	11.00	-10.80	-39.95	-40.17	-66.39	-64.96	64.81	63.16
	7	5772.90	-14.88	11.36	-9.50	-42.25	-42.16	-	-	-	-
384	2	1673.04	-7.53	8.25	-13.70	-26.45	-26.15	-44.43	-45.14	56.35	57.36
	3	2509.56	-9.52	9.58	-13.10	-30.90	-30.96	-53.33	-56.49	60.80	63.90
	4	3346.08	-10.72	9.67	-12.00	-34.28	-34.36	-63.66	-63.43	67.75	67.44
	5	4182.68	-12.46	10.59	-11.10	-36.90	-37.13	-63.54	-64.03	65.01	65.27
	6	5019.12	-13.94	11.00	-10.10	-40.04	-40.64	-68.69	-65.85	67.02	63.58
	7	5855.64	-14.92	11.36	-9.40	-42.75	-42.94	-	-	-	-
777	2	1696.62	-7.61	8.25	-13.60	-26.64	-26.78	-49.71	-48.60	61.44	60.19
	3	2544.93	-9.56	9.58	-13.00	-30.32	-30.81	-50.84	-53.04	58.89	60.60
	4	3393.24	-10.77	9.67	-11.90	-34.25	-34.55	-66.82	-63.88	70.94	67.70
	5	4241.55	-12.36	10.59	-11.20	-37.07	-37.26	-66.42	-66.31	67.72	67.42
	6	5089.86	-14.20	11.00	-9.80	-40.12	-40.75	-68.24	-66.85	66.49	64.47
	7	5938.17	-15.12	11.36	-9.20	-43.10	-42.67	-	-	-	-

6.6 PCS Radiated Spurious & Harmonic Conversion Table

Date : 2008.03.14

Test Engineer : JH WOO

Tx Cable loss
Tx Horn Ant Gain
Tx Level to radiate -13dBm
ESI Level received from Tx with -13dBm
Tested Level from EUT
= EIRP - (-13 +)

CH	Har	Frequency (MHz)	Tx C/L dB	Tx Horn Gain dBi	Tx Level dBm	ESI Level : H dBm	ESI Level : V dBm	Tested EUT Level : H dBm	Tested EUT Level : H dBm	Result EUT : H (dBc)	Result EUT : V (dBc)
25	2	3702.50	-11.21	12.40	-14.20	-37.37	-37.15	-64.50	-61.54	63.85	61.11
	3	5553.75	-14.60	12.90	-11.30	-41.96	-41.77	-56.80	-52.65	51.56	47.60
	4	7405.00	-17.62	10.50	-5.90	-45.25	-45.08	-64.76	-63.38	56.23	55.02
	5	9256.25	-19.95	11.20	-4.30	-49.47	-49.46	-69.29	-64.51	56.54	51.77
	6	11107.50	-22.59	11.60	-2.00	-53.57	-53.77	-69.01	-69.21	52.16	52.16
	7	12958.75	-23.95	12.90	-2.00	-56.60	-56.68	-	-	-	-
600	2	3760.00	-11.50	12.40	-13.90	-37.64	-37.61	-57.36	-57.98	56.44	57.09
	3	5640.00	-14.83	12.90	-11.10	-41.41	-41.76	-62.51	-58.55	57.82	53.51
	4	7520.00	-17.89	10.60	-5.70	-44.71	-44.90	-64.39	-62.33	56.40	54.15
	5	9400.00	-20.33	11.60	-4.30	-49.48	-49.62	-69.53	-62.18	56.77	49.28
	6	11280.00	-22.49	12.10	-2.60	-54.00	-54.13	-69.90	-67.54	52.62	50.13
	7	13160.00	-24.50	12.80	-1.30	-56.48	-56.54	-	-	-	-
1175	2	3817.50	-11.78	12.40	-13.60	-37.09	-37.94	-54.65	-56.91	54.28	55.69
	3	5726.25	-14.79	13.00	-11.20	-42.32	-42.24	-61.63	-54.66	56.03	49.14
	4	7635.00	-18.29	11.20	-5.90	-44.93	-45.20	-65.85	-63.14	57.64	54.66
	5	9543.75	-21.04	11.70	-3.70	-49.12	-48.74	-67.30	-69.80	54.90	57.78
	6	11452.50	-22.26	11.70	-2.40	-54.27	-54.35	-69.75	-69.00	52.20	51.37
	7	13361.25	-24.33	12.30	-1.00	-57.91	-57.89	-	-	-	-

6.7 Frequency Stability

6.7.1 CDMA Frequency Stability Table

Operating Frequency : 836,520,000 Hz

Channel : 384

Reference Voltage : 3.7VDC

Deviation Limit : ± 0.00025 % or 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency Error (Hz)	Frequency (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	-13.21	836,519,987	-0.000002	-0.016
100%		-30	-14.91	836,519,985	-0.000002	-0.018
100%		-20	28.88	836,520,029	0.000003	0.035
100%		-10	39.21	836,520,039	0.000005	0.047
100%		0	48.33	836,520,048	0.000006	0.058
100%		+10	41.42	836,520,041	0.000005	0.050
100%		+20	-13.21	836,519,987	-0.000002	-0.016
100%		+30	39.29	836,520,039	0.000005	0.047
100%		+40	13.24	836,520,013	0.000002	0.016
100%		+50	-19.81	836,519,980	-0.000002	-0.024
100%		+60	20.24	836,520,020	0.000002	0.024
85%	3.25	+20	23.34	836,520,023	0.000003	0.028
115%	4.26	+20	38.64	836,520,039	0.000005	0.046
Batt. Endpoint	3.25	+20	23.34	836,520,023	0.000003	0.028

Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.

The EUT is tested down to the battery end point

6.7.2 PCS Frequency Stability Table

Operating Frequency : 1,880,000,000 Hz

Channel : 600

Reference Voltage : 3.7VDC


Deviation Limit : ± 0.00025 % or 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency Error (Hz)	Frequency (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	10.23	1,880,000,010	0.000001	0.005
100%		-30	15.26	1,880,000,015	0.000001	0.008
100%		-20	-10.13	1,879,999,990	-0.000001	-0.005
100%		-10	-16.64	1,879,999,983	-0.000001	-0.009
100%		0	25.12	1,880,000,025	0.000001	0.013
100%		+10	-22.51	1,879,999,977	-0.000001	-0.012
100%		+20	10.23	1,880,000,010	0.000001	0.005
100%		+30	15.56	1,880,000,016	0.000001	0.008
100%		+40	20.56	1,880,000,021	0.000001	0.011
100%		+50	-25.56	1,879,999,974	-0.000001	-0.014
100%		+60	30.53	1,880,000,031	0.000002	0.016
85%	3.25	+20	35.66	1,880,000,036	0.000002	0.019
115%	4.26	+20	-30.58	1,879,999,969	-0.000002	-0.016
Batt. Endpoint	3.25	+20	35.66	1,880,000,036	0.000002	0.019

Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.

The EUT is tested down to the battery end point


6.7.3 CDMA Frequency Stability Graph



– End of page –


Zoom In

Frequency Stability




– End of page –

6.7.4 PCS Frequency Stability Graph



– End of page –

Zoom In



7. SAMPLE CALCULATION

7.1 Emission Designator

Emission Designator = 1M25F9W

Calculation : 2M + 2DK

CDMA BW = 1.25MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination(Audio/Data)

(Measured at the 99.75% power bandwidth)

– End of page –



8. CONCLUSION


The data collected shows that the SAMSUNG Dual-Band CDMA Phone with Bluetooth
FCC ID : A3LSCHU940 complies with all the requirements of Parts 2, 22, 24 of the FCC Rules.

- End of page -


9. TEST PLOTS

 Agilent

R T



 Agilent

R T




Agilent

R T



Agilent

R T



Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Power Out Ch.384

Ref 25.5 dBm

Atten 30 dB

#Samp

Log

10

dB/

Offst

7.68

dB

#LgAv

100

W1 S2

S3 FC

$E(f)$:

FTun

Swp

Center 836.52 MHz

Span 10 MHz

#Res BW 3 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Center Freq

836.520000 MHz

Start Freq

831.520000 MHz

Stop Freq

841.520000 MHz

CF Step

1.00000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Power Out Ch.777

Ref 25.5 dBm

Atten 30 dB

#Samp

Log

10

dB/

Offst

7.68

dB

#LgAv

100

W1 S2

S3 FC

$E(f)$:

FTun

Swp

Center 848.31 MHz

Span 10 MHz

#Res BW 3 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Center Freq

848.310000 MHz

Start Freq

843.310000 MHz

Stop Freq

853.310000 MHz

CF Step

1.00000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track


On

Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T




Freq/Channel

Center Freq	824.700000 MHz
Start Freq	823.200000 MHz
Stop Freq	826.200000 MHz
CF Step	300.000000 kHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T



Freq/Channel


Center Freq	836.520000 MHz
Start Freq	835.020000 MHz
Stop Freq	838.020000 MHz
CF Step	300.000000 kHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel




Center Freq	848.310000 MHz
Start Freq	846.810000 MHz
Stop Freq	849.810000 MHz
CF Step	300.000000 kHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent



R T



Freq/Channel



Center Freq	881.500000 MHz
Start Freq	869.000000 MHz
Stop Freq	894.000000 MHz
CF Step	2.50000000 MHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

File Operation Status, C:\TEMP.GIF file saved

[illegible][illegible]



Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.384

Ref 25.5 dBm Atten 30 dB

#Peak

Log

10

dB/

Offst

7.68

dB

DI

-13.0

dBm

#LgAv


M1 S2

S3 FC

$E(f)$:

FTun

Swp



Center 1.255 GHz Span 2.49 GHz

#Res BW 1 MHz #VBW 1 MHz Sweep 4.16 ms (601 pts)

AC Coupled: unspecified below 20 MHz

File Operation Status, C:\TEMP.GIF file saved

Center Freq
1.25500000 GHz

Start Freq
10.00000000 MHz

Stop Freq
2.50000000 GHz

CF Step
249.0000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.384

Ref 25.5 dBm Atten 30 dB

Mkr1 475.0 MHz

-43.73 dBm

#Peak

Log

10

dB/

Offst

7.68

dB

DI

-13.0

dBm

#LgAv


M1 S2

S3 FC

$E(f)$:

FTun

Swp



Center 373.3 MHz Span 726.5 MHz

#Res BW 1 MHz #VBW 1 MHz Sweep 1.24 ms (601 pts)

AC Coupled: unspecified below 20 MHz

File Operation Status, C:\TEMP.GIF file saved

Center Freq
373.260000 MHz



Start Freq
10.00000000 MHz

Stop Freq
736.520000 MHz

CF Step
72.6520000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off



Agilent

R T

Freq/Channel




File Operation Status, C:\TEMP.GIF file saved



Agilent

R T

Freq/Channel




File Operation Status, C:\TEMP.GIF file saved



Agilent

R T

Freq/Channel



Center Freq
824.000000 MHz

Start Freq
823.000000 MHz

Stop Freq
825.000000 MHz

CF Step
200.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

Invalid suffix

Agilent

R T

Freq/Channel



Center Freq
849.000000 MHz

Start Freq
848.000000 MHz

Stop Freq
850.000000 MHz

CF Step
200.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

Invalid suffix

Agilent

R T

Freq/Channel



Center Freq
821.000000 MHz

Start Freq
819.000000 MHz

Stop Freq
823.000000 MHz

CF Step
400.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
852.000000 MHz

Start Freq
850.000000 MHz

Stop Freq
854.000000 MHz

CF Step
400.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

* Agilent

R T


Freq/Channel



**Center Freq**
1.85125000 GHz**Start Freq**
1.84975000 GHz**Stop Freq**
1.85275000 GHz**CF Step**
300.000000 kHz
Auto Man**Freq Offset**
0.00000000 Hz**Signal Track**
On Off

* Agilent

R T

Freq/Channel


**Center Freq**
1.88000000 GHz**Start Freq**
1.87850000 GHz**Stop Freq**
1.88150000 GHz**CF Step**
300.000000 kHz
Auto Man**Freq Offset**
0.00000000 Hz**Signal Track**
On Off



Agilent

R T

Freq/Channel



Center Freq
1.88000000 GHz

Start Freq
1.87500000 GHz

Stop Freq
1.88500000 GHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.90875000 GHz

Start Freq
1.90375000 GHz

Stop Freq
1.91375000 GHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
1.85125000 GHz

Start Freq
1.84975000 GHz

Stop Freq
1.85275000 GHz

CF Step
300.000000 kHz
Auto Man


Freq Offset
0.00000000 Hz

Signal Track
On Off

Agilent

R T

Freq/Channel



Center Freq
1.88000000 GHz


Start Freq
1.87850000 GHz

Stop Freq
1.88150000 GHz

CF Step
300.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off



Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.25

Ref 25 dBm

Atten 30 dB

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv

M1 S2

S3 FC

$E(f)$:

FTun

Swp

AC Coupled: unspecified below 20 MHz

Center Freq

1.25500000 GHz

Start Freq

10.00000000 MHz

Stop Freq

2.50000000 GHz

CF Step

249.0000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Center 1.255 GHz

Span 2.49 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 4.16 ms (601 pts)

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.25

Ref 25 dBm

Atten 30 dB

Mkr1 498 MHz

-42.71 dBm

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv

M1 S2

S3 FC

$E(f)$:

FTun

Swp

AC Coupled: unspecified below 20 MHz

Center Freq

880.625000 MHz

Start Freq

10.00000000 MHz

Stop Freq

1.75125000 GHz

CF Step

174.125000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Center 881 MHz



Span 1.741 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 2.92 ms (601 pts)

File Operation Status, C:\TEMP.GIF file saved



Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.600

Ref 25 dBm

Atten 30 dB

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv


M1 S2

S3 FC

£(f):

FTun

Swp



Center 1.255 GHz

Span 2.49 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 4.16 ms (601 pts)

Center Freq
1.25500000 GHz

Start Freq
10.0000000 MHz

Stop Freq
2.50000000 GHz

CF Step
249.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.600

Ref 25 dBm

Atten 30 dB

Mkr1 405 MHz

-43.08 dBm

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv


M1 S2

S3 FC

£(f):

FTun

Swp



Center 895 MHz

Span 1.77 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 2.96 ms (601 pts)

Center Freq
895.000000 MHz

Start Freq
10.0000000 MHz



Stop Freq
1.78000000 GHz

CF Step
177.000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved



Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.1175

Ref 25 dBm

Atten 30 dB

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv

M1 S2

S3 FC

£(f):

FTun

Swp

AC Coupled: unspecified below 20 MHz

Center 1.255 GHz

Span 2.49 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 4.16 ms (601 pts)

Center Freq
1.25500000 GHz

Start Freq
10.00000000 MHz

Stop Freq
2.50000000 GHz

CF Step
249.0000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel

FCC ID:A3LSCHU940 Cond Spur Ch.1175

Ref 25 dBm

Atten 30 dB

Mkr1 1.185 GHz

-42.63 dBm

#Peak

Log

10

dB/

Offst

8.7

dB

DI

-13.0

dBm

#LgAv

M1 S2

S3 FC

£(f):

FTun

Swp

AC Coupled: unspecified below 20 MHz

Center 909 MHz

Span 1.799 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 3 ms (601 pts)

Center Freq
909.375000 MHz

Start Freq
10.00000000 MHz



Stop Freq
1.80875000 GHz

CF Step
179.875000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off


File Operation Status, C:\TEMP.GIF file saved



Agilent

R T

Freq/Channel



Center Freq
1.85000000 GHz

Start Freq
1.84750000 GHz

Stop Freq
1.85250000 GHz

CF Step
500.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

Invalid suffix

Agilent

R T

Freq/Channel



Center Freq
1.91000000 GHz

Start Freq
1.90750000 GHz

Stop Freq
1.91250000 GHz

CF Step
500.000000 kHz
Auto Man

Freq Offset
0.00000000 Hz


Signal Track
On Off

Invalid suffix

Agilent

R T

Freq/Channel



Center Freq
 1.84700000 GHz

Start Freq
 1.84500000 GHz

Stop Freq
 1.84900000 GHz

CF Step
 400.000000 kHz
 Auto Man

Freq Offset
 0.00000000 Hz


Signal Track
 On Off

File Operation Status, C:\TEMP.GIF file saved

Agilent

R T

Freq/Channel



Center Freq
 1.91300000 GHz

Start Freq
 1.91100000 GHz

Stop Freq
 1.91500000 GHz

CF Step
 400.000000 kHz
 Auto Man

Freq Offset
 0.00000000 Hz

Signal Track
 On Off

File Operation Status, C:\TEMP.GIF file saved