



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 15B Certification

Applicant Name:

Samsung Electronics, Co. Ltd.
18600 Broadwick St.
Rancho Dominguez, CA 90220
United States

Date of Testing:

April 2, 2008

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0804010389.A3L

FCC ID: A3LSCHW510

APPLICANT: Samsung Electronics, Co. Ltd.

EUT Type: PCS GSM/GPRS Phone with Bluetooth

Model(s): SCH-W510, SPH-W5100

FCC Rule Part(s): FCC Part 15 Subpart B

FCC Classification: FCC Class B Digital Device (JBP)

Test Procedure: ANSI C63.4-2003

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2003 (See Test Report). These measurements were performed with no deviation from the standards.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

NVLAP accreditation does not constitute any product endorsement by NVLAP or any agency of the United States Government. PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President

NVLAP[®]
Lab Code 100431-0

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 1 of 20

TABLE OF CONTENTS

FCC Class B MEASUREMENT REPORT.....	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 PCTEST TEST LOCATION	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 OPERATION MODE.....	5
2.3 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.4 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TEST.....	6
3.1 EVALUATION PROCEDURE	6
3.2 CONDUCTED EMISSIONS	6
3.3 RADIATED EMISSIONS.....	7
4.0 SAMPLE CALCULATIONS	8
4.1 CONDUCTED EMISSION MEASUREMENT SAMPLE CALCULATION	8
4.2 RADIATED EMISSION MEASUREMENT SAMPLE CALCULATION	8
5.0 TEST EQUIPMENT CALIBRATION DATA	9
6.0 ENVIRONMENTAL CONDITIONS	10
7.0 TEST DATA	11
7.1 SUMMARY	11
7.2 TEST SUPPORT EQUIPMENT.....	11
7.3 RADIATED MEASUREMENT DATA.....	12
7.4 LINE CONDUCTED MEASUREMENT DATA.....	13
8.0 CONCLUSION	15
9.0 TEST SETUP PHOTOGRAPHS	16
10.0 EUT PHOTOGRAPHS	19

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 2 of 20



MEASUREMENT REPORT

FCC Part 15B – Unintentional Radiators



§ 2.1033 General Information

APPLICANT: Samsung Electronics, Co. Ltd.

APPLICANT ADDRESS: 18600 Broadwick St.
Rancho Dominguez, CA 90220

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA

FCC RULE PART(S): FCC Part 15 Subpart B

FCC ID: A3LSCHW510

Test Device Serial No.: FF-045-C ☐ Production ☒ Pre-Production ☐ Engineering

FCC CLASSIFICATION: FCC Class B Digital Device (JBP)

DATE(S) OF TEST: April 2, 2008

Test Methodology

Both conducted and radiated measurements were taken using the methods and procedures described in ANSI C63.4-2003. Radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility / NVLAP Accreditation

Conducted and radiated tests were performed at PCTEST Engineering Lab in Columbia, MD 21045, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC 2451).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 3 of 20

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSCHW510	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 4 of 20

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung PCS GSM/GPRS Phone with Bluetooth FCC ID: A3LSCHW510**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.

Manufacturer / Base Model	FCC ID	Description
Samsung / Model: SCH-W510	A3LSCHW510	PCS GSM/GPRS Phone with Bluetooth

Table 2-1. EUT Equipment Description

2.2 Operation Mode

The Samsung PCS GSM/GPRS Phone with Bluetooth FCC ID: A3LSCHW510 was tested with a NOTEBOOK connected via USB interface port. For more information please see Section 7.0 for test data and Sections 9.0 and 10.0 for the test setup photographs.

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.4 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 5 of 20

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) was used in the measurement of the **Samsung PCS GSM/GPRS Phone with Bluetooth FCC ID: A3LSCHW510**.

Deviation from measurement procedure.....None

3.2 Conducted Emissions




Figure 3-1. Shielded Enclosure Line-Conducted Test Facility




Figure 3-2. Line Conducted Emission Test Set-Up




Figure 3-3. Wooden Table & Bonded LISNs




Figure 3-4. LISN Schematic Diagram

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see *Figure 3-1*). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see *Figure 3-2*). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see *Figure 3-3*). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see *Figure 3-4*). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 6 of 20

3.3 Radiated Emissions



Figure 3-5. 3-Meter Test Site



Figure 3-6. Dimensions of Outdoor Test Site



Figure 3-7. Turntable and System Setup



Figure 3-8. Normalized Site Attenuation Curves (H&V)

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using RobertsTM Dipole antennas or horn antennas (see Figure 3-5). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see Figure 3-6). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3-7). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-8.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 7 of 20

4.0 SAMPLE CALCULATIONS

4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

Class B limit = 60.0 dBmV (Quasi-peak limit)
Reading = - 57.8 dBm (calibrated quasi-peak level)
Convert to dBμV = - 57.8 + 107 = 49.2 dBμV

Margin = 49.2 - 60.0 = - 10.8 dB
= 10.8 dB below limit

4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

Class B limit = 100 mV/m = 40.0 dBmV/m
Reading = - 76.0 dBm (calibrated level)
Convert to dBμV = - 76.0 + 107 = 31.0 dBμV
Antenna Factor + Cable Loss = 5.8 dB/m
Total = 36.8 dBμV/m

Margin = 36.8 - 40.0 = - 3.2 dB
= 3.2 dB below limit

Note:

Level [dBμV] = 20 log₁₀ (Level [μV/m])
Level [dBμV] = Level [dBm] + 107

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 8 of 20

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
-	No.165 (30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166 (1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167 (100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	E4407B ESA Spectrum Analyzer	04/29/07	Annual	04/28/08	US39210313
Agilent	E4448A (3Hz-50GHz) Spectrum Analyzer	10/01/07	Annual	10/01/08	US42510244
Agilent	E8257D (250kHz-20GHz) Signal Generator	03/08/07	Biennial	03/08/09	MY45470194
Agilent	HP 11713A Attenuation/Switch Driver	12/13/07	Annual	12/13/08	3439A02645
Agilent	HP 8449B (1-26.5GHz) Pre-Amplifier	12/13/07	Annual	12/12/08	3008A00985
Agilent	HP 8566B (100Hz-22GHz) Spectrum Analyzer	12/13/07	Annual	12/13/08	3638A08713
Agilent	HP 8591A (9kHz-1.8GHz) Spectrum Analyzer	09/18/07	Annual	09/18/08	3144A02458
Compliance Design	Roberts Dipole Set	11/09/07	Biennial	11/08/09	146
Compliance Design	Roberts Dipole Set	11/09/07	Biennial	11/08/09	147
EMCO	3816/2 LISN	08/09/06	Biennial	08/08/08	9707-1077
EMCO	3816/2 LISN	08/09/06	Biennial	08/08/08	9707-1079
EMCO	6502 Active Loop Antenna (10k - 30 MHz)	11/06/07	Annual	11/05/08	267
EMCO	Dipole Pair	09/20/06	Biennial	09/19/08	23951
Pasternack	PE7000-6 6 dB Attenuator	N/A		N/A	N/A
SOLAR	8012-50 LISN (2)	11/08/07	Biennial	11/07/09	0310233, 0310234

Table 5-1. Annual Test Equipment Calibration Schedule

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 9 of 20

6.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C.

The relative humidity is controlled within range of 10% to 75%.

The atmospheric pressure is controlled within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth	Page 10 of 20	

7.0 TEST DATA

7.1 Summary

Test Date(s): April 2, 2008

Test Engineer: Jennifer Liu

FCC Part 15 Section	Description	Result
15.107	Conducted Emissions	PASS
15.109	Radiated Emissions	PASS

Table 7-1. Summary of Test Results

7.2 Test Support Equipment

1	Samsung Data Link Cable	Model: PCB080BDK 1.2m Shielded USB Cable	S/N: DW1YA08AS
2	Dell Notebook PC w/ Dell AC Adapter	Model: PP21L (DoC) Model: PA-1600-06D2 1.83m Unshielded AC power cord 1.80m Unshielded DC power cord with ferrite bead on notebook end	P/N: DF643 A00 S/N: CN-0TD231-71615-5BS-18EB
3	Dynex USB PC Camera	Model: DX-WC101 (DoC) 2.07m Shielded USB Cable	S/N: 122D05AC

Note: See test setup photographs for actual system test setup.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth	Page 11 of 20	

7.3 Radiated Measurement Data

§15.109; RSS-Gen (6(a))

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol [H/V]	Height [m]	Azimuth [degrees]	Field Strength [dBmV/m]	Field Strength [mV/m]	Margin [dB]
55.60	-94.63	12.93	V	1.8	245	25.30	18.40	-14.70
85.10	-93.05	9.05	V	1.3	168	23.00	14.12	-17.00
100.60	-94.10	12.14	V	1.4	221	25.04	17.87	-18.48
104.60	-91.69	12.19	V	1.5	165	27.50	23.72	-16.02
120.30	-96.57	12.44	V	1.2	55	22.87	13.91	-20.65
148.60	-97.74	17.47	V	1.9	94	26.73	21.71	-16.79

Table 7-2. Radiated Measurements at 3-meters




Figure 7-1. 3 Meter Limits

NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated Emissions were measured from 30MHz – 2000MHz.
3. The radiated limits are shown on Figure 7-1. Above 960MHz the limit is 500µV/m.

1. All readings are calibrated by Agilent E8257D (250kHz – 20GHz) PSG Signal Generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
2. AFCL = Antenna Factor (Roberts dipole) and Cable Loss (30 ft. RG58C/U).
3. Measurements made using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used with a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 12 of 20


7.4 Line Conducted Measurement Data

§15.107; RSS-Gen (7.2.2)

PCTEST Engineering Laboratory Inc.

Company : Samsung Electronics, Co. Ltd.
 Model Number : SCH-W510
 FCC ID Code : A3LSCHW510
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz
 Tested Date : 04/02/2008
 Note :



Plot 7-1. Line-Conducted Test Plot

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth		Page 13 of 20

Line Conducted Measurement Data (Cont'd)

§15.107; RSS-Gen (7.2.2)

No.	Line	Frequency [MHz]	QP [dBμV]	Limit [dBμV]	Margin [dB]	Average [dBμV]	Limit [dBμV]	Margin [dB]
1	A	0.335	40.61	59.23	-18.62	24.80	49.23	-24.43
2	A	0.447	29.24	56.84	-27.60	15.95	46.84	-30.89
3	A	0.478	32.43	56.36	-23.93	21.17	46.36	-25.19
4	A	0.514	35.00	56.00	-21.00	15.45	46.00	-30.55
5	A	0.542	39.84	56.00	-16.16	16.29	46.00	-29.71
6	A	0.601	24.87	56.00	-31.13	14.06	46.00	-31.94
7	A	0.666	32.69	56.00	-23.31	15.53	46.00	-30.47
8	A	0.727	34.41	56.00	-21.59	15.10	46.00	-30.90
9	A	0.774	33.27	56.00	-22.73	16.81	46.00	-29.19
10	A	1.649	33.51	56.00	-22.49	15.76	46.00	-30.24
11	B	0.175	50.98	64.67	-13.69	41.70	54.67	-12.97
12	B	0.179	47.41	64.30	-16.89	37.80	54.30	-16.50
13	B	0.190	32.74	63.82	-31.08	17.25	53.82	-36.57
14	B	0.234	45.77	62.27	-16.50	38.34	52.27	-13.93
15	B	0.239	39.22	61.96	-22.74	28.04	51.96	-23.92
16	B	0.296	36.91	60.22	-23.31	28.82	50.22	-21.40
17	B	0.351	37.98	58.87	-20.89	34.34	48.87	-14.53
18	B	2.233	17.09	56.00	-38.91	10.39	46.00	-35.61
19	B	3.209	27.85	56.00	-28.15	18.65	46.00	-27.35
20	B	3.863	34.49	56.00	-21.51	26.59	46.00	-19.41

Table 7-3. Line-Conducted Test Data

Notes:

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth	Page 14 of 20	

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung PCS GSM/GPRS Phone with Bluetooth FCC ID: A3LSCHW510** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC Rules.

FCC ID: A3LSCHW510		FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0804010389.A3L	Test Dates: April 2, 2008	EUT Type: PCS GSM/GPRS Phone with Bluetooth	Page 15 of 20	