SAMSUNG ELECTRONICS Co., Ltd.,
Regulatory Compliance Group
IT R&D Center
416 Maetan3-Dong,
Yeongtong-gu, Suwon city,
Gyeonggi-Do, Korea 443-742

FCC CFR47 PART 22 & 24 SUBPART CERTIFICATION REPORT

Model Tested:	**SCH-W579**
FCC ID (Requested):	**A3LSCHW579**
Report No:	**FD-145-R1**
Job No:	**FD-145**
Date issued:	**September 27, 2006**

- Abstract –
All measurement reported here in accordance with FCC Rules, 47CFR Part2, Part22, Part24.

Prepared By	SH ONG– Test Engineer	**Date**	2006.09.27
Checked By	WW JANG – Manager	**Date**	2006.09.27
Authorized By	SH PARK – Senior Manager	**Date**	2006.09.27

© Copyright SAMSUNG Electronics 2006

TABLE OF CONTENT

MEASUREMENT REPORT

	Page
1. FCC Certification Information	**3**
1.1 §2.1033 General Information	**3**
2. INTRODUCTION	**4**
2.1 General	**4**
3. MEASURING INSTRUMENT CALIBRATION	**5**
4. TEST EQUIPMENT LIST	**6**
5. DESCRIPTION OF TESTS	**7**
5.1.Output Power Variation	**7**
5.2 Effective Radiated Power/Equivalent Isotropic Radiated Power	**8**
5.3 Radiated Spurious & Harmonic Emission	**9**
5.4 Occupied Bandwidth	**11**
5.5 Spurious and Harmonic Emissions at Antenna Terminal	**11**
5.5.1 Occupied Bandwidth Emission Limits	**11**
5.5.2 Conducted Spurious Emission	**12**
5.6 Frequency Stability / Temperature Variation	**13**
6. TEST DATA	**14**
6.1 Effective Radiated Power(E.R.P.)	**14**
6.2 Equivalent Isotropic Radiated Power(E.I.R.P.)	**15**
6.3 Cellular CDMA Radiated Spurious & Harmonic Measurement	**16**
6.4 PCS CDMA Radiated Spurious & Harmonic Measurement	**17**
6.5 CDMA Radiated Spurious & Harmonic Conversion Table	**18**
6.6 PCS Radiated Spurious & Harmonic Conversion Table	**19**
6.7 Frequency Stability	**20**
6.7.1 CDMA Frequency Stability Table	**20**
6.7.2 PCS Frequency Stability Table	**21**
6.7.3 CDMA Frequency Stability Graph	**22**
6.7.4 PCS Frequency Stability Graph	**24**
7.SAMPLE CALCULATION	**26**
7.1 Emission Designator	
8. CONCLUSION	**27**
9. TEST PLOTS	**28**

MEASUREMENT REPORT

1. FCC Certification Information

The following information is in accordance with FCC Rules, 47CFR Part2, Subpart J, Sections 2.1033 – 2.1055.

1.1 §2.1033 General Information

· Applicant Name:	SAMSUNG ELECRONICS CO., LTD.
· Address:	416 Maetan3-Dong, Yeongtong-gu, Suwon City Gyeonggi-Do, Korea 443-742
· Attention:	SungJoo KIM, Engineering Manager (QA Lab)
· FCC ID:	A3LSCHW579
· Quantity:	Quantity production is planned
· Emission Designators:	1M28F9W (CDMA), 1M27F9W (PCS CDMA) 249KGXW(GSM1900)
· Tx Freq. Range:	824.70-848.31MHz (CDMA) 1851.25-1908.75MHz (PCS CDMA) 1850.2MHz -1909.8MHz (GSM1900)
· Rx Freq. Range:	869.70-893.31 MHz (CDMA) 1931.25-1988.75 MHz (PCS CDMA) 1930.2MHz - 1989.8MHz (GSM1900)
· Max. Power Rating:	0.333 W ERP CDMA(25.23 dBm) 0.049 W EIRP PCS CDMA (16.91 dBm) 1.726 W EIRP GSM1900 (32.37dBm)
· FCC Classification(s):	Licensed Portable Tx Held to Ear (PCE)
· Equipment (EUT) Type:	Dual-Band CDMA and PCS GSM Phone with Bluetooth
· Modulation(s):	CDMA
· Frequency Tolerance:	±0.00025% (2.5ppm)
· FCC Rule Part(s):	§24(E), §22(H), §2.
· Dates of Test:	Sept 15, Sept 18 -19, 2006
· Place of Test:	SAMSUNG Lab,
· Test Report S/N:	FD-145-R1

2. INTRODUCTION

2.1 General

These measurement test were conducted at **SAMSUNG ELECTRONICS CO., LTD(SUWON)**.
The site address is 416 Maetan3-Dong, Yeongtong-gu, Suwon City, Gyeonggi-Do, Korea 443-742
The site have 1 Fully-anechoic chamber and measurement facility.



Figure1. Map of the Suwon City area.

Measurement Procedure

The radiated and spurious measurements were made Fully-anechoic chamber at a 3-meter test range (see Figure2). The equipment under testing was placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The substitution antenna will replace the EUT antenna it the same position and in vertical polarization. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The test antenna shall be raised and lowered, if necessary, to ensure that the maximum signal is still being received. The signal generator, output level, shall be adjusted until an equal or a known related level to what was measured from the EUT is obtained in the spectrum analyzer. This level was recorded.
For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



Figure2. Photograph of 3m Fully-Anechoic Chamber

3. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

- End of page -

4. TEST EQUIPMENT LIST

Name Of Equipment	Model	Serial No.	Due Date
Spectrum Analyzer	ESI26	836119/010	2006-09-26
	E4440A(3Hz~26.5GHz)	MY41000236	2007-04-14
	E4440A(3Hz~26.5GHz)	MY41000233	2007-04-05
Signal Generator	SMIQ03B	83824/021	2006-12-07
	SMR20	835197/030	2007-01-10
Power Meter	E4419B	GB41293846	2007-09-06
Power Sensor	E9300B	MY41495557	2007-04-17
Amplifier	5S1G4	304866	2006-10-18
Pre-Amplifier	8449B	3008A00691	2007-01-02
Communication test set	8960	GB42230535	2007-01-02
	8960	GB42360886	2007-02-28
Antenna Master	MA240	240/618	Not Required
Controller	HD100	100/756	Not Required
Environmental Chamber	SH-241	92000548	2006-11-22
	SH-241	92000549	2006-11-22
Horn Antenna	HF906	360306/011	2007-03-31
Dipole Antenna	3121C-DB4	9007-587	2006-12-02
Receive Antenna	HL040	353255/020	2007-04-25
Attenuator	8494A	3308A31997	2006-12-19
	8496A	3308A14426	2006-12-21
Divider	11636B	51941	Not Required
	11636B	51942	Not Required
	11636B	51946	Not Required
High Pass Filter	WHK1.0/15G-10SS	1	Not Required
	WHK/3.5/18G-10SS	4	Not Required
Shielded Fully Anechoic Chamber	CHAMBER	ANT0001	Not Required

5. DESCRIPTION OF TESTS

5.1 Output Power Variation

Test Condition to measure the Output Power

This device was tested under all R.C.s and S.O.s and worst case is reported with RC3/SO55, with “All Up” power control bits.

The following procedures were followed according to FCC “SAR Measurement Procedures for 3G Devices”, May 2006.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Move 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 5-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH0 and demodulation of RC 3,4 or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 5-2 was applied.
5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

Parameter	Units	Value
$\hat{I}$or	dBm/1.23MHz	-104
Pilot Ec/Ior	dB	-7
Traffic Ec/Ior	dB	-7.4

Table 5-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\hat{I}$or	dBm/1.23MHz	-86
Pilot Ec/Ior	dB	-7
Traffic Ec/Ior	dB	-7.4

Table 5-2
Parameters for Max. Power for RC1

Band	Channel	CDMA2000 RC	SO2	SO55
Cellular	1013	RC1	24.48	24.48
		RC3	24.65	24.65
	384	RC1	24.55	24.55
		RC3	24.70	24.70
	777	RC1	24.36	24.36
		RC3	24.52	24.52
PCS	25	RC1	24.24	24.24
		RC3	24.36	24.36
	600	RC1	24.14	24.14
		RC3	24.16	24.16
	1175	RC1	24.12	24.12
		RC3	24.12	24.12

Table 5-3
Maximum Power Output Table for SCH-W579

5.2 Effective Radiated Power / Equivalent Isotropic Radiated Power

Test Set-up for the ERP/EIRP TEST

Effective Radiated Power Output and Equivalent Isotropic Radiated Power output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004 :



Figure 3. Diagram of ERP/EIRP test Set-up

The EUT was placed on a Non-conducted turntable 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA & PCS signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of dipole is measured. The ERP is recorded.

5.3 Radiated Spurious & Harmonic Emission

Test Set-up for the Radiated Emission TEST

Radiated Spurious Emission Measurements by Substitution Method according to

ANSI/TIA/EIA-603-C-2004



Figure 4. Diagram of Radiated Spurious & Harmonic test Set-up

The EUT was placed on a Non-conducted turntable 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used, with RBW=VBW=1MHz. The value that we could measure was only reported A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

SAMPLE CALCULATION

Example: Channel 600 PCS Mode 2nd Harmonic(3760MHz)

The receive analyzer reading at 3meters with the EUT on the turntable was –81.0dBm. The gain of the substituted antenna is 8.1dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0dBm of the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0dB at 3760MHz. So 6.1dB is added to the signal generator reading of –30.9dBm yielding –24.8dBm. The fundamental EIRP was 25.5dBm so this harmonic was 25.5dBm –(-24.8)= 50.3dBc .

- End of page -

5.4 Occupied Bandwidth

Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.
Plots of the EUT's occupied bandwidth are shown herein.

5.5 Spurious and Harmonic Emissions at Antenna Terminal

5.5.1 Occupied Bandwidth Emission Limits

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

- End of page -

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A	1850 – 1865	1930 – 1945
B	1870 – 1885	1950 – 1965
C	1895 – 1910	1975 – 1990
D	1865 – 1870	1945 – 1950
E	1885 – 1890	1965 – 1970
F	1890 – 1895	1970 – 1975

Table 1. Broadband PCS Service Frequency Blocks

BLOCK	Freq. Range (MHz) Transmitter (Tx)	Freq. Range (MHz) Receiver (Rx)
A* Low + A	824 – 835	869 – 880
B	835 – 845	880 – 890
A* High	845 – 846.5	890 – 891.5
B*	846.5 – 849	891.5 – 894

Table 2. Cellular Service Frequency Blocks

5.5.2 Conducted Spurious Emission

Minimum standard:
On any frequency outside a license frequency block, the power of any emission shall be attenuated below the transmitter power(P) by at least 43+10log (P)dB. Limit equivalent to –13dBm, calculation shown below.

43 + 10log (0.333 W) = 38.23dB
25.23Bm –38.23 dB = -13 dBm

Test Procedure:

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1% of the emission bandwidth to show compliance with the –13dBm limit, in the 1MHz bands immediately outside and adjacent to the edge of the frequency block. The measurements are repeated for the EUT's highest channel. For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 10GHz. (PCS Mode : 10MHz to 20GHz). A display line was placed at –13dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.
Plots are shown herein.

5.6 Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

a.) Temperature: The temperature is carried from -30°C to +60°C using an environmental chamber.
b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification- The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature(25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (Usually 14~16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE : The EUT is tested down to the battery endpoint.

- End of page -

6. TEST DATA

6.1 Effective Radiated Power(E.R.P.)

Supply Voltage : 3.7VDC

Modulation : CDMA

■ Reference level

Frequency (MHz)	Output (dBm)	Polarization	P/M (dBm)	Ant gain (dBd)	Ref level (dBm)
824.70	23.50	H	-16.31	0.00	-16.31
		V	-15.14	0.00	-15.14
836.52	24.50	H	-15.30	0.00	-15.30
		V	-14.13	0.00	-14.13
848.31	25.00	H	-14.81	0.00	-14.81
		V	-13.63	0.00	-13.63

■ Result

Frequency (MHz)	From EUT Tested level (dBm)	Polarization (H/V)	Azimuth (angle)	ERP (dBm)	ERP (W)	Battery
824.70	-16.22	H1	356	23.59	0.229	Standard
836.52	-15.40	H1	1	24.40	0.275	Standard
848.31	-14.58	H1	2	25.23	0.333	Standard

NOTE : Standard batteries are the only battery options for this phone

Radiated measurements at 3 meters by Substitution Method

6.2 Equivalent Isotropic Radiated Power(E.I.R.P.)

Supply Voltage : 3.7VDC

Modulation : PCS

■ Reference level

Frequency (MHz)	Output (dBm)	Polarization	P/M (dBm)	Ant gain (dBi)	Ref level (dBm)
1851.25	24.00	H	-16.18	6.90	-23.08
		V	-16.44	6.90	-23.34
1880.00	24.00	H	-16.23	6.90	-23.13
		V	-16.18	6.90	-23.08
1908.75	24.00	H	-16.14	6.90	-23.04
		V	-16.46	6.90	-23.36

■ Result

Frequency (MHz)	From EUT Tested level (dBm)	Polarization (H/V)	Azimuth (angle)	EIRP (dBm)	EIRP (W)	Battery
1851.25	-30.17	H1	359	16.91	0.049	Standard
1880.00	-32.08	H1	353	15.05	0.032	Standard
1908.75	-31.08	V	290	16.28	0.042	Standard

NOTE : Standard batteries are the only battery options for this phone

Radiated measurements at 3 meters by Substitution Method

6.3 Cellular CDMA Radiated Spurious & Harmonic measurement

Field Strength of SPURIOUS Radiation

Operating Frequency : 824.70 MHz(Low), 836.52MHz(Middle), 848.31MHz(High)

Measured Output Power : 25.23 dBm = 0.333W

Modulation Signal : CDMA

Limit : 43 + 10log$_{10}$(P) = 38.23 dBc

■ **Result**

Channel	Harmonic	Frequency (MHz)	From EUT Tested level (dBm)	POL (H/V)	Result (dBc)
1013	2	1649.40	-48.66	V	62.19
	3	2474.10	-62.57	H2	70.00
	4	3298.80	-67.14	V	69.50
	5	4123.50	-	-	-
	6	4948.20	-	-	-
	7	5772.90	-	-	-
384	2	1673.04	-50.14	V	63.46
	3	2509.56	-64.88	H2	72.33
	4	3346.08	-67.65	V	70.86
	5	4182.68	-	-	-
	6	5019.12	-	-	-
	7	5855.64	-	-	-
777	2	1696.62	-53.04	V	64.73
	3	2544.93	-65.84	H1	72.88
	4	3393.24	-67.74	V	70.72
	5	4241.55	-	-	-
	6	5089.86	-	-	-
	7	5938.17	-	-	-

Radiated Spurious Emission measurements at 3 meters by Substitution Method

6.4 PCS CDMA Radiated Spurious & Harmonic measurement

Field Strength of SPURIOUS Radiation

Operating Frequency : 1851.25 MHz(Low), 1880.00 MHz(Middle), 1908.75MHz(High)

Measured Output Power : 16.91 dBm = 0.049 W

Modulation Signal : PCS

Limit : 43 + 10log$_{10}$(P) = 29.91 dBc

■ Result

Channel	Harmonic	Frequency (MHz)	From EUT Tested level (dBm)	POL (H/V)	Result (dBc)
25	2	3702.50	-55.25	H1	44.58
	3	5553.75	-49.57	H1	34.43
	4	7405.55	-68.05	H1	49.22
	5	9256.25	-	-	-
	6	11107.50	-	-	-
	7	12958.75	-	-	-
600	2	3760.00	-48.72	H1	38.84
	3	5640.00	-59.10	H1	43.95
	4	7520.00	-68.26	H2	49.65
	5	9400.00	-	-	-
	6	11280.00	-	-	-
	7	13160.00	-	-	-
1175	2	3817.50	-52.38	H1	42.04
	3	5726.25	-58.88	H1	43.45
	4	7635.00	-68.20	H2	48.68
	5	9543.75	-	-	-
	6	11452.50	-	-	-
	7	13361.25	-	-	-

Radiated Spurious Emission measurements at 3 meters by Substitution Method

6.5 CDMA Radiated Spurious & Harmonic Conversion Table

Date : 2006 . 09. 19

Test Engineer : YE PARK

① Tx Cable loss
② Tx Horn Ant Gain
③ Rx Cable loss + HPF Insertion loss + Attenuator
④ Pre-Amp gain
⑤ Air loss
⑥ Tested Level from EUT
⑦ = ⑥ + ⑤ + ③ - ④
⑧ = ERP +2.14- ⑦

CH	Har	Frequency (MHz)	① Tx CL (dB)	② Horn Gain (dB)	Tx Level @ (S/G 0dBm)	⑥ Tested Level EUT : H (dBm)	⑥ Tested Level EUT : V (dBm)	⑦ Amplitude of Emission EUT : H (dBm)	⑦ Amplitude of Emission EUT : V (dBm)	⑧ Result EUT : H (dBc)	⑧ Result EUT : V (dBc)
1013	2	1649.40	7.70	8.03	0.33	-50.42	-48.66	-36.40	-34.82	63.77	62.19
	3	2474.10	9.92	9.55	-0.37	-62.57	-64.26	-42.63	-44.13	70.00	71.50
	4	3298.80	11.67	9.64	-2.03	-66.59	-67.14	-42.18	-42.13	69.55	69.50
	5	4123.50	13.24	10.67	-2.57	-	-	-	-	-	-
	6	4948.20	14.53	11.05	-3.48	-	-	-	-	-	-
	7	5772.90	16.87	11.23	-5.64	-	-	-	-	-	-
384	2	1673.04	7.80	8.03	0.23	-50.70	-50.14	-36.47	-36.09	63.84	63.46
	3	2509.56	10.06	9.55	-0.51	-64.88	-65.37	-44.96	-45.02	72.33	72.39
	4	3346.08	11.45	9.64	-1.81	-67.29	-67.65	-43.95	-43.49	71.32	70.86
	5	4182.68	13.72	10.67	-3.05	-	-	-	-	-	-
	6	5019.12	15.43	11.05	-4.38	-	-	-	-	-	-
	7	5855.64	17.19	11.23	-5.96	-	-	-	-	-	-
777	2	1696.62	7.96	8.03	0.07	-54.08	-53.04	-37.82	-37.36	65.19	64.73
	3	2544.93	10.15	9.55	-0.60	-65.84	-66.72	-45.51	-46.30	72.88	73.67
	4	3393.24	11.62	9.64	-1.98	-67.77	-67.74	-44.37	-43.35	71.74	70.72
	5	4241.55	13.71	10.67	-3.04	-	-	-	-	-	-
	6	5089.86	15.71	11.05	-4.66	-	-	-	-	-	-
	7	5938.17	17.09	11.23	-5.86	-	-	-	-	-	-

6.6 PCS Radiated Spurious & Harmonic Conversion Table

Date : 2006 . 09. 19

Test Engineer : YE PARK

① Tx Cable loss
② Tx Horn Ant Gain
③ Rx Cable loss + HPF Insertion loss + Attenuator
④ Pre-Amp gain
⑤ Air loss
⑥ Tested Level from EUT
⑦ = ⑥ + ⑤ + ③ - ④
⑧ = EIRP - ⑦

CH	Har	Frequency (MHz)	① Tx CL (dB)	② Horn Gain (dB)	Tx Level @ (S/G 10dBm)	⑥ Tested Level EUT : H (dBm)	⑥ Tested Level EUT : V (dBm)	⑦ Amplitude of Emission EUT : H (dBm)	⑦ Amplitude of Emission EUT : V (dBm)	⑧ Result EUT : H (dBc)	⑧ Result EUT : V (dBc)
25	2	3702.50	12.17	9.73	7.56	-55.25	-57.46	-27.67	-29.86	44.58	46.77
	3	5553.75	16.95	11.15	4.20	-49.57	-54.32	-17.52	-22.96	34.43	39.87
	4	7405.00	20.77	11.44	0.67	-68.05	-68.48	-32.31	-34.48	49.22	51.39
	5	9256.25	24.45	12.17	-2.28	-	-	-	-	-	-
	6	11107.50	28.18	13.66	-4.52	-	-	-	-	-	-
	7	12958.75	31.99	13.27	-8.72	-	-	-	-	-	-
600	2	3760.00	12.40	9.73	7.33	-48.72	-50.99	-21.93	-23.83	38.84	40.74
	3	5640.00	16.83	11.15	4.32	-59.10	-59.41	-27.04	-27.71	43.95	44.62
	4	7520.00	21.17	11.44	0.27	-68.26	-68.98	-32.74	-35.06	49.65	51.97
	5	9400.00	24.51	12.17	-2.34	-	-	-	-	-	-
	6	11280.00	28.38	13.66	-4.72	-	-	-	-	-	-
	7	13160.00	33.20	13.27	-9.93	-	-	-	-	-	-
1175	2	3817.50	13.69	9.73	6.04	-52.38	-54.16	-25.13	-26.30	42.04	43.21
	3	5726.25	17.30	11.15	3.85	-58.88	-58.67	-26.54	-26.75	43.45	43.66
	4	7635.00	21.23	11.44	0.21	-68.20	-68.59	-31.77	-33.39	48.68	50.30
	5	9543.75	26.48	12.17	-4.31	-	-	-	-	-	-
	6	11452.50	28.89	13.66	-5.23	-	-	-	-	-	-
	7	13361.25	32.93	13.27	-9.66	-	-	-	-	-	-

6.7 Frequency Stability

6.7.1 CDMA Frequency Stability Table

Operating Frequency : 836,520,000 Hz

Channel : 384

Reference Voltage : 3.7VDC

Deviation Limit : ±0.00025 % or 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency Error (Hz)	Frequency (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	47.69	836,520,048	0.000006	0.057
100%		-30	-21.31	836,519,979	-0.000003	-0.025
100%		-20	-10.56	836,519,989	-0.000001	-0.013
100%		-10	-41.58	836,519,958	-0.000005	-0.050
100%		0	20.51	836,520,021	0.000002	0.025
100%		+10	43.48	836,520,043	0.000005	0.052
100%		+20	21.53	836,520,022	0.000003	0.026
100%		+30	36.68	836,520,037	0.000004	0.044
100%		+40	42.44	836,520,042	0.000005	0.051
100%		+50	12.77	836,520,013	0.000002	0.015
100%		+60	18.69	836,520,019	0.000002	0.022
85%	3.35	+20	24.92	836,520,025	0.000003	0.030
115%	4.26	+20	31.73	836,520,032	0.000004	0.038
Batt. Endpoint	3.35	+20	24.92	836,520,025	0.000003	0.030

Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.

The EUT is tested down to the battery end point

6.7.2 PCS Frequency Stability Table

Operating Frequency : 1,880,000,000 Hz

Channel : 600

Reference Voltage : 3.7VDC

Deviation Limit : ±0.00025 % or 2.5ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency Error (Hz)	Frequency (Hz)	Deviation (%)	ppm
100%	3.70	+20(Ref)	26.66	1,880,000,027	0.000001	0.014
100%		-30	-12.33	1,879,999,988	-0.000001	-0.007
100%		-20	-46.74	1,879,999,953	-0.000002	-0.025
100%		-10	-56.99	1,879,999,943	-0.000003	-0.030
100%		0	-21.37	1,879,999,979	-0.000001	-0.011
100%		+10	41.92	1,880,000,042	0.000002	0.022
100%		+20	28.72	1,880,000,029	0.000002	0.015
100%		+30	-25.31	1,879,999,975	-0.000001	-0.013
100%		+40	-20.33	1,879,999,980	-0.000001	-0.011
100%		+50	26.72	1,880,000,027	0.000001	0.014
100%		+60	29.83	1,880,000,030	0.000002	0.016
85%	3.35	+20	41.63	1,880,000,042	0.000002	0.022
115%	4.26	+20	-11.56	1,879,999,988	-0.000001	-0.006
Batt. Endpoint	3.35	+20	41.63	1,880,000,042	0.000002	0.022

Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.

The EUT is tested down to the battery end point

6.7.3 CDMA Frequency Stability Graph



- End of page –

Zoom In



- End of page –

6.7.4 PCS Frequency Stability Graph



- End of page -

Zoom In



- End of page -

7. SAMPLE CALCULATION

7.1 Emission Designator

Emission Designator = 1M25F9W

Calculation : 2M + 2DK
CDMA BW = 1.25MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination(Audio/Data)
(Measured at the 99.75% power bandwidth)

- End of page -

8. CONCLUSION

The data collected shows that the SAMSUNG Dual-Band CDMA Phone with Bluetooth
FCC ID : A3LSCHW579 complies with all the requirements of Parts 2,22,24 of the FCC Rules.

- End of page -

9. TEST PLOTS

- End of page -


Agilent
L
Freq/Channel
Ch Freq 824.7 MHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.1013
Ref 24.5 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
7.64
dB
Center 824.700 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Center Freq
824.700000 MHz
Start Freq
823.200000 MHz
Stop Freq
826.200000 MHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Channel Power
24.56 dBm /1.2770 MHz
Power Spectral Density
-36.00 dBm/Hz
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 836.52 MHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.384
Ref 24.5 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
7.64
dB
Center 836.520 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Center Freq
836.520000 MHz
Start Freq
835.020000 MHz
Stop Freq
838.020000 MHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Channel Power
24.50 dBm /1.2687 MHz
Power Spectral Density
-36.03 dBm/Hz
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 848.31 MHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.777
Ref 24.5 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
7.64
dB
Center 848.310 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Channel Power
24.50 dBm /1.2763 MHz
Power Spectral Density
-36.06 dBm/Hz
Center Freq
848.310000 MHz
Start Freq
846.810000 MHz
Stop Freq
849.810000 MHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.1013
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 824.70 MHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
824.700000 MHz
Start Freq
819.700000 MHz
Stop Freq
829.700000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.384
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 836.52 MHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
836.520000 MHz
Start Freq
831.520000 MHz
Stop Freq
841.520000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.777
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 848.31 MHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
848.310000 MHz
Start Freq
843.310000 MHz
Stop Freq
853.310000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 824.7 MHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.1013
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
Center 824.700 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2770 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 8.281 kHz
x dB Bandwidth 1.393 MHz*
Center Freq
824.700000 MHz
Start Freq
823.200000 MHz
Stop Freq
826.200000 MHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 836.52 MHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.384
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
Center 836.520 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2687 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 4.133 kHz
x dB Bandwidth 1.386 MHz*
Center Freq
836.520000 MHz
Start Freq
835.020000 MHz
Stop Freq
838.020000 MHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 848.31 MHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.777
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
7.64
dB
Center 848.310 MHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2763 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 4.135 kHz
x dB Bandwidth 1.391 MHz*
Center Freq
848.310000 MHz
Start Freq
846.810000 MHz
Stop Freq
849.810000 MHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Rx Spurious Emission
Mkr1 880.00 MHz
Ref -50 dBm
Atten 10 dB
-85.79 dBm
#Avg
Log
10
dB/
Offst
8.01
dB
Dl
-80.0
dBm
PAvg
V1 S2
S3 FC
£(f):
FTun
Swp
Start 869.00 MHz
Stop 894.00 MHz
#Res BW 30 kHz
#VBW 30 kHz
Sweep 105.9 ms (601 pts)
Center Freq
881.500000 MHz
Start Freq
869.000000 MHz
Stop Freq
894.000000 MHz
CF Step
2.50000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.1013
Mkr1 1.649 GHz
Ref 24.5 dBm
Atten 30 dB
-29.91 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
1
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.1013
Mkr1 7.400 GHz
Ref 24.5 dBm
Atten 30 dB
-40.94 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
1
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.384
Mkr1 1.674 GHz
Ref 24.5 dBm
Atten 30 dB
-30.68 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
1
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.384
Mkr1 7.788 GHz
Ref 24.5 dBm
Atten 30 dB
-40.42 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
1
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.777
Mkr1 1.695 GHz
Ref 24.5 dBm
Atten 30 dB
-29.65 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.777
Mkr1 3.525 GHz
Ref 24.5 dBm
Atten 30 dB
-39.13 dBm
#Peak
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
£(f):
FTun
Swp
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 6.250 GHz
Span 7.5 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 12.52 ms (601 pts)
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Band Edge Ch.1013
Mkr1 824.000 MHz
Ref 24.5 dBm
Atten 30 dB
-17.657 dBm
#Samp
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 824.000 MHz
Span 2 MHz
#Res BW 13 kHz
VBW 13 kHz
Sweep 45.16 ms (601 pts)
Center Freq
824.000000 MHz
Start Freq
823.000000 MHz
Stop Freq
825.000000 MHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Band Edge Ch.777
Mkr1 849.000 MHz
Ref 24.5 dBm
Atten 30 dB
-15.316 dBm
#Samp
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 849.000 MHz
Span 2 MHz
#Res BW 13 kHz
VBW 13 kHz
Sweep 45.16 ms (601 pts)
Center Freq
849.000000 MHz
Start Freq
848.000000 MHz
Stop Freq
850.000000 MHz
CF Step
200.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 4MHz Span Ch.1013
Mkr1 822.960 MHz
Ref 24.5 dBm
Atten 30 dB
-27.204 dBm
#Samp
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 821.000 MHz
Span 4 MHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 1.56 ms (601 pts)
Center Freq
821.000000 MHz
Start Freq
819.000000 MHz
Stop Freq
823.000000 MHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 4MHz Span Ch.777
Mkr1 850.013 MHz
Ref 24.5 dBm
Atten 30 dB
-36.334 dBm
#Samp
Log
10
dB/
Offst
7.64
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 852.000 MHz
Span 4 MHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 1.56 ms (601 pts)
Center Freq
852.000000 MHz
Start Freq
850.000000 MHz
Stop Freq
854.000000 MHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.85125 GHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.25
Ref 24.5 dBm
#Atten 40 dB
#Avg
Log
10
dB/
Offst
8.57
dB
Center 1.851 250 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Center Freq
1.85125000 GHz
Start Freq
1.84975000 GHz
Stop Freq
1.85275000 GHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Channel Power
24.52 dBm /1.2699 MHz
Power Spectral Density
-36.05 dBm/Hz
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.600
Ref 24.5 dBm
#Atten 40 dB
#Avg
Log
10
dB/
Offst
8.57
dB
Center 1.880 000 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Center Freq
1.88000000 GHz
Start Freq
1.87850000 GHz
Stop Freq
1.88150000 GHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Channel Power
24.50 dBm /1.2665 MHz
Power Spectral Density
-36.03 dBm/Hz
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.90875 GHz
Trig Free
Channel Power
FCC ID:A3LSCHW579 Power Out Ch.1175
Ref 24.5 dBm
#Atten 40 dB
#Avg
Log
10
dB/
Offst
8.57
dB
Center 1.908 750 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Center Freq
1.90875000 GHz
Start Freq
1.90725000 GHz
Stop Freq
1.91025000 GHz
CF Step
300.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Channel Power
24.54 dBm /1.2614 MHz
Power Spectral Density
-35.97 dBm/Hz
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.25
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
8.57
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 1.851 25 GHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
1.85125000 GHz
Start Freq
1.84625000 GHz
Stop Freq
1.85625000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.600
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
8.57
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 1.880 00 GHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
1.88000000 GHz
Start Freq
1.87500000 GHz
Stop Freq
1.88500000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Power Out Ch.1175
Ref 24.5 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
8.57
dB
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 1.908 75 GHz
Span 10 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 1 ms (601 pts)
Center Freq
1.90875000 GHz
Start Freq
1.90375000 GHz
Stop Freq
1.91375000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.85125 GHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.25
Ref 24.5 dBm
#Atten 40 dB
#Samp
Log
10
dB/
Offst
8.57
dB
Center 1.851 250 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2699 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error -247.971 Hz
x dB Bandwidth 1.392 MHz*
Center Freq
1.85125000 GHz
Start Freq
1.84975000 GHz
Stop Freq
1.85275000 GHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.600
Ref 24.5 dBm
#Atten 40 dB
#Samp
Log
10
dB/
Offst
8.57
dB
Center 1.880 000 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2665 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 109.108 Hz
x dB Bandwidth 1.385 MHz*
Center Freq
1.88000000 GHz
Start Freq
1.87850000 GHz
Stop Freq
1.88150000 GHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.90875 GHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSCHW579 OBW Ch.1175
Ref 24.5 dBm
#Atten 40 dB
#Samp
Log
10
dB/
Offst
8.57
dB
Center 1.908 750 GHz
Span 3 MHz
#Res BW 30 kHz
#VBW 300 kHz
#Sweep 20 ms (601 pts)
Occupied Bandwidth
1.2614 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error -7.943 kHz
x dB Bandwidth 1.410 MHz*
Center Freq
1.90875000 GHz
Start Freq
1.90725000 GHz
Stop Freq
1.91025000 GHz
CF Step
300.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.25
Mkr1 1.359 GHz
Ref 24.5 dBm
#Atten 40 dB
-33.13 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
AC Coupled: unspecified below 20 MHz
1
M1 S2
S3 FC
£(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.25
Mkr1 17.26 GHz
Ref 24.5 dBm
#Atten 40 dB
-27.57 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
1
M1 S2
S3 FC
£(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.600
Mkr1 587 MHz
Ref 24.5 dBm
#Atten 40 dB
-33.00 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
AC Coupled: unspecified below 20 MHz
M1 S2
S3 FC
£(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.600
Mkr1 19.80 GHz
Ref 24.5 dBm
#Atten 40 dB
-28.00 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.1175
Mkr1 877 MHz
Ref 24.5 dBm
#Atten 40 dB
-32.75 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
AC Coupled: unspecified below 20 MHz
1
M1 S2
S3 FC
£(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Cond Spur Ch.1175
Mkr1 14.31 GHz
Ref 24.5 dBm
#Atten 40 dB
-28.14 dBm
Peak
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
1
M1 S2
S3 FC
£(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Band Edge Ch.25
Mkr1 1.850 000 GHz
Ref 24.5 dBm
Atten 30 dB
-28.163 dBm
#Samp
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.850 000 GHz
Span 5 MHz
#Res BW 13 kHz
VBW 13 kHz
Sweep 112.8 ms (601 pts)
Center Freq
1.85000000 GHz
Start Freq
1.84750000 GHz
Stop Freq
1.85250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 Band Edge Ch.1175
Mkr1 1.910 000 GHz
Ref 24.5 dBm
Atten 30 dB
-28.848 dBm
#Samp
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.910 000 GHz
Span 5 MHz
#Res BW 13 kHz
VBW 13 kHz
Sweep 112.8 ms (601 pts)
Center Freq
1.91000000 GHz
Start Freq
1.90750000 GHz
Stop Freq
1.91250000 GHz
CF Step
500.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 4MHz Span Ch.25
Mkr1 1.848 980 GHz
Ref 24.5 dBm
Atten 30 dB
-21.221 dBm
#Samp
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 1.847 000 GHz
Span 4 MHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
1.84700000 GHz
Start Freq
1.84500000 GHz
Stop Freq
1.84900000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID:A3LSCHW579 4MHz Span Ch.1175
Mkr1 1.911 013 GHz
Ref 24.5 dBm
Atten 30 dB
-20.592 dBm
#Samp
Log
10
dB/
Offst
8.57
dB
Dl
-13.0
dBm
LgAv
100
V1 S2
S3 FC
£(f):
FTun
Swp
Center 1.913 000 GHz
Span 4 MHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
1.91300000 GHz
Start Freq
1.91100000 GHz
Stop Freq
1.91500000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies