

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification and Description
Processor	CHORUS3 (360 Mhz)
Standard System memory	128 MB DDR2 SDRAM
Resolution	True 600 x 600 dpi (Addressible 1 200 dpi support)
Copy Quality mode	Text : Scan 300 x 300 dpi, Print: 600 x 600 dpi (Platen, ADF) Mixed : Scan 300 x 300 dpi, Print: 600 x 600 dpi (Platen, ADF) Photo : Scan 300 x 300 dpi, Print: 600 x 600 dpi (ADF) Scan 600 x 600 dpi, Print: 1200 x 1200 dpi (Platen)
Paper Handling	Paper Tray(standard) 250 Sheets MP Tray 50sheets
Power Rating	110 ~ 127 VAC, 5 A, 50/60 Hz
Power Consumption	Power save mode : 9 Watts Printing mode: MAX. 600 Watts
Printer Language	PCL6/PS3
PC Interfaces	USB2.0, NW, FAX
OS compatibility	Windows 2000/XP (32/64 bits) /Vista (32/64 bits) /2003 Server (32/64 bits) /2008 Server(32/64 bits) /7 (32/64 bits) /2008 Server R2 Various Linux OS: Fedora Core 4, 5, 6, Fedora 7, 8, 9, 10, 11, 12, RedHat Enterprise Linux WS 4, 5, SuSE 10.0, 10.1 openSuSE 10.2, 10.3, 11.0, 11.1, 11.2 SuSE Linux Enterprise Desktop 10, 11 Debian 4.0, 5.0 Ubuntu 5.04, 5.10, 6.04, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 Mandriva 2005LE, 2006, 2007, 2007.1 2008, 2008.1, 2009, 2009.1 Mac OS 10.3 ~ 10.6
Modes of Operation	USB Printing, ADF Scan, ADF Copy, 1 200 dpi Printing, Fax RX, Fax TX, Network Printing
Intended Class for Emissions	Class B